Superior communications.

5027 Irwindale Ave. Suite, Irwindale Ave, California, United States, 91706.

2018.05.02

To: Federal Communications Commission 7435 Oakland Mills Road Columbia, MD

FCC ID: YJW06121

To Whom It May Concern:

This letter is to ascertain that <u>Superior communications</u>. Product <u>Wireless charger</u>, Model: <u>06121</u>; <u>06122</u>, has been the units used for conducting FCC compliance testing, and it meets KDB 680106 D01 RF Exposure Wireless Charging App v03 Clause 5(b) 6 conditions.

KDB 000100 D01 K1 Exposure whereas charging App vos Clause 5(0) o conditions.	
1	Power transfer frequency is less that 1 MHz
	YES; the device operated in the frequency range from 110 to 205 kHz.
2	Output power from each primary coil is less than or equal to 15 watts.
	YES; the maximum output power of the primary coil is 10W.
3	The transfer system includes only single primary and secondary coils. This includes charging systems that may have multiple primary coils and clients that are able to detect and allow coupling only
	between individual pairs of coils.
	YES; the transfer system includes only single primary and secondary coils.
4	Client device is placed directly in contact with the transmitter.
	YES; Client device is placed directly in contact with the transmitter.
5	Mobile exposure conditions only (portable exposure conditions are not covered by this exclusion).
	YES
6	The aggregate H-field strengths at 15 cm surrounding the device and 20 cm above the top surface
	from all simultaneous transmitting coils are demonstrated to be less than 50% of the MPE limit.
	YES; The EUT field strength levels are 50% x MPE limts.

If you have any question or concerns, pls. contact us.

Client's signature :

Client's name / title : George.Chen/ VP Product Development

Telephone: 818-636-4985 Fax: 626-608-9043

Contact information / address: 5027 Irwindale Ave. Suite, Irwindale Ave, California, United States,

91706