

Test Report

Report No.: MTi211025009-02E2

Date of issue: Dec. 09, 2021


Applicant: Superior Communications.

Product: 15W Fast Charge Wireless Charger Stand

Model(s): 06499, 06512

FCC ID: YJW-06499

Shenzhen Microtest Co., Ltd. http://www.mtitest.com





Instructions


1. This test report shall not be partially reproduced without the written consent of the laboratory.

2. The test results in this test report are only responsible for the samples submitted

3. This test report is invalid without the seal and signature of the laboratory.

4. This test report is invalid if transferred, altered, or tampered with in any form without authorization.

Any objection to this test report shall be submitted to the laboratory within
 15 days from the date of receipt of the report.





Contents

1	General Description	5
	 1.1 Description of the EUT 1.2 Description of test modes 1.3 Description of support units 	5 5 6
2	Test facilities and accreditations	7
	2.1 Test laboratory	7
3	List of test equipment	7
4	Test result	8
4		
4	Test result 4.2 Test setup 4.3 Test Procedures	
4	4.2 Test setup4.3 Test Procedures4.4 Equipment Approval Considerations item 5 b) of KDB 680106 D01 v03r01	9 9 10
4	4.2 Test setup 4.3 Test Procedures	9 9 10
	4.2 Test setup4.3 Test Procedures4.4 Equipment Approval Considerations item 5 b) of KDB 680106 D01 v03r01	

Test Result Certification				
Applicant:	Superior Communications.			
Address:	5027 Irwindale Ave. Suite Irwindale Ave California United States.			
Manufacturer:	Shenzhen Powerqi Technology Co., Ltd.			
Address:	Room 201, 302, 401 of A4 Building, Block A, Fangxing Science and Technology Park, No. 13 of Baonan Road, Longgang District, Shenzhen, China			
Product description				
Product name:	15W Fast Charge Wireless Charger Stand			
Trademark:	AT&T			
Model name:	06499			
Serial Model:	06512			
Standards:	FCC CFR 47 PART 1, § 1.1310			
Test method:	KDB 680106 v03r01			
Date of Test	· · ·			
Date of test:	2021-10-29 ~ 2021-11-09			
Test result:	Pass			

Test Engineer :

my An

(Danny Xu)

Reviewed By: :

leor chen

(Leon Chen)

Approved By: :

Tom Kue

(Tom Xue)



1 General Description

1.1 Description of the EUT

Product name:	15W Fast Charge Wireless Charger Stand
Model name:	06499
Series Model:	06512
Model difference:	All the models are the same circuit and RF module, except the model name.
Electrical rating:	Input: 5VDC/2A; 9VDC/1.67A; 12VDC/1.5A Output: 5W,7.5W,10W,15W
Accessories:	 AC/DC Adapter: Model: QC95 Input: AC 110-240V~50/60Hz 0.6A Output: 3.6-6V=3A, 6.2-9V=2A, 9.2-12V=1.5A USB-C to USB-C cable (1.5 m)
RF specification:	
Operation frequency:	115 kHz – 205 kHz
Modulation type:	ASK
Antenna type:	Coil Antenna

1.2 Description of test modes

All the test modes were carried out with the EUT in normal operation, the final test mode of the EUT was the worst test mode for emission test, which was shown in this report and defined as:

No.	Emission test modes	
Mode 1	Operating mode (5W)	
Mode 2	Operating mode (7.5W)	
Mode 3	Operating mode (10W)	
Mode 4	Operating mode (15W)	
The test data only show worst test mode: Mode 4		





1.3 Description of support units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Support equipment list						
Description	Model	Serial No.	Manufacturer			
Load	/	/	YBZ			
Adapter	QC95	/	Shenzhen Powerqi Technology Co.,Ltd.			
Mobile phone	S9+	/	SAMSUNG			
Support cable list			•			
Description	Length (m)	From	То			
/	/	/	/			



2 Test facilities and accreditations

2.1 Test laboratory

Test laboratory:	Shenzhen Microtest Co., Ltd.
Test site location:	101, No. 7, Zone 2, Xinxing Industrial Park, Fuhai Avenue, Xinhe Community, Fuhai Street, Bao' an District, Shenzhen, Guangdong, China
Telephone:	(86-755)88850135
Fax:	(86-755)88850136
CNAS Registration No.:	CNAS L5868
FCC Registration No.:	448573

3 List of test equipment

No.	Equipment	Manufacturer	Model	Serial No.	Cal. date	Cal. Due
MTI-E115	Electric and Magnetic Field Probe – Analyzer	Narna	EHP-200A	101166	2021/06/02	2022/06/01



4 Test result

4.1.1 Requirement

§1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in §1.1307(b), except in the case of portable devices which shall be evaluated according to the provisions of FCC part 2.1093 of this chapter.

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
	(i) Limits for Oc	cupational/Controlled Expo	sure	
0.3-3.0	614	1.63	*(100)	≪6
3.0-30	1842/f	4.89/f	*(900/f ²)	<6
30-300	61.4	0.163	1.0	<6
300-1500			f/300	<6
1500-100000			5	<6
	(ii) Limits for Genera	al Population/Uncontrolled I	Exposure	
0.3-1.34	614	1.63	*(100)	<30
1.34-30	824/f	2.19/f	*(180/f²)	<30
30-300	27.5	0.073	0.2	<30
300-1500			f/1500	<30
1500-100000			1.0	<30

Table 1 to §1.1310(e)(1) - Limits for Maximum Permissible Exposure (MPE)

f = frequency in MHz


* = Plane-wave equivalent power density

Note 1: Occupational/controlled exposure limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure.

Note 2: General population/uncontrolled exposure limits apply in situations in which the general public may be exposed, or in which persons who are exposed as a consequence of their employment may not be fully aware of the potential for exposure or cannot exercise control over their exposure.



4.2 Test setup



4.3 Test Procedures

a. The RF exposure test was performed in anechoic chamber.

b. E and H-field measurements should be made with the center of the probe at a distance of 15 cm surrounding the device and 20 cm above the top surface of the primary/client pair.

c. The highest emission level was recorded and compared with limit.

d. The EUT was measured according to the dictates of KDB 680106 v03r01.



4.4 Equipment Approval Considerations item 5 b) of KDB 680106 D01 v03r01

Requirement	Device
1. Power transfer frequency is less than 1 MHz.	Yes. The operating frequencies are: 115 kHz – 205 kHz
2. Output power from each primary coil is less than or equal to 15 watts	Yes. The maximum output power is: 15W
3. The system may consist of more than one source primary coils, charging one or more clients. If more than one primary coil is present, the coil pairs may be powered on at the same time.	Yes. The EUT have a source primary coil.
4. Client device is placed directly in contact with the transmitter.	Yes. The client device is placed directly in contact with the transmitter.
5. Mobile exposure conditions only (portable exposure conditions are not covered by this exclusion).	Yes. Mobile exposure conditions only.
6. The aggregate H-field strengths anywhere at or beyond 15 cm surrounding the device, and 20 cm away from the surface from all coils that by design can simultaneously transmit, and while those coils are simultaneously energized, are demonstrated to be less than 50% of the applicable MPE limit.	Yes. See the test result in item 4.5.

Page 11 of 13

4.5 Test results

Micr©test

检

测

Test condition 1: Mode 4 operating mode with client device (1 % battery status of client device)

	Probe	E –field (V/m)		H–field (A/m)			
Antenna	Position	Measurement	Limit	Max. Percentage (%)	Measurement	Limit	Max. Percentage (%)
	Z axis	2.0210	614	0.40%	0.0812	1.63	25.34%
	Left	2.3281			0.1200		
4	Right	1.5944			0.0701		
1	Front	2.4513			0.0823		
	Rear	1.4623			0.2137		
	Bottom	0.7491			0.4130		
Conclusio	n: The M	easurement va	lue is less tha	n 50% MPE lir	nit, which meets	the requiren	nents.

Test condition 2: Mode 4 operating mode with client device (50 % battery status of client device)

Antonno	Probe	E –field Probe (V/m)		H–field (A/m)			
Antenna	Position	Measurement	Limit	Percentage (%)	Measurement	Limit	Percentage (%)
	Z axis	2.0235	614		0.0827	1.63	
	Left	2.3274		0.40%	0.1210		23.39%
4	Right	1.5955			0.0721		
1	Front	2.4545			0.0832		
	Rear	1.4631			0.2157		
	bottom	0.7327			0.3812		



Antenna	Probe Position	E –field (V/m)			H-field (A/m)		
		Measurement	Limit	Percentage (%)	Measurement	Limit	Percentage (%)
1	Z axis	2.0215	614	0.40%	0.0800	1.63	24.07%
	Left	2.3251			0.1201		
	Right	1.5933			0.0694		
	Front	2.4521			0.0815		
	Rear	1.4614			0.2127		
	bottom	0.7205			0.3924		
Conclusio	n: The M	easurement va	lue is less tha	n 50% MPE lir	nit, which meets	the requiren	nents.



Photographs of the test setup

See the APPENDIX 2 - Test Setup Photo.

Photographs of the EUT

See the APPENDIX 1 - EUT PHOTO.

----End of Report----