

FCC PART 15B

MEASUREMENT AND TEST REPORT




FOR

Shanghai feixun Communication Co., Ltd.

NO. 90, HQ Business Park, 4855 Guangfulin Road, Songjiang District, Shanghai

201616, China

FCC ID: YJY6775440012470

Report Concerns: Original Report	Equipment Type: Desktop Switch
Model:	<u>FreeSwitch 808I</u>
Report No.:	<u>STR10068143I</u>
Test Date:	<u>2010-06-13 to 2010-06-25</u>
Issue Date:	<u>2010-07-08</u>
Test Engineer:	<u>Jason</u> 
Reviewed By:	<u>Lahm Peng</u> 
Approved & Authorized By:	<u>Jandy so/PSQ Manager</u> 
Prepared By:	
SEM.Test Compliance Service Co., Ltd 3/F, Jinbao Commerce Building, Xin'an Fanshen Road, Bao'an District, Shenzhen, P.R.C. (518101) Tel.: +86-755-33663308 Fax.: +86-755-33663309 Website: www.semtest.com.cn	

Note: This test report is limited to the above client company and the product model only. It may not be duplicated without prior permitted by SEM.Test Compliance Service Co., Ltd.

TABLE OF CONTENTS

1. GENERAL INFORMATION.....3

1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....3

1.2 TEST STANDARDS.....3

1.3 RELATED SUBMITTAL(S)/GRANT(S)3

1.4 TEST METHODOLOGY3

1.5 TEST FACILITY4

1.6 EUT EXERCISE SOFTWARE4

1.7 ACCESSORIES EQUIPMENT LIST AND DETAILS4

1.8 EUT CABLE LIST AND DETAILS4

2. SUMMARY OF TEST RESULTS5

3. §15.107 (A)- CONDUCTED EMISSION6

3.1 MEASUREMENT UNCERTAINTY6

3.2 TEST EQUIPMENT LIST AND DETAILS6

3.3 TEST PROCEDURE.....6

3.4 BASIC TEST SETUP BLOCK DIAGRAM.....6

3.5 ENVIRONMENTAL CONDITIONS7

3.6 TEST RECEIVER SETUP7

3.7 SUMMARY OF TEST RESULTS/PLOTS7

3.8 CONDUCTED EMISSIONS TEST DATA.....7

4. §15.109(A)- RADIATED EMISSION12

4.1 MEASUREMENT UNCERTAINTY12

4.2 TEST EQUIPMENT LIST AND DETAILS12

4.3 TEST PROCEDURE.....12

4.4 TEST RECEIVER SETUP13

4.5 CORRECTED AMPLITUDE & MARGIN CALCULATION.....13

4.6 ENVIRONMENTAL CONDITIONS13

4.7 SUMMARY OF TEST RESULTS/PLOTS13

1. GENERAL INFORMATION

1.1 Product Description for Equipment Under Test (EUT)

Client Information

Applicant: Shanghai feixun Communication Co., Ltd.
 Address of applicant: NO. 90, HQ Business Park, 4855 Guangfulin Road,
 Songjiang District, Shanghai 201616, China

Manufacturer: Shanghai feixun Communication Co., Ltd.
 Address of manufacturer: NO. 2100 1-10 Songzheng Road, Songjiang District,
 Shanghai, China

General Description of E.U.T

Items	Description
EUT Description:	Desktop Switch
Trade Name:	FeiXun
Model No.:	FreeSwitch 808I
Rate Current:	DC 5V
Rate Voltage:	1A
Size:	15.7 x9.0 x2.5 cm
For more information refer to the circuit diagram form and the user's manual.	

The test data is gathered from a production sample, provided by the manufacturer.

1.2 Test Standards

The following report is prepared on behalf of the Shanghai feixun Communication Co., LTD. in accordance with Part 2, Subpart J, and Part 15, Subparts A and B of the Federal Communication Commissions rules.

The objective is to determine compliance with FCC Part 15.107, and 15.109 rules.

Maintenance of compliance is the responsibility of the manufacturer. Any modification of the product, which results in lowering the emission/immunity, should be checked to ensure compliance has been maintained.

1.3 Related Submittal(s)/Grant(s)

No Related Submittal(s).

1.4 Test Methodology

All measurements contained in this report were conducted with ANSI C63.4-2009, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

The equipment under test (EUT) was configured to measure its highest possible susceptibility against the tested

phenomena. The test modes were adapted accordingly in reference to the Operating Instructions.

1.5 Test Facility

FCC – Registration No.: **994117**

SEM.Test Compliance Services Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files and the Registration is 994117.

Industry Canada (IC) Registration No.: **7673A**

The 3m Semi-anechoic chamber of SEM.Test Compliance Services Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 7673A.

1.6 EUT Exercise Software

The EUT exercise program used during radiated and conducted testing was designed to exercise the system components. The test software, provided by the customer, is started while the EUT is on to simulate the normal work. under the Windows XP terminal.

1.7 Accessories Equipment List and Details

Description	Manufacturer	Model	Serial Number
Notebook PC	ASUA	X50R	74N0AS297138
Adapter	CLiCK	CPS005050100C	/

1.8 EUT Cable List and Details

Cable Description	Length (M)	Shielded/Unshielded	With Core/Without Core
POWER Cable	1.5	Unshielded	Without Core
Network Cable	2	Unshielded	Without Core

2. SUMMARY OF TEST RESULTS

Description of Test	Result
§15.107 (a) Conducted Emission	Compliant
§15.109(a) Radiated Emission	Compliant

3. §15.107 (a)- CONDUCTED EMISSION

3.1 Measurement Uncertainty

Base on NIS 81, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of any conducted emissions measurement is ± 2.88 dB.

3.2 Test Equipment List and Details


Description	Manufacturer	Model	Serial Number	Cal. Date	Due. Date
EMI Test Receiver	Rohde & Schwarz	ESPI	101611	2009-08-12	2010-08-11
L.I.S.N	Schwarz beck	NSLK8126	8126-224	2009-08-12	2010-08-11
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100911	2009-08-12	2010-08-11

3.3 Test Procedure

The setup of EUT is according with per ANSI C63.4-2009 measurement procedure. The specification used was with the FCC Part 15.107 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle. The spacing between the peripherals was 10 cm.

3.4 Basic Test Setup Block Diagram



3.5 Environmental Conditions

Temperature:	25 °C
Relative Humidity:	52%
ATM Pressure:	1012 mbar

3.6 Test Receiver Setup

During the conducted emission test, the test receiver was set with the following configurations:

Start Frequency 150 kHz
 Stop Frequency..... 30 MHz
 Sweep Speed Auto
 IF Bandwidth..... 10 kHz
 Quasi-Peak Adapter Bandwidth 9 kHz
 Quasi-Peak Adapter Mode Normal

3.7 Summary of Test Results/Plots

According to the data in section 3.8, the EUT complied with the FCC 15B Conducted margin for a Class B device, with the *worst* margin reading of:

-12.24 dB μ V at 0.162 MHz in the Line mode, Pk detector, 0.15-30MHz

3.8 Conducted Emissions Test Data

Plot of Conducted Emissions Test Data

Conducted Disturbance


EUT: Desktop Switch

M/N: FreeSwitch 808I

Operating Condition: Running with Program

Test Specification: N

Comment: AC 120V/60Hz connect to PC,



Date: 22.JUN.2010 11:01:00

EDIT PEAK LIST (Prescan Results)			
TRACE	FREQUENCY	LEVEL dBuV	DELTA LIMIT dB
Trace1:	-QP		
Trace2:	-AV		
Trace3:	---		
1 Max Peak	162 kHz	51.34	-14.01
2 Average	162 kHz	40.21	-15.15
1 Max Peak	526 kHz	38.25	-17.74
2 Average	526 kHz	28.13	-17.86

Date: 22.JUN.2010 11:01:08

Plot of Conducted Emissions Test Data

Conducted Disturbance


EUT: Desktop Switch

M/N: FreeSwitch 808I

Operating Condition: Running with Program

Test Specification: L

Comment: AC 120V/60Hz connect to PC,



Date: 22.JUN.2010 10:59:43

EDIT PEAK LIST (Prescan Results)			
TRACE	FREQUENCY	LEVEL dBuV	DELTA LIMIT dB
Trace1:	-QP		
Trace2:	-AV		
Trace3:	---		
1 Max Peak	162 kHz	53.12	-12.24
2 Average	162 kHz	43.10	-12.25
1 Max Peak	530 kHz	39.41	-16.59
2 Average	530 kHz	31.06	-14.93

Date: 22.JUN.2010 10:59:58

4. §15.109(a)- RADIATED EMISSION

4.1 Measurement Uncertainty

Base on NIS 81, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of any radiation emissions measurement is ± 5.10 dB.

4.2 Test Equipment List and Details


Description	Manufacturer	Model	Serial Number	Cal. Date	Due. Date
Spectrum Analyzer	ROHDE&SCHWARZ	FSEA20	DE25181	2009-08-12	2010-08-11
Positioning Controller	C&C	CC-C-1F	N/A	2009-08-12	2010-08-11
Trilog Broadband Antenna	SCHWARZBECK	VULB9163	9163-333	2009-07-21	2010-07-20
Horn Antenna	SCHWARZBECK	BBHX 9120	9120-426	2009-07-21	2010-07-20
RF Switch	EM	EMSW18	SW060023	2009-08-12	2010-08-11
Amplifier	Agilent	8447F	3113A06717	2009-08-12	2010-08-11
Coaxial Cable	SCHWARZBECK	AK9513	9513-10	2009-08-12	2010-08-11
Spectrum Analyzer	ROHDE&SCHWARZ	FSP	N/A	2010-04-16	2011-04-15

4.3 Test Procedure

The setup of EUT is according with per ANSI C63.4-2009 measurement procedure. The specification used was with the FCC Part 15.205 and FCC Part 15.109 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.



4.4 Test Receiver Setup

During the conducted emission test, the test receiver was set with the following configurations:

Start Frequency 30 MHz
 Stop Frequency..... 1000 MHz
 Sweep Speed Auto
 IF Bandwidth..... 10 kHz
 Quasi-Peak Adapter Bandwidth 120 kHz
 Quasi-Peak Adapter Mode Normal

4.5 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and the Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} - \text{Corr. Factor}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of $-6\text{dB}\mu\text{V}$ means the emission is $6\text{dB}\mu\text{V}$ below the maximum limit for Class B. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corr. Ampl.} - \text{FCC Part 15B Limit}$$

4.6 Environmental Conditions

Temperature:	25 °C
Relative Humidity:	54%
ATM Pressure:	1011 mbar

4.7 Summary of Test Results/Plots

According to the data, the EUT complied with the FCC 15B Class B standards, and had the worst margin of:

-1.90 dB μ V at 251.1803MHz in the Horizontal polarization, 30 MHz to 1 GHz, 3Meters

Plot of Radiation Emissions Test Data

Radiated Disturbance

EUT: Desktop Switch


M/N: FreeSwitch 808I

Operating Condition: Running with Program

Test Specification: Horizontal & Vertical


Comment: AC 120V/60Hz connect to PC,

Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	64.8864	30.01	5.25	35.26	40.00	-4.74	325	114	QP
2	138.3873	33.77	3.32	37.09	43.50	-6.41	360	100	peak
3	251.1803	36.39	7.71	44.10	46.00	-1.90	204	224	QP

Vertical



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	38.8879	25.70	7.64	33.34	40.00	-6.66	360	100	peak
2	124.5690	31.14	4.63	35.77	43.50	-7.73	0	100	peak
3	251.1803	32.54	7.71	40.25	46.00	-5.75	0	200	peak

***** END OF REPORT *****