

FCC/ISED - TEST REPORT

Report Number : **68.950.23.1192.01** Date of Issue: **January 10, 2024**

Model / HVIN : **CA0905**

Product Type : **Wireless Headphones**

Applicant : **Audio Partnership PLC**

Address : **Gallery Court, Hankey Place, London, SE1 4BB, United Kingdom**

Manufacturer : **Audio Partnership PLC**

Address : **Gallery Court, Hankey Place, London, SE1 4BB, United Kingdom**

Factory : **Charter Media (Dongguan) Co., Ltd.**

Address : **Dabandi Industrial Zone, Daning District, Humen Town, 523930 Dongguan City, Guangdong Province, PEOPLE'S REPUBLIC OF CHINA**

Test Result : **Positive** **Negative**

Total pages including Appendices : **46**

Any use for advertising purposes must be granted in writing. This technical report may only be quoted in full. This report is the result of a single examination of the object in question and is not generally applicable evaluation of the quality of other products in regular production. For further details, please see testing and certification regulation, chapter A-3.4.

1 Table of Contents

1	Table of Contents	2
2	Details about the Test Laboratory	3
3	Description of the Equipment Under Test	4
4	Summary of Test Standards	5
5	Summary of Test Results	6
6	General Remarks	7
7	Test Setups	8
8	Systems Test Configuration	10
9	Technical Requirement	11
9.1	Conducted Emission	11
9.2	Conducted Peak Output Power & EIRP	14
9.3	Power Spectral Density	16
9.4	6 dB Bandwidth and 99% Occupied Bandwidth	20
9.5	Spurious RF Conducted Emissions	27
9.6	Band Edge	35
9.7	Spurious Radiated Emissions for Transmitter	38
10	Test Equipment List	45
11	System Measurement Uncertainty	46

2 Details about the Test Laboratory

Details about the Test Laboratory

Test Site 1

Company name: TÜV SÜD Certification and Testing (China) Co., Ltd. Shenzhen Branch
Building 12 & 13, Zhiheng Wisdomland Business Park, Guankou Erlu,
Nantou, Nanshan District Shenzhen 518052
P.R. China

Telephone: +86 755 8828 6998

Fax: +86 755 8828 5299

FCC Registration No.: 514049

FCC Designation Number: CN5009

IC Registration No.: 10320A

ISED CAB identifier: CN0077

3 Description of the Equipment Under Test

Product Name/PMN	Wireless Headphones
Model no./ Hardware Version Identification No. (HVIN)	CA0905
FCC ID:	YKBCA0905-042
IC:	9095A-CA0905042
Options and accessories:	N/A
Rating:	Input:5V $\overline{\text{---}}$ 1A Battery Capacity:3.7V, 980mAh
RF Transmission Frequency:	2402MHz-2480MHz
No. of Operated Channel:	40
Modulation:	GFSK
Antenna Type:	Monopole antenna
Antenna Gain:	2.7dBi
Description of the EUT:	The Equipment Under Test (EUT) is a Wireless Headphones which support Bluetooth function. Only Bluetooth Low Energy included in this report.

NOTE 1: The above EUT's information is declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

4 Summary of Test Standards

Test Standards	
FCC Part 15 Subpart C 10-1-2021 Edition	PART 15 - RADIO FREQUENCY DEVICES Subpart C - Intentional Radiators
RSS-Gen Issue 5 April 2018 + Amendment 1 March 2019 + Amendment 2 February 2021	General Requirements for Compliance of Radio Apparatus
RSS-247 Issue 3 August 2023	Digital Transmission Systems (DTSS), Frequency Hopping Systems (FHSS) and License-Exempt Local Area Network (LE-LAN) Devices

All the test methods were according to KDB 558074 D01 15.247 Meas Guidance v05r02 Measurement Guidance and ANSI C63.10-2020.

5 Summary of Test Results

Technical Requirements			
FCC Part 15 Subpart C/ RSS-247 Issue 3/RSS-Gen Issue 5			
Test Condition		Test Site	Test Result
§15.207 & RSS-GEN 8.8	Conducted emission AC power port	Site 1	PASS
§15.247 (b) (3) & RSS-247 5.4(d)	Conducted peak output power	Site 1	PASS
RSS-247 5.4(d)	Equivalent Isotropic Radiated Power	Site 1	PASS
§15.247(a)(2) & RSS-247 5.2(a) & RSS-GEN 6.7	6dB bandwidth and 99% Occupied Bandwidth	Site 1	PASS
§15.247(e) & RSS-247 5.2(b)	Power spectral density	Site 1	PASS
§15.247(d) & RSS-247 5.5	Spurious RF conducted emissions	Site 1	PASS
§15.247(d) & RSS-247 5.5	Band edge	Site 1	PASS
§15.247(d) & §15.209 & §15.205 & RSS-247 5.5 & RSS-Gen 6.13	Spurious radiated emissions for transmitter	Site 1	PASS
§15.203 & RSS-Gen 6.8	Antenna requirement	See note 2	PASS

Note 1: N/A=Not Applicable.

Note 2: The EUT uses a monopole antenna and manufacturer will stick it down with glue, which gain is 2.7dBi. In accordance to §15.203 & RSS-Gen 6.8, it is considered sufficiently to comply with the provisions of this section.

6 General Remarks

Remarks

This submittal(s) (test report) is intended for FCC ID: YKBCA0905-042, IC: 9095A-CA0905042 complies with Section 15.207, 15.209, 15.247 of the FCC Part 15, Subpart C rules and RSS-247, RSS-GEN.

SUMMARY:

All tests according to the regulations cited on page 5 were

■ - Performed

□ - **Not** Performed

The Equipment under Test

■ - **Fulfills** the general approval requirements.

□ - **Does not** fulfill the general approval requirements.


Sample Received Date: December 25, 2023

Testing Start Date: December 25, 2023

Testing End Date: January 10, 2024

- TÜV SÜD Certification and Testing (China) Co., Ltd. Shenzhen Branch -

Reviewed by:



John Zhi
Project Manager

Prepared by:



Sanvin Zheng
Project Engineer

Tested by:




Carry Cai
Test Engineer




7 Test Setups

7.1 Radiated test setups


9KHz - 30MHz




30M - 1GHz




Above 1GHz



7.2 Conducted RF test setups



7.3 AC Power Line Conducted Emission test setups



8 Systems Test Configuration

Auxiliary Equipment Used during Test:

Description	Manufacturer	Model NO.	S/N
Adaptor	Apple	A1443	5VDC, 1.0A
Computer	HP	5CD302CY52	---

Cables Used During Test:

Cable	Length	Shielded/unshielded	With / without ferrite
C-to-C Cable	1.25m	Shielded	Without ferrite
3.5mm-to-C Cable	1.25m	Shielded	Without ferrite

Test software information:

Test Software Version	Bluetest3	
Modulation	Setting TX Power	Packet Type
GFSK	Default	RBS9

The system was configured to non-hopping mode, testing channel 0, 19, 39.

9 Technical Requirement

9.1 Conducted Emission

Test Method

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. Both sides of AC line were checked for maximum conducted interference.
6. The frequency range from 150 kHz to 30 MHz was searched.
7. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.


Limit

Frequency MHz	QP Limit dB μ V	AV Limit dB μ V
0.150-0.500	66-56*	56-46*
0.500-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

Conducted Emission

Product Type : Wireless Headphones
 M/N : CA0905
 Operating Condition : Charging+Transmitting
 Test Specification : Line
 Comment : AC 120V/60Hz



Critical_Freqs

Frequency (MHz)	MaxPeak (dBμV)	Average (dBμV)	Limit (dBμV)	Margin (dB)	Line	Corr. (dB)
0.154000	35.02	---	65.78	30.77	L1	9.52
0.190000	31.45	---	64.04	32.59	L1	9.54
0.370000	23.85	---	58.50	34.65	L1	9.57
0.850000	24.75	---	56.00	31.25	L1	9.60
2.266000	24.67	---	56.00	31.33	L1	9.63
4.418000	---	12.43	46.00	33.57	L1	9.72
4.926000	27.26	---	56.00	28.74	L1	9.74


Remark:

Max Peak= Read level + Corrector factor

Correct factor=cable loss + LISN factor

Conducted Emission

Product Type : Wireless Headphones
M/N : CA0905
Operating Condition : Charging+Transmitting
Test Specification : Neutral
Comment : AC 120V/60Hz



Critical Freqs

Frequency (MHz)	MaxPeak (dBμV)	Average (dBμV)	Limit (dBμV)	Margin (dB)	Line	Corr. (dB)
0.166000	33.64	---	65.16	31.52	N	9.57
0.222000	28.77	---	62.74	33.98	N	9.58
0.522000	---	12.68	46.00	33.32	N	9.62
0.522000	23.73	---	56.00	32.27	N	9.62
1.062000	24.08	---	56.00	31.92	N	9.63
2.330000	25.94	---	56.00	30.06	N	9.66
4.994000	26.04	---	56.00	29.96	N	9.78

Remark:

Max Peak= Read level + Corrector factor

Correct factor=cable loss + LISN factor

9.2 Conducted Peak Output Power & EIRP

Test Method

1. The RF output of EUT was connected to the power meter by RF cable. The path loss was compensated to the results for each measurement.
2. Set to the maximum power setting and enable the EUT transmit continuously
3. Use the following test receiver settings:
Span = approximately 5 times the 6dB bandwidth, centered on a hopping channel
RBW > the 6dB bandwidth of the emission being measured, VBW \geq 3RBW,
Sweep = auto, Detector function = peak, Trace = max hold
4. Allow the trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. The indicated level is the peak output power and record the results in the test report.
5. Repeat above procedures until all frequencies measured were complete.

Limits

According to §15.247 (b) (3) & RSS-247 5.4(d), conducted peak output power limit as below:

Frequency Range MHz	Limit W	Limit dBm
2400-2483.5	≤ 1	≤ 30

According to & RSS-247 5.4(d), EIRP limit as below:

Frequency Range MHz	Limit W	Limit dBm
2400-2483.5	≤ 4	≤ 36

Conducted Peak Output Power & EIRP

Frequency MHz	Mode	Conducted Peak Output Power dBm	Antenna Gain dBi	EIRP dBm	Result
Bottom channel 2402MHz	LE 1M	5.11	2.7	7.81	Pass
Middle channel 2440MHz	LE 1M	4.89	2.7	7.59	Pass
Top channel 2480MHz	LE 1M	4.89	2.7	7.59	Pass
Bottom channel 2402MHz	LE 2M	5.12	2.7	7.82	Pass
Middle channel 2440MHz	LE 2M	4.89	2.7	7.59	Pass
Top channel 2480MHz	LE 2M	4.89	2.7	7.59	Pass

9.3 Power Spectral Density

Test Method

1. The RF output of EUT was connected to the test receiver by RF cable. The path loss was compensated to the results for each measurement.
2. Set to the maximum power setting and enable the EUT transmit continuously
3. Set analyzer center frequency to DTS channel center frequency. RBW=3kHz, VBW≥3RBW, Span=1.5 times DTS bandwidth, Detector=Peak, Sweep=auto, Trace= max hold.
4. Allow the trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. The indicated level is the peak output power and record the results in the test report.
5. Repeat above procedures until other frequencies measured were completed.

Limit


Limit [dBm]

≤8


Test result

Frequency MHz	Mode	Power spectral density dBm/3KHz	Result
Bottom channel 2402MHz	LE 1M	-6.75	Pass
Middle channel 2440MHz	LE 1M	-6.71	Pass
Top channel 2480MHz	LE 1M	-6.67	Pass
Bottom channel 2402MHz	LE 2M	-10.24	Pass
Middle channel 2440MHz	LE 2M	-10.07	Pass
Top channel 2480MHz	LE 2M	-10.26	Pass


BLE_1M_Ant0_2402




BLE_1M_Ant0_2440




BLE_1M_Ant0_2480




BLE_2M_Ant0_2402



BLE_2M_Ant0_2440



BLE_2M_Ant0_2480



9.4 6 dB Bandwidth and 99% Occupied Bandwidth

Test Method for 6 dB Bandwidth

1. Set center frequency to the nominal EUT channel center frequency
2. Set RBW = 1 % to 5 % of the emission bandwidth
3. Set the video bandwidth (VBW) $\geq 3 \times$ RBW
4. Detector = Peak.
5. Trace mode = max hold.
6. Sweep = Sweep = No faster than coupled (auto) time.
7. Allow the trace to stabilize.
8. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.
9. Record the results in the test report.

Limit

Limit [kHz]

≥500

Test Method for 99 % Bandwidth

1. Set center frequency to the nominal EUT channel center frequency
2. Set span = 1.5 times to 5.0 times the OBW.
3. Set RBW = 1 % to 5 % of the OBW
4. Set VBW ≥ 3 RBW
5. Trace mode = max hold.
6. Sweep = auto couple.
7. Allow the trace to stabilize.
8. Use the 99 % power bandwidth function of the instrument.
9. Record the results in the test report.



Limit

Limit [kHz]


Test result

Frequency MHz	Mode	6dB bandwidth MHz	99% bandwidth MHz	Result
Bottom channel 2402MHz	LE 1M	0.723	1.038	Pass
Middle channel 2440MHz	LE 1M	0.718	1.038	Pass
Top channel 2480MHz	LE 1M	0.722	1.035	Pass
Bottom channel 2402MHz	LE 2M	1.214	2.080	Pass
Middle channel 2440MHz	LE 2M	1.263	2.081	Pass
Top channel 2480MHz	LE 2M	1.264	2.079	Pass


6 dB Bandwidth




BLE_1M_Ant0_2480




BLE_2M_Ant0_2402



BLE_2M_Ant0_2440




BLE_2M_Ant0_2480




99% Bandwidth


BLE_1M_Ant0_2402




BLE_1M_Ant0_2440




BLE_1M_Ant0_2480




BLE_2M_Ant0_2402



BLE_2M_Ant0_2440



BLE_2M_Ant0_2480



9.5 Spurious RF Conducted Emissions

Test Method


1. The RF output of EUT was connected to the spectrum analyzer by RF cable. The path loss was compensated to the results for each measurement.
2. Set to the maximum power setting, the instrument center frequency is set to the nominal EUT channel center frequency enable the EUT transmit continuously.
3. Use the following spectrum analyzer settings:
Span = wide enough to capture the peak level of the in-band emission and all spurious emissions (e.g., harmonics) from the lowest frequency generated in the EUT up through the 10th harmonic. Typically, several plots are required to cover this entire span.
RBW = 100 kHz, VBW \geq 3RBW, Sweep = auto, Detector function = peak, Trace = max hold
4. Allow the trace to stabilize. Set the marker on the peak of any spurious emission recorded.
5. The level displayed must comply with the limit specified in this Section. Submit these plots.
6. Repeat above procedures until all frequencies measured were complete.


Limit

Frequency Range MHz	Limit (dBc)
30-25000	-20


Spurious RF conducted emissions

Test Mode	Antenna	Channel (MHz)	Frequency Range (MHz)	Reference Level	Result (dBm)	Limit (dBm)	Verdict
BLE_1M	Ant0	2402	Reference	8.74	8.74	---	PASS
			30~25000	30~25000	-48.91	<=-11.20	PASS
		2440	Reference	8.80	8.80	---	PASS
			30~25000	30~25000	-50.03	<=-11.20	PASS
		2480	Reference	8.75	8.75	---	PASS
			30~25000	30~25000	-48.31	<=-11.20	PASS
BLE_2M	Ant0	2402	Reference	8.68	8.68	---	PASS
			30~25000	30~25000	-49.24	<=-11.25	PASS
		2440	Reference	8.75	8.75	---	PASS
			30~25000	30~25000	-50.06	<=-11.25	PASS
		2480	Reference	8.70	8.70	---	PASS
			30~25000	30~25000	-49.66	<=-11.25	PASS







BLE_1M_Ant0_2440_0-Reference




BLE_1M_Ant0_2440_30-25000




BLE_1M_Ant0_2480_0-Reference




BLE_1M_Ant0_2480_30-25000




BLE_2M_Ant0_2402_0-Reference




BLE_2M_Ant0_2402_30-25000




BLE_2M_Ant0_2440_0-Reference




BLE_2M_Ant0_2440_30-25000



BLE_2M_Ant0_2480_0-Reference



BLE_2M_Ant0_2480_30-25000



9.6 Band Edge

Test Method

1. The RF output of EUT was connected to the spectrum analyzer by RF cable. The path loss was compensated to the results for each measurement.
2. Set to the maximum power setting, the instrument center frequency is set to the nominal EUT channel center frequency enable the EUT transmit continuously.
3. Use the following spectrum analyzer settings:
Span = wide enough to capture the peak level of the in-band emission and all spurious emissions (e.g., harmonics) from the lowest frequency generated in the EUT up through the 10th harmonic. Typically, several plots are required to cover this entire span.
RBW = 100 kHz, VBW≥3RBW, Sweep = auto, Detector function = peak, Trace = max hold
4. Allow the trace to stabilize. Set the marker on the peak of any spurious emission recorded.
5. The level displayed must comply with the limit specified in this Section. Submit these plots.
6. Repeat above procedures until all frequencies measured were complete.



Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under § 15.247(b)(3) and RSS-247 section 5.4(d), the attenuation required shall be 30 dB instead of 20 dB.


Frequency Range MHz	Limit (dBc)
30-25000	-20

Band edge testing


Test Mode	Antenna	Channel	Channel (MHz)	Reference Level (dBm)	Result (dBm)	Limit (dBm)	Verdict
BLE_1M	Ant0	Low	2402	8.80	-44.40	<=-11.20	PASS
		High	2480	8.80	-51.34	<=-11.20	PASS
BLE_2M	Ant0	Low	2402	8.75	-25.31	<=-11.25	PASS
		High	2480	8.75	-49.10	<=-11.25	PASS



BLE_2M_Ant0_Low_2402



BLE_2M_Ant0_High_2480



9.7 Spurious Radiated Emissions for Transmitter

Test Method

1. The EUT was placed on a turn table which is 1.5m above ground plane for above 1GHz and 0.8m above ground for below 1GHz at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
2. The EUT was set 3 meters away from the interference – receiving antenna, which was mounted on the top of a variable – height antenna tower.
3. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
5. Use the following spectrum analyzer settings According to C63.10:

For Below 1GHz

Use the following test receiver settings:

Span = wide enough to capture the peak level of the in-band emission and all spurious
 RBW = 100 KHz to 120KHz, VBW ≥ RBW for peak measurement, Sweep = auto, Detector function = peak, Trace = max hold.

For Peak unwanted emissions Above 1GHz:

Span = wide enough to capture the peak level of the in-band emission and all spurious
 RBW = 1MHz, VBW ≥ RBW for peak measurement, Sweep = auto, Detector function = peak, Trace = max hold.

Procedures for average unwanted emissions measurements above 1000 MHz

a) RBW = 1MHz.

b) VBW \ [3 × RBW].

c) Detector = RMS (power averaging), if [span / (# of points in sweep)] \ RBW / 2.

Satisfying this condition can require increasing the number of points in the sweep or reducing the span. If the condition is not satisfied, then the detector mode shall be set to peak.

d) Averaging type = power (i.e., rms) (As an alternative, the detector and averaging type may be set for linear voltage averaging. Some instruments require linear display mode to use linear voltage averaging. Log or dB averaging shall not be used.)

e) Sweep time = auto.

f) Perform a trace average of at least 100 traces if the transmission is continuous. If the transmission is not continuous, then the number of traces shall be increased by a factor of 1 / D, where D is the duty cycle. For example, with 50% duty cycle, at least 200 traces shall be averaged. (If a specific emission is demonstrated to be continuous—i.e., 100% duty cycle—then rather than turning ON and OFF with the transmit cycle, at least 100 traces shall be averaged.)

g) If tests are performed with the EUT transmitting at a duty cycle less than 98%, then a correction factor shall be added to the measurement results prior to comparing with the emission limit, to compute the emission level that would have been measured had the test been performed at 100% duty cycle. The correction factor is computed as follows:

1) If power averaging (rms) mode was used in the preceding step e), then the correction factor is [10 log (1 / D)], where D is the duty cycle. For example, if the transmit duty

- cycle was 50%, then 3 dB shall be added to the measured emission levels.
- 2) If linear voltage averaging mode was used in the preceding step e), then the correction factor is $[20 \log (1 / D)]$, where D is the duty cycle. For example, if the transmit duty cycle was 50%, then 6 dB shall be added to the measured emission levels.
- 3) If a specific emission is demonstrated to be continuous (100% duty cycle) rather than turning ON and OFF with the transmit cycle, then no duty cycle correction is required for that emission (AV) at frequency above 1GHz.

Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under § 15.247(b)(3) and RSS 247 section 5.4(d), the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general field strength limits specified in § 15.209(a) and RSS-Gen is not required. In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a) and RSS-Gen section 8.9, must also comply with the radiated emission limits specified in § 15.209(a) and RSS-Gen section 8.10.

Frequency MHz	Field Strength μV/m	Field Strength dBμV/m	Detector	Measurement distance meters
0.009-0.490	2400/F(kHz)	48.5-13.8	AV	300
0.490-1.705	24000/F(kHz)	33.8-23.0	QP	30
1.705-30	30	29.5	QP	30
30-88	100	40	QP	3
88-216	150	43.5	QP	3
216-960	200	46	QP	3
960-1000	500	54	QP	3
Above 1000	500	54	AV	3
Above 1000	5000	74	PK	3

Note 1: Limit 3m(dBμV/m)=Limit 300m(dBμV/m)+40Log(300m/3m) (Below 30MHz)


Note 2: Limit 3m(dBμV/m)=Limit 30m(dBμV/m)+40Log(30m/3m) (Below 30MHz)

Spurious radiated emissions for transmitter

According to C63.10, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement, so AV emission value did not show in below table if the peak value complies with average limit.


The only worse case (which is subject to the maximum EIRP, LE 2M mode) test result is listed in the report.

Test data_30MHz to 1000MHz



Critical Freqs


Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
48.968889	23.18	40.00	16.82	200.0	H	331.0	18.29
100.863889	22.24	43.50	21.26	100.0	H	4.0	16.06
159.279444	25.17	43.50	18.33	100.0	H	187.0	13.12
353.387222	27.63	46.00	18.37	200.0	H	173.0	19.87
718.538333	34.92	46.00	11.08	100.0	H	357.0	26.59
926.603333	39.12	46.00	6.88	200.0	H	68.0	29.49



Critical Freqs


Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
51.771111	24.04	40.00	15.96	200.0	V	30.0	18.22
102.750000	21.41	43.50	22.09	100.0	V	230.0	16.01
197.971667	23.30	43.50	20.20	100.0	V	194.0	16.17
296.696111	25.74	46.00	20.26	200.0	V	249.0	18.40
482.558889	29.78	46.00	16.22	200.0	V	240.0	22.75
743.435000	35.25	46.00	10.75	200.0	V	134.0	27.36

BLE_2Mbps_Low Channel:



Critical Freqs


Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
1798.500000	40.46	74.00	33.54	150.0	H	323.0	-5.00
3075.000000	46.98	74.00	27.02	150.0	H	177.0	1.53
12711.000000	41.36	74.00	32.64	150.0	H	269.0	12.82



Critical Freqs


Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
1599.000000	43.94	74.00	30.06	150.0	V	275.0	-6.85
3501.500000	48.90	74.00	25.10	150.0	V	296.0	4.41
12785.000000	42.05	74.00	31.95	150.0	V	270.0	12.96

BLE_2Mbps _Middle Channel:



Critical Freqs


Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
1961.000000	41.64	74.00	32.36	150.0	H	201.0	-4.23
3517.000000	48.04	74.00	25.96	150.0	H	47.0	3.63
10563.500000	40.59	74.00	33.41	150.0	H	224.0	10.10



Critical Freqs


Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
1599.500000*	41.44	74.00	32.56	150.0	V	300.0	-6.84
3498.000000	48.50	74.00	25.50	150.0	V	331.0	4.33
12883.500000	42.65	74.00	31.35	150.0	V	189.0	12.93

BLE_2Mbps_High Channel:



Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
1592.500000	44.91	74.00	29.09	150.0	H	344.0	-6.96
2479.500000	48.99	74.00	25.01	150.0	H	167.0	-1.80
12551.500000*	42.37	74.00	31.63	150.0	H	91.0	12.54



Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
1598.500000*	46.96	74.00	27.04	150.0	V	146.0	-6.86
3040.000000	46.56	74.00	27.44	150.0	V	157.0	1.35
12659.000000*	42.32	74.00	31.68	150.0	V	333.0	12.75

Remark:

- (1) "*" means the emission(s) appear within the restrict bands shall follow the requirement of section 15.205 & RSS-GEN 8.10.
- (2) Data of measurement within frequency range 9kHz-30MHz, 18-26GHz are the noise floor or attenuated more than 20dB below the permissible limits or the field strength is too small to be measured, so test data does not present in this report.
- (3) Corrected Amplitude = Read level + Corrector factor
 Above 1GHz: Corrector factor = Antenna Factor + Cable Loss- Amplifier Gain
 Below 1GHz: Corrector factor = Antenna Factor + Cable Loss
 (The Reading Level is recorded by software which is not shown in the sheet)

10 Test Equipment List

List of Test Instruments

Conducted Emission Test

Description	Manufacturer	Model no.	Equipment ID	Serial no.	Cal interval (year)	Cal. due date
EMI Test Receiver	Rohde & Schwarz	ESR 3	68-4-74-19-002	102590	1	2024-5-19
LISN	Rohde & Schwarz	ENV216	68-4-87-19-001	102472	1	2024-5-20
Attenuator	Shanghai Huaxiang	TS2-26-3	68-4-81-16-003	080928189	1	2024-5-19
Test software	Rohde & Schwarz	EMC32	68-4-90-19-005-A01	Version 10.35.02	N/A	N/A
Shielding Room	TDK	CSR #2	68-4-90-19-005	----	3	2025-10-15

Radiated Emission Test, SAC-3 #2

Description	Manufacturer	Model no.	Equipment ID	Serial no.	Cal interval (year)	Cal. due date
EMI Test Receiver	Rohde & Schwarz	ESR 26	68-4-74-14-002	101269	1	2024-5-20
Trilog Super Broadband Test Antenna	Schwarzbeck	VULB 9162	68-4-80-19-003	284	1	2024-3-5
Horn Antenna	Rohde & Schwarz	HF907	68-4-80-14-005	102294	1	2024-5-28
Loop Antenna	Rohde & Schwarz	HFH2-Z2	68-4-80-14-006	100398	1	2024-8-7
Pre-amplifier	Rohde & Schwarz	SCU 18F	68-4-29-19-001	100745	1	2024-5-19
Pre-amplifier	Rohde & Schwarz	SCU 18F	68-4-29-19-002	100746	1	2024-5-19
Sideband Horn Antenna	Q-PAR	QWH-SL-18-40-K-SG	68-4-80-14-008	12827	1	2024-7-11
Pre-amplifier	Rohde & Schwarz	SCU 40A	68-4-29-14-002	100432	1	2024-8-1
Attenuator	Mini-circuits	UNAT-6+	68-4-81-21-002	15542	1	2024-5-19
3m Semi-anechoic chamber	TDK	SAC-3 #2	68-4-90-19-006	----	2	2024-5-28
Test software	Rohde & Schwarz	EMC32	68-4-90-19-006-A01	Version 10.35.02	N/A	N/A

RF Conducted Test

Description	Manufacturer	Model no.	Equipment ID	Serial no.	Cal interval (year)	Cal. due date
Signal Analyzer	Rohde & Schwarz	FSV40	68-4-74-14-004	101030	1	2024-5-19

11 System Measurement Uncertainty

For a 95% confidence level, the measurement expanded uncertainties for defined systems, in accordance with the recommendations of ISO 17025 were:

System Measurement Uncertainty	
Test Items	Extended Uncertainty
Uncertainty for Conducted Emission in shielding room (68-4-90-19-004) 150kHz-30MHz (for test using AMN ENV432 or ENV4200)	3.15dB
Uncertainty for Radiated Emission in 3m chamber (68-4-90-14-001) 9kHz-30MHz	4.70dB
Uncertainty for Radiated Emission in new 3m chamber (68-4-90-19-006) 30MHz-1000MHz	Horizontal: 4.63dB; Vertical: 4.78dB;
Uncertainty for Radiated Emission in new 3m chamber (68-4-90-19-006) 1000MHz-18000MHz	Horizontal: 5.38dB; Vertical: 5.38dB;
Uncertainty for Radiated Emission in new 3m chamber (68-4-90-19-006) 18GHz-40GHz	5.29dB
Uncertainty for Conducted RF test	RF Power Conducted: 1.31dB Frequency test involved: 0.6×10 ⁻⁸ or 1%

Measurement Uncertainty Decision Rule:

Determination of conformity with the specification limits is based on the decision rule according to IEC Guide 115: 2021, clause 4.4.3 and 4.5.1.

---THE END OF REPORT---