

FCC ID: **YKBG2-023**

Portable device

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB447498 D01 General RF Exposure Guidance V06

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})]^*$

$[\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

$f(\text{GHz})$ is the RF channel transmit frequency in GHz;

Power and distance are rounded to the nearest mW and mm before calculation;

The result is rounded to one decimal place for comparison;

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm

and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

We use 5mm as separation distance to calculate.

Maximum measured transmitter power:

BT DSS:

Transmit Frequency (GHz)	Mode	EIRP (dBm)	tune up maximum power	Result calculation	1-g SAR
2.402	GFSK	4.90	5.5	1.10	3.0
2.441	GFSK	4.08	5.5	1.11	3.0
2.480	GFSK	4.68	5.5	1.12	3.0
2.402	$\pi/4$ -DQPSK	4.93	5.5	1.10	3.0
2.441	$\pi/4$ -DQPSK	4.90	5.5	1.11	3.0
2.480	$\pi/4$ -DQPSK	5.47	5.5	1.12	3.0
2.402	8DPSK	4.98	5.5	1.10	3.0
2.441	8DPSK	5.04	5.5	1.11	3.0
2.480	8DPSK	5.33	5.5	1.12	3.0

BT DTS:

Transmit Frequency (GHz)	Mode	EIRP (dBm)	tune up maximum power	Result calculation	1-g SAR
2.402	GFSK	4.98	5.5	1.10	3.0
2.441	GFSK	4.46	5.5	1.11	3.0
2.480	GFSK	4.59	5.5	1.12	3.0

Conclusion:

For the max result : $1.12 \leq 3.0$ for 1-g SAR extremity SAR, No SAR is required.

Signature:



Date: 2016-8-22

NAME AND TITLE (Please print or type): David Lee/Manager

COMPANY (Please print or type): Shenzhen EMTEK Co.,Ltd./Building 69, Majialong Industry Zone, Nanshan District, Shenzhen,Guangdong,China