



FCC LISTED, REGISTRATION
NUMBER: 2764.01

ISED LISTED REGISTRATION
NUMBER: 23595-1

Test report No:
3858ERM.003A1

Test report

**USA FCC Part 15.249, 15.209
CANADA RSS-210, RSS-Gen
Radio Frequency Devices. Operation within the bands 902-928
MHz, 2400-2483.5 MHz, 5725-5875 MHz, and 24.0-24.25 GHz.**

(*) Identification of item tested	Cellular Communicator Module
(*) Trademark	Alarm.com
(*) Model and /or type reference tested	Rev4.9 LTE Communicator Module
Other identification of the product	FCC ID: YL6-143490L IC ID: 9111A-143490L HVIN: ADC-490L-XT HVIN: ADC-490L-SEM
(*) Features	Cellular, Z-Wave, Ethernet
Manufacturer	Alarm.com, Inc 8281 Greensboro Dr, Suite 100 Tyson, VA 22102 USA
Test method requested, standard	USA FCC Part 15.249 10-1-20 Edition: Operation within the bands 902 - 928 MHz, 2400 -2483.5 MHz, 5725 - 5875 MHz, and 24.0 – 24.25 GHz. USA FCC Part 15.209 10-1-20 Edition: Radiated emission limits; general requirements. CANADA RSS-210 Issue 10, August 2019 CANADA RSS-Gen Issue 5, April 2018 ANSI C63.10-2013: American National Standard for Testing Unlicensed Wireless Devices.
Summary	IN COMPLIANCE
Approved by (name / position & signature)	Domingo Galvez EMC&RF Lab Manager
Date of issue	02-23-2023
Report template No	FDT08_23 (* "Data provided by the client")

Index

Competences and guarantees	3
General conditions	3
Uncertainty	3
Data provided by the client.....	4
Usage of samples	4
Test sample description	6
Identification of the client.....	7
Testing period and place.....	7
Document history	7
Environmental conditions	8
Remarks and comments	8
Testing verdicts.....	9
Summary	9
List of equipment used during the test.....	10
Appendix A: Test results (Z-wave)	11

Competences and guarantees

DEKRA Certification Inc. is a testing laboratory accredited by A2LA (The American Association for Laboratory Accreditation), to perform the tests indicated in the Certificate 2764.01

DEKRA Certification Inc. is a testing laboratory competent to carry out the tests described in this report.

In order to assure the traceability to other national and international laboratories, DEKRA Certification Inc. has a calibration and maintenance program for its measurement equipment.

DEKRA Certification Inc. guarantees the reliability of the data presented in this report, which is the result of the measurements and the tests performed to the item under test on the date and under the conditions stated on the report and, it is based on the knowledge and technical facilities available at DEKRA Certification at the time of performance of the test.

DEKRA Certification Inc. is liable to the client for the maintenance of the confidentiality of all information related to the item under test and the results of the test.

The results presented in this Test Report apply only to the item under test established in this document.

IMPORTANT: No parts of this report may be reproduced or quoted out of context, in any form or by any means, except in full, without the previous written permission of DEKRA Certification Inc.

General conditions

1. This report is only referred to the item that has undergone the test.
2. This report does not constitute or imply on its own an approval of the product by the Certification Bodies or competent Authorities.
3. This document is only valid if complete; no partial reproduction can be made without previous written permission of DEKRA Certification Inc.
4. This test report cannot be used partially or in full for publicity and/or promotional purposes without previous written permission of DEKRA Certification Inc. and the Accreditation Bodies.

Uncertainty

Uncertainty (factor $k=2$) was calculated according to the DEKRA Certification internal document PODT000.

Test case	Frequency (MHz)	U (k=2)	Units
Occupied Bandwidth	908-916	1.87	%
Radiated Spurious Emission	30-180	4.27	dB
	180-1000	3.14	dB
	1000-18000	3.30	dB
	18000-40000	3.49	dB

Data provided by the client

The following data has been provided by the client:

1. Information relating to the description of the sample ("Identification of the item tested", "Trademark", "Model and/or type reference tested").
2. Alarm.com LTE Communicator Module with an integrated Z-Wave radio. This device transmits security and alarm signals through the LTE network. It is designed to fit into certain security panels and integrate with the Alarm.com cloud.

DEKRA declines any responsibility with respect to the information provided by the client and that may affect the validity of results.

Usage of samples

Samples used for test have been selected by: The client.

Sample S/01 is composed of the following elements, accessories and auxiliary equipment:

Id	Control Number	Description	Manufacturer/Model	Serial N°	Date of Reception	Application
S/01	3858/01	Module DCR 1 Radio + Z-Wave SEM Antenna	Alarm.com / Rev4.9-03	-	10/26/2022	Element Under Test
S/01	3858/07	Primary Cell antenna for DCR1	EPH-405AL	-	10/26/2022	Accessory
S/01	3858/10	USB to TTL Serial cable	FTDI Chip / TTL-232R-3V3	-	10/26/2022	Accessory
S/01	3858/12	AC adapter for DCR1/2	TRIAD / WSU120-3000	-	10/26/2022	Accessory
S/01	3796/08	Power Adapter Board	Alarm.com	-	07/14/2022	Accessory

Sample S/01, was used for the following test(s): All Radiated test indicated in appendix A.

Sample S/02 is composed of the following elements, accessories and auxiliary equipment:

Id	Control Number	Description	Manufacturer/Model	Serial N°	Date of Reception	Application
S/02	3858/02	Module DCR 1 Radio + Z-Wave CONCORD Antenna	Alarm.com / Rev4.9-03	-	10/26/2022	Element Under Test
S/02	3858/07	Primary Cell antenna for DCR1	EPH-405AL	-	10/26/2022	Accessory
S/02	3858/08	Diversity Cell antenna for DCR1	-	-	10/26/2022	Accessory
S/02	3858/10	USB to TTL Serial cable	FTDI Chip / TTL-232R-3V3	-	10/26/2022	Accessory
S/02	3858/12	AC adapter for DCR1/2	TRIAD / WSU120-3000	-	10/26/2022	Accessory
S/02	3796/08	Power Adapter Board	Alarm.com	-	07/14/2022	Accessory

Sample S/02, was used for the following test(s): All Radiated test indicated in appendix A.

Sample S/03 is composed of the following elements, accessories and auxiliary equipment:

Id	Control Number	Description	Manufacturer/Model	Serial N°	Date of Reception	Application
S/03	3858/03	Module DCR 1 Radio + Z-Wave XT Antenna	Alarm.com	-	10/26/2022	Element Under Test
S/03	3858/07	Primary Cell antenna for DCR1	EPH-405AL	-	10/26/2022	Accessory
S/03	3858/08	Diversity Cell antenna for DCR1	-	-	10/26/2022	Accessory
S/03	3858/10	USB to TTL Serial cable	FTDI Chip / TTL-232R-3V3	-	10/26/2022	Accessory
S/03	3858/12	AC adapter for DCR1/2	TRIAD / WSU120-3000	-	10/26/2022	Accessory
S/03	3796/08	Power Adapter Board	Alarm.com	-	07/14/2022	Accessory

Sample S/03, was used for the following test(s): All Radiated test indicated in appendix A.

Sample S/04 is composed of the following elements, accessories and auxiliary equipment:

Id	Control Number	Description	Manufacturer/Model	Serial N°	Date of Reception	Application
S/04	3858/03	Module DCR 1 Radio + Z-Wave XT Antenna	Alarm.com	-	10/26/2022	Element Under Test
S/04	3858/10	USB to TTL Serial cable	FTDI Chip / TTL-232R-3V3	-	10/26/2022	Accessory
S/04	3858/12	AC adapter for DCR1/2	TRIAD / WSU120-3000	-	10/26/2022	Accessory
S/04	3796/08	Power Adapter Board	Alarm.com	-	07/14/2022	Accessory

Sample S/04, was used for the following test(s): All Conducted test indicated in appendix A.

Test sample description

Test Sample description (compulsory information for EMC and RF testing services)

Ports..... :	Port name and description	Cable					
		Specified length [m]	Attached during test	Shielded	Coupled to patient		
	Ethernet		<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>		
	Power and data IO		<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>		
			<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>		
			<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>		
Supplementary information to the ports..... :	No Data Provided						
Rated power supply	Voltage and Frequency	Reference poles					
		L1	L2	L3	N	PE	
	<input type="checkbox"/>	AC: 120-240 – Input AC adapter	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
	<input type="checkbox"/>	AC:	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
	<input checked="" type="checkbox"/>	DC: 12Vdc					
<input type="checkbox"/>	DC:						
Rated Power	No Data Provided						
Clock frequencies..... :	32.768 kHz, 24 MHz, 50 MHz, 54 MHz, 132 MHz						
Other parameters	No Data Provided						
Software version	191						
Hardware version	Rev4.9						
Dimensions in cm (W x H x D)	No Data Provided						
Mounting position	<input type="checkbox"/>	Table top equipment					
	<input checked="" type="checkbox"/>	Wall/Ceiling mounted equipment					
	<input type="checkbox"/>	Floor standing equipment					
	<input type="checkbox"/>	Hand-held equipment					
	<input type="checkbox"/>	Other: Plugged into wall outlet					

Modules/parts.....:	Module/parts of test item	Type	Manufacturer
	LE910C1-NF	Cellular	Telit
	ME910G1-WW	Cellular	Telit
	ZM5202	Z-Wave	Silicon Labs
Accessories (not part of the test item)	Description	Type	Manufacturer
	No Data Provided		
Documents as provided by the applicant	Description	File name	Issue date
	Declaration Equipment	FDT30_18 Declaration Equipment Data_Rev4.9_Final	09/30/2022
Copy of marking plate:			
NO MARKING PLATE FOUND			

Identification of the client

Alarm.com, Inc
 8281 Greensboro Dr, Suite 100
 Tyson, VA 22102
 USA

Testing period and place

Test Location	DEKRA Certification Inc.
Date (start)	11-11-2022
Date (finish)	11-18-2022

Document history

Report number	Date	Description
3853ERM.003	12-07-22	First release
3853ERM.003A1	02-18-23	Second release. Add HVIN reference number in the cover page. This modification of the test report cancels and replaces the test report 3853ERM.003.

Environmental conditions

In the control chamber, the following limits were not exceeded during the test:

Temperature	Min. = 15 °C Max. = 35 °C
Relative humidity	Min. = 30 % Max. = 75 %
Air pressure	Min. = 860 mbar Max. = 1060 mbar

In the semianechoic chamber, the following limits were not exceeded during the test.

Temperature	Min. = 15 °C Max. = 35 °C
Relative humidity	Min. = 30 % Max. = 75 %
Air pressure	Min. = 860 mbar Max. = 1060 mbar

In the chamber for conducted measurements, the following limits were not exceeded during the test:

Temperature	Min. = 15 °C Max. = 35 °C
Relative humidity	Min. = 30 % Max. = 60 %
Air pressure	Min. = 860 mbar Max. = 1060 mbar

Remarks and comments

The tests have been performed by the technical personnel: Lakshmi Gollamudi, Juliana Cherry, Yuri Barone, Qi Zhang, and Koji Nishimoto.

Testing verdicts

Not applicable :	N/A
Pass :	P
Fail :	F
Not measured :	N/M

Summary

FCC PART 15.249 PARAGRAPH / RSS-210 (Z-wave)					
Report Section	FCC Spec Clause	RSS Spec Clause	Test Description	Verdict	Remark
A.1	§ 2.1049	RSS-Gen 6.7	99% Occupied Bandwidth	P	N/A
A.2	§ 15.249 (a)	RSS-210 B.10 (a)	Field Strength of fundamental	P	N/A
A.3	§ 15.249 (d)	RSS-210 B.10 (b)	Emission limitations radiated (Transmitter)	P	N/A
<u>Supplementary information and remarks:</u>					
None.					

List of equipment used during the test

Conducted Measurements

CONTROL NUMBER	DESCRIPTION	MANUFACTURER	MODEL	LAST CALIBRATION	NEXT CALIBRATION
1039	FSV40 Signal analyzer 40 GHz	Rohde & Schwarz	FSV40	2022/11	2024/11
1107	Ethernet SNMP Thermometer- SAC	HW Group	HWg-STE Plain	2022/10	2024/10

Radiated Measurements

CONTROL NUMBER	DESCRIPTION	MANUFACTURER	MODEL	LAST CALIBRATION	NEXT CALIBRATION
1461	RF pre-amplifier	Bonn Elektronik	BLMA0118-4A	2022/06	2024/06
1012	EMI TEST RECEIVER	Rohde & Schwarz	ESR 26	2022/04	2024/04
1014	Spectrum analyzer	Rohde & Schwarz	FSV40	2021/05	2023/05
1057	Double-ridge Waveguide Horn antenna 1-18 GHz	ETS LINDGREN	3115	2020/06	2023/06
1065	Biconical Log antenna	ETS LINDGREN	3142E	2020/08	2023/08
1111	ETHERNET SNMP THERMOMETER	HW GROUP	HWg-STE Plain	2022/10	2024/10
1179	Semi anechoic Absorber Lined Chamber	Frankonia	SAC 3 plus "L"	N/A	N/A
1314	WIRELESS MEASUREMENT SOFTWARE R&S EMC32	Rohde & Schwarz	N/A	N/A	N/A

Appendix A: Test results (Z-wave)

Appendix A Content

PRODUCT INFORMATION	13
DESCRIPTION OF TEST CONDITIONS	14
TEST A.1: 99% OCCUPIED BANDWIDTH	15
TEST A.2: FUNDAMENTAL FIELD STRENGTH	18
TEST A.3: EMISSION LIMITATIONS RADIATED (TRANSMITTER).....	26

PRODUCT INFORMATION

The following information is provided by the client

Information	Description
Modulation	GFSK/FSK
Operation mode	
- Operating Frequency Range	908.4/916 MHz
- RF Output Power	Z-Wave (Concord): -9 dBm Z-Wave (XT): -6 dBm Z-Wave (SEM): -6 dBm
Antenna type	Copper Wire
Antenna gain	Z-Wave (Concord): -0.1 dBi Peak Z-Wave (XT): -0.32 dBi Peak Z-Wave (SEM): -0.09 dBi Peak
Nominal Voltage	
- Supply Voltage	12 Vdc
- Type of power source	AC/DC Adapter
Equipment type	Z-wave Mesh

DESCRIPTION OF TEST CONDITIONS

(*): Data provided by the client.

TEST CONDITIONS	DESCRIPTION
TC/01	<p><u>Power supply (V):</u> $V_{\text{nominal}} = 12 \text{ Vdc}$</p> <p><u>Modulation:</u> GFSK/FSK</p> <p><u>Test Frequencies for Conducted/ Radiated tests:</u> Channel 0: 916.0 MHz - Baud Rate (100kbps) Channel 1: 908.4 MHz - Baud Rate (40kbps) Channel 2: 908.4 MHz - Baud Rate (9.6kbps)</p>


TEST A.1: 99% OCCUPIED BANDWIDTH

LIMITS:	Product standard:	§ 2.1049 and RSS-Gen
	Test standard:	§ 2.1049 and RSS-Gen 6.7

LIMITS

The occupied bandwidth shall be reported for all equipment in addition to the specified bandwidth required in the applicable RSSs.

TEST SETUP




TESTED SAMPLES:	S/04
TESTED CONDITIONS MODES:	TC/01
TEST RESULTS:	PASS

	Channel 0 916 MHz	Channel 1 908.4 MHz	Channel 2 908.4 MHz
99% bandwidth (kHz)	162.08	157.74	153.40


TEST RESULTS (Cont.):

Channel 0



Date: 28.NOV.2022 19:42:20

Channel 1



Date: 28.NOV.2022 19:49:18

TEST A.2: FUNDAMENTAL FIELD STRENGTH

LIMITS:	Product standard:	Part 15 Subpart C §15.249 and RSS-210
	Test standard:	Part 15 Subpart C §15.249(a) and RSS-210 B.10(a)

LIMITS

The field strength of emissions in this band shall not exceed 2500 millivolts/meter. The field strength of emissions from intentional radiators shall comply with the following

Frequency Range (MHz)	Field strength of fundamental (mV/m)	Field strength (dBµV/m)	Measurement distance (m)
902 - 928	50	93.98	3
2400 – 2483.5	50	93.98	3
5725 - 5875	50	93.98	3
24000-24250	250	107.96	3

For frequencies above 1000 MHz, the above field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

RSS-210. The field strength of fundamental and harmonic emissions, measured at 3 m, shall not exceed 50 mV/m and 0.5 mV/m respectively. Attenuation below the general field strength limits specified in RSS-Gen is not required

TEST SETUP


All radiated tests were performed in a semi-anechoic chamber. The measurement antenna is situated at a distance of 3 m for the frequency range 30-1000 MHz (Bilog antenna).

The equipment under test was set up on a non-conductive platform above the ground plane and the situation and orientation was varied to find the maximum radiated emission. It was also rotated 360° and the antenna height was varied from 1 to 4 meters to find the maximum radiated emission.

Measurements were made in both horizontal and vertical planes of polarization.

The field strength is calculated by adding correction factor to the measured level from the spectrum analyzer. This correction factor includes antenna factor and cable loss.

Radiated measurements setup $f < 1$ GHz




TESTED SAMPLES:	S/01
TESTED CONDITIONS MODES:	TC/01
TEST RESULTS:	PASS

	Channel 0 916 MHz	Channel 1 908.4 MHz	Channel 2 908.4 MHz
Field strength (dB μ V/m)	92.3	91.7	91.9

TEST RESULTS (Cont.):


Channel 0



- PK+_MAXH
- TX limits to Spurious Emission FCC15.249 (30MHz to 1GHz) 902-928MHz+15.209 QPK Limit
- ▽ MaxPeak-PK+ (Single)
- × QuasiPeak-QPK (Single)


TEST RESULTS (Cont.):

Channel 1



- PK+ _MAXH
- TX limits to Spurious Emission FCC15.249 (30MHz to 1GHz) 902-928MHz+15.209 QPK Limit
- ▽ MaxPeak-PK+ (Single)
- × QuasiPeak-QPK (Single)

Channel 2




- PK+ _MAXH
- TX limits to Spurious Emission FCC15.249 (30MHz to 1GHz) 902-928MHz+15.209 QPK Limit
- ▽ MaxPeak-PK+ (Single)
- × QuasiPeak-QPK (Single)

TESTED SAMPLES:	S/02
TESTED CONDITIONS MODES:	TC/01
TEST RESULTS:	PASS

	Channel 0 916 MHz	Channel 1 908.4 MHz	Channel 2 908.4 MHz
Field strength (dB μ V/m)	89.2	87.4	84.0

TEST RESULTS (Cont.):


Channel 0



- PK+ _MAXH
- TX limits to Spurious Emission FCC15.249 (30MHz to 1GHz) 902-928MHz+15.209 QPK Limit
- x MaxPeak-PK+ (Single)
- x QuasiPeak-QPK (Single)


TEST RESULTS (Cont.):

Channel 1



- PK+ _MAXH
- TX limits to Spurious Emission FCC15.249 (30MHz to 1GHz) 902-928MHz+15.209 QPK Limit
- ∇ MaxPeak-PK+ (Single)
- x QuasiPeak-QPK (Single)

Channel 2




- PK+ _MAXH
- TX limits to Spurious Emission FCC15.249 (30MHz to 1GHz) 902-928MHz+15.209 QPK Limit
- ∇ MaxPeak-PK+ (Single)
- x QuasiPeak-QPK (Single)

TESTED SAMPLES:	S/03
TESTED CONDITIONS MODES:	TC/01
TEST RESULTS:	PASS

	Channel 0 916 MHz	Channel 1 908.4 MHz	Channel 2 908.4 MHz
Field strength (dB μ V/m)	89.1	92.5	87.9

TEST RESULTS (Cont.):


Channel 0



- PK+ _MAXH
- TX limits to Spurious Emission FCC15.249 (30MHz to 1GHz) 902-928MHz+15.209 QPK Limit
- x MaxPeak-PK+ (Single)
- x QuasiPeak-QPK (Single)


TEST RESULTS (Cont.):

Channel 1



- PK+ _MAXH
- TX limits to Spurious Emission FCC15.249 (30MHz to 1GHz) 902-928MHz+15.209 QPK Limit
- ▽ MaxPeak-PK+ (Single)
- x QuasiPeak-QPK (Single)

Channel 2



- PK+ _MAXH
- TX limits to Spurious Emission FCC15.249 (30MHz to 1GHz) 902-928MHz+15.209 QPK Limit
- ▽ MaxPeak-PK+ (Single)
- x QuasiPeak-QPK (Single)

TEST A.3: EMISSION LIMITATIONS RADIATED (TRANSMITTER)

LIMITS:	Product standard:	Part 15 Subpart C §15.249 and RSS-210
	Test standard:	Part 15 Subpart C §15.249(b), RSS-210 and RSS-Gen 8.9 and 8.10

LIMITS

The field strength of harmonics from intentional radiators shall comply with section 15.249 mentioned as the following:

Frequency Range (MHz)	Field strength of fundamental (mV/m)	Field strength (dB μ V/m)	Measurement distance (m)
902 - 928	50	93.98	3
2400 – 2483.5	50	93.98	3
5725 - 5875	50	93.98	3
24000-24250	250	107.96	3

Radiated emissions outside of the specific frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of fundamental or to the general radiated emission limits specified in section 15.209:

Frequency Range (MHz)	Field strength (μ V/m)	Field strength (dB μ V/m)	Measurement distance (m)
0.009-0.490	2400/F(kHz)	-	300
0.490-1.705	24000/F(kHz)	-	30
1.705 - 30.0	30	-	30
30 - 88	100	40	3
88 - 216	150	43.5	3
216 - 960	200	46	3
960 - 25000	500	54	3

The emission limits shown in the above table are based on measurements employing CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.

For average radiated emission measurements above 1000 MHz, there is also a limit corresponding to 20 dB above the indicated values in the table is specified when measuring with peak detector function.

TEST SETUP


All radiated tests were performed in a semi-anechoic chamber. The measurement antenna is situated at a distance of 3 m for the frequency range 30-1000 MHz (Bi-log antenna) and 1 GHz-18 GHz (Double ridge horn antenna).

The equipment under test was set up on a non-conductive platform above the ground plane and the situation and orientation was varied to find the maximum radiated emission. It was also rotated 360° and the antenna height was varied from 1 to 4 meters to find the maximum radiated emission.


Measurements were made in both horizontal and vertical planes of polarization.

The field strength is calculated by adding correction factor to the measured level from the spectrum analyzer. This correction factor includes antenna factor, cable loss and pre-amplifiers gain.

Radiated measurements Setup $f < 1$ GHz




Radiated measurements setup $f > 1$ GHz



TESTED SAMPLES:	S/01
TESTED CONDITIONS MODES:	TC/01
TEST RESULTS:	PASS

Channel 0




- PK+_MAXH
- TX limits to Spurious Emission FCC15.249 (30MHz to 1GHz) 902-928MHz+15.209 QPK Limit
- ▽ MaxPeak-PK+ (Single)
- x QuasiPeak-QPK (Single)

Frequency (MHz)	MaxPeak (dBµV/m)	QuasiPeak (dBµV/m)	Pol	Margin - QPK (dB)	Limit - QPK (dBµV/m)	Comment
60.312500	35.8	28.3	V	11.7	40.0	
111.965000	34.0	24.3	V	19.2	43.5	
122.635000	31.1	22.8	V	20.7	43.5	
253.391000	29.0	16.4	V	29.6	46.0	
485.997000	40.5	35.3	V	10.7	46.0	
916.046500	93.4	92.3	H	1.7	94.0	Fundamental

TEST RESULTS (Cont.):

30-1000 MHz

Channel 1




- PK+_MAXH
- TX limits to Spurious Emission FCC15.249 (30MHz to 1GHz) 902-928MHz+15.209 QPK Limit
- ▽ MaxPeak-PK+ (Single)
- x QuasiPeak-QPK (Single)

Frequency (MHz)	MaxPeak (dBµV/m)	QuasiPeak (dBµV/m)	Pol	Margin - QPK (dB)	Limit - QPK (dBµV/m)	Comment
49.982000	25.6	18.8	V	21.2	40.0	
59.148500	34.8	28.0	V	12.0	40.0	
110.946500	32.8	22.0	V	21.5	43.5	
150.037500	29.5	23.0	V	20.5	43.5	
485.997000	40.3	35.3	V	10.7	46.0	
908.383500	91.9	91.7	H	2.3	94.0	Fundamental

TEST RESULTS (Cont.):

30-1000 MHz

Channel 2




- PK+ _MAXH
- TX limits to Spurious Emission FCC15.249 (30MHz to 1GHz) 902-928MHz+15.209 QPK Limit
- ▽ MaxPeak-PK+ (Single)
- × QuasiPeak-QPK (Single)

Frequency (MHz)	MaxPeak (dBµV/m)	QuasiPeak (dBµV/m)	Pol	Margin - QPK (dB)	Limit - QPK (dBµV/m)	Comment
58.615000	33.8	27.1	V	12.9	40.0	
81.361500	28.0	15.0	V	25.0	40.0	
105.563000	32.0	22.4	V	21.1	43.5	
149.989000	28.4	20.9	V	22.6	43.5	
485.997000	39.1	33.0	V	13.0	46.0	
908.432000	92.1	91.9	H	2.1	94.0	Fundamental

TEST RESULTS (Cont.):

1-18 GHz

Channel 0




— AVG_MAXH — TX limits to Spurious Emission FCC15.249 (Above 1GHz) 902-928MHz_Av

Frequency (MHz)	PK+_MAXH (dBµV/m)	AVG_MAXH (dBµV/m)	Pol	Margin - AVG (dB)	Limit - AVG (dBµV/m)
1125.000000	43.6	33.4	H	20.6	54.0
1374.500000	46.3	35.2	V	18.8	54.0
14198.000000	50.2	41.7	V	12.3	54.0

TEST RESULTS (Cont.):

1-18 GHz

Channel 1




— AVG_MAXH — TX limits to Spurious Emission FCC15.249 (Above 1GHz) 902-928MHz_Av

Frequency (MHz)	PK+ MAXH (dBµV/m)	AVG_MAXH (dBµV/m)	Pol	Margin - AVG (dB)	Limit - AVG (dBµV/m)
1375.000000	45.7	35.5	H	18.5	54.0
2725.500000	50.2	39.8	H	14.2	54.0
14192.500000	51.1	40.1	H	13.8	54.0

TEST RESULTS (Cont.):

1-18 GHz

Channel 2




— AVG_MAXH — TX limits to Spurious Emission FCC15.249 (Above 1GHz) 902-928MHz_Av

Frequency (MHz)	PK+_MAXH (dBµV/m)	AVG_MAXH (dBµV/m)	Pol	Margin - AVG (dB)	Limit - AVG (dBµV/m)
14198.000000	53.2	41.3	V	12.7	54.0
15875.500000	52.6	40.2	H	13.8	54.0
17873.500000	52.4	40.8	H	13.1	54.0

TESTED SAMPLES:	S/02
TESTED CONDITIONS MODES:	TC/01
TEST RESULTS:	PASS

Channel 0




- PK+_MAXH
- TX limits to Spurious Emission FCC15.249 (30MHz to 1GHz) 902-928MHz+15.209 QPK Limit
- ▽ MaxPeak-PK+ (Single)
- x QuasiPeak-QPK (Single)

Frequency (MHz)	MaxPeak (dBµV/m)	QuasiPeak (dBµV/m)	Pol	Margin - QPK (dB)	Limit - QPK (dBµV/m)	Comment
49.982000	35.5	33.1	V	6.9	40.0	
87.230000	35.1	27.4	V	12.7	40.0	
149.989000	36.0	33.1	V	10.4	43.5	
377.987500	35.5	27.4	V	18.6	46.0	
485.948500	37.5	29.7	V	16.3	46.0	
915.998000	89.7	89.2	V	4.8	94.0	Fundamental

TEST RESULTS (Cont.):

30-1000 MHz

Channel 1




- PK+_CLRWR
- PK+_MAXH
- TX limits to Spurious Emission FCC15.249 (30MHz to 1GHz) 902-928MHz+15.209 QPK Limit
- ▽ MaxPeak-PK+ (Single)
- × QuasiPeak-QPK (Single)

Frequency (MHz)	MaxPeak (dBµV/m)	QuasiPeak (dBµV/m)	Pol	Margin - QPK (dB)	Limit - QPK (dBµV/m)	Comment
49.982000	36.4	34.3	V	5.7	40.0	
87.618000	36.0	28.6	V	11.4	40.0	
149.989000	33.9	30.1	V	13.4	43.5	
377.987500	33.5	23.7	V	22.3	46.0	
485.997000	40.5	34.8	V	11.2	46.0	
908.383500	87.7	87.4	V	6.6	94.0	Fundamental

TEST RESULTS (Cont.):

30-1000 MHz

Channel 2




- PK+_MAXH
- TX limits to Spurious Emission FCC15.249 (30MHz to 1GHz) 902-928MHz+15.209 QPK Limit
- ▽ MaxPeak-PK+ (Single)
- × QuasiPeak-QPK (Single)

Frequency (MHz)	MaxPeak (dBµV/m)	QuasiPeak (dBµV/m)	Pol	Margin - QPK (dB)	Limit - QPK (dBµV/m)	Comment
49.982000	36.3	34.1	V	5.9	40.0	
87.715000	36.5	29.3	V	10.7	40.0	
149.989000	37.8	34.4	V	9.1	43.5	
377.987500	35.6	28.3	V	17.7	46.0	
485.997000	40.2	34.9	V	11.1	46.0	
908.383500	84.4	84.0	V	10.0	94.0	Fundamental

TEST RESULTS (Cont.):

1-18 GHz

Channel 0




— AVG_MAXH — TX limits to Spurious Emission FCC15.249 (Above 1GHz) 902-928MHz_Av

Frequency (MHz)	MaxPeak (dBµV/m)	QuasiPeak (dBµV/m)	PoI	Margin - QPK (dB)	Limit - QPK (dBµV/m)
2748.000000	52.8	47.4	V	6.6	54.0
14202.500000	49.4	41.2	V	12.8	54.0

TEST RESULTS (Cont.):

1-18 GHz

Channel 1




— AVG_MAXH — TX limits to Spurious Emission FCC15.249 (Above 1GHz) 902-928MHz_Av

Frequency (MHz)	PK+_MAXH (dBµV/m)	AVG_MAXH (dBµV/m)	PoI	Margin - AVG (dB)	Limit - AVG (dBµV/m)
2725.500000	52.0	44.8	H	9.2	54.0
14202.500000	50.2	41.1	H	12.8	54.0

TEST RESULTS (Cont.):

1-18 GHz

Channel 2




— AVG_MAXH — TX limits to Spurious Emission FCC15.249 (Above 1GHz) 902-928MHz_Av

Frequency (MHz)	PK+_MAXH (dBµV/m)	AVG_MAXH (dBµV/m)	Pol	Margin - AVG (dB)	Limit - AVG (dBµV/m)
2725.500000	53.0	46.5	V	7.5	54.0
14605.500000	51.0	41.3	H	12.7	54.0

TESTED SAMPLES:	S/03
TESTED CONDITIONS MODES:	TC/01
TEST RESULTS:	PASS

Channel 0




- PK+_MAXH
- TX limits to Spurious Emission FCC15.249 (30MHz to 1GHz) 902-928MHz+15.209 QPK Limit
- ∇ MaxPeak-PK+ (Single)
- x QuasiPeak-QPK (Single)

Frequency (MHz)	MaxPeak (dBµV/m)	QuasiPeak (dBµV/m)	PoI	Margin - QPK (dB)	Limit - QPK (dBµV/m)	Comment
49.982000	26.1	19.0	V	21.1	40.0	
59.294000	36.7	29.1	V	10.9	40.0	
96.057000	38.1	29.3	V	14.3	43.5	
124.187000	39.5	30.5	V	13.1	43.5	
485.997000	38.6	32.4	V	13.6	46.0	
916.046500	90.2	89.1	V	4.9	94.0	Fundamental

TEST RESULTS (Cont.):

30-1000 MHz

Channel 1




- PK+_MAXH
- TX limits to Spurious Emission FCC15.249 (30MHz to 1GHz) 902-928MHz+15.209 QPK Limit
- ▽ MaxPeak-PK+ (Single)
- × QuasiPeak-QPK (Single)

Frequency (MHz)	MaxPeak (dBµV/m)	QuasiPeak (dBµV/m)	Pol	Margin - QPK (dB)	Limit - QPK (dBµV/m)	Comment
49.982000	26.9	19.5	V	20.5	40.0	
55.511000	35.8	28.2	V	11.8	40.0	
98.142500	38.8	28.7	V	14.8	43.5	
124.332500	36.7	27.1	V	16.4	43.5	
485.997000	38.7	32.5	V	13.5	46.0	
908.432000	93.2	92.5	V	1.5	94.0	Fundamental

TEST RESULTS (Cont.):

30-1000 MHz

Channel 2




- PK+_MAXH
- TX limits to Spurious Emission FCC15.249 (30MHz to 1GHz) 902-928MHz+15.209 QPK Limit
- ▽ MaxPeak-PK+ (Single)
- × QuasiPeak-QPK (Single)

Frequency (MHz)	MaxPeak (dBµV/m)	QuasiPeak (dBµV/m)	Pol	Margin - QPK (dB)	Limit - QPK (dBµV/m)	Comment
49.982000	26.8	18.9	V	21.1	40.0	
87.618000	36.2	28.1	V	11.9	40.0	
96.639000	38.5	28.8	V	14.7	43.5	
378.036000	34.8	26.2	V	19.8	46.0	
485.997000	39.0	33.0	V	13.0	46.0	
908.480500	89.8	87.9	V	6.1	94.0	Fundamental

TEST RESULTS (Cont.):

1-18 GHz

Channel 0




— AVG_MAXH — TX limits to Spurious Emission FCC15.249 (Above 1GHz) 902-928MHz_Av

Frequency (MHz)	PK+_MAXH (dBµV/m)	AVG_MAXH (dBµV/m)	PoI	Margin - AVG (dB)	Limit - AVG (dBµV/m)
2748.000000	55.7	51.6	V	2.4	54.0
17996.000000	50.0	41.2	V	12.8	54.0

TEST RESULTS (Cont.):

1-18 GHz

Channel 1




— AVG_MAXH — TX limits to Spurious Emission FCC15.249 (Above 1GHz) 902-928MHz_Av

Frequency (MHz)	PK+_MAXH (dBµV/m)	AVG_MAXH (dBµV/m)	Pol	Margin - AVG (dB)	Limit - AVG (dBµV/m)
2725.500000	54.4	50.0	V	4.0	54.0
17996.500000	51.1	42.6	H	11.4	54.0

TEST RESULTS (Cont.):

1-18 GHz

Channel 2



— AVG_MAXH — TX limits to Spurious Emission FCC15.249 (Above 1GHz) 902-928MHz_Av

Frequency (MHz)	PK+_MAXH (dBµV/m)	AVG_MAXH (dBµV/m)	Pol	Margin - AVG (dB)	Limit - AVG (dBµV/m)
2725.500000	55.2	51.3	V	2.7	54.0
17993.500000	50.6	41.8	V	12.1	54.0