Rhein Tech Laboratories, Inc. 360 Herndon Parkway Suite 1400 Herndon, VA 20170 http://www.rheintech.com Client: Alarm.com Model/HVIN: ADC-XCVR200 Standards: FCC 15.247/IC RSS-247 ID's: YL6-143XCVR200/9111A-143XCVR200 Report #: 2016238

## Appendix C: FCC Modular Approval Criteria

Please refer to the following page.



To: American Certification Body, Inc. 6731 Whittier Avenue Suite C110 McLean, VA 22101

Subject: FCC Full Modular Approval Criteria - Alarm.com ADC-XCVR200

To Whom It May Concern:

Alarm.com requests full module approval certification for the transmitter module FCC: YL6-143XCVR200, Model: ADC-XCVR200. The module meets the requirements from KDB 996369, Section III as follows:

i. The radio elements must have the radio frequency circuitry shielded. Physical components and tuning capacitor(s) may be located external to the shield, but must be on the module assembly:

[Alarm.com] – Device is equipped with metal shielding to cover RF elements.

- The module must have buffered modulation/data inputs to ensure that the device will comply with Part 15 requirements with any type of input signal;
   [Alarm.com] Inputs to the module are buffered through microprocessor units.
- iii. The module must contain power supply regulation on the module; [Alarm.com] The device contains a 3.3V LDO regulator to power the radio.
- iv. The module must contain a permanently attached antenna, or contain a unique antenna connector, and be marketed and operated only with specific antenna(s), per Sections 15.203, 15.204(b), 15.204(c), 15.212(a), 2.929(b);

  [Alarm.com] The device is equipped with a printed PCB antenna.
- v. The module must demonstrate compliance in a stand-alone configuration;
  [Alarm.com] The device was tested outside of a host device that would normally supply power.
- vi. The module must be labeled with its permanently affixed FCC ID label, or use an electronic display (See KDB Publication 784748 about labeling requirements);

  [Alarm.com] The device is labeled with an Alarm.com-assigned FCC ID.
- vii. The module must comply with all specific rules applicable to the transmitter including all the conditions provided in the integration instructions by the grantee;

  [Alarm.com] The transmitter will not send data unless installed in a compatible control panel. In order for the module to do the aforementioned, a button on the control panel must be pushed.
- viii. The module must comply with RF exposure requirements (see Clause V below). [Alarm.com] The module is not a portable device it is installed in a static location.

Regards,

**Daniel Ramos** 

Senior VP, Corporate Development

11/28/2016