



FCC ID: YLZ-C2
IC: 9088A-C2

Statement of compliance to Maximum Permissible Exposure (MPE)

Equipment : Blu-ray Disc Player
Type/Model : MVBD2535GPH
Applicant : China Hualu Group Co., Ltd.
No.1 Hua Road Qixianling Hi-tech Zone, Dalian, China

Here assuming a worst-case prediction of power density (100% reflection), then
 $S = 4PG / (4\pi R^2) = PG / (\pi R^2)$.

Where S = power density in mW/cm²

P = transmit power in mW

G = numeric gain of transmit antenna

R = distance (cm)

As we can see from the test report SH10070489-002:

The maximum conducted power P = 21.22dBm = 132.43mW

G = 2.00dBi = 1.58

Here R is chosen to be 20cm,

$$S = PG / (\pi R^2) = 132.43 * 1.58 / (3.14 * 20 * 20) = 0.17\text{mW/cm}^2$$

This level is below the 1 mW/cm² MPE for General Population / Uncontrolled Exposure as stated in OET BULLETIN 65 Edition 97-01.

Conclusion: this EUT fulfills 47CFR Part 15.247(i) (2007) with the definition outlined in the User's Manual. (See appendix I)

Date of issue: Aug 21, 2010

Prepared by:

Wakeyou Wang (Project engineer)

Reviewed by:

Daniel Zhao (Reviewer)



FCC ID: YLZ-C2
IC: 9088A-C2

Appendix I

Definition below must be outlined in the User Manual:

To satisfy FCC RF exposure requirements, a separation distance of 20 cm or more should be maintained between the antenna of this device and persons during device operation. To ensure compliance, operations at closer than this distance is not recommended. The antenna used for this transmitter must not be co-located in conjunction with any other antenna or transmitter.