



## Statement of compliance to Maximum Permissible Exposure (MPE)

Equipment : Wi-Fi Module  
Type/Model : U15A-U  
Applicant : China Hualu Group Co., Ltd.  
No.1 Hua Road, Qixianling Hi-Tech Zone, Dalian, China

Power density (S) is calculated according to the formula:

$$S = PG / (4\pi R^2)$$

Where S = power density in mW/cm<sup>2</sup>

P = transmit power in mW

G = numeric gain of transmit antenna

R = distance (cm)

As we can see from the test report SH12020837-009:

The maximum conducted power P = 12.94dBm = 19.679mW

G = 2.00dBi = 1.585


Here R is chosen to be 20cm,

$$S = PG / (4\pi R^2) = 19.679 * 1.585 / (4 * 3.14 * 20 * 20) = 0.0062\text{mW/cm}^2$$

This level is below the 1 mW/cm<sup>2</sup> MPE for General Population / Uncontrolled Exposure as stated in OET BULLETIN 65 Edition 97-01.


Date of issue: May 22, 2012

Prepared by:



Wakeyou Wang (Project Engineer)

Reviewed by:



Daniel Zhao (Reviewer)



## Appendix I

**Definition below must be outlined in the User Manual:**

To satisfy FCC RF exposure requirements, a separation distance of 20 cm or more should be maintained between the antenna of this device and persons during device operation. To ensure compliance, operations at closer than this distance is not recommended.