Request for Modular/Limited Modular Approval

Date: September 17, 2020					
Subject: Manufacturer's Declaration for \square -Modular \boxtimes - Limited	Approval Modular Approval	□ - SplitModula□ - Limited Split		pproval	
Confidentiality Request for:YMX-EC7510WLC					
	nts – FCC Part 15.212				
For Items Marked "NO(*)", the Limited Modul		Filled Out on the Fo			
Modular Approval Requirement The modular transmitter must have its own RF shielding. This is intended to ensure that the module does not have to rely upon the shielding provided by the device into which it is installed in order for all modular transmitter emissions to comply with FCC limits. It is also intended to prevent coupling between the RF circuitry of the module and any wires or circuits in the device into which the module is			□- YES	ment Met ⊠ - NO(*)	
installed. Such coupling may result in non-compliant operation. The physical crystal and tuning capacitors may be located external to the shielded radio elements. 15.212(a)(1)(i)					
Details: <example a="" antenna="" board="" connector="" contains="" metal="" module="" next="" of="" shield="" the="" to="" top="" –=""></example>	which covers all RF co	mponents and circuit	ry. The shield	l is located on	
2. The modular transmitter must have buffered modulation/da ensure that the module will comply with FCC requirements over-modulation. 15.212(a)(1)(ii)			⊠ - YES	□ - NO(*)	
Details: <example buf<br="" circuit="" data="" is="" modulation="" the="" to="" –="">application></example>	Details: <example -="" application="" as="" buffered="" circuit="" data="" described="" description="" in="" is="" modulation="" operational="" provided="" the="" to="" with=""></example>				
 The modular transmitter must have its own power supply re ensure that the module will comply with FCC requirements supplying circuitry in the device into which the module is in 	regardless of the design	n of the power	⊠ - YES	□ - NO(*)	
Details: <example -="" application="" contains="" filed="" its="" module="" own="" please="" power="" refer="" regulation.="" schematic="" supply="" the="" this="" to="" with=""></example>					
4. The modular transmitter must comply with the antenna and 15.203, 15.204(b), 15.204(c), 15.212(a), and 2.929(b). The attached or employ a "unique" antenna coupler (at all confunction antenna, including the cable). The "professional installation to modules but can apply to limited modular approvals under	antenna must either be prections between the mon' provision of § 15.20	permanently odule and the 3 is not applicable	⊠ - YES	□ - NO(*)	
Details: <example a="" and="" antenna="" antennas="" approved="" connector.="" connects="" its="" list="" module="" of="" td="" tested="" the="" thi<="" to="" with="" –=""><th></th><td></td><td></td><td></td></example>					
5. The modular transmitter must be tested in a stand-alone cor inside another device during testing. This is intended to den complying with Part 15 emission limits regardless of the de Unless the transmitter module will be battery powered, it m requirements found in Section 15.207. AC or DC power lin the module must not contain ferrites, unless they will be ma 15.27(a)). The length of these lines shall be length typical or least 10 centimeters to insure that there is no coupling betwe quipment. Any accessories, peripherals, or support equipments shall be unmodified or commercially available (see Section	nonstrate that the module vice into which it is even ust comply with the AC es and data input/output wrketed with the module of actual use or, if that le een the case of the module the connected to the module	le is capable of entually installed. Cline conducted t lines connected to (see Section ength is unknown, at ule and supporting odule during testing	⊠ - YES	□ - NO(*)	
Details: <example -="" application="" as="" filed="" in="" module="" photographs="" setup="" shown="" stand-alone="" test="" tested="" the="" this="" was="" with=""></example>					

	Modular Approval Requirement	Requirement Met	
6.	The modular transmitter must be labeled with its own FCC ID number, or use an electron display (see KDB Publication 784748). If using a permanently affixed label with its own FCC ID number, if the FCC ID is not visible when the module is installed inside another device, then the outside of the device into which the module is installed must also display a label referring to the enclosed module. This exterior label can use wording such as the following: "Contains Transmitter Module FCC ID: XYZMODEL1" or "Contains FCC ID: XYZMODEL1." Any similar wording that expresses the same meaning may be used. The Grantee may either provide such a label, an example of which must be included in the application for equipment authorization, or, must provide adequate instructions along with the module which explain this requirement. In the latter case, a copy of these instructions must be included in the application for equipment authorization. If the modular transmitter uses an electronic display of the FCC identification number, the information	⊠ - YES	□ - NO(*)
	must be readily accessible and visible on the modular transmitter or on the device in which it is installed. If the module is installed inside another device, then the outside of the device into which the module is installed must display a label referring to the enclosed module. This exterior label can use wording such as the following: "Contains FCC certified transmitter module(s)." Any similar wording that expresses the same meaning may be used. The user manual must include instructions on how to access the electronic display. A copy of these instructions must be included in the application for equipment authorization. 15.212(a)(1)(vi)		
	Details: <example a="" application="" application.="" as="" exhibit="" filed="" in="" installation="" is="" label="" labeling="" manual="" module="" on="" shown="" the="" there="" this="" with="" –=""></example>	lication. Hos	st specific
7.	The modular transmitter must comply with all specific rule or operating requirements applicable to the transmitter, including all the conditions provided in the integration instructions by the grantee. A copy of these instructions must be included in the application for equipment authorization. For example, there are very strict operational and timing requirements that must be met before a transmitter is authorized for operation under Section 15.231. For instance, data transmission is prohibited, except for operation under Section 15.231(e), in which case there are separate field strength level and timing requirements. Compliance with these requirements must be assured. 15.212(a)(1)(vii)	⊠ - YES	□ - NO(*)
	Details: <example 15c="" application.="" complies="" fcc="" filed="" installation="" instructions="" manual="" module="" oem="" part="" requirements.="" the="" this="" to="" with="" –=""></example>	l installer are	provided in
8.	The modular transmitter must comply with any applicable RF exposure requirements. For example, FCC Rules in Sections 2.1091, 2.1093 and specific Sections of Part 15, including 15.319(i), 15.407(f), 15.253(f) and 15.255(g), require that Unlicensed PCS, UNII and millimeter wave devices perform routine environmental evaluation for RF Exposure to demonstrate compliance. In addition, spread spectrum transmitters operating under Section 15.247 are required to address RF Exposure compliance in accordance with Section 15.247(b)(4). Modular transmitters approved under other Sections of Part 15, when necessary, may also need to address certain RF Exposure concerns, typically by providing specific installation and operating instructions for users, installers and other interested parties to ensure compliance. 15.212(a)(1)(viii)	⊠ - YES	□ - NO(*)
	Details: <example -="" application.="" as="" exclusion="" exposure="" in="" inform="" levels="" meets="" module="" portable="" rf="" shown="" the=""></example>	ation filed wit	th this

Limited Module Description – When Applicable

* If a module does NOT meet one or more of the above 8 requirements, the applicant may request Limited Modular Approval (LMA). This Limited Modular Approval (LMA) is applied with the understanding that the applicant will demonstrate and will retain control over the final installation of the device, such that compliance of the end product is always assured. The operating condition(s) for the LMA; the module is only approved for use when installed in devices produced by grantee. A description regarding how control of the end product, into which the module will be installed, will be maintained by the applicant/manufacturer, such that full compliance of the end product is always ensured should be provided here.

Details: <example - N/A>

Software Considerations – KDB 594280 / KDB 442812 (One of the following 2 items must be applied)			
Requirement		Requirement Met	
1.	For <u>non-Software Defined Radio</u> transmitter modules where software is used to ensure compliance of the device, technical description must be provided about how such control is implemented to ensure prevention of third-party modification; see KDB Publication 594280.	☐ - Provided in Separate Cover Letter	□ - N/A
	Details: <example adjusted="" application.="" be="" by="" can="" device="" filed="" firmware="" letter="" modified="" not="" of="" or="" the="" this="" with="" –=""></example>	e end user as described in a se	parate cover
2.	For <u>Software Defined Radio (SDR)</u> devices, transmitter module applications must provide a software security description; see KDB Publication 442812.	☐ - Provided in Separate Cover Letter	□ - N/A
	Details: <example -n="" a=""></example>		

Split Modular Requirements			
Requirement	Provided in Manual		
 For split modular transmitters, specific descriptions for secure communications between front-end and control sections, including authentication and restrictions on third-party modifications; also, instructions to third-party integrators on how control is maintained. 	☐ - Provided in Separate Cover Letter	□ - N/A	
Details: <example -="" a="" n=""></example>			

OEM Integration Manual Guidance – KDB 996369 D03 Section 2						
OEM Integration Manual Guidance – KDD 990309 D03 Section 2						
Clear and Specific Instructions Describing the Conditions, Limitations, and Procedures						
	for th	ird-parties to use and	or integrate the module into a host device.			
D						
Require	ment					
			⊠ - No,	. 11 1		
			If No, and LMA applies, the applicant ca make the following detailed info public.			
T 411 1 1	1.16		to be basic integration instructions for			
Is this module sale to third pa		☐ - YES	information below must still be included in the operational			
sale to tilitu pa	rues:			description. If the applicant wishes to keep this info confidential, this		
			will require a separate statement cover les			
			is not for sale to third parties and that in internal confidential doc			
	Item	required to be in the	e manual – See KDB 996369 D03, Section 2	cuments.		
As of May 1, 20			ng information to be in the installation manual.	Modular transmitter		
applicants should i	include informati	on in their instruction	ns for all these items indicating clearly when the	y are not applicable. For		
			cate "Not Applicable". Also if a module is limite			
			ser instructions may not need to be detailed and			
		DB 996369 D03, Sectio	n, but this should include a cover letter as cited	above.		
		ated to the transmitter.	DI 2.2			
			B 996369 D03, Section 2.3			
			able loss, reduction of power for point to point			
		onal installation info				
		B 996369 D03, Section				
			tee uses to verify the host meets the necessary			
	limiting condition		ary, state how control will be maintained such	☐ - All Items shown to		
		s ensured, such as Class		the left are provided in		
		6369 D03, Section 2.5		the Modular Integration Guide (or UM) for Full		
			a, connectors, isolation requirements, tests for	Modular Approval (MA)		
	design verification, and production test procedures for ensuring compliance. If					
		nethod used to keep con perational description.	nfidential must be identified and information			
		B 996369 D03, Section	126	□ - An LMA applies		
			at allow host manufacturers to use the module.	and is approved ONLY		
	Two types of inst	ructions are necessary:	first to the host manufacturer to define	for use by the grantee in		
			m body) and second additional text needed to be	their own products, and not intended for sale to		
		nd user in the host produ	uct manuals.	3 rd parties as provided in		
6. Antennas. KDI	· ·		on and all applicable professional installer	a separate cover letter.		
u.	instructions when	applicable. The antenn	na list shall also identify the antenna types	Therefore the		
			"omni-directional" is not considered a type)	information shown to the		
		on. KDB 996369 D03, S		left is found in the theory of operation.		
		_	to provide a physical or e-label stating	theory of operation.		
		D: " with their finished p				
8. Information on test modes and additional testing requirements. KDB 996369 D03, Section 2.9 a. Test modes that should be taken into consideration by host integrators including						
			and simultaneous configurations.			
b.	Provide informati	on on how to configure	e test modes for evaluation			
Additional test	ing, Part 15 Subpa	ırt B disclaimer. KDB 9	996369 D03, Section 2.10			
Sincerely,	\sim	D C				
Silicolory,	Ven	Sei Cui				
By:	v		Pengfei Cui			
J	(Signat	rure/Title ¹)	(Print name)	_		

¹ - Must be signed by applicant contact given for applicant on the FCC site, or by the authorized agent if an appropriate authorized agent letter has been provided. Letters should be placed on appropriate letterhead.