



## Shenzhen Huaxia Testing Technology Co., Ltd

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua District, Shenzhen, China

Telephone: +86-755-26648640  
Fax: +86-755-26648637  
Website: [www.cqa-cert.com](http://www.cqa-cert.com)

Report Template Version: V04  
Report Template Revision Date: 2018-07-06

# RF Exposure Evaluation Report

**Report No. :** CQASZ20210701105E-02  
**Applicant:** XIAMEN COMFORT SCIENCE & TECHNOLOGY GROUP CO., LTD.  
**Address of Applicant:** (5/F) NO.168, QIANPU ROAD, SIMING DISTRICT, XIAMEN, CHINA.  
**Equipment Under Test (EUT):**  
**Product:** Massage Chair  
**Model No.:** AM-3D Pro Tecno, EI-6501A, Osaki-Pro 3D Prestige, Pro-Prestige 3D, EI-6501C, Titan Pro-Prestige, Titan Pro-3D Prestige, 6501F, AmaMedic-Premium  
**Test Model No.** AM-3D Pro Tecno  
**Brand Name:** N/A  
**FCC ID:** YMX-EI6501A-01  
**Standards:** 47 CFR Part 1.1307  
47 CFR Part 1.1310  
KDB447498D01 General RF Exposure Guidance v06  
**Date of Receipt:** 2021-07-19  
**Date of Test:** 2021-7-19 to 2021-8-9  
**Date of Issue:** 2021-08-30  
**Test Result :** **PASS\***

\*In the configuration tested, the EUT complied with the standards specified above

**Tested By:** Lewis Zhou  
( Lewis Zhou )

**Reviewed By:** Jun Li  
( Jun Li )

**Approved By:** Jack ai  
( Jack ai )



## 1 Version

### Revision History Of Report

Report No.	Version	Description	Issue Date
CQASZ20210701105E-02	Rev.01	Initial report	2021-08-30

## 2 Contents

	Page
1 VERSION.....	2
2 CONTENTS.....	3
.....	3
3 GENERAL INFORMATION.....	4
3.1 CLIENT INFORMATION.....	4
3.2 GENERAL DESCRIPTION OF EUT.....	4
4 RF EXPOSURE EVALUATION.....	5
4.1 RF EXPOSURE COMPLIANCE REQUIREMENT.....	5
4.1.1 <i>Limits</i> .....	5
4.1.2 <i>Test Procedure</i> .....	5
4.1.3 <i>EUT RF Exposure Evaluation standalone operations</i> .....	6

### 3 General Information

#### 3.1 Client Information

Applicant:	XIAMEN COMFORT SCIENCE & TECHNOLOGY GROUP CO., LTD.
Address of Applicant:	(5/F) NO.168, QIANPU ROAD, SIMING DISTRICT, XIAMEN, CHINA.
Manufacturer:	XIAMEN HEALTHCARE ELECTRONIC CO., LTD.
Address of Manufacturer:	65-66#, 62-63#Building, Siming Zone, Tongan Industrial District, Xiamen City, Fujian Province, P.R. China
Factory:	XIAMEN HEALTHCARE ELECTRONIC CO., LTD.
Address of Factory:	65-66#, 62-63#Building, Siming Zone, Tongan Industrial District, Xiamen City, Fujian Province, P.R. China

#### 3.2 General Description of EUT

Product Name:	Massage Chair
All Model No.:	AM-3D Pro Tecno, EI-6501A, Osaki-Pro 3D Prestige, Pro-Prestige 3D, EI-6501C, Titan Pro-Prestige, Titan Pro-3D Prestige, 6501F, AmaMedic-Premium
Test Model No.:	AM-3D Pro Tecno
Trade Mark:	N/A
EUT Supports Radios application	2402-2480MHz
Hardware Version:	V1.1
Software Version:	V1.0
Power Supply:	Input voltage: 110V-120V~, 60Hz Rated current: 1.1A
Product Type:	<input type="checkbox"/> Mobile <input type="checkbox"/> Portable <input checked="" type="checkbox"/> Fix Location
Test Software of EUT:	FCCAssist 1.0.1.2
Antenna Type:	PCB antenna
Antenna Gain:	-1.39dBi

Note:

All model:AM-3D Pro Tecno, EI-6501A, Osaki-Pro 3D Prestige, Pro-Prestige 3D, EI-6501C,

Titan Pro-Prestige, Titan Pro-3D Prestige, 6501F, AmaMedic-Premium

Only the model AM-3D Pro Tecno was tested, since the electrical circuit design, layout, components used and internal wiring were identical for the above models, with difference being color of appearance and model name.

## 4 RF Exposure Evaluation

### 4.1 RF Exposure Compliance Requirement

#### 4.1.1 Limits

According to FCC Part1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in part1.1307(b)

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
<b>(A) Limits for Occupational/Controlled Exposures</b>				
0.3–3.0 .....	614	1.63	*(100)	6
3.0–30 .....	1842/f	4.89/f	*(900/f <sup>2</sup> )	6
30–300 .....	61.4	0.163	1.0	6
300–1500 .....	.....	.....	f/300	6
1500–100,000 .....	.....	.....	5	6
<b>(B) Limits for General Population/Uncontrolled Exposure</b>				
0.3–1.34 .....	614	1.63	*(100)	30
1.34–30 .....	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30–300 .....	27.5	0.073	0.2	30
300–1500 .....	.....	.....	f/1500	30
1500–100,000 .....	.....	.....	1.0	30

F= Frequency in MHz

Friis Formula

Friis transmission formula:  $P_d = (P_{out} * G) / (4 * \pi * R^2)$

Where

$P_d$  = power density in mW/cm<sup>2</sup>

$P_{out}$  = output power to antenna in mW

G = gain of antenna in linear scale

$\pi$  = 3.1416

R = distance between observation point and center of the radiator in cm

$P_d$  is the limit of MPE, 1 mW/cm<sup>2</sup>. If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

#### 4.1.2 Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

#### 4.1.3 EUT RF Exposure Evaluation standalone operations

##### 1) For BT Classic

Antenna Gain: -1.39dBi

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 0.73 in linear scale.

Output Power Into Antenna & RF Exposure Evaluation Distance:

##### Measurement Data

GFSK mode				
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(2402MHz)	-0.700	-1±1	0	1
Middle(2441MHz)	0.390	-1.5±1	0.5	1.122
Highest(2480MHz)	1.920	1±1	2	1.585
π/4DQPSK mode				
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(2402MHz)	0.000	-1±1	0	1
Middle(2441MHz)	1.010	0.5±1	1.5	1.413
Highest(2480MHz)	2.460	1.5±1	2.5	1.778

The worst case:

Maximum tune-up Power (mW)	Antenna Gain (dBi)	Power Density at R = 20 cm (mW/cm <sup>2</sup> )	Limit	Result
1.778	-1.39	0.00025	1.0	PASS

Note: 1) Refer to report No. CQASZ20210701087E for EUT test Max Conducted Peak Output Power value.

2)  $P_d = (P_{out} * G) / (4 * \pi * R^2) = (1.778 * 0.73) / (4 * 3.1416 * 20^2) = 0.00025$