

APPLICATION CERTIFICATION FCC Part 15C
On Behalf of
XIAMEN COMFORT SCIENCE & TECHNOLOGY GROUP CO., LTD

Massage Chair
Model No.: HMC-600, OGI-3220A

FCC ID: YMX-HMC600

Prepared for : XIAMEN COMFORT SCIENCE & TECHNOLOGY GROUP CO., LTD

Address : (5/F)NO.168, QIANPU ROAD, SIMING DISTRICT, XIAMEN, FUJIAN, CHINA

Prepared by : Shenzhen Accurate Technology Co., Ltd.

Address : 1/F., Building A, Changyuan New Material Port, Science & Industry Park, Nanshan District, Shenzhen, Guangdong, P.R. China

Tel: (0755) 26503290

Fax: (0755) 26503396

Report No. : ATE20190505

Date of Test : April 15-18, 2019

Date of Report : April 22, 2019

TABLE OF CONTENTS

| Description | Page |
|---|-----------|
| Test Report Certification | |
| TABLE OF CONTENTS | 2 |
| 1. GENERAL INFORMATION | 5 |
| 1.1. Description of Device (EUT)..... | 5 |
| 1.2. Accessory and Auxiliary Equipment | 5 |
| 1.3. Description of Test Facility | 6 |
| 1.4. Measurement Uncertainty | 6 |
| 2. MEASURING DEVICE AND TEST EQUIPMENT | 7 |
| 3. OPERATION OF EUT DURING TESTING | 8 |
| 3.1. Operating Mode | 8 |
| 3.2. Configuration and peripherals | 8 |
| 4. TEST PROCEDURES AND RESULTS | 9 |
| 5. 20DB BANDWIDTH TEST | 10 |
| 5.1. Block Diagram of Test Setup..... | 10 |
| 5.2. The Requirement For Section 15.247(a)(1)..... | 10 |
| 5.3. EUT Configuration on Measurement | 10 |
| 5.4. Operating Condition of EUT | 10 |
| 5.5. Test Procedure | 10 |
| 5.6. Test Result | 11 |
| 6. CARRIER FREQUENCY SEPARATION TEST | 16 |
| 6.1. Block Diagram of Test Setup..... | 16 |
| 6.2. The Requirement For Section 15.247(a)(1)..... | 16 |
| 6.3. EUT Configuration on Measurement | 16 |
| 6.4. Operating Condition of EUT | 16 |
| 6.5. Test Procedure | 17 |
| 6.6. Test Result | 17 |
| 7. NUMBER OF HOPPING FREQUENCY TEST | 23 |
| 7.1. Block Diagram of Test Setup..... | 23 |
| 7.2. The Requirement For Section 15.247(a)(1)(iii)..... | 23 |
| 7.3. EUT Configuration on Measurement | 23 |
| 7.4. Operating Condition of EUT | 23 |
| 7.5. Test Procedure | 23 |
| 7.6. Test Result | 24 |
| 8. DWELL TIME TEST | 26 |
| 8.1. Block Diagram of Test Setup..... | 26 |
| 8.2. The Requirement For Section 15.247(a)(1)(iii)..... | 26 |
| 8.3. EUT Configuration on Measurement | 26 |
| 8.4. Operating Condition of EUT | 26 |
| 8.5. Test Procedure | 26 |
| 8.6. Test Result | 27 |
| 9. MAXIMUM PEAK OUTPUT POWER TEST | 33 |
| 9.1. Block Diagram of Test Setup..... | 33 |

| | | |
|------------|--|-----------|
| 9.2. | The Requirement For Section 15.247(b)(1)..... | 33 |
| 9.3. | EUT Configuration on Measurement | 33 |
| 9.4. | Operating Condition of EUT | 33 |
| 9.5. | Test Procedure | 33 |
| 9.6. | Test Result | 34 |
| 10. | RADIATED EMISSION TEST | 40 |
| 10.1. | Block Diagram of Test Setup..... | 40 |
| 10.2. | The Limit For Section 15.247(d) | 41 |
| 10.3. | Restricted bands of operation | 43 |
| 10.4. | Configuration of EUT on Measurement | 43 |
| 10.5. | Operating Condition of EUT | 44 |
| 10.6. | Test Procedure | 44 |
| 10.7. | Data Sample..... | 45 |
| 10.8. | The Field Strength of Radiation Emission Measurement Results | 45 |
| 11. | BAND EDGE COMPLIANCE TEST | 58 |
| 11.1. | Block Diagram of Test Setup..... | 58 |
| 11.2. | The Requirement For Section 15.247(d) | 58 |
| 11.3. | EUT Configuration on Measurement | 58 |
| 11.4. | Operating Condition of EUT | 58 |
| 11.5. | Test Procedure | 59 |
| 11.6. | Test Result | 59 |
| 12. | AC POWER LINE CONDUCTED EMISSION FOR FCC PART 15 SECTION 15.207(A) .. | 70 |
| 12.1. | Block Diagram of Test Setup..... | 70 |
| 12.2. | Power Line Conducted Emission Measurement Limits..... | 71 |
| 12.3. | Configuration of EUT on Measurement | 71 |
| 12.4. | Operating Condition of EUT | 71 |
| 12.5. | Test Procedure | 71 |
| 12.6. | Data Sample..... | 72 |
| 12.7. | Power Line Conducted Emission Measurement Results | 72 |
| 13. | ANTENNA REQUIREMENT..... | 75 |
| 13.1. | The Requirement | 75 |
| 13.2. | Antenna Construction | 75 |

Test Report Certification

Applicant : XIAMEN COMFORT SCIENCE & TECHNOLOGY GROUP CO., LTD
Manufacturer : XIAMEN OGAWA INTELLIGENT HEALTH EQUIPMENT CO., LTD
EUT Description : Massage Chair
Model No. : HMC-600, OGI-3220A
Brand Name : n.a.

Measurement Procedure Used:

FCC Rules and Regulations Part 15 Subpart C Section 15.247: 2018 ANSI C63.10: 2013

The device described above is tested by Shenzhen Accurate Technology Co., Ltd. to determine the maximum emission levels emanating from the device. The maximum emission levels are compared to the FCC Part 15 Subpart C Section 15.247 limits. The measurement results are contained in this test report and Shenzhen Accurate Technology Co., Ltd. is assumed full responsibility for the accuracy and completeness of these measurements. Also, this report shows that the Equipment Under Test (EUT) is to be technically compliant with the FCC requirements.

This report applies to above tested sample only. This report shall not be reproduced in part without written approval of Shenzhen Accurate Technology Co., Ltd.

Date of Test : April 15-18, 2019
Date of Report : April 22, 2019

Prepared by : _____
(Bob Wang, Engineer)

Approved & Authorized Signer : _____
(Sean Liu, Manager)



1. GENERAL INFORMATION

1.1. Description of Device (EUT)

| | | |
|-------------------------|---|---|
| Model Number | : | HMC-600, OGI-3220A (Note: These samples are same except their appearance color is different. So we prepare HMC-600 for test only.) |
| Bluetooth version | : | V 5.0 |
| Frequency Range | : | 2402MHz-2480MHz |
| Number of Channels | : | 79 |
| Antenna Gain(Max) | : | 0dBi |
| Antenna type | : | Plate loaded ceramic antenna |
| Adapter Input Voltage | : | AC 110-120V; 60Hz |
| Modulation mode | : | GFSK, $\pi/4$ DQPSK, 8DPSK |
| Applicant | : | XIAMEN COMFORT SCIENCE & TECHNOLOGY GROUP CO., LTD |
| Address | : | (5/F)NO.168, QIANPU ROAD, SIMING DISTRICT, XIAMEN, FUJIAN, CHINA |
| Manufacturer | : | XIAMEN OGAWA INTELLIGENT HEALTH EQUIPMENT CO., LTD |
| Address | : | THREE FLOOR NO 38-40 TIANYANG ROAD JIMEI ZONE XIAMEN T:3521880 |
| Date of sample received | : | April 10, 2019 |
| Date of Test | : | April 15-18, 2019 |
| Sample Number | : | 1900355 |

1.2. Accessory and Auxiliary Equipment

N/A

1.3. Description of Test Facility

- EMC Lab : Recognition of accreditation by Federal Communications Commission (FCC)
The Designation Number is CN1189
The Registration Number is 708358
- Listed by Innovation, Science and Economic Development Canada (ISED)
The Registration Number is 5077A-2
- Accredited by China National Accreditation Service for Conformity Assessment (CNAS)
The Registration Number is CNAS L3193
- Accredited by American Association for Laboratory Accreditation (A2LA)
The Certificate Number is 4297.01
- Name of Firm : Shenzhen Accurate Technology Co., Ltd.
- Site Location : 1/F., Building A, Changyuan New Material Port, Science & Industry Park, Nanshan District, Shenzhen, Guangdong, P.R. China

1.4. Measurement Uncertainty

- Conducted Emission Expanded Uncertainty = 2.23dB, k=2
- Radiated emission expanded uncertainty (9kHz-30MHz) = 3.08dB, k=2
- Radiated emission expanded uncertainty (30MHz-1000MHz) = 4.42dB, k=2
- Radiated emission expanded uncertainty (Above 1GHz) = 4.06dB, k=2

2. MEASURING DEVICE AND TEST EQUIPMENT

Table 1: List of Test and Measurement Equipment

| Kind of equipment | Manufacturer | Type | S/N | Calibrated dates | Calibrated until |
|-----------------------------|------------------------|------------------------------------|------------|------------------|------------------|
| EMI Test Receiver | Rohde&Schwarz | ESCS30 | 100307 | Jan. 05, 2019 | 1 Year |
| EMI Test Receiver | Rohde&Schwarz | ESPI3 | 101526/003 | Jan. 05, 2019 | 1 Year |
| Spectrum Analyzer | Agilent | E7405A | MY45115511 | Jan. 05, 2019 | 1 Year |
| Pre-Amplifier | Rohde&Schwarz | CBLU1183540-01 | 3791 | Jan. 05, 2019 | 1 Year |
| Loop Antenna | Schwarzbeck | FMZB1516 | 1516131 | Jan. 05, 2019 | 1 Year |
| Bilog Antenna | Schwarzbeck | VULB9163 | 9163-323 | Jan. 05, 2019 | 1 Year |
| Horn Antenna | Schwarzbeck | BBHA9120D | 9120D-655 | Jan. 05, 2019 | 1 Year |
| Horn Antenna | Schwarzbeck | BBHA9170 | 9170-359 | Jan. 05, 2019 | 1 Year |
| LISN | Rohde&Schwarz | ESH3-Z5 | 100305 | Jan. 05, 2019 | 1 Year |
| LISN | Schwarzbeck | NSLK8126 | 8126431 | Jan. 05, 2019 | 1 Year |
| Highpass Filter | Wainwright Instruments | WHKX3.6/18G-10SS | N/A | Jan. 05, 2019 | 1 Year |
| Band Reject Filter | Wainwright Instruments | WRCG2400/2485-2375/2510-60/11SS | N/A | Jan. 05, 2019 | 1 Year |
| RF COAXIAL CABLE | SUHNER | N-5m(Frequency range:9KHz-26.5GHz) | NO.3 | Jan. 05, 2019 | 1 Year |
| RF COAXIAL CABLE | SUHNER | N-5m(Frequency range:9KHz-26.5GHz) | NO.4 | Jan. 05, 2019 | 1 Year |
| RF COAXIAL CABLE | SUHNER | N-1m(Frequency range:9KHz-26.5GHz) | NO.5 | Jan. 05, 2019 | 1 Year |
| RF COAXIAL CABLE | SUHNER | N-1m(Frequency range:9KHz-26.5GHz) | NO.6 | Jan. 05, 2019 | 1 Year |
| Temporary antenna connector | NTGS | 14AE | N/A | March 20, 2019 | N/A |


Note: The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.

3. OPERATION OF EUT DURING TESTING

3.1. Operating Mode

The mode is used: Transmitting mode
Low Channel: 2402MHz
Middle Channel: 2441MHz
High Channel: 2480MHz
Hopping

3.2. Configuration and peripherals




4. TEST PROCEDURES AND RESULTS

| FCC Rules | Description of Test | Result |
|-------------------------------------|-----------------------------------|---------------|
| Section 15.207 | Conducted Emission Test | Compliant |
| Section 15.247(a)(1) | 20dB Bandwidth Test | Compliant |
| Section 15.247(a)(1) | Carrier Frequency Separation Test | Compliant |
| Section 15.247(a)(1)(iii) | Number Of Hopping Frequency Test | Compliant |
| Section 15.247(a)(1)(iii) | Dwell Time Test | Compliant |
| Section 15.247(b)(1) | Maximum Peak Output Power Test | Compliant |
| Section 15.247(d) Section 15.209 | Radiated Emission Test | Compliant |
| Section 15.247(d) | Band Edge Compliance Test | Compliant |
| Section 15.203 | Antenna Requirement | Compliant |

5. 20DB BANDWIDTH TEST

5.1. Block Diagram of Test Setup



(EUT: Massage Chair)

5.2. The Requirement For Section 15.247(a)(1)

Section 15.247(a)(1): Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.

5.3. EUT Configuration on Measurement

The equipment are installed on the emission measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

5.4. Operating Condition of EUT

5.4.1. Setup the EUT and simulator as shown as Section 5.1.

5.4.2. Turn on the power of all equipment.

5.4.3. Let the EUT work in TX (Hopping off) modes measure it. The transmit frequency are 2402-2480MHz. We select 2402MHz, 2441MHz, and 2480MHz TX frequency to transmit.

5.5. Test Procedure

5.5.1. The transmitter output was connected to the spectrum analyzer through a low loss cable.

5.5.2. Set RBW of spectrum analyzer to 100 kHz and VBW to 300 kHz.

5.5.3. The 20dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 20dB.


5.6. Test Result

Test Lab: Shielding room

| Channel | Frequency (MHz) | GFSK 20dB Bandwidth (MHz) | Π/4-DQPSK 20dB Bandwidth (MHz) | 8DPSK 20dB Bandwidth (MHz) | Result |
|---------|-----------------|---------------------------|--------------------------------|----------------------------|--------|
| Low | 2402 | 1.128 | 1.422 | 1.422 | Pass |
| Middle | 2441 | 1.128 | 1.410 | 1.416 | Pass |
| High | 2480 | 1.128 | 1.404 | 1.410 | Pass |


The spectrum analyzer plots are attached as below.

GFSK Mode




Comment A:
Date: 17.APR.2019 19:49:24

Middle channel



Comment A:
Date: 17.APR.2019 19:50:12


High channel



Comment A:
Date: 17.APR.2019 19:50:55


Π/4-DQPSK Mode

Low channel




Comment A:
Date: 17.APR.2019 19:55:20

Middle channel



Comment A:
Date: 17.APR.2019 19:53:19


High channel



Comment A:
 Date: 17.APR.2019 19:52:13


8DPSK Mode

Low channel




Comment A:
 Date: 17.APR.2019 19:57:53

Middle channel



Comment A:
 Date: 17.APR.2019 19:59:02


High channel



Comment A:
 Date: 17.APR.2019 19:59:51

6. CARRIER FREQUENCY SEPARATION TEST

6.1. Block Diagram of Test Setup



(EUT: Massage Chair)

6.2. The Requirement For Section 15.247(a)(1)

Section 15.247(a)(1): Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudorandomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

6.3. EUT Configuration on Measurement

The equipment are installed on the emission measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

6.4. Operating Condition of EUT

6.4.1. Setup the EUT and simulator as shown as Section 6.1.

6.4.2. Turn on the power of all equipment.

6.4.3. Let the EUT work in TX (Hopping on) modes measure it. The transmit frequency are 2402-2480MHz. We select 2402MHz, 2441MHz, and 2480MHz TX frequency to transmit.

6.5. Test Procedure

6.5.1. The transmitter output was connected to the spectrum analyzer through a low loss cable.

6.5.2. Set RBW of spectrum analyzer to 30 kHz and VBW to 100 kHz. Adjust Span to 2MHz.

6.5.3. Set the adjacent channel of the EUT Maxhold another trace.

6.5.4. Measurement the channel separation

6.6. Test Result

Test Lab: Shielding room

GFSK

| Channel | Frequency (MHz) | Channel Separation(MHz) | Limit (MHz) | Result |
|---------|-----------------|-------------------------|-----------------------------|--------|
| Low | 2402 | 1.002 | 25KHz or 2/3*20dB bandwidth | PASS |
| | 2403 | | | |
| Middle | 2440 | 1.002 | 25KHz or 2/3*20dB bandwidth | PASS |
| | 2441 | | | |
| High | 2479 | 1.002 | 25KHz or 2/3*20dB bandwidth | PASS |
| | 2480 | | | |

Π/4-DQPSK


| Channel | Frequency (MHz) | Channel Separation(MHz) | Limit (MHz) | Result |
|---------|-----------------|-------------------------|-----------------------------|--------|
| Low | 2402 | 1.008 | 25KHz or 2/3*20dB bandwidth | PASS |
| | 2403 | | | |
| Middle | 2440 | 1.002 | 25KHz or 2/3*20dB bandwidth | PASS |
| | 2441 | | | |
| High | 2479 | 1.002 | 25KHz or 2/3*20dB bandwidth | PASS |
| | 2480 | | | |

8DPSK

| Channel | Frequency (MHz) | Channel Separation(MHz) | Limit (MHz) | Result |
|---------|-----------------|-------------------------|-----------------------------|--------|
| Low | 2402 | 1.002 | 25KHz or 2/3*20dB bandwidth | PASS |
| | 2403 | | | |
| Middle | 2440 | 1.002 | 25KHz or 2/3*20dB bandwidth | PASS |
| | 2441 | | | |
| High | 2479 | 1.002 | 25KHz or 2/3*20dB bandwidth | PASS |
| | 2480 | | | |


GFSK Mode

Low channel




Comment A:
Date: 17.APR.2019 21:48:03

Middle channel



Comment A:
Date: 17.APR.2019 21:50:44


High channel



Comment A:
Date: 17.APR.2019 21:52:11


Π/4-DQPSK Mode

Low channel




Comment A:
Date: 17.APR.2019 22:04:49

Middle channel



Comment A:
Date: 17.APR.2019 22:02:28


High channel



Comment A:
Date: 17.APR.2019 21:53:08


8DPSK Mode

Low channel




Comment A:
Date: 17.APR.2019 22:07:44

Middle channel



Comment A:
Date: 17.APR.2019 22:09:08


High channel



Comment A:
Date: 17.APR.2019 22:10:53

7. NUMBER OF HOPPING FREQUENCY TEST

7.1. Block Diagram of Test Setup



(EUT: Massage Chair)

7.2. The Requirement For Section 15.247(a)(1)(iii)

Section 15.247(a)(1)(iii): Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.

7.3. EUT Configuration on Measurement

The equipment are installed on the emission measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

7.4. Operating Condition of EUT

7.4.1. Setup the EUT and simulator as shown as Section 7.1.

7.4.2. Turn on the power of all equipment.

7.4.3. Let the EUT work in TX (Hopping on) modes measure it.

7.5. Test Procedure

7.5.1. The transmitter output was connected to the spectrum analyzer through a low loss cable.

7.5.2. Set the spectrum analyzer as RBW=100 kHz, VBW=300 kHz.


7.5.3. Max hold, view and count how many channel in the band.

7.6. Test Result

Test Lab: Shielding room


| Total number of hopping channel | Measurement result(CH) | Limit(CH) |
|---------------------------------|------------------------|-----------|
| | 79 | ≥ 15 |

Number of hopping channels(GFSK)




Comment A:
Date: 17.APR.2019 22:20:16

Number of hopping channels($\Pi/4$ -DQPSK)



Comment A:
Date: 17.APR.2019 22:17:37


Number of hopping channels(8DPSK)



Comment A:
Date: 17.APR.2019 22:15:10

8. DWELL TIME TEST

8.1. Block Diagram of Test Setup



(EUT: Massage Chair)

8.2. The Requirement For Section 15.247(a)(1)(iii)

Section 15.247(a)(1)(iii): Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

8.3. EUT Configuration on Measurement

The equipment are installed on the emission measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

8.4. Operating Condition of EUT

8.4.1. Setup the EUT and simulator as shown as Section 8.1.

8.4.2. Turn on the power of all equipment.

8.4.3. Let the EUT work in TX (Hopping on) modes measure it. The transmit frequency are 2402-2480MHz. We select 2402MHz, 2441MHz, and 2480MHz TX frequency to transmit.

8.5. Test Procedure

8.5.1. The transmitter output was connected to the spectrum analyzer through a low loss cable.

8.5.2. Set center frequency of spectrum analyzer = operating frequency.

8.5.3. Set the spectrum analyzer as RBW=1MHz, VBW=3MHz, Span=0Hz, Adjust Sweep=5ms, 10ms, 15ms. Get the pulse time.

8.5.4. Repeat above procedures until all frequency measured were complete.

8.6. Test Result

Test Lab: Shielding room

GFSK Mode (Worst case)

| Mode | Channel Frequency (MHz) | Pulse Time (ms) | Dwell Time (ms) | Limit (ms) |
|--|-------------------------|-----------------|-----------------|------------|
| DH1 | 2441 | 0.41 | 131.2 | 400 |
| A period transmit time = $0.4 \times 79 = 31.6$ Dwell time = pulse time $\times (1600/(2*79)) \times 31.6$ | | | | |
| DH3 | 2441 | 1.71 | 273.6 | 400 |
| A period transmit time = $0.4 \times 79 = 31.6$ Dwell time = pulse time $\times (1600/(4*79)) \times 31.6$ | | | | |
| DH5 | 2441 | 2.97 | 316.8 | 400 |
| A period transmit time = $0.4 \times 79 = 31.6$ Dwell time = pulse time $\times (1600/(6*79)) \times 31.6$ | | | | |

$\Pi/4$ -DQPSK (Worst case)

| Mode | Channel Frequency (MHz) | Pulse Time (ms) | Dwell Time (ms) | Limit (ms) |
|--|-------------------------|-----------------|-----------------|------------|
| DH1 | 2441 | 0.40 | 128.0 | 400 |
| A period transmit time = $0.4 \times 79 = 31.6$ Dwell time = pulse time $\times (1600/(2*79)) \times 31.6$ | | | | |
| DH3 | 2441 | 1.68 | 268.8 | 400 |
| A period transmit time = $0.4 \times 79 = 31.6$ Dwell time = pulse time $\times (1600/(4*79)) \times 31.6$ | | | | |
| DH5 | 2441 | 2.97 | 316.8 | 400 |
| A period transmit time = $0.4 \times 79 = 31.6$ Dwell time = pulse time $\times (1600/(6*79)) \times 31.6$ | | | | |

8DPSK (Worst case)


| Mode | Channel Frequency (MHz) | Pulse Time (ms) | Dwell Time (ms) | Limit (ms) |
|--|-------------------------|-----------------|-----------------|------------|
| DH1 | 2441 | 0.41 | 131.2 | 400 |
| A period transmit time = $0.4 \times 79 = 31.6$ Dwell time = pulse time $\times (1600/(2*79)) \times 31.6$ | | | | |
| DH3 | 2441 | 1.71 | 273.6 | 400 |
| A period transmit time = $0.4 \times 79 = 31.6$ Dwell time = pulse time $\times (1600/(4*79)) \times 31.6$ | | | | |
| DH5 | 2441 | 3.00 | 320.0 | 400 |
| A period transmit time = $0.4 \times 79 = 31.6$ Dwell time = pulse time $\times (1600/(6*79)) \times 31.6$ | | | | |

Note: We tested GFSK mode and $\Pi/4$ -DQPSK & 8DPSK mode the low, middle and high channel and recorded the worst case data for all test mode.

The spectrum analyzer plots are attached as below.


GFSK Mode

DH1 Middle channel




Comment A:
Date: 17.APR.2019 21:21:53

DH3 Middle channel



Comment A:
Date: 17.APR.2019 21:23:59


DH5 Middle channel



Comment A:
Date: 17.APR.2019 21:25:56


Π/4-DQPSK

2DH1 Middle channel




Comment A:
Date: 17.APR.2019 21:33:14

2DH3 Middle channel



Comment A:
Date: 17.APR.2019 21:34:18


2DH5 Middle channel



Comment A:
Date: 17.APR.2019 21:35:32


8DPSK

3DH1 Middle channel




Comment A:
Date: 17.APR.2019 21:36:46

3DH3 Middle channel



Comment A:
Date: 17.APR.2019 21:38:23


3DH5 Middle channel



Comment A:
Date: 17.APR.2019 21:39:16

9. MAXIMUM PEAK OUTPUT POWER TEST

9.1. Block Diagram of Test Setup



(EUT: Massage Chair)

9.2. The Requirement For Section 15.247(b)(1)

Section 15.247(b)(1): For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.

9.3. EUT Configuration on Measurement

The equipment are installed on the emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

9.4. Operating Condition of EUT

9.4.1. Setup the EUT and simulator as shown as Section 9.1.

9.4.2. Turn on the power of all equipment.

9.4.3. Let the EUT work in TX (Hopping off) modes measure it. The transmit frequency are 2402-2480MHz. We select 2402MHz, 2441MHz, and 2480MHz TX frequency to transmit.

9.5. Test Procedure

9.5.1. The transmitter output was connected to the spectrum analyzer through a low loss cable.

9.5.2. Set RBW of spectrum analyzer to 3MHz and VBW to 10MHz.

9.5.3. Measurement the maximum peak output power.

9.6. Test Result

Test Lab: Shielding room

GFSK Mode

| Channel | Frequency (MHz) | Peak Output Power (dBm/W) | Limits dBm / W |
|---------|-----------------|---------------------------|----------------|
| Low | 2402 | -1.25/0.0007 | 21 / 0.125 |
| Middle | 2441 | -1.19/0.0008 | 21 / 0.125 |
| High | 2480 | -1.25/0.0007 | 21 / 0.125 |

Π/4-DQPSK Mode

| Channel | Frequency (MHz) | Peak Output Power (dBm/W) | Limits dBm / W |
|---------|-----------------|---------------------------|----------------|
| Low | 2402 | 0.82/0.0012 | 21 / 0.125 |
| Middle | 2441 | 0.85/0.0012 | 21 / 0.125 |
| High | 2480 | 0.85/0.0012 | 21 / 0.125 |


8DPSK

| Channel | Frequency (MHz) | Peak Output Power (dBm/W) | Limits dBm / W |
|---------|-----------------|---------------------------|----------------|
| Low | 2402 | 1.25/0.0013 | 21 / 0.125 |
| Middle | 2441 | 1.37/0.0014 | 21 / 0.125 |
| High | 2480 | 1.28/0.0013 | 21 / 0.125 |

The spectrum analyzer plots are attached as below.


GFSK Mode

Low channel




Comment A:
Date: 17.APR.2019 19:36:52

Middle channel



Comment A:
Date: 17.APR.2019 19:39:08


High channel



Comment A:
Date: 17.APR.2019 19:39:53


Π/4-DQPSK Mode

Low channel




Comment A:
Date: 17.APR.2019 19:42:17

Middle channel



Comment A:
Date: 17.APR.2019 19:41:46


High channel



Comment A:
Date: 17.APR.2019 19:40:53


8DPSK Mode

Low channel




Comment A:
Date: 17.APR.2019 19:45:04

Middle channel



Comment A:
Date: 17.APR.2019 19:44:28

High channel




Comment A:
Date: 17.APR.2019 19:43:52

10. RADIATED EMISSION TEST


10.1. Block Diagram of Test Setup

10.1.1. Block diagram of connection between the EUT and peripherals




10.1.2. Setup: Transmitting mode Semi-Anechoic Chamber Test Setup Diagram


(A) Radiated Emission Test Set-Up, Frequency below 30MHz



(B) Radiated Emission Test Set-Up, Frequency 30MHz-1GHz



(C) Radiated Emission Test Set-Up, Frequency above 1GHz



10.2. The Limit For Section 15.247(d)

Section 15.247(d): In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the

general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).

10.3.Restricted bands of operation

10.3.1.FCC Part 15.205 Restricted bands of operation

(a) Except as shown in paragraph (d) of this section, Only spurious emissions are permitted in any of the frequency bands listed below:

| MHz | MHz | MHz | GHz |
|--------------------------|---------------------|---------------|------------------|
| 0.090-0.110 | 16.42-16.423 | 399.9-410 | 4.5-5.15 |
| ¹ 0.495-0.505 | 16.69475-16.69525 | 608-614 | 5.35-5.46 |
| 2.1735-2.1905 | 16.80425-16.80475 | 960-1240 | 7.25-7.75 |
| 4.125-4.128 | 25.5-25.67 | 1300-1427 | 8.025-8.5 |
| 4.17725-4.17775 | 37.5-38.25 | 1435-1626.5 | 9.0-9.2 |
| 4.20725-4.20775 | 73-74.6 | 1645.5-1646.5 | 9.3-9.5 |
| 6.215-6.218 | 74.8-75.2 | 1660-1710 | 10.6-12.7 |
| 6.26775-6.26825 | 108-121.94 | 1718.8-1722.2 | 13.25-13.4 |
| 6.31175-6.31225 | 123-138 | 2200-2300 | 14.47-14.5 |
| 8.291-8.294 | 149.9-150.05 | 2310-2390 | 15.35-16.2 |
| 8.362-8.366 | 156.52475-156.52525 | 2483.5-2500 | 17.7-21.4 |
| 8.37625-8.38675 | 156.7-156.9 | 2690-2900 | 22.01-23.12 |
| 8.41425-8.41475 | 162.0125-167.17 | 3260-3267 | 23.6-24.0 |
| 12.29-12.293 | 167.72-173.2 | 3332-3339 | 31.2-31.8 |
| 12.51975-12.52025 | 240-285 | 3345.8-3358 | 36.43-36.5 |
| 12.57675-12.57725 | 322-335.4 | 3600-4400 | (²) |
| 13.36-13.41 | | | |

¹Until February 1, 1999, this restricted band shall be 0.490-0.510

²Above 38.6

(b) Except as provided in paragraphs (d) and (e), the field strength of emission appearing within these frequency bands shall not exceed the limits shown in Section 15.209. At frequencies equal to or less than 1000MHz, Compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.

10.4.Configuration of EUT on Measurement

The equipment is installed on Radiated Emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

10.5. Operating Condition of EUT

10.5.1. Setup the EUT and simulator as shown as Section 10.1.

10.5.2. Turn on the power of all equipment.

10.5.3. Let the EUT work in TX modes measure it. The transmit frequency are 2402-2480MHz. We select 2402MHz, 2441MHz, and 2480MHz TX frequency to transmit.

10.6. Test Procedure

The EUT and its simulators are placed on a turntable, which is 0.8 meter high above ground (Below 1GHz). The EUT and its simulators are placed on a turntable, which is 1.5 meter high above ground (Above 1GHz). The turntable can rotate 360 degrees to determine the position of the maximum emission level. EUT is set 3.0 meters away from the receiving antenna, which is mounted on an antenna tower. The antenna can be moved up and down between 1.0 meter and 4 meters to find out the maximum emission level. Broadband antenna (calibrated bi-log antenna) is used as receiving antenna. Both horizontal and vertical polarizations of the antenna are set on measurement. In order to find the maximum emission levels, all of the EUT location must be manipulated according to ANSI C63.10:2013 on radiated emission measurement. This EUT was tested in 3 orthogonal positions and the worst case position data was reported.

During the radiated emission test, the spectrum analyzer was set with the following configurations:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for peak measurement with peak detector at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average measurement with peak detection at frequency above 1GHz.
4. All modes of operation were investigated and the worst-case emissions are reported.

10.7.Data Sample

| Frequency (MHz) | Reading (dB μ v) | Factor (dB/m) | Result (dB μ v/m) | Limit (dB μ v/m) | Margin (dB) | Remark |
|-----------------|----------------------|---------------|-----------------------|----------------------|-------------|--------|
| X.XX | 48.69 | -13.35 | 35.34 | 46 | -10.66 | QP |

Frequency(MHz) = Emission frequency in MHz

Reading(dB μ v) = Uncorrected Analyzer/Receiver reading

Factor (dB/m) = Antenna factor + Cable Loss – Amplifier gain

Result(dB μ v/m) = Reading(dB μ v) + Factor(dB/m)

Limit (dB μ v/m) = Limit stated in standard

Margin (dB) = Result(dB μ v/m) - Limit (dB μ v/m)

QP = Quasi-peak Reading

Calculation Formula:

Margin(dB) = Result (dB μ V/m)–Limit(dB μ V/m)

Result(dB μ V/m)= Reading(dB μ V)+ Factor(dB/m)

The “Margin” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -7dB means the emission is 7dB below the limit.

10.8.The Field Strength of Radiation Emission Measurement Results

PASS.

Test Lab: 3m Anechoic chamber

Note: 1.We tested GFSK mode, $\Pi/4$ -DQPSK & 8DPSK Mode and recorded the worst case data (GFSK mode) for all test mode.

2. Testing is carried out with frequency rang 9kHz to the tenth harmonics, which above 3th Harmonics are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured. The measurements greater than 20dB below the limit from 9kHz to 30MHz and 18 to 26.5GHz.

The spectrum analyzer plots are attached as below.

Below 1GHz




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

| | |
|--|----------------------------|
| Job No.: jp2019 #102 | Polarization: Vertical |
| Standard: FCC Class B 3M Radiated | Power Source: AC 120V/60Hz |
| Test item: Radiation Test | Date: 19/04/17/ |
| Temp.(C)/Hum.(%) 25 C / 55 % | Time: 10/34/52 |
| EUT: Massage Chair | Engineer Signature: Ben |
| Mode: TX 2402MHz | Distance: 3m |
| Model: HMC-600 | |
| Manufacturer: XIAMEN OGAWA INTELLIGENT HEALTH EQUIPMENT CO., LTD | |

Note: Report NO.:ATE20190505



| No. | Freq. (MHz) | Reading (dBuV/m) | Factor (dB) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector | Height (cm) | Degree (deg.) | Remark |
|-----|-------------|------------------|-------------|-----------------|----------------|-------------|----------|-------------|---------------|--------|
| 1 | 30.1053 | 56.63 | -20.23 | 36.40 | 40.00 | -3.60 | QP | 100 | 236 | |
| 2 | 43.3853 | 58.66 | -24.16 | 34.50 | 40.00 | -5.50 | QP | 100 | 185 | |
| 3 | 66.8395 | 57.16 | -27.36 | 29.80 | 40.00 | -10.20 | QP | 100 | 96 | |
| 4 | 128.9385 | 60.29 | -27.69 | 32.60 | 43.50 | -10.90 | QP | 100 | 63 | |
| 5 | 174.4265 | 65.06 | -26.46 | 38.60 | 43.50 | -4.90 | QP | 100 | 175 | |
| 6 | 216.8803 | 61.86 | -24.04 | 37.82 | 46.00 | -8.18 | QP | 100 | 196 | |




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

| | |
|--|----------------------------|
| Job No.: jp2019 #103 | Polarization: Horizontal |
| Standard: FCC Class B 3M Radiated | Power Source: AC 120V/60Hz |
| Test item: Radiation Test | Date: 19/04/17/ |
| Temp.(C)/Hum.(%) 25 C / 55 % | Time: 10/38/01 |
| EUT: Massage Chair | Engineer Signature: Ben |
| Mode: TX 2402MHz | Distance: 3m |
| Model: HMC-600 | |
| Manufacturer: XIAMEN OGAWA INTELLIGENT HEALTH EQUIPMENT CO., LTD | |

Note: Report NO.:ATE20190505



| No. | Freq. (MHz) | Reading (dBuV/m) | Factor (dB) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector | Height (cm) | Degree (deg.) | Remark |
|-----|-------------|------------------|-------------|-----------------|----------------|-------------|----------|-------------|---------------|--------|
| 1 | 30.6387 | 48.96 | -20.36 | 28.60 | 40.00 | -11.40 | QP | 100 | 123 | |
| 2 | 86.3823 | 58.05 | -27.45 | 30.60 | 40.00 | -9.40 | QP | 100 | 201 | |
| 3 | 154.2427 | 58.88 | -27.68 | 31.20 | 43.50 | -12.30 | QP | 100 | 236 | |
| 4 | 173.8146 | 61.29 | -26.39 | 34.90 | 43.50 | -8.60 | QP | 100 | 196 | |
| 5 | 216.8803 | 60.04 | -24.04 | 36.00 | 46.00 | -10.00 | QP | 100 | 145 | |
| 6 | 747.0465 | 44.80 | -10.40 | 34.40 | 46.00 | -11.60 | QP | 100 | 178 | |



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg.A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: jp2019 #104

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: Massage Chair

Mode: TX 2441MHz

Model: HMC-600

Manufacturer: XIAMEN OGAWA INTELLIGENT HEALTH EQUIPMENT CO., LTD

Polarization: Horizontal

Power Source: AC 120V/60Hz


Date: 19/04/17/

Time: 10/42/54

Engineer Signature: Ben

Distance: 3m

Note: Report NO.:ATE20190505



| No. | Freq. (MHz) | Reading (dBuV/m) | Factor (dB) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector | Height (cm) | Degree (deg.) | Remark |
|-----|-------------|------------------|-------------|-----------------|----------------|-------------|----------|-------------|---------------|--------|
| 1 | 34.8928 | 51.22 | -21.42 | 29.80 | 40.00 | -10.20 | QP | 100 | 136 | |
| 2 | 71.4539 | 50.24 | -27.54 | 22.70 | 40.00 | -17.30 | QP | 100 | 265 | |
| 3 | 87.2980 | 52.04 | -27.44 | 24.60 | 40.00 | -15.40 | QP | 100 | 326 | |
| 4 | 148.9173 | 60.36 | -28.06 | 32.30 | 43.50 | -11.20 | QP | 100 | 65 | |
| 5 | 200.7470 | 59.64 | -24.34 | 35.30 | 43.50 | -8.20 | QP | 100 | 198 | |
| 6 | 216.1194 | 60.95 | -24.05 | 36.90 | 46.00 | -9.10 | QP | 100 | 236 | |



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: jp2019 #105

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: Massage Chair

Mode: TX 2441MHz

Model: HMC-600

Manufacturer: XIAMEN OGAWA INTELLIGENT HEALTH EQUIPMENT CO., LTD

Polarization: Vertical

Power Source: AC 120V/60Hz


Date: 19/04/17/

Time: 10/46/09

Engineer Signature: Ben

Distance: 3m

Note: Report NO.:ATE20190505



| No. | Freq. (MHz) | Reading (dBuV/m) | Factor (dB) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector | Height (cm) | Degree (deg.) | Remark |
|-----|-------------|------------------|-------------|-----------------|----------------|-------------|----------|-------------|---------------|--------|
| 1 | 30.3179 | 56.68 | -20.28 | 36.40 | 40.00 | -3.60 | QP | 100 | 123 | |
| 2 | 32.8697 | 53.31 | -20.91 | 32.40 | 40.00 | -7.60 | QP | 100 | 156 | |
| 3 | 37.9628 | 55.23 | -22.73 | 32.50 | 40.00 | -7.50 | QP | 100 | 256 | |
| 4 | 42.9305 | 56.28 | -24.08 | 32.20 | 40.00 | -7.80 | QP | 100 | 190 | |
| 5 | 176.2746 | 61.59 | -26.39 | 35.20 | 43.50 | -8.30 | QP | 100 | 263 | |
| 6 | 693.9101 | 48.41 | -11.61 | 36.80 | 46.00 | -9.20 | QP | 100 | 236 | |




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

| | |
|--|----------------------------|
| Job No.: jp2019 #106 | Polarization: Vertical |
| Standard: FCC Class B 3M Radiated | Power Source: AC 120V/60Hz |
| Test item: Radiation Test | Date: 19/04/17/ |
| Temp.(C)/Hum.(%) 25 C / 55 % | Time: 10/51/40 |
| EUT: Massage Chair | Engineer Signature: Ben |
| Mode: TX 2480MHz | Distance: 3m |
| Model: HMC-600 | |
| Manufacturer: XIAMEN OGAWA INTELLIGENT HEALTH EQUIPMENT CO., LTD | |

Note: Report NO.:ATE20190505



| No. | Freq. (MHz) | Reading (dBuV/m) | Factor (dB) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector | Height (cm) | Degree (deg.) | Remark |
|-----|-------------|------------------|-------------|-----------------|----------------|-------------|----------|-------------|---------------|--------|
| 1 | 30.0000 | 56.90 | -20.20 | 36.70 | 40.00 | -3.30 | QP | 100 | 123 | |
| 2 | 37.8297 | 58.97 | -22.67 | 36.30 | 40.00 | -3.70 | QP | 100 | 192 | |
| 3 | 41.4483 | 58.64 | -23.84 | 34.80 | 40.00 | -5.20 | QP | 100 | 296 | |
| 4 | 45.0951 | 58.26 | -24.46 | 33.80 | 40.00 | -6.20 | QP | 100 | 123 | |
| 5 | 175.6564 | 62.34 | -26.44 | 35.90 | 43.50 | -7.60 | QP | 100 | 256 | |
| 6 | 474.7912 | 52.09 | -16.69 | 35.40 | 46.00 | -10.60 | QP | 100 | 123 | |



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: jp2019 #122

Standard: FCC PK

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: Massage Chair

Mode: TX 2402MHz

Model: HMC-600

Manufacturer: XIAMEN OGAWA INTELLIGENT HEALTH EQUIPMENT CO., LTD

Polarization: Horizontal

Power Source: AC 120V/60Hz


Date: 19/04/18/

Time: 10/11/45

Engineer Signature: Ben

Distance: 3m

Note: Report NO.:ATE20190505



| No. | Freq. (MHz) | Reading (dBuV/m) | Factor (dB) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector | Height (cm) | Degree (deg.) | Remark |
|-----|-------------|------------------|-------------|-----------------|----------------|-------------|----------|-------------|---------------|--------|
| 1 | 2402.000 | 96.14 | -6.37 | 89.77 | | | peak | 100 | 23 | |
| 2 | 4804.000 | 58.48 | 0.70 | 59.18 | 74.00 | -14.82 | peak | 100 | 236 | |
| 3 | 4804.000 | 48.60 | 0.70 | 49.30 | 54.00 | -4.70 | AVG | 100 | 236 | |

Above 1GHz




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

| | |
|--|----------------------------|
| Job No.: jp2019 #123 | Polarization: Vertical |
| Standard: FCC PK | Power Source: AC 120V/60Hz |
| Test item: Radiation Test | Date: 19/04/18/ |
| Temp.(C)/Hum.(%) 25 C / 55 % | Time: 10/15/14 |
| EUT: Massage Chair | Engineer Signature: Ben |
| Mode: TX 2402MHz | Distance: 3m |
| Model: HMC-600 | |
| Manufacturer: XIAMEN OGAWA INTELLIGENT HEALTH EQUIPMENT CO., LTD | |

Note: Report NO.:ATE20190505



| No. | Freq. (MHz) | Reading (dBuV/m) | Factor (dB) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector | Height (cm) | Degree (deg.) | Remark |
|-----|-------------|------------------|-------------|-----------------|----------------|-------------|----------|-------------|---------------|--------|
| 1 | 2402.000 | 95.52 | -6.37 | 89.15 | | | peak | 100 | 125 | |
| 2 | 4804.000 | 47.67 | 0.70 | 48.37 | 74.00 | -25.63 | peak | 100 | 195 | |
| 3 | 4804.000 | 39.80 | 0.70 | 40.50 | 54.00 | -13.50 | AVG | 100 | 195 | |



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: jp2019 #122

Standard: FCC PK

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: Massage Chair

Mode: TX 2402MHz

Model: HMC-600

Manufacturer: XIAMEN OGAWA INTELLIGENT HEALTH EQUIPMENT CO., LTD

Polarization: Horizontal

Power Source: AC 120V/60Hz


Date: 19/04/18/

Time: 10/11/45

Engineer Signature: Ben

Distance: 3m

Note: Report NO.:ATE20190505



| No. | Freq. (MHz) | Reading (dBuV/m) | Factor (dB) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector | Height (cm) | Degree (deg.) | Remark |
|-----|-------------|------------------|-------------|-----------------|----------------|-------------|----------|-------------|---------------|--------|
| 1 | 2402.000 | 96.14 | -6.37 | 89.77 | | | peak | 100 | 23 | |
| 2 | 4804.000 | 58.48 | 0.70 | 59.18 | 74.00 | -14.82 | peak | 100 | 236 | |
| 3 | 4804.000 | 48.60 | 0.70 | 49.30 | 54.00 | -4.70 | AVG | 100 | 236 | |



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: jp2019 #124

Standard: FCC PK

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: Massage Chair

Mode: TX 2441MHz

Model: HMC-600

Manufacturer: XIAMEN OGAWA INTELLIGENT HEALTH EQUIPMENT CO., LTD

Polarization: Vertical

Power Source: AC 120V/60Hz


Date: 19/04/18/

Time: 10/18/12

Engineer Signature: Ben

Distance: 3m

Note: Report NO.:ATE20190505



| No. | Freq. (MHz) | Reading (dBuV/m) | Factor (dB) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector | Height (cm) | Degree (deg.) | Remark |
|-----|-------------|------------------|-------------|-----------------|----------------|-------------|----------|-------------|---------------|--------|
| 1 | 2441.000 | 92.95 | -6.20 | 86.75 | | | peak | 100 | 67 | |
| 2 | 4882.000 | 54.09 | 1.07 | 55.16 | 74.00 | -18.84 | peak | 100 | 156 | |
| 3 | 4882.000 | 46.03 | 1.07 | 47.10 | 54.00 | -6.90 | AVG | 100 | 156 | |



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: jp2019 #125

Standard: FCC PK

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: Massage Chair

Mode: TX 2441MHz

Model: HMC-600

Manufacturer: XIAMEN OGAWA INTELLIGENT HEALTH EQUIPMENT CO., LTD

Polarization: Horizontal

Power Source: AC 120V/60Hz


Date: 19/04/18/

Time: 10/21/24

Engineer Signature: Ben

Distance: 3m

Note: Report NO.:ATE20190505



| No. | Freq. (MHz) | Reading (dBuV/m) | Factor (dB) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector | Height (cm) | Degree (deg.) | Remark |
|-----|-------------|------------------|-------------|-----------------|----------------|-------------|----------|-------------|---------------|--------|
| 1 | 2441.000 | 94.41 | -6.20 | 88.21 | | | peak | 100 | 168 | |
| 2 | 4882.000 | 57.45 | 1.07 | 58.52 | 74.00 | -15.48 | peak | 100 | 156 | |
| 3 | 4882.000 | 47.23 | 1.07 | 48.30 | 54.00 | -5.70 | AVG | 100 | 156 | |



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: jp2019 #126

Standard: FCC PK

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: Massage Chair

Mode: TX 2480MHz

Model: HMC-600

Manufacturer: XIAMEN OGAWA INTELLIGENT HEALTH EQUIPMENT CO., LTD

Polarization: Horizontal

Power Source: AC 120V/60Hz


Date: 19/04/18/

Time: 10/23/59

Engineer Signature: Ben

Distance: 3m

Note: Report NO.:ATE20190505



| No. | Freq. (MHz) | Reading (dBuV/m) | Factor (dB) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector | Height (cm) | Degree (deg.) | Remark |
|-----|-------------|------------------|-------------|-----------------|----------------|-------------|----------|-------------|---------------|--------|
| 1 | 2480.000 | 95.61 | -6.04 | 89.57 | | | peak | 100 | 256 | |
| 2 | 4960.000 | 54.54 | 1.50 | 56.04 | 74.00 | -17.96 | peak | 100 | 145 | |
| 3 | 4960.000 | 45.40 | 1.50 | 46.90 | 54.00 | -7.10 | AVG | 100 | 145 | |



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: jp2019 #127

Standard: FCC PK

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: Massage Chair

Mode: TX 2480MHz

Model: HMC-600

Manufacturer: XIAMEN OGAWA INTELLIGENT HEALTH EQUIPMENT CO., LTD

Polarization: Vertical

Power Source: AC 120V/60Hz


Date: 19/04/18/

Time: 10/26/36

Engineer Signature: Ben

Distance: 3m


Note: Report NO.:ATE20190505



| No. | Freq. (MHz) | Reading (dBuV/m) | Factor (dB) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector | Height (cm) | Degree (deg.) | Remark |
|-----|-------------|------------------|-------------|-----------------|----------------|-------------|----------|-------------|---------------|--------|
| 1 | 2480.000 | 94.53 | -6.04 | 88.49 | | | peak | 100 | 310 | |
| 2 | 4960.000 | 49.65 | 1.50 | 51.15 | 74.00 | -22.85 | peak | 100 | 203 | |
| 3 | 4960.000 | 42.00 | 1.50 | 43.50 | 54.00 | -10.50 | AVG | 100 | 203 | |

11. BAND EDGE COMPLIANCE TEST

11.1. Block Diagram of Test Setup



(EUT: Massage Chair)

11.2. The Requirement For Section 15.247(d)

Section 15.247(d): In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).

11.3. EUT Configuration on Measurement

The equipment are installed on the emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

11.4. Operating Condition of EUT

11.4.1. Setup the EUT and simulator as shown as Section 11.1.

11.4.2. Turn on the power of all equipment.

11.4.3. Let the EUT work in TX (Hopping off, Hopping on) modes measure it. The transmit frequency are 2402-2480MHz. We select 2402MHz, 2480MHz TX frequency to transmit.

11.5. Test Procedure

11.5.1. The transmitter output was connected to the spectrum analyzer via a low loss cable.

11.5.2. Set RBW of spectrum analyzer to 100 kHz and VBW to 300 kHz with convenient frequency span including 100 kHz bandwidth from band edge.

11.5.3. The band edges was measured and recorded.

11.6. Test Result


Test Lab: Shielding room

Note: Both hopping-on mode and hopping-off mode had been pre-tested, and only the worst case was recorded in the test report.


| Frequency (MHz) | Result of Band Edge (dBc) | Limit of Band Edge (dBc) |
|-----------------|---------------------------|--------------------------|
| GFSK Mode | | |
| 2400.00 | 43.26 | > 20dBc |
| 2483.50 | 46.58 | > 20dBc |
| Π/4-DQPSK Mode | | |
| 2400.00 | 44.49 | > 20dBc |
| 2483.50 | 47.03 | > 20dBc |
| 8DPSK Mode | | |
| 2400.00 | 45.21 | > 20dBc |
| 2483.50 | 46.82 | > 20dBc |

The spectrum analyzer plots are attached as below.

GFSK Mode




Comment A:
Date: 18.APR.2019 12:19:20




Comment A:
Date: 18.APR.2019 10:19:55

Π/4-DQPSK Mode




Comment A:
Date: 18.APR.2019 10:24:31




Comment A:
Date: 18.APR.2019 10:33:19

8DPSK Mode



Comment A:
 Date: 18.APR.2019 10:26:14



Comment A:
 Date: 18.APR.2019 10:28:15

Radiated Band Edge Result

Note:

1. Emissions attenuated more than 20 dB below the permissible value are not reported.
2. The field strength is calculated by adding the antenna factor, high pass filter loss(if used) and cable loss, and subtracting the amplifier gain(if any)from the measured reading. The basic equation calculation is as follows:

Result = Reading + Corrected Factor

3. Display the measurement of peak values.

Test Procedure:

The EUT and its simulators are placed on a turntable, which is 1.5 meter high above ground(Above 1GHz). The turntable can rotate 360 degrees to determine the position of the maximum emission level. EUT is set 3.0 meters away from the receiving antenna, which is mounted on an antenna tower. The antenna can be moved up and down between 1.0 meter and 4 meters to find out the maximum emission level. Broadband antenna (calibrated bi-log antenna) is used as receiving antenna. Both horizontal and vertical polarizations of the antenna are set on measurement. In order to find the maximum emission levels, all of the EUT location must be manipulated according to ANSI C63.10:2013 on radiated emission measurement. The EUT was tested in 3 orthogonal planes.

Let the EUT work in TX (Hopping off, Hopping on) modes measure it.
We select 2402MHz, 2480MHz TX frequency to transmit(Hopping off mode).
We select 2402-2480MHz TX frequency to transmit(Hopping on mode).

During the radiated emission test, the spectrum analyzer was set with the following configurations:

- 1.The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for peak measurement with peak detector at frequency above 1GHz.
- 2.The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average measurement with peak detection at frequency above 1GHz.
- 3.All modes of operation were investigated and the worst case (GFSK mode) emissions are reported.

Test Lab: 3m Anechoic chamber

Non-hopping mode




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

| | |
|--|----------------------------|
| Job No.: jp2019 #130 | Polarization: Horizontal |
| Standard: FCC PK | Power Source: AC 120V/60Hz |
| Test item: Radiation Test | Date: 19/04/18/ |
| Temp.(C)/Hum.(%) 25 C / 55 % | Time: 10/38/39 |
| EUT: Massage Chair | Engineer Signature: Ben |
| Mode: TX 2402MHz | Distance: 3m |
| Model: HMC-600 | |
| Manufacturer: XIAMEN OGAWA INTELLIGENT HEALTH EQUIPMENT CO., LTD | |

Note: Report NO.:ATE20190505



| No. | Freq. (MHz) | Reading (dBuV/m) | Factor (dB) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector | Height (cm) | Degree (deg.) | Remark |
|-----|-------------|------------------|-------------|-----------------|----------------|-------------|----------|-------------|---------------|--------|
| 1 | 2390.000 | 40.30 | -6.32 | 33.98 | 74.00 | -40.02 | peak | 100 | 123 | |
| 2 | 2390.000 | 30.42 | -6.32 | 24.10 | 54.00 | -29.90 | AVG | 100 | 123 | |
| 3 | 2400.000 | 61.11 | -6.27 | 54.84 | 74.00 | -19.16 | peak | 100 | 203 | |
| 4 | 2400.000 | 50.27 | -6.27 | 44.00 | 54.00 | -10.00 | AVG | 100 | 203 | |

Note: Average measurement with peak detection at No.2&4




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

| | |
|--|----------------------------|
| Job No.: jp2019 #131 | Polarization: Vertical |
| Standard: FCC PK | Power Source: AC 120V/60Hz |
| Test item: Radiation Test | Date: 19/04/18/ |
| Temp.(C)/Hum.(%) 25 C / 55 % | Time: 10/41/43 |
| EUT: Massage Chair | Engineer Signature: Ben |
| Mode: TX 2402MHz | Distance: 3m |
| Model: HMC-600 | |
| Manufacturer: XIAMEN OGAWA INTELLIGENT HEALTH EQUIPMENT CO., LTD | |

Note: Report NO.:ATE20190505



| No. | Freq. (MHz) | Reading (dBuV/m) | Factor (dB) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector | Height (cm) | Degree (deg.) | Remark |
|-----|-------------|------------------|-------------|-----------------|----------------|-------------|----------|-------------|---------------|--------|
| 1 | 2390.000 | 40.55 | -6.32 | 34.23 | 74.00 | -39.77 | peak | 100 | 194 | |
| 2 | 2390.000 | 30.22 | -6.32 | 23.90 | 54.00 | -30.10 | AVG | 100 | 194 | |
| 3 | 2400.000 | 54.09 | -6.27 | 47.82 | 74.00 | -26.18 | peak | 100 | 206 | |
| 4 | 2400.000 | 44.07 | -6.27 | 37.80 | 54.00 | -16.20 | AVG | 100 | 206 | |

Note: Average measurement with peak detection at No.2&4




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

| | |
|--|----------------------------|
| Job No.: jp2019 #129 | Polarization: Horizontal |
| Standard: FCC PK | Power Source: AC 120V/60Hz |
| Test item: Radiation Test | Date: 19/04/18/ |
| Temp.(C)/Hum.(%) 25 C / 55 % | Time: 10/32/05 |
| EUT: Massage Chair | Engineer Signature: Ben |
| Mode: TX 2480MHz | Distance: 3m |
| Model: HMC-600 | |
| Manufacturer: XIAMEN OGAWA INTELLIGENT HEALTH EQUIPMENT CO., LTD | |

Note: Report NO.:ATE20190505



| No. | Freq. (MHz) | Reading (dBuV/m) | Factor (dB) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector | Height (cm) | Degree (deg.) | Remark |
|-----|-------------|------------------|-------------|-----------------|----------------|-------------|----------|-------------|---------------|--------|
| 1 | 2483.500 | 60.27 | -5.89 | 54.38 | 74.00 | -19.62 | peak | 100 | 196 | |
| 2 | 2483.500 | 50.09 | -5.89 | 44.20 | 54.00 | -9.80 | AVG | 100 | 196 | |
| 3 | 2500.000 | 40.22 | -5.81 | 34.41 | 74.00 | -39.59 | peak | 100 | 236 | |
| 4 | 2500.000 | 30.31 | -5.81 | 24.50 | 54.00 | -29.50 | AVG | 100 | 236 | |

Note: Average measurement with peak detection at No.2&4




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

| | |
|--|----------------------------|
| Job No.: jp2019 #128 | Polarization: Vertical |
| Standard: FCC PK | Power Source: AC 120V/60Hz |
| Test item: Radiation Test | Date: 19/04/18/ |
| Temp.(C)/Hum.(%) 25 C / 55 % | Time: 10/29/42 |
| EUT: Massage Chair | Engineer Signature: Ben |
| Mode: TX 2480MHz | Distance: 3m |
| Model: HMC-600 | |
| Manufacturer: XIAMEN OGAWA INTELLIGENT HEALTH EQUIPMENT CO., LTD | |

Note: Report NO.:ATE20190505



| No. | Freq. (MHz) | Reading (dBuV/m) | Factor (dB) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector | Height (cm) | Degree (deg.) | Remark |
|-----|-------------|------------------|-------------|-----------------|----------------|-------------|----------|-------------|---------------|--------|
| 1 | 2483.500 | 45.74 | -5.89 | 39.85 | 74.00 | -34.15 | peak | 100 | 103 | |
| 2 | 2483.500 | 35.69 | -5.89 | 29.80 | 54.00 | -24.20 | AVG | 100 | 103 | |
| 3 | 2500.000 | 41.39 | -5.81 | 35.58 | 74.00 | -38.42 | peak | 100 | 95 | |
| 4 | 2500.000 | 31.71 | -5.81 | 25.90 | 54.00 | -28.10 | AVG | 100 | 95 | |

Note: Average measurement with peak detection at No.2&4

Hopping mode




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

| | |
|--|----------------------------|
| Job No.: jp2019 #120 | Polarization: Vertical |
| Standard: FCC PK | Power Source: AC 120V/60Hz |
| Test item: Radiation Test | Date: 19/04/18/ |
| Temp.(C)/Hum.(%) 25 C / 55 % | Time: 10/06/16 |
| EUT: Massage Chair | Engineer Signature: Ben |
| Mode: HOPPING(GFSK) | Distance: 3m |
| Model: HMC-600 | |
| Manufacturer: XIAMEN OGAWA INTELLIGENT HEALTH EQUIPMENT CO., LTD | |

Note: Report NO.:ATE20190505



| No. | Freq. (MHz) | Reading (dBuV/m) | Factor (dB) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector | Height (cm) | Degree (deg.) | Remark |
|-----|-------------|------------------|-------------|-----------------|----------------|-------------|----------|-------------|---------------|--------|
| 1 | 2390.000 | 41.16 | -6.32 | 34.84 | 74.00 | -39.16 | peak | 100 | 256 | |
| 2 | 2390.000 | 31.62 | -6.32 | 25.30 | 54.00 | -28.70 | AVG | 100 | 256 | |
| 3 | 2400.000 | 58.65 | -6.27 | 52.38 | 74.00 | -21.62 | peak | 100 | 195 | |
| 4 | 2400.000 | 48.07 | -6.27 | 41.80 | 54.00 | -12.20 | AVG | 100 | 195 | |
| 5 | 2483.500 | 53.30 | -5.89 | 47.41 | 74.00 | -26.59 | peak | 100 | 136 | |
| 6 | 2483.500 | 43.69 | -5.89 | 37.80 | 54.00 | -16.20 | AVG | 100 | 136 | |
| 7 | 2500.000 | 42.31 | -5.81 | 36.50 | 74.00 | -37.50 | peak | 100 | 296 | |
| 8 | 2500.000 | 32.91 | -5.81 | 27.10 | 54.00 | -26.90 | AVG | 100 | 296 | |

Note: Average measurement with peak detection at No.2&4&6&8




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

| | |
|--|----------------------------|
| Job No.: jp2019 #121 | Polarization: Horizontal |
| Standard: FCC PK | Power Source: AC 120V/60Hz |
| Test item: Radiation Test | Date: 19/04/18/ |
| Temp.(C)/Hum.(%) 25 C / 55 % | Time: 10/09/05 |
| EUT: Massage Chair | Engineer Signature: Ben |
| Mode: HOPPING(GFSK) | Distance: 3m |
| Model: HMC-600 | |
| Manufacturer: XIAMEN OGAWA INTELLIGENT HEALTH EQUIPMENT CO., LTD | |

Note: Report NO.:ATE20190505



| No. | Freq. (MHz) | Reading (dBuV/m) | Factor (dB) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector | Height (cm) | Degree (deg.) | Remark |
|-----|-------------|------------------|-------------|-----------------|----------------|-------------|----------|-------------|---------------|--------|
| 1 | 2390.000 | 40.69 | -6.32 | 34.37 | 74.00 | -39.63 | peak | 100 | 278 | |
| 2 | 2390.000 | 30.22 | -6.32 | 23.90 | 54.00 | -30.10 | AVG | 100 | 278 | |
| 3 | 2400.000 | 56.98 | -6.27 | 50.71 | 74.00 | -23.29 | peak | 100 | 196 | |
| 4 | 2400.000 | 46.77 | -6.27 | 40.50 | 54.00 | -13.50 | AVG | 100 | 196 | |
| 5 | 2483.500 | 41.27 | -5.89 | 35.38 | 74.00 | -38.62 | peak | 100 | 245 | |
| 6 | 2483.500 | 31.29 | -5.89 | 25.40 | 54.00 | -28.60 | AVG | 100 | 245 | |
| 7 | 2500.000 | 41.25 | -5.81 | 35.44 | 74.00 | -38.56 | peak | 100 | 106 | |
| 8 | 2500.000 | 31.81 | -5.81 | 26.00 | 54.00 | -28.00 | AVG | 100 | 106 | |


Note: Average measurement with peak detection at No.2&4&6&8

12.AC POWER LINE CONDUCTED EMISSION FOR FCC PART

15 SECTION 15.207(A)


12.1.Block Diagram of Test Setup

12.1.1.Block diagram of connection between the EUT and simulators



(EUT: Massage Chair)

12.1.2.Test System Setup



- Note: 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

12.2. Power Line Conducted Emission Measurement Limits

| Frequency (MHz) | Limit dB(μV) | |
|-----------------|------------------|---------------|
| | Quasi-peak Level | Average Level |
| 0.15 - 0.50 | 66.0 – 56.0 * | 56.0 – 46.0 * |
| 0.50 - 5.00 | 56.0 | 46.0 |
| 5.00 - 30.00 | 60.0 | 50.0 |

NOTE1: The lower limit shall apply at the transition frequencies.
 NOTE2: The limit decreases linearly with the logarithm of the frequency in the range 0.15MHz to 0.50MHz.

12.3. Configuration of EUT on Measurement

The equipments are installed on Power Line Conducted Emission Measurement to meet the commission requirement and operating regulations in a manner, which tends to maximize its emission characteristics in a normal application.

12.4. Operating Condition of EUT

12.4.1. Setup the EUT and simulator as shown as Section 12.1.

12.4.2. Turn on the power of all equipment.

12.4.3. Let the EUT work in test mode and measure it.

12.5. Test Procedure

The EUT is put on the plane 0.1m high above the ground by insulating support and is connected to the power mains through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm coupling impedance for the EUT system. Please refer the block diagram of the test setup and photographs. Both sides of AC lines are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to ANSI C63.10: 2013 on Conducted Emission Measurement. The bandwidth of test receiver (R & S ESCS30) is set at 9kHz.

The frequency range from 150kHz to 30MHz is checked.

12.6.Data Sample

| Frequency (MHz) | Transducer value (dB) | QuasiPeak Level (dB μ V) | Average Level (dB μ V) | QuasiPeak Limit (dB μ V) | Average Limit (dB μ V) | QuasiPeak Margin (dB) | Average Margin (dB) | Remark (Pass/Fail) |
|-----------------|-----------------------|------------------------------|----------------------------|------------------------------|----------------------------|-----------------------|---------------------|--------------------|
| X.XX | 10.5 | 51.1 | 34.2 | 56.0 | 46.0 | 4.9 | 11.8 | Pass |

Frequency(MHz) = Emission frequency in MHz

Transducer value(dB) = Insertion loss of LISN + Cable Loss

Level(dB μ V) = Quasi-peak Reading/Average Reading + Transducer value

Limit (dB μ V) = Limit stated in standard

Margin = Limit (dB μ V) - Level (dB μ V)

Calculation Formula:

Margin = Limit (dB μ V) - Level (dB μ V)

12.7.Power Line Conducted Emission Measurement Results

PASS.

Test Lab: Shielding room

The frequency range from 150kHz to 30MHz is checked.

Maximizing procedure was performed on the six (6) highest emissions of the EUT. Emissions attenuated more than 20 dB below the permissible value are not reported.

All data was recorded in the Quasi-peak and average detection mode.

The spectral diagrams are attached as below.


ACCURATE TECHNOLOGY CO., LTD

CONDUCTED EMISSION STANDARD FCC PART 15B

EUT: Massage Chair M/N:HMC-600
 Manufacturer: XIAMEN OGAWA INTELLIGENT HEALTH EQUIPMENT CO., LTD
 Operating Condition: ON
 Test Site: 1#Shielding Room
 Operator: Ben
 Test Specification: N 120V 60Hz
 Comment: Report NO.:ATE20190505
 Start of Test: 2019-4-15 / 17:42:18

SCAN TABLE: "V 150K-30MHz fin"

Short Description: _SUB_STD_VTERM2 1.70
 Start Stop Step Detector Meas. IF Transducer
 Frequency Frequency Width Time Bandw.
 150.0 kHz 30.0 MHz 4.5 kHz QuasiPeak 1.0 s 9 kHz NSLK8126 2008
 Average



MEASUREMENT RESULT: "OG-0504-05_fin"

2019-4-15 17:44

| Frequency MHz | Level dBuV | Transd dB | Limit dBuV | Margin dB | Detector | Line | PE |
|---------------|------------|-----------|------------|-----------|----------|------|-----|
| 0.361500 | 26.70 | 10.9 | 59 | 32.0 | QP | N | GND |
| 0.402000 | 27.90 | 11.0 | 58 | 29.9 | QP | N | GND |
| 2.107500 | 38.90 | 11.3 | 56 | 17.1 | QP | N | GND |
| 2.265000 | 45.40 | 11.3 | 56 | 10.6 | QP | N | GND |
| 8.340000 | 45.10 | 11.5 | 60 | 14.9 | QP | N | GND |
| 15.135000 | 15.80 | 11.6 | 60 | 44.2 | QP | N | GND |

MEASUREMENT RESULT: "OG-0504-05_fin2"

2019-4-15 17:44

| Frequency MHz | Level dBuV | Transd dB | Limit dBuV | Margin dB | Detector | Line | PE |
|---------------|------------|-----------|------------|-----------|----------|------|-----|
| 0.321000 | 18.30 | 10.9 | 50 | 31.4 | AV | N | GND |
| 0.384000 | 14.00 | 10.9 | 48 | 34.2 | AV | N | GND |
| 2.103000 | 28.60 | 11.3 | 46 | 17.4 | AV | N | GND |
| 2.265000 | 33.70 | 11.3 | 46 | 12.3 | AV | N | GND |
| 8.115000 | 36.50 | 11.5 | 50 | 13.5 | AV | N | GND |
| 12.570000 | 10.80 | 11.6 | 50 | 39.2 | AV | N | GND |


ACCURATE TECHNOLOGY CO., LTD

CONDUCTED EMISSION STANDARD FCC PART 15B

EUT: Massage Chair M/N:HMC-600
 Manufacturer: XIAMEN OGAWA INTELLIGENT HEALTH EQUIPMENT CO., LTD
 Operating Condition: ON
 Test Site: 1#Shielding Room
 Operator: Ben
 Test Specification: L 120V 60Hz
 Comment: Report NO.:ATE20190505
 Start of Test: 2019-4-15 / 17:59:50

SCAN TABLE: "V 150K-30MHz fin"

| Start Frequency | Stop Frequency | Step Width | Detector | Meas. Time | IF Bandw. | Transducer |
|-----------------|----------------|------------|-----------|------------|-----------|---------------|
| 150.0 kHz | 30.0 MHz | 4.5 kHz | QuasiPeak | 1.0 s | 9 kHz | NSLK8126 2008 |
| Average | | | | | | |



MEASUREMENT RESULT: "OG-0504-12_fin"

2019-4-15 18:01

| Frequency MHz | Level dBuV | Transd dB | Limit dBuV | Margin dB | Detector | Line | PE |
|---------------|------------|-----------|------------|-----------|----------|------|-----|
| 0.159000 | 34.40 | 10.8 | 66 | 31.1 | QP | L1 | GND |
| 0.780000 | 23.80 | 11.1 | 56 | 32.2 | QP | L1 | GND |
| 2.121000 | 36.30 | 11.3 | 56 | 19.7 | QP | L1 | GND |
| 2.278500 | 42.70 | 11.3 | 56 | 13.3 | QP | L1 | GND |
| 8.187000 | 44.00 | 11.5 | 60 | 16.0 | QP | L1 | GND |
| 17.155500 | 22.90 | 11.7 | 60 | 37.1 | QP | L1 | GND |

MEASUREMENT RESULT: "OG-0504-12_fin2"

2019-4-15 18:01

| Frequency MHz | Level dBuV | Transd dB | Limit dBuV | Margin dB | Detector | Line | PE |
|---------------|------------|-----------|------------|-----------|----------|------|-----|
| 0.159000 | 28.50 | 10.8 | 56 | 27.0 | AV | L1 | GND |
| 0.775500 | 21.10 | 11.1 | 46 | 24.9 | AV | L1 | GND |
| 2.112000 | 35.00 | 11.3 | 46 | 11.0 | AV | L1 | GND |
| 2.355000 | 38.40 | 11.3 | 46 | 7.6 | AV | L1 | GND |
| 8.187000 | 37.60 | 11.5 | 50 | 12.4 | AV | L1 | GND |
| 12.867000 | 12.30 | 11.6 | 50 | 37.7 | AV | L1 | GND |


13.ANTENNA REQUIREMENT

13.1.The Requirement

According to Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

13.2.Antenna Construction

Device is equipped with permanent attached antenna, which isn't displaced by other antenna. The Max Antenna gain of EUT is 0dBi. Therefore, the equipment complies with the antenna requirement of Section 15.203.



***** End of Test Report *****