



Data Rate: MCS4

Band edge Channel Frequency 2462MHz



Data Rate: MCS7

Band edge Channel Frequency 2412MHz



Data Rate: MCS7

Band edge Channel Frequency 2462MHz


Modulation: 802.11n\_HT40

Data Rate (Mbps)	Channel Frequency (MHz)	Reference Value (B) (dBm)	Band edge Frequency (MHz)	Value at Band edge (A) (dBm)	A-B (dBc)	Minimum Limit (dBc)
MCS0	2422	-4.57	2394	-40.95	-36.38	-30
	2452	-4.50	2483.5	-47.34	-42.84	-30
MCS4	2422	-4.86	2393	-43.63	-38.77	-30
	2452	-4.50	2483.5	-47.82	-43.32	-30
MCS7	2422	-4.87	2398	-41.87	-37.00	-30
	2452	-4.60	2483.5	-47.44	-42.84	-30











Data Rate: MCS0

Channel Frequency 2412MHz




Data Rate: MCS0

Channel Frequency 2462MHz



Data Rate: MCS4

Channel Frequency 2412MHz



Data Rate: MCS4

Channel Frequency 2462MHz







**6.4.2 Out-Of-Band Emissions**

**Modulation: 802.11b**

**Data Rate 1Mbps**



**Frequency Range 9KHz – 1MHz**




**Frequency Range 1MHz – 30MHz**

**Prüfbericht - Nr.:**  
Test Report No.:

**ULR-TC56882030000049F**

Seite 96 von 170  
Page 96 of 170




Channel Frequency 2412MHz

Frequency Range 30 MHz – 1GHz

Modulation: 802.11b


Data Rate 1Mbps

Data Rate (Mbps)	Channel Frequency (MHz)	Value at the Band Edge		Reference Value B (dBm)	Band Edge Value A~B (dBc)	Limit (dBc)
		Frequency (GHz)	Value A (dBm)			
1	2412	13.73	-42.42	5.22	-47.64	-30
	2462	13.73	-42.15	4.98	-47.13	-30
11	2412	13.73	-41.43	5.32	-46.75	-30
	2462	13.73	-41.76	4.99	-46.75	-30




Channel Frequency 2412MHz

Frequency Range 1GHz – 26.5GHz



Channel Frequency 2437MHz

Frequency Range 1GHz – 26.5GHz




Channel Frequency 2462MHz

Frequency Range 1GHz – 26.5GHz


Modulation: 802.11b

Data Rate 11Mbps




Channel Frequency 2412MHz

Frequency Range 1GHz – 26.5GHz



Channel Frequency 2437MHz

Frequency Range 1GHz – 26.5GHz



Channel Frequency 2462MHz

Frequency Range 1GHz – 26.5GHz

**Prüfbericht - Nr.:**  
Test Report No.:


**ULR-TC56882030000049F**

Seite 100 von 170  
Page 100 of 170

**Modulation: 802.11g**


**Data Rate 6Mbps**

Data Rate (Mbps)	Channel Frequency (MHz)	Value at the Band Edge		Reference Value B (dBm)	Band Edge Value A~B (dBc)	Limit (dBc)
		Frequency (GHz)	Value A (dBm)			
6	2412	13.73	-42.44	-0.30	-42.14	-30
	2462	13.73	-41.55	-1.14	-40.41	-30
24	2412	13.73	-42.08	-0.61	-41.47	-30
	2462	13.73	-42.54	-0.63	-41.91	-30
54	2412	13.73	-41.71	-0.38	-41.33	-30
	2462	13.73	-41.89	-0.38	-41.51	-30




Channel Frequency 2412MHz

Frequency Range 1GHz – 26.5GHz



Channel Frequency 2437MHz

Frequency Range 1GHz – 26.5GHz



Channel Frequency 2462MHz

Frequency Range 1GHz – 26.5GHz




**Prüfbericht - Nr.:**  
Test Report No.:

**ULR-TC56882030000049F**

Seite 102 von 170  
Page 102 of 170


**Modulation: 802.11g**

**Data Rate 24Mbps**




Channel Frequency 2412MHz

Frequency Range 1GHz – 26.5GHz



Channel Frequency 2437MHz

Frequency Range 1GHz – 26.5GHz




Channel Frequency 2462MHz

Frequency Range 1GHz – 26.5GHz


Modulation: 802.11g

Data Rate 54Mbps




Channel Frequency 2412MHz

Frequency Range 1GHz – 26.5GHz



Channel Frequency 2437MHz

Frequency Range 1GHz – 26.5GHz



Channel Frequency 2462MHz

Frequency Range 1GHz – 26.5GHz

**Prüfbericht - Nr.:**  
Test Report No.:


**ULR-TC56882030000049F**

Seite 105 von 170  
Page 105 of 170

**Modulation: 802.11n\_20MHz**


**Data Rate MCS0**

Data Rate (Mbps)	Channel Frequency (MHz)	Value at the Band Edge		Reference Value B (dBm)	Band Edge Value A~B (dBc)	Limit (dBc)
		Frequency (GHz)	Value A (dBm)			
MCS0	2412	13.73	-42.65	0.12	-42.77	-30
	2462	13.73	-41.49	-0.05	-41.44	-30
MCS4	2412	13.73	-41.49	-0.12	-41.37	-30
	2462	13.73	-41.40	-0.08	-41.32	-30
MCS7	2412	13.73	-41.40	0.09	-41.49	-30
	2462	13.73	-42.39	0.03	-42.42	-30




Channel Frequency 2412MHz

Frequency Range 1GHz – 26.5GHz



Channel Frequency 2437MHz

Frequency Range 1GHz – 26.5GHz




Channel Frequency 2462MHz

Frequency Range 1GHz – 26.5GHz


Modulation: 802.11n\_20MHz

Data Rate MCS4




Channel Frequency 2412MHz

Frequency Range 1GHz – 26.5GHz



Channel Frequency 2437MHz

Frequency Range 1GHz – 26.5GHz




Channel Frequency 2462MHz

Frequency Range 1GHz – 26.5GHz


Modulation: 802.11n\_20MHz

Data Rate MCS7




Channel Frequency 2412MHz

Frequency Range 1GHz – 26.5GHz



Channel Frequency 2437MHz

Frequency Range 1GHz – 26.5GHz



Channel Frequency 2462MHz

Frequency Range 1GHz – 26.5GHz



**Prüfbericht - Nr.:**  
Test Report No.:


**ULR-TC56882030000049F**

Seite 110 von 170  
Page 110 of 170

**Modulation: 802.11n\_40MHz**


**Data Rate MCS0**

Data Rate (Mbps)	Channel Frequency (MHz)	Value at the Band Edge		Reference Value B (dBm)	Band Edge Value A~B (dBc)	Limit (dBc)
		Frequency (GHz)	Value A (dBm)			
MCS0	2422	13.73	-42.59	-4.57	-38.02	-30
	2452	13.73	-41.50	-4.50	-37.00	-30
MCS4	2422	13.73	-42.90	-4.86	-38.04	-30
	2452	13.73	-41.58	-4.50	-37.08	-30
MCS7	2422	13.73	-41.67	-4.87	-36.80	-30
	2452	13.73	-42.41	-4.60	-37.81	-30



**Channel Frequency 2422MHz**

**Frequency Range 1GHz – 26.5GHz**




Channel Frequency 2452MHz

Frequency Range 1GHz – 26.5GHz


Modulation: 802.11n\_40MHz

Data Rate MCS4



Channel Frequency 2422MHz

Frequency Range 1GHz – 26.5GHz




Channel Frequency 2452MHz

Frequency Range 1GHz – 26.5GHz


Modulation: 802.11n\_40MHz

Data Rate MCS7



Channel Frequency 2422MHz

Frequency Range 1GHz – 26.5GHz



Channel Frequency 2452MHz

Frequency Range 1GHz – 26.5GHz

## 6.5 Spurious Radiated Emissions & Restricted Bands of Operation

<b>Result</b>	<b>Pass</b>
Test Specification	FCC part 15 Subpart C 15.247 (d) / (15.209 & 15.205) / IC RSS-GEN, Section 8.9 and 8.10
Test Method	ANSI C63.10
Measurement Location	Semi Anechoic Chamber 30MHz - 1 GHz Fully Anechoic Chamber 1 GHz - 40GHz
Measurement Bandwidth	100 kHz for frequency range < 1GHz 1 MHz for Frequency range >1GHz
Detector	Refer remarks below
Measuring Distance	3 m
Requirement	As per the limits mentioned in the below table
Test setup	Refer Clause 7 TEST METHODOLOGY

**Table 7: Transmitter limits for Radiated emission**

<b>Frequency (MHz)</b>	<b>Field strength (μV/m)</b>	<b>Field strength (dBμV/m)</b>	<b>Distance of Measurement (m)</b>
0.009 – 0.490	2400/F(kHz)	48.50 – 13.80	300*
0.490 – 1.705	24000/F(kHz)	33.80 – 23.00	30*
1.705 -30	30	29.54	30*
30-88	100	40.0	3
88-216	150	43.5	3
216-960	200	46.0	3
Above 960	500	54.0	3

Remark: \* The limit shows in the table above of frequency range 0.009 – 0.490, 0.490 – 1.705 MHz and 1.705-30MHz is at 300 meter, 30 meter and 30 meter range respectively, which corresponds to 128.51 – 93.80, 73.80 – 62.96 and 69.54 dBμV/m at 3m range by extrapolation calculation and the measurement of loop antenna.

The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz Radiated emission limits in these three bands are based on measurements employing an average detector.

### Test Conditions:

Temperature (Norm) = + 25 °C

Voltage = 3.6V DC Li-Ion battery

Relative humidity = 62 %

**Prüfbericht - Nr.:**  
Test Report No.:

**ULR-TC56882030000049F**

Seite 115 von 170  
Page 115 of 170

**Test results:**

Note: All the losses are included during measurement and final values are mentioned in the test report. Refer Clause 7 TEST METHODOLOGY for more details


**Test results for frequency range 9kHz – 30MHz**

No emissions found in frequency range 9 kHz to 30 MHz, and measured levels are below 20dB from the limit line, hence not reported

**Test results for frequency range 30MHz – 1GHz**


**Mode of Operation: Curved Mode**

Polarization	Frequency (MHz)	Measured value (dBµV/m)	Limit (dBµV/m)	Margin (dB)
Vertical	34.00	22.71	40	-17.29
	51.91	22.06	40	-17.94
	60.47	22.95	40	-17.05
	228.80	24.23	46	-21.77
	274.20	18.21	46	-27.79
	900.00	38.52	46	-7.48
Horizontal	33.76	17.41	40	-22.59
	52.28	18.19	40	-21.81
	169.40	14.24	43.5	-29.26
	299.93	20.33	46	-25.67
	500.00	25.90	46	-20.10
	900.06	34.38	46	-11.62




**Channel Frequency 30MHz – 200MHz**

**Polarization Vertical**




**Channel Frequency 30MHz – 200MHz**

**Polarization Horizontal**



**Channel Frequency 200MHz – 1GHz**

**Polarization Vertical**




Channel Frequency 200MHz – 1GHz

Polarization Horizontal

**Mode of Operation: Linear Mode:**


Polarization	Frequency (MHz)	Measured value (dBµV/m)	Limit (dBµV/m)	Margin (dB)
Vertical	47.72	10.78	40	-29.22
	61.81	10.22	40	-29.78
	83.73	17.40	43.5	-26.10
	499.98	22.58	46	-23.42
	700.02	24.97	46	-21.03
	900.00	37.79	46	-8.21
Horizontal	34.85	10.32	40	-29.68
	48.45	10.60	40	-29.40
	67.46	9.31	40	-30.69
	300.01	18.42	46	-27.58
	499.98	26.15	46	-19.85
	900.00	30.23	46	-15.77






**Channel Frequency 30MHz – 200MHz**

**Polarization Vertical**




**Channel Frequency 30MHz – 200MHz**

**Polarization Horizontal**



Channel Frequency 200MHz – 1GHz

Polarization Vertical



Channel Frequency 200MHz – 1GHz

Polarization Horizontal

**Prüfbericht - Nr.:**  
Test Report No.:

**ULR-TC56882030000049F**

Seite 120 von 170  
Page 120 of 170

**Test results for the frequencies in the range 1 GHz to 26.5 GHz**

**Modulation: 802.11b**

**Data Rate: 1Mbps**

Channel Frequency (MHz)	Antenna Polarization	Measured Frequency (MHz)	Field Strength (dBµV/m)	Limit (dBµV/m)	Margin (dB)
2412	Vertical	2390(Pk)	45.35	74*	-28.65
		2390(Av)	31.02	54*	-22.98
		2412(Pk)	95.37	-	-
		2412(Av)	93.10	-	-
		4824(Pk)	42.64	74	-31.21
		4824(Av)	32.00	54	-21.16
		7236(Pk)	No Harmonics Found		
	7236(Av)	No Harmonics Found			
	Horizontal	2390(Pk)	39.57	74*	-34.43
		2390(Av)	28.22	54*	-25.78
		2412(Pk)	92.03	-	-
		2412(Av)	89.76	-	-
		4824(Pk)	42.79	74	-31.21
		4824(Av)	32.84	54	-21.16
7236(Pk)		No Harmonics Found			
7236(Av)	No Harmonics Found				
2437	Vertical	2437(Pk)	95.23	-	-
		2437(Av)	92.86	-	-
		4874(Pk)	46.42	74	-27.58
		4874(Av)	39.62	54	-14.38
		7311(Pk)	No Harmonics Found		
	7311(Av)	No Harmonics Found			
	Horizontal	2437(Pk)	90.43	-	-
		2437(Av)	87.73	-	-
		4874(Pk)	44.11	74	-29.89
		4874(Av)	35.74	54	-18.26
7311(Pk)		No Harmonics Found			
7311(Av)	No Harmonics Found				
2462	Vertical	2462(Pk)	92.77	-	-
		2462(Av)	90.32	-	-
		2483.5(Pk)	43.31	74*	-30.69
		2483.5(Av)	35.41	54*	-18.59
		4924(Pk)	47.02	74	-26.98
		4924(Av)	41.29	54	-12.71
		7386(Pk)	No Harmonics Found		
	7386(Av)	No Harmonics Found			
	Horizontal	2462(Pk)	88.36	-	-
		2462(Av)	85.95	-	-
		2483.5(Pk)	40.67	74*	-33.33
		2483.5(Av)	31.92	54*	-22.08
		4924(Pk)	48.03	74	-25.97
		4924(Av)	41.28	54	-12.72
7386(Pk)		No Harmonics Found			
7386(Av)	No Harmonics Found				

\*- : Indicate restricted band of operation §15.205

Pk: Peak Detector; Av: Average Detector

**Prüfbericht - Nr.:**  
Test Report No.:

**ULR-TC56882030000049F**

Seite 121 von 170  
Page 121 of 170

**Modulation: 802.11b**  
**Data Rate: 11Mbps**

Channel Frequency (MHz)	Antenna Polarization	Measured Frequency (MHz)	Field Strength (dBµV/m)	Limit (dBµV/m)	Margin (dB)
2412	Vertical	2390(Pk)	50.51	74*	-23.49
		2390(Av)	38.94	54*	-15.06
		2412(Pk)	100.48	-	-
		2412(Av)	92.04	-	-
		4824(Pk)	46.55	74	-30.20
		4824(Av)	38.41	54	-18.30
		7236(Pk)	No Harmonics Found		
	7236(Av)	No Harmonics Found			
	Horizontal	2390(Pk)	45.81	74*	-28.19
		2390(Av)	35.25	54*	-18.75
		2412(Pk)	96.88	-	-
		2412(Av)	88.27	-	-
		4824(Pk)	43.80	74	-30.20
		4824(Av)	35.70	54	-18.30
7236(Pk)		No Harmonics Found			
7236(Av)	No Harmonics Found				
2437	Vertical	2437(Pk)	99.10	-	-
		2437(Av)	90.93	-	-
		4874(Pk)	46.06	74	-27.94
		4874(Av)	40.87	54	-13.13
		7311(Pk)	No Harmonics Found		
	7311(Av)	No Harmonics Found			
	Horizontal	2437(Pk)	94.84	-	-
		2437(Av)	86.40	-	-
		4874(Pk)	44.48	74	-29.52
		4874(Av)	36.31	54	-17.69
7311(Pk)		No Harmonics Found			
7311(Av)	No Harmonics Found				
2462	Vertical	2462(Pk)	98.14	-	-
		2462(Av)	89.41	-	-
		2483.5(Pk)	45.29	74*	-28.71
		2483.5(Av)	33.95	54*	-20.05
		4924(Pk)	47.89	74	-26.11
		4924(Av)	41.29	54	-12.71
		7386(Pk)	No Harmonics Found		
	7386(Av)	No Harmonics Found			
	Horizontal	2462(Pk)	91.18	-	-
		2462(Av)	83.49	-	-
		2483.5(Pk)	40.38	74*	-33.62
		2483.5(Av)	29.33	54*	-24.67
		4924(Pk)	47.02	74	-26.98
4924(Av)		38.96	54	-15.04	
7386(Pk)	No Harmonics Found				
7386(Av)	No Harmonics Found				

\*- : Indicate restricted band of operation §15.205  
Pk: Peak Detector; Av: Average Detector

**Prüfbericht - Nr.:**  
Test Report No.:

**ULR-TC56882030000049F**

Seite 122 von 170  
Page 122 of 170

**Modulation: 802.11g**  
**Data Rate: 6Mbps**

Channel Frequency (MHz)	Antenna Polarization	Measured Frequency (MHz)	Field Strength (dBµV/m)	Limit (dBµV/m)	Margin (dB)
2412	Vertical	2390(Pk)	57.43	74*	-16.57
		2390(Av)	35.98	54*	-18.02
		2412(Pk)	96.74	-	-
		2412(Av)	86.42	-	-
		4824(Pk)	47.02	74	-29.47
		4824(Av)	39.56	54	-19.56
		7236(Pk)	No Harmonics Found		
	7236(Av)				
	Horizontal	2390(Pk)	53.31	74*	-20.69
		2390(Av)	32.95	54*	-21.05
		2412(Pk)	93.08	-	-
		2412(Av)	82.84	-	-
		4824(Pk)	44.53	74	-29.47
		4824(Av)	34.44	54	-19.56
7236(Pk)		No Harmonics Found			
7236(Av)					
2437	Vertical	2437(Pk)	99.94	-	-
		2437(Av)	89.84	-	-
		4874(Pk)	48.82	74	-25.18
		4874(Av)	41.28	54	-12.72
		7311(Pk)	No Harmonics Found		
	7311(Av)				
	Horizontal	2437(Pk)	94.48	-	-
		2437(Av)	85.38	-	-
		4874(Pk)	46.93	74	-27.07
		4874(Av)	37.91	54	-16.09
7311(Pk)		No Harmonics Found			
7311(Av)					
2462	Vertical	2462(Pk)	93.30	-	-
		2462(Av)	83.72	-	-
		2483.5(Pk)	54.86	74*	-19.14
		2483.5(Av)	33.56	54*	-20.44
		4924(Pk)	48.26	74	-25.74
		4924(Av)	41.40	54	-12.60
		7386(Pk)	No Harmonics Found		
	7386(Av)				
	Horizontal	2462(Pk)	89.15	-	-
		2462(Av)	78.75	-	-
		2483.5(Pk)	49.08	74*	-24.92
		2483.5(Av)	29.58	54*	-24.42
		4924(Pk)	47.28	74	-26.72
		4924(Av)	40.09	54	-13.91
7386(Pk)		No Harmonics Found			
7386(Av)					

\*- : Indicate restricted band of operation §15.205  
Pk: Peak Detector; Av: Average Detector

**Prüfbericht - Nr.:**  
Test Report No.:

**ULR-TC56882030000049F**

Seite 123 von 170  
Page 123 of 170

**Modulation: 802.11g**  
**Data Rate: 24Mbps**

Channel Frequency (MHz)	Antenna Polarization	Measured Frequency (MHz)	Field Strength (dBµV/m)	Limit (dBµV/m)	Margin (dB)
2412	Vertical	2390(Pk)	61.43	74*	-12.57
		2390(Av)	36.46	54*	-17.54
		2412(Pk)	98.13	-	-
		2412(Av)	85.95	-	-
		4824(Pk)	47.67	74	-27.53
		4824(Av)	40.21	54	-15.27
		7236(Pk)	No Harmonics Found		
	7236(Av)	No Harmonics Found			
	Horizontal	2390(Pk)	57.98	74*	-16.02
		2390(Av)	32.87	54*	-21.13
		2412(Pk)	94.31	-	-
		2412(Av)	82.30	-	-
		4824(Pk)	46.47	74	-27.53
		4824(Av)	38.73	54	-15.27
7236(Pk)		No Harmonics Found			
7236(Av)	No Harmonics Found				
2437	Vertical	2437(Pk)	100.80	-	-
		2437(Av)	88.59	-	-
		4874(Pk)	49.16	74	-24.84
		4874(Av)	41.72	54	-12.28
		7311(Pk)	No Harmonics Found		
	7311(Av)	No Harmonics Found			
	Horizontal	2437(Pk)	95.62	-	-
		2437(Av)	82.93	-	-
		4874(Pk)	47.46	74	-26.54
		4874(Av)	39.65	54	-14.35
7311(Pk)		No Harmonics Found			
7311(Av)	No Harmonics Found				
2462	Vertical	2462(Pk)	94.71	-	-
		2462(Av)	82.94	-	-
		2483.5(Pk)	57.75	74*	-16.25
		2483.5(Av)	32.36	54*	-21.64
		4924(Pk)	49.07	74	-24.93
		4924(Av)	42.63	54	-11.37
		7386(Pk)	No Harmonics Found		
	7386(Av)	No Harmonics Found			
	Horizontal	2462(Pk)	89.09	-	-
		2462(Av)	76.99	-	-
		2483.5(Pk)	52.05	74*	-21.95
		2483.5(Av)	27.82	54*	-26.18
		4924(Pk)	47.67	74	-26.33
		4924(Av)	40.76	54	-13.24
7386(Pk)		No Harmonics Found			
7386(Av)	No Harmonics Found				

\* - Indicate restricted band of operation §15.205

Pk: Peak Detector; Av: Average Detector

**Prüfbericht - Nr.:**  
Test Report No.:

**ULR-TC56882030000049F**

Seite 124 von 170  
Page 124 of 170

**Modulation: 802.11g**  
**Data Rate: 54Mbps**

Channel Frequency (MHz)	Antenna Polarization	Measured Frequency (MHz)	Field Strength (dBµV/m)	Limit (dBµV/m)	Margin (dB)	
2412	Vertical	2390(Pk)	61.96	74*	-12.04	
		2390(Av)	35.34	54*	-18.66	
		2412(Pk)	97.44	-	-	
		2412(Av)	84.60	-	-	
		4824(Pk)	47.86	74	-27.27	
		4824(Av)	40.57	54	-14.77	
		7236(Pk)	No Harmonics Found			
		7236(Av)	No Harmonics Found			
	Horizontal	2390(Pk)	55.18	74*	-18.82	
		2390(Av)	30.24	54*	-23.76	
		2412(Pk)	91.62	-	-	
		2412(Av)	78.51	-	-	
		4824(Pk)	46.73	74	-27.27	
		4824(Av)	39.23	54	-14.77	
		7236(Pk)	No Harmonics Found			
		7236(Av)	No Harmonics Found			
2437	Vertical	2437(Pk)	98.42	-	-	
		2437(Av)	84.93	-	-	
		4874(Pk)	49.02	74	-24.98	
		4874(Av)	42.72	54	-11.28	
		7311(Pk)	No Harmonics Found			
		7311(Av)	No Harmonics Found			
	Horizontal	2437(Pk)	92.49	-	-	
		2437(Av)	79.43	-	-	
		4874(Pk)	47.05	74	-26.95	
		4874(Av)	40.37	54	-13.63	
7311(Pk)	No Harmonics Found					
7311(Av)	No Harmonics Found					
2462	Vertical	2462(Pk)	95.30	-	-	
		2462(Av)	81.58	-	-	
		2483.5(Pk)	56.02	74*	-17.98	
		2483.5(Av)	32.26	54*	-21.74	
		4924(Pk)	48.88	74	-25.12	
		4924(Av)	42.59	54	-11.41	
		7386(Pk)	No Harmonics Found			
		7386(Av)	No Harmonics Found			
	Horizontal	2462(Pk)	90.66	-	-	
		2462(Av)	77.46	-	-	
		2483.5(Pk)	51.62	74*	-22.38	
		2483.5(Av)	28.23	54*	-25.77	
		4924(Pk)	48.44	74	-25.56	
		4924(Av)	41.32	54	-12.68	
7386(Pk)	No Harmonics Found					
7386(Av)	No Harmonics Found					

\*- : Indicate restricted band of operation §15.205  
Pk: Peak Detector; Av: Average Detector

**Prüfbericht - Nr.:**

**ULR-TC56882030000049F**

Seite 125 von 170

Page 125 of 170

**Modulation: 802.11n\_HT20**

**Data Rate: MCS0**

Channel Frequency (MHz)	Antenna Polarization	Measured Frequency (MHz)	Field Strength (dBµV/m)	Limit (dBµV/m)	Margin (dB)
2412	Vertical	2390(Pk)	61.09	74*	-12.91
		2390(Av)	39.81	54*	-14.19
		2412(Pk)	98.54	-	-
		2412(Av)	86.80	-	-
		4824(Pk)	46.74	74	-27.37
		4824(Av)	39.49	54	-15.54
		7236(Pk)	No Harmonics Found		
	7236(Av)	No Harmonics Found			
	Horizontal	2390(Pk)	55.34	74*	-18.66
		2390(Av)	34.14	54*	-19.86
		2412(Pk)	92.81	-	-
		2412(Av)	81.66	-	-
		4824(Pk)	46.63	74	-27.37
		4824(Av)	38.46	54	-15.54
7236(Pk)		No Harmonics Found			
7236(Av)	No Harmonics Found				
2437	Vertical	<b>2437(Pk)</b>	<b>100.35</b>	-	-
		<b>2437(Av)</b>	<b>89.57</b>	-	-
		<b>4874(Pk)</b>	<b>48.05</b>	<b>74</b>	<b>-25.95</b>
		<b>4874(Av)</b>	<b>40.58</b>	<b>54</b>	<b>-13.42</b>
		7311(Pk)	No Harmonics Found		
	7311(Av)	No Harmonics Found			
	Horizontal	<b>2437(Pk)</b>	<b>95.37</b>	-	-
		<b>2437(Av)</b>	<b>84.47</b>	-	-
		<b>4874(Pk)</b>	<b>46.53</b>	<b>74</b>	<b>-27.47</b>
		<b>4874(Av)</b>	<b>39.04</b>	<b>54</b>	<b>-14.96</b>
7311(Pk)		No Harmonics Found			
7311(Av)	No Harmonics Found				
2462	Vertical	2462(Pk)	95.84	-	-
		2462(Av)	84.18	-	-
		2483.5(Pk)	57.93	74*	-16.07
		2483.5(Av)	36.21	54*	-17.79
		4924(Pk)	48.02	74	-25.98
		4924(Av)	41.05	54	-12.95
		7386(Pk)	No Harmonics Found		
	7386(Av)	No Harmonics Found			
	Horizontal	2462(Pk)	91.41	-	-
		2462(Av)	79.93	-	-
		2483.5(Pk)	54.94	74*	-19.06
		2483.5(Av)	31.39	54*	-22.61
		4924(Pk)	46.32	74	-27.68
		4924(Av)	38.72	54	-15.28
7386(Pk)		No Harmonics Found			
7386(Av)	No Harmonics Found				

\*- : Indicate restricted band of operation §15.205

Pk: Peak Detector; Av: Average Detector



**Prüfbericht - Nr.:**  
Test Report No.:

**ULR-TC56882030000049F**

Seite 126 von 170  
Page 126 of 170

**Modulation: 802.11n\_HT20**  
**Data Rate: MCS4**

Channel Frequency (MHz)	Antenna Polarization	Measured Frequency (MHz)	Field Strength (dBµV/m)	Limit (dBµV/m)	Margin (dB)
2412	Vertical	2390(Pk)	60.91	74*	-13.09
		2390(Av)	37.63	54*	-16.37
		2412(Pk)	97.03	-	-
		2412(Av)	85.23	-	-
		4824(Pk)	47.69	74	-27.45
		4824(Av)	40.40	54	-14.60
		7236(Pk)	No Harmonics Found		
	7236(Av)	No Harmonics Found			
	Horizontal	2390(Pk)	52.27	74*	-21.73
		2390(Av)	31.64	54*	-22.36
		2412(Pk)	90.97	-	-
		2412(Av)	78.53	-	-
		4824(Pk)	46.55	74	-27.45
		4824(Av)	39.40	54	-14.60
7236(Pk)		No Harmonics Found			
7236(Av)	No Harmonics Found				
2437	Vertical	2437(Pk)	100.18	-	-
		2437(Av)	87.20	-	-
		4874(Pk)	48.13	74	-25.87
		4874(Av)	41.48	54	-12.52
		7311(Pk)	No Harmonics Found		
	7311(Av)	No Harmonics Found			
	Horizontal	2437(Pk)	92.82	-	-
		2437(Av)	80.97	-	-
		4874(Pk)	47.28	74	-26.72
		4874(Av)	39.84	54	-14.16
7311(Pk)		No Harmonics Found			
7311(Av)	No Harmonics Found				
2462	Vertical	2462(Pk)	94.64	-	-
		2462(Av)	82.41	-	-
		2483.5(Pk)	54.58	74*	-19.42
		2483.5(Av)	33.57	54*	-20.43
		4924(Pk)	48.96	74	-25.04
		4924(Av)	42.18	54	-11.82
		7386(Pk)	No Harmonics Found		
	7386(Av)	No Harmonics Found			
	Horizontal	2462(Pk)	90.82	-	-
		2462(Av)	78.08	-	-
		2483.5(Pk)	49.44	74*	-24.56
		2483.5(Av)	29.88	54*	-24.12
		4924(Pk)	46.62	74	-27.38
		4924(Av)	39.62	54	-14.38
7386(Pk)		No Harmonics Found			
7386(Av)	No Harmonics Found				

\* - : Indicate restricted band of operation §15.205  
Pk: Peak Detector; Av: Average Detector

**Prüfbericht - Nr.:**  
Test Report No.:

**ULR-TC56882030000049F**

Seite 127 von 170  
Page 127 of 170

**Modulation: 802.11n\_HT20**  
**Data Rate: MCS7**

Channel Frequency (MHz)	Antenna Polarization	Measured Frequency (MHz)	Field Strength (dBµV/m)	Limit (dBµV/m)	Margin (dB)
2412	Vertical	2390(Pk)	98.80	74*	24.80
		2390(Av)	84.50	54*	30.50
		2412(Pk)	63.95	-	-
		2412(Av)	36.83	-	-
		4824(Pk)	47.90	74	-26.10
		4824(Av)	40.13	54	-13.87
		7236(Pk)	No Harmonics Found		
	7236(Av)	No Harmonics Found			
	Horizontal	2390(Pk)	57.02	74*	-16.98
		2390(Av)	32.19	54*	-21.81
		2412(Pk)	93.04	-	-
		2412(Av)	78.91	-	-
		4824(Pk)	46.95	74	-27.05
		4824(Av)	39.41	54	-14.59
7236(Pk)		No Harmonics Found			
7236(Av)	No Harmonics Found				
2437	Vertical	2437(Pk)	97.14	-	-
		2437(Av)	82.63	-	-
		4874(Pk)	48.18	74	-25.82
		4874(Av)	42.01	54	-11.99
		7311(Pk)	No Harmonics Found		
	7311(Av)	No Harmonics Found			
	Horizontal	2437(Pk)	92.70	-	-
		2437(Av)	78.78	-	-
		4874(Pk)	47.27	74	-26.73
		4874(Av)	40.10	54	-13.90
7311(Pk)		No Harmonics Found			
7311(Av)	No Harmonics Found				
2462	Vertical	2462(Pk)	95.94	-	-
		2462(Av)	81.52	-	-
		2483.5(Pk)	59.56	74*	-14.44
		2483.5(Av)	33.09	54*	-20.91
		4924(Pk)	48.34	74	-25.66
		4924(Av)	42.38	54	-11.62
		7386(Pk)	No Harmonics Found		
	7386(Av)	No Harmonics Found			
	Horizontal	2462(Pk)	91.05	-	-
		2462(Av)	77.28	-	-
		2483.5(Pk)	53.91	74*	-20.09
		2483.5(Av)	29.61	54*	-24.39
		4924(Pk)	47.01	74	-26.99
		4924(Av)	40.02	54	-13.98
7386(Pk)		No Harmonics Found			
7386(Av)	No Harmonics Found				

\*- : Indicate restricted band of operation §15.205  
Pk: Peak Detector; Av: Average Detector

**Prüfbericht - Nr.:**  
Test Report No.:

**ULR-TC56882030000049F**

Seite 128 von 170  
Page 128 of 170

**Modulation: 802.11n\_HT40**  
**Data Rate: MCS0**

Channel Frequency (MHz)	Antenna Polarization	Measured Frequency (MHz)	Field Strength (dBµV/m)	Limit (dBµV/m)	Margin (dB)	
2422	Vertical	2390(Pk)	61.25	74*	-12.75	
		2390(Av)	39.74	54*	-14.26	
		2422(Pk)	93.31	-	-	
		2422(Av)	80.81	-	-	
		4844(Pk)	46.93	74	-27.07	
		4844(Av)	39.22	54	-14.78	
		7266(Pk)	No Harmonics Found			
		7266(Av)	No Harmonics Found			
	Horizontal	2390(Pk)	54.91	74*	-19.09	
		2390(Av)	34.84	54*	-19.16	
		2422(Pk)	88.45	-	-	
		2422(Av)	76.36	-	-	
		4844(Pk)	46.76	74	-27.24	
		4844(Av)	39.40	54	-14.60	
7266(Pk)		No Harmonics Found				
7266(Av)		No Harmonics Found				
2452	Vertical	2452(Pk)	92.55	-	-	
		2452(Av)	79.85	-	-	
		2483.5(Pk)	56.41	74*	-17.59	
		2483.5(Av)	35.69	54*	-18.31	
		4904(Pk)	48.37	74	-25.63	
		4904(Av)	41.68	54	-12.32	
		7356(Pk)	No Harmonics Found			
		7356(Av)	No Harmonics Found			
	Horizontal	2452(Pk)	86.88	-	-	
		2452(Av)	74.65	-	-	
		2483.5(Pk)	51.45	74*	-22.55	
		2483.5(Av)	31.07	54*	-22.93	
		4904(Pk)	44.71	74	-29.29	
		4904(Av)	36.08	54	-17.92	
7356(Pk)		No Harmonics Found				
7356(Av)		No Harmonics Found				

\*- : Indicate restricted band of operation §15.205  
Pk: Peak Detector; Av: Average Detector

**Prüfbericht - Nr.:**  
Test Report No.:

**ULR-TC56882030000049F**

Seite 129 von 170  
Page 129 of 170

**Modulation: 802.11n\_HT40**  
**Data Rate: MCS4**

Channel Frequency (MHz)	Antenna Polarization	Measured Frequency (MHz)	Field Strength (dBµV/m)	Limit (dBµV/m)	Margin (dB)
2422	Vertical	2390(Pk)	59.06	74*	-14.94
		2390(Av)	38.72	54*	-15.28
		2422(Pk)	92.33	-	-
		2422(Av)	78.48	-	-
		4844(Pk)	47.80	74	-26.20
		4844(Av)	41.04	54	-12.96
		7266(Pk)	No Harmonics Found		
	7266(Av)	No Harmonics Found			
	Horizontal	2390(Pk)	54.20	74*	-19.80
		2390(Av)	34.57	54*	-19.43
		2422(Pk)	88.02	-	-
		2422(Av)	73.39	-	-
		4844(Pk)	47.42	74	-26.58
		4844(Av)	39.59	54	-14.41
7266(Pk)		No Harmonics Found			
7266(Av)	No Harmonics Found				
2452	Vertical	2452(Pk)	91.49	-	-
		2452(Av)	76.79	-	-
		2483.5(Pk)	53.83	74*	-20.17
		2483.5(Av)	33.33	54*	-20.67
		4904(Pk)	48.65	74	-25.35
		4904(Av)	42.23	54	-11.77
		7356(Pk)	No Harmonics Found		
	7356(Av)	No Harmonics Found			
	Horizontal	2452(Pk)	87.39	-	-
		2452(Av)	72.59	-	-
		2483.5(Pk)	47.52	74*	-26.48
		2483.5(Av)	29.88	54*	-24.12
		4904(Pk)	47.18	74	-26.82
		4904(Av)	39.82	54	-14.18
7356(Pk)		No Harmonics Found			
7356(Av)	No Harmonics Found				

\*- : Indicate restricted band of operation §15.205  
Pk: Peak Detector; Av: Average Detector

**Prüfbericht - Nr.:**  
Test Report No.:

**ULR-TC56882030000049F**

Seite 130 von 170  
Page 130 of 170

**Modulation: 802.11n\_HT40**

**Data Rate: MCS7**


Channel Frequency (MHz)	Antenna Polarization	Measured Frequency (MHz)	Field Strength (dBµV/m)	Limit (dBµV/m)	Margin (dB)	
2422	Vertical	2390(Pk)	61.44	74*	-12.56	
		2390(Av)	38.25	54*	-15.75	
		2422(Pk)	92.95	-	-	
		2422(Av)	76.94	-	-	
		4844(Pk)	48.28	74	-25.72	
		4844(Av)	40.97	54	-13.03	
		7266(Pk)	No Harmonics Found			
		7266(Av)	No Harmonics Found			
	Horizontal	2390(Pk)	88.03	74*	14.03	
		2390(Av)	71.92	54*	17.92	
		2422(Pk)	55.07	-	-	
		2422(Av)	34.08	-	-	
		4844(Pk)	47.09	74	-26.91	
		4844(Av)	39.53	54	-14.47	
7266(Pk)		No Harmonics Found				
7266(Av)		No Harmonics Found				
2452	Vertical	2452(Pk)	89.83	-	-	
		2452(Av)	74.05	-	-	
		2483.5(Pk)	57.74	74*	-16.26	
		2483.5(Av)	33.22	54*	-20.78	
		4904(Pk)	48.98	74	-25.02	
		4904(Av)	42.03	54	-11.97	
		7356(Pk)	No Harmonics Found			
		7356(Av)	No Harmonics Found			
	Horizontal	2452(Pk)	86.46	-	-	
		2452(Av)	71.01	-	-	
		2483.5(Pk)	52.40	74*	-21.60	
		2483.5(Av)	29.31	54*	-24.69	
		4904(Pk)	47.11	74	-26.89	
		4904(Av)	39.99	54	-14.01	
7356(Pk)		No Harmonics Found				
7356(Av)		No Harmonics Found				

\* - : Indicate restricted band of operation §15.205  
Pk: Peak Detector; Av: Average Detector

**Worst case Plots**


**Data Rate: 11Mbps**

**Channel Frequency 2412MHz**




Channel Frequency: 2412MHz

Polarization: Vertical




Channel Frequency: 2412MHz

Polarization: Horizontal




Channel Frequency: 1 - 18 GHz

Polarization: Vertical




Channel Frequency: 1 - 18 GHz

Polarization: Horizontal



Channel Frequency: 2nd Harmonics

Polarization: Vertical




Channel Frequency: 2nd Harmonics

Polarization: Horizontal




Data Rate: MCS0\_n Mode 20MHz

Channel Frequency 2437MHz




Channel Frequency: 2437MHz

Polarization: Vertical




Channel Frequency: 2437MHz

Polarization: Horizontal




Channel Frequency: 1 - 18 GHz

Polarization: Vertical




Channel Frequency: 1 - 18 GHz

Polarization: Horizontal



Channel Frequency: 2nd Harmonics

Polarization: Vertical




Channel Frequency: 2nd Harmonics

Polarization: Horizontal


Data Rate: 11 Mbps

Channel Frequency 2462MHz




Channel Frequency: 2462MHz

Polarization: Vertical




Channel Frequency: 2462MHz

Polarization: Horizontal




Channel Frequency: 1 - 18 GHz

Polarization: Vertical




Channel Frequency: 1 - 18 GHz

Polarization: Horizontal



Channel Frequency: 18 - 40 GHz

Polarization: Vertical



Channel Frequency: 18 - 40 GHz

Polarization: Horizontal

**Prüfbericht - Nr.:**  
Test Report No.:


**ULR-TC568820300000049F**

Seite 140 von 170  
Page 140 of 170

## 7 TEST RESULTS FOR BLUETOOTH LOW ENERGY

### 7.1 Maximum Peak Conducted Output Power

<b>Result</b>	<b>Pass</b>
Test Specification	FCC part 15 Subpart C 15.247 (b)(3) / RSS 247 Issue 2, Section 5.4 (d)
Test Method	Subclause 11.9.1.1 of ANSI C63.10
Measurement Bandwidth	300 kHz
Detector	Peak
Port of testing	Antenna port
Requirement	Power ≤ 1 W (30 dBm) & e.i.r.p ≤ 4 W (36 dBm)



#### Test Condition

##### Normal Test Condition:

Temperature (Norm) = + 25 °C

Voltage = 3.6V DC Li-Ion battery

Relative humidity: 62%

#### KDB Guidelines applied:

Measurements were made as per section 8.3.1 in KDB 558074 D01 15.247 Measurement Guidance v05r02.

**Prüfbericht - Nr.:**  
Test Report No.:

**ULR-TC56882030000049F**


Seite 141 von 170  
Page 141 of 170

**Test results:**

**Note:**


1. All the losses are included during measurement and final values are mentioned in the test report.
2. Total Peak Output power (dBm) = Measured Peak power (dBm) + Attenuator factor (10dB) + Cable loss (0.6dB)
3. This product do not support additional beamforming gain / directional gain, it uses signal antenna and hence directional gain of the single antenna is 2.53 dBi
4. Maximum (e.i.r.p) = Maximum Peak output power (dBm) + antenna gain (2.53 dBi)

Data Rate (Mbps)	Channel Frequency (MHz)	Power Limit (dBm)	Maximum Peak Conducted Output Power (dBm)	Maximum (e.i.r.p)	Limit (e.i.r.p)
1	2402	30	4.42	6.95	36
	2440	30	4.97	7.50	36
	2480	30	5.08	7.61	36




Channel Frequency: 2402MHz





Channel Frequency: 2440MHz



Channel Frequency: 2480MHz

**Prüfbericht - Nr.:**  
Test Report No.:

**ULR-TC56882030000049F**

Seite 143 von 170  
Page 143 of 170


## 7.2 Maximum Power Spectral Density

### Result

### Pass

Test Specification	FCC part 15 Subpart C 15.247 (e) / RSS 247 Issue 2, Section 5.2 (b)
Test Method	Subclause 11.10.2 of ANSI C63.10
Measurement Bandwidth	3 kHz
Detector	Peak detector
Port of testing	Antenna port
Requirement	For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm

#### Test Method:



#### Test Condition

##### Normal Test Condition:

Temperature (Norm) = + 25°C

Voltage = 3.6V DC Li-Ion battery

Relative humidity: 62 %

#### KDB Guidelines applied:


Measurements were made as per section 8.4 in KDB 558074 D01 15.247 Measurement Guidance v05r02.

**Test results:**


**Note:**

1. All the losses are included during measurement and final values are mentioned in the test report.
2. Total Peak PSD (dBm) = Measured Peak PSD (dBm) + Attenuator factor (10dB) + Cable loss (0.6dB)
3. This product do not support additional beamforming gain / directional gain, it uses signal antenna and hence directional gain of the single antenna is 2.53 dBi


Data Rate (Mbps)	Channel Frequency (MHz)	Maximum Peak PSD (dBm/3kHz)	Limit (dBm/3kHz)
1	2402	-10.97	8
	2440	-10.48	8
	2480	-10.66	8



Channel Frequency: 2402MHz



Channel Frequency: 2440MHz



Channel Frequency: 2480MHz

**Prüfbericht - Nr.:**  
Test Report No.:

**ULR-TC568820300000049F**

Seite 146 von 170  
Page 146 of 170


### 7.3 DTS Bandwidth

**Result**

**Pass**

Test Specification	FCC part 15 Subpart C 15.247 (a) (2) / RSS 247 Issue 2, Section 5.2 (a)
Test Method	Subclause 11.8 of ANSI C63.10
Measurement Bandwidth	100 kHz
Detector	Peak
Port of testing	Antenna port
Requirement	The minimum 6 dB bandwidth shall be at least 500 kHz

**Test Method:**



**Test Condition**

**Normal Test Condition:**

Temperature (Norm) = + 25 °C      Voltage = 3.6V DC Li-Ion battery      Relative humidity: 62 %

**KDB Guidelines applied:**

Measurements were made as per section 8.2 in KDB 558074 D01 15.247 Measurement Guidance v05r02.

**Prüfbericht - Nr.:**  
Test Report No.:

**ULR-TC56882030000049F**


Seite 147 von 170  
Page 147 of 170

**Test results:**


**Note:**

1. All the losses are included during measurement and final values are mentioned in the test report.


Data Rate (Mbps)	Channel Frequency (MHz)	6 dB Bandwidth (MHz)	99% OBW (MHz)	Minimum Limit (MHz)
1	2402	730.34	1.062	0.5
	2440	739.96	1.057	0.5
	2480	736.28	1.056	0.5



Channel Frequency: 2402MHz



Channel Frequency: 2440MHz



Channel Frequency: 2480MHz


## 7.4 Emissions in non-restricted frequency bands and Conducted Spurious Emission

**Result**

**Pass**

Test Specification	FCC part 15 Subpart C 15.247 (d) / RSS 247 Issue 2, Section 5.5
Test Method	Subclause 11.11 of ANSIC63.10
Measurement Bandwidth	100 kHz
Detector	Peak
Port of testing	Antenna port
Requirement	In any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 30dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits

**Test Method:**



**Test Condition**

**Normal Test Condition:**

Temperature (Norm) = +25 °C      Voltage = 3.6V DC Li-Ion battery      Relative humidity: 62 %

**KDB Guidelines applied:**

Measurements were made as per section 8.5 in KDB 558074 D01 15.247 Measurement Guidance v05r02.



**Prüfbericht - Nr.:**  
Test Report No.:

**ULR-TC56882030000049F**

Seite 150 von 170  
Page 150 of 170


**Test results:**

**Note:**


1. All the losses are included during measurement and final values are mentioned in the test report.
2. Final Value (dBm) = Measured Value (dBm) + Attenuator factor (10dB) + Cable loss (0.6dB)
3. This product do not support additional beamforming gain / directional gain, it uses signal antenna and hence directional gain of the single antenna is 2.53 dBi

**7.4.1 Band edge and reference plots**


Data Rate (Mbps)	Channel Frequency (MHz)	Reference Value (B) (dBm)	Band edge Frequency (MHz)	Value at Band edge (A) (dBm)	A-B (dBC)	Minimum Limit (dBm)
1	2402	3.89	2399	-50.17	-54.06	-20
	2480	4.43	2483.5	-51.5	-55.93	-20




Reference Plot for Channel Frequency 2402MHz



Reference Plot for Channel Frequency 2480MHz




Channel Frequency: 2402MHz




Channel Frequency: 2480MHz


### 7.4.2 Out-Of-Band Emissions



Frequency Range 9KHz – 1MHz




Frequency Range 1MHz – 30MHz



Channel Frequency 2402MHz


Frequency Range 30MHz – 1GHz

Data Rate (Mbps)	Channel Frequency (MHz)	Value at the Band Edge		Reference Value B (dBm)	Band Edge Value A-B (dBc)	Limit (dBm)
		Frequency (GHz)	Value A (dBm)			
1	2402	13.68	-41.32	3.89	-45.21	-20
	2480	13.68	-41.85	4.43	-46.28	-20




Channel Frequency 2402MHz

Frequency Range 1GHz – 26.5GHz



Channel Frequency 2440MHz

Frequency Range 1GHz – 26.5GHz



Channel Frequency 2480MHz

Frequency Range 1GHz – 26.5GHz

## 7.5 Spurious Radiated Emissions & Restricted Bands of Operation

<b>Result</b>	<b>Pass</b>
Test Specification	FCC part 15 Subpart C 15.247 (d) / (15.209 & 15.205) / IC RSS-GEN, Section 8.9 and 8.10
Test Method	ANSI C63.10
Measurement Location	Semi Anechoic Chamber 30MHz - 1 GHz Fully Anechoic Chamber 1 GHz - 40GHz
Measurement Bandwidth	100 kHz for frequency range < 1GHz 1 MHz for Frequency range >1GHz
Detector	Refer remarks below
Measuring Distance	3 m
Requirement	As per the limits mentioned in the below table
Test setup	Refer TEST METHODOLOGY

**Table 8: Transmitter limits for Radiated emission**

Frequency (MHz)	Field strength ( $\mu\text{V}/\text{m}$ )	Field strength ( $\text{dB}\mu\text{V}/\text{m}$ )	Distance of Measurement (m)
0.009 – 0.490	2400/F(kHz)	48.50 – 13.80	300*
0.490 – 1.705	24000/F(kHz)	33.80 – 23.00	30*
1.705 -30	30	29.54	30*
30-88	100	40.0	3
88-216	150	43.5	3
216-960	200	46.0	3
Above 960	500	54.0	3

Remark: \* The limit shows in the table above of frequency range 0.009 – 0.490, 0.490 – 1.705 MHz and 1.705-30MHz is at 300 meter, 30 meter and 30 meter range respectively, which corresponds to 128.51 – 93.80, 73.80 – 62.96 and 69.54  $\text{dB}\mu\text{V}/\text{m}$  at 3m range by extrapolation calculation and the measurement of loop antenna.

The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz Radiated emission limits in these three bands are based on measurements employing an average detector.

### Test Conditions:

Temperature (Norm) = + 25 °C

Voltage = 3.6V DC Li-Ion battery

Relative humidity = 62 %

**Prüfbericht - Nr.:**  
Test Report No.:

**ULR-TC56882030000049F**

Seite 157 von 170  
Page 157 of 170

**Test results:**

Note: All the losses are included during measurement and final values are mentioned in the test report. Refer TEST METHODOLOGY for more details


**Test results for frequency range 9kHz – 30MHz**

No emissions found in frequency range 9 kHz to 30 MHz, and measured levels are below 20dB from the limit line, hence not reported

**Test results for frequency range 30MHz – 1GHz**

**Mode of Operation: Curved Mode**


Polarization	Frequency (MHz)	Measured value (dBµV/m)	Limit (dBµV/m)	Margin (dB)
Vertical	34.00	22.71	40	-17.29
	51.91	22.06	40	-17.94
	60.47	22.95	40	-17.05
	228.80	24.23	46	-21.77
	274.20	18.21	46	-27.79
	900.00	38.52	46	-7.48
Horizontal	33.76	17.41	40	-22.59
	52.28	18.19	40	-21.81
	169.40	14.24	43.5	-29.26
	299.93	20.33	46	-25.67
	500.00	25.90	46	-20.10
	900.06	34.38	46	-11.62



**Channel Frequency 30MHz – 200MHz**


**Polarization Vertical**






**Channel Frequency 30MHz – 200MHz**

**Polarization Horizontal**



**Channel Frequency 200MHz – 1GHz**

**Polarization Vertical**




Channel Frequency 200MHz – 1GHz

Polarization Horizontal


**Mode of Operation: Linear Mode:**

Polarization	Frequency (MHz)	Measured value (dBµV/m)	Limit (dBµV/m)	Margin (dB)
Vertical	47.72	10.78	40	-29.22
	61.81	10.22	40	-29.78
	83.73	17.40	43.5	-26.10
	499.98	22.58	46	-23.42
	700.02	24.97	46	-21.03
	900.00	37.79	46	-8.21
Horizontal	34.85	10.32	40	-29.68
	48.45	10.60	40	-29.40
	67.46	9.31	40	-30.69
	300.01	18.42	46	-27.58
	499.98	26.15	46	-19.85
	900.00	30.23	46	-15.77




Channel Frequency 30MHz – 200MHz

Polarization Vertical




Channel Frequency 30MHz – 200MHz

Polarization Horizontal



Channel Frequency 200MHz – 1GHz

Polarization Vertical



Channel Frequency 200MHz – 1GHz


Polarization Horizontal

Test results for the frequencies above 1GHz

Channel Frequency (MHz)	Antenna Polarization	Measured Frequency (MHz)	Field Strength (dBµV/m)	Limit (dBµV/m)	Margin (dB)
2402	V	2390(Pk)	41.74	74*	-32.26
		2390(Av)	25.67	54*	-28.33
		2402(Pk)	92.79	-	-
		2402(Av)	91.88	-	-
		4804(Pk)	46.12	74	-27.94
		4804(Av)	38.44	54	-16.12
		7206(Pk)	No Harmonics Found		
	7206(Av)				
	H	2390(Pk)	36.41	74*	-37.59
		2390(Av)	24.76	54*	-29.24
		2402(Pk)	90.78	-	-
		2402(Av)	89.86	-	-
		4804(Pk)	46.06	74	-27.94
		4804(Av)	37.88	54	-16.12
7206(Pk)		No Harmonics Found			
7206(Av)					
2440	V	<b>2440(Pk)</b>	<b>94.08</b>	-	-
		<b>2440(Av)</b>	<b>93.20</b>	-	-
		<b>4880(Pk)</b>	<b>53.50</b>	<b>74</b>	<b>-20.5</b>
		<b>4880(Av)</b>	<b>48.58</b>	<b>54</b>	<b>-5.42</b>
		<b>7320(Pk)</b>	No Harmonics Found		
	<b>7320(Av)</b>				
	H	<b>2440(Pk)</b>	<b>91.58</b>	-	-
		<b>2440(Av)</b>	<b>90.71</b>	-	-
		<b>4880(Pk)</b>	<b>52.54</b>	<b>74</b>	<b>-21.46</b>
		<b>4880(Av)</b>	<b>47.47</b>	<b>54</b>	<b>-6.53</b>
<b>7320(Pk)</b>		No Harmonics Found			
<b>7320(Av)</b>					
2480	V	2480(Pk)	92.63	-	-
		2480(Av)	91.71	-	-
		2483.5(Pk)	39.12	74*	-34.88
		2483.5(Av)	27.43	54*	-26.57
		4960(Pk)	54.74	74	-19.26
		4960(Av)	49.57	54	-4.43
		7440(Pk)	No Harmonics Found		
	7440(Av)				
	H	2480(Pk)	90.24	-	-
		2480(Av)	89.31	-	-
		2483.5(Pk)	38.19	74*	-35.81
		2483.5(Av)	25.84	54*	-28.16
		4960(Pk)	54.14	74	-19.86
		4960(Av)	49.03	54	-4.97
7440(Pk)		No Harmonics Found			
7440(Av)					


\*- : Indicate restricted band of operation §15.205  
Pk: Peak Detector; Av: Average Detector

**Worst case Plots**  
**Channel Frequency 2440MHz**




Channel Frequency: 2462MHz

Polarization: Vertical




Channel Frequency: 2462MHz

Polarization: Horizontal




Channel Frequency: 1-18GHz

Polarization: Vertical




Channel Frequency: 1-18GHz

Polarization: Horizontal



Channel Frequency: 2nd Harmonics


Polarization: Vertical



Channel Frequency: 2nd Harmonics


Polarization: Horizontal





Channel Frequency: 18 - 40 GHz

Polarization: Vertical



Channel Frequency: 18 - 40 GHz

Polarization: Horizontal

**Prüfbericht - Nr.:**  
Test Report No.:

**ULR-TC56882030000049F**

Seite 167 von 170  
Page 167 of 170

## 8 Conducted Spurious Emission Test on AC Power Line

**Result**

**Pass**

Test Specification : FCC Part 15 Section 15.207 / RSS Gen Issue 5 Section 8.8  
 Test Method : ANSI C 63.10-2013  
 Testing Location : Screened room  
 Measurement Bandwidth : 9kHz  
 Frequency Range : 150kHz – 30MHz  
 Supply Voltage : 110VAC,60Hz  
 Test Method : Refer TEST METHODOLOGY

**\*Note: The product has tested with AC to DC adapter and Wireless Qi charger**

**Limits of section 15.207**

Frequency of emission (MHz)	QP Limit (dBµV)	AV Limit (dBµV/m)
0.15 – 0.5	66 – 56*	56 – 46*
0.5 – 5	56	46
5 – 30	60	50


\* Decreases with the logarithm of the frequency

**Test Conditions:**

Normal Temperature = +24°C      Voltage (V norm) = 110V AC (Through AC to DC Adapter and Qi Charger)  
 RH = 64 %

**Test result:**

**Power: 110V 60HZ\_LINE**




**Line Graph**

Trace	Frequency	Level (dBµV)	Phase	Detector	Delta Limit/dB
1	158.00000000 kHz	46.94		Quasi Peak	-18.63
1	182.00000000 kHz	43.09		Quasi Peak	-21.30
2	17.81000000 MHz	22.47		Average	-27.53
2	16.69400000 MHz	20.24		Average	-29.76
2	15.58200000 MHz	20.08		Average	-29.92
2	17.25000000 MHz	20.05		Average	-29.95
2	17.53000000 MHz	19.90		Average	-30.10
2	16.13800000 MHz	19.81		Average	-30.19
2	16.97400000 MHz	19.57		Average	-30.43
2	18.08600000 MHz	19.45		Average	-30.55
1	16.69400000 MHz	28.89		Quasi Peak	-31.11
1	15.86200000 MHz	28.82		Quasi Peak	-31.18
1	16.41800000 MHz	28.44		Quasi Peak	-31.56
1	16.97400000 MHz	28.30		Quasi Peak	-31.70
1	18.08600000 MHz	28.04		Quasi Peak	-31.96

**Line Table**

Power: 110V60HZ\_NEUTRAL



Line Graph

Trace	Frequency	Level (dBµV)	Phase	Detector	Delta Limit/dB
1	298.000000000 kHz	43.13		Quasi Peak	-17.17
1	16.602000000 MHz	33.17		Quasi Peak	-26.83
1	150.000000000 kHz	38.64		Quasi Peak	-27.36
1	174.000000000 kHz	36.20		Quasi Peak	-28.57
2	16.870000000 MHz	18.16		Average	-31.84
2	15.798000000 MHz	16.87		Average	-33.13
2	16.066000000 MHz	16.86		Average	-33.14
2	17.138000000 MHz	16.82		Average	-33.18
2	16.334000000 MHz	16.64		Average	-33.36
2	17.406000000 MHz	16.53		Average	-33.47
2	17.942000000 MHz	16.45		Average	-33.55
2	17.674000000 MHz	16.29		Average	-33.71
1	16.870000000 MHz	25.85		Quasi Peak	-34.15
1	15.798000000 MHz	24.99		Quasi Peak	-35.01
1	17.406000000 MHz	24.06		Quasi Peak	-35.94
1	21.958000000 MHz	18.52		Quasi Peak	-41.48

Line Table

## 9 LIST OF TABLES

Table 1: List of test and measurement instruments.....	6
Table 2: Instrument application Software versions.....	6
Table 3: Ratings and System Details as declared by Client*.....	7
Table 4: Measurement Uncertainty .....	8
Table 5: List of Wi-Fi center Frequencies .....	11
Table 6: List of BLE Center frequencies.....	11
Table 7: Transmitter limits for Radiated emission .....	114
Table 8: Transmitter limits for Radiated emission .....	156

\*\*\*\*\*END OF TEST REPORT\*\*\*\*\*