

## TEST REPORT

**Report No.: HK13020622-1**

**Goldie Marketing Pty. Ltd.**

Application  
For  
Certification

(Original Grant)

**(FCC ID: YPS-RCIS201349T)**

Transmitter

Prepared and Checked by:

Signed On File  
Wong Cheuk Ho, Herbert  
Lead Engineer

Approved by:

---

Chan Chi Hung, Terry  
Assistant Supervisor  
Date: April 05, 2013

- The test report only allows to be revised within the retention period unless further standard or the requirement was noticed.
- This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

# INTERTEK TESTING SERVICES

---

## GENERAL INFORMATION

**Goldie Marketing Pty. Ltd.**

**BRAND NAME: Smurf 5in R/C Vehicle Assortment, MODEL: SMR015**

**FCC ID: YPS-RCIS201349T**

|                           |  |
|---------------------------|--|
| Grantee:                  | Goldie Marketing Pty. Ltd.   |
| Grantee Address:          | Unit 6A, 841 Mountain Highway,<br>Bayswater VIC 3153, Melbourne,<br>Australia. |
| Contact Person:           | Mr. Stephen Goldsworthy  |
| Tel:                      | 61-3-97206186  |
| Fax:                      | 61-3-97202659  |
| Brand Name:               | Smurf 5in R/C Vehicle Assortment   |
| Model:                    | SMR015   |
| Additional Model:         | SMR012   |
| Asst. No.:                | SMR010   |
| Type of EUT:              | Transmitter  |
| Description of EUT:       | Smurf 5in RC Gargamobile (SMR015)<br>Smurf 5in RC Leaf Coupe (SMR012)          |
| Serial Number:            | N/A  |
| FCC ID:                   | YPS-RCIS201349T  |
| Date of Sample Submitted: | February 25, 2013  |
| Date of Test:             | February 25, 2013 to March 13, 2013  |
| Report No.:               | HK13020622-1   |
| Report Date:              | April 05, 2013   |
| Environmental Conditions: | Temperature: +10 to 40°C<br>Humidity: 10 to 90%                                |

# INTERTEK TESTING SERVICES

---

## SUMMARY OF TEST RESULT

**Goldie Marketing Pty. Ltd.**

**BRAND NAME: Smurf 5in R/C Vehicle Assortment, MODEL: SMR015**

**FCC ID: YPS-RCIS201349T**

| TEST SPECIFICATION   | REFERENCE                     | RESULTS |
|--|-------------------------------|---------|
| Maximum Peak Output Power                                    | 15.247(b), (c) / RSS-210 A8.4 | N/A     |
| Hopping Channel Carrier Frequencies Separation               | 15.247(e) / RSS-210 A8.1      | N/A     |
| 20dB Bandwidth of the Hopping Channel                        | 15.247(a) / RSS-210 A8.1      | N/A     |
| Number of Hopping Frequencies                                | 15.247(e) / RSS-210 A8.1      | N/A     |
| Average Time of Occupancy of Hopping Frequency               | 15.247(e) / RSS-210 A8.1      | N/A     |
| Antennae Conducted Spurious Emissions                        | 15.247(d) / RSS-210 A8.5      | N/A     |
| Radiated Spurious Emissions                                  | 15.247(d) / RSS-210 A8.5      | N/A     |
| RF Exposure Compliance                                       | 15.247(i) / RSS-Gen 5.5       | N/A     |
| Transmitter Power Line Conducted Emissions                   | 15.207 / RSS-Gen 7.2.2        | N/A     |
| Transmitter Field Strength                                   | 15.227 / RSS-310 3.8          | N/A     |
| Transmitter Field Strength                                   | 15.229 / RSS-210 A2.7         | N/A     |
| Transmitter Field Strength, Bandwidth and Timing Requirement | 15.231(a) / RSS-210 A1.1.1    | N/A     |
| Transmitter Field Strength, Bandwidth and Timing Requirement | 15.231(e) / RSS-210 A1.1.5    | N/A     |
| Transmitter Field Strength and Bandwidth Requirement         | 15.239 / RSS-210 A2.8         | N/A     |
| Transmitter Field Strength and Bandwidth Requirement         | 15.249 / RSS-210 A2.9         | N/A     |
| Transmitter Field Strength and Bandwidth Requirement         | 15.235 / RSS-310 3.9          | Pass    |
| Receiver / Digital Device Radiated Eissions                  | 15.109 / ICES-003             | N/A     |
| Digital Device Conducted Emissions                           | 15.107 / ICES-003             | N/A     |

Note:

1. The EUT uses a permanently attached antenna which, in accordance to section 15.203, is considered sufficient to comply with the provisions of this section.
2. Pursuant to FCC part 15 Section 15.215(c), the 20 dB bandwidth of the emission was contained within the frequency band designated (mentioned as above) which the EUT operated. The effects, if any, from frequency sweeping, frequency hopping, other modulation techniques and frequency stability over excepted variations in temperature and supply voltage were considered.

# INTERTEK TESTING SERVICES

---

---

## Table of Contents

|            |  |    |
|------------|--|----|
| <b>1.0</b> | <b><u>General Description</u></b>          | 1  |
| 1.1        | Product Description                        | 1  |
| 1.2        | Related Submittal(s) Grants                | 1  |
| 1.3        | Test Methodology                           | 1  |
| 1.4        | Test Facility                              | 1  |
| <b>2.0</b> | <b><u>System Test Configuration</u></b>    | 2  |
| 2.1        | Justification                              | 2  |
| 2.2        | EUT Exercising Software                    | 2  |
| 2.3        | Special Accessories                        | 2  |
| 2.4        | Equipment Modification                     | 2  |
| 2.5        | Measurement Uncertainty                    | 2  |
| 2.6        | Support Equipment List and Description     | 3  |
| <b>3.0</b> | <b><u>Emission Results</u></b>             | 3  |
| 3.1        | Field Strength Calculation                 | 3  |
| 3.2        | Radiated Emission Configuration Photograph | 4  |
| 3.3        | Radiated Emission Data                     | 4  |
| <b>4.0</b> | <b><u>Equipment Photographs</u></b>        | 6  |
| <b>5.0</b> | <b><u>Product Labelling</u></b>            | 6  |
| <b>6.0</b> | <b><u>Technical Specifications</u></b>     | 6  |
| <b>7.0</b> | <b><u>Instruction Manual</u></b>           | 6  |
| <b>8.0</b> | <b><u>Miscellaneous Information</u></b>    | 6  |
| 8.1        | Measured Bandwidth                         | 6  |
| 8.2        | Discussion of Pulse Desensitization        | 7  |
| 8.3        | Calculation of Average Factor              | 7  |
| 8.4        | Emissions Test Procedures                  | 8  |
| <b>9.0</b> | <b><u>Equipment List</u></b>               | 10 |

# INTERTEK TESTING SERVICES

---

## 1.0 General Description

### 1.1 Product Description

The Equipment Under Test (EUT) is a transmitter of a RC Car operating at 49.860 MHz as dictated by a crystal. The EUT is powered by a 3.0 V DC source (2 x 1.5V AAA batteries). The EUT has a forward, backward, left and right control buttons.

After switching ON the EUT and the receiver of the RC Car, activating the control levers on the EUT can control the receiver moving forward, backward left and right.

The Model: SMR012 is the same as the Model: SMR015 in hardware aspect. The difference in character and the outlook only.

Antenna Type : External, Integral

For electronic filing, the brief circuit description is saved with filename: descri.pdf.

### 1.2 Related Submittal(s) Grants

The Certification procedure of receiver (with FCC ID: YPS-RCIS201349R) for this transmitter (with FCC ID: YPS-RCIS201349T) is being processed as the same time of this application.

### 1.3 Test Methodology

Radiated emission measurements was performed according to the procedures in ANSI C63.4 (2009). All radiated measurements were performed in an Open Area Test Site. Preliminary scans were performed in the Open Area Test Site only to determine worst case modes. All radiated tests were performed at an antenna to EUT distance of 3 meters, unless stated otherwise in the “**Justification Section**” of this Application.

### 1.4 Test Facility

The open area test site and conducted measurement facility used to collect the radiated data is located at Garment Centre, 576 Castle Peak Road, Kowloon, Hong Kong. This test facility and site measurement data have been placed on file with the FCC.

## INTERTEK TESTING SERVICES

---

### 2.0 System Test Configuration

#### 2.1 Justification

The system was configured for testing in a typical fashion (as a customer would normally use it), and in the confines as outlined in ANSI C63.4 (2009).

The EUT was powered by 2 X new 1.5V AAA batteries during test.

For maximizing emissions, the EUT was rotated through 360°, the antenna height was varied from 1 meter to 4 meters above the ground plane, and the antenna polarization was changed. This step by step procedure for maximizing emissions led to the data reported in Exhibit 3.0.

The unit was operated standalone and placed in the center of the turntable.

The equipment under test (EUT) was configured for testing in a typical fashion (as a customer would normally use it). The EUT was mounted to a plastic stand if necessary and placed on the wooden turntable, which enabled the engineer to maximize emissions through its placement in the three orthogonal axes.

#### 2.2 EUT Exercising Software

There was no special software to exercise the device. Once the unit is powered up, it transmits the RF signal continuously.

#### 2.3 Special Accessories

There are no special accessories necessary for compliance of this product.

#### 2.4 Equipment Modification

Any modifications installed previous to testing by Goldie Marketing Pty. Ltd. will be incorporated in each production model sold/leased in the United States.

No modifications were installed by Intertek Testing Services Hong Kong Ltd.

#### 2.5 Measurement Uncertainty

When determining of the test conclusion, the Measurement Uncertainty of test has been considered.

## INTERTEK TESTING SERVICES

---

### 2.6 Support Equipment List and Description

N/A.

### 3.0 Emission Results

Data is included of the worst case configuration (the configuration which resulted in the highest emission levels). A sample calculation, configuration photographs and data tables of the emissions are included.

#### 3.1 Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain (if any), Average Factor (optional) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CF - AG - AV$$

where  $FS$  = Field Strength in  $\text{dB}\mu\text{V}/\text{m}$

$RA$  = Receiver Amplitude (including preamplifier) in  $\text{dB}\mu\text{V}$

$CF$  = Cable Attenuation Factor in dB

$AF$  = Antenna Factor in dB

$AG$  = Amplifier Gain in dB

$AV$  = Average Factor in dB

In the following table(s), the reading shown on the data table reflects the preamplifier gain. An example for the calculations in the following table is as follows:

$$FS = RR + LF$$

where  $FS$  = Field Strength in  $\text{dB}\mu\text{V}/\text{m}$

$RR$  =  $RA - AG - AV$  in  $\text{dB}\mu\text{V}$

$LF$  =  $CF + AF$  in dB

Assume a receiver reading of 52.0  $\text{dB}\mu\text{V}$  is obtained. The antenna factor of 7.4 dB and cable factor of 1.6 dB are added. The amplifier gain of 29 dB and average factor of 5 dB are subtracted, giving a field strength of 27  $\text{dB}\mu\text{V}/\text{m}$ . This value in  $\text{dB}\mu\text{V}/\text{m}$  was converted to its corresponding level in  $\mu\text{V}/\text{m}$ .

$$RA = 52.0 \text{ dB}\mu\text{V}/\text{m}$$

$$AF = 7.4 \text{ dB}$$

$$RR = 18.0 \text{ dB}\mu\text{V}$$

$$CF = 1.6 \text{ dB}$$

$$LF = 9.0 \text{ dB}$$

$$AG = 29.0 \text{ dB}$$

$$AV = 5.0 \text{ dB}$$

$$FS = RR + LF$$

$$FS = 18 + 9 = 27 \text{ dB}\mu\text{V}/\text{m}$$

$$\text{Level in } \mu\text{V}/\text{m} = \text{Common Antilogarithm } [(27 \text{ dB}\mu\text{V}/\text{m})/20] = 22.4 \mu\text{V}/\text{m}$$

## **INTERTEK TESTING SERVICES**

---

---

### **3.2 Radiated Emission Configuration Photograph**

Worst Case Radiated Emission at 99.720 MHz

For electronic filing, the worst case radiated emission configuration photographs are saved with filename: radiated photos.pdf.

### **3.3 Radiated Emission Data**

The data on the following page lists the significant emission frequencies, the limit and the margin of compliance. Numbers with a minus sign are below the limit.

Judgment: Passed by 6.5 dB

# INTERTEK TESTING SERVICES

Applicant: Goldie Marketing Pty. Ltd.  
Model: SMR015  
Mode: Transmitting  
Sample: 1/2

Date of Test: March 13, 2013

Table 1

## Radiated Emissions

| Polarization | Frequency (MHz) | Reading (dB $\mu$ V) | Pre-Amp (dB) | Antenna Factor (dB) | Average Factor (dB) | Net at 3m (dB $\mu$ V/m) | Limit at 3m (dB $\mu$ V/m) | Margin (dB) |
|--------------|-----------------|----------------------|--------------|---------------------|---------------------|--------------------------|----------------------------|-------------|
| V            | 49.860          | 86.5                 | 16           | 11.0                | 22.6                | 58.9                     | 80.0                       | -21.1       |
| V            | 99.720          | 41.0                 | 16           | 12.0                | -                   | 37.0                     | 43.5                       | -6.5        |
| V            | 149.583         | 38.3                 | 16           | 14.0                | -                   | 36.3                     | 43.5                       | -7.2        |
| V            | 199.443         | 22.4                 | 16           | 16.0                | -                   | 22.4                     | 43.5                       | -21.1       |
| H            | 249.305         | 18.7                 | 16           | 20.0                | -                   | 22.7                     | 46.0                       | -23.3       |
| V            | 299.166         | 22.2                 | 16           | 22.0                | -                   | 28.2                     | 46.0                       | -17.8       |
| H            | 349.027         | 19.5                 | 16           | 24.0                | -                   | 27.5                     | 46.0                       | -18.5       |
| V            | 398.888         | 16.2                 | 16           | 25.0                | -                   | 25.2                     | 46.0                       | -20.8       |
| V            | 448.749         | 14.3                 | 16           | 26.0                | -                   | 24.3                     | 46.0                       | -21.7       |
| V            | 498.610         | 16.2                 | 16           | 26.0                | -                   | 26.2                     | 46.0                       | -19.8       |
| V            | 548.460         | 13.5                 | 16           | 28.0                | -                   | 25.5                     | 46.0                       | -20.5       |

NOTES: 1. Peak Detector Data unless otherwise stated.

2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distances were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative sign in the column shows value below limit.
4. Horn antenna is used for the emissions over 1000MHz.

## INTERTEK TESTING SERVICES

---

### 4.0 Equipment Photographs

For electronic filing, the photographs are saved with filename: external photos.pdf and internal photos.pdf.

### 5.0 Product Labelling

For electronics filing, the FCC ID label artwork and the label location are saved with filename: label.pdf.

### 6.0 Technical Specifications

For electronic filing, the block diagram and schematic of the tested EUT are saved with filename: block.pdf and circuit.pdf respectively.

### 7.0 Instruction Manual

For electronic filing, a preliminary copy of the Instruction Manual is saved with filename: manual.pdf.

This manual will be provided to the end-user with each unit sold/leased in the United States.

### 8.0 Miscellaneous Information

This miscellaneous information includes details of the measured bandwidth, the test procedure and calculation of factors such as pulse desensitization and averaging factor.

#### 8.1 Measured Bandwidth

The plot saved in bw.pdf which shows the fundamental emission is confined in the specified band. The field strength of any emission appearing between the band edges and up to 10kHz above and below the band edges (49.81 and 49.91 MHz) is at least 26 dB below the carrier level. And at 49.81 & 49.91 MHz, there are at least 34.2 dB below the carrier level. It meets requirement of Section 15.235(b).

## INTERTEK TESTING SERVICES

---

---

### 8.2 Discussion of Pulse Desensitization

Pulse desensitivity is not applicable for this device. The effective period ( $T_{eff}$ ) was approximately 7.4 ms for a digital "1" bit, as shown in the plots of Exhibit 8.3. With a resolution bandwidth (3 dB) of 100 kHz, the pulse desensitivity factor was 0 dB.

### 8.3 Calculation of Average Factor

Averaging factor in dB =  $20 \log_{10} (\text{duty cycle})$

The specification for output field strengths in accordance with the FCC rules specify measurements with an average detector. During testing, a spectrum analyzer incorporating a peak detector was used. Therefore, a reduction factor can be applied to the resultant peak signal level and compared to the limit for measurement instrumentation incorporating an average detector.

The time period over which the duty cycle is measured is 100 milliseconds, or the repetition cycle, whichever is a shorter time frame. The worst case (highest percentage on) duty cycle is used for the calculation. The duty cycle is measured by placing the spectrum analyzer in zero scan (receiver mode) and linear mode at maximum bandwidth (3 MHz at 3 dB down) and viewing the resulting time domain signal output from the analyzer on a Tektronix oscilloscope. The oscilloscope is used because of its superior time base and triggering facilities.

A plot of the worst-case duty cycle as detected in this manner are saved with filename: af.pdf

The duty cycle is simply the on-time divided by the period:

$$\begin{aligned} \text{The duration of one cycle} &= 100\text{ms} \\ \text{Effective period of the cycle} &= 200\text{us} \times 28 + 450\text{us} \times 4 \\ &= 7.4\text{ms} \end{aligned}$$

$$DC = 7.4 / 100\text{ms} = 0.074$$

Therefore, the averaging factor is found by  $20 \log_{10} 0.074 = -22.6$  dB

## INTERTEK TESTING SERVICES

---

### 8.4 Emissions Test Procedures

The following is a description of the test procedure used by Intertek Testing Services in the measurements of transmitters operating under Part 15, Subpart C rules.

The test set-up and procedures described below are designed to meet the requirements of ANSI C63.4 - 2009.

The transmitting equipment under test (EUT) is placed on a wooden turntable which is four feet in diameter and approximately one meter in height above the ground plane. During the radiated emissions test, the turntable is rotated and any cables leaving the EUT are manipulated to find the configuration resulting in maximum emissions. The EUT is adjusted through all three orthogonal axes to obtain maximum emission levels. The antenna height and polarization are varied during the testing to search for maximum signal levels.

Detector function for radiated emissions is in peak mode. Average readings, when required, are taken by measuring the duty cycle of the equipment under test and subtracting the corresponding amount in dB from the measured peak readings. A detailed description for the calculation of the average factor can be found in Exhibit 8.3.

The frequency range scanned is from the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic of the highest fundamental frequency or 40 GHz, whichever is lower. For line conducted emissions, the range scanned is 150 kHz to 30 MHz.

## INTERTEK TESTING SERVICES

---

### 8.4 Emissions Test Procedures (cont'd)

The EUT is warmed up for 15 minutes prior to the test.

AC power to the unit is varied from 85% to 115% nominal and variation in the fundamental emission field strength is recorded. If battery powered, a new, fully charged battery is used.

Conducted measurements are made as described in ANSI C63.4 - 2009.

The IF bandwidth used for measurement of radiated signal strength was 10 kHz for emission below 30 MHz and 120 kHz for emission from 30 MHz to 1000 MHz. Where pulsed transmissions of short enough pulse duration warrant, a greater bandwidth is selected according to the recommendations of Hewlett Packard Application Note 150-2. A discussion of whether pulse desensitivity is applicable to this unit is included in this report (See Exhibit 8.2). Above 1000 MHz, a resolution bandwidth of 1 MHz is used.

Transmitter measurements are normally conducted at a measurement distance of three meters. However, to assure low enough noise floor in the restricted bands and above 1 GHz, signals are acquired at a distance of one meter or less. All measurements are extrapolated to three meters using inverse scaling, but those measurements taken at a closer distance are so marked.

## INTERTEK TESTING SERVICES

---

### 9.0 Equipment List

#### 1) Radiated Emissions Test

|                      |                   |                      |                   |
|----------------------|-------------------|----------------------|-------------------|
| Equipment            | EMI Test Receiver | Log Periodic Antenna | Biconical Antenna |
| Registration No.     | EW-2251           | EW-0446              | EW-2512           |
| Manufacturer         | ROHDE SCHWARZ     | EMCO                 | EMCO              |
| Model No.            | ESCI              | 3146                 | 3104C             |
| Calibration Date     | Nov 23, 2012      | Oct 31, 2011         | Nov 15, 2011      |
| Calibration Due Date | Oct 30, 2013      | Apr 30, 2013         | May 15, 2013      |

|                      |  |  |                   |
|----------------------|--|--|-------------------|
| Equipment            | 14m Double Shield<br>RF Cable<br>(9kHz - 6GHz) | 14m Double Shield RF<br>Cable<br>(9kHz - 6GHz) | Spectrum Analyzer |
| Registration No.     | EW-2373  | EW-2376  | EW-2188           |
| Manufacturer         | RADIALL  | RADIALL  | AGILENTTECH       |
| Model No.            | nm/br56/bnc m 14m                              | nm/br56/bnc m 14m                              | E4407B            |
| Calibration Date     | Sep 22, 2012                                   | Sep 22, 2012                                   | Nov 05, 2012      |
| Calibration Due Date | Sep 12, 2013                                   | Sep 22, 2013                                   | Nov 05, 2013      |

#### 2) Bandwidth Measurement

|                      |                   |
|----------------------|-------------------|
| Equipment            | Spectrum Analyzer |
| Registration No.     | EW-2249           |
| Manufacturer         | R&S               |
| Model No.            | FSP30             |
| Calibration Date     | Oct 04, 2012      |
| Calibration Due Date | Oct 04, 2013      |