

Analysis Report

Report No.: HK13020622-1

The Equipment Under Test (EUT) is a portable transmitter of a RC Car operating at 49.860 MHz as dictated by a crystal. The EUT is powered by a 3.0 V DC source (2 x 1.5V AAA battery). The EUT has a left / right control lever and a forward / backward control lever.

After switching ON the EUT and the receiver of the RC Car, activating the control levers on the EUT can control the receiver moving forward, backward left and right directions.

Antenna Type: External integral antenna

Antenna Gain: 0dBi

Nominal rated field strength: 96.0dB μ V/m at 3m

Maximum allowed field strength of production tolerance: +3dB and -18dB

According to the KDB 447498:

Based on the Maximum allowed field strength of production tolerance was 99.0dB μ V/m at 3m in frequency 49.860MHz, thus;

The EIRP = $[(FS^2 * D) / 30] = 2.38mW$

Thus;

Conducted power = Radiated Power (EIRP) – Antenna Gain

So;

Conducted Power = 2.38mW.

The SAR Exclusion Threshold Level for 49.860MHz when the minimum test separation distance is < 50mm:

$$= [474 * (1 + \log 100/f(MHz))] / 2$$

$$= 308.6mW$$

Since the above conducted output power is well below the SAR Exclusion Threshold level, so the EUT is considered to comply with SAR requirement without testing.