



No. 1 Workshop, M-10, Middle section, Science & Technology Park,  
Shenzhen, Guangdong, China 518057

Telephone: +86 (0) 755 2601 2053  
Fax: +86 (0) 755 2671 0594  
Email: ee.shenzhen@sgs.com

Report No.: SZEM170600652102  
Page: 1 of 62

# TEST REPORT

**Application No.:** SZEM1706006521CR  
**Applicant:** Logitech Far East Ltd  
**Address of Applicant:** No. 2, Creation Road IV Science-Based Industrial Park Hsin-Chu Taiwan  
**Manufacturer:** Logitech Far East Ltd  
**Address of Manufacturer:** No. 2, Creation Road IV Science-Based Industrial Park Hsin-Chu Taiwan  
**Equipment Under Test (EUT):**  
**EUT Name:** A20 Wireless Headset  
**Model No.:** A20TXX01  
**Trade mark:** ASTRO



**FCC ID:** YQ6-A20TXX01  
**Standards:** 47 CFR Part 15, Subpart E 15.407 (2016)  
**Date of Receipt:** 2017-06-28  
**Date of Test:** 2017-07-09 to 2017-07-12  
**Date of Issue:** 2017-07-21

<b>Test Result :</b>	<b>Pass*</b>
----------------------	--------------

\* In the configuration tested, the EUT complied with the standards specified above.




Jack Zhang  
EMC Laboratory Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



<i>Revision Record</i>				
<i>Version</i>	<i>Chapter</i>	<i>Date</i>	<i>Modifier</i>	<i>Remark</i>
01		2017-07-21		Original

<b>Authorized for issue by:</b>				
				
		<hr/> <b>Benson Wang /Project Engineer</b>		
				
		<hr/> <b>Eric Fu /Reviewer</b>		



## 2 Test Summary

Radio Spectrum Technical Requirement				
Item	Standard	Method	Requirement	Result
Antenna Requirement	47 CFR Part 15, Subpart E 15.407	N/A	47 CFR Part 15, Subpart C 15.203	Pass

N/A: Not applicable

Radio Spectrum Matter Part				
Item	Standard	Method	Requirement	Result
Conducted Emissions at AC Power Line (150kHz-30MHz)	47 CFR Part 15, Subpart E 15.407	ANSI C63.10 (2013) Section 6.2	47 CFR Part 15, Subpart C 15.207 & 15.407 b(6)	Pass
99% Bandwidth	47 CFR Part 15, Subpart E 15.407	KDB 789033 II D	N/A	Pass
Minimum 6 dB bandwidth (5.725-5.85 GHz band )	47 CFR Part 15, Subpart E 15.407	KDB 789033 D02 II C 2	47 CFR Part 15, Subpart C 15.407 (e)	Pass
Maximum Conducted output power	47 CFR Part 15, Subpart E 15.407	KDB 789033 D02 II E	47 CFR Part 15, Subpart C 15.407 (a)	Pass
Peak Power spectrum density	47 CFR Part 15, Subpart E 15.407	KDB 789033 D02 II F	47 CFR Part 15, Subpart C 15.407 (a)	Pass
Radiated Emissions	47 CFR Part 15, Subpart E 15.407	KDB 789033 D02 II G	47 CFR Part 15, Subpart C 15.209 & 15.407(b)	Pass
Radiated Emissions which fall in the restricted bands	47 CFR Part 15, Subpart E 15.407	KDB 789033 D02 II G	47 CFR Part 15, Subpart C 15.209 & 15.407(b)	Pass
Frequency Stability	47 CFR Part 15, Subpart E 15.407	ANSI C63.10 (2013) Section 6.8	47 CFR Part 15, Subpart C 15.407 (g)	Pass

N/A: Not applicable



### 3 Contents

	Page
<b>1 COVER PAGE</b> .....	<b>1</b>
<b>2 TEST SUMMARY</b> .....	<b>3</b>
<b>3 CONTENTS</b> .....	<b>4</b>
<b>4 GENERAL INFORMATION</b> .....	<b>6</b>
4.1 DETAILS OF E.U.T. ....	6
4.2 DESCRIPTION OF SUPPORT UNITS .....	6
4.3 MEASUREMENT UNCERTAINTY .....	7
4.4 TEST LOCATION .....	8
4.5 TEST FACILITY .....	8
4.6 DEVIATION FROM STANDARDS .....	8
4.7 ABNORMALITIES FROM STANDARD CONDITIONS .....	8
<b>5 EQUIPMENT LIST</b> .....	<b>9</b>
<b>6 RADIO SPECTRUM TECHNICAL REQUIREMENT</b> .....	<b>11</b>
6.1 ANTENNA REQUIREMENT .....	11
6.1.1 <i>Test Requirement:</i> .....	11
6.1.2 <i>Conclusion</i> .....	11
<b>7 RADIO SPECTRUM MATTER TEST RESULTS</b> .....	<b>12</b>
7.1 CONDUCTED EMISSIONS AT AC POWER LINE (150KHZ-30MHZ) .....	12
7.1.1 <i>E.U.T. Operation</i> .....	13
7.1.2 <i>Test Setup Diagram</i> .....	13
7.1.3 <i>Measurement Procedure and Data</i> .....	13
7.2 99% BANDWIDTH .....	16
7.2.1 <i>E.U.T. Operation</i> .....	16
7.2.2 <i>Test Setup Diagram</i> .....	16
7.2.3 <i>Measurement Procedure and Data</i> .....	16
7.3 MINIMUM 6 DB BANDWIDTH (5.725-5.85 GHZ BAND ) .....	17
7.3.1 <i>E.U.T. Operation</i> .....	17
7.3.2 <i>Test Setup Diagram</i> .....	17
7.3.3 <i>Measurement Procedure and Data</i> .....	17
7.4 MAXIMUM CONDUCTED OUTPUT POWER .....	18
7.4.1 <i>E.U.T. Operation</i> .....	19
7.4.2 <i>Test Setup Diagram</i> .....	19
7.4.3 <i>Measurement Procedure and Data</i> .....	19
7.5 PEAK POWER SPECTRUM DENSITY .....	20
7.5.1 <i>E.U.T. Operation</i> .....	21
7.5.2 <i>Test Setup Diagram</i> .....	21
7.5.3 <i>Measurement Procedure and Data</i> .....	21
7.6 RADIATED EMISSIONS .....	22
7.6.1 <i>E.U.T. Operation</i> .....	22
7.6.2 <i>Test Setup Diagram</i> .....	22
7.6.3 <i>Measurement Procedure and Data</i> .....	23
7.7 RADIATED EMISSIONS WHICH FALL IN THE RESTRICTED BANDS .....	34
7.7.1 <i>E.U.T. Operation</i> .....	35
7.7.2 <i>Test Setup Diagram</i> .....	35



7.7.3	Measurement Procedure and Data.....	36
7.8	FREQUENCY STABILITY.....	41
7.8.1	E.U.T. Operation.....	41
7.8.2	Test Setup Diagram.....	41
7.8.3	Measurement Procedure and Data.....	41
<b>8</b>	<b>PHOTOGRAPHS.....</b>	<b>42</b>
8.1	CONDUCTED EMISSIONS AT AC POWER LINE (150KHZ-30MHZ) TEST SETUP.....	42
8.2	RADIATED EMISSIONS TEST SETUP.....	43
8.3	EUT CONSTRUCTIONAL DETAILS.....	44
<b>9</b>	<b>APPENDIX.....</b>	<b>45</b>
9.1	APPENDIX 15.407.....	45-62



## 4 General Information

### 4.1 Details of E.U.T.

Power supply:	powered by usb
Cable:	usb cable: 108cm shielded optical cable: 109cm unshielded
Operation Frequency:	5.745-5.825GHz.
Channel Numbers:	5G WiFi, 802.11a(VHT20): 5 Channels
Modulation Type	For 802.11a: OFDM(8PSK/QPSK/16QAM/64QAM)
Antenna Type:	Integral
Antenna Gain:	3.08dBi

### 4.2 Description of Support Units

Description	Manufacturer	Model No.	Serial No.
Laptop	Lenovo	T430u	REF. No.SEA1800

Note:

In FCC 15.31 , for each band in which the device can be operated with the device operating at the number of frequencies in each band specified in the following table, and the selected channel to perform the test as below:

Frequency Range of Operation Operating Frequency Range (in each Band)	Number of Measurement Frequencies Required	Location of Measurement Frequency in Band of Operation
1 MHz or less	1	centre
1 MHz to 10 MHz	2	1 near high end, 1 near low end
Greater than 10 MHz	3	1 near high end, 1 near centre

For 802.11a(HT20)

Mode	Channel	Frequency(MHz)
IEEE 802.11a 20MHz	The Lowest channel	5745
	The Middle channel	5785
	The Highest channel	5825

### 4.3 Measurement Uncertainty

No.	Item	Measurement Uncertainty
1	Radio Frequency	7.25 x 10 <sup>-8</sup>
2	Duty cycle	0.37%
3	Occupied Bandwidth	3%
4	RF conducted power	0.75dB
5	RF power density	2.84dB
6	Conducted Spurious emissions	0.75dB
7	RF Radiated power	4.5dB (below 1GHz)
		4.8dB (above 1GHz)
8	Radiated Spurious emission test	4.5dB (30MHz-1GHz)
		4.8dB (1GHz-18GHz)
9	Temperature test	1 °C
10	Humidity test	3%
11	Supply voltages	1.5%
12	Time	3%



#### **4.4 Test Location**

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch

No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, Guangdong, China.  
518057.

Tel: +86 755 2601 2053 Fax: +86 755 2671 0594

No tests were sub-contracted.

#### **4.5 Test Facility**

The test facility is recognized, certified, or accredited by the following organizations:

- **CNAS (No. CNAS L2929)**

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

- **A2LA (Certificate No. 3816.01)**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

- **VCCI**

The 10m Semi-anechoic chamber and Shielded Room of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-823, R-4188, T-1153 and C-2383 respectively.

- **FCC –Designation Number: CN1178**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized as an accredited testing laboratory.

Designation Number: CN1178. Test Firm Registration Number: 406779.

- **Industry Canada (IC)**

Two 3m Semi-anechoic chambers and the 10m Semi-anechoic chamber of SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab have been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 4620C-1, 4620C-2, 4620C-3.

#### **4.6 Deviation from Standards**

None

#### **4.7 Abnormalities from Standard Conditions**

None





## 5 Equipment List

Conducted Emissions at AC Power Line (150kHz-30MHz)					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
Shielding Room	ZhongYu Electron	GB-88	SEM001-06	2017-05-10	2018-05-10
Measurement Software	AUDIX	e3 V5.4.1221d	N/A	N/A	N/A
LISN	Rohde & Schwarz	ENV216	SEM007-01	2016-10-09	2017-10-09
LISN	ETS-LINDGREN	3816/2	SEM007-02	2017-04-14	2018-04-13
8 Line ISN	Fischer Custom Communications Inc.	FCC-TLISN-T8-02	EMC0120	2016-09-28	2017-09-28
4 Line ISN	Fischer Custom Communications Inc.	FCC-TLISN-T4-02	EMC0121	2016-09-28	2017-09-28
2 Line ISN	Fischer Custom	FCC-TLISN-T2-02	EMC0122	2016-09-28	2017-09-28

RF conducted test					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
DC Power Supply	ZhaoXin	RXN-305D	SEM011-02	2016-10-09	2017-10-09
Spectrum Analyzer	Rohde & Schwarz	FSP	SEM004-06	2016-10-09	2017-10-09
Measurement Software	JS Tonscend	JS1120-2 BT/WIFI V2.	N/A	N/A	N/A
Signal Generator	Rohde & Schwarz	SML03	SEM006-02	2017-04-14	2018-04-13
Power Meter	Rohde & Schwarz	NRVS	SEM014-02	2016-10-09	2017-10-09

RE in Chamber					
Test Equipment	Manufacturer	Model No.	Inventory No.	Cal. Date (yyyy-mm-dd)	Cal. Due date (yyyy-mm-dd)
10m Semi-Anechoic Chamber	SAEMC	FSAC1018	SEM001-03	2017-05-10	2018-05-10
EMI Test Receiver (9k-7GHz)	Rohde & Schwarz	ESR	SEM004-03	2017-04-14	2018-04-13
Trilog-Broadband Antenna (30M-1GHz)	Schwarzbeck	VULB9168	SEM003-18	2016-06-29	2019-06-29
Pre-amplifier (9kHz-1GHz)	Sonoma Instrument Co	310N	SEM005-04	2017-06-05	2018-06-04
Loop Antenna (9kHz-30MHz)	ETS-Lindgren	6502	SEM003-08	2015-08-14	2018-08-14
Measurement Software	AUDIX	e3 V8.2014-6-27	N/A	N/A	N/A



RE in chamber					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
3m Semi-Anechoic Chamber	AUDIX	N/A	SEM001-02	2017-05-10	2018-05-10
Measurement Software	AUDIX	e3 V8.2014-6-27	N/A	N/A	N/A
Spectrum Analyzer	Rohde & Schwarz	FSU43	SEM004-08	2017-04-14	2018-04-13
BiConiLog Antenna (26-3000MHz)	ETS-Lindgren	3142C	SEM003-02	2017-03-05	2020-03-05
Horn Antenna (1-18GHz)	Rohde & Schwarz	HF907	SEM003-07	2015-06-14	2018-06-14
Horn Antenna (15GHz-40GHz)	Schwarzbeck	BBHA 9170	SEM003-14	2017-06-16	2020-06-15
Pre-amplifier (0.1-1300MHz)	HP	8447D	SEM005-02	2016-10-09	2017-10-09
Low Noise Amplifier (100MHz-18GHz)	Black Diamond Series	BDLNA-0118-352810	SEM005-05	2016-10-09	2017-10-09
Pre-amplifier (0.1-26.5GHz)	Compliance Directions Systems Inc.	PAP-0126	SEM004-10	2016-10-17	2017-10-17
Pre-amplifier (26GHz-40GHz)	Compliance Directions Systems Inc.	PAP-2640-50	SEM005-08	2017-04-14	2018-04-13
DC Power Supply	Zhao Xin	RXN-305D	SEM011-02	2016-10-09	2017-10-09
Active Loop Antenna	ETS-Lindgren	6502	SEM003-08	2015-08-14	2018-08-14
Band filter	N/A	N/A	SEM023-01	N/A	N/A

General used equipment					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
Humidity/ Temperature Indicator	Shanghai Meteorological Industry Factory	ZJ1-2B	SEM002-03	2016-10-12	2017-10-12
Humidity/ Temperature Indicator	Shanghai Meteorological Industry Factory	ZJ1-2B	SEM002-04	2016-10-12	2017-10-12
Humidity/ Temperature Indicator	Mingle	N/A	SEM002-08	2016-10-12	2017-10-12
Barometer	Changchun Meteorological Industry Factory	DYM3	SEM002-01	2017-04-18	2018-04-18

## 6 Radio Spectrum Technical Requirement

### 6.1 Antenna Requirement

#### 6.1.1 Test Requirement:


47 CFR Part 15, Subpart C 15.203

#### 6.1.2 Conclusion

Standard Requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit permanently attached antenna or of one so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

EUT Antenna:



The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is 3.08dBi.



## 7 Radio Spectrum Matter Test Results

### 7.1 Conducted Emissions at AC Power Line (150kHz-30MHz)

Test Requirement 47 CFR Part 15, Subpart C 15.207 & 15.407 b(6)  
Test Method: ANSI C63.10 (2013) Section 6.2  
Limit:

Frequency of emission(MHz)	Conducted limit(dB $\mu$ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

\*Decreases with the logarithm of the frequency.

### 7.1.1 E.U.T. Operation


Operating Environment:

Temperature: 25 °C      Humidity: 55 % RH      Atmospheric Pressure: 1005 mbar

Pretest these mode to find the worst case: c:Charge + TX mode (Band 3)\_Keep the EUT in charging and continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; Only the data of worst case is recorded in the report.

The worst case for final test: c:Charge + TX mode (Band 3)\_Keep the EUT in charging and continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; Only the data of worst case is recorded in the report.

### 7.1.2 Test Setup Diagram




### 7.1.3 Measurement Procedure and Data

- 1) The mains terminal disturbance voltage test was conducted in a shielded room.
- 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a 50ohm/50μH + 5ohm linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.
- 3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane,
- 4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.
- 5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10 on conducted measurement.

Remark: LISN=Read Level+ Cable Loss+ LISN Factor


Mode:c; Line:Live Line



Site : Shielding Room  
Condition : CE LINE  
Job No. : 06521CR  
Test Mode : c

	Freq	Cable Loss	LISN Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB	dBuV	dBuV	dBuV	dB	
1 @	0.18056	0.02	9.64	40.22	49.88	54.46	-4.58	Peak
2 @	0.24422	0.02	9.64	35.60	45.26	51.95	-6.69	Peak
3 @	0.33385	0.02	9.64	29.77	39.43	49.35	-9.93	Peak
4 @	0.53215	0.02	9.64	24.55	34.22	46.00	-11.78	Peak
5 @	1.602	0.03	9.66	22.28	31.97	46.00	-14.03	Peak
6 @	11.745	0.15	9.89	24.66	34.70	50.00	-15.30	Peak

Mode:c; Line:Neutral Line



Site : Shielding Room  
 Condition : CE NEUTRAL  
 Job No. : 06521CR  
 Test Mode : c

	Freq	Cable Loss	LISN Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB	dBuV	dBuV	dBuV	dB	
1 @	0.18152	0.02	9.63	40.47	50.12	54.42	-4.30	Peak
2 @	0.24293	0.02	9.63	35.49	45.14	52.00	-6.86	Peak
3 @	0.29869	0.02	9.63	33.16	42.81	50.28	-7.47	Peak
4 @	0.47360	0.02	9.63	26.16	35.81	46.45	-10.64	Peak
5 @	1.487	0.03	9.65	25.32	35.00	46.00	-11.00	Peak
6 @	13.479	0.15	9.93	23.65	33.74	50.00	-16.26	Peak

**7.2 99% Bandwidth**

Test Requirement N/A  
 Test Method: KDB 789033 II D


**7.2.1 E.U.T. Operation**

Operating Environment:

Temperature: 25 °C Humidity: 55 % RH Atmospheric Pressure: 1005 mbar

Test mode b:TX mode (Band 3)\_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; Only the data of worst case is recorded in the report.

**7.2.2 Test Setup Diagram**



**7.2.3 Measurement Procedure and Data**

The detailed test data see: Appendix 15.407




**7.3 Minimum 6 dB bandwidth (5.725-5.85 GHz band )**

Test Requirement 47 CFR Part 15, Subpart C 15.407 (e)  
 Test Method: KDB 789033 D02 II C 2  
 Limit:  $\geq 500$  kHz

**7.3.1 E.U.T. Operation**

Operating Environment:  
 Temperature: 25 °C Humidity: 55 % RH Atmospheric Pressure: 1005 mbar  
 Test mode b:TX mode (Band 3)\_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; Only the data of worst case is recorded in the report.

**7.3.2 Test Setup Diagram**



**7.3.3 Measurement Procedure and Data**

The detailed test data see: Appendix 15.407



#### 7.4 Maximum Conducted output power

Test Requirement 47 CFR Part 15, Subpart C 15.407 (a)

Test Method: KDB 789033 D02 II E

Limit:

Frequency band(MHz)	Limit
5150-5250	≤1W(30dBm) for master device
	≤250mW(24dBm) for client device
5250-5350	≤250mW(24dBm) for client device or 11dBm+10logB*
5470-5725	≤250mW(24dBm) for client device or 11dBm+10logB*
5725-5850	≤1W(30dBm)

Remark: \*Where B is the 26dB emission bandwidth in MHz.

The maximum conducted output power must be measured over any interval of continuous transmission using instrumentation calibrated in terms of an rms-equivalent voltage.


**7.4.1 E.U.T. Operation**

Operating Environment:

Temperature: 25 °C      Humidity: 55 % RH      Atmospheric Pressure: 1005 mbar

Test mode      b:TX mode (Band 3)\_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a, Only the data of worst case is recorded in the report.

**7.4.2 Test Setup Diagram**



**7.4.3 Measurement Procedure and Data**

The detailed test data see: Appendix 15.407



### 7.5 Peak Power spectrum density

Test Requirement 47 CFR Part 15, Subpart C 15.407 (a)  
Test Method: KDB 789033 D02 II F  
Limit:

Frequency band(MHz)	Limit
5150-5250	≤17dBm in 1MHz for master device
	≤11dBm in 1MHz for client device
5250-5350	≤11dBm in 1MHz for client device
5470-5725	≤11dBm in 1MHz for client device
5725-5850	≤30dBm in 500 kHz

Remark: The maximum power spectral density is measured as a conducted emission by direct connection of a calibrated test instrument to the equipment under test.


**7.5.1 E.U.T. Operation**

Operating Environment:

Temperature: 25 °C      Humidity: 55 % RH      Atmospheric Pressure: 1005 mbar

Test mode      b:TX mode (Band 3)\_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; Only the data of worst case is recorded in the report.

**7.5.2 Test Setup Diagram**



**7.5.3 Measurement Procedure and Data**

The detailed test data see: Appendix 15.407

## 7.6 Radiated Emissions

Test Requirement: 47 CFR Part 15, Subpart C 15.209 & 15.407(b)  
 Test Method: KDB 789033 D02 II G  
 Measurement Distance: 10m

### 7.6.1 E.U.T. Operation

Operating Environment:


Temperature: 23 °C      Humidity: 54 % RH      Atmospheric Pressure: 1005 mbar

Pretest these mode to find the worst case: b:TX mode (Band 3)\_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; Only the data of worst case is recorded in the report.

c:Charge + TX mode (Band 3)\_Keep the EUT in charging and continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; Only the data of worst case is recorded in the report.

The worst case for final test: b:TX mode (Band 3)\_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; Only the data of worst case is recorded in the report.

### 7.6.2 Test Setup Diagram





### **7.6.3 Measurement Procedure and Data**

- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.

Remark: Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor



**Radiated Emission below 1GHz**

The test was performed at a 10m test site. According to below formulate and the test data at 10m test distance,

$$L_3 / L_{10} = D_{10} / D_3$$

Note:

L<sub>3</sub>: Level @ 3m distance. Unit: uV/m;

L<sub>10</sub>: Level @ 10m distance. Unit: uV/m;

D<sub>3</sub>: 3m distance. Unit: m

D<sub>10</sub>: 10m distance. Unit: m

The level at 3m test distance is below:


Mode b:

Frequency (MHz)	Level @ 10m (dBuV/m)	Level @ 10m (uV/m)	Level @ 3m (uV/m)	Level @ 3m (dBuV/m)	Limit @ 3m (dBuV/m)	Margin (dB)	Ant. Polarization
48.84	22.52	13.37	44.55	32.98	40.00	-7.02	V
106.76	16.49	6.68	22.25	26.95	43.50	-16.55	V
227.69	20.44	10.52	35.07	30.90	46.00	-15.10	V
273.23	19.28	9.20	30.68	29.74	46.00	-16.26	V
689.56	25.75	19.39	64.62	36.21	46.00	-9.79	V
842.13	27.12	22.70	75.66	37.58	46.00	-8.42	V
45.06	16.62	6.78	22.59	27.08	40.00	-12.92	H
51.12	20.92	11.12	37.06	31.38	40.00	-8.62	H
214.51	24.21	16.24	54.12	34.67	43.50	-8.83	H
259.23	18.73	8.64	28.80	29.19	46.00	-16.81	H
737.07	24.90	17.58	58.60	35.36	46.00	-10.64	H
925.76	27.07	22.57	75.23	37.53	46.00	-8.47	H





Radiated Emission below 1GHz  
30MHz~1GHz (QP) Horizontal




Condition: 10m HORIZONTAL  
Job No. : 06521CR  
Test Mode: b

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 pp	48.84	6.88	12.81	33.00	35.83	22.52	29.50	-6.98
2	106.76	7.24	10.06	32.79	31.98	16.49	33.10	-16.61
3	227.69	7.74	10.64	32.67	34.73	20.44	35.60	-15.16
4	273.23	7.97	11.95	32.62	31.98	19.28	35.60	-16.32
5	689.56	9.12	20.00	32.60	29.23	25.75	35.60	-9.85
6	842.13	9.31	21.54	32.56	28.83	27.12	35.60	-8.48



Vertical




Condition: 10m VERTICAL  
Job No. : 06521CR  
Test Mode: b

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Limit Level	Limit Line	Over Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	45.06	6.80	12.90	32.99	29.91	16.62	29.50	-12.88
2	51.12	6.92	12.69	32.99	34.30	20.92	29.50	-8.58
3	214.51	7.67	9.82	32.68	39.40	24.21	35.60	-11.39
4	259.23	7.90	11.46	32.64	32.01	18.73	35.60	-16.87
5	737.07	9.20	20.61	32.60	27.69	24.90	35.60	-10.70
6 pp	925.76	9.51	22.57	32.50	27.49	27.07	35.60	-8.53



Transmitter Emission above 1GHz

Mode:b; Polarization:Horizontal; Modulation Type:802.11a; bandwidth:20MHz; Channel:Low




Condition: 3m HORIZONTAL  
Job No: : 06521CR,06524CR  
Mode: : 5745 TX SE  
: Lampstand

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Limit Level	Over Line	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dB	
1	1256.512	4.16	24.75	38.07	43.28	34.12	74.00	-39.88 peak
2	1672.779	4.67	26.56	38.03	42.67	35.87	74.00	-38.13 peak
3	4267.237	7.02	33.60	38.13	45.13	47.62	74.00	-26.38 peak
4	11490.000	12.33	38.09	35.50	37.04	51.96	74.00	-22.04 peak
5	pp15003.420	14.85	41.30	38.90	35.25	52.50	74.00	-21.50 peak
6	17235.000	17.60	43.08	36.18	27.13	51.63	74.00	-22.37 peak



Mode:b; Polarization:Vertical; Modulation Type:802.11a; bandwidth:20MHz; Channel:Low




Condition: 3m Vertical  
Job No: : 06521CR,06524CR  
Mode: : 5745 TX SE  
: Lampstand

	Cable	Ant	Preamp	Read	Limit	Over		
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	4.20	24.87	38.07	43.81	34.81	74.00	-39.19	peak
2	4.71	26.68	38.03	43.64	37.00	74.00	-37.00	peak
3	6.57	33.16	37.98	45.75	47.50	74.00	-26.50	peak
4	12.33	38.09	35.50	37.93	52.85	74.00	-21.15	peak
5	14.82	41.08	38.91	35.38	52.37	74.00	-21.63	peak
6	17.60	43.08	36.18	27.42	51.92	74.00	-22.08	peak



Mode:b; Polarization:Horizontal; Modulation Type:802.11a; bandwidth:20MHz; Channel:middle




Condition: 3m HORIZONTAL  
Job No: : 06521CR,06524CR  
Mode: : 5785 TX SE  
: Lampstand

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1263.796	4.17	24.79	38.07	42.61	33.50	74.00	-40.50	peak
2	1697.129	4.70	26.66	38.03	40.51	33.84	74.00	-40.16	peak
3	4254.921	7.00	33.60	38.13	43.67	46.14	74.00	-27.86	peak
4	11570.000	12.34	38.17	35.51	36.86	51.86	74.00	-22.14	peak
5	pp14873.890	14.82	41.08	38.91	35.47	52.46	74.00	-21.54	peak
6	17355.000	17.93	43.23	36.12	26.78	51.82	74.00	-22.18	peak



Mode:b; Polarization:Vertical; Modulation Type:802.11a; bandwidth:20MHz; Channel:middle




Condition: 3m VERTICAL  
Job No: : 06521CR,06524CR  
Mode: : 5785 TX SE  
: Lampstand

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Limit Level	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	1289.627	4.21	24.91	38.07	43.87	34.92	74.00	-39.08 peak
2	1578.822	4.57	26.16	38.04	40.67	33.36	74.00	-40.64 peak
3	4254.921	7.00	33.60	38.13	43.43	45.90	74.00	-28.10 peak
4	pp11570.000	12.34	38.17	35.51	35.87	50.87	74.00	-23.13 peak
5	14830.960	14.81	41.00	38.92	33.43	50.32	74.00	-23.68 peak
6	17355.000	17.93	43.23	36.12	24.24	49.28	74.00	-24.72 peak



Mode:b; Polarization:Horizontal; Modulation Type:802.11a; bandwidth:20MHz; Channel:High




Condition: 3m HORIZONTAL  
Job No: : 06521CR,06524CR  
Mode: : 5825 TX SE  
: Lampstand

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Limit Level	Over Line	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dB	
1	1300.858	4.22	24.96	38.07	44.58	35.69	74.00	-38.31 peak
2	1663.137	4.66	26.52	38.03	41.65	34.80	74.00	-39.20 peak
3	4086.182	6.80	33.60	38.04	43.49	45.85	74.00	-28.15 peak
4	11650.000	12.35	38.25	35.53	37.37	52.44	74.00	-21.56 peak
5	14830.960	14.81	41.00	38.92	34.64	51.53	74.00	-22.47 peak
6	pp17475.000	18.25	43.37	36.06	27.05	52.61	74.00	-21.39 peak



Mode:b; Polarization:Vertical; Modulation Type:802.11a; bandwidth:20MHz; Channel:High



Condition: 3m VERTICAL  
Job No: : 06521CR,06524CR  
Mode: : 5825 TX SE  
: Lampstand

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Limit Level	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dB	
1	1231.345	4.12	24.63	38.08	42.45	33.12	74.00	-40.88 peak
2	1697.129	4.70	26.66	38.03	42.37	35.70	74.00	-38.30 peak
3	4456.315	7.23	33.60	38.23	43.51	46.11	74.00	-27.89 peak
4	11650.000	12.35	38.25	35.53	36.38	51.45	74.00	-22.55 peak
5	14830.960	14.81	41.00	38.92	34.08	50.97	74.00	-23.03 peak
6	pp17475.000	18.25	43.37	36.06	26.51	52.07	74.00	-21.93 peak





Remark:

- 1) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:  
Final Test Level = Receiver Reading + Antenna Factor + Cable Factor – Preamplifier Factor
- 2) Scan from 9kHz to 25GHz, The disturbance above 13GHz and below 30MHz was very low, and the above harmonics were the highest point could be found when testing, so only the above harmonics had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported .
- 3) As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. So, only the peak measurements were shown in the report.



### 7.7 Radiated Emissions which fall in the restricted bands

Test Requirement 47 CFR Part 15, Subpart C 15.209 & 15.407(b)  
Test Method: KDB 789033 D02 II G  
Measurement Distance: 3m  
Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

**7.7.1 E.U.T. Operation**

Operating Environment:


Temperature: 23 °C Humidity: 54 % RH Atmospheric Pressure: 1005 mbar

Pretest these mode to find the worst case: b:TX mode (Band 3)\_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; Only the data of worst case is recorded in the report.

c:Charge + TX mode (Band 3)\_Keep the EUT in charging and continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; Only the data of worst case is recorded in the report.


The worst case for final test: b:TX mode (Band 3)\_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; Only the data of worst case is recorded in the report.

**7.7.2 Test Setup Diagram**



Below 30MHz

30MHz-1GHz



Above 1GHz




### **7.7.3 Measurement Procedure and Data**

- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.

Remark: Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor

Mode:b; Polarization:Horizontal; Modulation Type:802.11a; bandwidth:20MHz; Channel:Low




Condition: 3m HORIZONTAL  
 Job No : 06521CR,06524CR  
 Mode : 5745 Band edge  
 : Lampstand

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Limit Level	Over Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	5715.000	8.47	34.53	38.36	50.37	55.01	109.40	-54.39	Peak
2	5725.000	8.48	34.54	38.35	60.46	65.13	125.20	-60.07	Peak
3 pp	5748.109	8.50	34.55	38.35	91.97	96.67	125.20	-28.53	Peak



Mode:b; Polarization:Vertical; Modulation Type:802.11a; bandwidth:20MHz; Channel:Low




Condition: 3m Vertical  
Job No : 06521CR,06524CR  
Mode : 5745 Band edge  
: Lampstand

	Cable	Ant	Preamp	Read	Limit	Over			
Freq	Loss	Factor	Factor	Level	Level	Line	Limit		
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		
1	5715.000	8.47	34.53	38.36	45.99	50.63	109.40	-58.77	Peak
2	5725.000	8.48	34.54	38.35	51.96	56.63	125.20	-68.57	Peak
3	pp 5739.056	8.49	34.55	38.35	83.74	88.43	125.20	-36.77	Peak



Mode:b; Polarization:Horizontal; Modulation Type:802.11a; bandwidth:20MHz; Channel:High




Condition: 3m HORIZONTAL  
Job No : 06521CR,06524CR  
Mode : 5825 Band edge  
: Lampstand

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	pp 5828.249	8.58	34.60	38.33	91.69	96.54	125.20	-28.66 Peak
2	5850.000	8.60	34.61	38.33	53.15	58.03	125.20	-67.17 Peak
3	5860.000	8.61	34.62	38.33	46.13	51.03	109.41	-58.38 Peak



Mode:b; Polarization:Vertical; Modulation Type:802.11a; bandwidth:20MHz; Channel:High



Condition: 3m VERTICAL

Job No : 06521CR,06524CR

Mode : 5825 Band edge

: Lampstand

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	pp 5827.563	8.58	34.60	38.33	83.03	87.88	125.20	-37.32 Peak
2	5850.000	8.60	34.61	38.33	44.06	48.94	125.20	-76.26 Peak
3	5860.000	8.61	34.62	38.33	43.88	48.78	109.41	-60.63 Peak




### 7.8 Frequency Stability

Test Requirement: 47 CFR Part 15, Subpart C 15.407 (g)  
 Test Method: ANSI C63.10 (2013) Section 6.8  
 Limit: The frequency tolerance shall be maintained within the band of operation frequency over a temperature variation of 0 degrees to 35 degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C.

#### 7.8.1 E.U.T. Operation

Operating Environment:  
 Temperature: 25 °C      Humidity: 55 % RH      Atmospheric Pressure: 1005 mbar  
 Test mode: b:TX mode (Band 3)\_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; Only the data of worst case is recorded in the report.

#### 7.8.2 Test Setup Diagram



#### 7.8.3 Measurement Procedure and Data



The detailed test data see: Appendix 15.407

## 8 Photographs

### 8.1 Conducted Emissions at AC Power Line (150kHz-30MHz) Test Setup



## 8.2 Radiated Emissions Test Setup





### **8.3 EUT Constructional Details**

Refer to Appendix A - Photographs of EUT Constructional Details for SZEM1706006521CR






## 9 Appendix

### 9.1 Appendix 15.407

#### 1.Emission Bandwidth Measurement

Test Mode	Test Channel	Ant	EBW[MHz]	Limit[MHz]	Verdict
11A	5745	Ant1	16.650	$\geq 0.5$	PASS
11A	5785	Ant1	16.650	$\geq 0.5$	PASS
11A	5825	Ant1	16.650	$\geq 0.5$	PASS










## 2.Occupied Bandwidth Measurement

Test Mode	Test Channel	Ant	OBW[MHz]	Limit[MHz]	Verdict
11A	5745	Ant1	18.090	---	PASS
11A	5785	Ant1	18.060	---	PASS
11A	5825	Ant1	17.880	---	PASS












**3. Maximum Conduct Output Power**

Test Mode	Test Channel	Ant	Level [dBm]	10log(1/x) Factor [dB]	Power [dBm]	Limit [dBm]	Verdict
11A	5745	Ant1	8.51	0	8.51	<30.00	PASS
11A	5785	Ant1	8.66	0	8.66	<30.00	PASS
11A	5825	Ant1	7.70	0	7.70	<30.00	PASS












#### 4. Maximum Power Spectral Density

Test Mode	Test Channel	Ant	Level [dBm/500kHz]	10log(1/x) Factor[dB]	10log(500kHz/RBW) Factor [dB]	PSD [dBm/500kHz]	Limit [dBm/500kHz]	Verdict
11A	5745	Ant1	-6	0	0	-6	<17.00	PASS
11A	5785	Ant1	-5.86	0	0	-5.86	<17.00	PASS
11A	5825	Ant1	-6.79	0	0	-6.79	<17.00	PASS












**5.Duty Cycle (x)**

Test Mode	Test Channel	Ant	Duty Cycle[%]	10log(1/x) Factor[dB]
11A	5745	Ant1	100	0
11A	5785	Ant1	100	0
11A	5825	Ant1	100	0



This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.





6.Frequency Stability

Test mode:	802.11a(HT20)	Frequency(MHz):	5745
------------	---------------	-----------------	------

Temperature (°C)	Voltage(VAC)	Measurement Frequency(MHz)	Delta Frequency(kHz)	Result
35	120	5745.7183	-0.7183	Pass
25		5745.7189	-0.7189	Pass
15		5745.7196	-0.7196	Pass
5		5745.7194	-0.7194	Pass
0		5745.7189	-0.7189	Pass
20	138	5745.7182	-0.7182	Pass
	120	5745.7189	-0.7189	Pass
	102	5745.7192	-0.7192	Pass



**SGS-CSTC Standards Technical Services Co., Ltd.**  
**Shenzhen Branch**

Report No.: SZEM170600652102

Page: 62 of 62

Test mode:	802.11a(HT20)	Frequency(MHz):	5785
------------	---------------	-----------------	------

Temperature (°C)	Voltage(VAC)	Measurement Frequency(MHz)	Delta Frequency(kHz)	Result
35	120	5785.9313	-0.9313	Pass
25		5785.9431	-0.9431	Pass
15		5785.9015	-0.9015	Pass
5		5785.9012	-0.9012	Pass
0		5785.9313	-0.9313	Pass
20	138	5785.9431	-0.9413	Pass
	120	5785.9011	-0.9011	Pass
	102	5785.9016	-0.9016	Pass

Test mode:	802.11a(HT20)	Frequency(MHz):	5825
------------	---------------	-----------------	------

Temperature (°C)	Voltage(VAC)	Measurement Frequency(MHz)	Delta Frequency(kHz)	Result
35	120	5824.9016	0.0984	Pass
25		5824.9022	0.0978	Pass
15		5824.9026	0.0974	Pass
5		5824.9018	0.0982	Pass
0		5824.9017	0.0983	Pass
20	138	5824.9014	0.0986	Pass
	120	5824.9022	0.0978	Pass
	102	5824.9031	0.0969	Pass