

RF Exposure Evaluation Declaration

Product Name: GPS Tracker
Model No.: GV500
FCC ID: YQD--GV500

Applicant : Queclink Wireless Solutions Co.,Ltd.

Address : Room 501, Building 9, No.99, Tianzhou Road, Shanghai, China

Date of Receipt : 08-24-2015

Issued Date : 09-22-2015

Report No. : UL12620150824FCC058-3

Report Version : V1.0

The test results relate only to the samples tested.

The test results shown in the test report are traceable to the national/international standard through the calibration of the equipment and evaluated measurement uncertainty herein.

This report must not be used to claim product endorsement by TAF, CNAS or any agency of the Government.

The test report shall not be reproduced except in full without the written approval of Unilab Corporation.


RF Exposure Evaluation Declaration

Issued Date : 09-22-2015

Report No. : UL12620150824FCC058-3

Product Name : GPS Locator
Model No. : GV500
Applicant : Queclink Wireless Solutions Co.,Ltd
Address : Room 501, Building 9, No 99, TianZhou Road, Shanghai, China
Manufacturer : Queclink Wireless Solutions Co.,Ltd.
Address : Room 501, Building 9, No 99, TianZhou Road, Shanghai, China
EUT Voltage : Extreme Low:8V DC,Nominal:12/24V DC,Extreme High:32V DC
Brand Name : Queclink
Applicable Standard : FCC's Rules(47 C.F.R. § 1.1310 and 2.1091)
Test Result : Complied
Performed Location : Unilab (Shanghai) Co.,Ltd.
FCC 2.948 register number is 714465
No.1350, Lianxi Road, Pudong New District, Shangha, China
TEL:+86-21-5027-5125/FAX:+86-21-5027-7862

Documented By :



(Technical Engineer: Paul Yang)

Reviewed By :



(Senior Engineer: Forest Cao)

Approved By :



(Supervisor: Eva Wang)

1. EUT Description

Product Name:	GPS Locator
Model Name:	GV500
Hardware Version:	V1.01
Software Version:	GV500NR00A01V05M128_MXIC
RF Exposure Environment:	Uncontrolled
GSM/GPRS	
Support Band:	GSM850/ PCS 1900
Tx Frequency Range:	GSM 850: 824.2MHz to 848.8MHz PCS 1900: 1850.2MHz to 1909.8MHz
Rx Frequency Range:	GSM 850: 869.2MHz to 893.8MHz PCS 1900: 1930.2MHz to 1989.8MHz
Type of modulation:	GMSK
Antenna Type:	Internal
Antenna Peak Gain:	GSM 850:-3.1dBi PCS 1900:-2.2dBi

2. RF Exposure Evaluation

2.1 Limits

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range(MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (Minutes)
(A)Limits for Occupation/Control Exposures				
300-1500	--	--	F/300	6
1500-100,000	--	--	5	6
(B)Limits for General Occupation/UnControlled Exposures				
300-1500	--	--	F/1500	6
1500-100,000	--	--	1	30

F= Frequency in MHz

Friis Formula

Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * R^2)$

Where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

P_d is the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

2.2. Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

The temperature and related humidity: 26°C and 52% RH.

2.3.Test Result of RF Exposure Evaluation

This device is evaluated by mobile device with general population/uncontrolled exposure condition
 For this device, the calculation is using the most conservative values, and the results are as follows:

Test Mode	Antenna Gain (dBi)	Maximum Output Power (dBm)	Average Power (dBm)	Average ERP/EIRP (mW)	Calculated RF Exposure at d = 20cm (mW/cm ²)	MPE Limit (mW/cm ²)
GSM 850	-3.1	33.5	24.5	138.04	0.03	0.55
GPR S850	-3.1	33	24	123.03	0.02	0.55
PCS 1900	-2.2	30.5	21.5	85.11	0.02	1.00
GPRS 1900	-2.2	30	21	75.86	0.02	1.00

The averaged power calculated method are shown as below:
 Averaged power=Maximum burst averaged power(1 Tx Slot)-9dB
 Duty cycle =12.5%
 Average EIRP Power=Average Power+Antenna Gain

Test Mode	Antenna Gain (dBi)	Maximum Output Power (dBm)	Average Power (dBm)	Average ERP/EIRP (mW)	Calculated RF Exposure at d = 20cm (mW/cm ²)	MPE Limit (mW/cm ²)
GSM 850	-3.1	32.97	23.97	122.18	0.02	0.55
GPR S850	-3.1	32.94	23.94	121.34	0.02	0.55
PCS 1900	-2.2	29.59	20.59	69.02	0.01	1.00
GPRS 1900	-2.2	29.58	20.58	68.87	0.01	1.00

The averaged power calculated method are shown as below:
 Averaged power=Maximum burst averaged power(1 Tx Slot)-9dB
 Duty cycle =12.5%
 Average EIRP Power=Average Power+Antenna Gain

This device can pass RF exposure limit.