



Certificate # 2861.01



Page 1 of 10

Test Report

Verified code: 238413

Report No.: E202211048579-3

Customer: Quealink Wireless Solutions Co., Ltd.
Address: No.30, Lane 500, Xinlong Road, Minhang District, Shanghai, China 201101
Sample Name: Box-Disguised Rechargeable Tracker
Sample Model: GL33
Receive Sample Date: Nov.15,2022
Test Date: Nov.16,2022 ~ Nov.30,2022
Reference Document: CFR 47, FCC Part 2.1091 Radio frequency radiation exposure evaluation: mobile devices.
Test Result: Pass

Prepared by: *Huang lifang* Reviewed by: *Feng Hui* Approved by: *Zhao Zetian*

GUANGZHOU GRG METROLOGY & TEST CO., LTD

Issued Date: 2023-02-03

GUANGZHOU GRG METROLOGY & TEST CO., LTD.

Address: No.163, Pingyun Road, West of Huangpu Avenue, Guangzhou, Guangdong, China
Tel: (+86) 400-602-0999 FAX: (+86) 020-38698685 Web: <http://www.grgtest.com>



Statement

1. The report is invalid without "special seal for inspection and testing"; some copies are invalid; The report is invalid if it is altered or missing; The report is invalid without the signature of the person who prepared, reviewed and approved it.
2. The sample information is provided by the client and responsible for its authenticity; The content of the report is only valid for the samples sent this time.
3. When there are reports in both Chinese and English, the Chinese version will prevail when the language problems are inconsistent.
4. If there is any objection concerning the report, please inform us within 15 days from the date of receiving the report.
5. Without the agreement of the laboratory, the client is not authorized to use the test results for unapproved propaganda.

----- The following blanks -----

TABLE OF CONTENTS

1.	GENERAL DESCRIPTION OF EUT	5
1.1	APPLICANT	5
1.2	MANUFACTURER	5
1.3	FACTORY	5
1.4	BASIC DESCRIPTION OF EQUIPMENT UNDER TEST	5
2.	LABORATORY AND ACCREDITATIONS	6
2.1	LABORATORY	6
2.2	ACCREDITATIONS	6
3.	EVALUATION METHOD	7
4.	CALCULATION METHOD	8
5.	ESTIMATION RESULT	9
5.1	MEASUREMENT RESULTS	9
6.	CONCLUSION	10

----- The following blanks -----

REPORT ISSUED HISTORY

Report Version	Report No.	Description	Compile Date
1.0	E202211048579-3	Original Issue	2023-01-11

Note:

1. The maximum output Power of GSM is refer to the module report. (Report No.: E202211048579-1)

----- The following blanks -----

1. GENERAL DESCRIPTION OF EUT

1.1 APPLICANT

Name: Queclink Wireless Solutions Co., Ltd.
Address: No.30, Lane 500, Xinlong Road, Minhang District, Shanghai, China 201101

1.2 MANUFACTURER

Name: Queclink Wireless Solutions Co., Ltd.
Address: No.30, Lane 500, Xinlong Road, Minhang District, Shanghai, China 201101

1.3 FACTORY

Name: Queclink Wireless Solutions Co., Ltd.
Address: No.30, Lane 500, Xinlong Road, Minhang District, Shanghai, China 201101

1.4 BASIC DESCRIPTION OF EQUIPMENT UNDER TEST

Equipment: Box-Disguised Rechargeable Tracker
Model No.: GL33
Adding Model: /
Trade Name: Queclink
FCC ID: YQD-GL33
Power Supply: Input power: 5V ---- 1A
DC 3.7V power supplied by battery
Battery Specification: Model: GSP104065
Nominal Voltage: 3.7Vdc
Rated Capacity: 2800mAh
Frequency Range: GSM 850 TX: 824 MHz ~ 849 MHz
GSM 1900 TX: 1850 MHz ~ 1910 MHz
Transmit Power: Reference Section 5 Table 3
Modulation type: GPRS: GMSK
Antenna Specification: Reference Section 5 Table 1
Temperature Range: -20°C~60°C
Hardware Version: GL33R00A01V44N32
Software Version: R104V1.04
Sample No: /
Note: /

2. LABORATORY AND ACCREDITATIONS

2.1 LABORATORY

The tests & measurements refer to this report were performed by Shenzhen EMC Laboratory of Guangzhou GRG Metrology & Test Co., Ltd.

Add.: No.1301 Guanguang Road Xinlan Community, Guanlan Street, Longhua District Shenzhen, 518110, People's Republic of China.

P.C.: 518110

Tel : 0755-61180008

Fax: 0755-61180008

2.2 ACCREDITATIONS

Our laboratories are accredited and approved by the following approval agencies according to ISO/IEC 17025.

USA A2LA(Certificate #2861.01)

The measuring facility of laboratories has been authorized or registered by the following approval agencies.

Canada ISED (Company Number: 24897, CAB identifier:CN0069)

USA FCC (Registration Number: 759402, Designation Number:CN1198)

Copies of granted accreditation certificates are available for downloading from our web site,
<http://www.grgtest.com>

----- The following blanks -----

3. EVALUATION METHOD

Exposure category: General population/uncontrolled environment
 EUT Type: Production Unit
 Device Type: Mobile Device

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as mobile device whereby a distance of 0.2m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with.

In accordance with KDB447498D01 for Simultaneous transmission MPE test exclusion applies when the sum of the MPE ratios for all simultaneous transmitting antennas incorporated in a host device, based on the calculated/estimated, numerically modeled or measured field strengths or power density, is ≤ 1.0 . The MPE ratio of each antenna is determined at the minimum test separation distance required by the operating configurations and exposure conditions of the host device, according to the ratio of field strengths or power density to MPE limit, at the test frequency. Either the maximum peak or spatially averaged results from measurements or numerical simulations may be used to determine the MPE ratios. Spatial averaging does not apply when MPE is estimated using simple calculations based on far-field plane-wave equivalent conditions. The antenna installation and operating requirements for the host device must meet the minimum test separation distances required by all antennas, in both standalone and simultaneous transmission operations, to satisfy compliance.

LIMITS FOR GENERAL POPULATION/UNCONTROLLEDEXPOSURE

(B)Limits for General Population/Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength(H) (A/m)	Power Density (S) (Mw/cm ²)	Averaging Time[E] ² , [H] ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

Note: f=frequency in MHz; *Plane-wave equivalent power density

----- The following blanks -----

4. CALCULATION METHOD

Predication of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = PG / 4\pi R^2$$

Where: S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to anisotropic radiator

R=distance to the center of radiation of the antenna

From the EUT RF output power, the minimum mobile separation distance, d=20cm, as well as the maximum gain of the used as following information, the RF power density can be obtained.

Table 1 Antenna Specification

Frequency Band	Antenna type	Internal Identification	Maximum antenna gain
GSM 850	PCB antenna	Antenna 1	-4.62 dBi
GSM 1900			0.15 dBi

Table 2 Transmit Power

Frequency Band	Maximum Output Power (dBm)	Tune-up Output Power Range (dBm)
GSM 850	32.43	33.00
GSM 1900	29.06	30.00

Note:

1. The maximum output Power of GSM is refer to the module report. (Report No.: E202211048579-1)

----- The following blanks -----

5. ESTIMATION RESULT

5.1 MEASUREMENT RESULTS

STANDALONE MPE

Mode	Frequency (MHz)	Antenna Gain (dBi)	Tune-up Output power (dBm)	EIRP (mW)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)	Results
GSM 850	824 - 849	-4.62	33.0	1995.26	0.14	0.55	Pass
GSM 1900	1850 - 1910	0.15	30.0	1000.00	0.21	1.00	Pass

Remark: 1. MPE use distance is 20cm from manufacturer declaration of user manual.

----- The following blanks -----

6. CONCLUSION

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure of mobile device.

----- **End of Report** -----