FCC §1.1310& §2.1091 - MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Applicable Standard

According to subpart 15.247(i) and subpart §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for Maximum Permissible Exposure (MPE) (§1.1310, §2.1091)

(B) Limits for General Population/Uncontrolled Exposure									
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm²)	Averaging Time (minutes)					
0.3-1.34	614	1.63	*(100)	30					
1.34-30	824/f	2.19/f	*(180/f ²)	30					
30-300	27.5	0.073	0.2	30					
300-1500	/		f/1500	30					
1500-100,000	/		1.0	30					

f = frequency in MHz; * = Plane-wave equivalent power density;

According to §1.1310 and §2.1091 RF exposure is calculated.

Calculated Formulary:

Predication of MPE limit at a given distance

 $S = PG/4\pi R^2 =$ power density (in appropriate units, e.g. mW/cm²);

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

For simultaneously transmit system, the calculated power density should comply with:

$$\sum_{i} \frac{S_i}{S_{Limit,i}} \leq 1$$

Calculated Data:

Mode	Frequency Range (MHz)	Antenna Gain		Target Output Power		Evaluation Distance	Power Density	MPE Limit
		(dBi)	(numeric)	(dBm)	(mW)	(cm)	(mW/cm^2)	$(\mathrm{mW/cm}^2)$
BLE	2402~2480	3.28	2.13	-3.50	0.45	20	0.0002	1.00
WCDMA II	1850~1910	-4.39	0.36	24.00	251.189	20	0.0182	1.00
WCDMA IV	1710~1755	-4.14	0.39	24.00	251.189	20	0.0193	1.00
WCDMA V	824~849	-5.55	0.28	24.00	251.189	20	0.0139	0.55
LTE Band 2	1850~1910	-4.39	0.36	24.50	281.838	20	0.0204	1.00
LTE Band 4	1710~1755	-4.14	0.39	24.50	281.838	20	0.0216	1.00
LTE Band 5	824~849	-5.55	0.28	24.50	281.838	20	0.0156	0.55
LTE Band 12	699~716	-6.24	0.24	24.50	281.838	20	0.0133	0.47
LTE Band 13	777~787	-4.17	0.38	24.50	281.838	20	0.0215	0.52

Note:

(1) The target output powers are all declared by the Manufacturer.

(2) The LTE/WCDMA module FCC ID: XMR201807EG91NA.

(3) BLE and WCDMA or LTE can transmit simultaneously; the worst condition was as below:

$$\sum_{i} \frac{S_{i}}{S_{Limit,i}} = 0.0002/1.00 + 0.0215/0.52 = 0.0002 + 0.0413 = 0.0415 < 1.0$$

Result: The device meet FCC MPE at 20 cm distance.