

FCC ID: YR8ES101

Maximum Permissible Exposure

as specified in Table 1B of 47 CFR 1.1310 – Limits for Maximum Permissible Exposure (MPE), Limits for General Population/Uncontrolled Exposure

Frequency range (MHz)	Power density (mW/cm ²)
300 – 1,500	f/1500
1,500 – 100,000	1.0

Calculations 850 MHz band (824.7 – 848.31 MHz)

Maximum peak output power at antenna input terminal: 33.14 dBm (~2.06 W)

Predicted distance **R**: 20 cm

Predicted frequency: 848.86 MHz

MPE limit **S**: 0.5659 mW/cm²

Equation OET bulletin 65, page 18, edition 97-01: $S = P * G / (4\pi R^2)$

S = power density

P = power input to the antenna

G = numeric gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the centre of radiation of the antenna

Maximum allowable antenna gain: max **1.40 dBi**

Prediction

The maximum allowable MPE value of 0,5498 mW/cm² will be reached in a distance of 20 cm in case that an antenna with an antenna gain of **1.40 dBi** will be used. This means that the power density levels in a distance of 20 cm are in accordance with the FCC regulations as long as the used antenna has a gain below **1.40 dBi**.

FCC ID: YR8ES101

Maximum Permissible Exposure

as specified in Table 1B of 47 CFR 1.1310 – Limits for Maximum Permissible Exposure (MPE), Limits for General Population/Uncontrolled Exposure

Frequency range (MHz)	Power density (mW/cm ²)
300 – 1,500	f/1500
1,500 – 100,000	1.0

Calculations 1900 MHz band (1851.25 – 1908.75 MHz)

Maximum peak output power at antenna input terminal: 30.75 dBm (~1.1885 W)

Prediction distance **R**: 20 cm

Prediction frequency: 1850.14 MHz

MPE limit **S**: 1 mW/cm²

Equation OET bulletin 65, page 18, edition 97-01: $S = P * G / (4\pi R^2)$

S = power density

P = power input to the antenna

G = numeric gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the centre of radiation of the antenna

Maximum allowable antenna gain for mobile/portable stations: **6.26 dBi**

Maximum allowable antenna gain for other stations: **2.26 dBi**

Prediction

The maximum allowable MPE value of 1 mW/cm² will be reached in a distance of 20 cm in case that an antenna with an antenna gain of **6.26 dBi** will be used. This means that the power density levels in a distance of 20 cm are in accordance with the FCC regulations as long as the used antenna has a gain below **6.26 dBi**. For mobile and portable stations the EIRP is restricted to 2.0 Watts, (§24.232 (c)). Therefore the maximum antenna gain is **2.26 dBi**.