

MPE Calculations : (Bluetooth)

- Frequency range : 2402 MHz ~ 2480 MHz
- Measured RF output power : 3.35 dBm
- Target Power & Tolerance : 3.00 dBm \pm 1 dB (Max. 4 dBm & Min. 2 dBm)
- Maximum antenna peak gain : 6.35 dBi
- **Maximum output power for the calculatio 4.00 dBm**

The EUT will only be used with a separation of 20 centimeters or greater between the antenna and the body of the user.

The MPE calculation for this exposure is shown below.

<ul style="list-style-type: none"> ▪ EIRP = P + G = 4.00 dBm + 6.35 dBi = 10.35 dBm = 10.84 mW 	<ul style="list-style-type: none"> - Note P = Power input to the antenna(dBm) G = Power gain of the antenna(dBi)
--	--

- Power density at the specific separation

<ul style="list-style-type: none"> ▪ S = $EIRP / (4 R^2 \pi)$ = 10.840 / (4 X 20² X π) = 0.002157 mW/cm² 	<ul style="list-style-type: none"> - Note S = Maximum power dencity(mW/cm²) EIRP = Equivalent Isotropic Radiated Power(mW) R = Distance to the center of the radiation of the antenna(20cm)
--	---

Conclusion : The exposure condition of this device is compliant with FCC rules.

The maximum permissible exposure(MPE) of the general population/Uncontrolled for this device is 1.0 mW/cm².