



FCC TEST REPORT

FOR

DATECS LTD.

BluePad-50 Plus MSR

Test Model: BluePad-50 Plus MSR

Additional Model No.: Quantum Pay PIN 451

Prepared for : DATECS LTD.
Address : 115A Tzarigradsko Shosse, Fl.4, 1784 SOFIA, Bulgaria
Prepared by : Shenzhen LCS Compliance Testing Laboratory Ltd.
Address : 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China
Tel : (+86)755-82591330
Fax : (+86)755-82591332
Web : www.LCS-cert.com
Mail : webmaster@LCS-cert.com

Date of receipt of test sample : July 05, 2023
Number of tested samples : 2
Sample No. : A070423069-1, A070423069-2
Serial number : Prototype
Date of Test : July 05, 2023 ~ July 21, 2023
Date of Report : July 22, 2023





FCC TEST REPORT
FCC CFR 47 PART 15 C (15.225)

Report Reference No. : LCSA070423069ED

Date of Issue : July 22, 2023

Testing Laboratory Name : Shenzhen LCS Compliance Testing Laboratory Ltd.

Address : 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Testing Location/ Procedure : Full application of Harmonised standards
Partial application of Harmonised standards
Other standard testing method

Applicant's Name : DATECS LTD.

Address : 115A Tzarigradsko Shosse, Fl.4, 1784 SOFIA, Bulgaria

Test Specification

Standard : FCC CFR 47 PART 15 C(15.225)

Test Report Form No : LCSEMC-1.0

TRF Originator : Shenzhen LCS Compliance Testing Laboratory Ltd.

Master TRF : Dated 2011-03

Shenzhen LCS Compliance Testing Laboratory Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen LCS Compliance Testing Laboratory Ltd. is acknowledged as copyright owner and source of the material.

Test Item Description : BluePad-50 Plus MSR

Trade Mark : BluePad-50 Plus MSR

Test Model : BluePad-50 Plus MSR

Ratings : Input: DC 5V, 1000mA
DC 3.7V by Rechargeable Li-Polymer, 620mAh

Result : Positive

Compiled by:

Kevin Huang

Kevin Huang/ Administrator

Supervised by:

Cary Luo

Cary Luo/ Technique principal

Approved by:

Gavin Liang

Gavin Liang/ Manager





FCC -- TEST REPORT

| | |
|--|---------------------------------------|
| Test Report No. : LCSA070423069ED | <u>July 22, 2023</u> Date of issue |
|--|---------------------------------------|

| | |
|--------------------------|--|
| Test Model..... | : BluePad-50 Plus MSR |
| EUT..... | : BluePad-50 Plus MSR |
| Applicant..... | : DATECS LTD. |
| Address..... | : 115A Tzarigradsko Shosse, Fl.4, 1784 SOFIA, Bulgaria |
| Telephone..... | : / |
| Fax..... | : / |
| Manufacturer..... | : DATECS LTD. |
| Address..... | : 115A Tzarigradsko Shosse, Fl.4, 1784 SOFIA, Bulgaria |
| Telephone..... | : / |
| Fax..... | : / |
| Factory..... | : DATECS LTD. |
| Address..... | : 115A Tzarigradsko Shosse, Fl.4, 1784 SOFIA, Bulgaria |
| Telephone..... | : / |
| Fax..... | : / |

| | |
|--------------------|-----------------|
| Test Result | Positive |
|--------------------|-----------------|

The test report merely corresponds to the test sample.
 It is not permitted to copy extracts of these test result without the written permission of the test laboratory.





Revision History

| Report Version | Issue Date | Revision Content | Revised By |
|----------------|---------------|------------------|------------|
| 000 | July 22, 2023 | Initial Issue | --- |
| | | | |
| | | | |





TABLE OF CONTENTS

- 1. GENERAL INFORMATION 6**
 - 1.1 Description of Device (EUT)6
 - 1.2 Support equipment List 7
 - 1.3 External I/O 7
 - 1.4 Description of Test Facility 7
 - 1.5 Statement of The Measurement Uncertainty8
 - 1.6 Measurement Uncertainty 8
 - 1.7 Description of Test Modes 8
- 2. TEST METHODOLOGY 9**
 - 2.1. EUT Configuration 9
 - 2.2. EUT Exercise9
 - 2.3 General Test Procedures9
- 3. SYSTEM TEST CONFIGURATION 10**
 - 3.1. Justification 10
 - 3.2. EUT Exercise Software10
 - 3.3. Special Accessories 10
 - 3.4. Block Diagram/Schematics 10
 - 3.5. Equipment Modifications10
 - 3.6. Test Setup10
- 4. SUMMARY OF TEST RESULTS 11**
- 5. RADIATED MEASUREMENT 12**
 - 5.1. Radiated Emission12
 - 5.2. Field Strength of Fundamental Emissions and Mask Measurement 19
- 6. BANDWIDTH OF THE OPERATING FREQUENCY 21**
 - 6.1. Standard Applicable 21
 - 6.2. Test Result 21
- 7. FREQUENCY STABILITY MEASUREMENT 22**
 - 7.1 Standard Applicable 22
 - 7.2 Test Result 22
- 8. LINE CONDUCTED EMISSIONS 23**
 - 8.1. Standard Applicable 23
 - 8.2. Block Diagram of Test Setup 23
 - 8.3. Test Results 23
- 9. ANTENNA REQUIREMENTS 26**
 - 9.1 Standard Applicable 26
 - 9.2 Antenna Connected Construction 26
- 10. LIST OF MEASURING EQUIPMENTS 27**
- 11. TEST SETUP PHOTOGRAPHS OF EUT 28**
- 12. EXTERIOR PHOTOGRAPHS OF THE EUT 28**
- 13. INTERIOR PHOTOGRAPHS OF THE EUT 28**





1. GENERAL INFORMATION

1.1 Description of Device (EUT)

| | |
|----------------------|--|
| EUT | : BluePad-50 Plus MSR |
| Test Model | : BluePad-50 Plus MSR |
| Additional Model No. | : Quantum Pay PIN 451 |
| Model Declaration | : PCB board, structure and internal of these model(s) are the same, So no additional models were tested |
| Power Supply | : Input: DC 5V, 1000mA DC 3.7V by Rechargeable Li-Polymer, 620mAh |
| Hardware Version | : 41D1xxxC1xxx |
| Software Version | : 3.0.xx.xx |
| Bluetooth | : |
| Frequency Range | : 2402MHz~2480MHz |
| Channel Number | : 40 channels for Bluetooth V5.1 (DTS)(BT LE/ BT 2LE) |
| Channel Spacing | : 2MHz for Bluetooth V5.1 (DTS)(BT LE/ BT 2LE) |
| Modulation Type | : GFSK for Bluetooth V5.1 (DTS)(BT LE/ BT 2LE) |
| Bluetooth Version | : V5.1 |
| Antenna Description | : FPC Antenna, -5.92dBi(Max.) |
| WIFI(2.4G Band) | : |
| Frequency Range | : 2412MHz~2462MHz |
| Channel Spacing | : 5MHz |
| Channel Number | : 11 Channels for 20MHz bandwidth (2412~2462MHz) |
| Modulation Type | : IEEE 802.11b: DSSS (CCK, DQPSK, DBPSK) IEEE 802.11g: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n: OFDM (64QAM, 16QAM, QPSK, BPSK) |
| Antenna Description | : PCB Antenna, 2.0dBi(Max.) |
| NFC | : |
| Operating Frequency | : 13.56MHz |
| Modulation Type | : ASK |
| Antenna Description | : Flex PCB Antenna, 0dBi(Max.) |





1.2 Support equipment List

| Manufacturer | Description | Model | Serial Number | Certificate |
|---------------------------------------|---------------|----------------|---------------|-------------|
| SHENZHEN TIANYIN ELECTRONICS CO., LTD | Power Adapter | TPA-46050200UU | --- | FCC |

Note: The adapter is supplied by lab and only use tested.

1.3 External I/O

| I/O Port Description | Quantity | Cable |
|----------------------|----------|-----------------------------|
| Type-C USB Port | 1 | USB Cable: 0.9m, unshielded |
| Dock Connector Port | 1 | N/A |

1.4 Description of Test Facility

NVLAP Accreditation Code is 600167-0.

FCC Designation Number is CN5024.

CAB identifier is CN0071.

CNAS Registration Number is L4595.

Test Firm Registration Number: 254912.

The 3m-Semi anechoic test site fulfils CISPR 16-1-4 according to ANSI C63.4:2014 and CISPR 16-1-4:2010 SVSWR requirement for radiated emission above 1GHz.





1.5 Statement of The Measurement Uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. To CISPR 16 – 4 “Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements” and is documented in the LCS quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

1.6 Measurement Uncertainty

| Test Item | Frequency Range | Uncertainty | Note |
|------------------------|-----------------|-------------|------|
| Radiation Uncertainty | 9KHz~30MHz | ±3.10dB | (1) |
| | 30MHz~200MHz | ±2.96dB | (1) |
| | 200MHz~1000MHz | ±3.10dB | (1) |
| | 1GHz~26.5GHz | ±3.80dB | (1) |
| | 26.5GHz~40GHz | ±3.90dB | (1) |
| Conduction Uncertainty | 150kHz~30MHz | ±1.63dB | (1) |
| Power disturbance | 30MHz~300MHz | ±1.60dB | (1) |

(1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

1.7 Description of Test Modes

The EUT has been tested under operating condition.

This test was performed with EUT in X, Y, Z position and the worst case was found when EUT in Y position.

AC conducted emission pre-test at both at AC 120V/60Hz and AC 240V/50Hz modes, recorded worst case.

AC conducted emission pre-test at power adapter modes, recorded worst case;

Worst-case mode and channel used for 150 KHz-30 MHz power line conducted emissions was the mode and channel with the highest output power.

Worst-case mode and channel used for 9 KHz-1000 MHz radiated emissions was the mode and channel with the highest output power.





2. TEST METHODOLOGY

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

The radiated testing was performed at an antenna-to-EUT distance of 3 meters. All radiated and conducted emissions measurement was performed at Shenzhen LCS Compliance Testing Laboratory Ltd.

2.1. EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

2.2. EUT Exercise

The EUT was operated in the engineering mode to fix the TX frequency that was for the purpose of the measurements.

According to its specifications, the EUT must comply with the requirements of the Section 15.225 under the FCC Rules Part 15 Subpart C.

2.3 General Test Procedures

2.3.1 Conducted Emissions

The EUT is placed on the turntable, which is 0.8 m above ground plane. According to the requirements in Section 6.2.1 of ANSI C63.10-2013 Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using Quasi-peak and average detector modes.

2.3.2 Radiated Emissions

The EUT is placed on a turn table, which is 0.8 m above ground plane below 1GHz and 1.5 m above ground plane above 1GHz. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna, which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the maximum emissions, exploratory radiated emission measurements were made according to the requirements in Section 6.3 of ANSI C63.10-2013.





3. SYSTEM TEST CONFIGURATION

3.1. Justification

The system was configured for testing in a continuous transmits condition.

3.2. EUT Exercise Software

The system was configured for testing in a continuous transmits condition and change test channels by key to trigger provided by applicant.

3.3. Special Accessories

| No. | Equipment | Manufacturer | Model No. | Serial No. | Length | shielded/ unshielded | Notes |
|-----|-----------|--------------|-----------|------------|--------|-------------------------|-------|
| / | / | / | / | / | / | / | / |

3.4. Block Diagram/Schematics

Please refer to the related document

3.5. Equipment Modifications

Shenzhen LCS Compliance Testing Laboratory Ltd. has not done any modification on the EUT.

3.6. Test Setup

Please refer to the test setup photo.





4. SUMMARY OF TEST RESULTS

| Applied Standard: FCC Part 15 Subpart C | | |
|---|----------------------|--------|
| Test Items | FCC Rules | Result |
| Line Conducted Emissions | §15.207(a) | PASS |
| Field Strength of Fundamental Emissions | §15.225(a)(b)(c) | PASS |
| Radiated Emissions | §15.225(d) & §15.209 | PASS |
| 20dB Bandwidth | § 15.215 | PASS |
| Frequency Stability | §15.225(e) | PASS |
| Antenna Requirement | §15.203 | PASS |





5. RADIATED MEASUREMENT

5.1. Radiated Emission

5.1.1. Standard Applicable

According to §15.209/ §15.205

15.205 (a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

| MHz | MHz | MHz | GHz |
|-------------------|---------------------|---------------|-------------|
| 0.090-0.110 | 16.42-16.423 | 399.9-410 | 4.5-5.15 |
| \1\ 0.495-0.505 | 16.69475-16.69525 | 608-614 | 5.35-5.46 |
| 2.1735-2.1905 | 16.80425-16.80475 | 960-1240 | 7.25-7.75 |
| 4.125-4.128 | 25.5-25.67 | 1300-1427 | 8.025-8.5 |
| 4.17725-4.17775 | 37.5-38.25 | 1435-1626.5 | 9.0-9.2 |
| 4.20725-4.20775 | 73-74.6 | 1645.5-1646.5 | 9.3-9.5 |
| 6.215-6.218 | 74.8-75.2 | 1660-1710 | 10.6-12.7 |
| 6.26775-6.26825 | 108-121.94 | 1718.8-1722.2 | 13.25-13.4 |
| 6.31175-6.31225 | 123-138 | 2200-2300 | 14.47-14.5 |
| 8.291-8.294 | 149.9-150.05 | 2310-2390 | 15.35-16.2 |
| 8.362-8.366 | 156.52475-156.52525 | 2483.5-2500 | 17.7-21.4 |
| 8.37625-8.38675 | 156.7-156.9 | 2690-2900 | 22.01-23.12 |
| 8.41425-8.41475 | 162.0125-167.17 | 3260-3267 | 23.6-24.0 |
| 12.29-12.293 | 167.72-173.2 | 3332-3339 | 31.2-31.8 |
| 12.51975-12.52025 | 240-285 | 3345.8-3358 | 36.43-36.5 |
| 12.57675-12.57725 | 322-335.4 | 3600-4400 | (\2\) |
| 13.36-13.41 | | | |

\1\ Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

\2\ Above 38.6

According to §15.247 (d): 20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

| Frequencies (MHz) | Field Strength (microvolts/meter) | Measurement Distance (meters) |
|-------------------|-----------------------------------|-------------------------------|
| 0.009~0.490 | 2400/F(KHz) | 300 |
| 0.490~1.705 | 24000/F(KHz) | 30 |
| 1.705~30.0 | 30 | 30 |
| 30~88 | 100 | 3 |
| 88~216 | 150 | 3 |
| 216~960 | 200 | 3 |
| Above 960 | 500 | 3 |

5.1.2. Measuring Instruments and Setting

Please refer to equipment list in this report. The following table is the setting of spectrum analyzer and receiver.

| Spectrum Parameter | Setting |
|---|---|
| Attenuation | Auto |
| Start Frequency | 1000 MHz |
| Stop Frequency | 10 th carrier harmonic |
| RB / VB (Emission in restricted band) | 1MHz / 1MHz for Peak, 1 MHz / 1/B kHz for Average |
| RB / VB (Emission in non-restricted band) | 1MHz / 1MHz for Peak, 1 MHz / 1/B kHz for Average |





| Receiver Parameter | Setting |
|------------------------|--|
| Attenuation | Auto |
| Start ~ Stop Frequency | 9kHz~150kHz / RB/VB 200Hz/1KHz for QP/AVG |
| Start ~ Stop Frequency | 150kHz~30MHz / RB/VB 9kHz/30KHz for QP/AVG |
| Start ~ Stop Frequency | 30MHz~1000MHz / RB/VB 120kHz/1MHz for QP |

5.1.3. Test Procedures

1) Sequence of testing 9 kHz to 30 MHz

Setup:

- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
- If the EUT is a tabletop system, a rotatable table with 0.8 m height is used.
- If the EUT is a floor standing device, it is placed on the ground.
- Auxiliary equipment and cables were positioned to simulate normal operation conditions.
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- The measurement distance is 3 meter.
- The EUT was set into operation.

Premeasurement:

- The turntable rotates from 0° to 315° using 45° steps.
- The antenna height is 1.0 meter.
- At each turntable position the analyzer sweeps with peak detection to find the maximum of all emissions

Final measurement:

- Identified emissions during the premeasurement the software maximizes by rotating the turntable position (0° to 360°) and by rotating the elevation axes (0° to 360°).
- The final measurement will be done in the position (turntable and elevation) causing the highest emissions with QPK detector.
- The final levels, frequency, measuring time, bandwidth, turntable position, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement and the limit will be stored.





2) Sequence of testing 30 MHz to 1 GHz

Setup:

- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
- If the EUT is a tabletop system, a table with 0.8 m height is used, which is placed on the ground plane.
- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.
- Auxiliary equipment and cables were positioned to simulate normal operation conditions
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- The measurement distance is 3 meter.
- The EUT was set into operation.

Premeasurement:


- The turntable rotates from 0° to 315° using 45° steps.
- The antenna is polarized vertical and horizontal.
- The antenna height changes from 1 to 3 meter.
- At each turntable position, antenna polarization and height the analyzer sweeps three times in peak to find the maximum of all emissions.

Final measurement:


- The final measurement will be performed with minimum the six highest peaks.
- According to the maximum antenna and turntable positions of premeasurement the software maximize the peaks by changing turntable position ($\pm 45^\circ$) and antenna movement between 1 and 4 meter.
- The final measurement will be done with QP detector with an EMI receiver.
- The final levels, frequency, measuring time, bandwidth, antenna height, antenna polarization, turntable angle, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement with marked maximum final measurements and the limit will be stored.



5.1.4. Test Setup Layout



Below 30MHz



Below 1GHz





5.1.5. Test Results

| | | | |
|---------------|-----------|----------------|-------|
| Temperature | 23.8°C | Humidity | 52.1% |
| Test Engineer | Taylor Hu | Configurations | NFC |


PASS.

The test data please refer to following page:

9 KHz~30MHz

Note: Only recorded the worst test result.

X axis



| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector |
|-----|-----------------|----------------|---------------|----------------|----------------|-------------|----------|
| 1 | 13.6584 | 72.54 | -10.02 | 62.52 | 69.54 | -7.02 | QP |

Remark:

- 1). X axis / Y axis/ Z axis were tested,report only recorded the worst result of X axis..
- 2). Margin=Reading level + Factor- Limit






30MHz ~ 1GHz

Horizontal:

70.0 dBuV/m




| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector |
|-----|-----------------|----------------|---------------|----------------|----------------|-------------|----------|
| 1 | 36.8953 | 30.06 | -17.70 | 12.36 | 40.00 | -27.64 | QP |
| 2 | 57.7962 | 35.95 | -18.45 | 17.50 | 40.00 | -22.50 | QP |
| 3 | 75.9773 | 40.68 | -19.72 | 20.96 | 40.00 | -19.04 | QP |
| 4 | 192.4185 | 34.33 | -17.35 | 16.98 | 43.50 | -26.52 | QP |
| 5 | 385.2804 | 30.66 | -14.60 | 16.06 | 46.00 | -29.94 | QP |
| 6 | 578.6700 | 29.85 | -10.80 | 19.05 | 46.00 | -26.95 | QP |





Vertical:

70.0 dBuV/m



| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector |
|-----|-----------------|----------------|---------------|----------------|----------------|-------------|----------|
| 1 | 31.9545 | 30.84 | -18.19 | 12.65 | 40.00 | -27.35 | QP |
| 2 | 59.4405 | 32.58 | -18.75 | 13.83 | 40.00 | -26.17 | QP |
| 3 | 78.6887 | 35.36 | -19.83 | 15.53 | 40.00 | -24.47 | QP |
| 4 | 192.4185 | 34.69 | -18.11 | 16.58 | 43.50 | -26.92 | QP |
| 5 | 372.0045 | 29.69 | -14.75 | 14.94 | 46.00 | -31.06 | QP |
| 6 | 605.6592 | 28.77 | -10.59 | 18.18 | 46.00 | -27.82 | QP |

Note:

Pre-scan all modes and recorded the worst case results in this report.

Emission level (dBuV/m) = 20 log Emission level (uV/m).


Corrected Reading: Factor + Read Level = Level.

Margin=Level – Limit.




5.2. Field Strength of Fundamental Emissions and Mask Measurement

5.2.1. Block Diagram of Test Setup



Below 30MHz



Below 1GHz

5.2.2. Field strength of fundamental emissions limit and Mask limit

The field strength of fundamental emissions shall not exceed 15848 microvolts/meter at 30 meters. The emissions limit in this paragraph is based on measurement instrumentation employing a QP detector.

| Frequencies (MHz) | Field Strength (microvolts/meter) | Field Strength (dB μ V/m) at 10m | Field Strength (dB μ V/m) at 3m |
|--------------------|-----------------------------------|--------------------------------------|-------------------------------------|
| 13.553 ~ 13.567MHz | 15848 at 30m | 103.08 (QP) | 124 (QP) |

Mask Limit:

| Frequency (MHz) | Limit (dB μ V/m) | Distance (m) |
|-----------------|----------------------|--------------|
| 1.705-13.110 | 69.5 | 3 |
| 13.110-13.410 | 80.5 | 3 |
| 13.410-13.553 | 90.5 | 3 |
| 13.553-13.567 | 124.0 | 3 |
| 13.567-13.710 | 90.5 | 3 |
| 13.710-14.010 | 80.5 | 3 |
| 14.010-30.000 | 69.5 | 3 |






5.2.3. Test Results

| | | | |
|---------------|-----------|----------------|-------|
| Temperature | 23.7°C | Humidity | 52.6% |
| Test Engineer | Taylor Hu | Configurations | NFC |

PASS.

The test data please refer to following page:

X axis



| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector |
|-----|-----------------|----------------|---------------|----------------|----------------|-------------|----------|
| 1 | 13.5600 | 74.38 | -10.01 | 64.37 | 124.00 | -59.63 | QP |

*Note: Factor= Antenna Factor + Cable Loss

Measured= Reading + Factor, Margin= Measured - Limit
Emission level (dBμV/m) = 20 log Emission level (μV/m).

Measured distance is 3m.

All emissions emit from non-NFC function of digital unintentional emissions. All NFC's spurious emissions are below 20dB of limits.

X axis / Y axis/ Z axis were tested,report only recorded the worst result of X axis.





6. BANDWIDTH OF THE OPERATING FREQUENCY


6.1. Standard Applicable

Intentional radiators must be designed to ensure that the 20 dB bandwidth of the emissions in the specific band (13.553 ~ 13.567MHz).

6.2. Test Result

| | |
|-------------------------|----------------------|
| EUT | BluePad-50 Plus MSR |
| RBW | 100Hz |
| VBW | 100Hz |
| SPAN | 500Hz |
| Carrier Frequency (MHz) | 20dB Bandwidth (KHz) |
| 13.56 | 0.246 |

Please refer to the test plot:





7. FREQUENCY STABILITY MEASUREMENT

7.1 Standard Applicable

The frequency tolerance of the carrier signal shall be maintained within +/- 0.01% (100ppm) of the operating frequency over a temperature variation of -20 degrees to +50 degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C. For battery operated equipment, the equipment tests shall be performed using a full charged battery.

7.2 Test Result

Voltage vs. Frequency Stability

| Voltage(V) | Measurement Frequency (MHz) | Deviation (KHz) | Deviation (ppm) | Limit (ppm) |
|------------|-----------------------------|-----------------|-----------------|-------------|
| VN | 13.56047 | 0.47 | 34.47 | 100 |
| VL | 13.56035 | 0.35 | 25.51 | 100 |
| VH | 13.56021 | 0.21 | 15.53 | 100 |

Temperature vs. Frequency Stability

| Temperature (°C) | Measurement Frequency (MHz) | Deviation (KHz) | Deviation (ppm) | Limit (ppm) |
|------------------|-----------------------------|-----------------|-----------------|-------------|
| -20 | 13.56028 | 0.28 | 20.78 | 100 |
| -10 | 13.56018 | 0.18 | 13.31 | 100 |
| 0 | 13.56036 | 0.36 | 26.73 | 100 |
| 10 | 13.56035 | 0.35 | 25.48 | 100 |
| 20 | 13.56045 | 0.45 | 33.22 | 100 |
| 30 | 13.56029 | 0.29 | 21.07 | 100 |
| 40 | 13.56045 | 0.45 | 33.47 | 100 |
| 50 | 13.56028 | 0.28 | 20.30 | 100 |



8. LINE CONDUCTED EMISSIONS


8.1. Standard Applicable

According to §15.207(a): For an intentional radiator which is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed 250 microvolts (The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz). The limits at specific frequency range are listed as follows:

| Frequency Range (MHz) | Limits (dBµV) | |
|-----------------------|---------------|----------|
| | Quasi-peak | Average |
| 0.15 to 0.50 | 66 to 56 | 56 to 46 |
| 0.50 to 5 | 56 | 46 |
| 5 to 30 | 60 | 50 |

* Decreasing linearly with the logarithm of the frequency

8.2. Block Diagram of Test Setup



8.3. Test Results

PASS.

| | | | |
|---------------|-----------|----------------|-------|
| Temperature | 23.5°C | Humidity | 53.6% |
| Test Engineer | Taylor Hu | Configurations | NFC |


The test data please refer to following page.





AC Conducted Emission @ AC 120V/60Hz (worst case)

Line




| No. | Mk. | Freq. MHz | Reading Level dBuV | Correct Factor dB | Measure- ment dBuV | Limit dBuV | Margin dB | Detector | Comment |
|-----|-----|--------------|--------------------------|-------------------------|--------------------------|---------------|--------------|----------|---------|
| 1 | | 0.1861 | 15.85 | 19.63 | 35.48 | 64.21 | -28.73 | QP | |
| 2 | | 0.1861 | 4.82 | 19.63 | 24.45 | 54.21 | -29.76 | AVG | |
| 3 | * | 0.5326 | 23.54 | 19.65 | 43.19 | 56.00 | -12.81 | QP | |
| 4 | | 0.5326 | 9.98 | 19.65 | 29.63 | 46.00 | -16.37 | AVG | |
| 5 | | 0.8836 | 14.15 | 19.64 | 33.79 | 56.00 | -22.21 | QP | |
| 6 | | 0.8836 | -0.36 | 19.64 | 19.28 | 46.00 | -26.72 | AVG | |
| 7 | | 1.2121 | 13.94 | 19.66 | 33.60 | 56.00 | -22.40 | QP | |
| 8 | | 1.2121 | 0.96 | 19.66 | 20.62 | 46.00 | -25.38 | AVG | |
| 9 | | 2.2426 | 11.17 | 19.68 | 30.85 | 56.00 | -25.15 | QP | |
| 10 | | 2.2516 | -3.34 | 19.68 | 16.34 | 46.00 | -29.66 | AVG | |
| 11 | | 6.5266 | 12.16 | 19.72 | 31.88 | 60.00 | -28.12 | QP | |
| 12 | | 6.5266 | 0.20 | 19.72 | 19.92 | 50.00 | -30.08 | AVG | |





Neutral

dBuV



| No. | Mk. | Freq. MHz | Reading Level dBuV | Correct Factor dB | Measure- ment dBuV | Limit dBuV | Margin dB | Detector | Comment |
|-----|-----|--------------|--------------------------|-------------------------|--------------------------|---------------|--------------|----------|---------|
| 1 | | 0.1861 | 18.03 | 19.63 | 37.66 | 64.21 | -26.55 | QP | |
| 2 | | 0.1861 | 5.85 | 19.63 | 25.48 | 54.21 | -28.73 | AVG | |
| 3 | * | 0.5235 | 21.35 | 19.65 | 41.00 | 56.00 | -15.00 | QP | |
| 4 | | 0.5235 | 10.85 | 19.65 | 30.50 | 46.00 | -15.50 | AVG | |
| 5 | | 0.7125 | 14.76 | 19.65 | 34.41 | 56.00 | -21.59 | QP | |
| 6 | | 0.7125 | 2.47 | 19.65 | 22.12 | 46.00 | -23.88 | AVG | |
| 7 | | 1.1310 | 14.28 | 19.65 | 33.93 | 56.00 | -22.07 | QP | |
| 8 | | 1.1310 | 2.05 | 19.65 | 21.70 | 46.00 | -24.30 | AVG | |
| 9 | | 2.6746 | 13.03 | 19.71 | 32.74 | 56.00 | -23.26 | QP | |
| 10 | | 2.6746 | -1.31 | 19.71 | 18.40 | 46.00 | -27.60 | AVG | |
| 11 | | 6.5176 | 11.62 | 19.82 | 31.44 | 60.00 | -28.56 | QP | |
| 12 | | 6.5176 | -2.57 | 19.82 | 17.25 | 50.00 | -32.75 | AVG | |

Measurement = Reading + Correct, Margin = Measurement - Limit.
 Correct Factor = Lism Factor + Cable Factor





9. ANTENNA REQUIREMENTS

9.1 Standard Applicable

According to antenna requirement of §15.203.

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be re-placed by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of Sections 15.211, 15.213, 15.217, 15.219, or 15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with Section 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this Part are not exceeded.

9.2 Antenna Connected Construction

9.2.1. Standard Applicable

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

9.2.2. Antenna Connector Construction

The gains of antenna used for transmitting is 0dBi, and the antenna is Flex PCB Antenna connect to PCB board and no consideration of replacement. Please see the antenna photo for details.

9.2.3. Results: Compliance.





10. LIST OF MEASURING EQUIPMENTS

| Item | Equipment | Manufacturer | Model No. | Serial No. | Cal Date | Due Date |
|------|--------------------------|-------------------|-------------|-----------------|------------|------------|
| 1 | Power Meter | R&S | NRVS | 100444 | 2023-06-15 | 2024-06-14 |
| 2 | Power Sensor | R&S | NRV-Z81 | 100458 | 2023-06-15 | 2024-06-14 |
| 3 | Power Sensor | R&S | NRV-Z32 | 10057 | 2023-06-15 | 2024-06-14 |
| 4 | Test Software | Tonscend | JS1120-2 | / | N/A | N/A |
| 5 | RF Control Unit | Tonscend | JS0806-2 | N/A | 2022-10-29 | 2023-10-28 |
| 6 | MXA Signal Analyzer | Agilent | N9020A | MY50510140 | 2022-10-29 | 2023-10-28 |
| 7 | DC Power Supply | Agilent | E3642A | N/A | 2022-10-29 | 2023-10-28 |
| 8 | EMI Test Software | AUDIX | E3 | / | N/A | N/A |
| 9 | 3m Semi Anechoic Chamber | SIDT FRANKONIA | SAC-3M | 03CH03-HY | 2023-06-15 | 2024-06-14 |
| 10 | Positioning Controller | Max-Full | MF7802BS | MF780208586 | N/A | N/A |
| 11 | Active Loop Antenna | SCHWARZBECK | FMZB 1519B | 00005 | 2021-08-29 | 2024-08-28 |
| 12 | By-log Antenna | SCHWARZBECK | VULB9163 | 9163-470 | 2021-09-12 | 2024-09-11 |
| 13 | Horn Antenna | SCHWARZBECK | BBHA 9120D | 9120D-1925 | 2021-09-05 | 2024-09-04 |
| 14 | Broadband Horn Antenna | SCHWARZBECK | BBHA 9170 | 791 | 2021-08-29 | 2024-08-28 |
| 15 | Broadband Preamplifier | SCHWARZBECK | BBV9719 | 9719-025 | 2023-06-15 | 2024-06-14 |
| 16 | EMI Test Receiver | R&S | ESR 7 | 101181 | 2023-06-15 | 2024-06-14 |
| 17 | RS SPECTRUM ANALYZER | R&S | FSP40 | 100503 | 2022-10-29 | 2023-10-28 |
| 18 | Broadband Preamplifier | / | BP-01M18G | P190501 | 2023-06-15 | 2024-06-14 |
| 19 | 6dB Attenuator | / | 100W/6dB | 1172040 | 2023-06-15 | 2024-06-14 |
| 20 | 3dB Attenuator | / | 2N-3dB | / | 2022-10-29 | 2023-10-28 |
| 21 | EMI Test Receiver | R&S | ESPI | 101940 | 2022-08-18 | 2023-08-17 |
| 22 | Artificial Mains | R&S | ENV216 | 101288 | 2023-06-15 | 2024-06-14 |
| 23 | 10dB Attenuator | SCHWARZBECK | MTS-IMP-136 | 261115-001-0032 | 2023-06-15 | 2024-06-14 |
| 24 | EMI Test Software | Farad | EZ | / | N/A | N/A |





11. Test Setup Photographs of Eut

Please refer to separated files for Test Setup Photos of the EUT.

12. Exterior Photographs of the Eut

Please refer to separated files for Exterior Photos of the EUT.

13. Interior Photographs of the Eut

Please refer to separated files for Interior Photos of the EUT.

-----THE END OF REPORT-----

