

Wi-Fi 5GHz (Baseline)

Frequency: 5620 MHz; Duty Cycle: 1:1; Room Ambient Temperature: 24.0°C; Liquid Temperature: 23.0°C

Medium parameters used: $f = 5620$ MHz; $\sigma = 5.859$ S/m; $\epsilon_r = 46.246$; $\rho = 1000$ kg/m³

DASY5 Configuration:

- Area Scan Setting: Find Secondary Maximum Within: 2.0 dB and with a peak SAR value greater than 0.0012W/kg
- Electronics: DAE4 Sn1357; Calibrated: 2/20/2015
- Probe: EX3DV4 - SN3901; ConvF(3.8, 3.8, 3.8); Calibrated: 1/27/2015;
- Sensor-Surface: 2mm (Mechanical Surface Detection (Locations From Previous Scan Used)), Sensor-Surface: 2mm (Mechanical Surface Detection)
- Phantom: ELI v4.0 (B); Type: QDOVA001BB; Serial: 1099

Rear/802.11a_Ch 124/Area Scan (9x16x1): Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (measured) = 1.81 W/kg


Rear/802.11a_Ch 124/Zoom Scan (7x7x12)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 16.224 V/m; Power Drift = 0.35 dB

Peak SAR (extrapolated) = 4.14 W/kg

SAR(1 g) = 0.927 W/kg; SAR(10 g) = 0.262 W/kg

Maximum value of SAR (measured) = 1.94 W/kg



0 dB = 1.94 W/kg = 2.88 dBW/kg

Report No.: 12U14485-8A
 FCC ID: BCG-A142

Issue Date: 9/5/2012

Test Laboratory: UL CCS SAR Lab C

Date: 8/2/2012

WiFi 5.5GHz


Frequency: 5620 MHz; Duty Cycle: 1:1; Room Ambient Temperature: 25.0°C; Liquid Temperature: 24.0°C
 Medium parameters used: $f = 5620$ MHz; $\sigma = 5.904$ mho/m; $\epsilon_r = 50.36$; $\rho = 1000$ kg/m³

DASY5 Configuration:

- Area Scan setting - Find Secondary Maximum Within: 2.0 dB and with a peak SAR value greater than 0.0012W/kg
- Electronics: DAE4 9n1239; Calibrated: 6/6/2012
- Probe: EXGOV4 - 9N3773; ComF(3.46, 3.46, 3.46); Calibrated: 3/14/2012
- Sensor-Surface: 2.5mm (Mechanical Surface Detection (Locations From Previous Scan Used)), Sensor-Surface: 2mm (Mechanical Surface Detection)
- Phantom: ELI v5.0 (A); Type: QDOVA001BB; Serial: 1120

Front/802.11a_Ch 124/Area Scan (10x15x1): Measurement grid: dx=10mm, dy=10mm
 Maximum value of SAR (measured) = 1.579 mW/g

Front/802.11a_Ch 124/Zoom Scan (7x7x12)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm
 Reference Value = 17.655 V/m; Power Drift = -0.18 dB
 Peak SAR (extrapolated) = 4.9650
 SAR(1 g) = 1.13 mW/g; SAR(10 g) = 0.316 mW/g
 Maximum value of SAR (measured) = 2.286 mW/g



0 dB = 2.290mW/g = 7.20 dB mW/g