

WGI Innovations, Ltd.

YN1 MODULE

Model: YN1-rx



15 August, 2011

Report No.: 11020861-FCC Part 15.247
(This report supersedes NONE)



Modifications made to the product : None

This Test Report is Issued Under the Authority of:


	
Peter Cai Compliance Engineer	Spring Zhou Technical Director

This test report may be reproduced in full only.
Test result presented in this test report is applicable to the representative sample only.

RF Test Report

TO: FCC 15.247:2010

SIEMIC, INC.
Accessing global markets



Laboratory Introduction

SIEMIC, headquartered in the heart of Silicon Valley, with superior facilities in US and Asia, is one of the leading independent testing and certification facilities providing customers with one-stop shop services for Compliance Testing and Global Certifications.




In addition to [testing](#) and [certification](#), SIEMIC provides initial design reviews and [compliance management](#) through out a project. Our extensive experience with [China](#), [Asia Pacific](#), [North America](#), [European](#), and [international](#) compliance requirements, assures the fastest, most cost effective way to attain regulatory compliance for the [global markets](#).

Accreditations for Conformity Assessment

Country/Region	Accreditation Body	Scope
USA	FCC, A2LA	EMC , RF/Wireless , Telecom
Canada	IC, A2LA, NIST	EMC, RF/Wireless , Telecom
Taiwan	BSMI , NCC , NIST	EMC, RF, Telecom , Safety
Hong Kong	OFTA , NIST	RF/Wireless ,Telecom
Australia	NATA, NIST	EMC, RF, Telecom , Safety
Korea	KCC/RRA, NIST	EMI, EMS, RF , Telecom, Safety
Japan	VCCI, JATE, TELEC, RFT	EMI, RF/Wireless, Telecom
Mexico	NOM, COFETEL, Caniety	Safety, EMC , RF/Wireless, Telecom
Europe	A2LA, NIST	EMC, RF, Telecom , Safety

Accreditations for Product Certifications

Country	Accreditation Body	Scope
USA	FCC TCB, NIST	EMC , RF , Telecom
Canada	IC FCB , NIST	EMC , RF , Telecom
Singapore	iDA, NIST	EMC , RF , Telecom
EU	NB	EMC & R&TTE Directive



SIEMIC, INC.
Accessing global markets

Title: RF Test Report for YN1 MODULE
Model: YN1-rx
To: FCC 15.247:2010

Serial#: 11020861-FCC Part 15.247
Issue Date: 15 August, 2011
Page: 3 of 86
www.siemic.com.cn

This page has been left blank intentionally.



CONTENTS

1	EXECUTIVE SUMMARY & EUT INFORMATION	5
2	TECHNICAL DETAILS	6
3	MODIFICATION	7
4	TEST SUMMARY	8
5	MEASUREMENTS, EXAMINATION AND DERIVED RESULTS	9
	ANNEX A. TEST INSTRUMENT & METHOD.....	68
	ANNEX B. EUT AND TEST SETUP PHOTOGRAPHS	72
	ANNEX C. TEST SETUP AND SUPPORTING EQUIPMENT.....	79
	ANNEX D. USER MANUAL / BLOCK DIAGRAM / SCHEMATICS / PART LIST	83
	ANNEX E. SIEMIC ACCREDITATION CERTIFICATES.....	84



1 Executive Summary & EUT information

The purpose of this test programme was to demonstrate compliance of the WGI Innovations, Ltd., YN1 MODULE, and model: YN1-rx against the current Stipulated Standards. The YN1 MODULE has demonstrated compliance with the FCC 15.247:2010.

EUT Information

EUT	
Description	YN1 MODULE
Model No	YN1-rx (Note)
Serial No	N/A
Input Power	5VDC
Classification	
Per Stipulated	Spread Spectrum System/Device
Test Standard	

Note: SCA1 has the same design as YN1. The only difference is the board, packages and enclosure coatings.



SIEMIC, Inc.


Accessing global markets

Title: RF Test Report for YN1 MODULE
Model: YN1-rx
To: FCC 15.247:2010

Serial#: 11020861-FCC Part 15.247
Issue Date: 15 August, 2011
Page: 6 of 86
www.siemic.com.cn

2 TECHNICAL DETAILS

Purpose	Compliance testing of YN1 MODULE with stipulated standard
Applicant / Client	WGI Innovations, Ltd. 602 Fountain Parkway Grand Prairie, TX 75050, U.S.A.
Manufacturer	Haojia Electronic (Shenzhen) Ltd. Fangmapu, Gui Hua Village, Guanlan, Baoan, Shenzhen, Guangdong 518110
Laboratory performing the tests	SIEMIC Nanjing (China) Laboratories NO.2-1,Longcang Dadao, Yuhua Economic Development Zone, Nanjing, China Tel:+86(25)86730128/86730129 Fax:+86(25)86730127 Email:info@siemic.com
Test report reference number	11020861-FCC Part 15.247
Date EUT received	29 July, 2011
Standard applied	FCC 15.247:2010
Dates of test	11 August, 2011
No of Units :	1
Equipment Category :	DTS
Trade Name :	Wildgame Innovations
Model :	YN1-rx
RF Operating Frequency (ies)	2.4GHz TX: 2412MHz – 2462MHz & 2422MHz – 2452MHz 433MHz RX
Number of Channels :	2.4GHz TX: 11ch for 802.11b/g/n-20MHz; 7ch for 802.11n-40MHz
Modulation :	802.11b/g/n
FCC ID :	YTT-YN1MODULE



SIEMIC, Inc.
Accessing global markets

Title: RF Test Report for YN1 MODULE
Model: YN1-rx
To: FCC 15.247:2010

Serial#: 11020861-FCC Part 15.247
Issue Date: 15 August, 2011
Page: 7 of 86
www.siemac.com.cn

3 MODIFICATION

NONE

4 TEST SUMMARY

The product was tested in accordance with the following specifications.
All testing has been performed according to below product classification:

Spread Spectrum System/Device

Test Results Summary

Test Standard	Description	Pass / Fail
CFR 47 Part 15.247: 2010		
15.203	Antenna Requirement	Pass
15.205	Restricted Band of Operation	Pass
15.207(a)	Conducted Emissions Voltage	Pass
15.247(a)(1)	Channel Separation	N/A
15.247(a)(1)	Occupied Bandwidth	Pass
15.247(a)(2)	6dB Bandwidth	Pass
15.247(a)(1)	Number of Hopping Channels	N/A
15.247(a)(1)	Time of Occupancy	N/A
15.247(b)	Output Power	Pass
15.247(c)	Antenna Gain > 6 dBi	Pass
15.247(d)	Conducted Spurious Emissions	Pass
15.209; 15.247(d)	Radiated Spurious Emissions	Pass
15.247(e)	Power Spectral Density	Pass
15.247(f)	Hybrid System Requirement	N/A
15.247(g)	Hopping Capability	N/A
15.247(h)	Hopping Coordination Requirement	N/A
15.247(i)	RF Exposure requirement	Pass

ANSI C63.4: 2009

PS: All measurement uncertainties are not taken into consideration for all presented test result.

5 MEASUREMENTS, EXAMINATION AND DERIVED RESULTS

5.1 Antenna Requirement

Requirement(s): 47 CFR §15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

Antenna requirement must meet at least one of the following:

- a) Antenna must be permanently attached to the device.
- b) Antenna must use a unique type of connector to attach to the device.
- c) Device must be professionally installed. Installer shall be responsible for ensuring that the correct antenna is employed with the device.

The EUT antenna is using a unique type of connector. Antenna maximum gain is 2.2dBi.

5.2 Conducted Emissions Voltage

Requirement:

Frequency of emission (MHz)	Conducted limit (dBμV)	
	Quasi-peak	Average
0.15–0.5	66 to 56*	56 to 46*
0.5–5	56	46
5–30	60	50

*Decreases with the logarithm of the frequency.

Procedures:

1. All possible modes of operation were investigated. Only the 6 worst case emissions measured, using the correct CISPR and Average detectors, are reported. All other emissions were relatively insignificant.
2. A "-ve" margin indicates a PASS as it refers to the margin present below the limit line at the particular frequency.
3. Conducted Emissions Measurement Uncertainty
All test measurements carried out are traceable to national standards. The uncertainty of the measurement at a confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2, in the range 9kHz – 30MHz (Average & Quasi-peak) is ±3.5dB.
4. Environmental Conditions

Temperature	23°C
Relative Humidity	50%
Atmospheric Pressure	1019mbar
5. Test date : N/A
Tested By : Peter Cai

Note: Not applicable because equipment is battery operated.

5.3 6dB Occupied Bandwidth

1. Conducted Measurement
EUT was set for low, mid, high channel with modulated mode and highest RF output power. The spectrum analyzer was connected to the antenna terminal.
2. Environmental Conditions

Temperature	23°C
Relative Humidity	50%
Atmospheric Pressure	1019mbar
3. Conducted Emissions Measurement Uncertainty
All test measurements carried out are traceable to national standards. The uncertainty of the measurement at a confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2, in the range 30MHz – 40GHz is ±1.5dB.
4. Test date : 11 August, 2011
Tested By : Peter Cai


Requirement(s): 47 CFR § 15.247(a)(1)

Procedures: The 6dB Bandwidths were measured conducted using a spectrum analyzer at low, mid, and hi channels. 6dB Bandwidth Limit: >500kHz.


Protocol	Channel	Channel Frequency (MHz)	6dB Occupied Bandwidth Limit (MHz)	6dB Channel Bandwidth (MHz)
802.11b	Low	2412	0.5	11.17
802.11b	Mid	2437	0.5	11.33
802.11b	High	2462	0.5	11.33
802.11g	Low	2412	0.5	16.50
802.11g	Mid	2437	0.5	16.58
802.11g	High	2462	0.5	16.67
802.11n-20MHz	Low	2412	0.5	17.67
802.11n-20MHz	Mid	2437	0.5	17.67
802.11n-20MHz	High	2462	0.5	17.75
802.11n-40MHz	Low	2422	0.5	36.50
802.11n-40MHz	Mid	2437	0.5	36.20
802.11n-40MHz	High	2452	0.5	36.30




Refer to the attached plots.




6dB Bandwidth – Low Channel (802.11b)



6dB Bandwidth – Mid Channel (802.11b)



6dB Bandwidth – Low Channel (802.11n-20MHz)



6dB Bandwidth – Mid Channel (802.11n-20MHz)

5.4 Power Spectral Density

1. Conducted Measurement
EUT was set for low, mid, high channel with modulated mode and highest RF output power.
The spectrum analyzer was connected to the antenna terminal.
2. Environmental Conditions

Temperature	23°C
Relative Humidity	50%
Atmospheric Pressure	1019mbar
3. Conducted Emissions Measurement Uncertainty
All test measurements carried out are traceable to national standards. The uncertainty of the measurement at a confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2, in the range 30MHz – 40GHz is ±1.5dB.
4. Test date : 11 August, 2011
Tested By : Peter Cai

Requirement(s): 47 CFR § 15.247(e)

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3KHz band during any time interval of continuous transmission.


Procedures: The power spectral density measurement was taken conducted using a spectrum analyzer.

RBW=3KHz, VBW>RBW, Sweep time to SPAN/RBW(s).


The result:

Protocol	Channel	Channel Frequency (MHz)	Peak Spectral Density Limit (dBm/3KHz)	Peak Spectral Density (dBm/3KHz)
802.11b	Low	2412	8	-6.33
802.11b	Mid	2437	8	-6.33
802.11b	High	2462	8	-4.83
802.11g	Low	2412	8	-15.33
802.11g	Mid	2437	8	-16.17
802.11g	High	2462	8	-16.33
802.11n-20MHz	Low	2412	8	-14.33
802.11n-20MHz	Mid	2437	8	-14.83
802.11n-20MHz	High	2462	8	-18.17
802.11n-40MHz	Low	2422	8	-19.17
802.11n-40MHz	Mid	2437	8	-19.17
802.11n-40MHz	High	2452	8	-19.17


Refer to the attached plots.




PSD - Low Channel (802.11b)



PSD - Mid Channel (802.11b)



PSD - High Channel (802.11b)




PSD - Low Channel (802.11g)




SIEMIC, INC.
Accessing global markets

Title: RF Test Report for YN1 MODULE
Model: YN1-rx
To: FCC 15.247:2010

Serial#: 11020861-FCC Part 15.247
Issue Date: 15 August, 2011
Page: 21 of 86
www.siemec.com.cn



PSD - Mid Channel (802.11g)




PSD - High Channel (802.11g)




SIEMIC, INC.
Accessing global markets

Title: RF Test Report for YN1 MODULE
Model: YN1-rx
To: FCC 15.247.2010

Serial#: 11020861-FCC Part 15.247
Issue Date: 15 August, 2011
Page: 22 of 86
www.siemec.com.cn



PSD - Low Channel (802.11n-20MHz)




PSD - Mid Channel (802.11n-20MHz)




SIEMIC, INC.
Accessing global markets

Title: RF Test Report for YN1 MODULE
Model: YN1-rx
To: FCC 15.247.2010

Serial#: 11020861-FCC Part 15.247
Issue Date: 15 August, 2011
Page: 23 of 86
www.siemec.com.cn



PSD - High Channel (802.11n-20MHz)




PSD - Low Channel (802.11n-40MHz)




SIEMIC, INC.
Accessing global markets

Title: RF Test Report for YN1 MODULE
Model: YN1-rx
To: FCC 15.247:2010

Serial#: 11020861-FCC Part 15.247
Issue Date: 15 August, 2011
Page: 24 of 86
www.siemec.com.cn



PSD - Mid Channel (802.11n-40MHz)



PSD - High Channel (802.11n-40MHz)

5.5 Peak Output Power

1. **Conducted Measurement**
EUT was set for low, mid, high channel with modulated mode and highest RF output power. The spectrum analyzer was connected to the antenna terminal.
2. **Conducted Emissions Measurement Uncertainty**
All test measurements carried out are traceable to national standards. The uncertainty of the measurement at a confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2, in the range 30MHz – 40GHz is ± 1.5 dB.
3. **Environmental Conditions**

Temperature	23°C
Relative Humidity	50%
Atmospheric Pressure	1019mbar
4. Test date : 11 August, 2011
Tested By : Peter Cai


Standard Requirement: 47 CFR § 15.247(b)

Procedures: The peak output power was measured conducted using a spectrum analyzer at low, mid, and hi channels. Peak detector was set to measure the power output. The power is converted from watt to dBm, therefore, 1 watt = 30 dBm. The highest antenna gain that will be used is 2dBi.


Test Result:

Protocol	Channel	Channel Frequency (MHz)	Peak Output Power Limit (dBm)	Measured Output Power (dBm)
802.11b	Low	2412	30	16.8
802.11b	Mid	2437	30	16.5
802.11b	High	2462	30	16.0
802.11g	Low	2412	30	17.5
802.11g	Mid	2437	30	17.0
802.11g	High	2462	30	16.3
802.11n-20MHz	Low	2412	30	17.0
802.11n-20MHz	Mid	2437	30	16.7
802.11n-20MHz	High	2462	30	16.2
802.11n-40MHz	Low	2422	30	17.3
802.11n-40MHz	Mid	2437	30	16.9
802.11n-40MHz	High	2452	30	16.8

Refer to the attached plots.



Output Power Low Channel (802.11b)



Output Power Mid Channel (802.11b)




SIEMIC, INC.


Accessing global markets

Title: RF Test Report for YN1 MODULE
Model: YN1-rx
To: FCC 15.247.2010

Serial#: 11020861-FCC Part 15.247
Issue Date: 15 August, 2011
Page: 27 of 86
www.siemec.com.cn



Output Power High Channel (802.11b)



Output Power Low Channel (802.11g)




SIEMIC, INC.


Accessing global markets

Title: RF Test Report for YN1 MODULE
Model: YN1-rx
To: FCC 15.247.2010

Serial#: 11020861-FCC Part 15.247
Issue Date: 15 August, 2011
Page: 28 of 86
www.siemic.com.cn



Output Power Mid Channel (802.11g)



Output Power High Channel (802.11g)




SIEMIC, INC.


Accessing global markets

Title: RF Test Report for YN1 MODULE
Model: YN1-rx
To: FCC 15.247.2010

Serial#: 11020861-FCC Part 15.247
Issue Date: 15 August, 2011
Page: 29 of 86
www.siemec.com.cn



Output Power Low Channel (802.11n-20MHz)



Output Power Mid Channel (802.11n-20MHz)




SIEMIC, INC.


Accessing global markets

Title: RF Test Report for YN1 MODULE
Model: YN1-rx
To: FCC 15.247.2010


Serial#: 11020861-FCC Part 15.247
Issue Date: 15 August, 2011
Page: 30 of 86
www.siemic.com.cn




Output Power High Channel (802.11n-20MHz)



Output Power Low Channel (802.11n-40MHz)



Output Power Mid Channel (802.11n-40MHz)



Output Power High Channel (802.11n-40MHz)

5.6 Antenna Port Emission


1. Conducted Measurement
EUT was set for low, mid, high channel with modulated mode and highest RF output power.
The spectrum analyzer was connected to the antenna terminal.
2. Conducted Emissions Measurement Uncertainty
All test measurements carried out are traceable to national standards. The uncertainty of the measurement at a confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2, in the range 30MHz – 40GHz is $\pm 1.5\text{dB}$.
3. Environmental Conditions

Temperature	23°C
Relative Humidity	50%
Atmospheric Pressure	1019mbar
4. Test date : 11 August, 2011
Tested By : Peter Cai


Standard Requirement: Radiated emission limits: In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the modulation products of the spreading sequence, the information sequence and the carrier frequency shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power

Procedures: The conducted spurious emissions were measured conducted using a spectrum analyzer at low, mid, and hi channels. The limit was determined by attenuating 20 dB of the RF peak power output.

Test Result: Pass



Antenna Port Emission Low Channel -1(802.11b)



Antenna Port Emission Low Channel -2(802.11b)




SIEMIC, INC.


Accessing global markets

Title: RF Test Report for YN1 MODULE
Model: YN1-rx
To: FCC 15.247.2010


Serial#: 11020861-FCC Part 15.247
Issue Date: 15 August, 2011
Page: 34 of 86
www.siemec.com.cn




Antenna Port Emission Low Channel -3(802.11b)




Antenna Port Emission Low Channel -4(802.11b)




Antenna Port Emission Mid-1 Channel (802.11b)



Antenna Port Emission Mid-2 Channel (802.11b)



Antenna Port Emission Mid-3 Channel (802.11b)



Antenna Port Emission Mid-4 Channel (802.11b)




SIEMIC, INC.


Accessing global markets

Title: RF Test Report for YN1 MODULE
Model: YN1-rx
To: FCC 15.247.2010


Serial#: 11020861-FCC Part 15.247
Issue Date: 15 August, 2011
Page: 37 of 86
www.siemec.com.cn



Antenna Port Emission High-1 Channel (802.11b)




Antenna Port Emission High-2 Channel (802.11b)




SIEMIC, INC.
Accessing global markets

Title: RF Test Report for YN1 MODULE
Model: YN1-rx
To: FCC 15.247.2010

Serial#: 11020861-FCC Part 15.247
Issue Date: 15 August, 2011
Page: 38 of 86
www.siemic.com.cn



Antenna Port Emission High-3 Channel (802.11b)




Antenna Port Emission High-4 Channel (802.11b)




SIEMIC, INC.
Accessing global markets

Title: RF Test Report for YN1 MODULE
Model: YN1-rx
To: FCC 15.247:2010

Serial#: 11020861-FCC Part 15.247
Issue Date: 15 August, 2011
Page: 39 of 86
www.siemic.com.cn



Antenna Port Emission Low-1 Channel (802.11g)




Antenna Port Emission Low-2 Channel (802.11g)




SIEMIC, INC.
Accessing global markets

Title: RF Test Report for YN1 MODULE
Model: YN1-rx
To: FCC 15.247.2010


Serial#: 11020861-FCC Part 15.247
Issue Date: 15 August, 2011
Page: 40 of 86
www.siemic.com.cn




Antenna Port Emission Low-3 Channel (802.11g)



Antenna Port Emission Low-4 Channel (802.11g)



Antenna Port Emission Mid-1 Channel (802.11g)



Antenna Port Emission Mid-2 Channel (802.11g)




SIEMIC, INC.


Accessing global markets

Title: RF Test Report for YN1 MODULE
Model: YN1-rx
To: FCC 15.247.2010


Serial#: 11020861-FCC Part 15.247
Issue Date: 15 August, 2011
Page: 42 of 86
www.siemic.com.cn




Antenna Port Emission Mid-3 Channel (802.11g)




Antenna Port Emission Mid-4 Channel (802.11g)




Antenna Port Emission High-1 Channel (802.11g)



Antenna Port Emission High-2 Channel (802.11g)



Antenna Port Emission High-3 Channel (802.11g)



Antenna Port Emission High-4 Channel (802.11g)




SIEMIC, INC.


Accessing global markets

Title: RF Test Report for YN1 MODULE
Model: YN1-rx
To: FCC 15.247.2010


Serial#: 11020861-FCC Part 15.247
Issue Date: 15 August, 2011
Page: 45 of 86
www.siemic.com.cn



Antenna Port Emission Low-1 Channel (802.11n 20MHz)




Antenna Port Emission Low-2 Channel (802.11n 20MHz)




SIEMIC, INC.
Accessing global markets

Title: RF Test Report for YN1 MODULE
Model: YN1-rx
To: FCC 15.247.2010

Serial#: 11020861-FCC Part 15.247
Issue Date: 15 August, 2011
Page: 46 of 86
www.siemic.com.cn



Antenna Port Emission Low-3 Channel (802.11n 20MHz)




Antenna Port Emission Low-4 Channel (802.11n 20MHz)




SIEMIC, INC.
Accessing global markets

Title: RF Test Report for YN1 MODULE
Model: YN1-rx
To: FCC 15.247.2010

Serial#: 11020861-FCC Part 15.247
Issue Date: 15 August, 2011
Page: 47 of 86
www.siemic.com.cn



Antenna Port Emission Mid-1 Channel (802.11n 20MHz)



Antenna Port Emission Mid-2 Channel (802.11n 20MHz)




SIEMIC, INC.


Accessing global markets

Title: RF Test Report for YN1 MODULE
Model: YN1-rx
To: FCC 15.247.2010

Serial#: 11020861-FCC Part 15.247
Issue Date: 15 August, 2011
Page: 48 of 86
www.siemic.com.cn



Antenna Port Emission Mid-3 Channel (802.11n 20MHz)



Antenna Port Emission Mid-4 Channel (802.11n 20MHz)




SIEMIC, INC.


Accessing global markets

Title: RF Test Report for YN1 MODULE
Model: YN1-rx
To: FCC 15.247:2010


Serial#: 11020861-FCC Part 15.247
Issue Date: 15 August, 2011
Page: 49 of 86
www.siemic.com.cn




Antenna Port Emission High-1 Channel (802.11n 20MHz)




Antenna Port Emission High-2 Channel (802.11n 20MHz)




Antenna Port Emission High-3 Channel (802.11n 20MHz)




Antenna Port Emission High-4 Channel (802.11n 20MHz)




Antenna Port Emission Low-1 Channel (802.11n 40MHz)



Antenna Port Emission Low-2 Channel (802.11n 40MHz)



Antenna Port Emission Low-3 Channel (802.11n 40MHz)



Antenna Port Emission Low-1 Channel (802.11n 40MHz)




SIEMIC, Inc.


Accessing global markets

Title: RF Test Report for YN1 MODULE
Model: YN1-rx
To: FCC 15.247.2010



Serial#: 11020861-FCC Part 15.247
Issue Date: 15 August, 2011
Page: 53 of 86
www.siemic.com.cn




Antenna Port Emission Mid-1 Channel (802.11n 40MHz)




Antenna Port Emission Mid-2 Channel (802.11n 40MHz)




Antenna Port Emission Mid-3 Channel (802.11n 40MHz)



Antenna Port Emission Mid-4 Channel (802.11n 40MHz)



Antenna Port Emission High-1 Channel (802.11n 40MHz)




Antenna Port Emission High-2 Channel (802.11n 40MHz)




SIEMIC, INC.
Accessing global markets

Title: RF Test Report for YN1 MODULE
Model: YN1-rx
To: FCC 15.247.2010

Serial#: 11020861-FCC Part 15.247
Issue Date: 15 August, 2011
Page: 56 of 86
www.siemic.com.cn




Antenna Port Emission High-3 Channel (802.11n 40MHz)



Antenna Port Emission High-4 Channel (802.11n 40MHz)

Note: All modes were measured, only worst case 802.11g mode test result was presented.



Radiated Emission Plot




Test Data

Frequency (MHz)	Quasi Peak (dBuV/m)	Azimuth	Polarity(H/V)	Height (cm)	Factors (dB)	Limit (dBuV/m)	Margin (dB)
533.42	18.39	79.00	V	248.00	-26.48	46.00	-27.61
640.21	20.87	33.00	V	108.00	-22.95	46.00	-25.13
576.01	35.99	96.00	V	101.00	-24.37	46.00	-10.01
647.63	30.28	92.00	V	100.00	-22.88	46.00	-15.72
853.33	21.63	14.00	V	108.00	-19.64	46.00	-24.37
719.65	33.80	179.00	V	100.00	-20.81	46.00	-12.20

Radiated Emission Plot

Peak Detector 
 Quasi Peak Limit 



Test Data

Frequency (MHz)	Quasi Peak (dBuV/m)	Azimuth	Polarity(H/V)	Height (cm)	Factors (dB)	Limit (dBuV/m)	Margin (dB)
227.62	38.43	0.00	H	100.00	-31.96	46.00	-7.57
719.64	32.83	318.00	H	114.00	-21.41	46.00	-13.17
816.02	30.68	313.00	H	101.00	-20.40	46.00	-15.32
864.39	30.27	358.00	H	160.00	-18.58	46.00	-15.73
862.89	30.04	3.00	H	153.00	-18.57	46.00	-15.96
768.02	31.51	327.00	H	105.00	-21.23	46.00	-14.49

5.8 Radiated Spurious Emissions > 1GHz & Band Edge

1. All possible modes of operation were investigated. Only the 6 worst case emissions measured, using the correct CISPR detectors, are reported. All other emissions were relatively insignificant.
2. A "-ve" margin indicates a PASS as it refers to the margin present below the limit line at the particular frequency.
3. Radiated Emissions Measurement Uncertainty
All test measurements carried out are traceable to national standards. The uncertainty of the measurement at a confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2, in the range 30MHz – 1GHz & 1GHz above (3m & 10m) is +/-6dB.
4. Environmental Conditions Temperature 23°C
 Relative Humidity 50%
 Atmospheric Pressure 1019mbar
5. Test date : 11 August, 2011
 Tested By : Peter Cai

Standard Requirement: The emissions from the Low-power radio-frequency devices shall not exceed the field strength levels specified in the following table and the level of any unwanted emissions shall not exceed the level of the fundamental emission. The tighter limit applies at the band edges.

Test Result: Pass

Mode: 802.11b

@ 2412MHz @ 3 Meter

Frequency	Direction	Height	Polar	Cable loss	Amplifier	Corrected Reading	15.247/15.209	15.247/15.209	
GHz	Degree	Meter	H / V	(dB)	(dB)	(dBuV/m)	Limit (dBuV/m)	Margin	Comments
4.824	9.00	1.07	v	5.15	55.00	55.4	74.00	-18.6	Peak
4.824	12.00	1.10	h	5.15	55.00	51.8	74.00	-22.2	Peak
4.824	9.00	1.07	v	5.15	55.00	42.6	54.00	-11.4	Ave
4.824	12.00	1.10	h	5.15	55.00	40.6	54.00	-13.4	Ave
7.236	5.30	1.12	v	7.23	55.00	65.6	74.00	-8.4	Peak
7.236	6.11	1.15	h	7.23	55.00	63.7	74.00	-10.3	Peak
7.236	5.30	1.12	v	7.23	55.00	49.5	54.00	-4.5	Ave
7.236	6.11	1.15	h	7.23	55.00	47.9	54.00	-6.1	Ave
9.678	31.0	1.26	v	8.56	55.00	55.1	74.00	-18.9	Peak
9.678	3.0	1.34	h	8.56	55.00	54.3	74.00	-19.7	Peak
9.678	31.0	1.26	v	8.56	55.00	44.3	54.00	-9.7	Ave
9.678	3.0	1.34	h	8.56	55.00	43.2	54.00	-10.8	Ave
12.06	0	1.06	v	11.03	55.00	51.1	74.00	-22.9	Peak
12.06	12.0	1.24	h	11.03	55.00	50.7	74.00	-23.3	Peak
12.06	0	1.06	v	11.03	55.00	42.2	54.00	-11.8	Ave
12.06	12.0	1.24	h	11.03	55.00	40.6	54.00	-13.4	Ave

Emission was scanned up to 25GHz.

@ 2437MHz @ 3Meter

Frequency	Direction	Height	Polar	Cable loss	Amplifier	Corrected Reading	15.247/15.209	15.247/15.209	
GHz	Degree	Meter	H / V	(dB)	(dB)	(dBuV/m)	Limit (dBuV/m)	Margin	Comments
4.874	31.00	1.10	v	5.16	55.00	56.5	74.00	-17.6	Peak
4.874	25.00	1.00	h	5.16	55.00	53.1	74.00	-20.9	Peak
4.874	31.00	1.10	v	5.16	55.00	44.9	54.00	-9.1	Ave
4.874	25.00	1.00	h	5.16	55.00	43.6	54.00	-10.4	Ave
7.311	13.00	1.20	v	7.31	55.00	68.1	74.00	-5.9	Peak
7.311	4.00	1.03	h	7.31	55.00	66.4	74.00	-7.6	Peak
7.311	13.00	1.20	v	7.31	55.00	50.5	54.00	-3.5	Ave
7.311	4.00	1.03	h	7.31	55.00	50.1	54.00	-3.9	Ave
9.748	22.0	1.30	v	8.66	55.00	57.6	74.00	-16.4	Peak
9.748	7.0	1.00	h	8.66	55.00	56.0	74.00	-18.0	Peak
9.748	22.0	1.30	v	8.66	55.00	44.3	54.00	-9.7	Ave
9.748	7.0	1.00	h	8.66	55.00	45.2	54.00	-8.8	Ave
12.185	0	1.20	v	11.22	55.00	52.0	74.00	-22.0	Peak
12.185	0	1.08	h	11.22	55.00	51.4	74.00	-22.6	Peak
12.185	0	1.20	v	11.22	55.00	43.1	54.00	-10.9	Ave
12.185	0	1.08	h	11.22	55.00	40.7	54.00	-13.3	Ave

Emission was scanned up to 25GHz.

@ 2462MHz @ 3Meter

Frequency	Direction	Height	Polar	Cable loss	Amplifier	Corrected Reading	15.247/15.209	15.247/15.209	
GHz	Degree	Meter	H / V	(dB)	(dB)	(dBuV/m)	Limit (dBuV/m)	Margin	Comments
4.924	15.00	1.07	v	5.17	55.00	54.3	74.00	-19.7	Peak
4.924	25.00	1.10	h	5.17	55.00	53.1	74.00	-20.9	Peak
4.924	15.00	1.07	v	5.17	55.00	44.5	54.00	-9.5	Ave
4.924	25.00	1.10	h	5.17	55.00	42.6	54.00	-11.4	Ave
7.386	0	1.20	v	7.36	55.00	66.4	74.00	-7.6	Peak
7.386	3.00	1.00	h	7.36	55.00	64.4	74.00	-9.6	Peak
7.386	0	1.20	v	7.36	55.00	48.9	54.00	-5.1	Ave
7.386	3.00	1.00	h	7.36	55.00	48.2	54.00	-5.8	Ave
9.848	6.00	1.10	v	8.74	55.00	55.3	74.00	-18.7	Peak
9.848	21.00	1.08	h	8.74	55.00	54.8	74.00	-19.2	Peak
9.848	6.00	1.10	v	8.74	55.00	43.3	54.00	-10.7	Ave
9.848	21.00	1.08	h	8.74	55.00	45.2	54.00	-8.8	Ave
12.31	4.00	1.34	v	11.39	55.00	51.0	74.00	-23.0	Peak
12.31	9.00	1.27	h	11.39	55.00	50.5	74.00	-23.5	Peak
12.31	4.00	1.34	v	11.39	55.00	42.7	54.00	-11.3	Ave
12.31	9.00	1.27	h	11.39	55.00	40.3	54.00	-13.7	Ave

Emission was scanned up to 25GHz.

Mode: 802.11g

@ 2412MHz @ 3 Meter

Frequency	Direction	Height	Polar	Cable loss	Amplifier	Corrected Reading	15.247/15.209	15.247/15.209	
GHz	Degree	Meter	H / V	(dB)	(dB)	(dBuV/m)	Limit (dBuV/m)	Margin	Comments
4.824	9.00	1.07	v	5.15	55.00	54.7	74.00	-19.3	Peak
4.824	12.00	1.10	h	5.15	55.00	51.6	74.00	-22.4	Peak
4.824	9.00	1.07	v	5.15	55.00	41.4	54.00	-12.6	Ave
4.824	12.00	1.10	h	5.15	55.00	40.0	54.00	-14.0	Ave
7.236	5.30	1.12	v	7.23	55.00	64.2	74.00	-9.8	Peak
7.236	6.11	1.15	h	7.23	55.00	62.8	74.00	-11.2	Peak
7.236	5.30	1.12	v	7.23	55.00	48.1	54.00	-5.9	Ave
7.236	6.11	1.15	h	7.23	55.00	47.4	54.00	-6.6	Ave
9.678	31.0	1.26	v	8.56	55.00	54.6	74.00	-19.4	Peak
9.678	3.0	1.34	h	8.56	55.00	53.5	74.00	-20.5	Peak
9.678	31.0	1.26	v	8.56	55.00	42.8	54.00	-11.2	Ave
9.678	3.0	1.34	h	8.56	55.00	41.9	54.00	-12.1	Ave
12.06	0	1.06	v	11.03	55.00	50.9	74.00	-23.1	Peak
12.06	12.0	1.24	h	11.03	55.00	49.7	74.00	-24.3	Peak
12.06	0	1.06	v	11.03	55.00	41.8	54.00	-12.2	Ave
12.06	12.0	1.24	h	11.03	55.00	40.4	54.00	-13.6	Ave

Emission was scanned up to 25GHz.

@ 2437MHz @ 3Meter

Frequency	Direction	Height	Polar	Cable loss	Amplifier	Corrected Reading	15.247/15.209	15.247/15.209	
GHz	Degree	Meter	H / V	(dB)	(dB)	(dBuV/m)	Limit (dBuV/m)	Margin	Comments
4.874	31.00	1.10	v	5.16	55.00	54.6	74.00	-19.4	Peak
4.874	25.00	1.00	h	5.16	55.00	52.2	74.00	-21.8	Peak
4.874	31.00	1.10	v	5.16	55.00	43.5	54.00	-10.5	Ave
4.874	25.00	1.00	h	5.16	55.00	42.6	54.00	-11.4	Ave
7.311	13.00	1.20	v	7.31	55.00	64.7	74.00	-9.3	Peak
7.311	4.00	1.03	h	7.31	55.00	63.1	74.00	-10.9	Peak
7.311	13.00	1.20	v	7.31	55.00	48.2	54.00	-5.8	Ave
7.311	4.00	1.03	h	7.31	55.00	47.6	54.00	-6.4	Ave
9.748	22.0	1.30	v	8.66	55.00	55.1	74.00	-18.9	Peak
9.748	7.0	1.00	h	8.66	55.00	53.2	74.00	-20.8	Peak
9.748	22.0	1.30	v	8.66	55.00	41.3	54.00	-12.7	Ave
9.748	7.0	1.00	h	8.66	55.00	43.6	54.00	-10.4	Ave
12.185	0	1.20	v	11.22	55.00	50.5	74.00	-23.5	Peak
12.185	0	1.08	h	11.22	55.00	50.9	74.00	-23.1	Peak
12.185	0	1.20	v	11.22	55.00	42.1	54.00	-11.9	Ave
12.185	0	1.08	h	11.22	55.00	40.8	54.00	-13.2	Ave

Emission was scanned up to 25GHz.

@ 2462MHz @ 3Meter

Frequency	Direction	Height	Polar	Cable loss	Amplifier	Corrected Reading	15.247/15.209	15.247/15.209	
GHz	Degree	Meter	H / V	(dB)	(dB)	(dBuV/m)	Limit (dBuV/m)	Margin	Comments
4.924	15.00	1.07	v	5.17	55.00	51.9	74.00	-22.1	Peak
4.924	25.00	1.10	h	5.17	55.00	52.8	74.00	-21.2	Peak
4.924	15.00	1.07	v	5.17	55.00	45.6	54.00	-8.4	Ave
4.924	25.00	1.10	h	5.17	55.00	43.1	54.00	-10.9	Ave
7.386	0	1.20	v	7.36	55.00	63.6	74.00	-10.4	Peak
7.386	3.00	1.00	h	7.36	55.00	62.0	74.00	-12.0	Peak
7.386	0	1.20	v	7.36	55.00	47.7	54.00	-6.3	Ave
7.386	3.00	1.00	h	7.36	55.00	46.4	54.00	-7.6	Ave
9.848	6.00	1.10	v	8.74	55.00	54.3	74.00	-19.7	Peak
9.848	21.00	1.08	h	8.74	55.00	52.8	74.00	-21.2	Peak
9.848	6.00	1.10	v	8.74	55.00	41.5	54.00	-12.5	Ave
9.848	21.00	1.08	h	8.74	55.00	43.1	54.00	-10.9	Ave
12.31	4.00	1.34	v	11.39	55.00	50.3	74.00	-23.7	Peak
12.31	9.00	1.27	h	11.39	55.00	49.6	74.00	-24.4	Peak
12.31	4.00	1.34	v	11.39	55.00	42.7	54.00	-11.3	Ave
12.31	9.00	1.27	h	11.39	55.00	41.7	54.00	-12.3	Ave

Emission was scanned up to 25GHz.

Mode: 802.11n-20MHz

@ 2412MHz @ 3 Meter

Frequency	Direction	Height	Polar	Cable loss	Amplifier	Corrected Reading	15.247/15.209	15.247/15.209	
GHz	Degree	Meter	H / V	(dB)	(dB)	(dBuV/m)	Limit (dBuV/m)	Margin	Comments
4.824	9.00	1.07	v	5.15	55.00	54.7	74.00	-19.3	Peak
4.824	12.00	1.10	h	5.15	55.00	51.6	74.00	-22.4	Peak
4.824	9.00	1.07	v	5.15	55.00	41.4	54.00	-12.6	Ave
4.824	12.00	1.10	h	5.15	55.00	40.0	54.00	-14.0	Ave
7.236	5.30	1.12	v	7.23	55.00	64.2	74.00	-9.8	Peak
7.236	6.11	1.15	h	7.23	55.00	62.8	74.00	-11.2	Peak
7.236	5.30	1.12	v	7.23	55.00	48.1	54.00	-5.9	Ave
7.236	6.11	1.15	h	7.23	55.00	47.4	54.00	-6.6	Ave
9.678	31.0	1.26	v	8.56	55.00	54.6	74.00	-19.4	Peak
9.678	3.0	1.34	h	8.56	55.00	53.5	74.00	-20.5	Peak
9.678	31.0	1.26	v	8.56	55.00	42.8	54.00	-11.2	Ave
9.678	3.0	1.34	h	8.56	55.00	41.9	54.00	-12.1	Ave
12.06	0	1.06	v	11.03	55.00	50.9	74.00	-23.1	Peak
12.06	12.0	1.24	h	11.03	55.00	49.7	74.00	-24.3	Peak
12.06	0	1.06	v	11.03	55.00	41.8	54.00	-12.2	Ave
12.06	12.0	1.24	h	11.03	55.00	40.4	54.00	-13.6	Ave

Emission was scanned up to 25GHz.

@ 2437MHz @ 3Meter

Frequency	Direction	Height	Polar	Cable loss	Amplifier	Corrected Reading	15.247/15.209	15.247/15.209	
GHz	Degree	Meter	H / V	(dB)	(dB)	(dBuV/m)	Limit (dBuV/m)	Margin	Comments
4.874	31.00	1.10	v	5.16	55.00	51.6	74.00	-22.4	Peak
4.874	25.00	1.00	h	5.16	55.00	51.3	74.00	-22.7	Peak
4.874	31.00	1.10	v	5.16	55.00	44.1	54.00	-9.9	Ave
4.874	25.00	1.00	h	5.16	55.00	43.4	54.00	-10.6	Ave
7.311	13.00	1.20	v	7.31	55.00	62.0	74.00	-12.0	Peak
7.311	4.00	1.03	h	7.31	55.00	60.8	74.00	-13.2	Peak
7.311	13.00	1.20	v	7.31	55.00	47.5	54.00	-6.5	Ave
7.311	4.00	1.03	h	7.31	55.00	46.4	54.00	-7.6	Ave
9.748	22.0	1.30	v	8.66	55.00	54.3	74.00	-19.7	Peak
9.748	7.0	1.00	h	8.66	55.00	51.8	74.00	-22.2	Peak
9.748	22.0	1.30	v	8.66	55.00	40.6	54.00	-13.4	Ave
9.748	7.0	1.00	h	8.66	55.00	41.7	54.00	-12.3	Ave
12.185	0	1.20	v	11.22	55.00	51.2	74.00	-23.8	Peak
12.185	0	1.08	h	11.22	55.00	52.7	74.00	-21.3	Peak
12.185	0	1.20	v	11.22	55.00	43.4	54.00	-10.6	Ave
12.185	0	1.08	h	11.22	55.00	42.5	54.00	-11.5	Ave

Emission was scanned up to 25GHz.

@ 2462MHz @ 3Meter

Frequency	Direction	Height	Polar	Cable loss	Amplifier	Corrected Reading	15.247/15.209	15.247/15.209	
GHz	Degree	Meter	H / V	(dB)	(dB)	(dBuV/m)	Limit (dBuV/m)	Margin	Comments
4.924	15.00	1.07	v	5.17	55.00	51.6	74.00	-22.4	Peak
4.924	25.00	1.10	h	5.17	55.00	49.5	74.00	-24.5	Peak
4.924	15.00	1.07	v	5.17	55.00	46.3	54.00	-7.7	Ave
4.924	25.00	1.10	h	5.17	55.00	44.0	54.00	-10.0	Ave
7.386	0	1.20	v	7.36	55.00	60.6	74.00	-13.4	Peak
7.386	3.00	1.00	h	7.36	55.00	58.7	74.00	-15.3	Peak
7.386	0	1.20	v	7.36	55.00	46.7	54.00	-7.3	Ave
7.386	3.00	1.00	h	7.36	55.00	46.4	54.00	-7.6	Ave
9.848	6.00	1.10	v	8.74	55.00	53.4	74.00	-20.6	Peak
9.848	21.00	1.08	h	8.74	55.00	51.7	74.00	-22.3	Peak
9.848	6.00	1.10	v	8.74	55.00	42.4	54.00	-11.6	Ave
9.848	21.00	1.08	h	8.74	55.00	41.8	54.00	-12.2	Ave
12.31	4.00	1.34	v	11.39	55.00	51.6	74.00	-22.4	Peak
12.31	9.00	1.27	h	11.39	55.00	50.3	74.00	-23.7	Peak
12.31	4.00	1.34	v	11.39	55.00	41.8	54.00	-12.2	Ave
12.31	9.00	1.27	h	11.39	55.00	40.9	54.00	-13.1	Ave

Emission was scanned up to 25GHz.

Mode: 802.11n-40MHz

@ 2422MHz @ 3 Meter

Frequency	Direction	Height	Polar	Cable loss	Amplifier	Corrected Reading	15.247/15.209	15.247/15.209	
GHz	Degree	Meter	H / V	(dB)	(dB)	(dBuV/m)	Limit (dBuV/m)	Margin	Comments
4.844	9.00	1.07	v	5.15	55.00	54.7	74.00	-19.3	Peak
4.844	12.00	1.10	h	5.15	55.00	51.6	74.00	-22.4	Peak
4.844	9.00	1.07	v	5.15	55.00	41.4	54.00	-12.6	Ave
4.844	12.00	1.10	h	5.15	55.00	40.0	54.00	-14.0	Ave
7.266	5.30	1.12	v	7.23	55.00	64.2	74.00	-9.8	Peak
7.266	6.11	1.15	h	7.23	55.00	62.8	74.00	-11.2	Peak
7.266	5.30	1.12	v	7.23	55.00	48.1	54.00	-5.9	Ave
7.266	6.11	1.15	h	7.23	55.00	47.4	54.00	-6.6	Ave
9.688	31.0	1.26	v	8.56	55.00	54.6	74.00	-19.4	Peak
9.688	3.0	1.34	h	8.56	55.00	53.5	74.00	-20.5	Peak
9.688	31.0	1.26	v	8.56	55.00	42.8	54.00	-11.2	Ave
9.688	3.0	1.34	h	8.56	55.00	41.9	54.00	-12.1	Ave
12.11	0	1.06	v	11.03	55.00	50.9	74.00	-23.1	Peak
12.11	12.0	1.24	h	11.03	55.00	49.7	74.00	-24.3	Peak
12.11	0	1.06	v	11.03	55.00	41.8	54.00	-12.2	Ave
12.11	12.0	1.24	h	11.03	55.00	40.4	54.00	-13.6	Ave

Emission was scanned up to 25GHz.

@ 2437MHz @ 3Meter

Frequency	Direction	Height	Polar	Cable loss	Amplifier	Corrected Reading	15.247/15.209	15.247/15.209	
GHz	Degree	Meter	H / V	(dB)	(dB)	(dBuV/m)	Limit (dBuV/m)	Margin	Comments
4.874	31.00	1.10	v	5.16	55.00	53.5	74.00	-20.5	Peak
4.874	25.00	1.00	h	5.16	55.00	52.0	74.00	-22.0	Peak
4.874	31.00	1.10	v	5.16	55.00	44.9	54.00	-9.1	Ave
4.874	25.00	1.00	h	5.16	55.00	43.1	54.00	-10.9	Ave
7.311	13.00	1.20	v	7.31	55.00	65.6	74.00	-8.4	Peak
7.311	4.00	1.03	h	7.31	55.00	63.4	74.00	-10.6	Peak
7.311	13.00	1.20	v	7.31	55.00	49.6	54.00	-4.4	Ave
7.311	4.00	1.03	h	7.31	55.00	48.3	54.00	-5.7	Ave
9.748	22.0	1.30	v	8.66	55.00	56.5	74.00	-17.5	Peak
9.748	7.0	1.00	h	8.66	55.00	54.2	74.00	-19.8	Peak
9.748	22.0	1.30	v	8.66	55.00	42.4	54.00	-11.6	Ave
9.748	7.0	1.00	h	8.66	55.00	44.1	54.00	-19.9	Ave
12.185	0	1.20	v	11.22	55.00	51.9	74.00	-22.1	Peak
12.185	0	1.08	h	11.22	55.00	52.7	74.00	-21.3	Peak
12.185	0	1.20	v	11.22	55.00	43.7	54.00	-10.3	Ave
12.185	0	1.08	h	11.22	55.00	41.9	54.00	-12.1	Ave

Emission was scanned up to 25GHz.

@ 2452MHz @ 3Meter

Frequency	Direction	Height	Polar	Cable loss	Amplifier	Corrected Reading	15.247/15.209	15.247/15.209	
GHz	Degree	Meter	H / V	(dB)	(dB)	(dBuV/m)	Limit (dBuV/m)	Margin	Comments
4.904	15.00	1.07	v	5.17	55.00	55.8	74.00	-18.2	Peak
4.904	25.00	1.10	h	5.17	55.00	54.3	74.00	-19.7	Peak
4.904	15.00	1.07	v	5.17	55.00	46.4	54.00	-7.6	Ave
4.904	25.00	1.10	h	5.17	55.00	44.3	54.00	-9.7	Ave
7.356	0	1.20	v	7.36	55.00	64.8	74.00	-9.2	Peak
7.356	3.00	1.00	h	7.36	55.00	63.1	74.00	-10.9	Peak
7.356	0	1.20	v	7.36	55.00	48.2	54.00	-5.8	Ave
7.356	3.00	1.00	h	7.36	55.00	47.0	54.00	-7.0	Ave
9.808	6.00	1.10	v	8.74	55.00	56.9	74.00	-17.1	Peak
9.808	21.00	1.08	h	8.74	55.00	53.4	74.00	-20.6	Peak
9.808	6.00	1.10	v	8.74	55.00	43.6	54.00	-10.4	Ave
9.808	21.00	1.08	h	8.74	55.00	44.0	54.00	-10.0	Ave
12.26	4.00	1.34	v	11.39	55.00	52.1	74.00	-21.9	Peak
12.26	9.00	1.27	h	11.39	55.00	50.9	74.00	-23.1	Peak
12.26	4.00	1.34	v	11.39	55.00	43.4	54.00	-10.6	Ave
12.26	9.00	1.27	h	11.39	55.00	42.0	54.00	-12.0	Ave

Emission was scanned up to 25GHz.

Band Edge 802.11b mode

Channel	Polarity	Detector	Frequency	Result	Limit	Margin
Low Channel	V	Peak	2400	36.77	74	-37.23
Low Channel	H	Peak	2400	32.12	74	-41.88
Low Channel	V	Avg	2400	26.44	54	-27.56
Low Channel	H	Avg	2400	24.59	54	-29.41

Channel	Polarity	Detector	Frequency	Result	Limit	Margin
High Channel	V	Peak	2483.5	33.23	74	-40.77
High Channel	H	Peak	2483.5	35.67	74	-38.33
High Channel	V	Avg	2483.5	24.33	54	-29.67
High Channel	H	Avg	2483.5	26.75	54	-27.25

Band Edge 802.11g mode

Channel	Polarity	Detector	Frequency	Result	Limit	Margin
Low Channel	V	Peak	2400	36.55	74	-37.45
Low Channel	H	Peak	2400	33.42	74	-40.58
Low Channel	V	Avg	2400	27.25	54	-26.75
Low Channel	H	Avg	2400	25.62	54	-28.38

Channel	Polarity	Detector	Frequency	Result	Limit	Margin
High Channel	V	Peak	2483.5	34.67	74	-39.33
High Channel	H	Peak	2483.5	35.22	74	-38.78
High Channel	V	Avg	2483.5	24.18	54	-29.82
High Channel	H	Avg	2483.5	26.97	54	-27.03

Band Edge 802.11n-20MHz mode

Channel	Polarity	Detector	Frequency	Result	Limit	Margin
Low Channel	V	Peak	2400	37.41	74	-36.59
Low Channel	H	Peak	2400	33.45	74	-40.55
Low Channel	V	Avg	2400	25.57	54	-28.43
Low Channel	H	Avg	2400	26.59	54	-27.41

Channel	Polarity	Detector	Frequency	Result	Limit	Margin
High Channel	V	Peak	2483.5	35.24	74	-38.76
High Channel	H	Peak	2483.5	35.74	74	-38.26
High Channel	V	Avg	2483.5	25.12	54	-28.88
High Channel	H	Avg	2483.5	24.45	54	-29.55

Band Edge 802.11n-40MHz mode

Channel	Polarity	Detector	Frequency	Result	Limit	Margin
Low Channel	V	Peak	2400	37.54	74	-36.46
Low Channel	H	Peak	2400	33.54	74	-40.46
Low Channel	V	Avg	2400	25.87	54	-28.13
Low Channel	H	Avg	2400	26.12	54	-27.88

Channel	Polarity	Detector	Frequency	Result	Limit	Margin
High Channel	V	Peak	2483.5	35.02	74	-38.98
High Channel	H	Peak	2483.5	34.44	74	-39.56
High Channel	V	Avg	2483.5	25.93	54	-28.07
High Channel	H	Avg	2483.5	24.44	54	-29.56

Annex A. TEST INSTRUMENT & METHOD

Annex A.i. TEST INSTRUMENTATION & GENERAL PROCEDURES

Instrument	Manufacturer	Model	CAL Due Date
Spectrum Analyzer	HP	8563 E	2012.05.26
EMI Receiver	Rohde & Schwarz	ESPI 3	2012.05.26
Antenna (30MHz~2GHz)	Sunol Sciences	JB1	2011.10.04
Horn Antenna (1~18GHz)	A-INFOMW	JXTXLB-10180	2011.10.04
Horn Antenna (1~18GHz)	ETS-Lindgren	3115	2011.10.04
Pre-Amplifier(0.01 ~ 1.3GHz)	HP	8447F	2012.05.26
Pre-Amplifier(0.1 ~ 18GHz)	MITEQ	AMF-7D-00101800-30- 10P	2012.05.26
Horn Antenna (18~40GHz)	Com Power	AH-840	2012.05.26
Microwave Pre-Amp (18~40GHz)	Com Power	PA-840	2012.05.26

Annex A.ii. CONDUCTED EMISSIONS TEST DESCRIPTION

Test Set-up

1. The EUT and supporting equipment were set up in accordance with the requirements of the standard on top of a 1.5m x 1m x 0.8m high, non-metallic table, as shown in Annex B.
2. The power supply for the EUT was fed through a 50Ω/50μH EUT LISN, connected to filtered mains.
3. The RF OUT of the EUT LISN was connected to the EMI test receiver via a low-loss coaxial cable.
4. All other supporting equipments were powered separately from another main supply.

Test Method

1. The EUT was switched on and allowed to warm up to its normal operating condition.
2. A scan was made on the NEUTRAL line (for AC mains) or Earth line (for DC power) over the required frequency range using an EMI test receiver.
3. High peaks, relative to the limit line, were then selected.
4. The EMI test receiver was then tuned to the selected frequencies and the necessary measurements made with a receiver bandwidth setting of 10 KHz. For FCC tests, only Quasi-peak measurements were made; while for CISPR/EN tests, both Quasi-peak and Average measurements were made.
5. Steps 2 to 4 were then repeated for the LIVE line (for AC mains) or DC line (for DC power).

Sample Calculation Example

At 20 MHz	limit = 250 μV = 47.96 dBμV
Transducer factor of LISN, pulse limiter & cable loss at 20 MHz = 11.20 dB	
Q-P reading obtained directly from EMI Receiver = 40.00 dBμV (Calibrated for system losses)	
Therefore, Q-P margin = 47.96 – 40.00 = 7.96	i.e. 7.96 dB below limit

Annex A.iii. RADIATED EMISSIONS TEST DESCRIPTION


EUT Characterisation

EUT characterisation, over the frequency range from 30MHz to 10th Harmonic, was done in order to minimise radiated emissions testing time while still maintaining high confidence in the test results.

The EUT was placed in the chamber, at a height of about 0.8m on a turntable. Its radiated emissions frequency profile was observed, using a spectrum analyzer /receiver with the appropriate broadband antenna placed 3m away from the EUT. Radiated emissions from the EUT were maximised by rotating the turntable manually, changing the antenna polarisation and manipulating the EUT cables while observing the frequency profile on the spectrum analyzer / receiver. Frequency points at which maximum emissions occurred, clock frequencies and operating frequencies were then noted for the formal radiated emissions test at the Open Area Test Site (OATS).

Test Set-up

1. The EUT and supporting equipment were set up in accordance with the requirements of the standard on top of a 1.5m X 1.0m X 0.8m high, non-metallic table.
2. The filtered power supply for the EUT and supporting equipment were tapped from the appropriate power sockets located on the turntable.
3. The relevant broadband antenna was set at the required test distance away from the EUT and supporting equipment boundary.



Test Method

The following procedure was performed to determine the maximum emission axis of EUT:

1. With the receiving antenna is H polarization, rotate the EUT in turns with three orthogonal axes to determine the axis of maximum emission.
2. With the receiving antenna is V polarization, rotate the EUT in turns with three orthogonal axes to determine the axis of maximum emission.
3. Compare the results derived from above two steps. So, the axis of maximum emission from EUT was determined and the configuration was used to perform the final measurement.

Final Radiated Emission Measurement

1. Setup the configuration according to figure 1. Turn on EUT and make sure that it is in normal function.
2. For emission frequencies measured below 1 GHz, a pre-scan is performed in a shielded chamber to determine the accurate frequencies of higher emissions will be checked on a open test site. As the same purpose, for emission frequencies measured above 1 GHz, a pre-scan also be performed with a 1 meter measuring distance before final test.
3. For emission frequencies measured below and above 1 GHz, set the spectrum analyzer on a 100 kHz and 1 MHz resolution bandwidth respectively for each frequency measured in step 2.
4. The search antenna is to be raised and lowered over a range from 1 to 4 meters in horizontally polarized orientation. Position the highness when the highest value is indicated on spectrum analyzer, then change the orientation of EUT on test table over a range from 0 ° to 360 ° with a speed as slow as possible, and keep the azimuth that highest emission is indicated on the spectrum analyzer. Vary the antenna position again and record the highest value as a final reading.
5. Repeat step 4 until all frequencies need to be measured were complete.
6. Repeat step 5 with search antenna in vertical polarized orientations.

During the radiated emission test, the Spectrum Analyzer was set with the following configurations:

Frequency Band (MHz)	Function	Resolution bandwidth	Video Bandwidth
30 to 1000	Peak	100 kHz	100 kHz
Above 1000	Peak	1 MHz	1 MHz
	Average	1 MHz	10 Hz

Sample Calculation Example

The field strength is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain (if any) from the measured reading. For the limit is employed average value, therefore the peak value can be transferred to average value by subtracting the duty factor. The basic equation with a sample calculation is as follows:

$$\text{Peak} = \text{Reading} + \text{Corrected Factor}$$

where

$$\text{Corr. Factor} = \text{Antenna Factor} + \text{Cable Factor} - \text{Amplifier Gain (if any)}$$

And the average value is

$$\text{Average} = \text{Peak Value} + \text{Duty Factor or}$$

$$\text{Set RBW} = 1\text{MHz, VBW} = 10\text{Hz.}$$

Note:

If the measured frequencies are fall in the restricted frequency band, the limit employed must be quasi peak value when frequencies are below or equal to 1 GHz. And the measuring instrument is set to quasi peak detector function.

Annex B. EUT AND TEST SETUP PHOTOGRAPHS

Annex B.i. Photograph : EUT External Photo



Front View of EUT



Rear View of EUT



SIEMIC, Inc.
Accessing global markets

Title: RF Test Report for YN1 MODULE
Model: YN1-rx
To: FCC 15.247:2010

Serial#: 11020861-FCC Part 15.247
Issue Date: 15 August, 2011
Page: 73 of 86
www.siemec.com.cn



Top View of EUT



Bottom View of EUT



SIEMIC, Inc.
Accessing global markets

Title: RF Test Report for YN1 MODULE
Model: YN1-rx
To: FCC 15.247.2010

Serial#: 11020861-FCC Part 15.247
Issue Date: 15 August, 2011
Page: 74 of 86
www.siemic.com.cn




Left View of EUT




Right View of EUT


Annex B.ii. Photograph : EUT Internal Photo




Front View of WIFI PCB Board




Rear View of WIFI PCB Board




Front View of 433MHz RX PCB Board



Rear View of 433MHz RX PCB Board



Front View of EUT Cover off




SIEMIC, INC.
Accessing global markets


Title: RF Test Report for YN1 MODULE
Model: YN1-rx
To: FCC 15.247:2010

Serial#: 11020861-FCC Part 15.247
Issue Date: 15 August, 2011
Page: 78 of 86
www.siemec.com.cn

Annex B.iii. Photograph : Test Setup Photo



Radiated Emission Test Setup Front View Below 1GHz



Radiated Emission Test Setup Front View Above 1GHz


Annex C. TEST SETUP AND SUPPORTING EQUIPMENT

EUT TEST CONDITIONS

Annex C. i. SUPPORTING EQUIPMENT DESCRIPTION

The following is a description of supporting equipment and details of cables used with the EUT.

Equipment Description (Including Brand Name)	Model & Serial Number	Cable Description (List Length, Type & Purpose)
Camera	D10	N/A



SIEMIC, INC.
Accessing global markets

Title: RF Test Report for YN1 MODULE
Model: YN1-rx
To: FCC 15.247:2010


Serial#: 11020861-FCC Part 15.247
Issue Date: 15 August, 2011
Page: 80 of 86
www.siemec.com.cn


Block Configuration Diagram for Conducted Emission

N/A



Block Configuration Diagram for Radiated Emission





SIEMIC, INC.

Accessing global markets


Title: RF Test Report for YN1 MODULE
Model: YN1-rx
To: FCC 15.247:2010

Serial#: 11020861-FCC Part 15.247
Issue Date: 15 August, 2011
Page: 82 of 86
www.siemic.com.cn

Annex C.ii. EUT OPERATING CONDITIONS

The following is the description of how the EUT is exercised during testing.

Test	Description Of Operation
Emissions Testing	TX mode is continuous transmitting with full power.



SIEMIC, INC.
Accessing global markets

Title: RF Test Report for YN1 MODULE
Model: YN1-rx
To: FCC 15.247:2010

Serial#: 11020861-FCC Part 15.247
Issue Date: 15 August, 2011
Page: 83 of 86
www.siemic.com.cn

Annex D. USER MANUAL / BLOCK DIAGRAM / SCHEMATICS / PART LIST

Please see attachment

Annex E. SIEMIC ACCREDITATION CERTIFICATES

SIEMIC ACCREDITATION DETAILS: FCC Registration NO:986914





SIEMIC, Inc.

Accessing global markets

Title: RF Test Report for YN1 MODULE
Model: YN1-rx
To: FCC 15.247:2010

Serial#: 11020861-FCC Part 15.247
Issue Date: 15 August, 2011
Page: 85 of 86
www.siemic.com.cn

SIEMIC ACCREDITATION DETAILS: FCC Listing, Registration NO:986914

FEDERAL COMMUNICATIONS COMMISSION

Laboratory Division
7435 Oakland Mills Road
Columbia, MD 21046

April 19, 2011

Registration Number: 986914

SIEMIC Nanjing (China) Laboratories
2-1 Longcang Avenue,
Yuhua Economic and Technology Development Park,
Nanjing, 210039
China

Attention: Leslie Bai,

Re: Measurement facility located at 2-1 Longcang Avenue, Nanjing, China
Anechoic chamber (3 meters) and 3&10 meter OATS
Date of Renewal: April 19, 2011

Dear Sir or Madam:

Your request for renewal of the registration of the subject measurement facility has been received. The information submitted has been placed in your file and the registration has been renewed. The name of your organization will remain on the list of facilities whose measurement data will be accepted in conjunction with applications for Certification under Parts 15 or 18 of the Commission's Rules. Please note that the file must be updated for any changes made to the facility and the registration must be renewed at least every three years.

Measurement facilities that have indicated that they are available to the public to perform measurement services on a fee basis may be found on the FCC website www.fcc.gov under E-Filing, OET Equipment Authorization Electronic Filing, Test Firms.

Sincerely,

Phyllis Parrish
Industry Analyst




SIEMIC, INC.

Accessing global markets

Title: RF Test Report for YN1 MODULE
Model: YN1-rx
To: FCC 15.247:2010

Serial#: 11020861-FCC Part 15.247
Issue Date: 15 August, 2011
Page: 86 of 86
www.siemic.com.cn

SIEMIC ACCREDITATION DETAILS: Industry of Canada Registration No. 4842



January 25, 2011

OUR FILE: 46405-4842
Submission No: 145222

Siemic Nanjing (China) Laboratories
2-1 Longcang Avenue
Yuhua Economic & Technology Dev. Park, Nanjing
China

Attention: Leslie Bai

Dear Sir/Madame:

The Bureau has received your application for the registration of a 3/10m OATS. Be advised that the information received was satisfactory to Industry Canada. The following number(s) is now associated to the site(s) for which registration / renewal was sought (Site# 4842B-2). Please reference the appropriate site number in the body of test reports containing measurements performed on the site. In addition, please keep for your records the following information;

- The company address code associated to the site(s) located at the above address is: **4842B**

Furthermore, to obtain or renew a unique site number, the applicant shall demonstrate that the site has been accredited to ANSI C63.4-2003 or later. A scope of accreditation indicating the accreditation by a recognized accreditation body to ANSI C63.4-2003 or later shall be accepted. Please indicate in a letter the previous assigned site number if applicable and the type of site (example: 3 metre OATS or 3 metre chamber). If the test facility is not accredited to ANSI C63.4-2003 or later, the test facility shall submit test data demonstrating full compliance with the ANSI standard. The Bureau will evaluate the filing to determine if recognition shall be granted.

The frequency for re-validation of the test site and the information that is required to be filed or retained by the testing party shall comply with the requirements established by the accrediting organization. However, in all cases, test site re-validation shall occur on an interval not to exceed three years. There is no fee or form associated with an OATS filing. OATS submissions are encouraged to be submitted electronically to the Bureau using the following URL;
http://strategis.ic.gc.ca/epic/internet/inceb-bhst.nsf/en/h_tr00052e.html.

If you have any questions, you may contact the Bureau by e-mail at certification.bureau@ic.gc.ca Please reference our file and submission number above for all correspondence.

Yours sincerely,

Dalwinder Gill
For: Wireless Laboratory Manager
Certification and Engineering Bureau
3701 Carling Ave., Building 94
P.O. Box 11490, Station "H"
Ottawa, Ontario K2H 8S2
Email: dalwinder.gill@ic.gc.ca
Tel. No. (613) 998-8363
Fax. No. (613) 990-4752