Celer_TLDPH00P1 機下標



WIFI 2.4 / 5 GHz SSID Wind-0078 WIFI 2.4 / 5GHz Password



MD: 2024W03

IP: 192.168.1.1 GUI: windbit.lan Login User: root Login Password: root



LAN MAC: 00A026360078

Model: TLDPH00P1

FCC ID: YUATLDPH00P1

Celer

This device complies with Part 15 of the FCC rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) This device must accept any interference received, including Interference that may cause undesired operation



Celer Series

Teldat S.A.

Isaac Newton 10 28760 Madrid, Spain 10R-06 5501



www.teldat.com

Designed by Teldat in Spain. Assembled in Taiwan

INPUT: 12-24V === 24W

Celer-5G_TLDPH01P1 機下標



WIFI 2.4 / 5 GHz SSID Wind-0078 WIFI 2.4 / 5GHz Password



MD: 2024W03

IP: 192.168.1.1 GUI: windbit.lan Login User: root Login Password: root



LAN MAC: 00A026360078

Model: TLDPH01P1

FCC ID: YUATLDPH00P1

Contains FCC ID: XMR2022RM520NGL

Celer-5G

This device complies with Part 15 of the FCC rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) This device must accept any interference received, including Interference that may cause undesired operation



Celer Series

Teldat S.A.

Isaac Newton 10 28760 Madrid, Spain

www.teldat.com

10R-06 5501



Designed by Teldat in Spain. Assembled in Taiwan

INPUT: 12-24V === 24W

Celer-LTE2_TLDPH03P1 機下標



WIFI 2.4 / 5 GHz SSID Wind-0078 WIFI 2.4 / 5GHz Password



MD: 2024W03

IP: 192.168.1.1 GUI: windbit.lan Login User: root Login Password: root



LAN MAC: 00A026360078

Model: TLDPH03P1

FCC ID: YUATLDPH00P1

Contains FCC ID: XMR201906EM06A

Celer-LTE2

This device complies with Part 15 of the FCC rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) This device must accept any interference received, including Interference that may cause undesired operation



Celer Series

Teldat S.A.

Isaac Newton 10 28760 Madrid, Spain

www.teldat.com





INPUT: 12-24V === 24W

Designed by Teldat in Spain. Assembled in Taiwan

機下標位置示意圖





