

## Statement of compliance to Maximum Permissible Exposure (MPE)

Applicant : Pass & Seymour, Inc., d/b/a Legrand  
301 Fulling Mill Road, Suite G, Middletown,  
Pennsylvania 17057 USA

Manufacturer : Hzsamko Technologies Co.,Ltd.  
No.8,Jiaqi Road,Xianlin Street,Yuhang  
District, Hangzhou, China.

Equipment : Player Subsystem

Type/Model : PCBA-200010-01 Player System

**According to §2.1091, §2.1093 and §1.1307(b), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission’s guidelines.**

The  $S = PG / (4\pi R^2)$

Where S = power density in mW/cm<sup>2</sup>

P = transmit power in mW

G = numeric gain of transmit antenna


R = distance (cm)

The calculations in the table below use the highest gain of antenna for the EUT. These calculations represent worst case in terms of the exposure levels.

Freq band	Power		Antenna Gain		R	S	Limits	Conclusion
	MHz	dBm	mW	dBi				
2400 -2483.5	29.60	912.011	2.79	1.901	20	0.35	1	Pass
5150-5250	15.80	38.019	4.20	2.630	20	0.020	1	
5725-5850	17.00	50.119	4.20	2.630	20	0.026	1	


Date of issue: Jan 9, 2017

Prepared by:



Wakeyou Wang (Project Engineer)

Reviewed by:



Daniel Zhao (Reviewer)

## Appendix I

**Definition below must be outlined in the User Manual:**

To satisfy FCC RF exposure requirements, a separation distance of 20 cm or more should be maintained between the antenna of this device and persons during device operation. To ensure compliance, operations at closer than this distance is not recommended.