

MPE CALCULATION

FCC ID: YV8-204450

RF Exposure Requirements:	47 CFR §1. 1307(b)
RF Radiation Exposure Limits:	47 CFR §1. 1310
RF Radiation Exposure Guidelines:	FCC OST/OET Bulletin Number 65
EUT Frequency Band:	904.861-924.873 MHz
Limits for General Population/Uncontrolled Exposure in the band of:	1500 - 100,000 MHz
Power Density Limit:	0.62 mW/cm ²

Equation: $S = PG / 4\pi R^2$ or $R = \sqrt{PG / 4\pi S}$
Where, S = Power Density
P = Power Input to Antenna
G = Antenna Gain
R = distance to the center of radiated antenna

Prediction distance 20cm


Power = 0.144 mW, Antenna Gain = 2.56 dBi, Power density = 0.00007334 mW/cm²

Prediction Distance (cm)	Target power (mW)	Max. Antenna Gain (dBi)	Power Density (mW/ cm ²)
20	0.144	2.56	0.00007334

Note: Even taking into account the tolerance, this device can be satisfied with the limits.

The Above Result had shown that the Device complied with MPE requirement.

Completed By: Teody Manansala



SIEMIC, Inc

775 Montague Expressway, Milpitas, CA 95035

Phone: (408) 526-1188

Date: March 21, 2016