

1-4F, Huafeng Science Park, Xin'an Sixth Road, 82<sup>th</sup> District, Bao'an, Shenzhen, China.

Telephone: +86-755-29451282,  
Fax: +86-755-22639141

Report No.: EBO1410121-E308

Page 1 of 23

# TEST REPORT

**Applicant:** Shenzhen Firstview Electronic Co. Ltd.

**Address of Applicant:** 3-4/F, Block B, Huafeng 1st Technology Zone Baoan Main Road, Baoan District, Shenzhen, China

## Equipment Under Test (EUT)

**Product Name:** 7 inch Tablet PC

**Model No.:** VTA0730, M741

**FCC ID:** YW5VTA0730

**Applicable standards:** FCC CFR Title 47 Part 15 Subpart B:2013

**Date of sample receipt:** November 3, 2014

**Date of Test:** November 3, 2014 To November 14, 2014

**Date of report issue:** November 14, 2014

**Test Result :** PASS \*

\* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:



Kevin Yu  
Laboratory Manager

This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product and does not permit the use of the EBO product certification mark. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report.

This report may only be reproduced and distributed in full. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of EBO International Electrical Approvals or testing done by EBO International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by EBO International Electrical Approvals in writing.

This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."

**2 Version**

Version No.	Date	Description
00	<i>November 14, 2014</i>	<i>Original</i>

**Prepared By:****Date:***November 14, 2014*

---

*Project Engineer***Check By:****Date:***November 14, 2014*

---

*Reviewer*

**3 Contents**

	Page
<b>1 COVER PAGE</b>	1
<b>2 VERSION</b>	2
<b>3 CONTENTS</b>	3
<b>4 TEST SUMMARY</b>	4
<b>5 GENERAL INFORMATION</b>	5
5.1 CLIENT INFORMATION	5
5.2 GENERAL DESCRIPTION OF EUT	5
5.3 TEST MODE	5
5.4 TEST FACILITY	6
5.5 TEST LOCATION	6
5.6 DESCRIPTION OF SUPPORT UNITS	7
5.7 DEVIATION FROM STANDARDS	7
5.8 ABNORMALITIES FROM STANDARD CONDITIONS	7
5.9 OTHER INFORMATION REQUESTED BY THE CUSTOMER	7
<b>6 TEST INSTRUMENTS LIST</b>	8
<b>7 TEST RESULTS AND MEASUREMENT DATA</b>	9
7.1 CONDUCTED EMISSIONS	9
7.2 RADIATED EMISSION	12
<b>8 TEST SETUP PHOTO</b>	18
<b>9 EUT CONSTRUCTIONAL DETAILS</b>	20

## 4 Test Summary

Test Item	Section in CFR 47	Result
Conducted Emission	Part15.107	PASS
Radiated Emissions	Part15.109	PASS

*PASS: The EUT complies with the essential requirements in the standard.*

## 5 General Information

### 5.1 Client Information

Applicant:	Shenzhen Firstview Electronic Co. Ltd.
Address of Applicant:	3-4/F, Block B, Huafeng 1st Technology Zone Baoan Main Road, Baoan District, Shenzhen, China
Manufacturer:	Shenzhen Firstview Electronic Co. Ltd.
Address of Manufacturer:	F3-6, Block B, Huafeng 1st Technology Zone, Baoan Main Road, Baoan District, Shenzhen, P.R.China

### 5.2 General Description of EUT

Product Name:	7 inch Tablet PC
Model No.:	VTA0730, M741
Test Model No.:	VTA0730
Power supply:	Input: DC 5V, 1500mA from adapter Or DC 3.7V, 2000mAh Li-ion Battery

### 5.3 Test mode

Test mode:	
REC mode	Keep the EUT in REC mode
TF Card playing mode	Keep the EUT in TF Card playing mode
PC mode	Keep the EUT in data exchanging with PC mode
<b>Test voltage:</b>	
AC 120V/60Hz	

## 5.4 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

• **CNAS —Registration No.: CNAS L5775**

CNAS has accredited Global United Technology Services Co., Ltd. To ISO/IEC 17025 General Requirements for the competence of testing and calibration laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

• **FCC —Registration No.: 600491**

Global United Technology Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in files. Registration 600491, July 20, 2010.

• **Industry Canada (IC)**

The 3m Semi-anechoic chamber of Global United Technology Services Co., Ltd. Has been Registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 9079A-2, June 26, 2013.

## 5.5 Test Location

All tests were performed at:

Global United Technology Services Co., Ltd.

Address: 2nd Floor, Block No.2, Laodong Industrial Zone, Xixiang Road Baoan District, Shenzhen, China

**5.6 Description of Support Units**

Manufacturer	Description	Model	Serial Number	FCC Approval
HP	Printer	CB495A	05257893	DoC
Apple	PC	A1278	C1MN99ERDTY3	DoC

**5.7 Deviation from Standards**

Biconical, log.per. antenna and horn antenna were used instead of dipole antenna.  
Semi-anechoic Chamber was used as alternation of open air test sites, and all test suites were performed with radiated method in it.

**5.8 Abnormalities from Standard Conditions**

None.

**5.9 Other Information Requested by the Customer**

None.

## 6 Test Instruments list

Radiated Emission:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	3m Semi- Anechoic Chamber	ZhongYu Electron	9.0(L)*6.0(W)* 6.0(H)	GTS250	Mar. 29 2014	Mar. 28 2015
2	Control Room	ZhongYu Electron	6.2(L)*2.5(W)* 2.4(H)	GTS251	N/A	N/A
3	ESU EMI Test Receiver	R&S	ESU26	GTS203	July 01 2014	June 30 2015
4	BiConiLog Antenna	SCHWARZBECK	VULB9163	GTS214	July 01 2014	June 30 2015
5	Double -ridged waveguide horn	SCHWARZBECK	9120D	GTS208	June 27 2014	June 26 2015
6	RF Amplifier	HP	8347A	GTS204	July 01 2014	June 30 2015
7	Preamplifier	HP	8349B	GTS206	July 01 2014	June 30 2015
8	EMI Test Software	AUDIX	E3	N/A	N/A	N/A
9	Coaxial cable	GTS	N/A	GTS210	Mar. 29 2014	Mar. 28 2015
10	Coaxial Cable	GTS	N/A	GTS211	Mar. 29 2014	Mar. 28 2015
11	Thermo meter	N/A	N/A	GTS256	Mar. 29 2014	Mar. 28 2015

Conducted Emission:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	Shielding Room	ZhongYu Electron	7.0(L)x3.0(W)x3.0(H)	GTS264	July 01 2014	June 30 2015
2	EMI Test Receiver	Rohde & Schwarz	ESCS30	GTS223	July 01 2014	June 30 2015
3	10dB Pulse Limita	Rohde & Schwarz	N/A	GTS224	July 01 2014	June 30 2015
4	Coaxial Switch	ANRITSU CORP	MP59B	GTS225	July 01 2014	June 30 2015
5	LISN	SCHWARZBECK MESS-ELEKTRONIK	NSLK 8127	GTS226	July 01 2014	June 30 2015
6	Coaxial Cable	GTS	N/A	GTS227	July 01 2014	June 30 2015
7	EMI Test Software	AUDIX	E3	N/A	N/A	N/A

General used equipment:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	Barometer	ChangChun	DYM3	GTS257	July 08 2014	July 07 2015


## 7 Test Results and Measurement Data

### 7.1 Conducted Emissions

Test Requirement:	FCC Part15 B Section 15.107		
Test Method:	ANSI C63.4:2003		
Test Frequency Range:	150KHz to 30MHz		
Class / Severity:	Class B		
Receiver setup:	RBW=9KHz, VBW=30KHz, Sweep time=auto		
Limit:	Frequency range (MHz)	Limit (dBuV)	
		Quasi-peak	Average
	0.15-0.5	66 to 56*	56 to 46*
	0.5-5	56	46
	5-30	60	50
* Decreases with the logarithm of the frequency.			
Test setup:	<p style="text-align: center;"><b>Reference Plane</b></p> <p>Remark E.U.T: Equipment Under Test LISN: Line Impedance Stabilization Network Test table height=0.8m</p>		
Test procedure:	<ol style="list-style-type: none"> <li>1. The E.U.T and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uH coupling impedance for the measuring equipment.</li> <li>2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs).</li> <li>3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.4: 2003 on conducted measurement.</li> </ol>		
Test Instruments:	Refer to section 6 for details		
Test mode:	Refer to section 5.3 for details. All of the mode were tested and found the "PC mode" is the worst case. Only the data of worst case was reported.		
Test results:	Pass		

## Measurement Data

Test mode:	PC mode		LINE
------------	---------	--	------




Trace: 282

Site : Shielded room  
Condition : FCC PART15 CLASSB QP LISN-2013 LINE

Test Engineer: Mike

Freq	Read	LISN	Cable	Limit	Over	Remark
	Level	Factor	Loss	Level	Line	
MHz	dBuV		dB	dBuV	dBuV	dB
1	0.150	50.40	0.15	0.12	50.67	66.00 -15.33 QP
2	0.195	48.00	0.14	0.13	48.27	63.80 -15.53 QP
3	0.262	40.63	0.11	0.11	40.85	61.38 -20.53 QP
4	0.585	32.54	0.13	0.12	32.79	56.00 -23.21 QP
5	3.720	32.62	0.19	0.15	32.96	56.00 -23.04 QP
6	6.252	33.77	0.23	0.16	34.16	60.00 -25.84 QP

Test mode:	PC mode		NEUTRAL
------------	---------	--	---------



Site : Shielded room  
Condition : FCC PART15 CLASSB QP LISN-2013 NEUTRAL  
Test Engineer: Mike


	Read Freq	LISN Level	Cable Loss	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	
1	0.202	48.26	0.07	0.13	48.46	63.54	-15.08 QP
2	0.264	41.07	0.06	0.11	41.24	61.29	-20.05 QP
3	0.400	37.53	0.06	0.11	37.70	57.86	-20.16 QP
4	0.529	35.53	0.07	0.11	35.71	56.00	-20.29 QP
5	3.720	31.59	0.14	0.15	31.88	56.00	-24.12 QP
6	6.285	32.91	0.17	0.16	33.24	60.00	-26.76 QP

Notes:


1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Final Level =Receiver Read level + LISN Factor + Cable Loss
4. If the average limit is met when using a quasi-peak detector receiver, the EUT shall be deemed to meet both limits and measurement with the average detector receiver is unnecessary.

## 7.2 Radiated Emission

Test Requirement:	FCC Part15 B Section 15.109																								
Test Method:	ANSI C63.4:2003																								
Test Frequency Range:	30MHz to 6GHz																								
Test site:	Measurement Distance: 3m (Semi-Anechoic Chamber)																								
Receiver setup:	<table border="1"><thead><tr><th>Frequency</th><th>Detector</th><th>RBW</th><th>VBW</th><th>Remark</th></tr></thead><tbody><tr><td>30MHz-1GHz</td><td>Quasi-peak</td><td>120kHz</td><td>300kHz</td><td>Quasi-peak Value</td></tr><tr><td>Above 1GHz</td><td>Peak</td><td>1MHz</td><td>3MHz</td><td>Peak Value</td></tr><tr><td></td><td>Peak</td><td>1MHz</td><td>10Hz</td><td>Average Value</td></tr></tbody></table>					Frequency	Detector	RBW	VBW	Remark	30MHz-1GHz	Quasi-peak	120kHz	300kHz	Quasi-peak Value	Above 1GHz	Peak	1MHz	3MHz	Peak Value		Peak	1MHz	10Hz	Average Value
Frequency	Detector	RBW	VBW	Remark																					
30MHz-1GHz	Quasi-peak	120kHz	300kHz	Quasi-peak Value																					
Above 1GHz	Peak	1MHz	3MHz	Peak Value																					
	Peak	1MHz	10Hz	Average Value																					
Limit:	<table border="1"><thead><tr><th>Frequency</th><th>Limit (dBuV/m @3m)</th><th>Remark</th></tr></thead><tbody><tr><td>30MHz-88MHz</td><td>40.00</td><td>Quasi-peak Value</td></tr><tr><td>88MHz-216MHz</td><td>43.50</td><td>Quasi-peak Value</td></tr><tr><td>216MHz-960MHz</td><td>46.00</td><td>Quasi-peak Value</td></tr><tr><td>960MHz-1GHz</td><td>54.00</td><td>Quasi-peak Value</td></tr><tr><td rowspan="2">Above 1GHz</td><td>54.00</td><td>Average Value</td></tr><tr><td>74.00</td><td>Peak Value</td></tr></tbody></table>					Frequency	Limit (dBuV/m @3m)	Remark	30MHz-88MHz	40.00	Quasi-peak Value	88MHz-216MHz	43.50	Quasi-peak Value	216MHz-960MHz	46.00	Quasi-peak Value	960MHz-1GHz	54.00	Quasi-peak Value	Above 1GHz	54.00	Average Value	74.00	Peak Value
Frequency	Limit (dBuV/m @3m)	Remark																							
30MHz-88MHz	40.00	Quasi-peak Value																							
88MHz-216MHz	43.50	Quasi-peak Value																							
216MHz-960MHz	46.00	Quasi-peak Value																							
960MHz-1GHz	54.00	Quasi-peak Value																							
Above 1GHz	54.00	Average Value																							
	74.00	Peak Value																							
Test Procedure:	<ol style="list-style-type: none"><li>1. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.</li><li>2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.</li><li>3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.</li><li>4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.</li><li>5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.</li><li>6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.</li></ol>																								
Test setup:	Below 1GHz																								



Above 1GHz



Test environment:	Temp.: 25 °C	Humid.: 52%	Press.: 1 012mbar
Measurement Record:	Uncertainty: $\pm 4.5\text{dB}$		
Test Instruments:	Refer to section 6 for details		
Test mode:	Refer to section 5.3 for details. All of the mode were tested and found the "PC mode" is the worst case. Only the data of worst case was reported.		
Test results:	Pass		

**Note:**


The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level = Receiver Reading + Antenna Factor + Cable Factor – Preamplifier Factor

**Measurement Data**

Below 1GHz


Test mode:	PC mode	Ant Pol.	Horizontal
------------	---------	----------	------------



Site : 3m chamber  
Condition : FCC PART15 CLASS B 3m VULB9163-2013M HORIZONTAL  
Test Engineer: Bing

	ReadAntenna	Cable	Preamp	Limit	Over	
Freq	Level	Factor	Loss	Level	Line	Limit
MHz	dB <sub>uV</sub>	dB/m	dB	dB	dB <sub>uV/m</sub>	dB <sub>uV/m</sub>
1	43.966	47.64	15.56	0.71	32.02	31.89
2	60.280	43.65	14.69	0.86	31.94	27.26
3	185.788	48.95	12.16	1.77	32.10	30.78
4	290.017	49.66	14.86	2.31	32.18	34.65
5	331.355	46.55	15.79	2.53	32.08	32.79
6	665.804	35.39	20.69	3.97	31.14	28.91
					40.00	-8.11 QP
					40.00	-12.74 QP
					43.50	-12.72 QP
					46.00	-11.35 QP
					46.00	-13.21 QP
					46.00	-17.09 QP

Test mode:	PC mode	Ant Pol.	Vertical
------------	---------	----------	----------




Site : 3m chamber  
Condition : FCC PART15 CLASS B 3m VULB9163-2013M VERTICAL  
Test Engineer: Bing

	ReadAntenna	Cable	Preamp	Limit	Over			
	Freq	Level	Factor	Loss	Level	Line	Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB
1	33.211	52.56	14.31	0.59	32.06	35.40	40.00	-4.60 QP
2	44.743	50.85	15.55	0.72	32.01	35.11	40.00	-4.89 QP
3	154.821	53.37	10.45	1.60	32.00	33.42	43.50	-10.08 QP
4	189.074	50.97	12.48	1.78	32.11	33.12	43.50	-10.38 QP
5	627.274	35.22	20.55	3.83	31.08	28.52	46.00	-17.48 QP
6	890.728	35.30	23.00	4.82	31.19	31.93	46.00	-14.07 QP

Above 1GHz


Test mode:	PC mode	Ant Pol.	Horizontal
------------	---------	----------	------------



Site : 3m chamber  
 Condition : FCC PART 15 (PK) 3m BBHA9120D ANT(>1GHZ) HORIZONTAL  
 Test Engineer: Bing

Freq	ReadAntenna	Cable		Preamp	Limit	Over	Line	Limit	Remark
		Level	Factor						
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	dB	
1	1062.814	29.14	24.65	4.35	32.87	25.27	54.00	-28.73	Average
2	1062.814	39.68	24.65	4.35	32.87	35.81	74.00	-38.19	Peak
3	1415.668	29.33	25.51	4.62	33.45	26.01	54.00	-27.99	Average
4	1415.668	39.45	25.51	4.62	33.45	36.13	74.00	-37.87	Peak
5	1982.685	28.63	26.06	4.95	34.43	25.21	54.00	-28.79	Average
6	1982.685	38.50	26.06	4.95	34.43	35.08	74.00	-38.92	Peak
7	2737.291	28.21	28.23	5.70	33.63	28.51	54.00	-25.49	Average
8	2737.291	38.54	28.23	5.70	33.63	38.84	74.00	-35.16	Peak
9	3574.914	28.65	29.11	7.11	32.67	32.20	54.00	-21.80	Average
10	3574.914	38.32	29.11	7.11	32.67	41.87	74.00	-32.13	Peak
11	4804.636	25.56	31.78	8.60	32.09	33.85	54.00	-20.15	Average
12	4804.636	35.44	31.78	8.60	32.09	43.73	74.00	-30.27	Peak

Test mode:	PC mode	Ant Pol.	Vertical
------------	---------	----------	----------



Site : 3m chamber  
 Condition : FCC PART 15 (PK) 3m BBHA9120D ANT(>1GHZ) VERTICAL  
 Test Engineer: Bing

	ReadAntenna	Cable	Preamp	Limit	Over				
	Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	1117.495	28.62	24.83	4.40	32.95	24.90	54.00	-29.10	Average
2	1117.495	38.73	24.83	4.40	32.95	35.01	74.00	-38.99	Peak
3	1642.661	27.81	24.88	4.77	33.85	23.61	54.00	-30.39	Average
4	1642.661	37.71	24.88	4.77	33.85	33.51	74.00	-40.49	Peak
5	2288.263	27.46	27.98	5.28	34.13	26.59	54.00	-27.41	Average
6	2288.263	37.38	27.98	5.28	34.13	36.51	74.00	-37.49	Peak
7	2961.827	26.46	28.44	5.89	33.37	27.42	54.00	-26.58	Average
8	2961.827	36.78	28.44	5.89	33.37	37.74	74.00	-36.26	Peak
9	4472.336	24.13	31.26	8.31	31.92	31.78	54.00	-22.22	Average
10	4472.336	34.15	31.26	8.31	31.92	41.80	74.00	-32.20	Peak
11	5799.177	21.32	32.63	9.93	32.25	31.63	54.00	-22.37	Average
12	5799.177	31.95	32.63	9.93	32.25	42.26	74.00	-31.74	Peak

## 8 Test Setup Photo

Radiated Emission





Conducted Emission





## 9 EUT Constructional Details









----- End -----