

Passive Test For WiFi2.4												
Freq (MHz)	Effi (%)	Effi (dB)	Gain (dBi)	Gain (dBi)	UHS (%)	DHIS (%)	Max (dBi)	Min (dBi)	Directivity (dBi)	Beamwidth (3dB)	AntH (dBi)	AntV (dBi)
2400	46.6	-3.32	0.68	-1.47	17.792	28.81	0.68	-18.24	3.99	75	49.04	48.91
2410	51.79	-2.86	0.92	-1.23	19.923	31.871	0.92	-18.56	3.78	75	49.07	48.93
2420	56.29	-2.5	1.14	-1.01	21.862	34.422	1.14	-19.03	3.63	75	49.02	48.97
2430	58.38	-2.34	1.26	-0.89	22.776	35.605	1.26	-18.76	3.59	75	49.13	49.11
2440	60.85	-2.16	1.48	-0.67	23.632	37.219	1.48	-18.1	3.63	75	49.13	49.11
2450	63.86	-1.95	1.74	-0.41	24.575	39.281	1.74	-17.39	3.69	75	49.39	49.35
2460	67.3	-1.72	1.99	-0.16	25.635	41.661	1.99	-16.92	3.71	60	49.39	49.35
2470	68.54	-1.64	2	-0.15	25.975	42.562	2	-17.26	3.64	60	49.39	49.3
2480	69.86	-1.56	2.04	-0.11	26.614	43.345	2.04	-17.74	3.6	60	49.44	49.35
2490	65.65	-1.83	1.73	-0.42	25.365	40.281	1.73	-18.8	3.55	60	49.19	49.13
2500	66.17	-1.79	1.74	-0.41	26.063	40.107	1.74	-19.95	3.53	75	49.33	49.33

Application Information	
04Version	4.95.303
TotalTime	13m 14s 432ms
AdditionalInfor	NULL

