

FCC RF Exposure Exemption report
for

Gaming Mouse

Model No.: M-VM610

FCC ID: YWO-M-VM610

of

Applicant: ELECOM CO., LTD.

Address: Fushimimachi 4-1-1, Chuo-ku, Osaka City, Osaka Japan 541-8765

Tested and Prepared

by

Worldwide Testing Services (Taiwan) Co., Ltd.

FCC Registration No.: TW1477, TW1072

Industry Canada filed test laboratory Reg. No.: 20037, 5107A



Report No.: W6M22307-22829-EE

6F, NO. 58, LANE 188, RUEY-KUANG RD., NEIHU TAIPEI 114, TAIWAN, R.O.C.
TEL: 886-2-66068877 FAX: 886-2-66068879 E-mail: wts@wts-lab.com



Registration number: W6M22307-22829-EE
FCC ID: YWO-M-VM610

TABLE OF CONTENTS

1 GENERAL INFORMATION.....2

1.1 NOTES2

1.2 TESTING LABORATORY3

 1.2.1 Location3

 1.2.2 Details of accreditation status3

1.3 APPLICATION DETAILS3

1.4 GENERAL INFORMATION OF TEST ITEM.....4

1.5 TEST STANDARDS4

2 TEST CONFIGURATION5

2.1 TEST ENVIRONMENT5

2.2 MEASUREMENT UNCERTAINTY5

2.3 TEST EQUIPMENT LIST.....5

3 EQUIVALENT ISOTROPIC RADIATED POWER (EIRP).....6

3.1 EXEMPTION LIMITS FOR ROUTINE EVALUATION ACCORDING TO FCC KDB PUBLICATION.....6



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M22307-22829-EE

FCC ID: YWO-M-VM610

1 General Information

1.1 Notes

The purpose of conformity testing is to increase the probability of adherence to the essential requirements or conformity specifications, as appropriate.

The complexity of the technical specifications, however, means that full and thorough testing is impractical for both technical and economic reasons.

Furthermore, there is no guarantee that a test sample which has passed all the relevant tests conforms to a specification.

Neither is there any guarantee that such a test sample will interwork with other genuinely open systems.

The existence of the tests nevertheless provides the confidence that the test sample possesses the qualities as maintained and that its performance generally conforms to representative cases of communications equipment.

Laboratory disclaimer-

1. The test results of this test report relate exclusively to the item tested as specified in 1.5.
2. The test report may only be reproduced or published in full.
3. Reproduction or publication of extracts from the report requires the prior written approval of the Worldwide Testing Services(Taiwan) Co., Ltd.
4. Antenna gain is provided by applicant and laboratory issue relevant data and results.

Tester:

November 03, 2023

Ken Kang

Date

WTS-Lab.

Name

Signature

Technical responsibility for area of testing:

November 03, 2023

Kevin Wang

Date

WTS

Name

Signature



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M22307-22829-EE

FCC ID: YWO-M-VM610

1.2 Testing laboratory

1.2.1 Location

10m OATS

No.5-1, Lishui, Shuang Sing Village, Wanli Dist.,
New Taipei City 207, Taiwan (R.O.C.)

3 meter semi-anechoic chamber

No.35, Aly. 21, Ln. 228, Ankang Rd., Neihu Dist.,
Taipei City 114, Taiwan (R.O.C.)

Tel: 886-2-6613-0228

Worldwide Testing Services (Taiwan) Co., Ltd.

6F., No. 58, Ln. 188, Ruiguang Rd., Neihu Dist.,
Taipei City 114, Taiwan (R.O.C.)

Tel: 886-2-6606-8877

1.2.2 Details of accreditation status

Accredited testing laboratory

FCC filed test laboratory Reg. No.: TW1477, TW1072

Industry Canada filed test laboratory Reg. No.: 20037, 5107A

Test location, where different from Worldwide Testing Services (Taiwan) Co., Ltd. :

Name: ./.

Accredited no.: ./.

Street: ./.

Town: ./.

Country: ./.

1.3 Application details

Approval holder

Name: ELECOM CO., LTD.

Street: Fushimimachi 4-1-1, Chuo-ku,

Town: Osaka City, Osaka

Country: Japan 541-8765


Manufacturer: (if applicable)

Name: ./.

Street: ./.

Town: ./.

Country: ./.



Registration number: W6M22307-22829-EE
FCC ID: YWO-M-VM610

Date of receipt of test item: July 14, 2023
Date of test: from July 17, 2023 to October 31, 2023

1.4 General information of Test item

Type of test item: Gaming Mouse
Model no.: M-VM610
Multi-listing model no.: ./.
Brand name: ELECOM
Power supply: USB 5Vd.c. / Battery 3.7Vd.c., 220mAh, 0.81Wh
Type of antenna: PCB antenna
Antenna gain: 3.03 dBi

Technical data

| Mode | Channel | Conducted Power (dBm) |
|------|------------------|-----------------------|
| 2.4G | Ch 0 : 2402 MHz | -3.15 |
| | Ch 19 : 2440 MHz | -3.11 |
| | Ch 39 : 2480 MHz | -3.15 |


Operation modes: Duplex
Modulation type: GFSK
Sample no.: #01
Special statement: ./.

Classification:

| | |
|--|-------------------------------------|
| Fixed Device | <input type="checkbox"/> |
| Mobile Device (Human Body distance > 20cm) | <input type="checkbox"/> |
| Portable Device (Human Body distance < 20cm) | <input checked="" type="checkbox"/> |

1.5 Test standards

FCC KDB Publication
447498 D01 General RF Exposure Guidance v06



Registration number: W6M22307-22829-EE

FCC ID: YWO-M-VM610

2 Test configuration

2.1 Test environment

Relative humidity content: 20 ... 75 %

Air pressure: 86 ... 103 kPa

Extreme conditions parameters: ./.

2.2 Measurement uncertainty

| Test item Name | Uncertainty |
|--|--------------------------------|
| Estimation Result of Uncertainty of Conducted Output Power Measurement (Peak Output Power (transmitter)) | Expanded Uncertainty : 1.48 dB |

The decision rule is: Measurement uncertainty is not included in the calculation of test results.

2.3 Test Equipment List

RF Conducted

| No. | Test equipment | Type | Serial No. | Manufacturer | Cal. Date | Next Cal. Date |
|-----------------|------------------------|--------------------------|-------------|--------------|-----------------|----------------|
| ETSTW-CE 009 | TEMP.&HUMIDITY CHAMBER | GTH-225-40-1P-U | MAA0305-009 | GIANT FORCE | 2023/7/24 | 2024/7/23 |
| ETSTW-RE 050 | Attenuator 10dB | 50HF-010-1 | None | JFW | 2023/2/17 | 2024/2/16 |
| ETSTW-RE 051 | Attenuator 6dB | 50HF-006-1 | None | JFW | 2023/2/17 | 2024/2/16 |
| ETSTW-RE 053 | Attenuator 3dB | 50HF-003-1 | None | JFW | 2023/2/17 | 2024/2/16 |
| ETSTW-RE 055 | SPECTRUM ANALYZER | FSU 26 | 200074 | R&S | 2023/3/22 | 2024/3/21 |
| ETSTW-RE 060 | Attenuator 30dB | 5015-30 | F651012z-01 | ATM | 2023/2/17 | 2024/2/16 |
| ETSTW-RE 099 | DC Block | 50DB-007-1 | None | JFW | 2023/2/17 | 2024/2/16 |
| ETSTW-RE 112 | AC POWER SOURCE | TFC-1005 | T-0A023536 | T-Power | Function test | |
| ETSTW-RE 127 | RF Switch Box | RFS-01 | None | WTS | 2023/2/17 | 2024/2/16 |
| ETSTW-RE 153 | Signal Analyzer | FSV40 | 101929 | R&S | 2023/9/20 | 2024/9/19 |
| ETSTW-GSM 023 | Power Divider | 4901.19.A | None | SUHNER | 2023/8/28 | 2024/8/27 |
| ETSTW-Cable 027 | Microwave Cable | SUCOFLEX 104 | 279083 | HUBER+SUHNER | 2023/4/27 | 2024/4/26 |
| ETSTW-Cable 030 | Microwave Cable | SUCOFLEX 104 (S_Cable 9) | 279067 | HUBER+SUHNER | 2023/02/17 | 2024/2/16 |
| ETSTW-Cable 045 | Microwave Cable | SUCOFLEX 104 | 325536 | HUBER+SUHNER | 2023/10/20 | 2024/10/19 |
| ETSTW-Cable 058 | Microwave Cable | SUCOFLEX 104 | none | HUBER+SUHNER | 2023/5/26 | 2024/5/25 |
| WTSTW-SW 008 | Signal studio | Agilent | None | AUDIX | Version 2.0.0.1 | |



Registration number: W6M22307-22829-EE
FCC ID: YWO-M-VM610

3 Equivalent Isotropic Radiated Power (EIRP)

FCC Rule: 15.247

EIRP = max. conducted output power + antenna gain

EIRP = -3.11 dBm + 3.03 dBi [antenna gain claimed by manufacturer] = -0.08 dBm = 0.9817 mW

3.1 Exemption Limits for Routine Evaluation according to FCC KDB Publication

RESULT:

Test standard : FCC KDB Publication
447498 D01 General RF Exposure Guidance v06

3.3.1 Exemption Limits for Routine Evaluation – SAR Evaluation

SAR evaluation is required if the separation distance between the user and/or bystander and the antenna and/or radiating element of the device is less than or equal to 20 cm, except when the device operates at or below the applicable output power level (adjusted for tune-up tolerance) for the specified separation distance defined in Table .

Table: SAR evaluation — Exemption limits for routine evaluation based on frequency and separation distance

| MHz | 5 | 10 | 15 | 20 | 25 | mm |
|------|-------|-------|-------|-------|-------|-----------------------------------|
| 2440 | 10.02 | 19.05 | 29.07 | 38.11 | 48.11 | SAR Test Exclusion Threshold (mW) |

| MHz | 30 | 35 | 40 | 45 | 50 | mm |
|------|-------|-------|-------|-------|-------|-----------------------------------|
| 2440 | 57.15 | 67.16 | 77.18 | 86.22 | 96.24 | SAR Test Exclusion Threshold (mW) |

Output power level shall be the higher of the maximum conducted or equivalent isotropically radiated power (e.i.r.p.) source-based, time-averaged output power.

Established separation distance is 5 mm.

Operating frequency band : 2402-2480 MHz

Max. output power level at 5 mm separation distance at 2440 MHz according to table is: 10.02 mW

The product is exempt from SAR Evaluation/Testing because the output power of 0.9817 mW is below the exemption limit of 10.02 mW.