

FCC Part 15

EMI TEST REPORT

(Part 3 – Bluetooth High Power)

of

E.U.T. : Rugged Tablet PC
Model No. : ALGIZ 7X, CS25 plus, CS25
LRBT plus, CS25 GNSS plus,
CC61 plus, CC60 plus
FCC ID. : YY3-0112070926724

for

APPLICANT : Handheld Group AB.
ADDRESS : Kinnegatan 17, 53133, Lidköping, Sweden

Test Performed by

ELECTRONICS TESTING CENTER, TAIWAN

NO. 34. LIN 5, DINGFU VIL., LINKOU DIST.,
NEW TAIPEI CITY, TAIWAN, 24442, R.O.C.

Tel:(02)26023052 Fax:(02)26010910
<http://www.etc.org.tw> ; e-mail : emc@etc.org.tw

Report Number : 13-06-RBF-026-06-03

TEST REPORT CERTIFICATION

Applicant : Handheld Group AB
Kinnegatan 17, 53133, Lidköping, Sweden

Manufacture : WINMATE Communication INC.
9F, No.111-6, Shing-De Rd., San-Chung District, New Taipei City
241 Taiwan

Description of Device :

a) Type of EUT : Rugged Tablet PC

b) Trade Name : Handheld

c) Model No. : ALGIZ 7X, CS25 plus, CS25 LRBT plus, CS25 GNSS plus, CC61 plus, CC60 plus

d) Power Supply : Switching Adapter
I/P: 100-240VAC, 50-60Hz, 2.5A
O/P: 12VDC, 6.6A

Regulation Applied : FCC Rules and Regulations Part 15 Subpart C

I HEREBY CERTIFY THAT: The data shown in this report were made in accordance with the procedures given in ANSI C63.4, and the energy emitted by the device was founded to be within the limits applicable. I assume full responsibility for accuracy and completeness of these data.

Note: 1. The result of the testing report relate only to the item tested.
2. The testing report shall not be reproduced expect in full, without the written approval of ETC.

Summary of Tests

Test	Results
Radiated Emission	Pass
Conducted Emission	Pass
Hopping Channel Separation	Pass
Number of Hopping frequencies used	Pass
Hopping Channel Bandwidth	Pass
Dwell Time of each frequency	Pass
Output Power Requirement	Pass
100 kHz Bandwidth of Frequency Band Edges Requirement	Pass
Out-of-Band Conducted Emission Requirement	Pass


Date Test Item Received : Jun. 19, 2013
Date Test Campaign Completed : Sep. 25, 2013
Date of Issue : Dec. 03, 2013

Test Engineer :



(Vincent Chang, Engineer)

Approve & Authorized :



S. S. Liou, Section Manager
EMC Dept. II of ELECTRONICS
TESTING CENTER, TAIWAN



Table of Contents	Page
1 GENERAL INFORMATION.....	1
1.1 Product Description.....	1
1.2 Characteristics of Device	1
1.3 Test Methodology	1
1.4 Test Facility.....	1
2 PROVISIONS APPLICABLE.....	2
2.1 Definition	2
2.2 Requirement for Compliance	3
2.3 Restricted Bands of Operation	5
2.4 Labeling Requirement.....	6
2.5 User Information	6
3 SYSTEM TEST CONFIGURATION	7
3.1 Justification	7
3.2 Devices for Tested System.....	7
4 RADIATED EMISSION MEASUREMENT	8
4.1 Applicable Standard	8
4.2 Measurement Procedure.....	8
4.3 Measuring Instrument	10
4.4 Radiated Emission Data	11
4.5 Field Strength Calculation.....	19
4.6 Photos of Radiation Measuring Setup.....	20
5 CONDUCTED EMISSION MEASUREMENT.....	21
5.1 Standard Applicable	21
5.2 Measurement Procedure.....	21
5.3 Conducted Emission Data	23
5.4 Result Data Calculation.....	25
5.5 Conducted Measurement Equipment	25
5.6 Photos of Conduction Measuring Setup.....	26
6 ANTENNA REQUIREMENT	27
6.1 Standard Applicable	27
6.2 Antenna Construction.....	27
7 HOPPING CHANNEL SEPARATION.....	28
7.1 Standard Applicable	28
7.2 Measurement Procedure.....	28
7.3 Measurement Equipment	29

- 7.4 Measurement Data 29
- 8 NUMBER OF HOPPING FREQUENCY USED 33**
- 8.1 Standard Applicable 33
- 8.2 Measurement Procedure..... 33
- 8.3 Measurement Equipment 33
- 8.4 Measurement Data 34
- 9 CHANNEL BANDWIDTH..... 38**
- 9.1 Standard Applicable 38
- 9.2 Measurement Procedure..... 38
- 9.3 Measurement Equipment 39
- 9.4 Measurement Data 39
- 10 DWELL TIME ON EACH CHANNEL 43**
- 10.1 Standard Applicable 43
- 10.2 Measurement Procedure..... 43
- 10.3 Measurement Equipment 43
- 10.4 Measurement Data 44
- 11 OUTPUT POWER MEASUREMENT 54**
- 11.1 Standard Applicable 54
- 11.2 Measurement Procedure..... 54
- 11.3 Measurement Equipment 54
- 11.4 Measurement Data 55
- 12 100 kHz BANDWIDTH OF BAND EDGES MEASUREMENT 59**
- 12.1 Standard Applicable 59
- 12.2 Measurement Procedure..... 59
- 12.3 Measurement Equipment 60
- 12.4 Measurement Data 60
- 13 CONDUCTED SPURIOUS EMISSION MEASUREMENT 65**
- 13.1 Standard Applicable 65
- 13.2 Measurement Procedure..... 65
- 13.3 Measurement Equipment 65
- 13.4 Measurement Data 66

1 GENERAL INFORMATION

1.1 Product Description

- a) Type of EUT : Rugged Tablet PC
- b) Trade Name : Handheld
- c) Model No. : ALGIZ 7X, CS25 plus, CS25 LRBT plus, CS25 GNSS plus, CC61 plus, CC60 plus
- d) Power Supply : Switching Adapter
I/P: 100-240VAC, 50-60Hz, 2.5A
O/P: 12VDC, 6.6A

1.2 Characteristics of Device

Frequency band	: Bluetooth: 2402MHz~2480MHz
Number of channels	: Bluetooth: 79 channels
Channel spacing	: 1MHz
Transmitter antenna source	: Internal IFA antenna

1.3 Test Methodology

Both conducted and radiated emissions were performed according to the procedures illustrated in ANSI C63.4 (2003). Other required measurements were illustrated in separate sections of this test report for details. FCC DA 00-705 was used as the referencing measurement procedure of RF tests.

1.4 Test Facility

The open area test site and conducted measurement facility used to collect the radiated data is located on the roof top of Building at NO. 34. LIN 5, DINGFU VIL., LINKOU DIST., NEW TAIPEI CITY, TAIWAN, 24442, R.O.C.

This site has been fully described in a report submitted to your office, and accepted in a letter dated Jan. 11, 2011.

2 PROVISIONS APPLICABLE

2.1 Definition

Unintentional radiator:

A device that intentionally generates and radio frequency energy for use within the device, or that sends radio frequency signals by conduction to associated equipment via connecting wiring, but which is not intended to emit RF energy by radiation or induction.

Class A Digital Device:

A digital device which is marketed for use in commercial or business environment; exclusive of a device which is market for use by the general public, or which is intended to be used in the home.

Class B Digital Device :

A digital device which is marketed for use in a residential environment notwithstanding use in a commercial, business of industrial environment. Example of such devices that are marketed for the general public.

Note : A manufacturer may also qualify a device intended to be marketed in a commercial, business, or industrial environment as a Class B digital device, and in fact is encouraged to do so, provided the device complies with the technical specifications for a Class B Digital Device. In the event that a particular type of device has been found to repeatedly cause harmful interference to radio communications, the Commission may classify such a digital device as a Class B Digital Device, Regardless of its intended use.

Intentional radiator:

A device that intentionally generates and emits radio frequency energy by radiation or induction.

2.2 Requirement for Compliance

(1) Conducted Emission Requirement

Except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

Frequency MHz	Quasi Peak dB μ V	Average dB μ V
0.15 - 0.5	66-56*	56-46*
0.5 - 5.0	56	46
5.0 - 30.0	60	50

* Decreases with the logarithm of the frequency

For intentional device, according to §15.207(a) Line Conducted Emission Limits is same as above table.

(2) Radiated Emission Requirement

For unintentional device, according to §15.109(a), except for Class A digital devices, the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values:

Frequency MHz	Distance Meters	Radiated dB μ V/m	Radiated μ V/m
30 - 88	3	40.0	100
88 - 216	3	43.5	150
216 - 960	3	46.0	200
Above 960	3	54.0	500

For intentional device, according to §15.209(a), the general requirement of field strength of radiated emissions from intentional radiators at a distance of 3 meters shall not exceed the above table.

(3) Antenna Requirement

For intentional device, according to §15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

(4) Hopping Channel Separation

According to 15.247(a)(1), frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

(5) Number of Hopping frequencies used

According to 15.247(a)(1)(iii), frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels.

(6) Hopping Channel Bandwidth

For frequency hopping system operating in the 2400–2483.5 MHz band, there is no requirement for the maximum 20dB bandwidth of the hopping channel. The measurement of the hopping channel bandwidth is for the reference of the hopping channel separation requirement.

(7) Dwell Time of each frequency

According to 15.247(a)(1)(iii), for frequency hopping system operating in the 2400-2483.5 band, the average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

(8) Output Power Requirement

According to 15.247(b)(1), for frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725–5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400–2483.5 MHz band: 0.125 watts.

(9) 100 kHz Bandwidth of Frequency Band Edges Requirement

According to 15.247(d), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the

transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required.

(10) Out-of-Band Conducted Emission Requirement

According to 15.247(d), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required.

2.3 Restricted Bands of Operation

Only spurious emissions are permitted in any of the frequency bands listed below :

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42-16.423	399.9-410	4.5-5.15
0.495 - 0.505 **	16.69475 - 16.69525	608-614	5.35-5.46
2.1735 - 2.1905	16.80425 - 16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475 - 156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2655-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3360-4400	Above 38.6
13.36-13.41			

** : Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz

2.4 Labeling Requirement

The device shall bear the following statement in a conspicuous location on the device :

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions : (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

2.5 User Information

The users manual or instruction manual for an intentional or unintentional radiator shall caution the user that changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

For a Class B digital device or peripheral, the instructions furnished the user shall include the following or similar statement, placed in a prominent location in the text of the manual.

The Federal Communications Commission Radio Frequency Interference Statement includes the following paragraph.

This equipment has been tested and found to comply with the limits for a Class B Digital Device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation.

This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instruction may cause harmful interference to radio communication. However, there is no guarantee that interference will not occur in a particular installation.

If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.

- Increase the separation between the equipment and receiver.

- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.

- Consult the dealer or an experienced radio / TV technician for help.

3 SYSTEM TEST CONFIGURATION

3.1 Justification

For both radiated and conducted emissions, the system was configured for testing in a typical fashion as a customer would normally use it. The peripherals other than EUT were connected in normally standing by situation. Three highest emissions were verified with varying placement of the transmitting antenna connected to EUT (if applicable) to maximize the emission from EUT.

For conducted and radiated emissions, whichever RF channel is operated, the digital circuits' function identically. As the reason, measurement of emissions from digital circuits is performed with the highest, middle and the lowest channel by transmitting mode.

3.2 Devices for Tested System

Device	Manufacture	Model / FCC ID	Cable Description
Rugged Tablet PC *	HANDHELD GROUP AB.	ALGIZ 7X/ YY3-ALGIZ7X	1.8m Unshielded AC Adapter
Earphone	KINYO	EM3000	0.8m Unshielded Earhpone Cable
Monitor	BenQ	FP547	1.8m Unshielded AC Power Cord 0.8m Shielded D-SUB data line
2.5"USB Disk	PHILIPS	100GB	0.3m Unshielded USB Line
2.5"USB Disk	Ministation 3.0	HD-PCTU3	0.3m Unshielded USB Line

Remark "*" means equipment under test.

4 RADIATED EMISSION MEASUREMENT

4.1 Applicable Standard

For unintentional radiator, the radiated emission shall comply with §15.109(a).

For intentional radiators, according to §15.247 (a), operation under this provision is limited to frequency hopping and direct sequence spread spectrum, and the out band emission shall be comply with §15.247 (c)

4.2 Measurement Procedure

1. Setup the configuration per figure 1 and 2 for frequencies measured below and above 1 GHz respectively.
2. For emission frequencies measured below 1 GHz, a pre-scan is performed in a shielded chamber to determine the accurate frequencies of higher emissions will be checked on a open test site. As the same purpose, for emission frequencies measured above 1 GHz, a pre-scan also be performed with a 1 meter measuring distance before final test.
3. For emission frequencies measured below and above 1 GHz, set the spectrum analyzer on a 100 kHz and 1 MHz resolution bandwidth respectively for each frequency measured in step 2.
4. The search antenna is to be raised and lowered over a range from 1 to 4 meters in horizontally polarized orientation. Position the highness when the highest value is indicated on spectrum analyzer, then change the orientation of EUT on test table over a range from 0 ° to 360 ° with a speed as slow as possible, and keep the azimuth that highest emission is indicated on the spectrum analyzer. Vary the antenna position again and record the highest value as a final reading. A RF test receiver is also used to confirm emissions measured.
5. Repeat step 4 until all frequencies need to be measured were complete.
6. Repeat step 5 with search antenna in vertical polarized orientations.
7. Check the three frequencies of highest emission with varying the placement of cables associated with EUT to obtain the worse case and record the result.

Figure 1 : Frequencies measured below 1 GHz configuration





Figure 2 : Frequencies measured above 1 GHz configuration



4.3 Measuring Instrument

The following instrument are used for radiated emissions measurement:


Equipment	Manufacturer	Model No.	Calibration Date	Next Cal. Date
Test Receiver	Rohde & Schwarz	ESVS30	2013/05/06	2014/05/05
Bi-Log Antenna	ETC	MCTD 2756	2012/01/17	2014/01/17
Log-periodic Antenna	EMCO	3146	2012/10/17	2013/10/16
Double Ridged Guide Horn Antenna	EMCO	3116	2012/11/23	2013/11/22
Biconical Antenna	EMCO	3110	2012/10/17	2013/10/16
Double Ridged Antenna	EMCO	3115	2013/04/29	2014/04/28
Amplifier	HP	8449B	2013/01/09	2014/01/08
Amplifier	HP	83051A	2013/05/06	2014/05/05
Amplifier	HP	8447D	2013/05/03	2014/05/02
Spectrum	Rohde & Schwarz	FSP40	2012/12/07	2013/12/06

Measuring instrument setup in measured frequency band when specified detector function is used :

Frequency Band (MHz)	Instrument	Function	Resolution bandwidth	Video Bandwidth
30 to 1000	RF Test Receiver	Quasi-Peak	120 kHz	N/A
	Spectrum Analyzer	Peak	100 kHz	100 kHz
Above 1000	Spectrum Analyzer	Peak	1 MHz	1 MHz
	Spectrum Analyzer	Average	1 MHz	10 Hz

4.4 Radiated Emission Data

4.4.1 Tx Portion




Site	:CHAMBER #2	Date	:2013-09-25
Limit	:1G TO 40G PEAK	Ant. Pol.	: HORIZONTAL
EUT	:7" Tab PC	Temp.	:25°C
Power Rating	:120V 60Hz	Humi.	:65%
Engineer.	:VC		
Test Mode	:TX RX-CHLo:2402MHz,Mi:2441MHz,Hi:2480MHz		

Freq MHz	Reading dBuV	Correction Factor dB	Result dBuV/m	Limits dBuV/m	Over limit dB	Detector
4804.0000	42.6	1.3	43.9	54.0	-10.1	Average
4804.0000	52.5	1.3	53.8	74.0	-20.2	Peak
4882.0000	42.2	1.4	43.6	54.0	-10.4	Average
4882.0000	52.1	1.4	53.5	74.0	-20.5	Peak
4960.0000	41.7	1.6	43.3	54.0	-10.7	Average
4960.0000	51.6	1.6	53.2	74.0	-20.8	Peak

Note :

1. Result = Reading + Corrected Factor
2. Corrected Factor = Antenna Factor + Cable Loss - Amplifier Gain (if any)
3. The margin value=Limit - Result




Site	:CHAMBER #2	Date	:2013-09-25
Limit	:1G TO 40G PEAK	Ant. Pol.	: VERTICAL
EUT	:7" Tab PC	Temp.	:25°C
Power Rating	:120V 60Hz	Humi.	:65%
Engineer.	:VC		
Test Mode	:TX RX-CHLo:2402MHz,Mi:2441MHz,Hi:2480MHz		

Freq MHz	Reading dBuV	Correction Factor dB	Result dBuV/m	Limits dBuV/m	Over limit dB	Detector
4804.0000	40.0	1.3	41.3	54.0	-12.7	Average
4804.0000	49.9	1.3	51.2	74.0	-22.8	Peak
4882.0000	40.1	1.4	41.5	54.0	-12.5	Average
4882.0000	50.2	1.4	51.6	74.0	-22.4	Peak
4960.0000	40.2	1.6	41.8	54.0	-12.2	Average
4960.0000	50.1	1.6	51.7	74.0	-22.3	Peak

Note :

1. Result = Reading + Corrected Factor
2. Corrected Factor = Antenna Factor + Cable Loss - Amplifier Gain (if any)
3. The margin value=Limit - Result

4.4.2 Radiated Emissions in Restricted Bands




Site :CHAMBER #2 Date :2013-09-25
 Limit :1G TO 40G PEAK Ant. Pol. :HORIZONTAL
 EUT :7" Tab PC
 Temp. :25°C
 Humi. :65%
 Test Mode :CH LO & HI - Restricted Bands

Freq MHz	Reading dBuV	Correction Factor dB	Result dBuV/m	Limits dBuV/m	Over limit dB	Detector
2341.0000	47.0	-6.0	41.0	74.0	-33.0	Peak
2363.5000	47.3	-5.9	41.4	74.0	-32.6	Peak
2490.5000	48.6	-5.5	43.1	74.0	-30.9	Peak
2499.0000	47.2	-5.5	41.7	74.0	-32.3	Peak

Note :

1. Result = Reading + Corrected Factor
2. Corrected Factor = Antenna Factor + Cable Loss - Amplifier Gain (if any)
3. The margin value=Limit - Result



Site :CHAMBER #2 Date :2013-09-25
 Limit :1G TO 40G PEAK Ant. Pol. :VERTICAL
 EUT :7" Tab PC
 Temp. :25°C
 Humi. :65%
 Test Mode :CH LO & HI - Restricted Bands


Freq MHz	Reading dBuV	Correction Factor dB	Result dBuV/m	Limits dBuV/m	Over limit dB	Detector
2359.0000	47.8	-5.9	41.9	74.0	-32.1	Peak
2366.0000	47.6	-5.9	41.7	74.0	-32.3	Peak
2486.5000	47.1	-5.5	41.6	74.0	-32.4	Peak
2493.0000	47.6	-5.5	42.1	74.0	-31.9	Peak

Note :

1. Result = Reading + Corrected Factor
2. Corrected Factor = Antenna Factor + Cable Loss - Amplifier Gain (if any)
3. The margin value=Limit - Result

4.4.3 Other Emissions

a) Emission frequencies below 1 GHz




Site	:OPEN SITE	Date	:2013-07-05
Limit	:3M	Ant. Pol.	:HORIZONTAL
EUT	:7" TABLE PC	Temp.	:20°C
Power Rating	:120V/60Hz (ADAPTER)	Humi.	:65%
Model	: ALGIZ 7X	Engineer.	:VC
Test Mode	:CHARGE & FULL SYSTEM & BT LINK MODE		

Freq MHz	Reading dBuV	Correction Factor dB	Result dBuV/m	Limits dBuV/m	Over limit dB	Detector
239.5200	25.7	19.3	45.0	46.0	-1.0	QP
262.8000	20.3	21.4	41.7	46.0	-4.3	QP
472.3200	23.4	20.9	44.3	46.0	-1.7	QP
509.1800	20.1	21.8	41.9	46.0	-4.1	QP
652.7400	15.7	24.3	40.0	46.0	-6.0	QP
800.1800	16.8	26.3	43.1	46.0	-2.9	QP

Note :

1. Result = Reading + Corrected Factor
2. Corrected Factor = Antenna Factor + Cable Loss
3. The margin value=Limit - Result




Site	:OPEN SITE	Date	:2013-07-05
Limit	:3M	Ant. Pol.	:VERTICAL
EUT	:7" TABLE PC	Temp.	:20°C
Power Rating	:120V/60Hz (ADAPTER)	Humi.	:65%
Model	: ALGIZ 7X	Engineer.	:VC
Test Mode	:CHARGE & FULL SYSTEM & BT LINK MODE		

Freq MHz	Reading dBuV	Correction Factor dB	Result dBuV/m	Limits dBuV/m	Over limit dB	Detector
47.4600	25.3	12.3	37.6	40.0	-2.4	QP
68.8000	28.1	10.5	38.6	40.0	-1.4	QP
224.0000	21.5	18.7	40.2	46.0	-5.8	QP
288.0200	18.0	23.5	41.5	46.0	-4.5	QP
472.3200	20.8	20.9	41.7	46.0	-4.3	QP
796.3000	16.9	26.3	43.2	46.0	-2.8	QP

Note :

1. Result = Reading + Corrected Factor
2. Corrected Factor = Antenna Factor + Cable Loss
3. The margin value=Limit - Result

b) Emission frequencies above 1 GHz




Site	:CHAMBER #2	Date	:2013-07-05
Limit	:1G TO 40G PEAK	Ant. Pol.	:HORIZONTAL
EUT	:7" TABLE PC	Temp.	:20°C
Power Rating	:120V/60Hz (ADAPTER)	Humi.	:65%
Model	: ALGIZ 7X	Engineer.	:VC
Test Mode	:CHARGE & FULL SYSTEM & BT LINK MODE		

Freq MHz	Reading dBuV	Correction Factor dB	Result dBuV/m	Limits dBuV/m	Over limit dB	Detector
2122.0000	48.4	-6.7	41.7	74.0	-32.3	Peak
3295.0000	47.4	-2.7	44.7	74.0	-29.3	Peak
3805.0000	47.7	-0.8	46.9	74.0	-27.1	Peak
5590.0000	45.1	3.0	48.1	74.0	-25.9	Peak
6023.5000	44.9	3.6	48.5	74.0	-25.5	Peak
7018.0000	45.0	5.0	50.0	74.0	-24.0	Peak

Note :

1. Result = Reading + Corrected Factor
2. Corrected Factor = Antenna Factor + Cable Loss - Amplifier Gain (if any)
3. The margin value=Limit - Result
4. Peak measurements are compared to the average limit - as peak measurements are below the average limit, they also comply with the peak limit.



Site : CHAMBER #2 Date : 2013-07-05
 Limit : 1G TO 40G PEAK Ant. Pol. : VERTICAL
 EUT : 7" TABLE PC Temp. : 20°C
 Power Rating : 120V/60Hz (ADAPTER) Humi. : 65%
 Model : ALGIZ 7X Engineer. : VC
 Test Mode : CHARGE & FULL SYSTEM & BT LINK MODE

Freq MHz	Reading dBuV	Correction Factor dB	Result dBuV/m	Limits dBuV/m	Over limit dB	Detector
2020.0000	48.5	-7.1	41.4	74.0	-32.6	Peak
2785.0000	47.8	-4.4	43.4	74.0	-30.6	Peak
3448.0000	47.3	-2.1	45.2	74.0	-28.8	Peak
4264.0000	46.8	0.1	46.9	74.0	-27.1	Peak
6712.0000	45.6	4.3	49.9	74.0	-24.1	Peak
7222.0000	46.1	5.6	51.7	74.0	-22.3	Peak

Note :

1. Result = Reading + Corrected Factor
2. Corrected Factor = Antenna Factor + Cable Loss - Amplifier Gain (if any)
3. The margin value = Limit - Result
4. Peak measurements are compared to the average limit - as peak measurements are below the average limit, they also comply with the peak limit.

4.5 Field Strength Calculation


The field strength is calculated by adding the Antenna Factor, High Pass Filter Loss (if used) and Cable Loss, and subtracting the Amplifier Gain (if any) from the measured reading. The basic equation calculation is as follows:

$$\mathbf{Result = Reading + Corrected Factor}$$

where Corrected Factor

$$= \text{Antenna FACTOR} + \text{Cable Loss} + \text{High Pass Filter Loss} - \text{Amplifier Gain}$$

4.6 Photos of Radiation Measuring Setup



5 CONDUCTED EMISSION MEASUREMENT

5.1 Standard Applicable

According to §15.207(a), except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.


Frequency MHz	Quasi Peak dB μ V	Average dB μ V
0.15 - 0.5	66-56*	56-46*
0.5 - 5.0	56	46
5.0 - 30.0	60	50

* Decreases with the logarithm of the frequency


5.2 Measurement Procedure

1. Setup the configuration per figure 5.
2. A preliminary scan with a spectrum monitor is performed to identify the frequency of emission that has the highest amplitude relative to the limit by operating the EUT in selected modes of operation, typical cable positions, and with a typical system configuration.
3. Record the 6 or 8 highest emissions relative to the limit.
4. Measure each frequency obtained from step 3 by a test receiver set on quasi peak detector function, and then records the accuracy frequency and emission level. If all emissions measured in the specified band are attenuated more than 20 dB from the limit, this step would be ignored, and the peak detector function would be used.
5. Confirm the highest three emissions with variation of the EUT cable configuration and record the final data.
6. Repeat all above procedures on measuring each operation mode of EUT.

Figure 5: Conducted emissions measurement configuration



5.3 Conducted Emission Data




Site : conducted #1 Date : 07-05-2013
 Condition : CLASS-B QP LISN : NEUTRAL
 Tem / Hum : 25 °C / 65%
 Test Mode : CHARGE & FULL SYSTEM & BLUETOOTH LINK MODE
 EUT : 7" Tab PC
 Power Rating : 120V/60Hz (Adapter)
 Memo : Memo :

Freq (MHz)	Reading (dBuV)	Factor (dB)	Emission Level (dBuV)	Limit Line (dBuV)	Over Limit (dB)	Remark
0.1694	34.2	10.3	44.5	65.0	-20.5	QP
0.2894	25.5	10.3	35.8	60.5	-24.7	QP
0.4171	24.2	10.3	34.5	57.5	-23.0	QP
1.0940	18.5	10.4	28.9	56.0	-27.1	QP
11.1980	19.9	10.7	30.6	60.0	-29.4	QP
16.6610	23.5	10.9	34.4	60.0	-25.6	QP

Note :

1. Result = Reading + Factor
2. Factor = LISN Factor + Cable Loss



Site : conducted #1 Date : 07-05-2013
 Condition : CLASS-B QP LISN : LINE
 Tem / Hum : 25 °C / 65%
 Test Mode : CHARGE & FULL SYSTEM & BLUETOOTH LINK MODE
 EUT : 7" Tab PC
 Power Rating : 120V/60Hz (Adapter)

Memo : Memo :

Freq (MHz)	Reading (dBuV)	Factor (dB)	Emission Level (dBuV)	Limit Line (dBuV)	Over Limit (dB)	Remark
0.2894	24.9	10.3	35.2	60.5	-25.3	QP
0.4994	20.3	10.3	30.6	56.0	-25.4	QP
1.0540	17.6	10.5	28.1	56.0	-27.9	QP
2.3340	17.2	10.5	27.7	56.0	-28.3	QP
11.1980	20.9	10.6	31.5	60.0	-28.5	QP
17.3830	23.7	10.8	34.5	60.0	-25.5	QP

Note :

1. Result = Reading + Factor
2. Factor = LISN Factor + Cable Loss

5.4 Result Data Calculation

The result data is calculated by adding the LISN Factor to the measured reading. The basic equation with a sample calculation is as follows:

$$\mathbf{RESULT = READING + LISN FACTOR}$$

Assume a receiver reading of 22.5 dB μ V is obtained, and LISN Factor is 0.1 dB, then the total of disturbance voltage is 22.6 dB μ V.

$$\text{RESULT} = 22.5 + 0.1 = 22.6 \text{ dB } \mu \text{ V}$$

$$\begin{aligned} \text{Level in } \mu \text{ V} &= \text{Common Antilogarithm}[(22.6 \text{ dB } \mu \text{ V})/20] \\ &= 13.48 \mu \text{ V} \end{aligned}$$

5.5 Conducted Measurement Equipment

The following test equipments are used during the conducted test.

Equipment	Manufacturer	Model No.	Calibration Date	Next Cal. Date
EMI Test Receiver	Rohde & Schwarz	ESCI	2012/07/16	2013/07/16
LISN	EMCO	3825/2	2012/11/02	2013/11/01
LISN	Rohde & Schwarz	ESH2-Z5	2013/04/12	2014/04/11

5.6 Photos of Conduction Measuring Setup



6 ANTENNA REQUIREMENT

6.1 Standard Applicable

For intentional device, according to 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

6.2 Antenna Construction

Please see photos submitted in Exhibit.

The antenna was embedded in the EUT. No consideration of replacement. The antenna gain is 3.8dBi. No need to reduce the peak output power.

7 HOPPING CHANNEL SEPARATION


7.1 Standard Applicable

According to 15.247(a)(1), frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

7.2 Measurement Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT as shown in figure 4 without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. The EUT must have its hopping function enabled. Then set it to any one convenient frequency within its operating range.
3. Use the following spectrum analyzer settings:
 - Span = wide enough to capture the peaks of two adjacent channels
 - Resolution (or IF) Bandwidth (RBW) $\geq 1\%$ of the span
 - Video (or Average) Bandwidth (VBW) \geq RBW
 - Sweep = auto
 - Detector function = peak
 - Trace = max hold
4. Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels. Plot the result on the screen of spectrum analyzer.
5. Repeat above procedures until all frequencies measured were complete.

Figure 4 : Measurement configuration.



7.3 Measurement Equipment

Equipment	Manufacturer	Model No.	Calibration Date	Next Cal. Date
Spectrum Analyzer	Rohde & Schwarz	FSP40	2012/12/07	2013/12/06
Attenuator	Weinschel Engineering	1	N/A	N/A

7.4 Measurement Data

Test Date : Sep. 23, 2013 Temperature : 25 °C Humidity : 65 %

- a) Channel Low : Adjacent Hopping Channel Separation is 1.000 MHz
- b) Channel Middle : Adjacent Hopping Channel Separation is 1.000 MHz
- c) Channel High : Adjacent Hopping Channel Separation is 1.000 MHz


Note : The expanded uncertainty: frequency $\times 1.65 \times 10^{-6}$ ($1 \text{ GHz} < f \leq 18 \text{ GHz}$).

Channel Low



*RBW 30 kHz Delta 1 [T1]
VBW 100 kHz 0.11 dB
SWT 2.5 ms 1.000000000 MHz

Ref 31 dBm Att 60 dB




Channel Middle



*RBW 30 kHz Delta 1 [T1]
VBW 100 kHz -0.33 dB
SWT 2.5 ms 1.000000000 MHz

Ref 31 dBm

Att 60 dB




Channel High



*RBW 30 kHz Delta 1 [T1]
VBW 100 kHz -0.19 dB
SWT 2.5 ms 1.000000000 MHz

Ref 31 dBm

Att 60 dB



8 NUMBER OF HOPPING FREQUENCY USED

8.1 Standard Applicable

According to 15.247(a)(1)(iii), frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels.

8.2 Measurement Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT as shown in figure 4 without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. The EUT must have its hopping function enabled.
3. Use the following spectrum analyzer settings:
 - Span = the frequency band of operation
 - RBW \geq 1% of the span
 - VBW \geq RBW
 - Sweep = auto
 - Detector function = peak
 - Trace = max hold
4. Allow the trace to stabilize. Plot the result on the screen of spectrum analyzer.
5. Repeat above procedures until all frequencies measured were complete.

8.3 Measurement Equipment

Equipment	Manufacturer	Model No.	Calibration Date	Next Cal. Date
Spectrum Analyzer	Rohde & Schwarz	FSP40	2012/12/07	2013/12/06
Attenuator	Weinschel Engineering	1	N/A	N/A

8.4 Measurement Data

Test Date : Sep. 23, 2013 Temperature : 25 °C Humidity : 65 %

There are 79 hopping frequencies used.

Note : The expanded uncertainty: $frequency \times 1.65 \times 10^{-6}$ ($1 \text{ GHz} < f \leq 18 \text{ GHz}$).

Channel Low




*RBW 300 kHz

VBW 1 MHz

SWT 2.5 ms

Ref 30 dBm

Att 60 dB




Channel Middle



*RBW 300 kHz
VBW 1 MHz
SWT 2.5 ms

Ref 30 dBm

Att 60 dB



Channel High




*RBW 300 kHz
VBW 1 MHz
SWT 2.5 ms

Ref 30 dBm

Att 60 dB

Offset 1 dB

1 PK
VIEW



A

LVL

9 CHANNEL BANDWIDTH

9.1 Standard Applicable

For frequency hopping system operating in the 2400–2483.5 MHz band, there is no requirement for the maximum 20dB bandwidth of the hopping channel. The measurement of the hopping channel bandwidth is for the reference of the hopping channel separation requirement.

9.2 Measurement Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT as shown in figure 4 without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range.
3. Use the following spectrum analyzer settings:
 - Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hopping channel
 - RBW \geq 1% of the 20 dB bandwidth
 - VBW \geq RBW
 - Sweep = auto
 - Detector function = peak
 - Trace = max hold
4. Allow the trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. Use the marker-delta function to measure 20 dB down one side of the emission. Reset the marker-delta function, and move the marker to the other side of the emission, until it is (as close as possible to) even with the reference marker level. The marker-delta reading at this point is the 20 dB bandwidth of the emission. Plot the result on the screen of spectrum analyzer.
5. Repeat above procedures until all frequencies measured were complete.

9.3 Measurement Equipment

Equipment	Manufacturer	Model No.	Calibration Date	Next Cal. Date
Spectrum Analyzer	Rohde & Schwarz	FSP40	2012/12/07	2013/12/06
Attenuator	Weinschel Engineering	1	N/A	N/A

9.4 Measurement Data

Test Date : Sep. 23, 2013 Temperature : 25 °C Humidity : 65 %

- a) Channel Low : Channel Bandwidth is 828 kHz
- b) Channel Middle : Channel Bandwidth is 820 kHz
- c) Channel High : Channel Bandwidth is 896 kHz

Note : The expanded uncertainty: $frequency \times 1.65 \times 10^{-6}$ ($1 \text{ GHz} < f \leq 18 \text{ GHz}$).

Channel Low




*RBW 30 kHz Marker 1 [T1]
VBW 100 kHz 17.18 dBm
SWT 2.5 ms 2.401976000 GHz

Ref 31 dBm

Att 60 dB

1 PK
VIEW



Center 2.402 GHz

200 kHz/

Span 2 MHz

Channel Middle




*RBW 30 kHz Marker 1 [T1]
VBW 100 kHz 16.81 dBm
SWT 2.5 ms 2.440972000 GHz

Ref 31 dBm

Att 60 dB

1 PK
VIEW



Center 2.441 GHz

200 kHz/

Span 2 MHz

Channel High




*RBW 30 kHz Marker 1 [T1]
VBW 100 kHz 15.61 dBm
SWT 2.5 ms 2.479968000 GHz

Ref 31 dBm

Att 60 dB

1 PK
VIEW



A

LVL

Center 2.48 GHz 200 kHz/ Span 2 MHz

10 DWELL TIME ON EACH CHANNEL

10.1 Standard Applicable

According to 15.247(a)(1)(iii), for frequency hopping system operating in the 2400-2483.5 band, the average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

10.2 Measurement Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT as shown in figure 4 without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. The EUT must have its hopping function enabled.
3. Use the following spectrum analyzer settings:
 - Span = zero span, centered on a hopping channel
 - RBW = 1 MHz
 - VBW \geq RBW
 - Sweep = as necessary to capture the entire dwell time per hopping channel
 - Detector function = peak
 - Trace = max hold
4. Use the marker-delta function to determine the dwell time. Plot the result on the screen of spectrum analyzer.
5. Repeat above procedures until all frequencies measured were complete.

10.3 Measurement Equipment

Equipment	Manufacturer	Model No.	Calibration Date	Next Cal. Date
Spectrum Analyzer	Rohde & Schwarz	FSP40	2012/12/07	2013/12/06
Attenuator	Weinschel Engineering	1	N/A	N/A

10.4 Measurement Data

Test Date : Sep. 23, 2013 Temperature : 25 °C Humidity : 65 %

Period = 0.4(seconds) x 79(channels) = 31.6 seconds

A. DH1 Mode

The Bluetooth system hops at a rate of 1600 times per second. This means there are 1600 timeslots in one second. The DH1 data rate operates on a one-slot transmission and one-slot receiving basis. Thus there are $1600/(1+1) = 800$ transmissions per second. In one period for each particular channel there are $10.13 \times 31.6 = 320.1$ times of transmissions.

- a) Channel Low : the dwell time is $0.480\text{ms} \times 320.1 = 153.648$ ms
- b) Channel Middle : the dwell time is $0.480\text{ms} \times 320.1 = 153.648$ ms
- c) Channel Hi : the dwell time is $0.480\text{ms} \times 320.1 = 153.648$ ms

The maximum time of occupancy for a particular channel is 153.9ms in any 31.6 second period, which is less than the 400ms allowed by the rules; therefore, it meets the requirements of this section.

B. DH3 Mode

The Bluetooth system hops at a rate of 1600 times per second. This means there are 1600 timeslots in one second. The DH3 data rate operates on a three-slot transmission and one-slot receiving basis. Thus there are $1600/(3+1) = 400$ transmissions per second. In one period for each particular channel there are $5.06 \times 31.6 = 159.9$ times of transmissions.

- a) Channel Low : the dwell time is $1.84\text{ms} \times 159.9 = 294.216$ ms
- b) Channel Middle : the dwell time is $1.84\text{ms} \times 159.9 = 294.216$ ms
- c) Channel Hi : the dwell time is $1.84\text{ms} \times 159.9 = 294.216$ ms

The maximum time of occupancy for a particular channel is 307.0ms in any 31.6 second period, which is less than the 400 ms allowed by the rules; therefore, it meets the requirements of this section.

C. DH5 Mode

The Bluetooth system hops at a rate of 1600 times per second. This means there are 1600 timeslots in one second. The DH5 data rate operates on a five-slot transmission and one-slot receiving basis. Thus there are $1600/(5+1) = 266.7$ transmissions per second. In one period for each particular channel there are $3.38 \times 31.6 = 106.81$ times of transmissions.

- a) Channel Low : the dwell time is $3.12\text{ms} \times 106.81 = 333.2472$ ms
- b) Channel Middle : the dwell time is $3.12\text{ms} \times 106.81 = 333.2472$ ms
- c) Channel Hi : the dwell time is $3.12\text{ms} \times 106.81 = 333.2472$ ms


The maximum time of occupancy for a particular channel is 342.9ms in any 31.6 second period, which is less than the 400 ms allowed by the rules; therefore, it meets the requirements of this section.

Note : The expanded uncertainty 1 μ s.

Channel Low; DH1




RBW 1 MHz Delta 1 [T1]
*VBW 1 MHz -4.65 dB
Ref 30 dBm Att 60 dB SWT 10 ms 480.000000 µs



23 2013 1 28


Channel Middle; DH1



Channel High; DH1




RBW 1 MHz Delta 1 [T1]
*VBW 1 MHz -4.99 dB
Ref 30 dBm Att 60 dB SWT 10 ms 480.000000 μ s



Channel Low; DH3




RBW 1 MHz Delta 1 [T1]
*VBW 1 MHz -0.68 dB
Ref 30 dBm Att 60 dB SWT 20 ms 1.840000 ms



Channel Middle; DH3




RBW 1 MHz Delta 1 [T1]
*VBW 1 MHz -0.68 dB
Ref 30 dBm Att 60 dB SWT 20 ms 1.840000 ms



Channel High; DH3




RBW 1 MHz Delta 1 [T1]
*VBW 1 MHz -5.33 dB
Ref 30 dBm Att 60 dB SWT 20 ms 1.840000 ms




Channel Low; DH5




RBW 1 MHz Delta 1 [T1]
*VBW 1 MHz -0.06 dB
Ref 30 dBm Att 60 dB SWT 30 ms 3.120000 ms



Channel Middle; DH5



Channel High; DH5



11 OUTPUT POWER MEASUREMENT

11.1 Standard Applicable

According to 15.247(b)(1), for frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725–5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400–2483.5 MHz band: 0.125 watts.

11.2 Measurement Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT as shown in figure 4 without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
3. Use the following spectrum analyzer settings:
 - Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel
 - RBW > the 20 dB bandwidth of the emission being measured
 - VBW \geq RBW
 - Sweep = auto
 - Detector function = peak
 - Trace = max hold
4. Allow the trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. The indicated level is the peak output power. Plot the result on the screen of spectrum analyzer.
5. Repeat above procedures until all frequencies measured were complete.

11.3 Measurement Equipment

Equipment	Manufacturer	Model No.	Calibration Date	Next Cal. Date
Spectrum Analyzer	Rohde & Schwarz	FSP40	2012/12/07	2013/12/06
Attenuator	Weinschel Engineering	1	N/A	N/A

11.4 Measurement Data

Test Date : Sep. 23, 2013 Temperature : 25 °C Humidity : 65 %

- a) Channel Low : Output Peak Power is 17.02 dBm = **50.350** mW
- b) Channel Middle : Output Peak Power is 16.75 dBm = **47.315** mW
- c) Channel High : Output Peak Power is 16.31 dBm = **42.756** mW

Note : The expanded uncertainty: 2dB.


Channel Low



*RBW 1 MHz Marker 1 [T1]
VBW 3 MHz 17.02 dBm
SWT 2.5 ms 2.401830000 GHz

Ref 31 dBm

Att 60 dB



Channel Middle




*RBW 1 MHz Marker 1 [T1]
VBW 3 MHz 16.75 dBm
SWT 2.5 ms 2.440980000 GHz

Ref 31 dBm

Att 60 dB

1 PK
VIEW




Channel High



*RBW 1 MHz Marker 1 [T1]
VBW 3 MHz 16.31 dBm
SWT 2.5 ms 2.479930000 GHz

Ref 31 dBm

Att 60 dB



12 100 kHz BANDWIDTH OF BAND EDGES MEASUREMENT

12.1 Standard Applicable

According to 15.247(d), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required.

12.2 Measurement Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT as shown in figure 4 without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
3. Use the following spectrum analyzer settings:
 - Span = wide enough to capture the peak level of the emission operating on the channel closest to the bandedge, as well as any modulation products which fall outside of the authorized band of operation
 - RBW \geq 1% of the span
 - VBW \geq RBW
 - Sweep = auto
 - Detector function = peak
 - Trace = max hold
4. Allow the trace to stabilize. Set the marker on the emission at the bandedge, or on the highest modulation product outside of the band, if this level is greater than that at the bandedge. Enable the marker-delta function, then use the marker-to-peak function to move the marker to the peak of the in-band emission. Plot the result on the screen of spectrum analyzer.
5. Repeat above procedures until all measured frequencies were complete.

12.3 Measurement Equipment

Equipment	Manufacturer	Model No.	Calibration Date	Next Cal. Date
Spectrum Analyzer	Rohde & Schwarz	FSP40	2012/12/07	2013/12/06
Attenuator	Weinschel Engineering	1	N/A	N/A

12.4 Measurement Data

Test Date : Sep. 23, 2013 Temperature : 25 °C Humidity : 65 %

- a) Lower Band Edge : All emissions in this 100kHz bandwidth are attenuated more than 20dB from the carrier.
- b) Upper Band Edge : All emissions in this 100kHz bandwidth are attenuated more than 20dB from the carrier.

Note : The expanded uncertainty: 2dB.

Lower Band Edge (Hoppin off)



*RBW 100 kHz Marker 1 [T1]
VBW 300 kHz -31.29 dBm
SWT 2.5 ms 2.398820000 GHz


Ref 30 dBm

Att 60 dB

SWT 2.5 ms

2.398820000 GHz

1 PK
VIEW



A

LVL

Upper Band Edge (Hoppin off)




*RBW 100 kHz Marker 1 [T1]
VBW 300 kHz -31.86 dBm
SWT 2.5 ms 2.484640000 GHz

Ref 30 dBm

Att 60 dB

1 PK
VIEW



Start 2.479 GHz


1 MHz/

Stop 2.489 GHz

Lower Band Edge (Hoppin on)



*RBW 100 kHz Marker 1 [T1]
VBW 300 kHz -30.32 dBm
SWT 2.5 ms 2.398280000 GHz




Upper Band Edge (Hoppin on)



*RBW 100 kHz Marker 1 [T1]
VBW 300 kHz -30.61 dBm
SWT 2.5 ms 2.484480000 GHz

Ref 30 dBm

Att 60 dB



13 CONDUCTED SPURIOUS EMISSION MEASUREMENT

13.1 Standard Applicable

According to 15.247(c), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required.

13.2 Measurement Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT as shown in figure 4 without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.

3. Use the following spectrum analyzer settings:

Span = wide enough to capture the peak level of the in-band emission and all spurious emissions (e.g., harmonics) from the lowest frequency generated in the EUT up through the 10th harmonic. Typically, several plots are required to cover this entire span.

RBW = 100 kHz

VBW \geq RBW

Sweep = auto

Detector function = peak

Trace = max hold.

4. Allow the trace to stabilize. Set the marker on the peak of any spurious emission recorded. Plot the result on the screen of spectrum analyzer.
5. Repeat above procedures until all measured frequencies were complete.

13.3 Measurement Equipment

Equipment	Manufacturer	Model No.	Calibration Date	Next Cal. Date
Spectrum Analyzer	Rohde & Schwarz	FSP40	2012/12/07	2013/12/06
Attenuator	Weinschel Engineering	1	N/A	N/A

13.4 Measurement Data

Test Date : Sep. 23, 2013 Temperature : 25 °C Humidity : 65 %

Mode : Low Channel

- a) 1 GHz to 26.5 GHz frequency band: All emissions are attenuated more than 20dB from the carrier.

Mode : Middle Channel

- a) 1 GHz to 26.5 GHz frequency band: All emissions are attenuated more than 20dB from the carrier.

Mode : High Channel

- a) 1 GHz to 26.5 GHz frequency band: All emissions are attenuated more than 20dB from the carrier.

Note : The expanded uncertainty: 2dB.

Channel Low



*RBW 100 kHz


VBW 300 kHz

SWT 2.4 s

Ref 30 dBm

*Att 10 dB

1 PK
VIEW



Channel Middle



*RBW 100 kHz


VBW 300 kHz

SWT 2.4 s

Ref 30 dBm

*Att 10 dB

1 PK
VIEW



Channel High



*RBW 100 kHz
VBW 300 kHz
SWT 2.4 s

Ref 30 dBm

*Att 10 dB

1 PK
VIEW

