



Chunghwa Telecom CO., Ltd
Telecommunication Laboratories
Testing & Certification Center

TEL : +886 3 4244445
FAX : +886 3 4202444
ADDR. : No. 99, Dianyuan Rd., Yang-Mei city, Taoyuan,
Taiwan, R.O.C.
E-mail: mhko@cht.com.tw <http://www.chttl.com.tw>

Report No : TSC-102-05-AP-12 (SAR)

Date of Issue : June 05, 2013



SAR Test Report

Device Under Test : Rugged Tablet PC

Model No. : ALGIZ 10X

Applicant : Handheld Group AB

This Test report applied to the tested sample only.

This report shall not be reproduced in part without prior written permission of
Telecommunication Laboratories Testing & Certification Center, Chunghwa
Telecom Co., Ltd.



Report No : TSC-102-05-AP-12 (SAR)

Applicant : Handheld Group AB
TEL. : 46-510-547170
Addr. : Kinnegatan 17, 53133, Lidköping, Sweden

Device Under Test : Rugged Tablet PC
Trade name : Handheld
Model No. : ALGIZ 10X
Manufacturer : WINMATE Communication INC.

Applied Date : May 15, 2013

Date of Sample Arrived : May 15, 2013

Date of Finished : May 23, 2013

Applied standard : IEEE 1528 2003, 47 CFR §2.1093, OET 65 Supplement C 01-01
 Industry Canada RSS-210




Cited Document : KDB 447498, 450824, 616217, 248227, 616217, 648474, 941225,
 FCC DA02-1438,

Test Equipment : Refer to page 31

Test Environment : 24°C, 55 % R.H.

Test results : IEEE 1528 2003 Complied

SAR 1g = **1.115** W/kg (Maximum), Refer to page 36

Approved by	Reviewed by	Test Engineer
 Ko Ming-Hong	 Chia-cheng Chang	 Shin-yen Du

Report No : TSC-102-05-AP-12 (SAR)

TABLE OF CONTENTS

1. GENERAL INFORMATION	4
1.1 EUT DESCRIPTION	4
1.2 TEST ENVIRONMENT	4
2. SAR MEASUREMENT SYSTEM	5
2.1 ALSAS-10U SYSTEM DESCRIPTION	5
2.2 ISOTROPIC E-FIELD PROBE	6
2.3 BOUNDARY DETECTION UNIT AND PROBE MOUNTING DEVICE	8
2.4 DAQ-PAQ (ANALOG TO DIGITAL ELECTRONICS)	8
2.5 AXIS ARTICULATED ROBOT	8
2.6 ALSAS UNIVERSAL WORKSTATION	9
2.7 PHANTOM TYPES	9
3. TISSUE SIMULATING LIQUID.....	10
3.1 THE COMPOSITION OF THE TISSUE SIMULATING LIQUID	10
3.2 TISSUE CALIBRATION RESULT	10
3.3 TISSUE DIELECTRIC PARAMETERS FOR HEAD AND BODY PHANTOMS.....	12
4. SAR MEASUREMENT PROCEDURE	13
4.1 SAR SYSTEM VALIDATION	13
4.2 ARRANGEMENT ASSESSMENT SETUP	28
4.3 SAR MEASUREMENT PROCEDURE	28
5. SAR EXPOSURE LIMITS	29
6. TEST EQUIPMENT LIST.....	30
7. MEASUREMENT UNCERTAINTY	31
8 SAR TEST RESULTS	32
9. EUT PHOTOGRAPHS	38
A. TEST CONFIGURATIONS AND TEST DATA	42
A.1 TEST CONFIGURATION.....	42
A.2 LIQUID LEVEL PHOTO.....	48
A.3 TISSUE LIQUIDS DIELECTRIC PARAMETER.....	49
A.3.1 2450 MHz TISSUE LIQUIDS DIELECTRIC MEASUREMENT DATA	49
A.3.2 850 MHz TISSUE LIQUIDS DIELECTRIC MEASUREMENT DATA	49
A.3.3 1900 MHz TISSUE LIQUIDS DIELECTRIC MEASUREMENT DATA	49
A.4. TEST DATA	50
A.4.1 802.11B MODE	50
A.4.2 GPRS MODE	62
A.4.3 WCDMA MODE.....	98
A.4.4 CDMA2000 MODE	134



Report No : TSC-102-05-AP-12 (SAR)

A. 4.5 DIPOLE CALIBRATION DATA	170
A. 4.6 PROBE CALIBRATION DATA	178

Report No : TSC-102-05-AP-12 (SAR)

1. General Information

1.1 EUT Description

Product Name	Rugged Tablet PC
Trade Name	Handheld
Model No.	ALGIZ 10X
Operation Frequency	GPRS/EGPRS850, WCDMA Band 5 CDMA2000 BC0, U/L 824-849MHz, D/L 869-894 MHz; GPRS/EGPRS1900, WCDMA Band 2 CDMA2000 BC1, U/L 1850-1910MHz, D/L 1930-1990 MHz; WiFi and Bluetooth 2402-2483MHz
FCC ID	YY3-ALGIZ10X
Antenna Type	INTERNAL(WLAN/Bluetooth Antenna Gain: 2dBi ; Mobile Antenna Gain: 2dBi)
Device Category	Portable
Battery	T-GEE, ALG10X-08A, Rating:DC7.4V, 5300mAh, 39.22Whr
WLAN Module	WPEA-152GN(BT)
Mobile Module	Sierra MC 8355
RF Exposure Environment	Uncontrolled
Output Power (Conducted)	Please refer to P.33

1.2 Test Environment

Ambient conditions in the laboratory:

Items	Required	Actual
Temperature (°C)	24	See first page
Humidity (%RH)	55	See first page

Report No : TSC-102-05-AP-12 (SAR)

2. SAR Measurement System

2.1 ALSAS-10U System Description

ALSAS-10-U is fully compliant with the technical and scientific requirements of IEEE 1528, IEC 62209, EN50361, CENELEC, ARIB, ACA, and the Federal Communications Commission. The system comprises of a six axes articulated robot which utilizes a dedicated controller. ALSAS-10U uses the latest methodologies and FDTD modeling to provide a platform which is repeatable with minimum uncertainty.

2.1.1 Applications

Predefined measurement procedures compliant with the guidelines of CENELEC, IEEE, IEC, FCC, etc are utilized during the assessment for the device. Automatic detection for all SAR maximum are embedded within the core architecture for the system, ensuring that peak locations used for centering the zoom scan are within a 1mm resolution and a 0.05mm repeatable position. System operation range currently available up-to 6 GHz in simulated tissue.

2.1.2 Area Scans

Area scans are defined prior to the measurement process being executed with a user defined variable spacing between each measurement point (integral) allowing low uncertainty measurements to be conducted. Scans defined for FCC applications utilize a 10mm² step integral, with 1mm interpolation used to locate the peak SAR area used for zoom scan assessments.

Where the system identifies multiple SAR peaks (which are within 25% of peak value) the system will provide the user with the option of assessing each peak location individually for zoom scan averaging.



Report No : TSC-102-05-AP-12 (SAR)

2.1.3 Zoom Scan (Cube Scan Averaging)

The averaging zoom scan volume utilized in the ALSAS-10U software is in the shape of a cube and the side dimension of a 1 g or 10 g mass is dependent on the density of the liquid representing the simulated tissue. A density of 1000 kg/m³ is used to represent the head and body tissue density and not the phantom liquid density, in order to be consistent with the definition of the liquid dielectric properties, i.e. the side length of the 1 g cube is 10mm, with the side length of the 10 g cube 21,5mm.

When the cube intersects with the surface of the phantom, it is oriented so that 3 vertices touch the surface of the shell or the center of a face is tangent to the surface. The face of the cube closest to the surface is modified in order to conform to the tangent surface.

The zoom scan integer steps can be user defined so as to reduce uncertainty, but normal practice for typical test applications (including FCC) utilize a physical step of 7x7x7 (5mmx5mmx5mm) providing a volume of 30mm in the X & Y axis, and 30mm in the Z axis.

2.1.4 ALSAS-10U Interpolation and Extrapolation Uncertainty

The overall uncertainty for the methodology and algorithms the used during the SAR calculation was evaluated using the data from IEEE 1528 based on the example f3 algorithm:

$$f_3(x, y, z) = A \frac{a^2}{\frac{a^2}{4} + x'^2 + y'^2} \cdot \left(e^{-\frac{2z}{a}} + \frac{a^2}{2(a + 2z)^2} \right)$$


2.2 Isotropic E-Field Probe

The isotropic E-Field probe has been fully calibrated and assessed for isotropicity, and boundary effect within a controlled environment. Depending on the frequency for which the probe is calibrated the method utilized for calibration will change. A number of methods is used for calibrating probes, and these are outlined in the table below:

Calibration Frequency	Air Calibration	Tissue Calibration
2450MHz	TEM Cell	Temperature

The E-Field probe utilizes a triangular sensor arrangement as detailed in the diagram below:

Report No : TSC-102-05-AP-12 (SAR)



SAR is assessed with a calibrated probe which moves at a default height of 5mm from the center of the diode, which is mounted to the sensor, to the phantom surface (in the Z Axis). The 5mm offset height has been selected so as to minimize any resultant boundary effect due to the probe being in close proximity to the phantom surface.

The following algorithm is an example of the function used by the system for linearization of the output from the probe when measuring complex modulation schemes.

$$V_i = U_i + U_i^2 \cdot \frac{cf}{dcp_i}$$

2.2.1 Isotropic E-Field Probe Specification

Calibration in Air	Frequency Dependent Below 2GHz Calibration in air performed in a TEM Cell Above 2GHz Calibration in air performed in waveguide
Sensitivity	0.70 $\mu\text{V}/(\text{V}/\text{m})^2$ to 0.85 $\mu\text{V}/(\text{V}/\text{m})^2$
Dynamic Range	0.0005 W/kg to 100W/kg
Isotropic Response	Better than 0.2dB
Diode Compression point (DCP)	Calibration for Specific Frequency
Probe Tip Radius	< 5mm
Sensor Offset	1.56 (+/- 0.02mm)
Probe Length	290mm
Video Bandwidth	@ 500 Hz: 1dB @1.02 KHz: 3dB
Boundary Effect	Less than 2% for distance greater than 2.4mm
Spatial Resolution	Diameter less than 5mm Compliant with Standards

Report No : TSC-102-05-AP-12 (SAR)

2.3 Boundary Detection Unit and Probe Mounting Device

ALSAS-10U incorporates a boundary detection unit with a sensitivity of 0.05mm for detecting all types of surfaces. The robust design allows for detection during probe tilt (probe normalize) exercises, and utilizes a second stage emergency stop. The signal electronics are fed directly into the robot controller for high accuracy surface detection in lateral and axial detection modes (X, Y, & Z).

The probe is mounted directly onto the Boundary Detection unit for accurate tooling and displacement calculations controlled by the robot kinematics. The probe is connect to an isolated probe interconnect where the output stage of the probe is fed directly into the amplifier stage of the Daq-Paq

2.4 Daq-Paq (Analog to Digital Electronics)

ALSAS-10U incorporates a fully calibrated Daq-Paq (analog to digital conversion system) which has a 4 channel input stage, sent via a 2 stage auto-set amplifier module. The input signal is amplified accordingly so as to offer a dynamic range from 5µV to 800mV. Integration of the fields measured is carried out at board level utilizing a Co-Processor which then sends the measured fields down into the main computational module in digitized form via an RS232 communications port. Probe linearity and duty cycle compensation is carried out within the main Daq-Paq module.

ADC	12 Bit
Amplifier Range	20mV to 200mV and 150mV to 800mV
Field Integration	Local Co-Processor utilizing proprietary integration algorithms
Number of Input Channels	4 in total 3 dedicated and 1 spare
Communication	Packet data via RS232

2.5 Axis Articulated Robot



ALSAS-10U utilizes a six axis articulated robot, which is controlled using a Pentium based real-time movement controller. The movement kinematics engine utilizes proprietary (Thermo CRS) interpolation and extrapolation algorithms, which allow full freedom of movement for each of the six joints within the working envelope. Utilization of joint 6 allows for full probe rotation with a tolerance better than 0.05mm around the central axis.

Robot/Controller Manufacturer	Thermo CRS
Number of Axis	Six independently controlled axis
Positioning Repeatability	0.05mm
Controller Type	Single phase Pentium based C500C
Robot Reach	710mm
Communication	RS232 and LAN compatible

Report No : TSC-102-05-AP-12 (SAR)

2.6 ALSAS Universal Workstation

ALSAS Universal workstation allows for repeatability and fast adaptability. It allows users to do calibration, testing and measurements using different types of phantoms with one set up, which significantly speeds up the measurement process.

2.7 Phantom Types

The ALSAS-10U allows the integration of multiple phantom types. SAM Phantoms fully compliant with IEEE 1528, EN50361 Universal Phantom, and Universal Flat.

2.7.1 APREL Laboratories Universal Phantom

The Universal Phantom is used on the ALSAS-10U as a system validation phantom. The Universal Phantom has been fully validated both experimentally from 800MHz to 6GHz and numerically using XFDTD numerical software. The shell thickness is 2mm overall, with a 4mm spacer located at the NF/MB intersection providing an overall thickness of 6mm in line with the requirements of IEEE-1528.

The design allows for fast and accurate measurements, of handsets, by allowing the conservative SAR to be evaluated at on frequency for both left and right head experiments in one measurement.



Report No : TSC-102-05-AP-12 (SAR)

3. Tissue Simulating Liquid

3.1 The composition of the tissue simulating liquid

INGREDIENT (% Weight)	900MHz Head	850MHz Body	1900MHz Head	1900MHz Body	2450MHz Head	2450MHz Body
Water	40.92%	53.92%	52.64%	68.64%	73.2	70.2
Salt	1.48%	0.98%	0.36%	0.36%	0.04	0.1
Sugar	56.5%	44.5%	0%	0%	0%	0%
HEC	0.40%	1%	0%	0%	0%	0%
Preventol	0.10%	0.10%	0%	0%	0%	0%
DGBE	0%	0%	47.0%	31.0%	26.7%	29.7%

3.2 Tissue Calibration Result

The dielectric parameters of the liquids were verified prior to the SAR evaluation using APREL Dielectric Probe Kit and Anritsu MS4623B Vector Network Analyzer

Head Tissue Simulant Measurement				Oct. 18 2012	
Frequency [MHz]	Description	Dielectric Parameters		Tissue Temp. [°C]	
		ϵ_r	σ [s/m]		
900 MHz	Reference result $\pm 5\%$ window	41.5 $\pm 5\%$	0.97 $\pm 5\%$	N/A	
	Measured	41.7	0.96	23.0	
Body Tissue Simulant Measurement				May. 17 2013	
Frequency [MHz]	Description	Dielectric Parameters		Tissue Temp. [°C]	
		ϵ_r	σ [s/m]		
835 MHz	Reference result $\pm 5\%$ window	55.2 $\pm 5\%$	0.97 $\pm 5\%$	N/A	
	Measured	53.0	0.99	24.0	

Report No : TSC-102-05-AP-12 (SAR)

Head Tissue Simulant Measurement				Oct. 24 2012
Frequency [MHz]	Description	Dielectric Parameters		Tissue Temp. [°C]
		ϵ_r	σ [s/m]	
1900 MHz	Reference result $\pm 5\%$ window	$40.0 \pm 5\%$	$1.40 \pm 5\%$	N/A
		39.5	1.41	23.0
Body Tissue Simulant Measurement				May 15 2013
Frequency [MHz]	Description	Dielectric Parameters		Tissue Temp. [°C]
		ϵ_r	σ [s/m]	
1900 MHz	Reference result $\pm 5\%$ window	$53.3 \pm 5\%$	$1.52 \pm 5\%$	N/A
		52.8	1.48	24.0

Head Tissue Simulant Measurement				Oct. 18 2012
Frequency [MHz]	Description	Dielectric Parameters		Tissue Temp. [°C]
		ϵ_r	σ [s/m]	
2450 MHz	Reference result $\pm 5\%$ window	$39.2 \pm 5\%$	$1.80 \pm 5\%$	N/A
		39.5	1.81	23.0
Body Tissue Simulant Measurement				May 23 2013
Frequency [MHz]	Description	Dielectric Parameters		Tissue Temp. [°C]
		ϵ_r	σ [s/m]	
2450 MHz	Reference result $\pm 5\%$ window	$52.7 \pm 5\%$	$1.95 \pm 5\%$	N/A
		53.1	1.99	24.0

Report No : TSC-102-05-AP-12 (SAR)

3.3 Tissue Dielectric Parameters for Head and Body Phantoms

The head tissue dielectric parameters recommended by the IEEE SCC-34/SC-2 in P1528 have been incorporated in the following table. These head parameters are derived from planar layer models simulating the highest expected SAR for the dielectric properties and tissue thickness variations in a human head. Other head and body tissue parameters that have not been specified in P1528 are derived from the tissue dielectric parameters computed from the 4-Cole-Cole equations described in Reference [12] and extrapolated according to the head parameters specified in P1528.

Target Frequency (MHz)	Head		Body	
	ϵ_r	σ (S/m)	ϵ_r	σ (S/m)
150	52.3	0.76	61.9	0.80
300	45.3	0.87	58.2	0.92
450	43.5	0.87	56.7	0.94
835	41.5	0.90	55.2	0.97
900	41.5	0.97	55.0	1.05
915	41.5	0.98	55.0	1.06
1450	40.5	1.20	54.0	1.30
1610	40.3	1.29	53.8	1.40
1800 – 2000	40.0	1.40	53.3	1.52
2450	39.2	1.80	52.7	1.95
3000	38.5	2.40	52.0	2.73
5800	35.3	5.27	48.2	6.00


(ϵ_r = relative permittivity, σ = conductivity and $\rho = 1000 \text{ kg/m}^3$)

Report No : TSC-102-05-AP-12 (SAR)

4. SAR Measurement Procedure

4.1 SAR System Validation

4.1.1 Validation Dipoles



The dipoles used is based on the IEEE-1528 standard, and is complied with mechanical and electrical specifications in line with the requirements of both IEEE and FCC Supplement C. the table below provides details for the mechanical and electrical specifications for the dipoles.

Frequency	L (mm)	h (mm)
900 MHz	149	83.9
1900 MHz	68	39.5
2450MHz	51.5	30.4

4.1.2 Validation Result

Frequency (MHz)	Power	SAR _{1g} (mw/g)	Power Drift (%)	Date
900	1 W	10.8	-	Oct. 18 2010
	500mW	5.58	4.438	Oct. 24 2012
	Normalize to 1 W	11.16		
1900	1 W	39.7	-	Oct. 18 2010
	250mW	9.587	-2.901	Oct. 18 2012
	Normalize to 1 W	38.35		
2450	1 W	52.4	-	Nov. 10 2012
	500mW	26.015	-2.336	Oct. 18 2012
	Normalize to 1 W	52.03		

Report No : TSC-102-05-AP-12 (SAR)

835MHz System validation
SAR Test Report

Report Date : 24-Oct-2012
By Operator : 123
Measurement Date : 24-Oct-2012
Starting Time : 24-Oct-2012 03:32:47 PM
End Time : 24-Oct-2012 03:55:28 PM
Scanning Time : 1361 secs

Product Data
Device Name : validation
Serial No. : 123
Type : Dipole
Model : 900
Frequency : 900.00 MHz
Max. Transmit Pwr : 1 W
Drift Time : 0 min(s)
Length : 2 mm
Width : 161 mm
Depth : 1 mm
Antenna Type : Internal
Orientation : Rotated Left 90°
Power Drift-Start : 5.581 W/kg
Power Drift-Finish: 5.829 W/kg
Power Drift (%) : 4.438
Picture :

Phantom Data
Name : APREL-Uni
Type : Uni-Phantom
Size (mm) : 280 x 280 x 200
Serial No. : User Define
Location : Center
Description : Uni_Phantom

Tissue Data
Type : HEAD
Serial No. : 900
Frequency : 900.00 MHz
Last Calib. Date : 24-Oct-2012
Temperature : 23.00 °C
Ambient Temp. : 23.00 °C
Humidity : 50.00 RH%
Epsilon : 41.70 F/m
Sigma : 0.96 S/m
Density : 1000.00 kg/cu. M
Probe Data
Name : Probe 255
Model : E020
Type : E-Field Triangle
Serial No. : 255

Report No : TSC-102-05-AP-12 (SAR)
Last Calib. Date : 06-Dec-2011
Frequency : 900.00 MHz
Duty Cycle Factor: 1
Conversion Factor: 6.8
Probe Sensitivity: 1.20 1.20 1.20 $\mu\text{V}/(\text{V}/\text{m})^2$
Compression Point: 95.00 mV
Offset : 1.56 mm


Measurement Data

Crest Factor : 1
Scan Type : Complete
Tissue Temp. : 23.00 °C
Ambient Temp. : 23.00 °C
Set-up Date : 24-Oct-2012
Set-up Time : 2:37:02 PM
Area Scan : 4x12x1 : Measurement x=15mm, y=15mm, z=4mm
Zoom Scan : 5x5x8 : Measurement x=8mm, y=8mm, z=4mm

Other Data

DUT Position : Rotated Left 90°
Separation : 0
Channel : Mid

Report No : TSC-102-05-AP-12 (SAR)



1 gram SAR value : 5.225 W/kg
 Area Scan Peak SAR : 4.614 W/kg
 Zoom Scan Peak SAR : 9.138 W/kg

Exposure Assessment Measurement Uncertainty


Source of Uncertainty	Tolerance Value	Probability Distribution	Divisor	c_i^{-1} (1-g)	Standard Uncertainty (1-g) %
Measurement System					
Probe Calibration	3.5	normal	1	1	3.5
Axial Isotropy	3.7	rectangular	$\sqrt{3}$	$(1-cp)^{1/2}$	1.5
Hemispherical Isotropy	10.9	rectangular	$\sqrt{3}$	\sqrt{cp}	4.4
Boundary Effect	1.0	rectangular	$\sqrt{3}$	1	0.6
Linearity	4.7	rectangular	$\sqrt{3}$	1	2.7
Detection Limit	1.0	rectangular	$\sqrt{3}$	1	0.6
Readout Electronics	1.0	normal	1	1	1.0
Response Time	0.8	rectangular	$\sqrt{3}$	1	0.5
Integration Time	1.7	rectangular	$\sqrt{3}$	1	1.0
RF Ambient Condition	3.0	rectangular	$\sqrt{3}$	1	1.7
Probe Positioner	0.4	rectangular	$\sqrt{3}$	1	0.2

Report No : TSC-102-05-AP-12 (SAR)

Mech.					
Restriction					
Probe Positioning with respect to Phantom Shell	2.9	rectangular	$\sqrt{3}$	1	1.7
Extrapolation and Integration	3.7	rectangular	$\sqrt{3}$	1	2.1
Test Sample Positioning	4.0	normal	1	1	4.0
Device Holder Uncertainty	2.0	normal	1	1	2.0
Drift of Output Power	4.4	rectangular	$\sqrt{3}$	1	2.6
Phantom and Setup					
Phantom Uncertainty(shape & thickness tolerance)	3.4	rectangular	$\sqrt{3}$	1	2.0
Liquid Conductivity(target)	5.0	rectangular	$\sqrt{3}$	0.7	2.0
Liquid Conductivity(meas.)	0.0	normal	1	0.7	0.0
Liquid Permittivity(target)	5.0	rectangular	$\sqrt{3}$	0.6	1.7
Liquid Permittivity(meas.)	0.5	normal	1	0.6	0.3
Combined Uncertainty		RSS			9.6
Combined Uncertainty (coverage factor=2)		Normal(k=2)			19.2

Report No : TSC-102-05-AP-12 (SAR)

SAR-Z Axis
at Hotspot x:1.08 y:0.76



Report No : TSC-102-05-AP-12 (SAR)

1900MHz System validation

SAR Test Report

Report Date : 18-Oct-2012
By Operator : 123
Measurement Date : 18-Oct-2012
Starting Time : 18-Oct-2012 04:30:47 PM
End Time : 18-Oct-2012 04:50:43 PM
Scanning Time : 1196 secs

Product Data

Device Name : validation
Serial No. : 123
Type : Dipole
Model : 1900
Frequency : 1900.00 MHz
Max. Transmit Pwr : 1 W
Drift Time : 0 min(s)
Length : 2 mm
Width : 68 mm
Depth : 1 mm
Antenna Type : Internal
Orientation : Rotated Left 90°
Power Drift-Start : 10.671 W/kg
Power Drift-Finish: 10.361 W/kg
Power Drift (%) : -2.901
Picture :

Phantom Data

Name : APREL-Uni
Type : Uni-Phantom
Size (mm) : 280 x 280 x 200
Serial No. : User Define
Location : Center
Description : Uni_Phantom

Tissue Data

Type : HEAD
Serial No. : 1900
Frequency : 1900.00 MHz
Last Calib. Date : 18-Oct-2012
Temperature : 23.00 °C
Ambient Temp. : 23.00 °C
Humidity : 50.00 RH%
Epsilon : 39.50 F/m
Sigma : 1.41 S/m
Density : 1000.00 kg/cu. M

Probe Data

Name : Probe 255
Model : E020

Report No : TSC-102-05-AP-12 (SAR)


Type : E-Field Triangle
 Serial No. : 255
 Last Calib. Date : 06-Dec-2011
 Frequency : 1900.00 MHz
 Duty Cycle Factor: 1
 Conversion Factor: 5.8
 Probe Sensitivity: 1.20 1.20 1.20 $\mu\text{V}/(\text{V}/\text{m})^2$
 Compression Point: 95.00 mV
 Offset : 1.56 mm

Measurement Data

Crest Factor : 1
 Scan Type : Complete
 Tissue Temp. : 23.00 °C
 Ambient Temp. : 23.00 °C
 Set-up Date : 18-Oct-2012
 Set-up Time : 3:05:01 PM
 Area Scan : 5x7x1 : Measurement x=15mm, y=15mm, z=4mm
 Zoom Scan : 5x5x8 : Measurement x=8mm, y=8mm, z=4mm

Other Data

DUT Position : Rotated Left 90°
 Separation : 0
 Channel : Mid



1 gram SAR value : 9.587 W/kg
 Area Scan Peak SAR : 10.670 W/kg
 Zoom Scan Peak SAR : 18.916 W/kg


Report No : TSC-102-05-AP-12 (SAR)

Exposure Assessment Measurement Uncertainty

Source of Uncertainty	Tolerance Value	Probability Distribution	Divisor	c_i^{-1} (1-g)	Standard Uncertainty (1-g) %
Measurement System					
Probe Calibration	3.5	normal	1	1	3.5
Axial Isotropy	3.7	rectangular	$\sqrt{3}$	$(1-cp)^{1/2}$	1.5
Hemispherical Isotropy	10.9	rectangular	$\sqrt{3}$	\sqrt{cp}	4.4
Boundary Effect	1.0	rectangular	$\sqrt{3}$	1	0.6
Linearity	4.7	rectangular	$\sqrt{3}$	1	2.7
Detection Limit	1.0	rectangular	$\sqrt{3}$	1	0.6
Readout Electronics	1.0	normal	1	1	1.0
Response Time	0.8	rectangular	$\sqrt{3}$	1	0.5
Integration Time	1.7	rectangular	$\sqrt{3}$	1	1.0
RF Ambient Condition	3.0	rectangular	$\sqrt{3}$	1	1.7
Probe Positioner Mech.	0.4	rectangular	$\sqrt{3}$	1	0.2
Restriction					
Probe Positioning with respect to Phantom Shell	2.9	rectangular	$\sqrt{3}$	1	1.7
Extrapolation and Integration	3.7	rectangular	$\sqrt{3}$	1	2.1
Test Sample Positioning	4.0	normal	1	1	4.0
Device Holder Uncertainty	2.0	normal	1	1	2.0
Drift of Output Power	2.9	rectangular	$\sqrt{3}$	1	1.7
Phantom and Setup					
Phantom Uncertainty(shape & thickness tolerance)	3.4	rectangular	$\sqrt{3}$	1	2.0
Liquid Conductivity(target)	5.0	rectangular	$\sqrt{3}$	0.7	2.0
Liquid Conductivity(meas.)	0.7	normal	1	0.7	0.5
Liquid Permittivity(target)	5.0	rectangular	$\sqrt{3}$	0.6	1.7
Liquid Permittivity(meas.)	1.3	normal	1	0.6	0.8
Combined Uncertainty		RSS			9.4
Combined Uncertainty (coverage factor=2)		Normal(k=2)			18.9

Report No : TSC-102-05-AP-12 (SAR)

SAR-Z Axis
at Hotspot x:0.09 y:-0.24



Report No : TSC-102-05-AP-12 (SAR)

2450MHz System validation
SAR Test Report

Report Date : 18-Oct-2012
By Operator : 123
Measurement Date : 18-Oct-2012
Starting Time : 18-Oct-2012 11:55:08 AM
End Time : 18-Oct-2012 12:12:29 PM
Scanning Time : 1041 secs

Product Data
Device Name : validation
Serial No. : 123
Type : Other
Model : 2450
Frequency : 2450.00 MHz
Max. Transmit Pwr : 1 W
Drift Time : 0 min(s)
Length : 45 mm
Width : 3 mm
Depth : 2 mm
Antenna Type : Internal
Orientation : Rotated Left 90°
Power Drift-Start : 24.552 W/kg
Power Drift-Finish: 23.978 W/kg
Power Drift (%) : -2.336
Picture :

Phantom Data
Name : APREL-Uni
Type : Uni-Phantom
Size (mm) : 280 x 280 x 200
Serial No. : User Define
Location : Center
Description : Uni_Phantom

Tissue Data
Type : HEAD
Serial No. : 2450
Frequency : 2450.00 MHz
Last Calib. Date : 18-Oct-2012
Temperature : 24.00 °C
Ambient Temp. : 24.00 °C
Humidity : 50.00 RH%
Epsilon : 39.50 F/m
Sigma : 1.81 S/m
Density : 1000.00 kg/cu. M
Probe Data
Name : Probe 255
Model : E020
Type : E-Field Triangle
Serial No. : 255

Report No : TSC-102-05-AP-12 (SAR)

Last Calib. Date : 06-Dec-2011

Frequency : 2450.00 MHz

Duty Cycle Factor: 1

Conversion Factor: 4.7

Probe Sensitivity: 1.20 1.20 1.20 $\mu\text{V}/(\text{V}/\text{m})^2$

Compression Point: 95.00 mV

Offset : 1.56 mm

Measurement Data

Crest Factor : 1

Scan Type : Complete

Tissue Temp. : 24.00 °C

Ambient Temp. : 24.00 °C

Set-up Date : 18-Oct-2012

Set-up Time : 11:54:51 AM

Area Scan : 4x6x1 : Measurement x=15mm, y=15mm, z=4mm

Zoom Scan : 5x5x8 : Measurement x=8mm, y=8mm, z=4mm


Other Data

DUT Position : Rotated Left 90°

Separation : 0

Channel : Mid

Report No : TSC-102-05-AP-12 (SAR)



1 gram SAR value : 26.015 W/kg
Area Scan Peak SAR : 23.056 W/kg
Zoom Scan Peak SAR : 52.745 W/kg


Report No : TSC-102-05-AP-12 (SAR)

Exposure Assessment Measurement Uncertainty

Source of Uncertainty	Tolerance Value	Probability Distribution	Divisor	c_i^{-1} (1-g)	Standard Uncertainty (1-g) %
Measurement System					
Probe Calibration	3.5	normal	1	1	3.5
Axial Isotropy	3.7	rectangular	$\sqrt{3}$	$(1-cp)^{1/2}$	1.5
Hemispherical Isotropy	10.9	rectangular	$\sqrt{3}$	\sqrt{cp}	4.4
Boundary Effect	1.0	rectangular	$\sqrt{3}$	1	0.6
Linearity	4.7	rectangular	$\sqrt{3}$	1	2.7
Detection Limit	1.0	rectangular	$\sqrt{3}$	1	0.6
Readout Electronics	1.0	normal	1	1	1.0
Response Time	0.8	rectangular	$\sqrt{3}$	1	0.5
Integration Time	1.7	rectangular	$\sqrt{3}$	1	1.0
RF Ambient Condition	3.0	rectangular	$\sqrt{3}$	1	1.7
Probe Positioner Mech.	0.4	rectangular	$\sqrt{3}$	1	0.2
Restriction					
Probe Positioning with respect to Phantom Shell	2.9	rectangular	$\sqrt{3}$	1	1.7
Extrapolation and Integration	3.7	rectangular	$\sqrt{3}$	1	2.1
Test Sample Positioning	4.0	normal	1	1	4.0
Device Holder Uncertainty	2.0	normal	1	1	2.0
Drift of Output Power	2.3	rectangular	$\sqrt{3}$	1	1.3
Phantom and Setup					
Phantom Uncertainty(shape & thickness tolerance)	3.4	rectangular	$\sqrt{3}$	1	2.0
Liquid Conductivity(target)	5.0	rectangular	$\sqrt{3}$	0.7	2.0
Liquid Conductivity(meas.)	0.6	normal	1	0.7	0.4
Liquid Permittivity(target)	5.0	rectangular	$\sqrt{3}$	0.6	1.7
Liquid Permittivity(meas.)	0.8	normal	1	0.6	0.5
Combined Uncertainty		RSS			9.3
Combined Uncertainty (coverage factor=2)		Normal(k=2)			18.7

Report No : TSC-102-05-AP-12 (SAR)

SAR-Z Axis
at Hotspot x:1.10 y:0.76



Report No : TSC-102-05-AP-12 (SAR)

4.2 Arrangement Assessment Setup

4.2.1 Test Positions for body-worn

Body-worn operating configurations should be tested with the belt-clips and holsters attached to the device and positioned against a flat phantom in normal use configurations. A separation distance of 1.5 cm between the back of the device and a flat phantom is recommended for testing body-worn SAR compliance under such circumstances. Other separation distance may be use, but not exceed 2.5 cm.

4.3 SAR Measurement Procedure

The ALSAS-10U calculates SAR using the following equation,

$$SAR = \frac{\sigma |E|^2}{\rho}$$

σ : represents the simulated tissue conductivity

ρ : represents the tissue density

The EUT is set to transmit at the required power in line with product specification, at each frequency relating to the LOW, MID, and HIGH channel settings.

Pre-scans are made on the device to establish the location for the transmitting antenna, using a large area scan in either air or tissue simulation fluid.

The EUT is placed against the Universal Phantom where the maximum area scan dimensions are larger than the physical size of the resonating antenna. When the scan size is not large enough to cover the peak SAR distribution, it is modified by either extending the area scan size in both the X and Y directions, or the device is shifted within the predefined area.

The area scan is then run to establish the peak SAR location (interpolated resolution set at 1mm²) which is then used to orient the center of the zoom scan. The zoom scan is then executed and the 1g and 10g averages are derived from the zoom scan volume (interpolated resolution set at 1mm³).

Report No : TSC-102-05-AP-12 (SAR)

5. SAR Exposure Limits

SAR assessments have been made in line with the requirements of IEEE-1528, FCC Supplement C, and comply with ANSI/IEEE C95.1-1992 "Uncontrolled Environments" limits. These limits apply to a location which is deemed as "Uncontrolled Environment" which can be described as a situation where the general public may be exposed to an RF source with no prior knowledge or control over their exposure.

Limits for General Population/Uncontrolled Exposure (W/kg)

Type Exposure	Uncontrolled Environment Limit
Spatial Peak SAR (1g cube tissue for brain or body)	1.60 W/kg
Spatial Average SAR (whole body)	0.08 W/kg
Spatial Peak SAR (10g for hands, feet, ankles and wrist)	4.00 W/kg

Report No : TSC-102-05-AP-12 (SAR)

6. Test Equipment List

Instrument	Manufacturer	Model No.	Calibration Due	Calibration Cycle(year)
Data Acquisition Package	Apral	ALS-DAQ-PAQ-2	NCR	NCR
Apral Laboratories Probe	Apral	ALS-E020(257)	13-Nov-2013	1
*Apral Laboratories Dipole	Apral	ALS-D-900-S-2	18-Oct-2013	3
*Apral Laboratories Dipole	Apral	ALS-D-1900-S-2	18-Oct-2013	3
*Apral Laboratories Dipole	Apral	ALS-D-2450-S-2	13-Nov-2015	3
Boundary Detection Sensor System	Apral	ALS-PMDPS-2	NCR	NCR
Dielectric Probe Kit	Apral	ALS-PR-DIEL	NCR	NCR
Universal Work Station	Apral	ALS-UWS	NCR	NCR
Device Holder 2.0	Apral	ALS-H-E-SET-2	NCR	NCR
Left Ear SAM Phantom	Apral	ALS-P-SAM-L	NCR	NCR
Right Ear SAM Phantom	Apral	ALS-P-SAM-R	NCR	NCR
Flat Phantom	Apral	ALS-P-UP-1	NCR	NCR
Apral Dipole Spacer	Apral	ALS-DS-U	NCR	NCR
SAR Software	Apral	ALSAS-10	NCR	NCR
CRS C500C Controller	Thermo	ALS-C500	NCR	NCR
CRF F3 Robot	Thermo	ALS-F3	NCR	NCR
Power Amplifier	Mini-Circuit	ZHL-42	NCR	NCR
Directional Coupler	Agilent	778D-012	NCR	NCR
Power meter	HP	438A	May 25 2014	1
Vector S/G	R&S	SMU200A	May 11 2013	1
Wireless Communications Test Set	Agilent	8960	May 31 2014	1
Vector Network	Anritsu	MS4623B	May 17 2014	1

*The ALS-D-2450-S-2 dipole meet KDB 450824 requirements for the extended 3-year calibration interval. Please refer to P.163 and P.166 (return loss -25.451dB vs -29.4dB; impedance 46.2Ω vs 50.7Ω)

Report No : TSC-102-05-AP-12 (SAR)

7. Measurement Uncertainty

Source of Uncertainty	Tolerance Value	Probability Distribution	Divisor	c_i^{-1} (1-g)	Standard Uncertainty (1-g) %
Measurement System					
Probe Calibration	3.5	normal	1	1	3.5
Axial Isotropy	3.7	rectangular	$\sqrt{3}$	$(1-cp)^{1/2}$	1.5
Hemispherical Isotropy	10.9	rectangular	$\sqrt{3}$	\sqrt{cp}	4.4
Boundary Effect	1.0	rectangular	$\sqrt{3}$	1	0.6
Linearity	4.7	rectangular	$\sqrt{3}$	1	2.7
Detection Limit	1.0	rectangular	$\sqrt{3}$	1	0.6
Readout Electronics	1.0	normal	1	1	1.0
Response Time	0.8	rectangular	$\sqrt{3}$	1	0.5
Integration Time	1.7	rectangular	$\sqrt{3}$	1	1.0
RF Ambient Condition	3.0	rectangular	$\sqrt{3}$	1	1.7
Probe Positioner Mech.	0.4	rectangular	$\sqrt{3}$	1	0.2
Restriction					
Probe Positioning with respect to Phantom Shell	2.9	rectangular	$\sqrt{3}$	1	1.7
Extrapolation and Integration	3.7	rectangular	$\sqrt{3}$	1	2.1
Test Sample Positioning	4.0	normal	1	1	4.0
Device Holder Uncertainty	2.0	normal	1	1	2.0
Drift of Output Power	4.4	rectangular	$\sqrt{3}$	1	2.6
Phantom and Setup					
Phantom Uncertainty(shape & thickness tolerance)	3.4	rectangular	$\sqrt{3}$	1	2.0
Liquid Conductivity(target)	5.0	rectangular	$\sqrt{3}$	0.7	2.0
Liquid Conductivity(meas.)	0.0	normal	1	0.7	0.0
Liquid Permittivity(target)	5.0	rectangular	$\sqrt{3}$	0.6	1.7
Liquid Permittivity(meas.)	0.5	normal	1	0.6	0.3
Combined Uncertainty		RSS			9.6
Combined Uncertainty (coverage factor=2)		Normal(k=2)			19.2

Report No : TSC-102-05-AP-12 (SAR)

8 SAR Test Results

Conducted power measured(Mobile)

Mode	Channel	Output Power(dBm)
850MHz GPRS/EGPRS	128	32.2/32.1
	190	31.8/31.6
	251	32.0/31.9
1900MHz GPRS/EGPRS	512	28.6/28.5
	661	28.9/28.8
	810	28.9/28.7
WCBMA Band 5 WCDMA/HSUPA	4132	24.83/24.43
	4183	24.74/24.23
	4233	24.52/24.50
WCBMA Band 2 WCDMA/HSUPA	9262	24.07/24.13
	9400	24.70/24.77
	9538	24.40/24.49
CDMA2000 BC0 1X/EVDO	1013	23.32/23.50
	384	23.48/23.49
	777	23.71/23.59
CDMA2000 BC1 1X/EVDO	25	23.64/23.58
	600	23.84/23.72
	1175	23.52/23.50

This EUT use the same model of mobile module with TSC-101-10-AP-07.

Report No : TSC-102-05-AP-12 (SAR)

Conducted power measured(WiFi and Bluetooth)

Mode	Output Power
802.11b	17.3
802.11g	13.3
802.11n(HT20)	11.5
802.11n(HT40)	11.3
BT 1.0	2
BT 2.1+EDR	3.51
BT 3.0	3.79
BT 4.0	7.87

Report No : TSC-102-05-AP-12 (SAR)

SAR Measured(Mobile)

Test Position Body	Test Configuration	Frequency		Conducted Power (dBm)	SAR 1g (W/kg)	Power Drift %	Limit (W/kg)
		Channel	MHz	Max			
850MHz GPRS	Side Touch	128	824.20	32.2	0.368	-3.245	1.6
	Side Touch	190	836.60	31.8	0.403	-6.228	1.6
	Side Touch	251	848.80	32.0	0.398	4.015	1.6
1900MHz GPRS	Side Touch	512	1850.20	28.6	0.708	-4.290	1.6
	Side Touch	661	1880.00	28.9	0.765	-1.443	1.6
	Side Touch	810	1909.80	28.9	0.624	2.807	1.6

Report No : TSC-102-05-AP-12 (SAR)

Test Position Body	Test Configuration	Frequency		Conducted Power (dBm)	SAR 1g (W/kg)	Power Drift %	Limit (W/kg)
		Channel	MHz	Max			
WCBMA Band 5	Side Touch	4132	826.40	24.83	0.740	-4.132	1.6
	Side Touch	4182	836.40	24.74	0.743	0.309	1.6
	Side Touch	4233	846.60	24.52	0.746	0.232	1.6
WCBMA Band 2	Side Touch	9262	1852.40	24.07	1.014	4.960	1.6
	Side Touch	9400	1880.00	24.70	1.115	-5.484	1.6
	Side Touch	9538	1907.60	24.40	1.104	-7.895	1.6
	Front Touch	9400	1880.00	24.70	0.071	21.892	1.6
	Rear Touch	9400	1880.00	24.70	0.076	10.827	1.6

Note: Front Touch and Rear Touch test configuration were for evaluation only.

Report No : TSC-102-05-AP-12 (SAR)

Test Position Body	Test Configuration	Frequency		Conducted Power (dBm)	SAR 1g (W/kg)	Power Drift %	Limit (W/kg)
		Channel	MHz	Max			
CDMA2000 BC0 1X	Side Touch	1013	824.7	23.32	0.405	3.041	1.6
	Side Touch	384	836.52	23.48	0.421	2.556	1.6
	Side Touch	777	848.31	23.71	0.381	5.656	1.6
CDMA2000 BC1 1X	Side Touch	25	1851.25	23.64	0.408	0.391	1.6
	Side Touch	600	1880	23.84	0.520	-6.906	1.6
	Side Touch	1175	1908.75	23.52	0.491	-1.624	1.6

Report No : TSC-102-05-AP-12 (SAR)

SAR Measured(WiFi)

Test Position Body	Antenna Type	Frequency		SAR 1g (W/kg)	Power Drift %	Limit (W/kg)
		Channel	MHz			
802.11b_ Front	INTERNAL	1	2412	0.102	-4.337	1.6
802.11b_ Front	INTERNAL	6	2437	0.172	-4.218	1.6
802.11b_ Front	INTERNAL	11	2462	0.075	6.211	1.6
802.11b_ Side	INTERNAL	6	2437	0.095	-5.836	1.6
802.11b_ Rear	INTERNAL	6	2437	0.076	-8.950	1.6

Note:

1. The test signals (Tx power, Continuous mode and Channel) were Controlled by “RF test utility” which provides by Manufacturer during WiFi SAR testing.
2. Mobile and WiFi system can't use at the same time.
3. According to KDB 248227, SAR is not required for 802.11g channels when the maximum average output power is less than 1/4 dB higher than that measured on the corresponding 802.11b channels.
4. Some test cases power drift were > 5% , but the combined uncertainty (coverage factor=2) were < 30%.The test results was evaluated OK.
5. Bluetooth Conducted Maximum Output power ≤ 7.87 dBm. The MPE is compliant with the MPE limits of 1.1310.

1.1310 MPE Limits

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842/f	4.89/f	*(900/f ²)	6
30–300	61.4	0.163	1.0	6
300–1500	f/300	6
1500–100,000	5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500	f/1500	30
1500–100,000	1.0	30

f = frequency in MHz

* = Plane-wave equivalent power density

NOTE 1 TO TABLE 1: Occupational/controlled limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure. Limits for occupational/controlled exposure also apply in situations when an individual is transient through a location where occupational/controlled limits apply provided he or she is made aware of the potential for exposure.

NOTE 2 TO TABLE 1: General population/uncontrolled exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or can not exercise control over their exposure.

Report No : TSC-102-05-AP-12 (SAR)

9. EUT Photographs



Front View of EUT

Report No : TSC-102-05-AP-12 (SAR)




Rear View of EUT

Report No : TSC-102-05-AP-12 (SAR)



2G/3G Mobile Transmit Antenna Location

Report No : TSC-102-05-AP-12 (SAR)



WLAN Transmit Antenna Location

Report No : TSC-102-05-AP-12 (SAR)

A. TEST CONFIGURATIONS AND TEST DATA

A.1 TEST CONFIGURATION

WiFi Side Touch




Report No : TSC-102-05-AP-12 (SAR)

WiFi RearTouch



Report No : TSC-102-05-AP-12 (SAR)

WiFi Front Touch




Report No : TSC-102-05-AP-12 (SAR)

Mobile Side Touch




Report No : TSC-102-05-AP-12 (SAR)

Mobile Rear Touch



Report No : TSC-102-05-AP-12 (SAR)


Mobile Front Touch



Report No : TSC-102-05-AP-12 (SAR)

A.2 LIQUID LEVEL PHOTO

Liquid Level in Flat Phantom > 15cm



Report No : TSC-102-05-AP-12 (SAR)

A.3 TISSUE LIQUIDS Dielectric Parameter

A.3.1 2450 MHz TISSUE LIQUIDS Dielectric measurement data

Head Tissue

Tissue Data
Epsilon : 39.5 F/m
Sigma : 1.81 S/m

Body Tissue

Tissue Data
Epsilon : 53.1 F/m
Sigma : 1.99 S/m

A.3.2 850 MHz TISSUE LIQUIDS Dielectric measurement data

900MHz Head Tissue

Tissue Data
Epsilon : 41.7 F/m
Sigma : 0.96 S/m

850 MHz Body Tissue

Tissue Data
Epsilon : 53.0 F/m
Sigma : 0.99 S/m

A.3.3 1900 MHz TISSUE LIQUIDS Dielectric measurement data

Head Tissue

Tissue Data
Epsilon : 39.5 F/m
Sigma : 1.41 S/m

Body Tissue

Tissue Data
Epsilon : 52.8 F/m
Sigma : 1.48 S/m

Report No : TSC-102-05-AP-12 (SAR)

A.4. TEST DATA

A.4.1 802.11b Mode

Low Channel Front Touch

SAR Test Report

Report Date : 23-May-2013
By Operator : 123
Measurement Date : 23-May-2013
Starting Time : 23-May-2013 03:20:10 PM
End Time : 23-May-2013 03:43:19 PM
Scanning Time : 1389 secs

Product Data

Device Name : Winmate
Serial No. : ALGIZ 10X
Type : Other
Model : ALGIZ 10X
Frequency : 2400.00 MHz
Max. Transmit Pwr : 0.1 W
Drift Time : 0 min(s)
Length : 280 mm
Width : 175 mm
Depth : 36 mm
Antenna Type : Internal
Orientation : Touch
Power Drift-Start : 0.062 W/kg
Power Drift-Finish: 0.059 W/kg
Power Drift (%) : -4.337
Picture :

Phantom Data

Name : APREL-Uni
Type : Uni-Phantom
Size (mm) : 280 x 280 x 200
Serial No. : User Define
Location : Center
Description : Uni_Phantom

Tissue Data

Type : BODY
Serial No. : 2450
Frequency : 2450.00 MHz
Last Calib. Date : 23-May-2013
Temperature : 24.00 °C
Ambient Temp. : 24.00 °C
Humidity : 55.00 RH%
Epsilon : 53.10 F/m
Sigma : 1.99 S/m

Report No : TSC-102-05-AP-12 (SAR)

Density : 1000.00 kg/cu. m
Probe Data
Name : Probe 257 - CHTL
Model : E020
Type : E-Field Triangle
Serial No. : 257
Last Calib. Date : 14-Nov-2012
Frequency : 2450.00 MHz
Duty Cycle Factor: 1
Conversion Factor: 4.5
Probe Sensitivity: 1.20 1.20 1.20 $\mu\text{V}/(\text{V}/\text{m})^2$
Compression Point: 95.00 mV
Offset : 1.56 mm


Measurement Data

Crest Factor : 1
Scan Type : Complete
Tissue Temp. : 24.00 °C
Ambient Temp. : 24.00 °C
Set-up Date : 23-May-2013
Set-up Time : 10:31:35 AM
Area Scan : 9x6x1 : Measurement x=15mm, y=15mm, z=4mm
Zoom Scan : 5x5x8 : Measurement x=8mm, y=8mm, z=4mm

Other Data

DUT Position : Touch
Separation : 0
Channel : Low

Report No : TSC-102-05-AP-12 (SAR)



1 gram SAR value : 0.102 W/kg
Area Scan Peak SAR : 0.081 W/kg
Zoom Scan Peak SAR : 0.000 W/kg

Report No : TSC-102-05-AP-12 (SAR)

Exposure Assessment Measurement Uncertainty

Source of Uncertainty	Tolerance Value	Probability Distribution	Divisor	c_i^{-1} (1-g)	Standard Uncertainty (1-g) %
Measurement System					
Probe Calibration	3.5	normal	1	1	3.5
Axial Isotropy	3.7	rectangular	$\sqrt{3}$	$(1-cp)^{1/2}$	1.5
Hemispherical Isotropy	10.9	rectangular	$\sqrt{3}$	\sqrt{cp}	4.4
Boundary Effect	1.0	rectangular	$\sqrt{3}$	1	0.6
Linearity	4.7	rectangular	$\sqrt{3}$	1	2.7
Detection Limit	1.0	rectangular	$\sqrt{3}$	1	0.6
Readout Electronics	1.0	normal	1	1	1.0
Response Time	0.8	rectangular	$\sqrt{3}$	1	0.5
Integration Time	1.7	rectangular	$\sqrt{3}$	1	1.0
RF Ambient Condition	3.0	rectangular	$\sqrt{3}$	1	1.7
Probe Positioner Mech.	0.4	rectangular	$\sqrt{3}$	1	0.2
Restriction					
Probe Positioning with respect to Phantom Shell	2.9	rectangular	$\sqrt{3}$	1	1.7
Extrapolation and Integration	3.7	rectangular	$\sqrt{3}$	1	2.1
Test Sample Positioning	4.0	normal	1	1	4.0
Device Holder Uncertainty	2.0	normal	1	1	2.0
Drift of Output Power	4.3	rectangular	$\sqrt{3}$	1	2.5
Phantom and Setup					
Phantom Uncertainty(shape & thickness tolerance)	3.4	rectangular	$\sqrt{3}$	1	2.0
Liquid Conductivity(target)	5.0	rectangular	$\sqrt{3}$	0.7	2.0
Liquid Conductivity(meas.)	2.1	normal	1	0.7	1.4
Liquid Permittivity(target)	5.0	rectangular	$\sqrt{3}$	0.6	1.7
Liquid Permittivity(meas.)	0.8	normal	1	0.6	0.5
Combined Uncertainty		RSS			9.7
Combined Uncertainty (coverage factor=2)		Normal (k=2)			19.4

Report No : TSC-102-05-AP-12 (SAR)

Mid Channel Front Touch

SAR Test Report

Report Date : 23-May-2013
By Operator : 123
Measurement Date : 23-May-2013
Starting Time : 23-May-2013 02:50:49 PM
End Time : 23-May-2013 03:14:05 PM
Scanning Time : 1396 secs

Product Data

Device Name : Winmate
Serial No. : ALGIZ 10X
Type : Other
Model : ALGIZ 10X
Frequency : 2400.00 MHz
Max. Transmit Pwr : 0.1 W
Drift Time : 0 min(s)
Length : 280 mm
Width : 175 mm
Depth : 36 mm
Antenna Type : Internal
Orientation : Touch
Power Drift-Start : 0.084 W/kg
Power Drift-Finish: 0.080 W/kg
Power Drift (%) : -4.218
Picture :

Phantom Data

Name : APREL-Uni
Type : Uni-Phantom
Size (mm) : 280 x 280 x 200
Serial No. : User Define
Location : Center
Description : Uni_Phantom

Tissue Data

Type : BODY
Serial No. : 2450
Frequency : 2450.00 MHz
Last Calib. Date : 23-May-2013
Temperature : 24.00 °C
Ambient Temp. : 24.00 °C
Humidity : 55.00 RH%
Epsilon : 53.10 F/m
Sigma : 1.99 S/m
Density : 1000.00 kg/cu. m

Probe Data

Name : Probe 257 - CHTL
Model : E020
Type : E-Field Triangle

Report No : TSC-102-05-AP-12 (SAR)

Serial No. : 257
Last Calib. Date : 14-Nov-2012
Frequency : 2450.00 MHz
Duty Cycle Factor: 1
Conversion Factor: 4.5
Probe Sensitivity: 1.20 1.20 1.20 $\mu\text{V}/(\text{V}/\text{m})^2$
Compression Point: 95.00 mV
Offset : 1.56 mm


Measurement Data

Crest Factor : 1
Scan Type : Complete
Tissue Temp. : 24.00 °C
Ambient Temp. : 24.00 °C
Set-up Date : 23-May-2013
Set-up Time : 10:31:35 AM
Area Scan : 9x6x1 : Measurement x=15mm, y=15mm, z=4mm
Zoom Scan : 5x5x8 : Measurement x=8mm, y=8mm, z=4mm

Other Data

DUT Position : Touch
Separation : 0
Channel : Mid

Report No : TSC-102-05-AP-12 (SAR)



1 gram SAR value : 0.172 W/kg
Area Scan Peak SAR : 0.143 W/kg
Zoom Scan Peak SAR : 0.200 W/kg

Report No : TSC-102-05-AP-12 (SAR)

Exposure Assessment Measurement Uncertainty

Source of Uncertainty	Tolerance Value	Probability Distribution	Divisor	c_i^{-1} (1-g)	Standard Uncertainty (1-g) %
Measurement System					
Probe Calibration	3.5	normal	1	1	3.5
Axial Isotropy	3.7	rectangular	$\sqrt{3}$	$(1-cp)^{1/2}$	1.5
Hemispherical Isotropy	10.9	rectangular	$\sqrt{3}$	\sqrt{cp}	4.4
Boundary Effect	1.0	rectangular	$\sqrt{3}$	1	0.6
Linearity	4.7	rectangular	$\sqrt{3}$	1	2.7
Detection Limit	1.0	rectangular	$\sqrt{3}$	1	0.6
Readout Electronics	1.0	normal	1	1	1.0
Response Time	0.8	rectangular	$\sqrt{3}$	1	0.5
Integration Time	1.7	rectangular	$\sqrt{3}$	1	1.0
RF Ambient Condition	3.0	rectangular	$\sqrt{3}$	1	1.7
Probe Positioner Mech.	0.4	rectangular	$\sqrt{3}$	1	0.2
Restriction					
Probe Positioning with respect to Phantom Shell	2.9	rectangular	$\sqrt{3}$	1	1.7
Extrapolation and Integration	3.7	rectangular	$\sqrt{3}$	1	2.1
Test Sample Positioning	4.0	normal	1	1	4.0
Device Holder Uncertainty	2.0	normal	1	1	2.0
Drift of Output Power	4.2	rectangular	$\sqrt{3}$	1	2.4
Phantom and Setup					
Phantom Uncertainty(shape & thickness tolerance)	3.4	rectangular	$\sqrt{3}$	1	2.0
Liquid Conductivity(target)	5.0	rectangular	$\sqrt{3}$	0.7	2.0
Liquid Conductivity(meas.)	2.1	normal	1	0.7	1.4
Liquid Permittivity(target)	5.0	rectangular	$\sqrt{3}$	0.6	1.7
Liquid Permittivity(meas.)	0.8	normal	1	0.6	0.5
Combined Uncertainty		RSS			9.7
Combined Uncertainty (coverage factor=2)		Normal(k=2)			19.3

High Channel Front Touch

SAR Test Report

Report Date : 23-May-2013

Report No : TSC-102-05-AP-12 (SAR)

By Operator : 123
Measurement Date : 23-May-2013
Starting Time : 23-May-2013 03:51:15 PM
End Time : 23-May-2013 04:14:27 PM
Scanning Time : 1392 secs

Product Data

Device Name : Winmate
Serial No. : ALGIZ 10X
Type : Other
Model : ALGIZ 10X
Frequency : 2400.00 MHz
Max. Transmit Pwr : 0.1 W
Drift Time : 0 min(s)
Length : 280 mm
Width : 175 mm
Depth : 36 mm
Antenna Type : Internal
Orientation : Touch
Power Drift-Start : 0.064 W/kg
Power Drift-Finish: 0.068 W/kg
Power Drift (%) : 6.211
Picture :

Phantom Data

Name : APREL-Uni
Type : Uni-Phantom
Size (mm) : 280 x 280 x 200
Serial No. : User Define
Location : Center
Description : Uni_Phantom

Tissue Data

Type : BODY
Serial No. : 2450
Frequency : 2450.00 MHz
Last Calib. Date : 23-May-2013
Temperature : 24.00 °C
Ambient Temp. : 24.00 °C
Humidity : 55.00 RH%
Epsilon : 53.10 F/m
Sigma : 1.99 S/m
Density : 1000.00 kg/cu. m

Probe Data

Name : Probe 257 - CHTL
Model : E020
Type : E-Field Triangle
Serial No. : 257
Last Calib. Date : 14-Nov-2012
Frequency : 2450.00 MHz
Duty Cycle Factor: 1
Conversion Factor: 4.5
Probe Sensitivity: 1.20 1.20 1.20 $\mu\text{V}/(\text{V}/\text{m})^2$

Report No : TSC-102-05-AP-12 (SAR)

Compression Point: 95.00 mV

Offset : 1.56 mm

Measurement Data

Crest Factor : 1

Scan Type : Complete

Tissue Temp. : 24.00 °C

Ambient Temp. : 24.00 °C

Set-up Date : 23-May-2013

Set-up Time : 10:31:35 AM

Area Scan : 9x6x1 : Measurement x=15mm, y=15mm, z=4mm

Zoom Scan : 5x5x8 : Measurement x=8mm, y=8mm, z=4mm


Other Data

DUT Position : Touch

Separation : 0

Channel : High

Report No : TSC-102-05-AP-12 (SAR)



1 gram SAR value : 0.075 W/kg
Area Scan Peak SAR : 0.091 W/kg
Zoom Scan Peak SAR : 0.000 W/kg

Report No : TSC-102-05-AP-12 (SAR)

Exposure Assessment Measurement Uncertainty

Source of Uncertainty	Tolerance Value	Probability Distribution	Divisor	c_i^{-1} (1-g)	Standard Uncertainty (1-g) %
Measurement System					
Probe Calibration	3.5	normal	1	1	3.5
Axial Isotropy	3.7	rectangular	$\sqrt{3}$	$(1-cp)^{1/2}$	1.5
Hemispherical Isotropy	10.9	rectangular	$\sqrt{3}$	\sqrt{cp}	4.4
Boundary Effect	1.0	rectangular	$\sqrt{3}$	1	0.6
Linearity	4.7	rectangular	$\sqrt{3}$	1	2.7
Detection Limit	1.0	rectangular	$\sqrt{3}$	1	0.6
Readout Electronics	1.0	normal	1	1	1.0
Response Time	0.8	rectangular	$\sqrt{3}$	1	0.5
Integration Time	1.7	rectangular	$\sqrt{3}$	1	1.0
RF Ambient Condition	3.0	rectangular	$\sqrt{3}$	1	1.7
Probe Positioner Mech.	0.4	rectangular	$\sqrt{3}$	1	0.2
Restriction					
Probe Positioning with respect to Phantom Shell	2.9	rectangular	$\sqrt{3}$	1	1.7
Extrapolation and Integration	3.7	rectangular	$\sqrt{3}$	1	2.1
Test Sample Positioning	4.0	normal	1	1	4.0
Device Holder Uncertainty	2.0	normal	1	1	2.0
Drift of Output Power	6.2	rectangular	$\sqrt{3}$	1	3.6
Phantom and Setup					
Phantom Uncertainty(shape & thickness tolerance)	3.4	rectangular	$\sqrt{3}$	1	2.0
Liquid Conductivity(target)	5.0	rectangular	$\sqrt{3}$	0.7	2.0
Liquid Conductivity(meas.)	2.1	normal	1	0.7	1.4
Liquid Permittivity(target)	5.0	rectangular	$\sqrt{3}$	0.6	1.7
Liquid Permittivity(meas.)	0.8	normal	1	0.6	0.5
Combined Uncertainty		RSS			10.0
Combined Uncertainty (coverage factor=2)		Normal (k=2)			20.0

Report No : TSC-102-05-AP-12 (SAR)

A.4.2 GPRS Mode

850MHz Low Channel Side Touch

SAR Test Report

Report Date : 17-May-2013
By Operator : 123
Measurement Date : 17-May-2013
Starting Time : 17-May-2013 08:45:27 AM
End Time : 17-May-2013 09:12:47 AM
Scanning Time : 1640 secs

Product Data

Device Name : Winmate
Serial No. : ALGIZ 10X
Type : Other
Model : ALGIZ 10X
Frequency : 835.00 MHz
Max. Transmit Pwr : 2 W
Drift Time : 0 min(s)
Length : 280 mm
Width : 175 mm
Depth : 36 mm
Antenna Type : Internal
Orientation : Touch
Power Drift-Start : 0.364 W/kg
Power Drift-Finish: 0.352 W/kg
Power Drift (%) : -3.245
Picture :

Phantom Data

Name : APREL-Uni
Type : Uni-Phantom
Size (mm) : 280 x 280 x 200
Serial No. : User Define
Location : Center
Description : Uni_Phantom

Tissue Data

Type : BODY
Serial No. : 835
Frequency : 835.00 MHz
Last Calib. Date : 15-May-2013
Temperature : 24.00 °C
Ambient Temp. : 24.00 °C
Humidity : 55.00 RH%
Epsilon : 53.00 F/m
Sigma : 0.99 S/m
Density : 1000.00 kg/cu. m
Probe Data

Report No : TSC-102-05-AP-12 (SAR)

Name : Probe 257 - CHTL
Model : E020
Type : E-Field Triangle
Serial No. : 257
Last Calib. Date : 14-Nov-2012
Frequency : 835.00 MHz
Duty Cycle Factor: 4
Conversion Factor: 6.9
Probe Sensitivity: 1.20 1.20 1.20 $\mu\text{V}/(\text{V}/\text{m})^2$
Compression Point: 95.00 mV
Offset : 1.56 mm


Measurement Data

Crest Factor : 4
Scan Type : Complete
Tissue Temp. : 24.00 °C
Ambient Temp. : 24.00 °C
Set-up Date : 17-May-2013
Set-up Time : 8:35:36 AM
Area Scan : 8x6x1 : Measurement x=15mm, y=15mm, z=4mm
Zoom Scan : 5x5x8 : Measurement x=8mm, y=8mm, z=4mm

Other Data

DUT Position : Touch
Separation : 0
Channel : Low

Report No : TSC-102-05-AP-12 (SAR)



Report No : TSC-102-05-AP-12 (SAR)

1 gram SAR value : 0.368 W/kg
Area Scan Peak SAR : 0.456 W/kg
Zoom Scan Peak SAR : 0.810 W/kg


Report No : TSC-102-05-AP-12 (SAR)

Exposure Assessment Measurement Uncertainty

Source of Uncertainty	Tolerance Value	Probability Distribution	Divisor	c_i^{-1} (1-g)	Standard Uncertainty (1-g) %
Measurement System					
Probe Calibration	3.5	normal	1	1	3.5
Axial Isotropy	3.7	rectangular	$\sqrt{3}$	$(1-cp)^{1/2}$	1.5
Hemispherical Isotropy	10.9	rectangular	$\sqrt{3}$	\sqrt{cp}	4.4
Boundary Effect	1.0	rectangular	$\sqrt{3}$	1	0.6
Linearity	4.7	rectangular	$\sqrt{3}$	1	2.7
Detection Limit	1.0	rectangular	$\sqrt{3}$	1	0.6
Readout Electronics	1.0	normal	1	1	1.0
Response Time	0.8	rectangular	$\sqrt{3}$	1	0.5
Integration Time	1.7	rectangular	$\sqrt{3}$	1	1.0
RF Ambient Condition	3.0	rectangular	$\sqrt{3}$	1	1.7
Probe Positioner Mech.	0.4	rectangular	$\sqrt{3}$	1	0.2
Restriction					
Probe Positioning with respect to Phantom Shell	2.9	rectangular	$\sqrt{3}$	1	1.7
Extrapolation and Integration	3.7	rectangular	$\sqrt{3}$	1	2.1
Test Sample Positioning	4.0	normal	1	1	4.0
Device Holder Uncertainty	2.0	normal	1	1	2.0
Drift of Output Power	3.2	rectangular	$\sqrt{3}$	1	1.9
Phantom and Setup					
Phantom Uncertainty(shape & thickness tolerance)	3.4	rectangular	$\sqrt{3}$	1	2.0
Liquid Conductivity(target)	5.0	rectangular	$\sqrt{3}$	0.7	2.0
Liquid Conductivity(meas.)	2.1	normal	1	0.7	1.4
Liquid Permittivity(target)	5.0	rectangular	$\sqrt{3}$	0.6	1.7
Liquid Permittivity(meas.)	4.0	normal	1	0.6	2.4
Combined Uncertainty		RSS			9.8
Combined Uncertainty (coverage factor=2)		Normal (k=2)			19.7

Report No : TSC-102-05-AP-12 (SAR)

SAR-Z Axis
at Hotspot x:15.07 y:-7.24



Report No : TSC-102-05-AP-12 (SAR)

850MHz Mid Channel Side Touch

SAR Test Report

Report Date : 16-May-2013
By Operator : 123
Measurement Date : 16-May-2013
Starting Time : 16-May-2013 04:04:34 PM
End Time : 16-May-2013 04:26:07 PM
Scanning Time : 1293 secs

Product Data

Device Name : Winmate
Serial No. : ALGIZ 10X
Type : Other
Model : ALGIZ 10X
Frequency : 835.00 MHz
Max. Transmit Pwr : 2 W
Drift Time : 0 min(s)
Length : 280 mm
Width : 175 mm
Depth : 36 mm
Antenna Type : Internal
Orientation : Touch
Power Drift-Start : 0.280 W/kg
Power Drift-Finish: 0.263 W/kg
Power Drift (%) : -6.228
Picture :

Phantom Data

Name : APREL-Uni
Type : Uni-Phantom
Size (mm) : 280 x 280 x 200
Serial No. : User Define
Location : Center
Description : Uni_Phantom

Tissue Data

Type : BODY
Serial No. : 835
Frequency : 835.00 MHz
Last Calib. Date : 15-May-2013
Temperature : 24.00 °C
Ambient Temp. : 24.00 °C
Humidity : 55.00 RH%
Epsilon : 53.00 F/m
Sigma : 0.99 S/m
Density : 1000.00 kg/cu. m
Probe Data
Name : Probe 257 - CHTL
Model : E020

Report No : TSC-102-05-AP-12 (SAR)

Type : E-Field Triangle
Serial No. : 257
Last Calib. Date : 14-Nov-2012
Frequency : 835.00 MHz
Duty Cycle Factor: 4
Conversion Factor: 6.9
Probe Sensitivity: 1.20 1.20 1.20 $\mu\text{V}/(\text{V}/\text{m})^2$
Compression Point: 95.00 mV
Offset : 1.56 mm


Measurement Data

Crest Factor : 4
Scan Type : Complete
Tissue Temp. : 24.00 °C
Ambient Temp. : 24.00 °C
Set-up Date : 16-May-2013
Set-up Time : 3:39:42 PM
Area Scan : 8x6x1 : Measurement x=15mm, y=15mm, z=4mm
Zoom Scan : 5x5x8 : Measurement x=8mm, y=8mm, z=4mm

Other Data

DUT Position : Touch
Separation : 0
Channel : Mid

Report No : TSC-102-05-AP-12 (SAR)



Report No : TSC-102-05-AP-12 (SAR)

1 gram SAR value : 0.403 W/kg
Area Scan Peak SAR : 0.483 W/kg
Zoom Scan Peak SAR : 0.860 W/kg


Report No : TSC-102-05-AP-12 (SAR)

Exposure Assessment Measurement Uncertainty

Source of Uncertainty	Tolerance Value	Probability Distribution	Divisor	c_i^{-1} (1-g)	Standard Uncertainty (1-g) %
Measurement System					
Probe Calibration	3.5	normal	1	1	3.5
Axial Isotropy	3.7	rectangular	$\sqrt{3}$	$(1-cp)^{1/2}$	1.5
Hemispherical Isotropy	10.9	rectangular	$\sqrt{3}$	\sqrt{cp}	4.4
Boundary Effect	1.0	rectangular	$\sqrt{3}$	1	0.6
Linearity	4.7	rectangular	$\sqrt{3}$	1	2.7
Detection Limit	1.0	rectangular	$\sqrt{3}$	1	0.6
Readout Electronics	1.0	normal	1	1	1.0
Response Time	0.8	rectangular	$\sqrt{3}$	1	0.5
Integration Time	1.7	rectangular	$\sqrt{3}$	1	1.0
RF Ambient Condition	3.0	rectangular	$\sqrt{3}$	1	1.7
Probe Positioner Mech.	0.4	rectangular	$\sqrt{3}$	1	0.2
Restriction					
Probe Positioning with respect to Phantom Shell	2.9	rectangular	$\sqrt{3}$	1	1.7
Extrapolation and Integration	3.7	rectangular	$\sqrt{3}$	1	2.1
Test Sample Positioning	4.0	normal	1	1	4.0
Device Holder Uncertainty	2.0	normal	1	1	2.0
Drift of Output Power	6.2	rectangular	$\sqrt{3}$	1	3.6
Phantom and Setup					
Phantom Uncertainty(shape & thickness tolerance)	3.4	rectangular	$\sqrt{3}$	1	2.0
Liquid Conductivity(target)	5.0	rectangular	$\sqrt{3}$	0.7	2.0
Liquid Conductivity(meas.)	2.1	normal	1	0.7	1.4
Liquid Permittivity(target)	5.0	rectangular	$\sqrt{3}$	0.6	1.7
Liquid Permittivity(meas.)	4.0	normal	1	0.6	2.4
Combined Uncertainty		RSS			10.3
Combined Uncertainty (coverage factor=2)		Normal (k=2)			20.6

Report No : TSC-102-05-AP-12 (SAR)

SAR-Z Axis
at Hotspot x:15.08 y:-7.24



Report No : TSC-102-05-AP-12 (SAR)

850MHz High Channel Side Touch

SAR Test Report

Report Date : 16-May-2013
By Operator : 123
Measurement Date : 16-May-2013
Starting Time : 16-May-2013 04:44:59 PM
End Time : 16-May-2013 05:11:46 PM
Scanning Time : 1607 secs

Product Data

Device Name : Winmate
Serial No. : ALGIZ 10X
Type : Other
Model : ALGIZ 10X
Frequency : 835.00 MHz
Max. Transmit Pwr : 2 W
Drift Time : 0 min(s)
Length : 280 mm
Width : 175 mm
Depth : 36 mm
Antenna Type : Internal
Orientation : Touch
Power Drift-Start : 0.148 W/kg
Power Drift-Finish: 0.150 W/kg
Power Drift (%) : 4.015
Picture :

Phantom Data

Name : APREL-Uni
Type : Uni-Phantom
Size (mm) : 280 x 280 x 200
Serial No. : User Define
Location : Center
Description : Uni_Phantom

Tissue Data

Type : BODY
Serial No. : 835
Frequency : 835.00 MHz
Last Calib. Date : 15-May-2013
Temperature : 24.00 °C
Ambient Temp. : 24.00 °C
Humidity : 55.00 RH%
Epsilon : 53.00 F/m
Sigma : 0.99 S/m
Density : 1000.00 kg/cu. m

Probe Data

Name : Probe 257 - CHTL
Model : E020
Type : E-Field Triangle

Report No : TSC-102-05-AP-12 (SAR)

Serial No. : 257
Last Calib. Date : 14-Nov-2012
Frequency : 835.00 MHz
Duty Cycle Factor: 4
Conversion Factor: 6.9
Probe Sensitivity: 1.20 1.20 1.20 $\mu\text{V}/(\text{V}/\text{m})^2$
Compression Point: 95.00 mV
Offset : 1.56 mm


Measurement Data

Crest Factor : 4
Scan Type : Complete
Tissue Temp. : 24.00 °C
Ambient Temp. : 24.00 °C
Set-up Date : 16-May-2013
Set-up Time : 3:39:42 PM
Area Scan : 8x6x1 : Measurement x=15mm, y=15mm, z=4mm
Zoom Scan : 5x5x8 : Measurement x=8mm, y=8mm, z=4mm

Other Data

DUT Position : Touch
Separation : 0
Channel : High

Report No : TSC-102-05-AP-12 (SAR)



Report No : TSC-102-05-AP-12 (SAR)

1 gram SAR value : 0.398 W/kg
Area Scan Peak SAR : 0.403 W/kg
Zoom Scan Peak SAR : 0.820 W/kg


Report No : TSC-102-05-AP-12 (SAR)

Exposure Assessment Measurement Uncertainty

Source of Uncertainty	Tolerance Value	Probability Distribution	Divisor	c_i^{-1} (1-g)	Standard Uncertainty (1-g) %
Measurement System					
Probe Calibration	3.5	normal	1	1	3.5
Axial Isotropy	3.7	rectangular	$\sqrt{3}$	$(1-cp)^{1/2}$	1.5
Hemispherical Isotropy	10.9	rectangular	$\sqrt{3}$	\sqrt{cp}	4.4
Boundary Effect	1.0	rectangular	$\sqrt{3}$	1	0.6
Linearity	4.7	rectangular	$\sqrt{3}$	1	2.7
Detection Limit	1.0	rectangular	$\sqrt{3}$	1	0.6
Readout Electronics	1.0	normal	1	1	1.0
Response Time	0.8	rectangular	$\sqrt{3}$	1	0.5
Integration Time	1.7	rectangular	$\sqrt{3}$	1	1.0
RF Ambient Condition	3.0	rectangular	$\sqrt{3}$	1	1.7
Probe Positioner Mech.	0.4	rectangular	$\sqrt{3}$	1	0.2
Restriction					
Probe Positioning with respect to Phantom Shell	2.9	rectangular	$\sqrt{3}$	1	1.7
Extrapolation and Integration	3.7	rectangular	$\sqrt{3}$	1	2.1
Test Sample Positioning	4.0	normal	1	1	4.0
Device Holder Uncertainty	2.0	normal	1	1	2.0
Drift of Output Power	4.0	rectangular	$\sqrt{3}$	1	2.3
Phantom and Setup					
Phantom Uncertainty(shape & thickness tolerance)	3.4	rectangular	$\sqrt{3}$	1	2.0
Liquid Conductivity(target)	5.0	rectangular	$\sqrt{3}$	0.7	2.0
Liquid Conductivity(meas.)	2.1	normal	1	0.7	1.4
Liquid Permittivity(target)	5.0	rectangular	$\sqrt{3}$	0.6	1.7
Liquid Permittivity(meas.)	4.0	normal	1	0.6	2.4
Combined Uncertainty		RSS			9.9
Combined Uncertainty (coverage factor=2)		Normal (k=2)			19.8

Report No : TSC-102-05-AP-12 (SAR)

SAR-Z Axis
at Hotspot x:23.04 y:-7.21



Report No : TSC-102-05-AP-12 (SAR)

1900MHz Low Channel Side Touch

SAR Test Report

Report Date : 16-May-2013
By Operator : 123
Measurement Date : 16-May-2013
Starting Time : 16-May-2013 02:36:14 PM
End Time : 16-May-2013 03:02:51 PM
Scanning Time : 1597 secs

Product Data

Device Name : Winmate
Serial No. : ALGIZ 10X
Type : Other
Model : ALGIZ 10X
Frequency : 1900.00 MHz
Max. Transmit Pwr : 1 W
Drift Time : 0 min(s)
Length : 280 mm
Width : 175 mm
Depth : 36 mm
Antenna Type : Internal
Orientation : Touch
Power Drift-Start : 0.238 W/kg
Power Drift-Finish: 0.204 W/kg
Power Drift (%) : -4.290
Picture :

Phantom Data

Name : APREL-Uni
Type : Uni-Phantom
Size (mm) : 280 x 280 x 200
Serial No. : User Define
Location : Center
Description : Uni_Phantom

Tissue Data

Type : BODY
Serial No. : 1900
Frequency : 1900.00 MHz
Last Calib. Date : 15-May-2013
Temperature : 24.00 °C
Ambient Temp. : 24.00 °C
Humidity : 55.00 RH%
Epsilon : 52.80 F/m
Sigma : 1.48 S/m
Density : 1000.00 kg/cu. m
Probe Data
Name : Probe 257 - CHTL
Model : E020

Report No : TSC-102-05-AP-12 (SAR)

Type : E-Field Triangle
Serial No. : 257
Last Calib. Date : 14-Nov-2012
Frequency : 1900.00 MHz
Duty Cycle Factor: 4
Conversion Factor: 5.9
Probe Sensitivity: 1.20 1.20 1.20 $\mu\text{V}/(\text{V}/\text{m})^2$
Compression Point: 95.00 mV
Offset : 1.56 mm


Measurement Data

Crest Factor : 4
Scan Type : Complete
Tissue Temp. : 24.00 °C
Ambient Temp. : 24.00 °C
Set-up Date : 16-May-2013
Set-up Time : 10:13:01 AM
Area Scan : 8x6x1 : Measurement x=15mm, y=15mm, z=4mm
Zoom Scan : 5x5x8 : Measurement x=8mm, y=8mm, z=4mm

Other Data

DUT Position : Touch
Separation : 0
Channel : Low

Report No : TSC-102-05-AP-12 (SAR)



Report No : TSC-102-05-AP-12 (SAR)

1 gram SAR value : 0.708 W/kg
Area Scan Peak SAR : 0.640 W/kg
Zoom Scan Peak SAR : 1.571 W/kg


Report No : TSC-102-05-AP-12 (SAR)

Exposure Assessment Measurement Uncertainty

Source of Uncertainty	Tolerance Value	Probability Distribution	Divisor	c_i^{-1} (1-g)	Standard Uncertainty (1-g) %
Measurement System					
Probe Calibration	3.5	normal	1	1	3.5
Axial Isotropy	3.7	rectangular	$\sqrt{3}$	$(1-cp)^{1/2}$	1.5
Hemispherical Isotropy	10.9	rectangular	$\sqrt{3}$	\sqrt{cp}	4.4
Boundary Effect	1.0	rectangular	$\sqrt{3}$	1	0.6
Linearity	4.7	rectangular	$\sqrt{3}$	1	2.7
Detection Limit	1.0	rectangular	$\sqrt{3}$	1	0.6
Readout Electronics	1.0	normal	1	1	1.0
Response Time	0.8	rectangular	$\sqrt{3}$	1	0.5
Integration Time	1.7	rectangular	$\sqrt{3}$	1	1.0
RF Ambient Condition	3.0	rectangular	$\sqrt{3}$	1	1.7
Probe Positioner Mech.	0.4	rectangular	$\sqrt{3}$	1	0.2
Restriction					
Probe Positioning with respect to Phantom Shell	2.9	rectangular	$\sqrt{3}$	1	1.7
Extrapolation and Integration	3.7	rectangular	$\sqrt{3}$	1	2.1
Test Sample Positioning	4.0	normal	1	1	4.0
Device Holder Uncertainty	2.0	normal	1	1	2.0
Drift of Output Power	4.3	rectangular	$\sqrt{3}$	1	2.5
Phantom and Setup					
Phantom Uncertainty(shape & thickness tolerance)	3.4	rectangular	$\sqrt{3}$	1	2.0
Liquid Conductivity(target)	5.0	rectangular	$\sqrt{3}$	0.7	2.0
Liquid Conductivity(meas.)	2.6	normal	1	0.7	1.8
Liquid Permittivity(target)	5.0	rectangular	$\sqrt{3}$	0.6	1.7
Liquid Permittivity(meas.)	0.9	normal	1	0.6	0.6
Combined Uncertainty		RSS			9.7
Combined Uncertainty (coverage factor=2)		Normal (k=2)			19.5

Report No : TSC-102-05-AP-12 (SAR)

SAR-Z Axis
at Hotspot x:23.06 y:-15.25



Report No : TSC-102-05-AP-12 (SAR)

1900MHz Middle Channel Side Touch

SAR Test Report

Report Date : 16-May-2013
By Operator : 123
Measurement Date : 16-May-2013
Starting Time : 16-May-2013 02:07:44 PM
End Time : 16-May-2013 02:34:32 PM
Scanning Time : 1608 secs

Product Data

Device Name : Winmate
Serial No. : ALGIZ 10X
Type : Other
Model : ALGIZ 10X
Frequency : 1900.00 MHz
Max. Transmit Pwr : 1 W
Drift Time : 0 min(s)
Length : 280 mm
Width : 175 mm
Depth : 36 mm
Antenna Type : Internal
Orientation : Touch
Power Drift-Start : 0.232 W/kg
Power Drift-Finish: 0.228 W/kg
Power Drift (%) : -1.443
Picture :

Phantom Data

Name : APREL-Uni
Type : Uni-Phantom
Size (mm) : 280 x 280 x 200
Serial No. : User Define
Location : Center
Description : Uni_Phantom

Tissue Data

Type : BODY
Serial No. : 1900
Frequency : 1900.00 MHz
Last Calib. Date : 15-May-2013
Temperature : 24.00 °C
Ambient Temp. : 24.00 °C
Humidity : 55.00 RH%
Epsilon : 52.80 F/m
Sigma : 1.48 S/m
Density : 1000.00 kg/cu. m
Probe Data
Name : Probe 257 - CHTL
Model : E020

Report No : TSC-102-05-AP-12 (SAR)

Type : E-Field Triangle
Serial No. : 257
Last Calib. Date : 14-Nov-2012
Frequency : 1900.00 MHz
Duty Cycle Factor: 4
Conversion Factor: 5.9
Probe Sensitivity: 1.20 1.20 1.20 $\mu\text{V}/(\text{V}/\text{m})^2$
Compression Point: 95.00 mV
Offset : 1.56 mm


Measurement Data

Crest Factor : 4
Scan Type : Complete
Tissue Temp. : 24.00 °C
Ambient Temp. : 24.00 °C
Set-up Date : 16-May-2013
Set-up Time : 10:13:01 AM
Area Scan : 8x6x1 : Measurement x=15mm, y=15mm, z=4mm
Zoom Scan : 5x5x8 : Measurement x=8mm, y=8mm, z=4mm

Other Data

DUT Position : Touch
Separation : 0
Channel : Mid

Report No : TSC-102-05-AP-12 (SAR)



Report No : TSC-102-05-AP-12 (SAR)

1 gram SAR value : 0.765 W/kg
Area Scan Peak SAR : 0.629 W/kg
Zoom Scan Peak SAR : 1.661 W/kg


Report No : TSC-102-05-AP-12 (SAR)

Exposure Assessment Measurement Uncertainty

Source of Uncertainty	Tolerance Value	Probability Distribution	Divisor	c_i^{-1} (1-g)	Standard Uncertainty (1-g) %
Measurement System					
Probe Calibration	3.5	normal	1	1	3.5
Axial Isotropy	3.7	rectangular	$\sqrt{3}$	$(1-cp)^{1/2}$	1.5
Hemispherical Isotropy	10.9	rectangular	$\sqrt{3}$	\sqrt{cp}	4.4
Boundary Effect	1.0	rectangular	$\sqrt{3}$	1	0.6
Linearity	4.7	rectangular	$\sqrt{3}$	1	2.7
Detection Limit	1.0	rectangular	$\sqrt{3}$	1	0.6
Readout Electronics	1.0	normal	1	1	1.0
Response Time	0.8	rectangular	$\sqrt{3}$	1	0.5
Integration Time	1.7	rectangular	$\sqrt{3}$	1	1.0
RF Ambient Condition	3.0	rectangular	$\sqrt{3}$	1	1.7
Probe Positioner Mech.	0.4	rectangular	$\sqrt{3}$	1	0.2
Restriction					
Probe Positioning with respect to Phantom Shell	2.9	rectangular	$\sqrt{3}$	1	1.7
Extrapolation and Integration	3.7	rectangular	$\sqrt{3}$	1	2.1
Test Sample Positioning	4.0	normal	1	1	4.0
Device Holder Uncertainty	2.0	normal	1	1	2.0
Drift of Output Power	1.4	rectangular	$\sqrt{3}$	1	0.8
Phantom and Setup					
Phantom Uncertainty(shape & thickness tolerance)	3.4	rectangular	$\sqrt{3}$	1	2.0
Liquid Conductivity(target)	5.0	rectangular	$\sqrt{3}$	0.7	2.0
Liquid Conductivity(meas.)	2.6	normal	1	0.7	1.8
Liquid Permittivity(target)	5.0	rectangular	$\sqrt{3}$	0.6	1.7
Liquid Permittivity(meas.)	0.9	normal	1	0.6	0.6
Combined Uncertainty		RSS			9.5
Combined Uncertainty (coverage factor=2)		Normal (k=2)			18.9

Report No : TSC-102-05-AP-12 (SAR)

SAR-Z Axis
at Hotspot x:23.06 y:-15.25



Report No : TSC-102-05-AP-12 (SAR)

1900MHz High Channel Side Touch
SAR Test Report

Report Date : 16-May-2013
By Operator : 123
Measurement Date : 16-May-2013
Starting Time : 16-May-2013 03:05:02 PM
End Time : 16-May-2013 03:31:32 PM
Scanning Time : 1590 secs

Product Data
Device Name : Winmate
Serial No. : ALGIZ 10X
Type : Other
Model : ALGIZ 10X
Frequency : 1900.00 MHz
Max. Transmit Pwr : 1 W
Drift Time : 0 min(s)
Length : 280 mm
Width : 175 mm
Depth : 36 mm
Antenna Type : Internal
Orientation : Touch
Power Drift-Start : 0.201 W/kg
Power Drift-Finish: 0.206 W/kg
Power Drift (%) : 2.807
Picture :

Phantom Data
Name : APREL-Uni
Type : Uni-Phantom
Size (mm) : 280 x 280 x 200
Serial No. : User Define
Location : Center
Description : Uni_Phantom

Tissue Data
Type : BODY
Serial No. : 1900
Frequency : 1900.00 MHz
Last Calib. Date : 15-May-2013
Temperature : 24.00 °C
Ambient Temp. : 24.00 °C
Humidity : 55.00 RH%
Epsilon : 52.80 F/m
Sigma : 1.48 S/m
Density : 1000.00 kg/cu. m
Probe Data
Name : Probe 257 - CHTL
Model : E020
Type : E-Field Triangle
Serial No. : 257

Report No : TSC-102-05-AP-12 (SAR)
Last Calib. Date : 14-Nov-2012
Frequency : 1900.00 MHz
Duty Cycle Factor: 4
Conversion Factor: 5.9
Probe Sensitivity: 1.20 1.20 1.20 $\mu\text{V}/(\text{V}/\text{m})^2$
Compression Point: 95.00 mV
Offset : 1.56 mm


Measurement Data

Crest Factor : 4
Scan Type : Complete
Tissue Temp. : 24.00 °C
Ambient Temp. : 24.00 °C
Set-up Date : 16-May-2013
Set-up Time : 10:13:01 AM
Area Scan : 8x6x1 : Measurement x=15mm, y=15mm, z=4mm
Zoom Scan : 5x5x8 : Measurement x=8mm, y=8mm, z=4mm

Other Data

DUT Position : Touch
Separation : 0
Channel : High

Report No : TSC-102-05-AP-12 (SAR)



Report No : TSC-102-05-AP-12 (SAR)

1 gram SAR value : 0.624 W/kg
Area Scan Peak SAR : 0.590 W/kg
Zoom Scan Peak SAR : 1.511 W/kg


Report No : TSC-102-05-AP-12 (SAR)

Exposure Assessment Measurement Uncertainty

Source of Uncertainty	Tolerance Value	Probability Distribution	Divisor	c_i^{-1} (1-g)	Standard Uncertainty (1-g) %
Measurement System					
Probe Calibration	3.5	normal	1	1	3.5
Axial Isotropy	3.7	rectangular	$\sqrt{3}$	$(1-cp)^{1/2}$	1.5
Hemispherical Isotropy	10.9	rectangular	$\sqrt{3}$	\sqrt{cp}	4.4
Boundary Effect	1.0	rectangular	$\sqrt{3}$	1	0.6
Linearity	4.7	rectangular	$\sqrt{3}$	1	2.7
Detection Limit	1.0	rectangular	$\sqrt{3}$	1	0.6
Readout Electronics	1.0	normal	1	1	1.0
Response Time	0.8	rectangular	$\sqrt{3}$	1	0.5
Integration Time	1.7	rectangular	$\sqrt{3}$	1	1.0
RF Ambient Condition	3.0	rectangular	$\sqrt{3}$	1	1.7
Probe Positioner Mech.	0.4	rectangular	$\sqrt{3}$	1	0.2
Restriction					
Probe Positioning with respect to Phantom Shell	2.9	rectangular	$\sqrt{3}$	1	1.7
Extrapolation and Integration	3.7	rectangular	$\sqrt{3}$	1	2.1
Test Sample Positioning	4.0	normal	1	1	4.0
Device Holder Uncertainty	2.0	normal	1	1	2.0
Drift of Output Power	2.8	rectangular	$\sqrt{3}$	1	1.6
Phantom and Setup					
Phantom Uncertainty(shape & thickness tolerance)	3.4	rectangular	$\sqrt{3}$	1	2.0
Liquid Conductivity(target)	5.0	rectangular	$\sqrt{3}$	0.7	2.0
Liquid Conductivity(meas.)	2.6	normal	1	0.7	1.8
Liquid Permittivity(target)	5.0	rectangular	$\sqrt{3}$	0.6	1.7
Liquid Permittivity(meas.)	0.9	normal	1	0.6	0.6
Combined Uncertainty		RSS			9.6
Combined Uncertainty (coverage factor=2)		Normal (k=2)			19.1

Report No : TSC-102-05-AP-12 (SAR)

SAR-Z Axis
at Hotspot x:15.10 y:-14.24



Report No : TSC-102-05-AP-12 (SAR)

A.4.3 WCDMA Mode

850MHz Band 5 Low Channel Side Touch

SAR Test Report

Report Date : 17-May-2013
By Operator : 123
Measurement Date : 17-May-2013
Starting Time : 17-May-2013 10:42:05 AM
End Time : 17-May-2013 11:03:49 AM
Scanning Time : 1304 secs

Product Data
Device Name : Winmate
Serial No. : ALGIZ 10X
Type : Other
Model : ALGIZ 10X
Frequency : 835.00 MHz
Max. Transmit Pwr : 0.25 W
Drift Time : 0 min(s)
Length : 280 mm
Width : 175 mm
Depth : 36 mm
Antenna Type : Internal
Orientation : Touch
Power Drift-Start : 0.501 W/kg
Power Drift-Finish: 0.480 W/kg
Power Drift (%) : -4.132
Picture :

Phantom Data
Name : APREL-Uni
Type : Uni-Phantom
Size (mm) : 280 x 280 x 200
Serial No. : User Define
Location : Center
Description : Uni_Phantom

Tissue Data
Type : BODY
Serial No. : 835
Frequency : 835.00 MHz
Last Calib. Date : 15-May-2013
Temperature : 24.00 °C
Ambient Temp. : 24.00 °C
Humidity : 55.00 RH%
Epsilon : 53.00 F/m
Sigma : 0.99 S/m

Report No : TSC-102-05-AP-12 (SAR)

Density : 1000.00 kg/cu. m
Probe Data
Name : Probe 257 - CHTL
Model : E020
Type : E-Field Triangle
Serial No. : 257
Last Calib. Date : 14-Nov-2012
Frequency : 835.00 MHz
Duty Cycle Factor: 1
Conversion Factor: 6.9
Probe Sensitivity: 1.20 1.20 1.20 $\mu\text{V}/(\text{V}/\text{m})^2$
Compression Point: 95.00 mV
Offset : 1.56 mm


Measurement Data

Crest Factor : 1
Scan Type : Complete
Tissue Temp. : 24.00 °C
Ambient Temp. : 24.00 °C
Set-up Date : 17-May-2013
Set-up Time : 8:35:36 AM
Area Scan : 8x6x1 : Measurement x=15mm, y=15mm, z=4mm
Zoom Scan : 5x5x8 : Measurement x=8mm, y=8mm, z=4mm

Other Data

DUT Position : Touch
Separation : 0
Channel : Low

Report No : TSC-102-05-AP-12 (SAR)



Report No : TSC-102-05-AP-12 (SAR)

1 gram SAR value : 0.740 W/kg
Area Scan Peak SAR : 0.795 W/kg
Zoom Scan Peak SAR : 1.611 W/kg


Report No : TSC-102-05-AP-12 (SAR)

Exposure Assessment Measurement Uncertainty

Source of Uncertainty	Tolerance Value	Probability Distribution	Divisor	c_i^{-1} (1-g)	Standard Uncertainty (1-g) %
Measurement System					
Probe Calibration	3.5	normal	1	1	3.5
Axial Isotropy	3.7	rectangular	$\sqrt{3}$	$(1-cp)^{1/2}$	1.5
Hemispherical Isotropy	10.9	rectangular	$\sqrt{3}$	\sqrt{cp}	4.4
Boundary Effect	1.0	rectangular	$\sqrt{3}$	1	0.6
Linearity	4.7	rectangular	$\sqrt{3}$	1	2.7
Detection Limit	1.0	rectangular	$\sqrt{3}$	1	0.6
Readout Electronics	1.0	normal	1	1	1.0
Response Time	0.8	rectangular	$\sqrt{3}$	1	0.5
Integration Time	1.7	rectangular	$\sqrt{3}$	1	1.0
RF Ambient Condition	3.0	rectangular	$\sqrt{3}$	1	1.7
Probe Positioner Mech.	0.4	rectangular	$\sqrt{3}$	1	0.2
Restriction					
Probe Positioning with respect to Phantom Shell	2.9	rectangular	$\sqrt{3}$	1	1.7
Extrapolation and Integration	3.7	rectangular	$\sqrt{3}$	1	2.1
Test Sample Positioning	4.0	normal	1	1	4.0
Device Holder Uncertainty	2.0	normal	1	1	2.0
Drift of Output Power	4.1	rectangular	$\sqrt{3}$	1	2.4
Phantom and Setup					
Phantom Uncertainty(shape & thickness tolerance)	3.4	rectangular	$\sqrt{3}$	1	2.0
Liquid Conductivity(target)	5.0	rectangular	$\sqrt{3}$	0.7	2.0
Liquid Conductivity(meas.)	2.1	normal	1	0.7	1.4
Liquid Permittivity(target)	5.0	rectangular	$\sqrt{3}$	0.6	1.7
Liquid Permittivity(meas.)	4.0	normal	1	0.6	2.4
Combined Uncertainty		RSS			9.9
Combined Uncertainty (coverage factor=2)		Normal (k=2)			19.9

Report No : TSC-102-05-AP-12 (SAR)

SAR-Z Axis
at Hotspot x:7.08 y:-7.24



Report No : TSC-102-05-AP-12 (SAR)

850MHz Band 5
Mid Channel Side Touch

SAR Test Report

Report Date : 17-May-2013
By Operator : 123
Measurement Date : 17-May-2013
Starting Time : 17-May-2013 11:43:11 AM
End Time : 17-May-2013 12:05:11 PM
Scanning Time : 1320 secs

Product Data

Device Name : Winmate
Serial No. : ALGIZ 10X
Type : Other
Model : ALGIZ 10X
Frequency : 835.00 MHz
Max. Transmit Pwr : 0.25 W
Drift Time : 0 min(s)
Length : 280 mm
Width : 175 mm
Depth : 36 mm
Antenna Type : Internal
Orientation : Touch
Power Drift-Start : 0.500 W/kg
Power Drift-Finish: 0.501 W/kg
Power Drift (%) : 0.309
Picture :

Phantom Data

Name : APREL-Uni
Type : Uni-Phantom
Size (mm) : 280 x 280 x 200
Serial No. : User Define
Location : Center
Description : Uni_Phantom

Tissue Data

Type : BODY
Serial No. : 835
Frequency : 835.00 MHz
Last Calib. Date : 15-May-2013
Temperature : 24.00 °C
Ambient Temp. : 24.00 °C
Humidity : 55.00 RH%
Epsilon : 53.00 F/m
Sigma : 0.99 S/m
Density : 1000.00 kg/cu. m
Probe Data
Name : Probe 257 - CHTL

Report No : TSC-102-05-AP-12 (SAR)

Model : E020
Type : E-Field Triangle
Serial No. : 257
Last Calib. Date : 14-Nov-2012
Frequency : 835.00 MHz
Duty Cycle Factor: 1
Conversion Factor: 6.9
Probe Sensitivity: 1.20 1.20 1.20 $\mu\text{V}/(\text{V}/\text{m})^2$
Compression Point: 95.00 mV
Offset : 1.56 mm


Measurement Data

Crest Factor : 1
Scan Type : Complete
Tissue Temp. : 24.00 °C
Ambient Temp. : 24.00 °C
Set-up Date : 17-May-2013
Set-up Time : 8:35:36 AM
Area Scan : 8x6x1 : Measurement x=15mm, y=15mm, z=4mm
Zoom Scan : 5x5x8 : Measurement x=8mm, y=8mm, z=4mm

Other Data

DUT Position : Touch
Separation : 0
Channel : Mid

Report No : TSC-102-05-AP-12 (SAR)



Report No : TSC-102-05-AP-12 (SAR)

1 gram SAR value : 0.743 W/kg
Area Scan Peak SAR : 0.815 W/kg
Zoom Scan Peak SAR : 1.611 W/kg


Report No : TSC-102-05-AP-12 (SAR)

Exposure Assessment Measurement Uncertainty

Source of Uncertainty	Tolerance Value	Probability Distribution	Divisor	c_i^{-1} (1-g)	Standard Uncertainty (1-g) %
Measurement System					
Probe Calibration	3.5	normal	1	1	3.5
Axial Isotropy	3.7	rectangular	$\sqrt{3}$	$(1-cp)^{1/2}$	1.5
Hemispherical Isotropy	10.9	rectangular	$\sqrt{3}$	\sqrt{cp}	4.4
Boundary Effect	1.0	rectangular	$\sqrt{3}$	1	0.6
Linearity	4.7	rectangular	$\sqrt{3}$	1	2.7
Detection Limit	1.0	rectangular	$\sqrt{3}$	1	0.6
Readout Electronics	1.0	normal	1	1	1.0
Response Time	0.8	rectangular	$\sqrt{3}$	1	0.5
Integration Time	1.7	rectangular	$\sqrt{3}$	1	1.0
RF Ambient Condition	3.0	rectangular	$\sqrt{3}$	1	1.7
Probe Positioner Mech.	0.4	rectangular	$\sqrt{3}$	1	0.2
Restriction					
Probe Positioning with respect to Phantom Shell	2.9	rectangular	$\sqrt{3}$	1	1.7
Extrapolation and Integration	3.7	rectangular	$\sqrt{3}$	1	2.1
Test Sample Positioning	4.0	normal	1	1	4.0
Device Holder Uncertainty	2.0	normal	1	1	2.0
Drift of Output Power	0.3	rectangular	$\sqrt{3}$	1	0.2
Phantom and Setup					
Phantom Uncertainty(shape & thickness tolerance)	3.4	rectangular	$\sqrt{3}$	1	2.0
Liquid Conductivity(target)	5.0	rectangular	$\sqrt{3}$	0.7	2.0
Liquid Conductivity(meas.)	2.1	normal	1	0.7	1.4
Liquid Permittivity(target)	5.0	rectangular	$\sqrt{3}$	0.6	1.7
Liquid Permittivity(meas.)	4.0	normal	1	0.6	2.4
Combined Uncertainty		RSS			9.6
Combined Uncertainty (coverage factor=2)		Normal (k=2)			19.3

Report No : TSC-102-05-AP-12 (SAR)

SAR-Z Axis
at Hotspot x:7.10 y:-7.24



Report No : TSC-102-05-AP-12 (SAR)

850MHz Band 5
High Channel Side Touch

SAR Test Report

Report Date : 17-May-2013
By Operator : 123
Measurement Date : 17-May-2013
Starting Time : 17-May-2013 11:05:58 AM
End Time : 17-May-2013 11:27:34 AM
Scanning Time : 1296 secs

Product Data

Device Name : Winmate
Serial No. : ALGIZ 10X
Type : Other
Model : ALGIZ 10X
Frequency : 835.00 MHz
Max. Transmit Pwr : 0.25 W
Drift Time : 0 min(s)
Length : 280 mm
Width : 175 mm
Depth : 36 mm
Antenna Type : Internal
Orientation : Touch
Power Drift-Start : 0.497 W/kg
Power Drift-Finish: 0.498 W/kg
Power Drift (%) : 0.232
Picture :

Phantom Data

Name : APREL-Uni
Type : Uni-Phantom
Size (mm) : 280 x 280 x 200
Serial No. : User Define
Location : Center
Description : Uni_Phantom

Tissue Data

Type : BODY
Serial No. : 835
Frequency : 835.00 MHz
Last Calib. Date : 15-May-2013
Temperature : 24.00 °C
Ambient Temp. : 24.00 °C
Humidity : 55.00 RH%
Epsilon : 53.00 F/m
Sigma : 0.99 S/m
Density : 1000.00 kg/cu. m
Probe Data
Name : Probe 257 - CHTL

Report No : TSC-102-05-AP-12 (SAR)

Model : E020
Type : E-Field Triangle
Serial No. : 257
Last Calib. Date : 14-Nov-2012
Frequency : 835.00 MHz
Duty Cycle Factor: 1
Conversion Factor: 6.9
Probe Sensitivity: 1.20 1.20 1.20 $\mu\text{V}/(\text{V}/\text{m})^2$
Compression Point: 95.00 mV
Offset : 1.56 mm


Measurement Data

Crest Factor : 1
Scan Type : Complete
Tissue Temp. : 24.00 °C
Ambient Temp. : 24.00 °C
Set-up Date : 17-May-2013
Set-up Time : 8:35:36 AM
Area Scan : 8x6x1 : Measurement x=15mm, y=15mm, z=4mm
Zoom Scan : 5x5x8 : Measurement x=8mm, y=8mm, z=4mm

Other Data

DUT Position : Touch
Separation : 0
Channel : High

Report No : TSC-102-05-AP-12 (SAR)



Report No : TSC-102-05-AP-12 (SAR)

1 gram SAR value : 0.746 W/kg
Area Scan Peak SAR : 0.821 W/kg
Zoom Scan Peak SAR : 1.611 W/kg


Report No : TSC-102-05-AP-12 (SAR)

Exposure Assessment Measurement Uncertainty

Source of Uncertainty	Tolerance Value	Probability Distribution	Divisor	c_i^{-1} (1-g)	Standard Uncertainty (1-g) %
Measurement System					
Probe Calibration	3.5	normal	1	1	3.5
Axial Isotropy	3.7	rectangular	$\sqrt{3}$	$(1-cp)^{1/2}$	1.5
Hemispherical Isotropy	10.9	rectangular	$\sqrt{3}$	\sqrt{cp}	4.4
Boundary Effect	1.0	rectangular	$\sqrt{3}$	1	0.6
Linearity	4.7	rectangular	$\sqrt{3}$	1	2.7
Detection Limit	1.0	rectangular	$\sqrt{3}$	1	0.6
Readout Electronics	1.0	normal	1	1	1.0
Response Time	0.8	rectangular	$\sqrt{3}$	1	0.5
Integration Time	1.7	rectangular	$\sqrt{3}$	1	1.0
RF Ambient Condition	3.0	rectangular	$\sqrt{3}$	1	1.7
Probe Positioner Mech.	0.4	rectangular	$\sqrt{3}$	1	0.2
Restriction					
Probe Positioning with respect to Phantom Shell	2.9	rectangular	$\sqrt{3}$	1	1.7
Extrapolation and Integration	3.7	rectangular	$\sqrt{3}$	1	2.1
Test Sample Positioning	4.0	normal	1	1	4.0
Device Holder Uncertainty	2.0	normal	1	1	2.0
Drift of Output Power	0.2	rectangular	$\sqrt{3}$	1	0.1
Phantom and Setup					
Phantom Uncertainty(shape & thickness tolerance)	3.4	rectangular	$\sqrt{3}$	1	2.0
Liquid Conductivity(target)	5.0	rectangular	$\sqrt{3}$	0.7	2.0
Liquid Conductivity(meas.)	2.1	normal	1	0.7	1.4
Liquid Permittivity(target)	5.0	rectangular	$\sqrt{3}$	0.6	1.7
Liquid Permittivity(meas.)	4.0	normal	1	0.6	2.4
Combined Uncertainty		RSS			9.6
Combined Uncertainty (coverage factor=2)		Normal (k=2)			19.3

Report No : TSC-102-05-AP-12 (SAR)

SAR-Z Axis
at Hotspot x:7.04 y:-7.22



Report No : TSC-102-05-AP-12 (SAR)

1900 MHz Band 2

Low Channel Rear Touch

SAR Test Report

Report Date : 16-May-2013
By Operator : 123
Measurement Date : 16-May-2013
Starting Time : 16-May-2013 11:22:11 AM
End Time : 16-May-2013 11:44:57 AM
Scanning Time : 1366 secs

Product Data

Device Name : Winmate
Serial No. : ALGIZ 10X
Type : Other
Model : ALGIZ 10X
Frequency : 1900.00 MHz
Max. Transmit Pwr : 0.25 W
Drift Time : 0 min(s)
Length : 280 mm
Width : 175 mm
Depth : 36 mm
Antenna Type : Internal
Orientation : Touch
Power Drift-Start : 1.062 W/kg
Power Drift-Finish: 1.115 W/kg
Power Drift (%) : 4.960
Picture :

Phantom Data

Name : APREL-Uni
Type : Uni-Phantom
Size (mm) : 280 x 280 x 200
Serial No. : User Define
Location : Center
Description : Uni_Phantom

Tissue Data

Type : BODY
Serial No. : 1900
Frequency : 1900.00 MHz
Last Calib. Date : 15-May-2013
Temperature : 24.00 °C
Ambient Temp. : 24.00 °C
Humidity : 55.00 RH%
Epsilon : 52.80 F/m
Sigma : 1.48 S/m
Density : 1000.00 kg/cu. m
Probe Data
Name : Probe 257 - CHTL

Report No : TSC-102-05-AP-12 (SAR)

Model : E020
Type : E-Field Triangle
Serial No. : 257
Last Calib. Date : 14-Nov-2012
Frequency : 1900.00 MHz
Duty Cycle Factor: 1
Conversion Factor: 5.9
Probe Sensitivity: 1.20 1.20 1.20 $\mu\text{V}/(\text{V}/\text{m})^2$
Compression Point: 95.00 mV
Offset : 1.56 mm


Measurement Data

Crest Factor : 1
Scan Type : Complete
Tissue Temp. : 24.00 °C
Ambient Temp. : 24.00 °C
Set-up Date : 16-May-2013
Set-up Time : 10:13:01 AM
Area Scan : 9x6x1 : Measurement x=15mm, y=15mm, z=4mm
Zoom Scan : 5x5x8 : Measurement x=8mm, y=8mm, z=4mm

Other Data

DUT Position : Touch
Separation : 0
Channel : Low

Report No : TSC-102-05-AP-12 (SAR)



Report No : TSC-102-05-AP-12 (SAR)

1 gram SAR value : 1.014 W/kg
Area Scan Peak SAR : 1.518 W/kg
Zoom Scan Peak SAR : 2.802 W/kg


Report No : TSC-102-05-AP-12 (SAR)

Exposure Assessment Measurement Uncertainty

Source of Uncertainty	Tolerance Value	Probability Distribution	Divisor	c_i^{-1} (1-g)	Standard Uncertainty (1-g) %
Measurement System					
Probe Calibration	3.5	normal	1	1	3.5
Axial Isotropy	3.7	rectangular	$\sqrt{3}$	$(1-cp)^{1/2}$	1.5
Hemispherical Isotropy	10.9	rectangular	$\sqrt{3}$	\sqrt{cp}	4.4
Boundary Effect	1.0	rectangular	$\sqrt{3}$	1	0.6
Linearity	4.7	rectangular	$\sqrt{3}$	1	2.7
Detection Limit	1.0	rectangular	$\sqrt{3}$	1	0.6
Readout Electronics	1.0	normal	1	1	1.0
Response Time	0.8	rectangular	$\sqrt{3}$	1	0.5
Integration Time	1.7	rectangular	$\sqrt{3}$	1	1.0
RF Ambient Condition	3.0	rectangular	$\sqrt{3}$	1	1.7
Probe Positioner Mech.	0.4	rectangular	$\sqrt{3}$	1	0.2
Restriction					
Probe Positioning with respect to Phantom Shell	2.9	rectangular	$\sqrt{3}$	1	1.7
Extrapolation and Integration	3.7	rectangular	$\sqrt{3}$	1	2.1
Test Sample Positioning	4.0	normal	1	1	4.0
Device Holder Uncertainty	2.0	normal	1	1	2.0
Drift of Output Power	5.0	rectangular	$\sqrt{3}$	1	7.5
Phantom and Setup					
Phantom Uncertainty(shape & thickness tolerance)	3.4	rectangular	$\sqrt{3}$	1	2.0
Liquid Conductivity(target)	5.0	rectangular	$\sqrt{3}$	0.7	2.0
Liquid Conductivity(meas.)	2.6	normal	1	0.7	1.8
Liquid Permittivity(target)	5.0	rectangular	$\sqrt{3}$	0.6	1.7
Liquid Permittivity(meas.)	0.9	normal	1	0.6	0.6
Combined Uncertainty		RSS			9.9
Combined Uncertainty (coverage factor=2)		Normal (k=2)			19.7

Report No : TSC-102-05-AP-12 (SAR)

SAR-Z Axis
at Hotspot x:23.06 y:-7.22



Report No : TSC-102-05-AP-12 (SAR)

1900 MHz Band 2
Mid Channel Side Touch

SAR Test Report

Report Date : 16-May-2013
By Operator : 123
Measurement Date : 16-May-2013
Starting Time : 16-May-2013 10:51:45 AM
End Time : 16-May-2013 11:14:43 AM
Scanning Time : 1378 secs

Product Data

Device Name : Winmate
Serial No. : ALGIZ 10X
Type : Other
Model : ALGIZ 10X
Frequency : 1900.00 MHz
Max. Transmit Pwr : 0.25 W
Drift Time : 0 min(s)
Length : 280 mm
Width : 175 mm
Depth : 36 mm
Antenna Type : Internal
Orientation : Touch
Power Drift-Start : 0.333 W/kg
Power Drift-Finish: 0.315 W/kg
Power Drift (%) : -5.484
Picture :

Phantom Data

Name : APREL-Uni
Type : Uni-Phantom
Size (mm) : 280 x 280 x 200
Serial No. : User Define
Location : Center
Description : Uni_Phantom

Tissue Data

Type : BODY
Serial No. : 1900
Frequency : 1900.00 MHz
Last Calib. Date : 15-May-2013
Temperature : 24.00 °C
Ambient Temp. : 24.00 °C
Humidity : 55.00 RH%
Epsilon : 52.80 F/m
Sigma : 1.48 S/m
Density : 1000.00 kg/cu. m
Probe Data
Name : Probe 257 - CHTL

Report No : TSC-102-05-AP-12 (SAR)

Model : E020
Type : E-Field Triangle
Serial No. : 257
Last Calib. Date : 14-Nov-2012
Frequency : 1900.00 MHz
Duty Cycle Factor: 1
Conversion Factor: 5.9
Probe Sensitivity: 1.20 1.20 1.20 $\mu\text{V}/(\text{V}/\text{m})^2$
Compression Point: 95.00 mV
Offset : 1.56 mm


Measurement Data

Crest Factor : 1
Scan Type : Complete
Tissue Temp. : 24.00 °C
Ambient Temp. : 24.00 °C
Set-up Date : 16-May-2013
Set-up Time : 10:13:01 AM
Area Scan : 9x6x1 : Measurement x=15mm, y=15mm, z=4mm
Zoom Scan : 5x5x8 : Measurement x=8mm, y=8mm, z=4mm

Other Data

DUT Position : Touch
Separation : 0
Channel : Mid

Report No : TSC-102-05-AP-12 (SAR)



Report No : TSC-102-05-AP-12 (SAR)

1 gram SAR value : 1.115 W/kg
Area Scan Peak SAR : 1.041 W/kg
Zoom Scan Peak SAR : 2.722 W/kg


Report No : TSC-102-05-AP-12 (SAR)

Exposure Assessment Measurement Uncertainty

Source of Uncertainty	Tolerance Value	Probability Distribution	Divisor	c_i^{-1} (1-g)	Standard Uncertainty (1-g) %
Measurement System					
Probe Calibration	3.5	normal	1	1	3.5
Axial Isotropy	3.7	rectangular	$\sqrt{3}$	$(1-cp)^{1/2}$	1.5
Hemispherical Isotropy	10.9	rectangular	$\sqrt{3}$	\sqrt{cp}	4.4
Boundary Effect	1.0	rectangular	$\sqrt{3}$	1	0.6
Linearity	4.7	rectangular	$\sqrt{3}$	1	2.7
Detection Limit	1.0	rectangular	$\sqrt{3}$	1	0.6
Readout Electronics	1.0	normal	1	1	1.0
Response Time	0.8	rectangular	$\sqrt{3}$	1	0.5
Integration Time	1.7	rectangular	$\sqrt{3}$	1	1.0
RF Ambient Condition	3.0	rectangular	$\sqrt{3}$	1	1.7
Probe Positioner Mech.	0.4	rectangular	$\sqrt{3}$	1	0.2
Restriction					
Probe Positioning with respect to Phantom Shell	2.9	rectangular	$\sqrt{3}$	1	1.7
Extrapolation and Integration	3.7	rectangular	$\sqrt{3}$	1	2.1
Test Sample Positioning	4.0	normal	1	1	4.0
Device Holder Uncertainty	2.0	normal	1	1	2.0
Drift of Output Power	5.5	rectangular	$\sqrt{3}$	1	3.2
Phantom and Setup					
Phantom Uncertainty(shape & thickness tolerance)	3.4	rectangular	$\sqrt{3}$	1	2.0
Liquid Conductivity(target)	5.0	rectangular	$\sqrt{3}$	0.7	2.0
Liquid Conductivity(meas.)	2.6	normal	1	0.7	1.8
Liquid Permittivity(target)	5.0	rectangular	$\sqrt{3}$	0.6	1.7
Liquid Permittivity(meas.)	0.9	normal	1	0.6	0.6
Combined Uncertainty		RSS			10.0
Combined Uncertainty (coverage factor=2)		Normal (k=2)			19.9

Report No : TSC-102-05-AP-12 (SAR)

SAR-Z Axis
at Hotspot x:7.10 y:15.78



Report No : TSC-102-05-AP-12 (SAR)

1900 MHz Band 2
High Channel Side Touch

SAR Test Report

Report Date : 16-May-2013
By Operator : 123
Measurement Date : 16-May-2013
Starting Time : 16-May-2013 01:23:35 PM
End Time : 16-May-2013 01:46:22 PM
Scanning Time : 1367 secs

Product Data

Device Name : Winmate
Serial No. : ALGIZ 10X
Type : Other
Model : ALGIZ 10X
Frequency : 1900.00 MHz
Max. Transmit Pwr : 0.25 W
Drift Time : 0 min(s)
Length : 280 mm
Width : 175 mm
Depth : 36 mm
Antenna Type : Internal
Orientation : Touch
Power Drift-Start : 0.973 W/kg
Power Drift-Finish: 0.896 W/kg
Power Drift (%) : -7.895
Picture :

Phantom Data

Name : APREL-Uni
Type : Uni-Phantom
Size (mm) : 280 x 280 x 200
Serial No. : User Define
Location : Center
Description : Uni_Phantom

Tissue Data

Type : BODY
Serial No. : 1900
Frequency : 1900.00 MHz
Last Calib. Date : 15-May-2013
Temperature : 24.00 °C
Ambient Temp. : 24.00 °C
Humidity : 55.00 RH%
Epsilon : 52.80 F/m
Sigma : 1.48 S/m
Density : 1000.00 kg/cu. m
Probe Data
Name : Probe 257 - CHTL
Model : E020

Report No : TSC-102-05-AP-12 (SAR)

Type : E-Field Triangle
Serial No. : 257
Last Calib. Date : 14-Nov-2012
Frequency : 1900.00 MHz
Duty Cycle Factor: 1
Conversion Factor: 5.9
Probe Sensitivity: 1.20 1.20 1.20 $\mu\text{V}/(\text{V}/\text{m})^2$
Compression Point: 95.00 mV
Offset : 1.56 mm


Measurement Data

Crest Factor : 1
Scan Type : Complete
Tissue Temp. : 24.00 °C
Ambient Temp. : 24.00 °C
Set-up Date : 16-May-2013
Set-up Time : 10:13:01 AM
Area Scan : 9x6x1 : Measurement x=15mm, y=15mm, z=4mm
Zoom Scan : 5x5x8 : Measurement x=8mm, y=8mm, z=4mm

Other Data

DUT Position : Touch
Separation : 0
Channel : High

Report No : TSC-102-05-AP-12 (SAR)



Report No : TSC-102-05-AP-12 (SAR)

1 gram SAR value : 1.104 W/kg
Area Scan Peak SAR : 1.543 W/kg
Zoom Scan Peak SAR : 2.702 W/kg


Report No : TSC-102-05-AP-12 (SAR)

Exposure Assessment Measurement Uncertainty

Source of Uncertainty	Tolerance Value	Probability Distribution	Divisor	c_i^{-1} (1-g)	Standard Uncertainty (1-g) %
Measurement System					
Probe Calibration	3.5	normal	1	1	3.5
Axial Isotropy	3.7	rectangular	$\sqrt{3}$	$(1-cp)^{1/2}$	1.5
Hemispherical Isotropy	10.9	rectangular	$\sqrt{3}$	\sqrt{cp}	4.4
Boundary Effect	1.0	rectangular	$\sqrt{3}$	1	0.6
Linearity	4.7	rectangular	$\sqrt{3}$	1	2.7
Detection Limit	1.0	rectangular	$\sqrt{3}$	1	0.6
Readout Electronics	1.0	normal	1	1	1.0
Response Time	0.8	rectangular	$\sqrt{3}$	1	0.5
Integration Time	1.7	rectangular	$\sqrt{3}$	1	1.0
RF Ambient Condition	3.0	rectangular	$\sqrt{3}$	1	1.7
Probe Positioner Mech.	0.4	rectangular	$\sqrt{3}$	1	0.2
Restriction					
Probe Positioning with respect to Phantom Shell	2.9	rectangular	$\sqrt{3}$	1	1.7
Extrapolation and Integration	3.7	rectangular	$\sqrt{3}$	1	2.1
Test Sample Positioning	4.0	normal	1	1	4.0
Device Holder Uncertainty	2.0	normal	1	1	2.0
Drift of Output Power	7.9	rectangular	$\sqrt{3}$	1	4.6
Phantom and Setup					
Phantom Uncertainty(shape & thickness tolerance)	3.4	rectangular	$\sqrt{3}$	1	2.0
Liquid Conductivity(target)	5.0	rectangular	$\sqrt{3}$	0.7	2.0
Liquid Conductivity(meas.)	2.6	normal	1	0.7	1.8
Liquid Permittivity(target)	5.0	rectangular	$\sqrt{3}$	0.6	1.7
Liquid Permittivity(meas.)	0.9	normal	1	0.6	0.6
Combined Uncertainty		RSS			10.5
Combined Uncertainty (coverage factor=2)		Normal (k=2)			21.0

Report No : TSC-102-05-AP-12 (SAR)

SAR-Z Axis
at Hotspot x:15.09 y:-7.24



Report No : TSC-102-05-AP-12 (SAR)

A.4.4 CDMA2000 Mode

850 MHz Band BC0 Low Channel Rear Touch

SAR Test Report

Report Date : 22-May-2013
By Operator : 123
Measurement Date : 22-May-2013
Starting Time : 22-May-2013 03:17:38 PM
End Time : 22-May-2013 03:40:37 PM
Scanning Time : 1379 secs

Product Data
Device Name : Winmate
Serial No. : ALGIZ 10X
Type : Other
Model : ALGIZ 10X
Frequency : 835.00 MHz
Max. Transmit Pwr : 0.25 W
Drift Time : 0 min(s)
Length : 280 mm
Width : 175 mm
Depth : 36 mm
Antenna Type : Internal
Orientation : Touch
Power Drift-Start : 0.335 W/kg
Power Drift-Finish: 0.345 W/kg
Power Drift (%) : 3.041
Picture :

Phantom Data
Name : APREL-Uni
Type : Uni-Phantom
Size (mm) : 280 x 280 x 200
Serial No. : User Define
Location : Center
Description : Uni_Phantom

Tissue Data
Type : BODY
Serial No. : 835
Frequency : 835.00 MHz
Last Calib. Date : 22-May-2013
Temperature : 24.00 °C
Ambient Temp. : 24.00 °C
Humidity : 55.00 RH%
Epsilon : 53.90 F/m
Sigma : 0.98 S/m
Density : 1000.00 kg/cu. m

Report No : TSC-102-05-AP-12 (SAR)

Probe Data

Name : Probe 257 - CHTL
Model : E020
Type : E-Field Triangle
Serial No. : 257
Last Calib. Date : 14-Nov-2012
Frequency : 835.00 MHz
Duty Cycle Factor: 1
Conversion Factor: 6.9
Probe Sensitivity: 1.20 1.20 1.20 $\mu\text{V}/(\text{V}/\text{m})^2$
Compression Point: 95.00 mV
Offset : 1.56 mm


Measurement Data

Crest Factor : 1
Scan Type : Complete
Tissue Temp. : 24.00 °C
Ambient Temp. : 24.00 °C
Set-up Date : 22-May-2013
Set-up Time : 9:05:36 AM
Area Scan : 9x6x1 : Measurement x=15mm, y=15mm, z=4mm
Zoom Scan : 5x5x8 : Measurement x=8mm, y=8mm, z=4mm

Other Data

DUT Position : Touch
Separation : 0
Channel : Low

Report No : TSC-102-05-AP-12 (SAR)



Report No : TSC-102-05-AP-12 (SAR)

1 gram SAR value : 0.405 W/kg
Area Scan Peak SAR : 0.488 W/kg
Zoom Scan Peak SAR : 0.820 W/kg


Report No : TSC-102-05-AP-12 (SAR)

Exposure Assessment Measurement Uncertainty

Source of Uncertainty	Tolerance Value	Probability Distribution	Divisor	c_i^{-1} (1-g)	Standard Uncertainty (1-g) %
Measurement System					
Probe Calibration	3.5	normal	1	1	3.5
Axial Isotropy	3.7	rectangular	$\sqrt{3}$	$(1-cp)^{1/2}$	1.5
Hemispherical Isotropy	10.9	rectangular	$\sqrt{3}$	\sqrt{cp}	4.4
Boundary Effect	1.0	rectangular	$\sqrt{3}$	1	0.6
Linearity	4.7	rectangular	$\sqrt{3}$	1	2.7
Detection Limit	1.0	rectangular	$\sqrt{3}$	1	0.6
Readout Electronics	1.0	normal	1	1	1.0
Response Time	0.8	rectangular	$\sqrt{3}$	1	0.5
Integration Time	1.7	rectangular	$\sqrt{3}$	1	1.0
RF Ambient Condition	3.0	rectangular	$\sqrt{3}$	1	1.7
Probe Positioner Mech.	0.4	rectangular	$\sqrt{3}$	1	0.2
Restriction					
Probe Positioning with respect to Phantom Shell	2.9	rectangular	$\sqrt{3}$	1	1.7
Extrapolation and Integration	3.7	rectangular	$\sqrt{3}$	1	2.1
Test Sample Positioning	4.0	normal	1	1	4.0
Device Holder Uncertainty	2.0	normal	1	1	2.0
Drift of Output Power	3.0	rectangular	$\sqrt{3}$	1	1.8
Phantom and Setup					
Phantom Uncertainty(shape & thickness tolerance)	3.4	rectangular	$\sqrt{3}$	1	2.0
Liquid Conductivity(target)	5.0	rectangular	$\sqrt{3}$	0.7	2.0
Liquid Conductivity(meas.)	1.0	normal	1	0.7	0.7
Liquid Permittivity(target)	5.0	rectangular	$\sqrt{3}$	0.6	1.7
Liquid Permittivity(meas.)	2.4	normal	1	0.6	1.4
Combined Uncertainty		RSS			9.5
Combined Uncertainty (coverage factor=2)		Normal (k=2)			19.1

Report No : TSC-102-05-AP-12 (SAR)

SAR-Z Axis
at Hotspot x:8.09 y:-7.24



Report No : TSC-102-05-AP-12 (SAR)

850 MHz Band BC0
Mid Channel Rear Touch

SAR Test Report

Report Date : 22-May-2013
By Operator : 123
Measurement Date : 22-May-2013
Starting Time : 22-May-2013 04:05:50 PM
End Time : 22-May-2013 04:28:27 PM
Scanning Time : 1357 secs

Product Data
Device Name : Winmate
Serial No. : ALGIZ 10X
Type : Other
Model : ALGIZ 10X
Frequency : 835.00 MHz
Max. Transmit Pwr : 0.25 W
Drift Time : 0 min(s)
Length : 280 mm
Width : 175 mm
Depth : 36 mm
Antenna Type : Internal
Orientation : Touch
Power Drift-Start : 0.370 W/kg
Power Drift-Finish: 0.379 W/kg
Power Drift (%) : 2.556
Picture :

Phantom Data
Name : APREL-Uni
Type : Uni-Phantom
Size (mm) : 280 x 280 x 200
Serial No. : User Define
Location : Center
Description : Uni_Phantom

Tissue Data
Type : BODY
Serial No. : 835
Frequency : 835.00 MHz
Last Calib. Date : 22-May-2013
Temperature : 24.00 °C
Ambient Temp. : 24.00 °C
Humidity : 55.00 RH%
Epsilon : 53.90 F/m
Sigma : 0.98 S/m
Density : 1000.00 kg/cu. m
Probe Data
Name : Probe 257 - CHTL
Model : E020
Type : E-Field Triangle

Report No : TSC-102-05-AP-12 (SAR)

Serial No. : 257
Last Calib. Date : 14-Nov-2012
Frequency : 835.00 MHz
Duty Cycle Factor: 1
Conversion Factor: 6.9
Probe Sensitivity: 1.20 1.20 1.20 $\mu\text{V}/(\text{V}/\text{m})^2$
Compression Point: 95.00 mV
Offset : 1.56 mm


Measurement Data

Crest Factor : 1
Scan Type : Complete
Tissue Temp. : 24.00 °C
Ambient Temp. : 24.00 °C
Set-up Date : 22-May-2013
Set-up Time : 9:05:36 AM
Area Scan : 9x6x1 : Measurement x=15mm, y=15mm, z=4mm
Zoom Scan : 5x5x8 : Measurement x=8mm, y=8mm, z=4mm

Other Data

DUT Position : Touch
Separation : 0
Channel : Mid

Report No : TSC-102-05-AP-12 (SAR)



Report No : TSC-102-05-AP-12 (SAR)

1 gram SAR value : 0.381 W/kg
Area Scan Peak SAR : 0.464 W/kg
Zoom Scan Peak SAR : 0.860 W/kg


Report No : TSC-102-05-AP-12 (SAR)

Exposure Assessment Measurement Uncertainty

Source of Uncertainty	Tolerance Value	Probability Distribution	Divisor	c_i^{-1} (1-g)	Standard Uncertainty (1-g) %
Measurement System					
Probe Calibration	3.5	normal	1	1	3.5
Axial Isotropy	3.7	rectangular	$\sqrt{3}$	$(1-cp)^{1/2}$	1.5
Hemispherical Isotropy	10.9	rectangular	$\sqrt{3}$	\sqrt{cp}	4.4
Boundary Effect	1.0	rectangular	$\sqrt{3}$	1	0.6
Linearity	4.7	rectangular	$\sqrt{3}$	1	2.7
Detection Limit	1.0	rectangular	$\sqrt{3}$	1	0.6
Readout Electronics	1.0	normal	1	1	1.0
Response Time	0.8	rectangular	$\sqrt{3}$	1	0.5
Integration Time	1.7	rectangular	$\sqrt{3}$	1	1.0
RF Ambient Condition	3.0	rectangular	$\sqrt{3}$	1	1.7
Probe Positioner Mech.	0.4	rectangular	$\sqrt{3}$	1	0.2
Restriction					
Probe Positioning with respect to Phantom Shell	2.9	rectangular	$\sqrt{3}$	1	1.7
Extrapolation and Integration	3.7	rectangular	$\sqrt{3}$	1	2.1
Test Sample Positioning	4.0	normal	1	1	4.0
Device Holder Uncertainty	2.0	normal	1	1	2.0
Drift of Output Power	2.6	rectangular	$\sqrt{3}$	1	1.5
Phantom and Setup					
Phantom Uncertainty(shape & thickness tolerance)	3.4	rectangular	$\sqrt{3}$	1	2.0
Liquid Conductivity(target)	5.0	rectangular	$\sqrt{3}$	0.7	2.0
Liquid Conductivity(meas.)	1.0	normal	1	0.7	0.7
Liquid Permittivity(target)	5.0	rectangular	$\sqrt{3}$	0.6	1.7
Liquid Permittivity(meas.)	2.4	normal	1	0.6	1.4
Combined Uncertainty		RSS			9.5
Combined Uncertainty (coverage factor=2)		Normal (k=2)			19.0

Report No : TSC-102-05-AP-12 (SAR)

SAR-Z Axis
at Hotspot x:8.09 y:-7.24



Report No : TSC-102-05-AP-12 (SAR)

850 MHz Band BC0
High Channel Rear Touch

SAR Test Report

Report Date : 22-May-2013
By Operator : 123
Measurement Date : 22-May-2013
Starting Time : 22-May-2013 03:41:16 PM
End Time : 22-May-2013 04:04:00 PM
Scanning Time : 1364 secs

Product Data

Device Name : Winmate
Serial No. : ALGIZ 10X
Type : Other
Model : ALGIZ 10X
Frequency : 835.00 MHz
Max. Transmit Pwr : 0.25 W
Drift Time : 0 min(s)
Length : 280 mm
Width : 175 mm
Depth : 36 mm
Antenna Type : Internal
Orientation : Touch
Power Drift-Start : 0.356 W/kg
Power Drift-Finish: 0.376 W/kg
Power Drift (%) : 5.656
Picture :

Phantom Data

Name : APREL-Uni
Type : Uni-Phantom
Size (mm) : 280 x 280 x 200
Serial No. : User Define
Location : Center
Description : Uni_Phantom

Tissue Data

Type : BODY
Serial No. : 835
Frequency : 835.00 MHz
Last Calib. Date : 22-May-2013
Temperature : 24.00 °C
Ambient Temp. : 24.00 °C
Humidity : 55.00 RH%
Epsilon : 53.90 F/m
Sigma : 0.98 S/m
Density : 1000.00 kg/cu. m
Probe Data
Name : Probe 257 - CHTL

Report No : TSC-102-05-AP-12 (SAR)

Model : E020
Type : E-Field Triangle
Serial No. : 257
Last Calib. Date : 14-Nov-2012
Frequency : 835.00 MHz
Duty Cycle Factor: 1
Conversion Factor: 6.9
Probe Sensitivity: 1.20 1.20 1.20 $\mu\text{V}/(\text{V}/\text{m})^2$
Compression Point: 95.00 mV
Offset : 1.56 mm


Measurement Data

Crest Factor : 1
Scan Type : Complete
Tissue Temp. : 24.00 °C
Ambient Temp. : 24.00 °C
Set-up Date : 22-May-2013
Set-up Time : 9:05:36 AM
Area Scan : 9x6x1 : Measurement x=15mm, y=15mm, z=4mm
Zoom Scan : 5x5x8 : Measurement x=8mm, y=8mm, z=4mm

Other Data

DUT Position : Touch
Separation : 0
Channel : High

Report No : TSC-102-05-AP-12 (SAR)



Report No : TSC-102-05-AP-12 (SAR)

1 gram SAR value : 0.421 W/kg
Area Scan Peak SAR : 0.463 W/kg
Zoom Scan Peak SAR : 0.910 W/kg


Report No : TSC-102-05-AP-12 (SAR)

Exposure Assessment Measurement Uncertainty

Source of Uncertainty	Tolerance Value	Probability Distribution	Divisor	c_i^{-1} (1-g)	Standard Uncertainty (1-g) %
Measurement System					
Probe Calibration	3.5	normal	1	1	3.5
Axial Isotropy	3.7	rectangular	$\sqrt{3}$	$(1-cp)^{1/2}$	1.5
Hemispherical Isotropy	10.9	rectangular	$\sqrt{3}$	\sqrt{cp}	4.4
Boundary Effect	1.0	rectangular	$\sqrt{3}$	1	0.6
Linearity	4.7	rectangular	$\sqrt{3}$	1	2.7
Detection Limit	1.0	rectangular	$\sqrt{3}$	1	0.6
Readout Electronics	1.0	normal	1	1	1.0
Response Time	0.8	rectangular	$\sqrt{3}$	1	0.5
Integration Time	1.7	rectangular	$\sqrt{3}$	1	1.0
RF Ambient Condition	3.0	rectangular	$\sqrt{3}$	1	1.7
Probe Positioner Mech.	0.4	rectangular	$\sqrt{3}$	1	0.2
Restriction					
Probe Positioning with respect to Phantom Shell	2.9	rectangular	$\sqrt{3}$	1	1.7
Extrapolation and Integration	3.7	rectangular	$\sqrt{3}$	1	2.1
Test Sample Positioning	4.0	normal	1	1	4.0
Device Holder Uncertainty	2.0	normal	1	1	2.0
Drift of Output Power	5.7	rectangular	$\sqrt{3}$	1	3.3
Phantom and Setup					
Phantom Uncertainty(shape & thickness tolerance)	3.4	rectangular	$\sqrt{3}$	1	2.0
Liquid Conductivity(target)	5.0	rectangular	$\sqrt{3}$	0.7	2.0
Liquid Conductivity(meas.)	1.0	normal	1	0.7	0.7
Liquid Permittivity(target)	5.0	rectangular	$\sqrt{3}$	0.6	1.7
Liquid Permittivity(meas.)	2.4	normal	1	0.6	1.4
Combined Uncertainty		RSS			9.9
Combined Uncertainty (coverage factor=2)		Normal (k=2)			19.9

Report No : TSC-102-05-AP-12 (SAR)

SAR-Z Axis
at Hotspot x:8.09 y:-7.24



Report No : TSC-102-05-AP-12 (SAR)

1900 MHz BC1 Band
Low Channel Rear Touch

SAR Test Report

Report Date : 23-May-2013
By Operator : 123
Measurement Date : 23-May-2013
Starting Time : 23-May-2013 10:00:17 AM
End Time : 23-May-2013 10:22:25 AM
Scanning Time : 1328 secs

Product Data

Device Name : Winmate
Serial No. : ALGIZ 10X
Type : Other
Model : ALGIZ 10X
Frequency : 1900.00 MHz
Max. Transmit Pwr : 1 W
Drift Time : 0 min(s)
Length : 280 mm
Width : 175 mm
Depth : 36 mm
Antenna Type : Internal
Orientation : Touch
Power Drift-Start : 0.309 W/kg
Power Drift-Finish: 0.310 W/kg
Power Drift (%) : 0.391
Picture :

Phantom Data

Name : APREL-Uni
Type : Uni-Phantom
Size (mm) : 280 x 280 x 200
Serial No. : User Define
Location : Center
Description : Uni_Phantom

Tissue Data

Type : BODY
Serial No. : 1900
Frequency : 1900.00 MHz
Last Calib. Date : 22-May-2013
Temperature : 24.00 °C
Ambient Temp. : 24.00 °C
Humidity : 55.00 RH%
Epsilon : 52.10 F/m
Sigma : 1.49 S/m
Density : 1000.00 kg/cu. m
Probe Data
Name : Probe 257 - CHTL

Report No : TSC-102-05-AP-12 (SAR)

Model : E020
Type : E-Field Triangle
Serial No. : 257
Last Calib. Date : 14-Nov-2012
Frequency : 1900.00 MHz
Duty Cycle Factor: 1
Conversion Factor: 5.9
Probe Sensitivity: 1.20 1.20 1.20 $\mu\text{V}/(\text{V}/\text{m})^2$
Compression Point: 95.00 mV
Offset : 1.56 mm


Measurement Data

Crest Factor : 1
Scan Type : Complete
Tissue Temp. : 24.00 °C
Ambient Temp. : 24.00 °C
Set-up Date : 23-May-2013
Set-up Time : 8:34:25 AM
Area Scan : 8x6x1 : Measurement x=15mm, y=15mm, z=4mm
Zoom Scan : 5x5x8 : Measurement x=8mm, y=8mm, z=4mm

Other Data

DUT Position : Touch
Separation : 0
Channel : Low

Report No : TSC-102-05-AP-12 (SAR)



Report No : TSC-102-05-AP-12 (SAR)

1 gram SAR value : 0.408 W/kg
Area Scan Peak SAR : 0.453 W/kg
Zoom Scan Peak SAR : 0.850 W/kg


Report No : TSC-102-05-AP-12 (SAR)

Exposure Assessment Measurement Uncertainty

Source of Uncertainty	Tolerance Value	Probability Distribution	Divisor	c_i^{-1} (1-g)	Standard Uncertainty (1-g) %
Measurement System					
Probe Calibration	3.5	normal	1	1	3.5
Axial Isotropy	3.7	rectangular	$\sqrt{3}$	$(1-cp)^{1/2}$	1.5
Hemispherical Isotropy	10.9	rectangular	$\sqrt{3}$	\sqrt{cp}	4.4
Boundary Effect	1.0	rectangular	$\sqrt{3}$	1	0.6
Linearity	4.7	rectangular	$\sqrt{3}$	1	2.7
Detection Limit	1.0	rectangular	$\sqrt{3}$	1	0.6
Readout Electronics	1.0	normal	1	1	1.0
Response Time	0.8	rectangular	$\sqrt{3}$	1	0.5
Integration Time	1.7	rectangular	$\sqrt{3}$	1	1.0
RF Ambient Condition	3.0	rectangular	$\sqrt{3}$	1	1.7
Probe Positioner Mech.	0.4	rectangular	$\sqrt{3}$	1	0.2
Restriction					
Probe Positioning with respect to Phantom Shell	2.9	rectangular	$\sqrt{3}$	1	1.7
Extrapolation and Integration	3.7	rectangular	$\sqrt{3}$	1	2.1
Test Sample Positioning	4.0	normal	1	1	4.0
Device Holder Uncertainty	2.0	normal	1	1	2.0
Drift of Output Power	0.4	rectangular	$\sqrt{3}$	1	0.2
Phantom and Setup					
Phantom Uncertainty(shape & thickness tolerance)	3.4	rectangular	$\sqrt{3}$	1	2.0
Liquid Conductivity(target)	5.0	rectangular	$\sqrt{3}$	0.7	2.0
Liquid Conductivity(meas.)	2.0	normal	1	0.7	1.4
Liquid Permittivity(target)	5.0	rectangular	$\sqrt{3}$	0.6	1.7
Liquid Permittivity(meas.)	2.3	normal	1	0.6	1.4
Combined Uncertainty		RSS			9.4
Combined Uncertainty (coverage factor=2)		Normal (k=2)			18.9

Report No : TSC-102-05-AP-12 (SAR)

SAR-Z Axis
at Hotspot x:7.12 y:-7.24



Report No : TSC-102-05-AP-12 (SAR)

1900 MHz BC1 Band
Mid Channel Rear Touch

SAR Test Report

Report Date : 22-May-2013
By Operator : 123
Measurement Date : 22-May-2013
Starting Time : 22-May-2013 04:32:26 PM
End Time : 22-May-2013 04:54:16 PM
Scanning Time : 1310 secs

Product Data

Device Name : Winmate
Serial No. : ALGIZ 10X
Type : Other
Model : ALGIZ 10X
Frequency : 1900.00 MHz
Max. Transmit Pwr : 1 W
Drift Time : 0 min(s)
Length : 280 mm
Width : 175 mm
Depth : 36 mm
Antenna Type : Internal
Orientation : Touch
Power Drift-Start : 0.488 W/kg
Power Drift-Finish: 0.454 W/kg
Power Drift (%) : -6.906
Picture :

Phantom Data

Name : APREL-Uni
Type : Uni-Phantom
Size (mm) : 280 x 280 x 200
Serial No. : User Define
Location : Center
Description : Uni_Phantom

Tissue Data

Type : BODY
Serial No. : 1900
Frequency : 1900.00 MHz
Last Calib. Date : 22-May-2013
Temperature : 24.00 °C
Ambient Temp. : 24.00 °C
Humidity : 55.00 RH%
Epsilon : 52.10 F/m
Sigma : 1.49 S/m
Density : 1000.00 kg/cu. m
Probe Data
Name : Probe 257 - CHTL

Report No : TSC-102-05-AP-12 (SAR)

Model : E020
Type : E-Field Triangle
Serial No. : 257
Last Calib. Date : 14-Nov-2012
Frequency : 1900.00 MHz
Duty Cycle Factor: 1
Conversion Factor: 5.9
Probe Sensitivity: 1.20 1.20 1.20 $\mu\text{V}/(\text{V}/\text{m})^2$
Compression Point: 95.00 mV
Offset : 1.56 mm


Measurement Data

Crest Factor : 1
Scan Type : Complete
Tissue Temp. : 24.00 °C
Ambient Temp. : 24.00 °C
Set-up Date : 22-May-2013
Set-up Time : 4:13:01 PM
Area Scan : 8x6x1 : Measurement x=15mm, y=15mm, z=4mm
Zoom Scan : 5x5x8 : Measurement x=8mm, y=8mm, z=4mm

Other Data

DUT Position : Touch
Separation : 0
Channel : Mid

Report No : TSC-102-05-AP-12 (SAR)



Report No : TSC-102-05-AP-12 (SAR)

1 gram SAR value : 0.520 W/kg
Area Scan Peak SAR : 0.560 W/kg
Zoom Scan Peak SAR : 1.150 W/kg


Report No : TSC-102-05-AP-12 (SAR)

Exposure Assessment Measurement Uncertainty

Source of Uncertainty	Tolerance Value	Probability Distribution	Divisor	c_i^{-1} (1-g)	Standard Uncertainty (1-g) %
Measurement System					
Probe Calibration	3.5	normal	1	1	3.5
Axial Isotropy	3.7	rectangular	$\sqrt{3}$	$(1-cp)^{1/2}$	1.5
Hemispherical Isotropy	10.9	rectangular	$\sqrt{3}$	\sqrt{cp}	4.4
Boundary Effect	1.0	rectangular	$\sqrt{3}$	1	0.6
Linearity	4.7	rectangular	$\sqrt{3}$	1	2.7
Detection Limit	1.0	rectangular	$\sqrt{3}$	1	0.6
Readout Electronics	1.0	normal	1	1	1.0
Response Time	0.8	rectangular	$\sqrt{3}$	1	0.5
Integration Time	1.7	rectangular	$\sqrt{3}$	1	1.0
RF Ambient Condition	3.0	rectangular	$\sqrt{3}$	1	1.7
Probe Positioner Mech.	0.4	rectangular	$\sqrt{3}$	1	0.2
Restriction					
Probe Positioning with respect to Phantom Shell	2.9	rectangular	$\sqrt{3}$	1	1.7
Extrapolation and Integration	3.7	rectangular	$\sqrt{3}$	1	2.1
Test Sample Positioning	4.0	normal	1	1	4.0
Device Holder Uncertainty	2.0	normal	1	1	2.0
Drift of Output Power	6.9	rectangular	$\sqrt{3}$	1	4.0
Phantom and Setup					
Phantom Uncertainty(shape & thickness tolerance)	3.4	rectangular	$\sqrt{3}$	1	2.0
Liquid Conductivity(target)	5.0	rectangular	$\sqrt{3}$	0.7	2.0
Liquid Conductivity(meas.)	2.0	normal	1	0.7	1.4
Liquid Permittivity(target)	5.0	rectangular	$\sqrt{3}$	0.6	1.7
Liquid Permittivity(meas.)	2.3	normal	1	0.6	1.4
Combined Uncertainty		RSS			10.3
Combined Uncertainty (coverage factor=2)		Normal (k=2)			20.5

Report No : TSC-102-05-AP-12 (SAR)

SAR-Z Axis
at Hotspot x:15.09 y:-7.24



Report No : TSC-102-05-AP-12 (SAR)

1900 MHz BC1 Band
High Channel Rear Touch

SAR Test Report

Report Date : 23-May-2013
By Operator : 123
Measurement Date : 23-May-2013
Starting Time : 23-May-2013 09:09:44 AM
End Time : 23-May-2013 09:31:48 AM
Scanning Time : 1324 secs

Product Data

Device Name : Winmate
Serial No. : ALGIZ 10X
Type : Other
Model : ALGIZ 10X
Frequency : 1900.00 MHz
Max. Transmit Pwr : 1 W
Drift Time : 0 min(s)
Length : 280 mm
Width : 175 mm
Depth : 36 mm
Antenna Type : Internal
Orientation : Touch
Power Drift-Start : 0.395 W/kg
Power Drift-Finish: 0.388 W/kg
Power Drift (%) : -1.624
Picture :

Phantom Data

Name : APREL-Uni
Type : Uni-Phantom
Size (mm) : 280 x 280 x 200
Serial No. : User Define
Location : Center
Description : Uni_Phantom

Tissue Data

Type : BODY
Serial No. : 1900
Frequency : 1900.00 MHz
Last Calib. Date : 22-May-2013
Temperature : 24.00 °C
Ambient Temp. : 24.00 °C
Humidity : 55.00 RH%
Epsilon : 52.10 F/m
Sigma : 1.49 S/m
Density : 1000.00 kg/cu. m
Probe Data
Name : Probe 257 - CHTL

Report No : TSC-102-05-AP-12 (SAR)

Model : E020
Type : E-Field Triangle
Serial No. : 257
Last Calib. Date : 14-Nov-2012
Frequency : 1900.00 MHz
Duty Cycle Factor: 1
Conversion Factor: 5.9
Probe Sensitivity: 1.20 1.20 1.20 $\mu\text{V}/(\text{V}/\text{m})^2$
Compression Point: 95.00 mV
Offset : 1.56 mm


Measurement Data

Crest Factor : 1
Scan Type : Complete
Tissue Temp. : 24.00 °C
Ambient Temp. : 24.00 °C
Set-up Date : 23-May-2013
Set-up Time : 8:34:25 AM
Area Scan : 8x6x1 : Measurement x=15mm, y=15mm, z=4mm
Zoom Scan : 5x5x8 : Measurement x=8mm, y=8mm, z=4mm

Other Data

DUT Position : Touch
Separation : 0
Channel : High

Report No : TSC-102-05-AP-12 (SAR)



Report No : TSC-102-05-AP-12 (SAR)

1 gram SAR value : 0.491 W/kg
Area Scan Peak SAR : 0.514 W/kg
Zoom Scan Peak SAR : 1.030 W/kg


Report No : TSC-102-05-AP-12 (SAR)

Exposure Assessment Measurement Uncertainty

Source of Uncertainty	Tolerance Value	Probability Distribution	Divisor	c_i^{-1} (1-g)	Standard Uncertainty (1-g) %
Measurement System					
Probe Calibration	3.5	normal	1	1	3.5
Axial Isotropy	3.7	rectangular	$\sqrt{3}$	$(1-cp)^{1/2}$	1.5
Hemispherical Isotropy	10.9	rectangular	$\sqrt{3}$	\sqrt{cp}	4.4
Boundary Effect	1.0	rectangular	$\sqrt{3}$	1	0.6
Linearity	4.7	rectangular	$\sqrt{3}$	1	2.7
Detection Limit	1.0	rectangular	$\sqrt{3}$	1	0.6
Readout Electronics	1.0	normal	1	1	1.0
Response Time	0.8	rectangular	$\sqrt{3}$	1	0.5
Integration Time	1.7	rectangular	$\sqrt{3}$	1	1.0
RF Ambient Condition	3.0	rectangular	$\sqrt{3}$	1	1.7
Probe Positioner Mech.	0.4	rectangular	$\sqrt{3}$	1	0.2
Restriction					
Probe Positioning with respect to Phantom Shell	2.9	rectangular	$\sqrt{3}$	1	1.7
Extrapolation and Integration	3.7	rectangular	$\sqrt{3}$	1	2.1
Test Sample Positioning	4.0	normal	1	1	4.0
Device Holder Uncertainty	2.0	normal	1	1	2.0
Drift of Output Power	1.6	rectangular	$\sqrt{3}$	1	0.9
Phantom and Setup					
Phantom Uncertainty(shape & thickness tolerance)	3.4	rectangular	$\sqrt{3}$	1	2.0
Liquid Conductivity(target)	5.0	rectangular	$\sqrt{3}$	0.7	2.0
Liquid Conductivity(meas.)	2.0	normal	1	0.7	1.4
Liquid Permittivity(target)	5.0	rectangular	$\sqrt{3}$	0.6	1.7
Liquid Permittivity(meas.)	2.3	normal	1	0.6	1.4
Combined Uncertainty		RSS			9.5
Combined Uncertainty (coverage factor=2)		Normal (k=2)			19.0

Report No : TSC-102-05-AP-12 (SAR)

SAR-Z Axis
at Hotspot x:7.04 y:-7.22



Report No : TSC-102-05-AP-12 (SAR)

A. 4.5 Dipole Calibration Data

NCL CALIBRATION LABORATORIES

Calibration File No: DC-1471
Project Number: CHT-dipole-2450B-cal-5703

CERTIFICATE OF CALIBRATION

It is certified that the equipment identified below has been calibrated in the
NCL CALIBRATION LABORATORIES by qualified personnel following recognized
procedures and using transfer standards traceable to NRC/NIST.

CHTL Validation Dipole

Manufacturer: APREL Laboratories
Part number: ALS-D-2450-S-2
Frequency: 2450 MHz
Serial No: 2450-220-00751

Customer: CHTL

Calibrated: 14th November 2012
Released on: 14th November 2012

This Calibration Certificate is Incomplete Unless Accompanied with the Calibration Results Summary

Released By: 
Art Brennan, Quality Manager

NCL CALIBRATION LABORATORIES

303 Terry Fox Drive, Suite 102
Kanata, Ontario
CANADA K2K 3J1

Division of APREL
TEL: (613) 435-8300
FAX: (613) 435-8306

Report No : TSC-102-05-AP-12 (SAR)

NCL Calibration Laboratories

Division of APREL Laboratories.

Conditions

Dipole 2450, 220-00751 was a re-calibration.

Ambient Temperature of the Laboratory: 22 °C +/- 0.5°C
Temperature of the Tissue: 21 °C +/- 0.5°C

We the undersigned attest that to the best of our knowledge the calibration of this subject has been accurately conducted and that all information contained within the results pages have been reviewed for accuracy.



Art Brennan, Quality Manager



Constantin Teodorian, Test Engineer

This page has been reviewed for content and attested to by signature within this document.

Report No : TSC-102-05-AP-12 (SAR)

NCL Calibration Laboratories

Division of APREL Laboratories.

Calibration Results Summary

The following results relate the Calibrated Dipole and should be used as a quick reference for the user.

Mechanical Dimensions (APREL)

Length: 51.5 mm
 Height: 30.4 mm


Electrical Specification

Test	Result
S11 R/L	-27.845 dB
SWR	1.085 U
Impedance	47.510 Ω

System Validation Results

Frequency	1 Gram	10 Gram	Peak
2450 MHz	50.754	23.857	101.89

Feed power 30dbm.



This page has been reviewed for content and attested to by signature within this document.

Report No : TSC-102-05-AP-12 (SAR)

NCL Calibration Laboratories

Division of APREL Laboratories.

Introduction

This Calibration Report has been produced in line with the SSI Dipole Calibration Procedure SSI-TP-018-ALSAS. The results contained within this report are for Validation Dipole 2450-220-00751. The calibration routine consisted of a three-step process. Step 1 was a mechanical verification of the dipole to ensure that it meets the mechanical specifications. Step 2 was an Electrical Calibration for the Validation Dipole, where the SWR, Impedance, and the Return loss were assessed. Step 3 involved a System Validation using the ALSAS-10U, along with APREL E-020 130 MHz to 26 GHz E-Field Probe Serial Number 212.

References

SSI-TP-018-ALSAS Dipole Calibration Procedure
SSI-TP-016 Tissue Calibration Procedure
IEEE 1528 "Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Body Due to Wireless Communications Devices: Experimental Techniques"

Conditions

Dipole 2450-220-00751 was a re-calibration.

Ambient Temperature of the Laboratory: 22 °C +/- 0.5°C
Temperature of the Tissue: 20 °C +/- 0.5°C

Dipole Calibration uncertainty

The calibration uncertainty for the dipole is made up of various parameters presented below.

Mechanical	1%
Positioning Error	1.22%
Electrical	1.7%
Tissue	2.2%
Dipole Validation	2.2%
TOTAL	8.32% (16.64% K=2)

This page has been reviewed for content and attested to by signature within this document.

4

Report No : TSC-102-05-AP-12 (SAR)

NCL Calibration Laboratories
Division of APREL Laboratories.

Dipole Calibration Results

Mechanical Verification

APREL Length	APREL Height	Measured Length	Measured Height
51.5 mm	30.4 mm	52.4 mm	30.6 mm

Tissue Validation

Body Tissue 2450 MHz	Measured
Dielectric constant, ϵ_r	51.23
Conductivity, σ [S/m]	1.92

This page has been reviewed for content and attested to by signature within this document.

5

Report No : TSC-102-05-AP-12 (SAR)


NCL Calibration Laboratories
 Division of APREL Laboratories.

Electrical Calibration

Test	Result
S11 R/L	-27.845 dB
SWR	1.085 U
Impedance	47.510 Ω

The Following Graphs are the results as displayed on the Vector Network Analyzer.

S11 Parameter Return Loss



This page has been reviewed for content and attested to by signature within this document.


Report No : TSC-102-05-AP-12 (SAR)

NCL Calibration Laboratories
 Division of APREL Laboratories.

SWR

S11 FORWARD REFLECTION

SWR ▶ REF-1.000 U 1.000 U/DIV



CH 1 - S11
 5.0504 mm REF
 0.000 dB OFFSET
 0.00° OFFSET

▶ MARKER 2
 2.450000 GHz
 1.005 U

MARKER TO MAX
 MARKER TO MIN

1 2.359346 GHz
 1.226 U

3 2.506884 GHz
 1.225 U

MARKER READOUT
 FUNCTIONS

This page has been reviewed for content and attested to by signature within this document.


7

Report No : TSC-102-05-AP-12 (SAR)

NCL Calibration Laboratories
 Division of APREL Laboratories.

Smith Chart Dipole Impedance

S11 FORWARD REFLECTION
 IMPEDANCE



CH 1 - S11
 5.0504 nV REF
 0.000 dB OFFSET
 0.00° OFFSET

▶ MARKER 2
 2.450000 GHz
 47.510 R
 -2.852 jR

MARKER TO MAX
 MARKER TO MIN

- 1 2.359346 GHz
59.778 R
4.707 jR
- 3 2.506884 GHz
41.587 R
3.699 jR

MARKER READOUT
 FUNCTIONS

Test Equipment

The test equipment used during Probe Calibration, manufacturer, model number and, current calibration status are listed and located on the main APREL server R:\NCL\Calibration Equipment\Instrument List May 2012.

This page has been reviewed for content and attested to by signature within this document.

Report No : TSC-102-05-AP-12 (SAR)

A. 4.6 Probe Calibration Data

NCL CALIBRATION LABORATORIES

Calibration File No.: PC-1470

Client.: CHTL

CERTIFICATE OF CALIBRATION


It is certified that the equipment identified below has been calibrated in the
NCL CALIBRATION LABORATORIES by qualified personnel following recognized
procedures and using transfer standards traceable to NRC/NIST.

Equipment: Miniature Isotropic RF Probe
Record of Calibration
Manufacturer: APREL Laboratories
Model No.: E-020
Serial No.: 257

Calibration Procedure: D01-032-E020-V2, D22-012-Tissue, D28-002-Dipole
Project No: CHT-E20-cal-5702

Calibrated: 14th November 2012
Released on: 14th November 2012

This Calibration Certificate is Incomplete Unless Accompanied with the Calibration Results Summary

Released By:  _____
Art Brennan, Quality Manager

NCL CALIBRATION LABORATORIES
303 Terry Fox Drive, Suite 102 Division of APREL
Kanata, Ontario TEL: (613) 435-8300
CANADA K2K 3J1 FAX: (613) 435-8306

B.

Report No : TSC-102-05-AP-12 (SAR)

NCL Calibration Laboratories

Division of APREL Inc.

Introduction

This Calibration Report reproduces the results of the calibration performed in line with the references listed below. Calibration is performed using accepted methodologies as per the references listed below. Probes are calibrated for air, and tissue and the values reported are the results from the physical quantification of the probe through meteorological practices.

Calibration Method

Probes are calibrated using the following methods.

<1000MHz

TEM Cell for sensitivity in air

Standard phantom using temperature transfer method for sensitivity in tissue

>1000MHz

Waveguide* method to determine sensitivity in air and tissue

*Waveguide is numerically (simulation) assessed to determine the field distribution and power

The boundary effect for the probe is assessed using a standard flat phantom where the probe output is compared against a numerically simulated series of data points

References

- o IEEE Standard 1528 (2003) including Amendment 1
IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques
- o EN 62209-1 (2006)
Human Exposure to RF Fields from hand-held and body-mounted wireless communication devices - Human models, instrumentation, and procedures-Part 1: Procedure to measure the Specific Absorption Rate (SAR) for hand-held mobile wireless devices
- o IEC 62209-2 Ed. 1.0 (2010-03)
Human exposure to RF fields from hand-held and body-mounted wireless devices - Human models, instrumentation, and procedures - Part 2: specific absorption rate (SAR) for wireless communication devices (30 MHz - 6 GHz)
- o TP-D01-032-E020-V2 E-Field probe calibration procedure
- o D22-012-Tissue dielectric tissue calibration procedure
- o D28-002-Dipole procedure for validation of SAR system using a dipole
- o IEEE 1309 Draft Standard for Calibration of Electromagnetic Field Sensors and Probes, Excluding Antennas, from 9kHz to 40GHz

Page 2 of 10

This page has been reviewed for content and attested to on Page 2 of this document.

Report No : TSC-102-05-AP-12 (SAR)

NCL Calibration Laboratories

Division of APREL Inc.

Conditions

Probe 257 was a recalibration.

Ambient Temperature of the Laboratory: 22 °C +/- 1.5°C
Temperature of the Tissue: 21 °C +/- 1.5°C
Relative Humidity: < 60%

Primary Measurement Standards

Instrument	Serial Number	Cal due date
Power meter Anritsu MA2408A	90025437	Nov.4, 2013
Power Sensor Anritsu MA2481D	103555	Nov 4, 2013
Attenuator HP 8495A (70dB)	1944A10711	Sept. 14, 2013
Network Analyzer Anritsu MT8801C	MB11855	Feb. 8, 2013

Secondary Measurement Standards

Signal Generator Agilent E4438C -506 MY55182336 June 7, 2013

Attestation

The below named signatories have conducted the calibration and review of the data which is presented in this calibration report.

We the undersigned attest that to the best of our knowledge the calibration of this subject has been accurately conducted and that all information contained within the results pages have been reviewed for accuracy.



Art Brennan, Quality Manager



Dan Brooks, Test Engineer

Report No : TSC-102-05-AP-12 (SAR)

NCL Calibration Laboratories

Division of APREL Inc.

Probe Summary

Probe Type:	E-Field Probe E020
Serial Number:	257
Frequency:	As presented on page 5
Sensor Offset:	1.56
Sensor Length:	2.5
Tip Enclosure:	Composite*
Tip Diameter:	< 5 mm
Tip Length:	60 mm
Total Length:	290 mm

*Resistive to recommended tissue recipes per IEEE-1528

Sensitivity in Air

Channel X:	1.2 $\mu\text{V}/(\text{V}/\text{m})^2$
Channel Y:	1.2 $\mu\text{V}/(\text{V}/\text{m})^2$
Channel Z:	1.2 $\mu\text{V}/(\text{V}/\text{m})^2$

Diode Compression Point:	95 mV
--------------------------	-------

Report No : TSC-102-05-AP-12 (SAR)

NCL Calibration Laboratories

Division of APREL Inc.

Calibration for Tissue (Head H, Body B)

Frequency	Tissue Type	Measured Epsilon	Measured Sigma	Calibration Uncertainty	Tolerance Uncertainty for 5%*	Conversion Factor
450 H	Head	X	X	X	X	X
450 B	Body	X	X	X	X	X
750 H	Head	X	X	X	X	X
750 B	Body	X	X	X	X	X
835 H	Head	X	X	X	X	X
835 B	Body	X	X	X	X	X
900 H	Head	40.86	0.97	3.5	3.6	6.4
900 B	Body	X	X	X	X	X
1450 H	Head	X	X	X	X	X
1450 B	Body	X	X	X	X	X
1500 H	Head	X	X	X	X	X
1500 B	Body	X	X	X	X	X
1640 H	Head	X	X	X	X	X
1640 B	Body	X	X	X	X	X
1750 H	Head	X	X	X	X	X
1750 B	Body	X	X	X	X	X
1800 H	Head	X	X	X	X	X
1800 B	Body	X	X	X	X	X
1900 H	Head	38.47	1.34	3.5	2.7	5.3
1900 B	Body	X	X	X	X	X
2000 H	Head	X	X	X	X	X
2000 B	Body	X	X	X	X	X
2100 H	Head	X	X	X	X	X
2100 B	Body	X	X	X	X	X
2300 H	Head	X	X	X	X	X
2300 B	Body	X	X	X	X	X
2450 H	Head	X	X	X	X	X
2450B	Body	51.23	1.92	3.5	3.5	4.5
2600 H	Head	X	X	X	X	X
2600 B	Body	X	X	X	X	X
3000 H	Head	X	X	X	X	X
3000 B	Body	X	X	X	X	X
3600 H	Head	X	X	X	X	X
3600 B	Body	X	X	X	X	X
5200 H	Head	X	X	X	X	X
5200 B	Body	X	X	X	X	X
5600 H	Head	X	X	X	X	X
5600 B	Body	X	X	X	X	X
5800 H	Head	X	X	X	X	X
5800 B	Body	X	X	X	X	X

Page 5 of 10

This page has been reviewed for content and attested to on Page 2 of this document.

Report No : TSC-102-05-AP-12 (SAR)

NCL Calibration Laboratories

Division of APREL Inc.

Boundary Effect:

Uncertainty resulting from the boundary effect is less than 2.1% for the distance between the tip of the probe and the tissue boundary, when less than 0.58mm.

Spatial Resolution:

The spatial resolution uncertainty is less than 1.5% for 4.9mm diameter probe.
The spatial resolution uncertainty is less than 1.0% for 2.5mm diameter probe.

DAQ-PAQ Contribution

To minimize the uncertainty calculation all tissue sensitivity values were calculated using a load impedance of 5 M Ω .

Boundary Effect:

For a distance of 0.58mm the worst case evaluated uncertainty (increase in the probe sensitivity) is less than 2.1%.


NOTES:

*The maximum deviation from the centre frequency when comparing the lower to upper range is listed.

Report No : TSC-102-05-AP-12 (SAR)

NCL Calibration Laboratories
Division of APREL Inc.

Receiving Pattern Air





Page 7 of 10
This page has been reviewed for content and attested to on Page 2 of this document.

Report No : TSC-102-05-AP-12 (SAR)

NCL Calibration Laboratories
Division of APREL Inc.

Isotropy Error Air




Isotropy Tissue: 0.10 dB

Report No : TSC-102-05-AP-12 (SAR)

NCL Calibration Laboratories
Division of APREL Inc.


Dynamic Range



Report No : TSC-102-05-AP-12 (SAR)

NCL Calibration Laboratories
Division of APREL Inc.

Video Bandwidth



Video Bandwidth at 500 Hz: 1 dB
Video Bandwidth at 1.02 KHz: 3 dB

Test Equipment

The test equipment used during Probe Calibration, manufacturer, model number and, current calibration status are listed and located on the main APREL server R:\NCL\Calibration Equipment\Instrument List May 2012.