



Maximum Permissible Exposure Report

1. Product Information

EUT	:	Cell Phone Signal booster
Equipment Type	:	Fixed Wideband Consumer Signal Booster
Test Model	:	F10IN-US53
Additional Model No.	:	N/A
Power Supply	:	For AC Adapter(model: SK01T-0500100U): Input: AC 100-240V,50/60Hz,0.25A Output: DC 5.0V=1.0A
Hardware Version	:	/
Software Version	:	/
Frequency Range	:	AWS Band(B4) Uplink: 1710~1755MHz, Downlink: 2110~2155 MHz PCS Band(B25) Uplink: 1850~1915MHz, Downlink: 1930~1995 MHz
Max .Gain	:	≤65dB(Uplink); ≤70dB(Downlink)
Max. Antenna Port Output power	:	Uplink: 20dBm Downlink:8dBm
Emission Designator	:	F9W, G7D, G7W, GXW, W7D
FCC Classification	:	B2W/Wideband Consumer Booster(CMRS)
Operating Temperature	:	-25 ℃~+55 ℃

**Antenna Information:**

External Antenna can only use antennas certificated as follows provided by manufacturer:

Outdoor Antenna					
Outdoor Antenna	Outdoor Antenna Gain				
	Lower 700MHz	Upper 700MHz	Celluler	PCS	AWS
Magnet Antenna	/	/	/	3.5	3.5
Log Periodic Antenna	/	/	/	8.0	8.0
Outdoor Omni Antenna	/	/	/	6.0	6.0
Indoor Antenna					
Indoor Antenna	Indoor Antenna Gain				
	Lower 700MHz	Upper 700MHz	Celluler	PCS	AWS
Indoor Panel Antenna	/	/	/	8.0	8.0
Ceiling Antenna	/	/	/	4.5	4.5
Outdoor Cable					
Outdoor Cable	Outdoor Cable Loss				
	Lower 700MHz	Upper 700MHz	Celluler	PCS	AWS
5-meter RG58 Coaxial cable with N male/SMA male connector	/	/	/	3.25	3.25
Outdoor Cable					
Outdoor Cable	Outdoor Cable Loss				
	Lower 700MHz	Upper 700MHz	Celluler	PCS	AWS
0.3-meter RG316 Coaxial cable with SMA male/SMA Female connector	/	/	/	0.7	0.7
Outdoor Cable					
Outdoor Cable	Outdoor Cable Loss				
	Lower 700MHz	Upper 700MHz	Celluler	PCS	AWS



10-meter RG58 Coaxial cable with SMA male/SMA female connector	/	/	/	6.5	6.5
Indoor Cable					
Indoor Cable	Indoor Cable Loss				
	Lower 700MHz	Upper 700MHz	Celluler	PCS	AWS
5-meter RG58 Coaxial cable with N male/SMA male connector	/	/	/	3.25	3.25



2. Evaluation Method

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as mobile device whereby a distance of 0.2m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with.

In accordance with KDB447498D01 for Simultaneous transmission MPE test exclusion applies when the sum of the MPE ratios for all simultaneous transmitting antennas incorporated in a host device, based on the calculated/estimated, numerically modelled or measured field strengths or power density, is ≤ 1.0 . The MPE ratio of each antenna is determined at the minimum test separation distance required by the operating configurations and exposure conditions of the host device, according to the ratio of field strengths or power density to MPE limit, at the test frequency. Either the maximum peak or spatially averaged results from measurements or numerical simulations may be used to determine the MPE ratios. Spatial averaging does not apply when MPE is estimated using simple calculations based on far-field plane-wave equivalent conditions. The antenna installation and operating requirements for the host device must meet the minimum test separation distances required by all antennas, in both standalone and simultaneous transmission operations, to satisfy compliance.

3. Limit

3.1 Refer Evaluation Method

[ANSI C95.1-1999](#): IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz.

[FCC KDB publication 447498 D01 General 1 RF Exposure Guidance v06](#): Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies.

[FCC CFR 47 part1 1.1310](#): Radiofrequency radiation exposure limits.

[FCC CFR 47 part2 2.1091](#): Radiofrequency radiation exposure evaluation: mobile devices

3.2 Limit

Limits for Maximum Permissible Exposure (MPE)/Controlled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100)*	6
3.0 – 30	1842/f	4.89/f	(900/f ²)*	6
30 – 300	61.4	0.163	1.0	6
300 – 1500	/	/	f/300	6
1500 – 100,000	/	/	5	6

Limits for Maximum Permissible Exposure (MPE)/Uncontrolled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100)*	30
3.0 – 30	824/f	2.19/f	(180/f ²)*	30
30 – 300	27.5	0.073	0.2	30
300 – 1500	/	/	f/1500	30
1500 – 100,000	/	/	1.0	30

F=frequency in MHz

*=Plane-wave equivalent power density



4. MPE Calculation Method

Predication of MPE limit at a given distance
Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S=PG/4\pi R^2$$

Where: S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna

5. Conducted Output Power

Operation Bands	Frequency (MHz)	Max. Output Power (dBm)	Cable Loss	Power to Antenna (dBm)
UL (1850~1915MHz)	1882.52	20.00	0.7	19.30
UL(1710~1755MHz)	1752.30	20.00	0.7	19.30
DL(1930~1995 MHz)	1959.04	8.00	3.25	4.75
DL(2110~2155 MHz)	2116.66	8.00	3.25	4.75



6. Measurement Results

Operation Bands	Frequency (MHz)	Power to Antenna (dBm)	Target (dBm)	Tolerance \pm (dB)
UL (1850~1915MHz)	1882.52	19.30	19	1.0
UL(1710~1755MHz)	1752.30	19.30	19	1.0
DL(1930~1995 MHz)	1959.04	4.75	5	1.0
DL(2110~2155 MHz)	2116.66	4.75	5	1.0



7. Limits for General /Uncontrolled Exposure

Maximum permissible exposure :

the report recorded the worst result of Outdoor Antenna (Log Periodic Antenna), Indoor Antenna(Indoor Panel Antenna)

Band/Mode	RF output power		Antenna Gain (dBi)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)	Results
	dBm	mW				
UL (1850~1915MHz)	20	100.0000	8.0	0.1255	1.0	PASS
UL(1710~1755MHz)	20	100.0000	8.0	0.1255	1.0	PASS
DL(1930~1995 MHz)	6	3.9811	8.0	0.0050	1.0	PASS
DL(2110~2155 MHz)	6	3.9811	8.0	0.0050	1.0	PASS

Remark:

1. Output power including turn-up tolerance;
2. Output power is burst average power;
3. MPE evaluate distance is 20cm from user manual provide by manufacturer;
4. MPE values = $PG/4\pi R$

8. Evaluation Results

As declared by the Applicant, the EUT is a wireless device used in a fix application, at least 20cm from any body part of the user or nearby persons; from the maximum EUT RF output power, the minimum separation distance, $r = 20\text{cm}$, as well as the gain of the used antenna refer to antenna information, the RF power density can be obtained.

Simultaneous Transmission MPE

Not need consider simultaneous transmission

9. Conclusion

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure of mobile device.

-----THE END OF REPORT-----