


```

Site no.      : 3m Chamber           Data no.   : 64
Dis. / Ant.  : 3m 3115(0911)       Ant. pol.  : HORIZONTAL
Limit        : FCC PART 15C PEAK
Env. / Ins.  : 23*C/54%           Engineer   : Leo-Li
EUT          : 2.4GHz 300Mbps Wireless PCI Adapter
Power supply : DC 3.3V From PC input AC 120V/60Hz
Test mode    : IEEE802.11n HT40 CH6 2437MHz Tx
M/N         : SMCWPCI-N5
    
```


	Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	4874.000	34.41	10.69	35.03	44.77	54.84	74.00	19.16	Peak
2	4874.000	34.41	10.69	35.03	30.48	40.55	54.00	13.45	Average

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 65
Dis. / Ant. : 3m 3115(0911) Ant. pol. : VERTICAL
Limit : FCC PART 15C PEAK
Env. / Ins. : 23°C/54% Engineer : Leo-Li
EUT : 2.4GHz 300Mbps Wireless PCI Adapter
Power supply : DC 3.3V From PC input AC 120V/60Hz
Test mode : IEEE802.11n HT40 CH6 2437MHz Tx
M/N : SMCWPCI-N5
:




```

Site no.      : 3m Chamber           Data no.   : 66
Dis. / Ant.  : 3m 3115(0911)       Ant. pol.  : VERTICAL
Limit        : FCC PART 15C PEAK
Env. / Ins.  : 23*C/54%           Engineer   : Leo-Li
EUT          : 2.4GHz 300Mbps Wireless PCI Adapter
Power supply : DC 3.3V From PC input AC 120V/60Hz
Test mode    : IEEE802.11n HT40 CH6 2437MHz Tx
M/N          : SMCWPCI-N5
    
```


	Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	4874.000	34.41	10.69	35.03	44.60	54.67	74.00	19.33	Peak
2	4874.000	34.41	10.69	35.03	30.81	40.88	54.00	13.12	Average

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 67
Dis. / Ant. : 3m 3115(0911) Ant. pol. : VERTICAL
Limit : FCC PART 15C PEAK
Env. / Ins. : 23°C/54% Engineer : Leo-Li
EUT : 2.4GHz 300Mbps Wireless PCI Adapter
Power supply : DC 3.3V From PC input AC 120V/60Hz
Test mode : IEEE802.11n HT40 CH9 2452MHz Tx
M/N : SMCWPCI-N5
:




Site no. : 3m Chamber Data no. : 68
 Dis. / Ant. : 3m 3115(0911) Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54% Engineer : Leo-Li
 EUT : 2.4GHz 300Mbps Wireless PCI Adapter
 Power supply : DC 3.3V From PC input AC 120V/60Hz
 Test mode : IEEE802.11n HT40 CH9 2452MHz Tx
 M/N : SMCWPCI-N5
 :


	Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	4904.000	34.46	10.74	35.00	44.83	55.03	74.00	18.97	Peak
2	4904.000	34.46	10.74	35.00	30.84	41.04	54.00	12.96	Average

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 69
Dis. / Ant. : 3m 3115(0911) Ant. pol. : HORIZONTAL
Limit : FCC PART 15C PEAK
Env. / Ins. : 23°C/54% Engineer : Leo-Li
EUT : 2.4GHz 300Mbps Wireless PCI Adapter
Power supply : DC 3.3V From PC input AC 120V/60Hz
Test mode : IEEE802.11n HT40 CH9 2452MHz Tx
M/N : SMCWPCI-N5
:




```

Site no.      : 3m Chamber           Data no.   : 70
Dis. / Ant.  : 3m 3115(0911)       Ant. pol.  : HORIZONTAL
Limit        : FCC PART 15C PEAK
Env. / Ins.  : 23*C/54%           Engineer   : Leo-Li
EUT         : 2.4GHz 300Mbps Wireless PCI Adapter
Power supply : DC 3.3V From PC input AC 120V/60Hz
Test mode    : IEEE802.11n HT40 CH9 2452MHz Tx
M/N         : SMCWPCI-N5
    
```

	Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	4904.000	34.46	10.74	35.00	44.90	55.10	74.00	18.90	Peak
2	4904.000	34.46	10.74	35.00	30.99	41.19	54.00	12.81	Average

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.




```

Site no.      : 3m Chamber           Data no.   : 71
Dis. / Ant.  : 3m 3115(0911)        Ant. pol.  : VERTICAL
Limit        : FCC PART 15C PEAK
Env. / Ins.  : 23*C/54%             Engineer   : Leo-Li
EUT          : 2.4GHz 300Mbps Wireless PCI Adapter
Power supply : DC 3.3V From PC input AC 120V/60Hz
Test mode    : IEEE802.11g CH11 2462MHz Tx
M/N         : SMCWPCI-N5
    
```

	Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBUV)	Emission Level (dBUV/m)	Limits (dBUV/m)	Margin (dB)	Remark
1	2462.000	29.48	7.54	36.61	109.44	109.85	74.00	-35.85	Peak
2	3286.000	32.72	8.88	36.20	46.26	51.66	74.00	22.34	Peak

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.




```

Site no.       : 3m Chamber           Data no.      : 72
Dis. / Ant.    : 3m 3115(0911)       Ant. pol.    : HORIZONTAL
Limit         : FCC PART 15C PEAK
Env. / Ins.    : 23°C/54%           Engineer     : Leo-Li
EUT           : 2.4GHz 300Mbps Wireless PCI Adapter
Power supply   : DC 3.3V From PC input AC 120V/60Hz
Test mode     : IEEE802.11g CH11 2462MHz Tx
M/N          : SMCWPCI-N5
    
```

	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Emission Reading (dBUV)	Emission Level (dBUV/m)	Limits (dBUV/m)	Margin (dB)	Remark
1	29.48	7.54	36.61	99.28	99.69	74.00	-25.69	Peak

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.




```

Site no.      : 3m Chamber           Data no.   : 81
Dis. / Ant.  : 3m 3115(0911)       Ant. pol.  : VERTICAL
Limit       : FCC PART 15C PEAK
Env. / Ins.  : 23°C/54%             Engineer   : Leo-Li
EUT        : 2.4GHz 300Mbps Wireless PCI Adapter
Power supply : DC 3.3V From PC input AC 120V/60Hz
Test mode   : IEEE802.11n HT20 CH11 2462MHz Tx
M/N        : SMCWPCI-N5
    
```

	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	29.48	7.54	36.61	111.12	111.53	74.00	-37.53	Peak

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.




```

Site no.       : 3m Chamber           Data no.      : 82
Dis. / Ant.    : 3m 3115(0911)       Ant. pol.    : HORIZONTAL
Limit         : FCC PART 15C PEAK
Env. / Ins.    : 23°C/54%           Engineer     : Leo-Li
EUT           : 2.4GHz 300Mbps Wireless PCI Adapter
Power supply   : DC 3.3V From PC input AC 120V/60Hz
Test mode      : IEEE802.11n HT20 CH11 2462MHz Tx
M/N           : SMCWPCI-N5
    
```

	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBUV)	Emission Level (dBUV/m)	Limits (dBUV/m)	Margin (dB)	Remark
1	29.48	7.54	36.61	101.48	101.89	74.00	-27.89	Peak

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.




```

Site no.      : 3m Chamber           Data no.   : 83
Dis. / Ant.  : 3m 3115(0911)       Ant. pol.  : HORIZONTAL
Limit        : FCC PART 15C PEAK
Env. / Ins.  : 23°C/54%           Engineer   : Leo-Li
EUT          : 2.4GHz 300Mbps Wireless PCI Adapter
Power supply : DC 3.3V From PC input AC 120V/60Hz
Test mode    : IEEE802.11n HT20 CH6 2437MHz Tx
M/N         : SMCWPCI-N5
    
```

	Ant. Factor	Cable loss	Amp. Factor	Reading	Emission Level	Limits	Margin	Remark
Freq. (MHz)	(dB/m)	(dB)	(dB)	(dBUV)	(dBUV/m)	(dBUV/m)	(dB)	
1 2437.000	29.47	7.46	36.61	107.58	107.90	74.00	-33.90	Peak

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 3m Chamber Data no. : 84
 Dis. / Ant. : 3m 3115(0911) Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54% Engineer : Leo-Li
 EUT : 2.4GHz 300Mbps Wireless PCI Adapter
 Power supply : DC 3.3V From PC input AC 120V/60Hz
 Test mode : IEEE802.11n HT20 CH6 2437MHz Tx
 M/N : SMCWPCI-N5
 :

	Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBUV)	Emission Level (dBUV/m)	Limits (dBUV/m)	Margin (dB)	Remark
1	2437.000	29.47	7.46	36.61	116.55	116.87	74.00	-42.87	Peak
2	3250.000	32.63	8.83	36.25	48.36	53.57	74.00	20.43	Peak

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.




```

Site no.      : 3m Chamber           Data no.   : 89
Dis. / Ant.  : 3m 3115(0911)        Ant. pol.  : HORIZONTAL
Limit        : FCC PART 15C PEAK
Env. / Ins.  : 23°C/54%             Engineer   : Leo-Li
EUT          : 2.4GHz 300Mbps Wireless PCI Adapter
Power supply : DC 3.3V From PC input AC 120V/60Hz
Test mode    : IEEE802.11n HT20 CH1 2412MHz Tx
M/N         : SMCWPCI-N5
    
```

	Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2412.000	29.45	7.43	36.62	99.56	99.82	74.00	-25.82	Peak

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.




```

Site no.      : 3m Chamber           Data no.   : 90
Dis. / Ant.  : 3m 3115(0911)        Ant. pol.  : VERTICAL
Limit        : FCC PART 15C PEAK
Env. / Ins.  : 23°C/54%             Engineer   : Leo-Li
EUT          : 2.4GHz 300Mbps Wireless PCI Adapter
Power supply : DC 3.3V From PC input AC 120V/60Hz
Test mode    : IEEE802.11n HT20 CH1 2412MHz Tx
M/N          : SMCWPCI-N5
    
```

	Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2412.000	29.45	7.43	36.62	110.31	110.57	74.00	-36.57	Peak
2	3214.000	32.54	8.79	36.28	49.96	55.01	74.00	18.99	Peak

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.




```

Site no.      : 3m Chamber           Data no.   : 95
Dis. / Ant.   : 3m 3115(0911)       Ant. pol.  : HORIZONTAL
Limit        : FCC PART 15C PEAK
Env. / Ins.   : 23°C/54%           Engineer   : Leo-Li
EUT          : 2.4GHz 300Mbps Wireless PCI Adapter
Power supply  : DC 3.3V From PC input AC 120V/60Hz
Test mode    : IEEE802.11n HT40 CH3 2422MHz Tx
M/N          : SMCWPCI-N5
    
```

	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBUV)	Emission Level (dBUV/m)	Limits (dBUV/m)	Margin (dB)	Remark
1	29.46	7.46	36.61	94.42	94.73	74.00	-20.73	Peak

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.




```

Site no.      : 3m Chamber           Data no.   : 96
Dis. / Ant.   : 3m 3115(0911)       Ant. pol.  : VERTICAL
Limit        : FCC PART 15C PEAK
Env. / Ins.   : 23°C/54%           Engineer   : Leo-Li
EUT          : 2.4GHz 300Mbps Wireless PCI Adapter
Power supply  : DC 3.3V From PC input AC 120V/60Hz
Test mode    : IEEE802.11n HT40 CH3 2422MHz Tx
M/N          : SMCWPCI-N5
    
```

	Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBUV)	Emission Level (dBUV/m)	Limits (dBUV/m)	Margin (dB)	Remark
1	2422.000	29.46	7.46	36.61	104.95	105.26	74.00	-31.26	Peak
2	3229.000	32.58	8.81	36.28	47.24	52.35	74.00	21.65	Peak

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.




```

Site no.      : 3m Chamber           Data no.   : 97
Dis. / Ant.   : 3m 3115(0911)       Ant. pol.  : VERTICAL
Limit        : FCC PART 15C PEAK
Env. / Ins.   : 23°C/54%           Engineer   : Leo-Li
EUT          : 2.4GHz 300Mbps Wireless PCI Adapter
Power supply  : DC 3.3V From PC input AC 120V/60Hz
Test mode    : IEEE802.11n HT40 CH6 2437MHz Tx
M/N         : SMCWPCI-N5
    
```

	Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2437.000	29.47	7.46	36.61	112.68	113.00	74.00	-39.00	Peak
2	3250.000	32.63	8.83	36.25	48.16	53.37	74.00	20.63	Peak

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.




```

Site no.      : 3m Chamber           Data no.   : 98
Dis. / Ant.   : 3m 3115(0911)       Ant. pol.  : HORIZONTAL
Limit        : FCC PART 15C PEAK
Env. / Ins.   : 23°C/54%           Engineer   : Leo-Li
EUT         : 2.4GHz 300Mbps Wireless PCI Adapter
Power supply : DC 3.3V From PC input AC 120V/60Hz
Test mode    : IEEE802.11n HT40 CH6 2437MHz Tx
M/N         : SMCWPCI-N5
    
```

	Ant.	Cable	Amp.	Emission				
Freq.	Factor	loss	Factor	Reading	Level	Limits	Margin	Remark
(MHz)	(dB/m)	(dB)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)	
1 2437.000	29.47	7.46	36.61	102.68	103.00	74.00	-29.00	Peak

Remarks:

1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 3m Chamber Data no. : 103
 Dis. / Ant. : 3m 3115(0911) Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54% Engineer : Leo-Li
 EUT : 2.4GHz 300Mbps Wireless PCI Adapter
 Power supply : DC 3.3V From PC input AC 120V/60Hz
 Test mode : IEEE802.11n HT40 CH9 2452MHz Tx
 M/N : SMCWPCI-N5
 :

	Ant.	Cable	Amp.	Emission				
Freq.	Factor	loss	Factor	Reading	Level	Limits	Margin	Remark
(MHz)	(dB/m)	(dB)	(dB)	(dBUV)	(dBUV/m)	(dBUV/m)	(dB)	
1 2452.000	29.47	7.50	36.61	94.67	95.03	74.00	-21.03	Peak

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 3m Chamber Data no. : 104
 Dis. / Ant. : 3m 3115(0911) Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54% Engineer : Leo-Li
 EUT : 2.4GHz 300Mbps Wireless PCI Adapter
 Power supply : DC 3.3V From PC input AC 120V/60Hz
 Test mode : IEEE802.11n HT40 CH9 2452MHz Tx
 M/N : SMCWPCI-N5
 :

	Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2452.000	29.47	7.50	36.61	104.18	104.54	74.00	-30.54	Peak
2	3271.000	32.72	8.86	36.22	43.14	48.50	74.00	25.50	Peak

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.



5. CONDUCTED SPURIOUS EMISSIONS

5.1. Test Equipment

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Spectrum Analyzer	Agilent	E4446A	US44300459	May.08,13	1 Year
2.	Attenuator	Agilent	8491B	MY39262165	May.08,13	1 Year
3.	RF Cable	Hubersuhner	SUCOFLEX102	28618/2	May.08,13	1Year

5.2. Limit

In any 100kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power.

5.3. Test Procedure

The transmitter output was connected to a spectrum analyzer, The resolution bandwidth is set to 100 kHz, The video bandwidth is set to 300 kHz and measure all the emissions detected.



5.4. Test result



PASS (The testing data was attached in the next pages.)

Chain 0:



Test Mode: IEEE 802.11b TX


Test CH1: 2412MHz








Test CH6: 2437MHz






Test CH11: 2462MHz











Test Mode: IEEE 802.11g TX


Test CH1: 2412MHz










Test CH6: 2437MHz








Test CH11: 2462MHz





Copyright 2000-2005 Agilent Technologies





Copyright 2000-2005 Agilent Technologies






Test Mode: IEEE 802.11n HT20 TX
 Test CH1: 2412MHz








Test CH6: 2437MHz







Test CH11: 2462MHz











Test Mode: IEEE 802.11n HT40 TX
Test CH1: 2422MHz













Test CH4: 2437MHz





Test CH7: 2452MHz









Chain 1:


Test Mode: IEEE 802.11b TX

Test CH1: 2412MHz







Test CH6: 2437MHz




Copyright 2000-2005 Agilent Technologies






Copyright 2000-2005 Agilent Technologies



Test CH11: 2462MHz











Test Mode: IEEE 802.11g TX


Test CH1: 2412MHz










Test CH6: 2437MHz








Test CH11: 2462MHz





Copyright 2000-2005 Agilent Technologies





Copyright 2000-2005 Agilent Technologies






Test Mode: IEEE 802.11n HT20 TX
 Test CH1: 2412MHz








Test CH6: 2437MHz







Test CH11: 2462MHz











Test Mode: IEEE 802.11n HT40 TX
Test CH1: 2422MHz













Test CH4: 2437MHz





Test CH7: 2452MHz





6. BAND EDGE COMPLIANCE TEST

6.1. Test Equipment

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Spectrum	Agilent	E4446A	US44300459	May.08, 13	1 Year
2.	Amp	HP	8449B	3008A08495	May.08, 13	1 Year
3.	Antenna	EMCO	3115	9607-4877	May.08, 13	1Year
4.	HF Cable	Hubersuhne	Sucoflex104	-	May.08, 13	1 Year

6.2. Limit


All the lower and upper band-edges emissions appearing within 2310MHz to 2390MHz and 2483.5MHz to 2500MHz restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions outside operation frequency band 2400MHz to 2483.5MHz shall be at least 20dB below the fundamental emissions, or comply with 15.209 limits.

6.3. Test Produce

1. The EUT is placed on a turntable, which is 0.8m above the ground plane and worked at highest radiated power.
2. The turntable was rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emission.
4. Set the spectrum analyzer in the following setting in order to capture the lower and upper band-edges of the emission:
 - (a) PEAK: RBW=1MHz; VBW=3MHz; Sweep=AUTO
 - (b) AVERAGE: RBW=1MHz; VBW=10Hz; Sweep=AUTO

6.4. Test Results

Pass (The testing data was attached in the next pages.)




Site no. : 3m Chamber Data no. : 111
 Dis. / Ant. : 3m 3115(0911) Ant. pol. : HORIZONTAL
 Limit : RSS-210 PEAK
 Env. / Ins. : 23°C/54% Engineer : Leo-Li
 EUT : 2.4GHz 300Mbps Wireless PCI Adapter
 Power supply : DC 3.3V From PC input AC 120V/60Hz
 Test mode : IEEE802.11b CH1 2412MHz Tx
 M/N : SMCWPCI-N5
 :

	Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2359.450	29.42	7.35	36.63	50.27	50.41	74.00	23.59	Peak
2	2390.000	29.44	7.39	36.62	48.24	48.45	74.00	25.55	Peak
3	2397.975	29.44	7.39	36.62	61.40	61.61	74.00	12.39	Peak
4	2400.000	29.44	7.43	36.62	55.78	56.03	74.00	17.97	Peak
5	2413.270	29.45	7.43	36.62	99.76	100.02	74.00	-26.02	Peak

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.




```

Site no.       : 3m Chamber           Data no.      : 112
Dis. / Ant.   : 3m 3115(0911)        Ant. pol.    : HORIZONTAL
Limit         : RSS-210 AV
Env. / Ins.   : 23*C/54%             Engineer     : Leo-Li
EUT           : 2.4GHz 300Mbps Wireless PCI Adapter
Power supply  : DC 3.3V From PC input AC 120V/60Hz
Test mode     : IEEE802.11b CH1 2412MHz Tx
M/N          : SMCWPCI-N5
    
```

	Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2373.250	29.43	7.35	36.62	37.64	37.80	54.00	16.20	Average
2	2390.000	29.44	7.39	36.62	36.76	36.97	54.00	17.03	Average
3	2398.205	29.44	7.39	36.62	55.69	55.90	54.00	-1.90	Average
4	2400.000	29.44	7.43	36.62	47.12	47.37	54.00	6.63	Average
5	2411.200	29.45	7.43	36.62	95.92	96.18	54.00	-42.18	Average

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 3m Chamber Data no. : 113
 Dis. / Ant. : 3m 3115(0911) Ant. pol. : VERTICAL
 Limit : RSS-210 AV
 Env. / Ins. : 23°C/54% Engineer : Leo-Li
 EUT : 2.4GHz 300Mbps Wireless PCI Adapter
 Power supply : DC 3.3V From PC input AC 120V/60Hz
 Test mode : IEEE802.11b CH1 2412MHz Tx
 M/N : SMCWPCI-N5
 :

	Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2390.000	29.44	7.39	36.62	39.97	40.18	54.00	13.82	Average
2	2398.205	29.44	7.39	36.62	65.39	65.60	54.00	-11.60	Average
3	2400.000	29.44	7.43	36.62	56.46	56.71	54.00	-2.71	Average
4	2411.200	29.45	7.43	36.62	104.98	105.24	54.00	-51.24	Average

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.




```

Site no.      : 3m Chamber           Data no.   : 114
Dis. / Ant.  : 3m 3115(0911)        Ant. pol.  : VERTICAL
Limit        : RSS-210 PEAK
Env. / Ins.  : 23*C/54%             Engineer   : Leo-Li
EUT         : 2.4GHz 300Mbps Wireless PCI Adapter
Power supply : DC 3.3V From PC input AC 120V/60Hz
Test mode    : IEEE802.11b CH1 2412MHz Tx
M/N         : SMCWPCI-N5
    
```

	Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2373.825	29.43	7.35	36.62	54.29	54.45	74.00	19.55	Peak
2	2390.000	29.44	7.39	36.62	51.87	52.08	74.00	21.92	Peak
3	2397.170	29.44	7.39	36.62	70.11	70.32	74.00	3.68	Peak
4	2400.000	29.44	7.43	36.62	64.97	65.22	74.00	8.78	Peak
5	2413.270	29.45	7.43	36.62	108.58	108.84	74.00	-34.84	Peak

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 3m Chamber Data no. : 127
 Dis. / Ant. : 3m 3115(0911) Ant. pol. : VERTICAL
 Limit : RSS-210 PEAK
 Env. / Ins. : 23°C/54% Engineer : Leo-Li
 EUT : 2.4GHz 300Mbps Wireless PCI Adapter
 Power supply : DC 3.3V From PC input AC 120V/60Hz
 Test mode : IEEE802.11b CH6 2462MHz Tx
 M/N : SMCWPCI-N5
 :

	Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2463.320	29.48	7.54	36.61	113.06	113.47	74.00	-39.47	Peak
2	2483.500	29.49	7.58	36.60	57.21	57.68	74.00	16.32	Peak
3	2500.000	29.50	7.62	36.60	58.37	58.89	74.00	15.11	Peak

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 3m Chamber Data no. : 128
 Dis. / Ant. : 3m 3115(0911) Ant. pol. : VERTICAL
 Limit : RSS-210 AV
 Env. / Ins. : 23°C/54% Engineer : Leo-Li
 EUT : 2.4GHz 300Mbps Wireless PCI Adapter
 Power supply : DC 3.3V From PC input AC 120V/60Hz
 Test mode : IEEE802.11b CH6 2462MHz Tx
 M/N : SMCWPCI-N5
 :

	Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2461.220	29.48	7.54	36.61	109.54	109.95	54.00	-55.95	Average
2	2483.500	29.49	7.58	36.60	46.76	47.23	54.00	6.77	Average
3	2500.000	29.50	7.62	36.60	49.91	50.43	54.00	3.57	Average

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.




```

Site no.      : 3m Chamber           Data no.   : 129
Dis. / Ant.  : 3m 3115(0911)        Ant. pol.  : HORIZONTAL
Limit        : RSS-210 PEAK
Env. / Ins.  : 23*C/54%             Engineer   : Leo-Li
EUT          : 2.4GHz 300Mbps Wireless PCI Adapter
Power supply : DC 3.3V From PC input AC 120V/60Hz
Test mode    : IEEE802.11b CH6 2462MHz Tx
M/N         : SMCWPCI-N5
    
```

	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBUV)	Emission Level (dBUV/m)	Limits (dBUV/m)	Margin (dB)	Remark
1	29.48	7.54	36.61	99.38	99.79	74.00	-25.79	Peak
2	29.49	7.58	36.60	48.80	49.27	74.00	24.73	Peak
3	29.50	7.62	36.60	50.05	50.57	74.00	23.43	Peak

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 3m Chamber Data no. : 130
 Dis. / Ant. : 3m 3115(0911) Ant. pol. : HORIZONTAL
 Limit : RSS-210 AV
 Env. / Ins. : 23°C/54% Engineer : Leo-Li
 EUT : 2.4GHz 300Mbps Wireless PCI Adapter
 Power supply : DC 3.3V From PC input AC 120V/60Hz
 Test mode : IEEE802.11b CH6 2462MHz Tx
 M/N : SMCWPCI-N5
 :

	Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2464.700	29.48	7.54	36.61	95.41	95.82	54.00	-41.82	Average
2	2483.500	29.49	7.58	36.60	37.78	38.25	54.00	15.75	Average
3	2500.000	29.50	7.62	36.60	38.44	38.96	54.00	15.04	Average

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 3m Chamber Data no. : 137
 Dis. / Ant. : 3m 3115(0911) Ant. pol. : HORIZONTAL
 Limit : RSS-210 PEAK
 Env. / Ins. : 23°C/54% Engineer : Leo-Li
 EUT : 2.4GHz 300Mbps Wireless PCI Adapter
 Power supply : DC 3.3V From PC input AC 120V/60Hz
 Test mode : IEEE802.11g CH1 2412MHz Tx
 M/N : SMCWPCI-N5
 :

	Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2388.200	29.44	7.39	36.62	58.94	59.15	74.00	14.85	Peak
2	2390.000	29.44	7.39	36.62	61.01	61.22	74.00	12.78	Peak
3	2391.880	29.44	7.39	36.62	66.50	66.71	74.00	7.29	Peak
4	2400.000	29.44	7.43	36.62	77.06	77.31	74.00	-3.31	Peak
5	2406.025	29.45	7.43	36.62	98.17	98.43	74.00	-24.43	Peak

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 3m Chamber Data no. : 138
 Dis. / Ant. : 3m 3115(0911) Ant. pol. : HORIZONTAL
 Limit : RSS-210 AV
 Env. / Ins. : 23°C/54% Engineer : Leo-Li
 EUT : 2.4GHz 300Mbps Wireless PCI Adapter
 Power supply : DC 3.3V From PC input AC 120V/60Hz
 Test mode : IEEE802.11g CH1 2412MHz Tx
 M/N : SMCWPCI-N5
 :

	Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2327.250	29.40	7.27	36.63	36.52	36.56	54.00	17.44	Average
2	2390.000	29.44	7.39	36.62	42.40	42.61	54.00	11.39	Average
3	2400.000	29.44	7.43	36.62	54.29	54.54	54.00	-0.54	Average
4	2418.675	29.45	7.43	36.61	84.30	84.57	54.00	-30.57	Average

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.




```

Site no.       : 3m Chamber           Data no.      : 139
Dis. / Ant.   : 3m 3115(0911)        Ant. pol.    : VERTICAL
Limit         : RSS-210 PEAK
Env. / Ins.   : 23*C/54%            Engineer     : Leo-Li
EUT           : 2.4GHz 300Mbps Wireless PCI Adapter
Power supply  : DC 3.3V From PC input AC 120V/60Hz
Test mode     : IEEE802.11g CH1 2412MHz Tx
M/N          : SMCWPCI-N5
    
```

	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	29.44	7.39	36.62	70.76	70.97	74.00	3.03	Peak
2	29.44	7.43	36.62	87.72	87.97	74.00	-13.97	Peak
3	29.45	7.46	36.61	110.19	110.49	74.00	-36.49	Peak

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.




```

Site no.      : 3m Chamber           Data no.   : 140
Dis. / Ant.  : 3m 3115(0911)       Ant. pol.  : VERTICAL
Limit       : RSS-210 AV
Env. / Ins.  : 23*C/54%           Engineer   : Leo-Li
EUT        : 2.4GHz 300Mbps Wireless PCI Adapter
Power supply : DC 3.3V From PC input AC 120V/60Hz
Test mode   : IEEE802.11g CH1 2412MHz Tx
M/N        : SMCWPCI-N5
    
```

	Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2390.000	29.44	7.39	36.62	50.69	50.90	54.00	3.10	Average
2	2400.000	29.44	7.43	36.62	64.63	64.88	54.00	-10.88	Average
3	2419.020	29.45	7.46	36.61	96.10	96.40	54.00	-42.40	Average

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 3m Chamber Data no. : 177
 Dis. / Ant. : 3m 3115(0911) Ant. pol. : VERTICAL
 Limit : RSS-210 AV
 Env. / Ins. : 23°C/54% Engineer : Leo-Li
 EUT : 2.4GHz 300Mbps Wireless PCI Adapter
 Power supply : DC 3.3V From PC input AC 120V/60Hz
 Test mode : IEEE802.11g CH11 2462MHz Tx
 M/N : SMCWPCI-N5
 :

	Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2468.480	29.48	7.54	36.60	95.94	96.36	54.00	-42.36	Average
2	2483.500	29.49	7.58	36.60	50.29	50.76	54.00	3.24	Average
3	2500.000	29.50	7.62	36.60	43.97	44.49	54.00	9.51	Average

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 3m Chamber Data no. : 178
 Dis. / Ant. : 3m 3115(0911) Ant. pol. : VERTICAL
 Limit : RSS-210 PEAK
 Env. / Ins. : 23°C/54% Engineer : Leo-Li
 EUT : 2.4GHz 300Mbps Wireless PCI Adapter
 Power supply : DC 3.3V From PC input AC 120V/60Hz
 Test mode : IEEE802.11g CH11 2462MHz Tx
 M/N : SMCWPCI-N5
 :

	Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2455.820	29.48	7.50	36.61	109.73	110.10	74.00	-36.10	Peak
2	2483.500	29.49	7.58	36.60	67.48	67.95	74.00	6.05	Peak
3	2483.900	29.49	7.58	36.60	68.27	68.74	74.00	5.26	Peak
4	2500.000	29.50	7.62	36.60	55.01	55.53	74.00	18.47	Peak

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.




```

Site no.       : 3m Chamber           Data no.      : 179
Dis. / Ant.   : 3m 3115(0911)        Ant. pol.    : HORIZONTAL
Limit        : RSS-210 PEAK
Env. / Ins.   : 23*C/54%             Engineer     : Leo-Li
EUT          : 2.4GHz 300Mbps Wireless PCI Adapter
Power supply  : DC 3.3V From PC input AC 120V/60Hz
Test mode    : IEEE802.11g CH11 2462MHz Tx
M/N         : SMCWPCI-N5
    
```

	Ant. Factor	Cable loss	Amp. Factor	Reading	Emission Level	Limits	Margin	Remark
Freq. (MHz)	(dB/m)	(dB)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)	
1 2458.880	29.48	7.54	36.61	99.33	99.74	74.00	-25.74	Peak
2 2483.500	29.49	7.58	36.60	57.59	58.06	74.00	15.94	Peak
3 2500.000	29.50	7.62	36.60	48.80	49.32	74.00	24.68	Peak

Remarks:

- Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
- The emission levels that are 20dB below the official limit are not reported.




Site no. : 3m Chamber Data no. : 180
 Dis. / Ant. : 3m 3115(0911) Ant. pol. : HORIZONTAL
 Limit : RSS-210 AV
 Env. / Ins. : 23°C/54% Engineer : Leo-Li
 EUT : 2.4GHz 300Mbps Wireless PCI Adapter
 Power supply : DC 3.3V From PC input AC 120V/60Hz
 Test mode : IEEE802.11g CH11 2462MHz Tx
 M/N : SMCWPCI-N5
 :

	Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2456.780	29.48	7.50	36.61	85.40	85.77	54.00	-31.77	Average
2	2483.500	29.49	7.58	36.60	40.63	41.10	54.00	12.90	Average
3	2500.000	29.50	7.62	36.60	37.58	38.10	54.00	15.90	Average

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.




```

Site no.      : 3m Chamber           Data no.   : 181
Dis. / Ant.   : 3m 3115(0911)       Ant. pol.  : VERTICAL
Limit        : RSS-210 AV
Env. / Ins.   : 23*C/54%           Engineer   : Leo-Li
EUT         : 2.4GHz 300Mbps Wireless PCI Adapter
Power supply  : DC 3.3V From PC input AC 120V/60Hz
Test mode    : IEEE802.11n HT20 CH11 2462MHz Tx
M/N         : SMCWPCI-N5
    
```

	Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2456.780	29.48	7.50	36.61	93.91	94.28	54.00	-40.28	Average
2	2483.500	29.49	7.58	36.60	51.09	51.56	54.00	2.44	Average
3	2500.000	29.50	7.62	36.60	42.91	43.43	54.00	10.57	Average

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.




```

Site no.       : 3m Chamber           Data no.      : 182
Dis. / Ant.   : 3m 3115(0911)        Ant. pol.    : VERTICAL
Limit         : RSS-210 PEAK
Env. / Ins.   : 23*C/54%             Engineer     : Leo-Li
EUT           : 2.4GHz 300Mbps Wireless PCI Adapter
Power supply  : DC 3.3V From PC input AC 120V/60Hz
Test mode     : IEEE802.11n HT20 CH11 2462MHz Tx
M/N          : SMCWPCI-N5
    
```

	Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2467.220	29.48	7.54	36.60	111.78	112.20	74.00	-38.20	Peak
2	2483.500	29.49	7.58	36.60	70.24	70.71	74.00	3.29	Peak
3	2484.800	29.49	7.58	36.60	71.06	71.53	74.00	2.47	Peak
4	2500.000	29.50	7.62	36.60	55.94	56.46	74.00	17.54	Peak

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 3m Chamber Data no. : 183
 Dis. / Ant. : 3m 3115(0911) Ant. pol. : HORIZONTAL
 Limit : RSS-210 PEAK
 Env. / Ins. : 23°C/54% Engineer : Leo-Li
 EUT : 2.4GHz 300Mbps Wireless PCI Adapter
 Power supply : DC 3.3V From PC input AC 120V/60Hz
 Test mode : IEEE802.11n HT20 CH11 2462MHz Tx
 M/N : SMCWPCI-N5
 :

	Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2467.100	29.48	7.54	36.60	101.86	102.28	74.00	-28.28	Peak
2	2483.500	29.49	7.58	36.60	57.88	58.35	74.00	15.65	Peak
3	2484.080	29.49	7.58	36.60	60.52	60.99	74.00	13.01	Peak
4	2500.000	29.50	7.62	36.60	49.98	50.50	74.00	23.50	Peak

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 3m Chamber Data no. : 184
 Dis. / Ant. : 3m 3115(0911) Ant. pol. : HORIZONTAL
 Limit : RSS-210 AV
 Env. / Ins. : 23°C/54% Engineer : Leo-Li
 EUT : 2.4GHz 300Mbps Wireless PCI Adapter
 Power supply : DC 3.3V From PC input AC 120V/60Hz
 Test mode : IEEE802.11n HT20 CH11 2462MHz Tx
 M/N : SMCWPCI-N5
 :

	Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBUV)	Emission Level (dBUV/m)	Limits (dBUV/m)	Margin (dB)	Remark
1	2455.520	29.48	7.50	36.61	84.87	85.24	54.00	-31.24	Average
2	2483.500	29.49	7.58	36.60	42.23	42.70	54.00	11.30	Average
3	2500.000	29.50	7.62	36.60	37.67	38.19	54.00	15.81	Average

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 3m Chamber Data no. : 189
 Dis. / Ant. : 3m 3115(0911) Ant. pol. : VERTICAL
 Limit : RSS-210 AV
 Env. / Ins. : 23°C/54% Engineer : Leo-Li
 EUT : 2.4GHz 300Mbps Wireless PCI Adapter
 Power supply : DC 3.3V From PC input AC 120V/60Hz
 Test mode : IEEE802.11n HT20 CH1 2412MHz Tx
 M/N : SMCWPCI-N5
 :

	Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2390.000	29.44	7.39	36.62	51.54	51.75	54.00	2.25	Average
2	2400.000	29.44	7.43	36.62	62.36	62.61	54.00	-8.61	Average
3	2419.250	29.45	7.46	36.61	93.30	93.60	54.00	-39.60	Average

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.




```

Site no.       : 3m Chamber           Data no.      : 190
Dis. / Ant.   : 3m 3115(0911)        Ant. pol.    : VERTICAL
Limit         : RSS-210 PEAK
Env. / Ins.   : 23*C/54%             Engineer     : Leo-Li
EUT           : 2.4GHz 300Mbps Wireless PCI Adapter
Power supply  : DC 3.3V From PC input AC 120V/60Hz
Test mode     : IEEE802.11n HT20 CH1 2412MHz Tx
M/N          : SMCWPCI-N5
    
```

	Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2390.000	29.44	7.39	36.62	70.12	70.33	74.00	3.67	Peak
2	2400.000	29.44	7.43	36.62	89.59	89.84	74.00	-15.84	Peak
3	2406.600	29.45	7.43	36.62	110.82	111.08	74.00	-37.08	Peak

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.




```

Site no.       : 3m Chamber           Data no.      : 191
Dis. / Ant.    : 3m 3115(0911)       Ant. pol.    : HORIZONTAL
Limit         : RSS-210 PEAK
Env. / Ins.    : 23°C/54%           Engineer     : Leo-Li
EUT           : 2.4GHz 300Mbps Wireless PCI Adapter
Power supply   : DC 3.3V From PC input AC 120V/60Hz
Test mode     : IEEE802.11n HT20 CH1 2412MHz Tx
M/N           : SMCWPCI-N5
    
```

	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	29.44	7.39	36.62	58.86	59.07	74.00	14.93	Peak
2	29.44	7.43	36.62	78.35	78.60	74.00	-4.60	Peak
3	29.45	7.43	36.62	100.61	100.87	74.00	-26.87	Peak

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.




```

Site no.      : 3m Chamber           Data no.   : 192
Dis. / Ant.   : 3m 3115(0911)       Ant. pol.  : HORIZONTAL
Limit        : RSS-210 AV
Env. / Ins.   : 23*C/54%           Engineer   : Leo-Li
EUT          : 2.4GHz 300Mbps Wireless PCI Adapter
Power supply  : DC 3.3V From PC input AC 120V/60Hz
Test mode    : IEEE802.11n HT20 CH1 2412MHz Tx
M/N         : SMCWPCI-N5
    
```

	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	29.44	7.39	36.62	42.00	42.21	54.00	11.79	Average
2	29.44	7.43	36.62	52.11	52.36	54.00	1.64	Average
3	29.45	7.46	36.61	83.19	83.49	54.00	-29.49	Average

Remarks:

- Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
- The emission levels that are 20dB below the official limit are not reported.




Site no. : 3m Chamber Data no. : 195
 Dis. / Ant. : 3m 3115(0911) Ant. pol. : VERTICAL
 Limit : RSS-210 AV
 Env. / Ins. : 23°C/54% Engineer : Leo-Li
 EUT : 2.4GHz 300Mbps Wireless PCI Adapter
 Power supply : DC 3.3V From PC input AC 120V/60Hz
 Test mode : IEEE802.11n HT40 CH3 2422MHz Tx
 M/N : SMCWPCI-N5
 :

	Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2390.000	29.44	7.39	36.62	51.56	51.77	54.00	2.23	Average
2	2400.000	29.44	7.43	36.62	56.04	56.29	54.00	-2.29	Average
3	2433.480	29.46	7.46	36.61	85.92	86.23	54.00	-32.23	Average

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.




```

Site no.      : 3m Chamber           Data no.   : 196
Dis. / Ant.  : 3m 3115(0911)        Ant. pol.  : VERTICAL
Limit        : RSS-210 PEAK
Env. / Ins.  : 23*C/54%             Engineer   : Leo-Li
EUT         : 2.4GHz 300Mbps Wireless PCI Adapter
Power supply : DC 3.3V From PC input AC 120V/60Hz
Test mode    : IEEE802.11n HT40 CH3 2422MHz Tx
M/N         : SMCWPCI-N5
    
```

	Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBUV)	Emission Level (dBUV/m)	Limits (dBUV/m)	Margin (dB)	Remark
1	2390.000	29.44	7.39	36.62	69.69	69.90	74.00	4.10	Peak
2	2400.000	29.44	7.43	36.62	84.31	84.56	74.00	-10.56	Peak
3	2407.580	29.45	7.43	36.62	105.68	105.94	74.00	-31.94	Peak

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 3m Chamber Data no. : 197
 Dis. / Ant. : 3m 3115(0911) Ant. pol. : HORIZONTAL
 Limit : RSS-210 PEAK
 Env. / Ins. : 23°C/54% Engineer : Leo-Li
 EUT : 2.4GHz 300Mbps Wireless PCI Adapter
 Power supply : DC 3.3V From PC input AC 120V/60Hz
 Test mode : IEEE802.11n HT40 CH3 2422MHz Tx
 M/N : SMCWPCI-N5
 :

	Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2390.000	29.44	7.39	36.62	58.61	58.82	74.00	15.18	Peak
2	2400.000	29.44	7.43	36.62	73.09	73.34	74.00	0.66	Peak
3	2436.000	29.46	7.46	36.61	95.02	95.33	74.00	-21.33	Peak

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.




```

Site no.      : 3m Chamber           Data no.   : 198
Dis. / Ant.  : 3m 3115(0911)        Ant. pol.  : HORIZONTAL
Limit        : RSS-210 AV
Env. / Ins.  : 23*C/54%             Engineer   : Leo-Li
EUT          : 2.4GHz 300Mbps Wireless PCI Adapter
Power supply : DC 3.3V From PC input AC 120V/60Hz
Test mode    : IEEE802.11n HT40 CH3 2422MHz Tx
M/N         : SMCWPCI-N5
    
```

	Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2390.000	29.44	7.39	36.62	42.63	42.84	54.00	11.16	Average
2	2400.000	29.44	7.43	36.62	46.84	47.09	54.00	6.91	Average
3	2430.680	29.46	7.46	36.61	76.59	76.90	54.00	-22.90	Average

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.




```

Site no.       : 3m Chamber           Data no.   : 203
Dis. / Ant.    : 3m 3115(0911)       Ant. pol.  : VERTICAL
Limit         : RSS-210 AV
Env. / Ins.    : 23*C/54%           Engineer   : Leo-Li
EUT           : 2.4GHz 300Mbps Wireless PCI Adapter
Power supply   : DC 3.3V From PC input AC 120V/60Hz
Test mode      : IEEE802.11n HT40 CH9 2452MHz Tx
M/N           : SMCWPCI-N5
    
```

	Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2458.240	29.48	7.50	36.61	86.03	86.40	54.00	-32.40	Average
2	2483.500	29.49	7.58	36.60	51.32	51.79	54.00	2.21	Average
3	2500.000	29.50	7.62	36.60	42.93	43.45	54.00	10.55	Average

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 3m Chamber Data no. : 204
 Dis. / Ant. : 3m 3115(0911) Ant. pol. : VERTICAL
 Limit : RSS-210 PEAK
 Env. / Ins. : 23°C/54% Engineer : Leo-Li
 EUT : 2.4GHz 300Mbps Wireless PCI Adapter
 Power supply : DC 3.3V From PC input AC 120V/60Hz
 Test mode : IEEE802.11n HT40 CH9 2452MHz Tx
 M/N : SMCWPCI-N5
 :

	Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2459.360	29.48	7.54	36.61	105.45	105.86	74.00	-31.86	Peak
2	2483.500	29.49	7.58	36.60	69.87	70.34	74.00	3.66	Peak
3	2483.840	29.49	7.58	36.60	70.98	71.45	74.00	2.55	Peak
4	2500.000	29.50	7.62	36.60	57.84	58.36	74.00	15.64	Peak

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.




```

Site no.      : 3m Chamber           Data no.   : 205
Dis. / Ant.  : 3m 3115(0911)       Ant. pol.  : HORIZONTAL
Limit        : RSS-210 PEAK
Env. / Ins.  : 23*C/54%           Engineer   : Leo-Li
EUT          : 2.4GHz 300Mbps Wireless PCI Adapter
Power supply : DC 3.3V From PC input AC 120V/60Hz
Test mode    : IEEE802.11n HT40 CH9 2452MHz Tx
M/N         : SMCWPCI-N5
    
```

	Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2458.400	29.48	7.50	36.61	94.86	95.23	74.00	-21.23	Peak
2	2483.500	29.49	7.58	36.60	59.16	59.63	74.00	14.37	Peak
3	2500.000	29.50	7.62	36.60	49.12	49.64	74.00	24.36	Peak

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 206
 Dis. / Ant. : 3m 3115(0911) Ant. pol. : HORIZONTAL
 Limit : RSS-210 AV
 Env. / Ins. : 23°C/54% Engineer : Leo-Li
 EUT : 2.4GHz 300Mbps Wireless PCI Adapter
 Power supply : DC 3.3V From PC input AC 120V/60Hz
 Test mode : IEEE802.11n HT40 CH9 2452MHz Tx
 M/N : SMCWPCI-N5
 :

	Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2458.240	29.48	7.50	36.61	76.68	77.05	54.00	-23.05	Average
2	2483.500	29.49	7.58	36.60	42.44	42.91	54.00	11.09	Average
3	2500.000	29.50	7.62	36.60	37.46	37.98	54.00	16.02	Average

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.

7. 6dB Bandwidth Test

7.1. Test Equipment

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Spectrum	Agilent	E4446A	US44300459	May.08, 13	1 Year
2.	Antenna	EMCO	3115	9607-4877	May.08, 13	1 Year
3.	HF Cable	Hubersuhner	Sucoflex104	-	May.08, 13	1 Year

7.2. Limit

For direct sequence systems, the minimum 6dB bandwidth shall be at least 500kHz

7.3. Test Procedure

The transmitter output was connected to a spectrum analyzer, The bandwidth of the fundamental frequency was measured by spectrum analyzer with 100kHz RBW and 300 kHz VBW. The 6dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 6dB.

7.4. Test Results

EUT:2.4GHz 300Mbps Wireless PCI Adapter		
M/N: SMCWPCI-N5		
Test date: 2013-06-12	Pressure: 101.1 kpa	Humidity: 53.2%
Tested by: Leo-Li	Test site: RF Site	Temperature : 25.1 °C

Cable loss: 1 dB		Attenuator loss: 20 dB		Antenna Gain: 2 dBi
Test Mode	CH	6dB bandwidth (MHz)		Limit (KHz)
		Chain0	Chain1	
11b	CH1	10.162	10.151	>500
	CH6	10.156	10.160	>500
	CH11	10.159	10.173	>500
11g	CH1	16.457	16.463	>500
	CH6	16.451	16.471	>500
	CH11	16.465	16.457	>500
11n HT20	CH1	17.658	17.644	>500
	CH6	17.652	17.634	>500
	CH11	17.673	17.669	>500
11n HT40	CH1	36.722	36.708	>500
	CH4	36.760	36.727	>500
	CH7	36.699	36.682	>500
Conclusion : PASS				

Chain 0:

Test Mode: IEEE 802.11b TX

Test CH1: 2412MHz

* **Agilent**
Trace

Ch Freq 2.412 GHz
Trig Free

Occupied Bandwidth

Ref 21 dBm
Atten 10 dB

#Peak
 Log
 10
 dB/
 Offst
 21
 dB

Center 2.412 00 GHz
Span 50 MHz

#Res BW 100 kHz
#VBW 300 kHz
Sweep 4.8 ms (601 pts)

Occupied Bandwidth	Occ BW % Pwr 99.00 %
14.1224 MHz	x dB -6.00 dB
Transmit Freq Error	-13.019 kHz
x dB Bandwidth	10.162 MHz

File Operation Status, A:\SCREN066.GIF file saved

Trace

1
2
3

Trace

Clear Write

Max Hold

Min Hold

View

Blank

More
1 of 2

Test CH6: 2437MHz

* **Agilent**
Trace

Ch Freq 2.437 GHz
Trig Free

Occupied Bandwidth

Ref 21 dBm
Atten 10 dB

#Peak
 Log
 10
 dB/
 Offst
 21
 dB

Center 2.437 00 GHz
Span 50 MHz

#Res BW 100 kHz
#VBW 300 kHz
Sweep 4.8 ms (601 pts)

Occupied Bandwidth	Occ BW % Pwr 99.00 %
14.1643 MHz	x dB -6.00 dB
Transmit Freq Error	-6.811 kHz
x dB Bandwidth	10.156 MHz

File Operation Status, A:\SCREN068.GIF file saved

Trace

1
2
3

Trace

Clear Write

Max Hold


Min Hold

View

Blank


More
1 of 2

Test CH11: 2462MHz




Test Mode: IEEE 802.11g TX


Test CH1: 2412MHz



Test CH6: 2437MHz



Test CH11: 2462MHz



Test Mode: IEEE 802.11n HT20 TX
 Test CH1: 2412MHz

* Agilent

Ch Freq 2.412 GHz
Trig Free

Ref 21 dBm
Atten 10 dB

#Peak
 Log
 10
 dB/
 Offst
 21
 dB

Center 2.412 00 GHz
Span 50 MHz

#Res BW 100 kHz
#VBW 300 kHz
Sweep 4.8 ms (601 pts)

Occupied Bandwidth	Occ BW % Pwr	99.00 %
18.8637 MHz	x dB	-6.00 dB
Transmit Freq Error		-14.710 kHz
x dB Bandwidth		17.658 MHz

File Operation Status, A:\SCREN063.GIF file saved

Trace

1
2
3

Trace

Clear Write

Max Hold

Min Hold

View

Blank

More
1 of 2

Test CH6: 2437MHz

* Agilent

Ch Freq 2.437 GHz
Trig Free

Ref 21 dBm
Atten 10 dB

#Peak
 Log
 10
 dB/
 Offst
 21
 dB

Center 2.437 00 GHz
Span 50 MHz

#Res BW 100 kHz
#VBW 300 kHz
Sweep 4.8 ms (601 pts)

Occupied Bandwidth	Occ BW % Pwr	99.00 %
20.1374 MHz	x dB	-6.00 dB
Transmit Freq Error		54.665 kHz
x dB Bandwidth		17.652 MHz

File Operation Status, A:\SCREN061.GIF file saved

Trace

1
2
3

Trace

Clear Write

Max Hold


Min Hold

View

Blank


More
1 of 2

Test CH11: 2462MHz




Test Mode: IEEE 802.11n HT40 TX


Test CH1: 2422MHz



Test CH4: 2437MHz




Test CH7: 2452MHz




Chain 1:

Test Mode: IEEE 802.11b TX


Test CH1: 2412MHz



Test CH6: 2437MHz




Test CH11: 2462MHz




Test Mode: IEEE 802.11g TX


Test CH1: 2412MHz




Test CH6: 2437MHz




Test CH11: 2462MHz




Test Mode: IEEE 802.11n HT20 TX
 Test CH1: 2412MHz



Test CH6: 2437MHz




Test CH11: 2462MHz




Test Mode: IEEE 802.11n HT40 TX


Test CH1: 2422MHz



Test CH4: 2437MHz



Test CH7: 2452MHz



8. OUTPUT POWER TEST

8.1. Test Equipment

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Spectrum	Agilent	E4446A	US44300459	May.08, 13	1 Year
2.	Amp	HP	8449B	3008A08495	May.08, 13	1 Year
3.	Antenna	EMCO	3115	9607-4877	May.08, 13	1 Year
4.	HF Cable	Hubersuhne	Sucoflex104	-	May.08, 13	1 Year
4.	Power Meter	Anritsu	ML2487A	6K00002472	May.08, 13	1 Year
5.	Power Sensor	Anritsu	MA2491A	033005	May.08, 13	1 Year

8.2. Limit (FCC Part 15C 15.247 b(3))

For systems using digital modulation in the 2400—2483.5MHz, The Peak out put Power shall not exceed 1W(30dBm)

8.3. Test Procedure

- 1, Connected the EUT's antenna port to measure device by 26dB attenuator.
- 2, For IEEE 802.11b/g and IEEE802.11n HT20 mode, use a PK power meter which's bandwidth is 20MHz and above 26dB bandwidth of signal to measure out each test modes' PK output power.
- 3, For IEEE802.11n HT40 mode, because the signal's bandwidth is about 40MHz and above 20MHz bandwidth of power sensor ML2491A. So Bandwidth correction method according to ANSI C63.10 clause 6.10.2.1 part (c) was used:
 - 1) Set the RBW=3MHz and VBW =8MHz
 - 2) Turn averaging off
 - 3) Set sweep to automatic
 - 4) Set the span just large enough to capture the emission
 - 5) Use a peak detector on max hold
 - 6) Record the measured power
 - 7) Calculate Output power of EUT use the formula:

Peak output power =measured power+ 10log[(26dB bandwidth of emission)/(analyzer RBW)]

Note: The cable loss and attenuator loss were offset into measure device as an amplitude offset.



8.4. Test Results


EUT: 2.4GHz 300Mbps Wireless PCI Adapter					
M/N: SMCWPCI-N5					
Test date: 2012-06-16		Pressure: 101.3 kpa		Humidity: 53 %	
Tested by: Leo-Li		Test site: RF site		Temperature: 25 °C	
Cable loss: 1 dB		Attenuator loss: 20 dB		Antenna Gain: 2 dBi	
Test Mode	CH (MHz)	Peak output Power (dBm)			Limit (dBm)
		Chain0	Chain1	Total	
11b	CH1	19.56	17.14	N/A	30
	CH6	18.67	17.79	N/A	30
	CH11	18.70	18.07	N/A	30
11g	CH1	22.54	19.44	N/A	30
	CH6	24.37	23.29	N/A	30
	CH11	16.87	16.35	N/A	30
11n HT20	CH1	17.49	15.93	19.84	30
	CH6	22.74	23.13	25.96	30
	CH11	15.65	16.13	18.96	30

Test Mode	CH	Result					Limit (dBm)
		Measured power(dBm)/3MHz		PK Output power (dBm)			
		Chain0	Chain1	Chain0	Chain1	Total	
11n HT40	CH1	3.57	3.48	14.77	14.65	17.72	30
	CH4	11.60	12.00	22.80	23.17	26.00	30
	CH7	3.41	3.92	14.61	15.09	17.87	30
Chain 0		26dB Bandwidth for 11n HT40: 39.514MHz					
Chain 1		26dB Bandwidth for 11n HT40: 39.303MHz					
Chain 0		BW correction factor = $10\log[(39.514\text{MHz})/(3\text{MHz})] = 11.20\text{dB}$					
Chain 1		BW correction factor = $10\log[(39.303\text{MHz})/(3\text{MHz})] = 11.17\text{dB}$					
Conclusion: PASS							


Chain 0:



Test Mode: IEEE 802.11n HT40







26dB Bandwidth







Chain 1:



Test Mode: IEEE 802.11n HT40





26dB Bandwidth





9. POWER SPECTRAL DENSITY TEST

9.1. Test Equipment

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Spectrum	Agilent	E4446A	US44300459	May.08, 13	1 Year
2.	Amp	HP	8449B	3008A08495	May.08, 13	1 Year
3.	Antenna	EMCO	3115	9607-4877	Aug.28, 13	1Year
4.	HF Cable	Hubersuhne	Sucoflex104	-	May.08, 13	1 Year

9.2. Limit

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3kHz band during any time interval of continuous transmission.

9.3. Test Procedure

1. Connected the EUT's antenna port to spectrum analyzer device by 20dB attenuator.
2. Set the test frequency as center frequency, Set RBW=3KHz, VBW=10KHz, Span large enough capture the entire frequency, Read out maximum peak level frequency
3. Set the frequency read from produce 2 as center frequency, then set the span=300KHz, Sweep time=Span/RBW, Then Max hold, read out each mode and each chain's Power density.

Note: The cable loss and attenuator loss were offset into measure device as an amplitude

9.4. Test Results

EUT: 2.4GHz 300Mbps Wireless PCI Adapter		
M/N: SMCWPCI-N5		
Test date: 2013-06-16	Pressure: 101.9 Kpa	Humidity: 53.6 %
Tested by: Leo-Li	Test site: RF Site	Temperature: 25.2°C


Cable loss: 1 dB		Attenuator loss: 20 dB			Antenna Gain: 2 dBi
Test Mode	CH	Power density (dBm/3KHz)			Limit (dBm/3KHz)
		Chain0	Chain1	Total	
11b	CH1	-8.37	-9.28	N/A	8
	CH6	-8.14	-9.41	N/A	8
	CH11	-9.30	-9.44	N/A	8
11g	CH1	-13.28	-13.53	N/A	8
	CH6	-9.81	-10.26	N/A	8
	CH11	-15.00	-15.70	N/A	8
11n HT20	CH1	-17.30	-17.79	-14.53	8
	CH6	-10.59	-10.66	-7.61	8
	CH11	-17.03	-17.16	-14.08	8
11n HT40	CH1	-21.57	-20.58	-18.04	8
	CH4	-13.40	-11.89	-9.57	8
	CH7	-21.71	-21.10	-18.38	8

Conclusion : PASS


Chain 0:

Test Mode: IEEE 802.11b TX


Test CH1: 2412MHz



Test CH6: 2437MHz




Test CH11: 2462MHz




Test Mode: IEEE 802.11g TX


Test CH1: 2412MHz




Test CH6: 2437MHz




Test CH11: 2462MHz




Test Mode: IEEE 802.11n HT20 TX
 Test CH1: 2412MHz



Test CH6: 2437MHz




Test CH11: 2462MHz




Test Mode: IEEE 802.11n HT40 TX


Test CH1: 2422MHz



Test CH4: 2437MHz




Test CH7: 2452MHz




Chain 1:

Test Mode: IEEE 802.11b TX


Test CH1: 2412MHz



Test CH6: 2437MHz




Test CH11: 2462MHz




Test Mode: IEEE 802.11g TX


Test CH1: 2412MHz




Test CH6: 2437MHz




Test CH11: 2462MHz




Test Mode: IEEE 802.11n HT20 TX
 Test CH1: 2412MHz



Test CH6: 2437MHz




Test CH11: 2462MHz




Test Mode: IEEE 802.11n HT40 TX


Test CH1: 2422MHz



Test CH4: 2437MHz



Test CH7: 2452MHz



10. ANTENNA REQUIREMENT

10.1. STANDARD APPLICABLE

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

10.2. ANTENNA CONNECTED CONSTRUCTION

The antennas used for this product are Dipole PCB antenna that no antenna other than that furnished by the responsible party shall be used with the device, the maximum peak gain of the transmit antenna is 2dBi.

11.MPE ESTIMATION

11.1.Limit for General Population/ Uncontrolled Exposures

Frequency	Power density (mW/ cm ²)	Averaging time(minutes)
300MHz----1.5GHz	F/1500	30
1.5GHz---100GHz	1.0	30

Frequency(MHz)	Power density (mW/ cm ²)	Averaging time(minutes)
2412	1	30
2437	1	30
2462	1	30

Note: F= Frequency in MHz

11.2. Estimation Result

EUT: 2.4GHz 300Mbps Wireless PCI Adapter		
M/N: SMCWPCI-N5		
Test date: 2013-06-16	Pressure: 100.6 kpa	Humidity: 47%
Tested by: Leo-Li	Test site: RF Site	Temperature: 25°C

Cable loss: 1 dB		Attenuator loss: 20 dB				Antenna Gain: 2 dBi	
Test Mode	CH	Frequency (MHz)	Peak Output Power (dBm)	Output Power (mW)	Antenna Gain (dBi)	Antenna Gain (Linear)	MPE
11b	CH1	2412	19.56	90.36	2	1.58	0.0285
	CH6	2437	18.67	73.62	2	1.58	0.0232
	CH11	2462	18.7	74.13	2	1.58	0.0234
11g	CH1	2412	22.54	179.47	2	1.58	0.0566
	CH6	2437	24.37	273.53	2	1.58	0.0863
	CH11	2462	16.87	48.64	2	1.58	0.0153
11n HT20	CH1	2412	19.84	96.38	2	1.58	0.0304
	CH6	2437	25.96	394.46	2	1.58	0.1244
	CH11	2462	18.96	78.70	2	1.58	0.0248
11n HT40	CH1	2412	17.72	59.16	2	1.58	0.0187
	CH4	2437	26	398.11	2	1.58	0.1256
	CH7	2462	17.87	61.24	2	1.58	0.0193

12. DEVIATION TO TEST SPECIFICATIONS

[NONE]