

RADIO PERFORMANCE TEST REPORT

Test Report No. : OT-223-RWD-044
Reception No. : 2112005097
Applicant : LG Innotek Co., Ltd.
Address : 26, Hanamsandan 5beon-ro Gwangsan-gu, Gwangju, 506-731, South Korea
Manufacturer : LG Innotek Co., Ltd.
Address : 26, Hanamsandan 5beon-ro Gwangsan-gu, Gwangju, 506-731, South Korea
Type of Equipment : RF Module
FCC ID. : YZP-ATC6NPL002
Model Name : ATC6NPL002
Multiple Model Name : N/A
Serial number : N/A
Total page of Report : 166 pages (including this page)
Date of Incoming : December 01, 2021
Date of issue : March 21, 2022

SUMMARY

The equipment complies with the regulation; **FCC PART 15 SUBPART E Section 15.407**

This test report only contains the result of a single test of the sample supplied for the examination.

It is not a generally valid assessment of the features of the respective products of the mass-production.

Tested by
Youngyong Kim/ Manager
ONETECH Corp.

Reviewed by
Tae-Ho, Kim / Senior Manager
ONETECH Corp.

Approved by
Ki-Hong, Nam / General Manager
ONETECH Corp.

This Report is not correlated with the authentication of KOLAS

It should not be reproduced except in full, without the written approval of ONETECH Corp.

OTC-TRF-RF-001(0)

ONETECH Corp.: 43-14, Jinsaegol-gil, Chowol-eup, Gwangju-si, Gyeonggi-do, 12735, Korea (TEL: 82-31-799-9500, FAX: 82-31-799-9599)

CONTENTS

	PAGE
1. VERIFICATION OF COMPLIANCE	9
2. TEST SUMMARY.....	10
2.1 TEST ITEMS AND RESULTS	10
2.2 ADDITIONS, DEVIATIONS, EXCLUSIONS FROM STANDARDS.....	10
2.3 RELATED SUBMITTAL(S) / GRANT(S)	10
2.4 PURPOSE OF THE TEST	10
2.5 TEST METHODOLOGY.....	10
2.6 TEST FACILITY.....	10
3. GENERAL INFORMATION.....	11
3.1 PRODUCT DESCRIPTION.....	11
4. EUT MODIFICATIONS.....	32
5. SYSTEM TEST CONFIGURATION	33
5.1 JUSTIFICATION.....	33
5.2 PERIPHERAL EQUIPMENT	33
5.3 MODE OF OPERATION DURING THE TEST	34
5.4 CONFIGURATION OF TEST SYSTEM.....	40
5.5 ANTENNA REQUIREMENT	40
6. PRELIMINARY TEST	40
6.1 AC POWER LINE CONDUCTED EMISSIONS TESTS.....	40
6.2 GENERAL RADIATED EMISSIONS TESTS	40
7. 99 % OCCUPIED BANDWIDTH & MINIMUM 26 DB BANDWIDTH	41
7.1 OPERATING ENVIRONMENT	41
7.2 TEST SET-UP	41
7.3 TEST DATE	41
7.4 TEST DATA FOR 802.11A RLAN MODE.....	42
7.4.1 Test data for Antenna 0	42
7.4.2 Test data for Antenna 1	44
7.5 TEST DATA FOR 802.11N_HT20 RLAN MODE	46
7.5.1 Test data for Antenna 0	46
7.5.2 Test data for Antenna 1	48
7.6 TEST DATA FOR 802.11N_HT40 RLAN MODE	50
7.6.1 Test data for Antenna 0	50

7.6.2 Test data for Antenna 1	52
7.7 TEST DATA FOR 802.11AC_VHT80 RLAN MODE.....	54
 7.7.1 Test data for Antenna 0	54
 7.7.2 Test data for Antenna 1	55
8. 6 DB BANDWIDTH	56
 8.1 OPERATING ENVIRONMENT	56
 8.2 TEST SET-UP	56
 8.3 TEST DATE	56
 8.4 TEST DATA FOR 802.11A RLAN MODE.....	57
 8.4.1 Test data for Antenna 0	57
 8.4.2 Test data for Antenna 1	57
 8.4.3 Test data for Staddle Channel_Antenna 0	57
 8.4.4 Test data for Staddle Channel_Antenna 1	57
 8.5 TEST DATA FOR 802.11N_HT20 RLAN MODE.....	58
 8.5.1 Test data for Antenna 0	58
 8.5.2 Test data for Antenna 1	58
 8.5.3 Test data for Staddle Channel_Antenna 0	58
 8.5.4 Test data for Staddle Channel_Antenna 1	58
 8.6 TEST DATA FOR 802.11N_HT40 RLAN MODE.....	59
 8.6.1 Test data for Antenna 0	59
 8.6.2 Test data for Antenna 1	59
 8.6.3 Test data for Staddle Channel_Antenna 0	59
 8.6.4 Test data for Staddle Channel_Antenna 1	59
 8.7 TEST DATA FOR 802.11AC_VHT80 RLAN MODE.....	60
 8.7.1 Test data for Antenna 0	60
 8.7.2 Test data for Antenna 1	60
 8.7.3 Test data for Staddle Channel_Antenna 0	60
 8.7.4 Test data for Staddle Channel_Antenna 1	60
9. MAXIMUM CONDUCTED(AVERAGE) OUTPUT POWER	61
 9.1 OPERATING ENVIRONMENT	61
 9.2 TEST SET-UP	61
 9.3 TEST DATE	61
 9.4 TEST DATA FOR 802.11A RLAN MODE.....	62
 9.4.1 Test data for Antenna 0	62
 9.4.2 Test data for Antenna 1	63
 9.4.3 Test data for Staddle Channel_Antenna 0	64
 9.4.4 Test data for Staddle Channel_Antenna 1	64

9.5 TEST DATA FOR 802.11N_HT20 RLAN MODE	65
9.5.1 Test data for Antenna 0	65
9.5.2 Test data for Antenna 1	66
9.5.3 Test data for Multiple Transmit	67
9.5.4 Test data for Staddle Channel_Antenna 0	68
9.5.5 Test data for Staddle Channel_Antenna 1	68
9.5.6 Test data for Staddle Channel_Multiple Transmit	68
9.6 TEST DATA FOR 802.11N_HT40 RLAN MODE	69
9.6.1 Test data for Antenna 0	69
9.6.2 Test data for Antenna 1	70
9.6.3 Test data for Multiple Transmit	71
9.6.4 Test data for Staddle Channel_Antenna 0	72
9.6.5 Test data for Staddle Channel_Antenna 1	72
9.6.6 Test data for Staddle Channel_Multiple Transmit	72
9.7 TEST DATA FOR 802.11AC_HT80 RLAN MODE.....	73
9.7.1 Test data for Antenna 0	73
9.7.2 Test data for Antenna 1	73
9.7.3 Test data for Multiple Transmit	74
9.7.4 Test data for Staddle Channel_Antenna 0	75
9.7.5 Test data for Staddle Channel_Antenna 1	75
9.7.6 Test data for Staddle Channel_Multiple Transmit	75
10. PEAK POWER SPECTRUL DENSITY	76
10.1 OPERATING ENVIRONMENT	76
10.2 TEST SET-UP	76
10.3 TEST DATE	76
10.4 TEST DATA FOR 802.11A RLAN MODE.....	77
10.4.1 Test data for Antenna 0	77
10.4.2 Test data for Antenna 1	78
10.4.3 Test data for Staddle Channel_Antenna 0	79
10.4.4 Test data for Staddle Channel_Antenna 1	79
10.5 TEST DATA FOR 802.11N_HT20 RLAN MODE	80
10.5.1 Test data for Antenna 0	80
10.5.2 Test data for Antenna 1	81
10.5.3 Test data for Multiple Transmit	82
10.5.4 Test data for Staddle Channel_Antenna 0	83
10.5.5 Test data for Staddle Channel_Antenna 1	83
10.5.6 Test data for Staddle Channel_Multiple Transmit	83

10.6 TEST DATA FOR 802.11N_HT40 RLAN MODE	84
10.6.1 Test data for Antenna 0	84
10.6.4 Test data for Staddle Channel_Antenna 0	87
10.6.5 Test data for Staddle Channel_Antenna 1	87
10.6.6 Test data for Staddle Channel_Multiple Transmit	87
10.7 TEST DATA FOR 802.11AC_HT80 RLAN MODE.....	88
10.7.1 Test data for Antenna 0	88
10.7.2 Test data for Antenna 1	88
10.7.3 Test data for Multiple Transmit	89
10.7.4 Test data for Staddle Channel_Antenna 0	90
10.7.5 Test data for Staddle Channel_Antenna 1	90
10.7.6 Test data for Staddle Channel_Multiple Transmit	90
11. FREQUENCY STABILITY WITH TEMPERATURE VARIATION.....	91
11.1 OPERATING ENVIRONMENT	91
11.2 TEST SET-UP	91
11.3 TEST DATE	91
11.4 TEST DATA FOR U-NII-1	92
11.5 TEST DATA FOR U-NII-2A.....	93
11.6 TEST DATA FOR U-NII-2C.....	94
11.7 TEST DATA FOR U-NII-3	95
12. FREQUENCY STABILITY WITH VOLTAGE VARIATION.....	96
12.1 OPERATING ENVIRONMENT	96
12.2 TEST SET-UP	96
12.3 TEST DATE	96
12.4 TEST DATA FOR U-NII-1	97
12.5 TEST DATA FOR U-NII-2A.....	97
12.6 TEST DATA FOR U-NII-2C.....	98
12.7 TEST DATA FOR U-NII-3	98
13. RADIATED SPURIOUS EMISSIONS	99
13.1 OPERATING ENVIRONMENT	99
13.2 TEST SET-UP FOR CONDUCTED MEASUREMENT	99
13.3 TEST DATE	99
13.4 TEST DATA FOR BELOW 30 MHZ	100
13.5 TEST DATA FOR 30 MHZ ~ 1 000 MHZ	101
13.5.1 Test data for WLAN 5 GHz	101
13.5.2 Test data for Intermodulation Mode(WLAN 5 GHz + Bluetooth)	102
13.5.3 Test data for Intermodulation Mode(WLAN 5 GHz + Bluetooth LE)	103

<i>13.5.4 Test data for Intermodulation Mode(WLAN 5 GHz + WLAN 2.4 GHz)</i>	104
13.6 TEST DATA FOR ABOVE 1 GHZ	105
<i>13.6.1 Test data for Frequency UNII 1</i>	105
<i>13.6.2 Test data for Frequency UNII 2A</i>	109
<i>13.6.3 Test data for Frequency UNII 2C</i>	114
<i>13.6.4 Test data for Frequency UNII 3</i>	119
14. RADIATED RESTRICTED BAND EDGE MEASUREMENTS	124
14.1 OPERATING ENVIRONMENT	124
14.2 TEST SET-UP FOR CONDUCTED MEASUREMENT	124
14.3 TEST DATE	124
14.4 TEST DATA FOR FREQUENCY UNII 1	125
<i>14.4.1 Test data for 802.11a RLAN Mode</i>	125
<i>14.4.2 Test data for 802.11n_HT20 RLAN Mode</i>	126
<i>14.4.3 Test data for 802.11n_HT40 RLAN Mode</i>	127
<i>14.4.4 Test data for 802.11ac_VHT80 RLAN Mode</i>	128
14.5 TEST DATA FOR FREQUENCY UNII 2A	129
<i>14.5.1 Test data for 802.11a RLAN Mode</i>	129
<i>14.5.2 Test data for 802.11n_HT20 RLAN Mode</i>	130
<i>14.5.3 Test data for 802.11n_HT40 RLAN Mode</i>	131
<i>14.5.4 Test data for 802.11ac_VHT80 RLAN Mode</i>	132
14.6 TEST DATA FOR FREQUENCY UNII 2C	133
<i>14.6.1 Test data for 802.11a RLAN Mode</i>	133
<i>14.6.2 Test data for 802.11n_HT20 RLAN Mode</i>	134
<i>14.6.3 Test data for 802.11n_HT40 RLAN Mode</i>	135
<i>14.6.4 Test data for 802.11ac_VHT80 RLAN Mode</i>	136
14.7 TEST DATA FOR FREQUENCY U-NII-3	137
<i>14.7.1 Test data for 802.11a RLAN Mode</i>	137
<i>14.7.2 Test data for 802.11n_HT20 RLAN Mode</i>	141
<i>14.7.3 Test data for 802.11n_HT40 RLAN Mode</i>	143
<i>14.7.4 Test data for 802.11ac_VHT80 RLAN Mode</i>	145
<i>14.7.5 U-NII-3 Emission Limits</i>	146
15. CONDUCTED EMISSION TEST	147
15.1 OPERATING ENVIRONMENT	147
15.2 TEST SET-UP	147
15.3 TEST DATE	147
15.4 TEST DATA FOR WLAN 5 GHz	148

16. DYNAMIC FREQUENCY SELECTION (DFS)	156
16.1 OPERATING ENVIRONMENT	156
16.2 TEST SET-UPS	156
16.3 DFS TEST SIGNALS	158
16.4 TECHNICAL REQUIREMENT SPECIFICATION	159
16.5 TEST DATE	159
16.6 TEST DATA	160
16.6.1 UNII 2A.....	160
16.6.2 UNII 3	163
17. LIST OF TEST EQUIPMENT	166

* Please refer to the Annex section for All test plots

Revision History

Rev. No.	Issue Report No.	Issued Date	Revisions	Section Affected
0	OT-223-RWD-044	March 21, 2022	Initial Release	All

1. VERIFICATION OF COMPLIANCE

Applicant : LG Innotek Co., Ltd.

Address : 26, Hanamsandan 5beon-ro Gwangsan-gu, Gwangju, 506-731, South Korea

Contact Person : Jeong Inchang / Senior Research Engineer

Telephone No. : +82-62-950-0332

FCC ID : YZP-ATC6NPL002

Model Name : ATC6NPL002

Brand Name :  **LG Innotek**

Serial Number : N/A

Date : March 21, 2022

EQUIPMENT CLASS	Unlicensed National Information Infrastructure(UNII)
E.U.T. DESCRIPTION	RF Module
THIS REPORT CONCERNS	Original Grant
MEASUREMENT PROCEDURES	ANSI C63.10: 2020
TYPE OF EQUIPMENT TESTED	Pre-Production
KIND OF EQUIPMENT	Certification
AUTHORIZATION REQUESTED	
EQUIPMENT WILL BE OPERATED UNDER FCC RULES PART(S)	FCC PART 15 SUBPART E Section 15.407 789033 D02 General UNII Test Procedures New Rules v02r01
Modifications on the Equipment to Achieve Compliance	None
Final Test was Conducted On	3 m, Semi Anechoic Chamber

- The above equipment was tested by ONETECH Corp. for compliance with the requirement set forth in the FCC Rules and Regulations. This said equipment in the configuration described in this report, shows the maximum emission levels emanating from equipment are within the compliance requirements.

2. TEST SUMMARY

2.1 Test items and results

SECTION	TEST ITEMS	RESULTS
15.407(a)	26 dB Bandwidth	PASS
15.407(a)	Maximum Conducted Output Power	Met the Limit / PASS
15.407(a)	Peak Power Spectral Density	Met the Limit / PASS
15.407(e)	6 dB Bandwidth	Met the Limit / PASS
15.407(g)	Frequency Stability	Met the Limit / PASS
15.407(b)	Undesirable Emissions	Met the Limit / PASS
15.205, 15.407(b)	General Field Strength Limits (Restricted Bands and Radiated Emission Limits)	Met the Limit / PASS
15.207	Conducted Limits	Met the Limit / PASS

2.2 Additions, deviations, exclusions from standards

No additions, deviations or exclusions have been made from standard.

2.3 Related Submittal(s) / Grant(s)

Original submittal only

2.4 Purpose of the test

To determine whether the equipment under test fulfills the requirements of the regulation stated in FCC PART 15 SUBPART E Section 15.407

2.5 Test Methodology

Both conducted and radiated testing was performed according to the procedures in ANSI C63.10: 2020. Radiated testing was performed at a distance of 3 m from EUT to the antenna.

2.6 Test Facility

The Onetech Corp. has been designated to perform equipment testing in compliance with ISO/IEC 17025.

The Electromagnetic compatibility measurement facilities are located at 43-14, Jinsaegol-gil, Chowol-eup, Gwangju-si, Gyeonggi-do, 12735, Korea.

- Site Filing:

VCCI (Voluntary Control Council for Interference) – Registration No. R-20122/ C-14617/ G-10666/ T-11842

ISED (Innovation, Science and Economic Development Canada) – Registration No. Site# 3736A-3

KOLAS (Korea Laboratory Accreditation Scheme) - Accreditation NO. KT085

FCC (Federal Communications Commission) - Accreditation No. KR0013

RRA (Radio Research Agency) – Designation No. KR0013

3. GENERAL INFORMATION

3.1 Product Description

The LG Innotek Co., Ltd., Model ATC6NPL002 (referred to as the EUT in this report) is a RF Module. The product specification described herein was obtained from product data sheet or user's manual.

DEVICE TYPE	RF Module	
OPERATING FREQUENCY	Bluetooth LE	2 402 MHz ~ 2 480 MHz
	Bluetooth	2 402 MHz ~ 2 480 MHz
	WLAN 2.4 GHz	2 412 MHz ~ 2 462 MHz (802.11b/g/n(HT20)/ax(HE20))
		2 422 MHz ~ 2 452 MHz (802.11n(HT40)/ax(HE40))
	WLAN 5 150 MHz ~ 5 250 MHz Band	5 180 MHz ~ 5 240 MHz (802.11a/n(HT20)/ac(VHT20)/ax(HE20))
		5 190 MHz ~ 5 230 MHz (802.11n(HT40)/ac(VHT40)/ax(HE40))
		5 210 MHz (802.11ac(VHT80)/ax(HE80))
	WLAN 5 250 MHz ~ 5 350 MHz Band	5 260 MHz ~ 5 320 MHz (802.11a/n(HT20)/ac(VHT20)/ax(HE20))
		5 270 MHz ~ 5 310 MHz (802.11n(HT40)/ac(VHT40)/ax(HE40))
		5 290 MHz (802.11ac(VHT80)/ax(HE80))
	WLAN 5 470 MHz ~ 5 725 MHz Band	5 500 MHz ~ 5 720 MHz (802.11a/n(HT20)/ac(VHT20)/ax(HE20))
		5 510 MHz ~ 5 710 MHz (802.11n(HT40)/ac(VHT40)/ax(HE40))
		5 530 MHz ~ 5 690 MHz (802.11ac(VHT80)/ax(HE80))
	WLAN 5 725 MHz ~ 5 850 MHz Band	5 745 MHz ~ 5 825 MHz (802.11a/n(HT20)/ac(VHT20)/ax(HE20))
		5 755 MHz ~ 5 795 MHz (802.11n(HT40)/ac(VHT40)/ax(HE40))
		5 775 MHz (802.11ac(VHT80)/ax(HE80))
MODULATION TYPE	Bluetooth LE	GFSK for 1 Mbps / 2 Mbps / 125 kbps / 500 kbps
	Bluetooth	GFSK for 1Mbps, $\pi/4$ -DQPSK for 2Mbps, 8-DPSK for 3Mbps
	WLAN 2.4 GHz	802.11b: DSSS Modulation(DBPSK/DQPSK/CCK)
		802.11g/n(HT20)/n(HT40)/ax(HE20)/ax(HE40): OFDM Modulation(BPSK/QPSK/16QAM/64QAM)
	WLAN 5 GHz	802.11a/n(HT20)/n(HT40)/ac(VHT80)/ax(HE20)/ax(HE40)/ax(HE80): OFDM Modulation(BPSK/QPSK/16QAM/64QAM)

RF OUTPUT POWER	Bluetooth LE	1 Mbps	1.21 dBm
		2 Mbps	1.17 dBm
		125 kbps	1.22 dBm
		500 kbps	1.24 dBm
	Bluetooth	1 Mbps	0.67 dBm
		2 Mbps	-0.27 dBm
		3 Mbps	0.09 dBm
	WLAN 2.4 GHz	Antenna 0	15.57 dBm(802.11b)
			11.80 dBm(802.11g)
			11.67 dBm(802.11n_HT20)
			13.27 dBm(802.11ax_HE20)_26 Tone
			13.06 dBm(802.11ax_HE20)_52 Tone
			12.66 dBm(802.11ax_HE20)_106 Tone
			11.85 dBm(802.11ax_HE20)_242 Tone
			11.47 dBm(802.11ax_HE20)_Single User
			11.31 dBm(802.11n_HT40)
			12.02 dBm(802.11ax_HE40)_26 Tone
			12.93 dBm(802.11ax_HE40)_52 Tone
			13.04 dBm(802.11ax_HE40)_106 Tone

RF OUTPUT POWER	WLAN 2.4 GHz	Antenna 1	16.19 dBm(802.11b) 12.88 dBm(802.11g) 13.11 dBm(802.11n_HT20) 13.35 dBm(802.11ax_HE20)_26 Tone 13.57 dBm(802.11ax_HE20)_52 Tone 13.47 dBm(802.11ax_HE20)_106 Tone 13.33 dBm(802.11ax_HE20)_242 Tone 13.65 dBm(802.11ax_HE20)_Single User 12.11 dBm(802.11n_HT40) 12.31 dBm(802.11ax_HE40)_26 Tone 12.67 dBm(802.11ax_HE40)_52 Tone 12.70 dBm(802.11ax_HE40)_106 Tone 12.68 dBm(802.11ax_HE40)_242 Tone 12.48 dBm(802.11ax_HE40)_484 Tone 12.69 dBm(802.11ax_HE40)_Single User
		Multiple Antenna	15.46 dBm(802.11n_HT20) 16.32 dBm(802.11ax_HE20)_26 Tone 16.22 dBm(802.11ax_HE20)_52 Tone 16.09 dBm(802.11ax_HE20)_106 Tone 15.66 dBm(802.11ax_HE20)_242 Tone 15.70 dBm(802.11ax_HE20)_Single User 14.74 dBm(802.11n_HT40) 14.90 dBm(802.11ax_HE40)_26 Tone 15.78 dBm(802.11ax_HE40)_52 Tone 15.83 dBm(802.11ax_HE40)_106 Tone 15.57 dBm(802.11ax_HE40)_242 Tone 15.04 dBm(802.11ax_HE40)_484 Tone 15.15 dBm(802.11ax_HE40)_Single User

RF OUTPUT POWER	WLAN 5 150 MHz ~ 5 250 MHz Band	Antenna 0	12.59 dBm(802.11a)
			12.15 dBm(802.11n_HT20)
			2.53 dBm(802.11ax_HE20)_26 Tone
			4.65 dBm(802.11ax_HE20)_52 Tone
			7.54 dBm(802.11ax_HE20)_106 Tone
			10.29 dBm(802.11ax_HE20)_242 Tone
			12.19 dBm(802.11ax_HE20)_Single User
			9.02 dBm(802.11n_HT40)
			3.32 dBm(802.11ax_HE40)_26 Tone
			5.26 dBm(802.11ax_HE40)_52 Tone
			7.72 dBm(802.11ax_HE40)_106 Tone
			7.54 dBm(802.11ax_HE40)_242 Tone
			7.43 dBm(802.11ax_HE40)_484 Tone
			9.15 dBm(802.11ax_HE40)_Single User
			8.33 dBm(802.11ac_VHT80)
			3.10 dBm(802.11ax_HE40)_26 Tone
			5.03 dBm(802.11ax_HE40)_52 Tone
			4.87 dBm(802.11ax_HE40)_106 Tone
			4.76 dBm(802.11ax_HE40)_242 Tone
			4.72 dBm(802.11ax_HE40)_484 Tone
			4.33 dBm(802.11ax_HE40)_996 Tone
			8.55 dBm(802.11ax_HE40)_Single User

RF OUTPUT POWER	WLAN 5 150 MHz ~ 5 250 MHz Band	Antenna 1	12.45 dBm(802.11a)
			12.01 dBm(802.11n_HT20)
			3.45 dBm(802.11ax_HE20)_26 Tone
			5.63 dBm(802.11ax_HE20)_52 Tone
			8.30 dBm(802.11ax_HE20)_106 Tone
			10.77 dBm(802.11ax_HE20)_242 Tone
			12.02 dBm(802.11ax_HE20)_Single User
			8.87 dBm(802.11n_HT40)
			4.18 dBm(802.11ax_HE40)_26 Tone
			6.25 dBm(802.11ax_HE40)_52 Tone
			8.44 dBm(802.11ax_HE40)_106 Tone
			8.29 dBm(802.11ax_HE40)_242 Tone
			8.20 dBm(802.11ax_HE40)_484 Tone
			9.21 dBm(802.11ax_HE40)_Single User
			8.11 dBm(802.11ac_VHT80)
			4.10 dBm(802.11ax_HE40)_26 Tone
			6.10 dBm(802.11ax_HE40)_52 Tone
			5.90 dBm(802.11ax_HE40)_106 Tone
			5.81 dBm(802.11ax_HE40)_242 Tone
			5.75 dBm(802.11ax_HE40)_484 Tone
			5.50 dBm(802.11ax_HE40)_996 Tone
			8.27 dBm(802.11ax_HE40)_Single User

RF OUTPUT POWER	WLAN 5 150 MHz ~ 5 250 MHz Band	Multiple Antenna	15.09 dBm(802.11n_HT20)
			6.03 dBm(802.11ax_HE20)_26 Tone
			8.18 dBm(802.11ax_HE20)_52 Tone
			10.95 dBm(802.11ax_HE20)_106 Tone
			13.55 dBm(802.11ax_HE20)_242 Tone
			15.11 dBm(802.11ax_HE20)_Single User
			11.95 dBm(802.11n_HT40)
			6.78 dBm(802.11ax_HE40)_26 Tone
			8.80 dBm(802.11ax_HE40)_52 Tone
			11.11 dBm(802.11ax_HE40)_106 Tone
			10.94 dBm(802.11ax_HE40)_242 Tone
			10.84 dBm(802.11ax_HE40)_484 Tone
			12.19 dBm(802.11ax_HE40)_Single User
			11.24 dBm(802.11ac_VHT80)
			6.64 dBm(802.11ax_HE40)_26 Tone
			8.61 dBm(802.11ax_HE40)_52 Tone
			8.42 dBm(802.11ax_HE40)_106 Tone
			8.32 dBm(802.11ax_HE40)_242 Tone
			8.27 dBm(802.11ax_HE40)_484 Tone
			7.96 dBm(802.11ax_HE40)_996 Tone
			11.42 dBm(802.11ax_HE40)_Single User

RF OUTPUT POWER	WLAN 5 250 MHz ~ 5 350 MHz Band	Antenna 0	12.38 dBm(802.11a)
			11.90 dBm(802.11n_HT20)
			2.66 dBm(802.11ax_HE20)_26 Tone
			4.79 dBm(802.11ax_HE20)_52 Tone
			7.63 dBm(802.11ax_HE20)_106 Tone
			10.35 dBm(802.11ax_HE20)_242 Tone
			11.97 dBm(802.11ax_HE20)_Single User
			8.28 dBm(802.11n_HT40)
			3.52 dBm(802.11ax_HE40)_26 Tone
			5.62 dBm(802.11ax_HE40)_52 Tone
			7.88 dBm(802.11ax_HE40)_106 Tone
			5.55 dBm(802.11ax_HE40)_242 Tone
			7.49 dBm(802.11ax_HE40)_484 Tone
			8.44 dBm(802.11ax_HE40)_Single User
			6.35 dBm(802.11ac_VHT80)
			3.18 dBm(802.11ax_HE40)_26 Tone
			5.13 dBm(802.11ax_HE40)_52 Tone
			4.96 dBm(802.11ax_HE40)_106 Tone
			4.88 dBm(802.11ax_HE40)_242 Tone
			4.86 dBm(802.11ax_HE40)_484 Tone
			4.82 dBm(802.11ax_HE40)_996 Tone
			6.54 dBm(802.11ax_HE40)_Single User

RF OUTPUT POWER	WLAN 5 250 MHz ~ 5 350 MHz Band	Antenna 1	12.39 dBm(802.11a) 11.94 dBm(802.11n_HT20) 3.67 dBm(802.11ax_HE20)_26 Tone 5.73 dBm(802.11ax_HE20)_52 Tone 8.46 dBm(802.11ax_HE20)_106 Tone 10.87 dBm(802.11ax_HE20)_242 Tone 12.03 dBm(802.11ax_HE20)_Single User 8.21 dBm(802.11n_HT40) 4.43 dBm(802.11ax_HE40)_26 Tone 6.58 dBm(802.11ax_HE40)_52 Tone 8.63 dBm(802.11ax_HE40)_106 Tone 6.48 dBm(802.11ax_HE40)_242 Tone 8.39 dBm(802.11ax_HE40)_484 Tone 8.48 dBm(802.11ax_HE40)_Single User 6.23 dBm(802.11ac_VHT80) 4.28 dBm(802.11ax_HE40)_26 Tone 6.24 dBm(802.11ax_HE40)_52 Tone 6.07 dBm(802.11ax_HE40)_106 Tone 5.88 dBm(802.11ax_HE40)_242 Tone 5.90 dBm(802.11ax_HE40)_484 Tone 5.86 dBm(802.11ax_HE40)_996 Tone 6.54 dBm(802.11ax_HE40)_Single User
--------------------	---------------------------------------	-----------	--

RF OUTPUT POWER	WLAN 5 250 MHz ~ 5 350 MHz Band	Multiple Antenna	14.89 dBm(802.11n_HT20)
			6.21 dBm(802.11ax_HE20)_26 Tone
			8.29 dBm(802.11ax_HE20)_52 Tone
			11.07 dBm(802.11ax_HE20)_106 Tone
			13.58 dBm(802.11ax_HE20)_242 Tone
			15.01 dBm(802.11ax_HE20)_Single User
			11.23 dBm(802.11n_HT40)
			6.98 dBm(802.11ax_HE40)_26 Tone
			9.14 dBm(802.11ax_HE40)_52 Tone
			11.28 dBm(802.11ax_HE40)_106 Tone
			9.05 dBm(802.11ax_HE40)_242 Tone
			10.97 dBm(802.11ax_HE40)_484 Tone
			11.47 dBm(802.11ax_HE40)_Single User
			9.30 dBm(802.11ac_VHT80)
			6.77 dBm(802.11ax_HE40)_26 Tone
			8.73 dBm(802.11ax_HE40)_52 Tone
			8.56 dBm(802.11ax_HE40)_106 Tone
			8.41 dBm(802.11ax_HE40)_242 Tone
			8.42 dBm(802.11ax_HE40)_484 Tone
			8.38 dBm(802.11ax_HE40)_996 Tone
			9.55 dBm(802.11ax_HE40)_Single User

RF OUTPUT POWER	WLAN 5 470 MHz ~ 5 725 MHz Band	Antenna 0	12.24 dBm(802.11a)
			11.76 dBm(802.11n_HT20)
			2.82 dBm(802.11ax_HE20)_26 Tone
			4.98 dBm(802.11ax_HE20)_52 Tone
			7.90 dBm(802.11ax_HE20)_106 Tone
			10.64 dBm(802.11ax_HE20)_242 Tone
			12.03 dBm(802.11ax_HE20)_Single User
			9.62 dBm(802.11n_HT40)
			3.69 dBm(802.11ax_HE40)_26 Tone
			5.92 dBm(802.11ax_HE40)_52 Tone
			8.02 dBm(802.11ax_HE40)_106 Tone
			7.72 dBm(802.11ax_HE40)_242 Tone
			7.76 dBm(802.11ax_HE40)_484 Tone
			9.99 dBm(802.11ax_HE40)_Single User
			5.91 dBm(802.11ac_VHT80)
			3.20 dBm(802.11ax_HE40)_26 Tone
			5.21 dBm(802.11ax_HE40)_52 Tone
			4.98 dBm(802.11ax_HE40)_106 Tone
			4.80 dBm(802.11ax_HE40)_242 Tone
			4.78 dBm(802.11ax_HE40)_484 Tone
			4.46 dBm(802.11ax_HE40)_996 Tone
			6.27 dBm(802.11ax_HE40)_Single User

RF OUTPUT POWER	WLAN 5 470 MHz ~ 5 725 MHz Band	Antenna 0_Straddle	9.32 dBm(802.11a) 9.20 dBm(802.11n_HT20) 2.00 dBm(802.11ax_HE20)_26 Tone 4.19 dBm(802.11ax_HE20)_52 Tone 6.86 dBm(802.11ax_HE20)_106 Tone 8.57 dBm(802.11ax_HE20)_242 Tone 9.31 dBm(802.11ax_HE20)_Single User 7.36 dBm(802.11n_HT40) -14.30 dBm(802.11ax_HE40)_26 Tone -6.24 dBm(802.11ax_HE40)_52 Tone 3.73 dBm(802.11ax_HE40)_106 Tone 5.66 dBm(802.11ax_HE40)_242 Tone 6.45 dBm(802.11ax_HE40)_484 Tone 7.74 dBm(802.11ax_HE40)_Single User 4.72 dBm(802.11ac_VHT80) -15.24 dBm(802.11ax_HE40)_26 Tone -7.11 dBm(802.11ax_HE40)_52 Tone 1.12 dBm(802.11ax_HE40)_106 Tone 2.80 dBm(802.11ax_HE40)_242 Tone 3.65 dBm(802.11ax_HE40)_484 Tone 4.16 dBm(802.11ax_HE40)_996 Tone 5.03 dBm(802.11ax_HE40)_Single User
--------------------	---------------------------------------	--------------------	--

RF OUTPUT POWER	WLAN 5 470 MHz ~ 5 725 MHz Band	Antenna 1	12.50 dBm(802.11a) 11.89 dBm(802.11n_HT20) 3.90 dBm(802.11ax_HE20)_26 Tone 8.53 dBm(802.11ax_HE20)_52 Tone 8.55 dBm(802.11ax_HE20)_106 Tone 11.07 dBm(802.11ax_HE20)_242 Tone 12.15 dBm(802.11ax_HE20)_Single User 9.93 dBm(802.11n_HT40) 5.05 dBm(802.11ax_HE40)_26 Tone 7.13 dBm(802.11ax_HE40)_52 Tone 9.13 dBm(802.11ax_HE40)_106 Tone 8.84 dBm(802.11ax_HE40)_242 Tone 8.81 dBm(802.11ax_HE40)_484 Tone 10.15 dBm(802.11ax_HE40)_Single User 5.90 dBm(802.11ac_VHT80) 4.26 dBm(802.11ax_HE40)_26 Tone 6.28 dBm(802.11ax_HE40)_52 Tone 6.15 dBm(802.11ax_HE40)_106 Tone 6.02 dBm(802.11ax_HE40)_242 Tone 5.96 dBm(802.11ax_HE40)_484 Tone 5.71 dBm(802.11ax_HE40)_996 Tone 6.27 dBm(802.11ax_HE40)_Single User
--------------------	---------------------------------------	-----------	---

RF OUTPUT POWER	WLAN 5 470 MHz ~ 5 725 MHz Band	Antenna 1_Straddle	9.42 dBm(802.11a) 9.23 dBm(802.11n_HT20) 3.92 dBm(802.11ax_HE20)_26 Tone 5.88 dBm(802.11ax_HE20)_52 Tone 8.59 dBm(802.11ax_HE20)_106 Tone 9.80 dBm(802.11ax_HE20)_242 Tone 9.35 dBm(802.11ax_HE20)_Single User 7.45 dBm(802.11n_HT40) -12.01 dBm(802.11ax_HE40)_26 Tone -4.37 dBm(802.11ax_HE40)_52 Tone 5.52 dBm(802.11ax_HE40)_106 Tone 7.38 dBm(802.11ax_HE40)_242 Tone 7.74 dBm(802.11ax_HE40)_484 Tone 7.79 dBm(802.11ax_HE40)_Single User 4.37 dBm(802.11ac_VHT80) -13.11 dBm(802.11ax_HE40)_26 Tone -5.17 dBm(802.11ax_HE40)_52 Tone 2.86 dBm(802.11ax_HE40)_106 Tone 4.42 dBm(802.11ax_HE40)_242 Tone 5.11 dBm(802.11ax_HE40)_484 Tone 5.32 dBm(802.11ax_HE40)_996 Tone 4.66 dBm(802.11ax_HE40)_Single User
--------------------	---------------------------------------	--------------------	--

RF OUTPUT POWER	WLAN 5 470 MHz ~ 5 725 MHz Band	Multiple Antenna	14.89 dBm(802.11n_HT20)
			6.33 dBm(802.11ax_HE20)_26 Tone
			9.99 dBm(802.11ax_HE20)_52 Tone
			11.21 dBm(802.11ax_HE20)_106 Tone
			13.87 dBm(802.11ax_HE20)_242 Tone
			15.10 dBm(802.11ax_HE20)_Single User
			12.79 dBm(802.11n_HT40)
			7.44 dBm(802.11ax_HE40)_26 Tone
			9.58 dBm(802.11ax_HE40)_52 Tone
			11.62 dBm(802.11ax_HE40)_106 Tone
			11.31 dBm(802.11ax_HE40)_242 Tone
			11.33 dBm(802.11ax_HE40)_484 Tone
			13.09 dBm(802.11ax_HE40)_Single User
			8.92 dBm(802.11ac_VHT80)
			6.77 dBm(802.11ax_HE40)_26 Tone
			8.79 dBm(802.11ax_HE40)_52 Tone
			8.61 dBm(802.11ax_HE40)_106 Tone
			8.46 dBm(802.11ax_HE40)_242 Tone
			8.42 dBm(802.11ax_HE40)_484 Tone
			8.14 dBm(802.11ax_HE40)_996 Tone
			9.28 dBm(802.11ax_HE40)_Single User

RF OUTPUT POWER	WLAN 5 470 MHz ~ 5 725 MHz Band	Multiple Antenna _Straddle	12.22 dBm(802.11n_HT20) 5.99 dBm(802.11ax_HE20)_26 Tone 8.12 dBm(802.11ax_HE20)_52 Tone 10.82 dBm(802.11ax_HE20)_106 Tone 12.24 dBm(802.11ax_HE20)_242 Tone 12.34 dBm(802.11ax_HE20)_Single User 10.41 dBm(802.11n_HT40) -9.99 dBm(802.11ax_HE40)_26 Tone -2.19 dBm(802.11ax_HE40)_52 Tone 7.73 dBm(802.11ax_HE40)_106 Tone 9.62 dBm(802.11ax_HE40)_242 Tone 10.15 dBm(802.11ax_HE40)_484 Tone 10.78 dBm(802.11ax_HE40)_Single User 7.56 dBm(802.11ac_VHT80) -11.04 dBm(802.11ax_HE40)_26 Tone -3.02 dBm(802.11ax_HE40)_52 Tone 5.08 dBm(802.11ax_HE40)_106 Tone 6.69 dBm(802.11ax_HE40)_242 Tone 7.45 dBm(802.11ax_HE40)_484 Tone 7.79 dBm(802.11ax_HE40)_996 Tone 7.86 dBm(802.11ax_HE40)_Single User
--------------------	---------------------------------------	-------------------------------	---

RF OUTPUT POWER	WLAN 5 725 MHz ~ 5 850 MHz Band	Antenna 0	11.47 dBm(802.11a) 11.43 dBm(802.11n_HT20) 10.25 dBm(802.11ax_HE20)_26 Tone 10.40 dBm(802.11ax_HE20)_52 Tone 10.13 dBm(802.11ax_HE20)_106 Tone 10.13 dBm(802.11ax_HE20)_242 Tone 11.28 dBm(802.11ax_HE20)_Single User 10.37 dBm(802.11n_HT40) 7.10 dBm(802.11ax_HE40)_26 Tone 7.39 dBm(802.11ax_HE40)_52 Tone 7.69 dBm(802.11ax_HE40)_106 Tone 7.32 dBm(802.11ax_HE40)_242 Tone 7.16 dBm(802.11ax_HE40)_484 Tone 10.38 dBm(802.11ax_HE40)_Single User 8.02 dBm(802.11ac_VHT80) 4.77 dBm(802.11ax_HE40)_26 Tone 4.91 dBm(802.11ax_HE40)_52 Tone 4.76 dBm(802.11ax_HE40)_106 Tone 4.66 dBm(802.11ax_HE40)_242 Tone 4.57 dBm(802.11ax_HE40)_484 Tone 4.48 dBm(802.11ax_HE40)_996 Tone 8.01 dBm(802.11ax_HE40)_Single User
--------------------	---------------------------------------	-----------	---

RF OUTPUT POWER	WLAN 5 725 MHz ~ 5 850 MHz Band	Antenna 0_Straddle	3.14 dBm(802.11a) 3.50 dBm(802.11n_HT20) 1.68 dBm(802.11ax_HE20)_26 Tone 3.49 dBm(802.11ax_HE20)_52 Tone 3.76 dBm(802.11ax_HE20)_106 Tone 3.11 dBm(802.11ax_HE20)_242 Tone 3.94 dBm(802.11ax_HE20)_Single User -2.90 dBm(802.11n_HT40) 1.45 dBm(802.11ax_HE40)_26 Tone 4.04 dBm(802.11ax_HE40)_52 Tone 3.01 dBm(802.11ax_HE40)_106 Tone -0.30 dBm(802.11ax_HE40)_242 Tone -3.47 dBm(802.11ax_HE40)_484 Tone -2.02 dBm(802.11ax_HE40)_Single User -9.20 dBm(802.11ac_VHT80) 2.00 dBm(802.11ax_HE40)_26 Tone 3.63 dBm(802.11ax_HE40)_52 Tone 0.73 dBm(802.11ax_HE40)_106 Tone -2.85 dBm(802.11ax_HE40)_242 Tone -5.78 dBm(802.11ax_HE40)_484 Tone -8.89 dBm(802.11ax_HE40)_996 Tone -8.06 dBm(802.11ax_HE40)_Single User
--------------------	---------------------------------------	--------------------	---

RF OUTPUT POWER	WLAN 5 725 MHz ~ 5 850 MHz Band	Antenna 1	11.78 dBm(802.11a) 11.49 dBm(802.11n_HT20) 11.36 dBm(802.11ax_HE20)_26 Tone 11.55 dBm(802.11ax_HE20)_52 Tone 11.29 dBm(802.11ax_HE20)_106 Tone 11.21 dBm(802.11ax_HE20)_242 Tone 11.16 dBm(802.11ax_HE20)_Single User 10.47 dBm(802.11n_HT40) 8.73 dBm(802.11ax_HE40)_26 Tone 9.01 dBm(802.11ax_HE40)_52 Tone 9.13 dBm(802.11ax_HE40)_106 Tone 8.83 dBm(802.11ax_HE40)_242 Tone 8.72 dBm(802.11ax_HE40)_484 Tone 10.31 dBm(802.11ax_HE40)_Single User 7.69 dBm(802.11ac_VHT80) 6.50 dBm(802.11ax_HE40)_26 Tone 6.53 dBm(802.11ax_HE40)_52 Tone 6.39 dBm(802.11ax_HE40)_106 Tone 6.26 dBm(802.11ax_HE40)_242 Tone 6.26 dBm(802.11ax_HE40)_484 Tone 5.91 dBm(802.11ax_HE40)_996 Tone 7.47 dBm(802.11ax_HE40)_Single User
--------------------	---------------------------------------	-----------	---

RF OUTPUT POWER	WLAN 5 725 MHz ~ 5 850 MHz Band	Antenna 1_Straddle	3.33 dBm(802.11a) 3.62 dBm(802.11n_HT20) 3.83 dBm(802.11ax_HE20)_26 Tone 5.36 dBm(802.11ax_HE20)_52 Tone 5.47 dBm(802.11ax_HE20)_106 Tone 4.50 dBm(802.11ax_HE20)_242 Tone 4.12 dBm(802.11ax_HE20)_Single User -2.38 dBm(802.11n_HT40) 3.33 dBm(802.11ax_HE40)_26 Tone 5.93 dBm(802.11ax_HE40)_52 Tone 4.85 dBm(802.11ax_HE40)_106 Tone 1.50 dBm(802.11ax_HE40)_242 Tone -1.68 dBm(802.11ax_HE40)_484 Tone -1.56 dBm(802.11ax_HE40)_Single User -8.90 dBm(802.11ac_VHT80) 3.96 dBm(802.11ax_HE40)_26 Tone 5.51 dBm(802.11ax_HE40)_52 Tone 2.53 dBm(802.11ax_HE40)_106 Tone -0.93 dBm(802.11ax_HE40)_242 Tone -3.96 dBm(802.11ax_HE40)_484 Tone -7.03 dBm(802.11ax_HE40)_996 Tone -7.70 dBm(802.11ax_HE40)_Single User
--------------------	---------------------------------------	--------------------	--

RF OUTPUT POWER	WLAN 5 725 MHz ~ 5 850 MHz Band	Multiple Antenna	14.34 dBm(802.11n_HT20)
			13.70 dBm(802.11ax_HE20)_26 Tone
			13.90 dBm(802.11ax_HE20)_52 Tone
			13.63 dBm(802.11ax_HE20)_106 Tone
			13.54 dBm(802.11ax_HE20)_242 Tone
			14.17 dBm(802.11ax_HE20)_Single User
			13.43 dBm(802.11n_HT40)
			10.97 dBm(802.11ax_HE40)_26 Tone
			11.25 dBm(802.11ax_HE40)_52 Tone
			11.33 dBm(802.11ax_HE40)_106 Tone
			11.04 dBm(802.11ax_HE40)_242 Tone
			11.02 dBm(802.11ax_HE40)_484 Tone
			13.34 dBm(802.11ax_HE40)_Single User
			10.87 dBm(802.11ac_VHT80)
			8.60 dBm(802.11ax_HE40)_26 Tone
			8.61 dBm(802.11ax_HE40)_52 Tone
			8.50 dBm(802.11ax_HE40)_106 Tone
			8.50 dBm(802.11ax_HE40)_242 Tone
			8.48 dBm(802.11ax_HE40)_484 Tone
			8.26 dBm(802.11ax_HE40)_996 Tone
			10.76 dBm(802.11ax_HE40)_Single User

RF OUTPUT POWER	WLAN 5 725 MHz ~ 5 850 MHz Band	Multiple Antenna _Straddle	6.57 dBm(802.11n_HT20) 5.90 dBm(802.11ax_HE20)_26 Tone 7.53 dBm(802.11ax_HE20)_52 Tone 7.71 dBm(802.11ax_HE20)_106 Tone 6.87 dBm(802.11ax_HE20)_242 Tone 7.04 dBm(802.11ax_HE20)_Single User 0.38 dBm(802.11n_HT40) 5.50 dBm(802.11ax_HE40)_26 Tone 8.10 dBm(802.11ax_HE40)_52 Tone 7.05 dBm(802.11ax_HE40)_106 Tone 3.70 dBm(802.11ax_HE40)_242 Tone 0.53 dBm(802.11ax_HE40)_484 Tone 1.23 dBm(802.11ax_HE40)_Single User -6.03 dBm(802.11ac_VHT80) 6.10 dBm(802.11ax_HE40)_26 Tone 7.68 dBm(802.11ax_HE40)_52 Tone 4.73 dBm(802.11ax_HE40)_106 Tone 1.23 dBm(802.11ax_HE40)_242 Tone -1.76 dBm(802.11ax_HE40)_484 Tone -4.85 dBm(802.11ax_HE40)_996 Tone -4.87 dBm(802.11ax_HE40)_Single User
--------------------	---------------------------------------	-------------------------------	---

ANTENNA TYPE	Dipole Antenna		
ANTENNA GAIN	Bluetooth LE	7 dBi	
	Bluetooth	7 dBi	
	WLAN 2.4 GHz	Antenna 0	7 dBi
		Antenna 1	7 dBi
		Multiple Antenna	10.01 dBi
	5 150 MHz ~ 5 250 MHz Band	Antenna 0	9 dBi
		Antenna 1	9 dBi
		Multiple Antenna	12.01 dBi
	5 250 MHz ~ 5 350 MHz Band	Antenna 0	9 dBi
		Antenna 1	9 dBi
		Multiple Antenna	12.01 dBi
	5 470 MHz ~ 5 725 MHz Band	Antenna 0	9 dBi
		Antenna 1	9 dBi
		Multiple Antenna	12.01 dBi
	5 725 MHz ~ 5 850 MHz Band	Antenna 0	9 dBi
		Antenna 1	9 dBi
		Multiple Antenna	12.01 dBi
List of each Osc. or crystal Freq.(Freq. >= 1 MHz)	40 MHz		

3.2 Alternative type(s)/model(s); also covered by this test report.

- None

4. EUT MODIFICATIONS

- None

5. SYSTEM TEST CONFIGURATION

5.1 Justification

This device was configured for testing in a typical way as a normal customer is supposed to be used. During the test, the following components were installed inside of the EUT.

DEVICE TYPE	MANUFACTURER	MODEL/PART NUMBER	FCC ID
Main Board	LG Innotek Co., Ltd.	cTP3.0_Rev0.1	N/A

5.2 Peripheral equipment

Defined as equipment needed for correct operation of the EUT, but not considered as tested:

Model	Manufacturer	Description	Connected to
ATC6NPL002	LG Innotek Co., Ltd.	RF Module (EUT)	-
ZUP36-6	NEMIC-LAMBDA	DC Power Supply	EUT
ideapad320	Lenovo	Notebokk PC	EUT

5.3 Mode of operation during the test

- Duty Cycle (Antenna 0)

Band	TEST Mode	Data Rate	On Time (ms)	Total Time (ms)	Duty Cycle (%)	Duty Cycle Factor (dB)
UNII (5.5 GHz)	802.11 a	6	1.430	1.445	98.96	0.045
		9	0.960	0.975	98.46	0.067
		12	0.725	0.740	97.97	0.089
		18	0.495	0.510	97.06	0.130
		24	0.378	0.393	96.18	0.169
		36	0.258	0.269	95.91	0.181
		48	0.200	0.214	93.46	0.294
		54	0.180	0.196	91.84	0.370
	802.11 n(HT20)	MCS0	1.340	1.355	98.89	0.048
		MCS1	0.685	0.700	97.86	0.094
		MCS2	0.472	0.486	97.12	0.127
		MCS3	0.364	0.378	96.30	0.164
		MCS4	0.256	0.272	94.12	0.263
		MCS5	0.200	0.214	93.46	0.294
		MCS6	0.184	0.198	92.93	0.318
		MCS7	0.168	0.182	92.31	0.348
	802.11 n(HT40)	MCS0	0.665	0.680	97.79	0.097
		MCS1	0.352	0.368	95.65	0.193
		MCS2	0.248	0.262	94.66	0.238
		MCS3	0.196	0.210	93.33	0.300
		MCS4	0.144	0.160	90.00	0.458
		MCS5	0.116	0.132	87.88	0.561
		MCS6	0.108	0.124	87.10	0.600
		MCS7	0.100	0.116	86.21	0.645
	802.11 ac(VHT80)	MCS0	0.334	0.350	95.43	0.203
		MCS1	0.188	0.204	92.16	0.355
		MCS2	0.144	0.160	90.00	0.458
		MCS3	0.116	0.132	87.88	0.561
		MCS4	0.096	0.112	85.71	0.669
		MCS5	0.080	0.096	83.33	0.792
		MCS6	0.076	0.092	82.61	0.830
		MCS7	0.072	0.088	81.82	0.872
		MCS8	0.068	0.084	80.95	0.918
		MCS9	0.064	0.080	80.00	0.969


-. Duty Cycle (Antenna 1)


Band	TEST Mode	Data Rate	On Time (ms)	Total Time (ms)	Duty Cycle (%)	Duty Cycle Factor (dB)
UNII (5.5 GHz)	802.11 a	6	1.430	1.445	98.96	0.045
		9	0.960	0.975	98.46	0.067
		12	0.725	0.740	97.97	0.089
		18	0.490	0.505	97.03	0.131
		24	0.376	0.391	96.16	0.170
		36	0.256	0.267	95.88	0.183
		48	0.200	0.215	93.02	0.314
		54	0.180	0.197	91.37	0.392
	802.11 n(HT20)	MCS0	1.340	1.357	98.75	0.055
		MCS1	0.685	0.702	97.58	0.106
		MCS2	0.472	0.486	97.12	0.127
		MCS3	0.364	0.378	96.30	0.164
		MCS4	0.256	0.272	94.12	0.263
		MCS5	0.200	0.214	93.46	0.294
		MCS6	0.184	0.198	92.93	0.318
		MCS7	0.168	0.182	92.31	0.348
	802.11 n(HT40)	MCS0	0.662	0.680	97.35	0.117
		MCS1	0.350	0.368	95.11	0.218
		MCS2	0.248	0.262	94.66	0.238
		MCS3	0.196	0.210	93.33	0.300
		MCS4	0.144	0.160	90.00	0.458
		MCS5	0.116	0.132	87.88	0.561
		MCS6	0.108	0.124	87.10	0.600
		MCS7	0.100	0.116	86.21	0.645
	802.11 ac(VHT80)	MCS0	0.332	0.348	95.40	0.204
		MCS1	0.188	0.204	92.16	0.355
		MCS2	0.144	0.160	90.00	0.458
		MCS3	0.116	0.132	87.88	0.561
		MCS4	0.096	0.112	85.71	0.669
		MCS5	0.080	0.096	83.33	0.792
		MCS6	0.076	0.092	82.61	0.830
		MCS7	0.072	0.088	81.82	0.872
		MCS8	0.068	0.084	80.95	0.918
		MCS9	0.064	0.080	80.00	0.969


Note – Duty Cycle : (Tx On Time / (Tx On Time + Tx Off Time)) * 100

Correction Factor : 10 * Log(1 / (Duty Cycle / 100))

- Test Plot_Antenna 0

- Test Plot_Antenna 1



5.4 Configuration of Test System

- Line Conducted Test:** The EUT was tested in the Transmitting mode. All supporting equipment were connected to another LISN. Preliminary Power line Conducted Emission test was performed by using the procedure in ANSI C63.10: 2020 to determine the worse operating conditions.
- Radiated Emission Test:** Preliminary radiated emissions test were conducted using the procedure in ANSI C63.10: 2020 to determine the worse operating conditions. Final radiated emission tests were conducted at 3 meter Semi Anechoic Chamber. The turntable was rotated through 360 degrees and the EUT was tested by positioned three orthogonal planes to obtain the highest reading on the field strength meter. Once maximum reading was determined, the search antenna was raised and lowered in both vertical and horizontal polarization.

5.5 Antenna Requirement

For intentional device, according to section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

Antenna Construction:

The antenna of the EUT is a Dipole Antenna. However, The manufacture has designed a strucyure that connects to the antenna using a unique coupling connector of the Fakra Type. So no consideration of replacement by the user.

6. PRELIMINARY TEST

6.1 AC Power line Conducted Emissions Tests

During Preliminary Test, the following operating mode was investigated.

Operation Mode	The Worse operating condition (Please check one only)
Transmitting Mode	X

6.2 General Radiated Emissions Tests

During Preliminary Test, the following operating mode was investigated.

Operation Mode	The Worse operating condition (Please check one only)
Transmitting Mode	X

7. 99 % OCCUPIED BANDWIDTH & MINIMUM 26 dB BANDWIDTH

7.1 Operating environment

Temperature : 24 °C
Relative humidity : 45 % R.H.

7.2 Test set-up

The antenna output of the EUT was connected to the spectrum analyzer. The resolution bandwidth is set to 1%-5% OBW for 99% bandwidth, and peak detection was used. The 99 % bandwidth is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers are each equal to 0.5 % of the total mean power of the given emission.

The antenna output of the EUT was connected to the spectrum analyzer. The resolution bandwidth is set to approximately 1% of the emission bandwidth, and peak detection was used. The 26 dB bandwidth is defined as the total spectrum over which the power is higher than the peak power minus 26 dB.



7.3 Test Date

December 05, 2021 ~ March 08, 2022

7.4 Test data for 802.11a RLAN Mode

7.4.1 Test data for Antenna 0

7.4.1.1 99 % OCCUPIED BANDWIDTH

- Test Result : Pass

FREQUENCY RANGE (MHz)	CHANNEL	FREQUENCY (MHz)	99 % Bandwidth (MHz)
5 150 ~ 5 250	Low	5 180.00	16.38
	Middle	5 220.00	16.53
	High	5 240.00	16.38
5 250 ~ 5 350	Low	5 260.00	16.53
	Middle	5 300.00	16.43
	High	5 320.00	16.38
5 470 ~ 5 725	Low	5 500.00	16.48
	Middle	5 580.00	16.43
	High	5 700.00	16.43
5 725 ~ 5 850	Low	5 745.00	16.43
	Middle	5 785.00	16.43
	High	5 825.00	16.48

7.4.1.2 MINIMUM 26 dB BANDWIDTH

- Test Result : Pass

FREQUENCY RANGE (MHz)	CHANNEL	FREQUENCY (MHz)	26 dB Bandwidth (MHz)
5 150 ~ 5 250	Low	5 180.00	19.58
	Middle	5 220.00	18.88
	High	5 240.00	19.73
5 250 ~ 5 350	Low	5 260.00	19.48
	Middle	5 300.00	18.78
	High	5 320.00	19.28
5 470 ~ 5 725	Low	5 500.00	19.18
	Middle	5 580.00	19.23
	High	5 700.00	19.33
5 725 ~ 5 850	Low	5 745.00	20.03
	Middle	5 785.00	19.83
	High	5 825.00	19.78

[Staddle Channel]

FREQUENCY RANGE (MHz)	FREQUENCY (MHz)	26 dB Bandwidth (MHz)
5 470 ~ 5 725	5 720.00	14.59
5 725 ~ 5 850	5 720.00	4.54

Remark: See next page for measurement data.

7.4.2 Test data for Antenna 1**7.4.2.1 99 % OCCUPIED BANDWIDTH**

-. Test Result : Pass

FREQUENCY RANGE (MHz)	CHANNEL	FREQUENCY (MHz)	99 % Bandwidth (MHz)
5 150 ~ 5 250	Low	5 180.00	16.43
	Middle	5 220.00	16.43
	High	5 240.00	16.43
5 250 ~ 5 350	Low	5 260.00	16.38
	Middle	5 300.00	16.43
	High	5 320.00	16.43
5 470 ~ 5 725	Low	5 500.00	16.48
	Middle	5 580.00	16.38
	High	5 700.00	16.43
5 725 ~ 5 850	Low	5 745.00	16.43
	Middle	5 785.00	16.48
	High	5 825.00	16.43

7.4.2.2 MINIMUM 26 dB BANDWIDTH

- Test Result : Pass

FREQUENCY RANGE (MHz)	CHANNEL	FREQUENCY (MHz)	26 dB Bandwidth (MHz)
5 150 ~ 5 250	Low	5 180.00	19.18
	Middle	5 220.00	19.13
	High	5 240.00	19.03
5 250 ~ 5 350	Low	5 260.00	19.33
	Middle	5 300.00	19.28
	High	5 320.00	19.48
5 470 ~ 5 725	Low	5 500.00	19.18
	Middle	5 580.00	19.28
	High	5 700.00	19.23
5 725 ~ 5 850	Low	5 745.00	19.83
	Middle	5 785.00	19.88
	High	5 825.00	19.83

[Staddle Channel]

FREQUENCY RANGE (MHz)	FREQUENCY (MHz)	26 dB Bandwidth (MHz)
5 470 ~ 5 725	5 720.00	14.69
5 725 ~ 5 850	5 720.00	4.64

Remark: See next page for measurement data.

7.5 Test data for 802.11n_HT20 RLAN Mode**7.5.1 Test data for Antenna 0****7.5.1.1 99 % OCCUPIED BANDWIDTH**

-. Test Result : Pass

FREQUENCY RANGE (MHz)	CHANNEL	FREQUENCY (MHz)	99 % Bandwidth (MHz)
5 150 ~ 5 250	Low	5 180.00	17.58
	Middle	5 220.00	17.58
	High	5 240.00	17.63
5 250 ~ 5 350	Low	5 260.00	17.63
	Middle	5 300.00	17.73
	High	5 320.00	17.63
5 470 ~ 5 725	Low	5 500.00	17.63
	Middle	5 580.00	17.63
	High	5 700.00	17.58
5 725 ~ 5 850	Low	5 745.00	17.58
	Middle	5 785.00	17.63
	High	5 825.00	17.63

7.5.1.2 MINIMUM 26 dB BANDWIDTH

- Test Result : Pass

FREQUENCY RANGE (MHz)	CHANNEL	FREQUENCY (MHz)	26 dB Bandwidth (MHz)
5 150 ~ 5 250	Low	5 180.00	19.68
	Middle	5 220.00	19.73
	High	5 240.00	19.83
5 250 ~ 5 350	Low	5 260.00	19.68
	Middle	5 300.00	19.68
	High	5 320.00	19.78
5 470 ~ 5 725	Low	5 500.00	19.48
	Middle	5 660.00	19.98
	High	5 700.00	19.63
5 725 ~ 5 850	Low	5 745.00	19.93
	Middle	5 785.00	19.73
	High	5 825.00	19.13

[Staddle Channel]

FREQUENCY RANGE (MHz)	FREQUENCY (MHz)	26 dB Bandwidth (MHz)
5 470 ~ 5 725	5 720.00	14.84
5 725 ~ 5 850	5 720.00	4.84

Remark: See next page for measurement data.

7.5.2 Test data for Antenna 1**7.5.2.1 99 % OCCUPIED BANDWIDTH**

-. Test Result : Pass

FREQUENCY RANGE (MHz)	CHANNEL	FREQUENCY (MHz)	99 % Bandwidth (MHz)
5 150 ~ 5 250	Low	5 180.00	17.58
	Middle	5 220.00	17.58
	High	5 240.00	17.58
5 250 ~ 5 350	Low	5 260.00	17.63
	Middle	5 300.00	17.58
	High	5 320.00	17.63
5 470 ~ 5 725	Low	5 500.00	17.58
	Middle	5 580.00	17.58
	High	5 700.00	17.58
5 725 ~ 5 850	Low	5 745.00	17.58
	Middle	5 785.00	17.63
	High	5 825.00	17.58

7.5.2.2 MINIMUM 26 dB BANDWIDTH

- Test Result : Pass

FREQUENCY RANGE (MHz)	CHANNEL	FREQUENCY (MHz)	26 dB Bandwidth (MHz)
5 150 ~ 5 250	Low	5 180.00	19.58
	Middle	5 220.00	19.78
	High	5 240.00	19.48
5 250 ~ 5 350	Low	5 260.00	19.58
	Middle	5 300.00	19.58
	High	5 320.00	19.53
5 470 ~ 5 725	Low	5 500.00	19.73
	Middle	5 580.00	19.88
	High	5 700.00	19.58
5 725 ~ 5 850	Low	5 745.00	19.13
	Middle	5 785.00	19.38
	High	5 825.00	19.48

[Staddle Channel]

FREQUENCY RANGE (MHz)	FREQUENCY (MHz)	26 dB Bandwidth (MHz)
5 470 ~ 5 725	5 720.00	14.74
5 725 ~ 5 850	5 720.00	4.84

Remark: See next page for measurement data.

7.6 Test data for 802.11n_HT40 RLAN Mode**7.6.1 Test data for Antenna 0****7.6.1.1 99 % OCCUPIED BANDWIDTH**

-. Test Result : Pass

FREQUENCY RANGE (MHz)	CHANNEL	FREQUENCY (MHz)	99 % Bandwidth (MHz)
5 150 ~ 5 250	Low	5 190.00	36.16
	High	5 230.00	36.06
5 250 ~ 5 350	Low	5 270.00	35.96
	High	5 310.00	36.06
5 470 ~ 5 725	Low	5 510.00	36.06
	Middle	5 550.00	36.06
	High	5 670.00	36.06
5 725 ~ 5 850	Low	5 755.00	36.16
	High	5 795.00	36.16

7.6.1.2 MINIMUM 26 dB BANDWIDTH

- Test Result : Pass

FREQUENCY RANGE (MHz)	CHANNEL	FREQUENCY (MHz)	26 dB Bandwidth (MHz)
5 150 ~ 5 250	Low	5 190.00	39.36
	High	5 230.00	39.46
5 250 ~ 5 350	Low	5 270.00	39.96
	High	5 310.00	39.36
5 470 ~ 5 725	Low	5 510.00	39.66
	Middle	5 550.00	39.76
	High	5 670.00	39.66
5 725 ~ 5 850	Low	5 755.00	39.36
	High	5 795.00	39.56

[Staddle Channel]

FREQUENCY RANGE (MHz)	FREQUENCY (MHz)	26 dB Bandwidth (MHz)
5 470 ~ 5 725	5 710.00	34.58
5 725 ~ 5 850	5 710.00	4.68

Remark: See next page for measurement data.

7.6.2 Test data for Antenna 1**7.6.2.1 99 % OCCUPIED BANDWIDTH**

-. Test Result : Pass

FREQUENCY RANGE (MHz)	CHANNEL	FREQUENCY (MHz)	99 % Bandwidth (MHz)
5 150 ~ 5 250	Low	5 190.00	36.06
	High	5 230.00	36.26
5 250 ~ 5 350	Low	5 270.00	36.06
	High	5 310.00	36.16
5 470 ~ 5 725	Low	5 510.00	36.06
	Middle	5 550.00	36.16
	High	5 670.00	36.06
5 725 ~ 5 850	Low	5 755.00	36.36
	High	5 795.00	36.26

7.6.2.2 MINIMUM 26 dB BANDWIDTH

- Test Result : Pass

FREQUENCY RANGE (MHz)	CHANNEL	FREQUENCY (MHz)	26 dB Bandwidth (MHz)
5 150 ~ 5 250	Low	5 190.00	39.66
	High	5 230.00	40.06
5 250 ~ 5 350	Low	5 270.00	40.66
	High	5 310.00	40.46
5 470 ~ 5 725	Low	5 510.00	40.36
	Middle	5 550.00	40.26
	High	5 670.00	40.06
5 725 ~ 5 850	Low	5 755.00	40.46
	High	5 795.00	40.36

[Staddle Channel]

FREQUENCY RANGE (MHz)	FREQUENCY (MHz)	26 dB Bandwidth (MHz)
5 470 ~ 5 725	5 710.00	35.28
5 725 ~ 5 850	5 710.00	5.18

Remark: See next page for measurement data.

7.7 Test data for 802.11ac_VHT80 RLAN Mode

7.7.1 Test data for Antenna 0

7.7.1.1 99 % OCCUPIED BANDWIDTH

- . Test Result : Pass

FREQUENCY RANGE (MHz)	CHANNEL	FREQUENCY (MHz)	99 % Bandwidth (MHz)
5 150 ~ 5 250	Middle	5 210.00	75.72
5 250 ~ 5 350	Middle	5 290.00	76.12
5 470 ~ 5 725	Middle	5 530.00	76.32
5 725 ~ 5 850	Middle	5 775.00	76.12

7.7.1.2 MINIMUM 26 dB BANDWIDTH

- . Test Result : Pass

FREQUENCY RANGE (MHz)	CHANNEL	FREQUENCY (MHz)	26 dB Bandwidth (MHz)
5 150 ~ 5 250	Middle	5 210.00	81.52
5 250 ~ 5 350	Middle	5 290.00	80.95
5 470 ~ 5 725	Middle	5 530.00	80.12
5 725 ~ 5 850	Middle	5 775.00	79.52

[Staddle Channel]

FREQUENCY RANGE (MHz)	FREQUENCY (MHz)	26 dB Bandwidth (MHz)
5 470 ~ 5 725	5 690.00	75.76
5 725 ~ 5 850	5 690.00	5.76

Remark: See next page for measurement data.

7.7.2 Test data for Antenna 1

7.7.2.1 99 % OCCUPIED BANDWIDTH

- Test Result : Pass

FREQUENCY RANGE (MHz)	CHANNEL	FREQUENCY (MHz)	99 % Bandwidth (MHz)
5 150 ~ 5 250	Middle	5 210.00	75.92
5 250 ~ 5 350	Middle	5 290.00	76.32
5 470 ~ 5 725	Middle	5 530.00	76.12
5 725 ~ 5 850	Middle	5 775.00	76.12

7.7.2.2 MINIMUM 26 dB BANDWIDTH

- Test Result : Pass

FREQUENCY RANGE (MHz)	CHANNEL	FREQUENCY (MHz)	26 dB Bandwidth (MHz)
5 150 ~ 5 250	Middle	5 210.00	81.12
5 250 ~ 5 350	Middle	5 290.00	81.32
5 470 ~ 5 725	Middle	5 530.00	81.72
5 725 ~ 5 850	Middle	5 775.00	81.52

[Staddle Channel]

FREQUENCY RANGE (MHz)	FREQUENCY (MHz)	26 dB Bandwidth (MHz)
5 470 ~ 5 725	5 690.00	75.56
5 725 ~ 5 850	5 690.00	6.16

Remark: See next page for measurement data.

8. 6 dB BANDWIDTH

8.1 Operating environment

Temperature : 23 °C

Relative humidity : 45 % R.H.

8.2 Test set-up

The antenna output of the EUT was connected to the spectrum analyzer. The resolution bandwidth is set to 100 kHz, and peak detection was used. The 6 dB bandwidth is defined as the total spectrum over which the power is higher than the peak power minus 6 dB.



8.3 Test Date

December 05, 2021 ~ March 08, 2022

8.4 Test data for 802.11a RLAN Mode

8.4.1 Test data for Antenna 0

- Test Result : Pass

FREQUENCY RANGE (MHz)	CHANNEL	FREQUENCY (MHz)	6 dB Bandwidth (MHz)
5 725 ~ 5 850	Low	5 745.00	16.33
	Middle	5 785.00	16.33
	High	5 825.00	16.33

8.4.2 Test data for Antenna 1

- Test Result : Pass

FREQUENCY RANGE (MHz)	CHANNEL	FREQUENCY (MHz)	6 dB Bandwidth (MHz)
5 725 ~ 5 850	Low	5 745.00	16.33
	Middle	5 785.00	16.33
	High	5 825.00	16.33

8.4.3 Test data for Staddle Channel_Antenna 0

- Test Result : Pass

FREQUENCY RANGE (MHz)	FREQUENCY (MHz)	6 dB Bandwidth (MHz)
5 470 ~ 5 725	5 720.00	13.14
5 725 ~ 5 850	5 720.00	3.19

8.4.4 Test data for Staddle Channel_Antenna 1

- Test Result : Pass

FREQUENCY RANGE (MHz)	FREQUENCY (MHz)	6 dB Bandwidth (MHz)
5 470 ~ 5 725	5 720.00	13.14
5 725 ~ 5 850	5 720.00	3.19

8.5 Test data for 802.11n_HT20 RLAN Mode

8.5.1 Test data for Antenna 0

- . Test Result : Pass

FREQUENCY RANGE (MHz)	CHANNEL	FREQUENCY (MHz)	6 dB Bandwidth (MHz)
5 725 ~ 5 850	Low	5 745.00	17.63
	Middle	5 785.00	17.53
	High	5 825.00	17.63

8.5.2 Test data for Antenna 1

- . Test Result : Pass

FREQUENCY RANGE (MHz)	CHANNEL	FREQUENCY (MHz)	6 dB Bandwidth (MHz)
5 725 ~ 5 850	Low	5 745.00	17.53
	Middle	5 785.00	17.53
	High	5 825.00	17.53

8.5.3 Test data for Staddle Channel_Antenna 0

- . Test Result : Pass

FREQUENCY RANGE (MHz)	FREQUENCY (MHz)	6 dB Bandwidth (MHz)
5 470 ~ 5 725	5 720.00	13.79
5 725 ~ 5 850	5 720.00	3.89

8.5.4 Test data for Staddle Channel_Antenna 1

- . Test Result : Pass

FREQUENCY RANGE (MHz)	FREQUENCY (MHz)	6 dB Bandwidth (MHz)
5 470 ~ 5 725	5 720.00	13.74
5 725 ~ 5 850	5 720.00	3.79

8.6 Test data for 802.11n_HT40 RLAN Mode

8.6.1 Test data for Antenna 0

- Test Result : Pass

FREQUENCY RANGE (MHz)	CHANNEL	FREQUENCY (MHz)	6 dB Bandwidth (MHz)
5 725 ~ 5 850	Low	5 755.00	35.56
	High	5 795.00	35.76

8.6.2 Test data for Antenna 1

- Test Result : Pass

FREQUENCY RANGE (MHz)	CHANNEL	FREQUENCY (MHz)	6 dB Bandwidth (MHz)
5 725 ~ 5 850	Low	5 755.00	35.56
	High	5 795.00	35.66

Remark: See next page for measurement data.

8.6.3 Test data for Staddle Channel_Antenna 0

- Test Result : Pass

FREQUENCY RANGE (MHz)	FREQUENCY (MHz)	6 dB Bandwidth (MHz)
5 470 ~ 5 725	5 710.00	33.08
5 725 ~ 5 850	5 710.00	3.18

8.6.4 Test data for Staddle Channel_Antenna 1

- Test Result : Pass

FREQUENCY RANGE (MHz)	FREQUENCY (MHz)	6 dB Bandwidth (MHz)
5 470 ~ 5 725	5 710.00	32.78
5 725 ~ 5 850	5 710.00	2.88

8.7 Test data for 802.11ac_VHT80 RLAN Mode

8.7.1 Test data for Antenna 0

- . Test Result : Pass

FREQUENCY RANGE (MHz)	CHANNEL	FREQUENCY (MHz)	6 dB Bandwidth (MHz)
5 725 ~ 5 850	Middle	5 775.00	76.12

Remark: See next page for measurement data.

8.7.2 Test data for Antenna 1

- . Test Result : Pass

FREQUENCY RANGE (MHz)	CHANNEL	FREQUENCY (MHz)	6 dB Bandwidth (MHz)
5 725 ~ 5 850	Middle	5 775.00	76.52

Remark: See next page for measurement data.

8.7.3 Test data for Staddle Channel_Antenna 0

- . Test Result : Pass

FREQUENCY RANGE (MHz)	FREQUENCY (MHz)	6 dB Bandwidth (MHz)
5 470 ~ 5 725	5 690.00	73.16
5 725 ~ 5 850	5 690.00	3.16

8.7.4 Test data for Staddle Channel_Antenna 1

- . Test Result : Pass

FREQUENCY RANGE (MHz)	FREQUENCY (MHz)	6 dB Bandwidth (MHz)
5 470 ~ 5 725	5 690.00	73.16
5 725 ~ 5 850	5 690.00	3.36

9. MAXIMUM CONDUCTED(AVERAGE) OUTPUT POWER

9.1 Operating environment

Temperature : 23 °C
Relative humidity : 45 % R.H.

9.2 Test set-up

The maximum peak output power was measured with the Power Meter connected to the antenna output of the EUT. The EUT was operating in transmit mode at the appropriate center frequency. The test of the staddle channel is performed by spectrum.



9.3 Test Date

December 05, 2021 ~ March 08, 2022

9.4 Test data for 802.11a RLAN Mode

9.4.1 Test data for Antenna 0

- Test Result : Pass
- Duty Cycle : 98.96 %

FREQUENCY RANGE (MHz)	CHANNEL	FREQUENCY (MHz)	MEASURED VALUE (dBm)	Duty Factor (dB)	Total Value (dBm)	LIMIT (dBm)	MARGIN (dB)
5 150 ~ 5 250	Low	5 180.00	11.60	0.045	11.65	21.00	9.36
	Middle	5 220.00	12.28	0.045	12.33	21.00	8.68
	High	5 240.00	12.54	0.045	12.59	21.00	8.42
5 250 ~ 5 350	Low	5 260.00	12.33	0.045	12.38	21.00	8.63
	Middle	5 300.00	12.13	0.045	12.18	21.00	8.83
	High	5 320.00	12.29	0.045	12.34	21.00	8.67
5 470 ~ 5 725	Low	5 500.00	11.42	0.045	11.47	21.00	9.54
	Middle	5 580.00	12.19	0.045	12.24	21.00	8.77
	High	5 700.00	11.70	0.045	11.75	21.00	9.26
5 725 ~ 5 850	Low	5 745.00	11.08	0.045	11.13	27.00	15.88
	Middle	5 785.00	11.42	0.045	11.47	27.00	15.54
	High	5 825.00	10.52	0.045	10.57	27.00	16.44

Remark : Margin = Limit –Total Value (=Measured Value +Duty Factor)

9.4.2 Test data for Antenna 1

- . Test Result : Pass
- . Duty Cycle : 98.96 %

FREQUENCY RANGE (MHz)	CHANNEL	FREQUENCY (MHz)	MEASURED VALUE (dBm)	Duty Factor (dB)	Total Value (dBm)	LIMIT (dBm)	MARGIN (dB)
5 150 ~ 5 250	Low	5 180.00	11.49	0.045	11.54	21.00	9.47
	Middle	5 220.00	12.21	0.045	12.26	21.00	8.75
	High	5 240.00	12.40	0.045	12.45	21.00	8.56
5 250 ~ 5 350	Low	5 260.00	12.34	0.045	12.39	21.00	8.62
	Middle	5 300.00	11.94	0.045	11.99	21.00	9.02
	High	5 320.00	12.11	0.045	12.16	21.00	8.85
5 470 ~ 5 725	Low	5 500.00	11.76	0.045	11.81	21.00	9.20
	Middle	5 580.00	12.45	0.045	12.50	21.00	8.51
	High	5 700.00	11.44	0.045	11.49	21.00	9.52
5 725 ~ 5 850	Low	5 745.00	11.73	0.045	11.78	27.00	15.23
	Middle	5 785.00	11.52	0.045	11.57	27.00	15.44
	High	5 825.00	11.25	0.045	11.30	27.00	15.71

Remark : Margin = Limit –Total Value (=Measured Value +Duty Factor)

9.4.3 Test data for Staddle Channel_Antenna 0

- . Test Result : Pass
- . Duty Cycle : 98.96 %

FREQUENCY RANGE (MHz)	CHANNEL	FREQUENCY (MHz)	MEASURED VALUE (dBm)	Duty Factor (dB)	Total Value (dBm)	LIMIT (dBm)	MARGIN (dB)
5 470 ~ 5 725	Middle	5 720.00	9.27	0.045	9.32	21.00	11.69
5 725 ~ 5 850	Middle	5 720.00	3.09	0.045	3.14	27.00	23.87

Remark : Margin = Limit –Total Value (=Measured Value +Duty Factor)

9.4.4 Test data for Staddle Channel_Antenna 1

- . Test Result : Pass
- . Duty Cycle : 98.96 %

FREQUENCY RANGE (MHz)	CHANNEL	FREQUENCY (MHz)	MEASURED VALUE (dBm)	Duty Factor (dB)	Total Value (dBm)	LIMIT (dBm)	MARGIN (dB)
5 470 ~ 5 725	Middle	5 720.00	9.37	0.045	9.42	21.00	11.59
5 725 ~ 5 850	Middle	5 720.00	3.28	0.045	3.33	27.00	23.68

Remark : Margin = Limit –Total Value (=Measured Value +Duty Factor)

9.5 Test data for 802.11n_HT20 RLAN Mode

9.5.1 Test data for Antenna 0

- Test Result : Pass
- Duty Cycle : 98.89 %

FREQUENCY RANGE (MHz)	CHANNEL	FREQUENCY (MHz)	MEASURED VALUE (dBm)	Duty Factor (dB)	Total Value (dBm)	LIMIT (dBm)	MARGIN (dB)
5 150 ~ 5 250	Low	5 180.00	11.23	0.048	11.28	21.00	9.72
	Middle	5 220.00	11.86	0.048	11.91	21.00	9.09
	High	5 240.00	12.10	0.048	12.15	21.00	8.85
5 250 ~ 5 350	Low	5 260.00	11.85	0.048	11.90	21.00	9.10
	Middle	5 300.00	11.59	0.048	11.64	21.00	9.36
	High	5 320.00	11.78	0.048	11.83	21.00	9.17
5 470 ~ 5 725	Low	5 500.00	10.94	0.048	10.99	21.00	10.01
	Middle	5 580.00	11.71	0.048	11.76	21.00	9.24
	High	5 700.00	11.12	0.048	11.17	21.00	9.83
5 725 ~ 5 850	Low	5 745.00	11.12	0.048	11.17	27.00	15.83
	Middle	5 785.00	11.38	0.048	11.43	27.00	15.57
	High	5 825.00	10.61	0.048	10.66	27.00	16.34

Remark : Margin = Limit –Total Value (=Measured Value +Duty Factor)

9.5.2 Test data for Antenna 1

- . Test Result : Pass
- . Duty Cycle : 98.75 %

FREQUENCY RANGE (MHz)	CHANNEL	FREQUENCY (MHz)	MEASURED VALUE (dBm)	Duty Factor (dB)	Total Value (dBm)	LIMIT (dBm)	MARGIN (dB)
5 150 ~ 5 250	Low	5 180.00	11.33	0.055	11.39	21.00	9.62
	Middle	5 220.00	11.77	0.055	11.83	21.00	9.18
	High	5 240.00	11.95	0.055	12.01	21.00	9.00
5 250 ~ 5 350	Low	5 260.00	11.77	0.055	11.83	21.00	9.18
	Middle	5 300.00	11.74	0.055	11.80	21.00	9.21
	High	5 320.00	11.88	0.055	11.94	21.00	9.07
5 470 ~ 5 725	Low	5 500.00	11.34	0.055	11.40	21.00	9.61
	Middle	5 580.00	11.83	0.055	11.89	21.00	9.12
	High	5 700.00	10.88	0.055	10.94	21.00	10.07
5 725 ~ 5 850	Low	5 745.00	11.43	0.055	11.49	27.00	15.52
	Middle	5 785.00	10.92	0.055	10.98	27.00	16.03
	High	5 825.00	10.75	0.055	10.81	27.00	16.20

Remark : Margin = Limit –Total Value (=Measured Value +Duty Factor)

9.5.3 Test data for Multiple Transmit

- Test Result : Pass

FREQUENCY RANGE (MHz)	CHANNEL	FREQUENCY (MHz)	ANT 0 TOTAL VALUE (dBm)	ANT 1 TOTAL VALUE (dBm)	ANT0 + ANT1 TOTAL VALUE (dBm)	LIMIT (dBm)	MARGIN (dB)
5 150 ~ 5 250	Low	5 180.00	11.28	11.39	14.34	18.00	3.66
	Middle	5 220.00	11.91	11.83	14.88	18.00	3.12
	High	5 240.00	12.15	12.01	15.09	18.00	2.91
5 250 ~ 5 350	Low	5 260.00	11.90	11.83	14.87	18.00	3.13
	Middle	5 300.00	11.64	11.80	14.73	18.00	3.27
	High	5 320.00	11.83	11.94	14.89	18.00	3.11
5 470 ~ 5 725	Low	5 500.00	10.99	11.40	14.21	18.00	3.79
	Middle	5 580.00	11.76	11.89	14.83	18.00	3.17
	High	5 700.00	11.17	10.94	14.06	18.00	3.94
5 725 ~ 5 850	Low	5 745.00	11.17	11.49	14.34	24.00	9.66
	Middle	5 785.00	11.43	10.98	14.22	24.00	9.78
	High	5 825.00	10.66	10.81	13.74	24.00	10.26

Remark : Margin = Limit -Measured Value

9.5.4 Test data for Staddle Channel_Antenna 0

- . Test Result : Pass
- . Duty Cycle : 88.89 %

FREQUENCY RANGE (MHz)	CHANNEL	FREQUENCY (MHz)	MEASURED VALUE (dBm)	Duty Factor (dB)	Total Value (dBm)	LIMIT (dBm)	MARGIN (dB)
5 470 ~ 5 725	Middle	5 720.00	9.15	0.048	9.20	21.00	11.80
5 725 ~ 5 850	Middle	5 720.00	3.45	0.048	3.50	27.00	23.50

Remark : Margin = Limit – Total Value (=Measured Value +Duty Factor)

9.5.5 Test data for Staddle Channel_Antenna 1

- . Test Result : Pass
- . Duty Cycle : 88.75 %

FREQUENCY RANGE (MHz)	CHANNEL	FREQUENCY (MHz)	MEASURED VALUE (dBm)	Duty Factor (dB)	Total Value (dBm)	LIMIT (dBm)	MARGIN (dB)
5 470 ~ 5 725	Middle	5 720.00	9.17	0.055	9.23	21.00	11.78
5 725 ~ 5 850	Middle	5 720.00	3.56	0.055	3.62	27.00	23.39

Remark : Margin = Limit – Total Value (=Measured Value +Duty Factor)

9.5.6 Test data for Staddle Channel_Multiple Transmit

- . Test Result : Pass

FREQUENCY RANGE (MHz)	CHANNEL	FREQUENCY (MHz)	ANT 0 TOTAL VALUE (dBm)	ANT 1 TOTAL VALUE (dBm)	ANT0 + ANT1 TOTAL VALUE(dBm)	LIMIT (dBm)	MARGIN (dB)
5 470 ~ 5 725	Middle	5 720.00	9.20	9.23	12.22	18.00	5.78
5 725 ~ 5 850	Middle	5 720.00	3.50	3.62	6.57	24.00	17.43

Remark 1 : Margin = Limit – Measured Value (=Receiver Reading + Cable Loss)

Remark 2 : Calculated Output Power= $10\log(10^{(\text{Antenna1 Output Power}/10)} + 10^{(\text{Antenna2 Output Power}/10)})$

9.6 Test data for 802.11n_HT40 RLAN Mode

9.6.1 Test data for Antenna 0

- Test Result : Pass
- Duty Cycle : 97.79 %

FREQUENCY RANGE (MHz)	CHANNEL	FREQUENCY (MHz)	MEASURED VALUE (dBm)	Duty Factor (dB)	Total Value (dBm)	LIMIT (dBm)	MARGIN (dB)
5 150 ~ 5 250	Low	5 190.00	8.35	0.097	8.45	21.00	12.55
	High	5 230.00	8.92	0.097	9.02	21.00	11.98
5 250 ~ 5 350	Low	5 270.00	8.18	0.097	8.28	21.00	12.72
	High	5 310.00	8.14	0.097	8.24	21.00	12.76
5 470 ~ 5 725	Low	5 510.00	8.95	0.097	9.05	21.00	11.95
	Middle	5 550.00	9.52	0.097	9.62	21.00	11.38
	High	5 670.00	9.21	0.097	9.31	21.00	11.69
5 725 ~ 5 850	Low	5 755.00	10.27	0.097	10.37	27.00	16.63
	High	5 795.00	10.16	0.097	10.26	27.00	16.74

Remark : Margin = Limit –Total Value (=Measured Value +Duty Factor)

9.6.2 Test data for Antenna 1

- . Test Result : Pass
- . Duty Cycle : 97.35 %

FREQUENCY RANGE (MHz)	CHANNEL	FREQUENCY (MHz)	MEASURED VALUE (dBm)	Duty Factor (dB)	Total Value (dBm)	LIMIT (dBm)	MARGIN (dB)
5 150 ~ 5 250	Low	5 190.00	8.41	0.117	8.53	21.00	12.47
	High	5 230.00	8.75	0.117	8.87	21.00	12.13
5 250 ~ 5 350	Low	5 270.00	8.03	0.117	8.15	21.00	12.85
	High	5 310.00	8.09	0.117	8.21	21.00	12.79
5 470 ~ 5 725	Low	5 510.00	9.18	0.117	9.30	21.00	11.70
	Middle	5 550.00	9.81	0.117	9.93	21.00	11.07
	High	5 670.00	9.01	0.117	9.13	21.00	11.87
5 725 ~ 5 850	Low	5 755.00	10.35	0.117	10.47	27.00	16.53
	High	5 795.00	9.72	0.117	9.84	27.00	17.16

Remark : Margin = Limit - Total Value (=Measured Value +Duty Factor)

9.6.3 Test data for Multiple Transmit

- Test Result : Pass

FREQUENCY RANGE (MHz)	CHANNEL	FREQUENCY (MHz)	ANT 0 TOTAL VALUE (dBm)	ANT 1 TOTAL VALUE (dBm)	ANT0 + ANT1 TOTAL VALUE (dBm)	LIMIT (dBm)	MARGIN (dB)
5 150 ~ 5 250	Low	5 190.00	8.45	8.53	11.50	18.00	6.50
	High	5 230.00	9.02	8.87	11.95	18.00	6.05
5 250 ~ 5 350	Low	5 270.00	8.28	8.15	11.22	18.00	6.78
	High	5 310.00	8.24	8.21	11.23	18.00	6.77
5 470 ~ 5 725	Low	5 510.00	9.05	9.30	12.18	18.00	5.82
	Middle	5 550.00	9.62	9.93	12.79	18.00	5.21
	High	5 670.00	9.31	9.13	12.23	18.00	5.77
5 725 ~ 5 850	Low	5 755.00	10.37	10.47	13.43	24.00	10.57
	High	5 795.00	10.26	9.84	13.06	24.00	10.94

Remark : Margin = Limit –Total Value (=Measured Value +Duty Factor)

9.6.4 Test data for Staddle Channel_Antenna 0

- . Test Result : Pass
- . Duty Cycle : 71.11 %

FREQUENCY RANGE (MHz)	CHANNEL	FREQUENCY (MHz)	MEASURED VALUE (dBm)	Duty Factor (dB)	Total Value (dBm)	LIMIT (dBm)	MARGIN (dB)
5 470 ~ 5 725	Middle	5 710.00	7.26	0.10	7.36	21.00	13.64
5 725 ~ 5 850	Middle	5 710.00	-3.00	0.10	-2.90	27.00	29.90

Remark : Margin = Limit – Total Value (=Measured Value +Duty Factor)

9.6.5 Test data for Staddle Channel_Antenna 1

- . Test Result : Pass
- . Duty Cycle : 73.33 %

FREQUENCY RANGE (MHz)	CHANNEL	FREQUENCY (MHz)	MEASURED VALUE (dBm)	Duty Factor (dB)	Total Value (dBm)	LIMIT (dBm)	MARGIN (dB)
5 470 ~ 5 725	Middle	5 710.00	7.33	0.12	7.45	21.00	13.55
5 725 ~ 5 850	Middle	5 710.00	-2.50	0.12	-2.38	27.00	29.38

Remark : Margin = Limit – Total Value (=Measured Value +Duty Factor)

9.6.6 Test data for Staddle Channel_Multiple Transmit

- . Test Result : Pass

FREQUENCY RANGE (MHz)	CHANNEL	FREQUENCY (MHz)	ANT 0 TOTAL VALUE (dBm)	ANT 1 TOTAL VALUE (dBm)	ANT0 + ANT1 TOTAL VALUE (dBm)	LIMIT (dBm)	MARGIN (dB)
5 470 ~ 5 725	Middle	5 710.00	7.36	7.45	10.41	18.00	7.59
5 725 ~ 5 850	Middle	5 710.00	-2.90	-2.38	0.38	24.00	23.62

Remark 1 : Margin = Limit – Measured Value (=Receiver Reading + Cable Loss)

Remark 2 : Calculated Output Power= $10\log(10^{(\text{Antenna1 Output Power}/10)} + 10^{(\text{Antenna2 Output Power}/10)})$

9.7 Test data for 802.11ac_HT80 RLAN Mode

9.7.1 Test data for Antenna 0

- . Test Result : Pass
- . Duty Cycle : 95.43 %

FREQUENCY RANGE (MHz)	CHANNEL	FREQUENCY (MHz)	MEASURED VALUE (dBm)	Duty Factor (dB)	Total Value (dBm)	LIMIT (dBm)	MARGIN (dB)
5 150 ~ 5 250	Middle	5 210.00	8.13	0.203	8.33	21.00	12.67
5 250 ~ 5 350	Middle	5 290.00	6.15	0.203	6.35	21.00	14.65
5 470 ~ 5 725	Middle	5 530.00	5.71	0.203	5.91	21.00	15.09
5 725 ~ 5 850	Middle	5 775.00	7.82	0.203	8.02	27.00	18.98

Remark : Margin = Limit –Total Value (=Measured Value +Duty Factor)

9.7.2 Test data for Antenna 1

- . Test Result : Pass
- . Duty Cycle : 95.40 %

FREQUENCY RANGE (MHz)	CHANNEL	FREQUENCY (MHz)	MEASURED VALUE (dBm)	Duty Factor (dB)	Total Value (dBm)	LIMIT (dBm)	MARGIN (dB)
5 150 ~ 5 250	Middle	5 210.00	7.91	0.204	8.11	21.00	12.89
5 250 ~ 5 350	Middle	5 290.00	6.03	0.204	6.23	21.00	14.77
5 470 ~ 5 725	Middle	5 530.00	5.70	0.204	5.90	21.00	15.10
5 725 ~ 5 850	Middle	5 775.00	7.49	0.204	7.69	27.00	19.31

Remark : Margin = Limit –Total Value (=Measured Value +Duty Factor)

9.7.3 Test data for Multiple Transmit

- . Test Result : Pass

FREQUENCY RANGE (MHz)	CHANNEL	FREQUENCY (MHz)	ANT 0 TOTAL VALUE (dBm)	ANT 1 TOTAL VALUE (dBm)	ANT0 + ANT1 TOTAL VALUE (dBm)	LIMIT (dBm)	MARGIN (dB)
5 150 ~ 5 250	Middle	5 210.00	8.33	8.11	11.24	18.00	6.76
5 250 ~ 5 350	Middle	5 290.00	6.35	6.23	9.30	18.00	8.70
5 470 ~ 5 725	Middle	5 530.00	5.91	5.90	8.92	18.00	9.08
5 725 ~ 5 850	Middle	5 775.00	8.02	7.69	10.87	24.00	13.13

Remark 1: Margin = Limit – Measured Value (=Power Sensor Reading + Cable Loss)

Remark 2: Calculated Output Power= $10\log(10^{(\text{Antenna0 Output Power}/10)} + 10^{(\text{Antenna1 Output Power}/10)})$

9.7.4 Test data for Staddle Channel_Antenna 0

- . Test Result : Pass
- . Duty Cycle : 50.63 %

FREQUENCY RANGE (MHz)	CHANNEL	FREQUENCY (MHz)	MEASURED VALUE (dBm)	Duty Factor (dB)	Total Value (dBm)	LIMIT (dBm)	MARGIN (dB)
5 470 ~ 5 725	Middle	5 690.00	4.52	0.20	4.72	21.00	16.28
5 725 ~ 5 850	Middle	5 690.00	-9.40	0.20	-9.20	27.00	36.20

Remark : Margin = Limit – Total Value (=Measured Value +Duty Factor)

9.7.5 Test data for Staddle Channel_Antenna 1

- . Test Result : Pass
- . Duty Cycle : 53.8 %

FREQUENCY RANGE (MHz)	CHANNEL	FREQUENCY (MHz)	MEASURED VALUE (dBm)	Duty Factor (dB)	Total Value (dBm)	LIMIT (dBm)	MARGIN (dB)
5 470 ~ 5 725	Middle	5 690.00	4.17	0.20	4.37	21.00	16.63
5 725 ~ 5 850	Middle	5 690.00	-9.10	0.20	-8.90	27.00	35.90

Remark : Margin = Limit – Total Value (=Measured Value +Duty Factor)

9.7.6 Test data for Staddle Channel_Multiple Transmit

- . Test Result : Pass

FREQUENCY RANGE (MHz)	CHANNEL	FREQUENCY (MHz)	ANT 0 TOTAL VALUE (dBm)	ANT 1 TOTAL VALUE (dBm)	ANT0 + ANT1 TOTAL VALUE (dBm)	LIMIT (dBm)	MARGIN (dB)
5 470 ~ 5 725	Middle	5 690.00	4.72	4.37	7.56	18.00	10.44
5 725 ~ 5 850	Middle	5 690.00	-9.20	-8.90	-6.03	24.00	30.03

Remark 1 : Margin = Limit – Measured Value (=Receiver Reading + Cable Loss)

Remark 2 : Calculated Output Power= $10\log(10^{(\text{Antenna1 Output Power}/10)} + 10^{(\text{Antenna2 Output Power}/10)})$

10. PEAK POWER SPECTRUM DENSITY


10.1 Operating environment

Temperature : 23 °C

Relative humidity : 45 % R.H.

10.2 Test set-up

The antenna output of the EUT was connected to the spectrum analyzer. The resolution bandwidth is set to 1 MHz, the video bandwidth is set to 3 times the resolution bandwidth. The maximum level from the EUT in 1 MHz bandwidth was measured with above condition.



10.3 Test Date

December 05, 2021 ~ March 08, 2022

10.4 Test data for 802.11a RLAN Mode

10.4.1 Test data for Antenna 0

- Operating condition : Highest Output Power Transmitting Mode

- Test Result : Pass

FREQUENCY RANGE (MHz)	CHANNEL	FREQUENCY (MHz)	MEASURED VALUE (dBm)	Duty Factor (dB)	Result value (dBm)	LIMIT (dBm / MHz)	MARGIN (dB)
5 150 ~ 5 250	Low	5 180.00	0.41	0.05	0.46	8.00	7.55
	Middle	5 220.00	0.81	0.05	0.86	8.00	7.15
	High	5 240.00	1.13	0.05	1.18	8.00	6.83
5 250 ~ 5 350	Low	5 260.00	0.90	0.05	0.95	8.00	7.06
	Middle	5 300.00	0.63	0.05	0.68	8.00	7.33
	High	5 320.00	0.76	0.05	0.81	8.00	7.20
5 470 ~ 5 725	Low	5 500.00	0.48	0.05	0.53	8.00	7.48
	Middle	5 580.00	0.84	0.05	0.89	8.00	7.12
	High	5 700.00	-0.06	0.05	-0.02	8.00	8.02
5 725 ~ 5 850	Low	5 745.00	-2.80	0.05	-2.76	27.00	29.76
	Middle	5 785.00	-2.68	0.05	-2.64	27.00	29.64
	High	5 825.00	-3.73	0.05	-3.69	27.00	30.69

Remark.1: See next page for measurement data.

Remark.2: Peak Power Spectral Density = Reading Value + Duty Cycle Factor

10.4.2 Test data for Antenna 1

- . Operating condition : Highest Output Power Transmitting Mode

- . Test Result : Pass

FREQUENCY RANGE (MHz)	CHANNEL	FREQUENCY (MHz)	MEASURED VALUE (dBm)	Duty Factor (dB)	Result value' (dBm)	LIMIT (dBm / MHz)	MARGIN (dB)
5 150 ~ 5 250	Low	5 180.00	0.01	0.05	0.06	8.00	7.95
	Middle	5 220.00	0.17	0.05	0.22	8.00	7.79
	High	5 240.00	0.55	0.05	0.60	8.00	7.41
5 250 ~ 5 350	Low	5 260.00	0.25	0.05	0.30	8.00	7.71
	Middle	5 300.00	0.26	0.05	0.31	8.00	7.70
	High	5 320.00	0.46	0.05	0.51	8.00	7.50
5 470 ~ 5 725	Low	5 500.00	0.31	0.05	0.36	8.00	7.65
	Middle	5 580.00	0.72	0.05	0.77	8.00	7.24
	High	5 700.00	-0.32	0.05	-0.28	8.00	8.28
5 725 ~ 5 850	Low	5 745.00	-2.98	0.05	-2.94	27.00	29.94
	Middle	5 785.00	-3.65	0.05	-3.61	27.00	30.61
	High	5 825.00	-3.68	0.05	-3.64	27.00	30.64

Remark.1: See next page for measurement data.

Remark.2: Peak Power Spectral Density = Reading Value + Duty Cycle Factor

10.4.3 Test data for Staddle Channel_Antenna 0

- . Operating condition : Highest Output Power Transmitting Mode
- . Test Result : Pass

FREQUENCY RANGE (MHz)	FREQUENCY (MHz)	MEASURED VALUE (dBm)	Duty Factor (dB)	Result Value (dBm)	LIMIT (dBm / MHz)	MARGIN (dB)
5 470 ~ 5 725	5 720.00	-0.58	0.05	-0.53	8.00	8.53
5 725 ~ 5 850	5 720.00	-4.05	0.05	-4.00	27.00	31.00

Remark.1: See next page for measurement data.

Remark.2: Peak Power Spectral Density = Reading Value + Duty Cycle Factor

10.4.4 Test data for Staddle Channel_Antenna 1

- . Operating condition : Highest Output Power Transmitting Mode
- . Test Result : Pass

FREQUENCY RANGE (MHz)	FREQUENCY (MHz)	MEASURED VALUE (dBm)	Duty Factor (dB)	Result Value (dBm)	LIMIT (dBm / MHz)	MARGIN (dB)
5 470 ~ 5 725	5 720.00	-0.61	0.05	-0.56	8.00	8.56
5 725 ~ 5 850	5 720.00	-3.82	0.05	-3.77	27.00	30.77

Remark.1: See next page for measurement data.

Remark.2: Peak Power Spectral Density = Reading Value + Duty Cycle Factor

10.5 Test data for 802.11n_HT20 RLAN Mode

10.5.1 Test data for Antenna 0

- Operating condition : Highest Output Power Transmitting Mode

- Test Result : Pass

FREQUENCY RANGE (MHz)	CHANNEL	FREQUENCY (MHz)	MEASURED VALUE (dBm)	Duty Factor (dB)	Result value' (dBm)	LIMIT (dBm / MHz)	MARGIN (dB)
5 150 ~ 5 250	Low	5 180.00	0.23	0.05	0.28	8.00	7.72
	Middle	5 220.00	0.75	0.05	0.80	8.00	7.20
	High	5 240.00	0.87	0.05	0.92	8.00	7.08
5 250 ~ 5 350	Low	5 260.00	0.54	0.05	0.59	8.00	7.41
	Middle	5 300.00	0.58	0.05	0.63	8.00	7.37
	High	5 320.00	0.67	0.05	0.72	8.00	7.28
5 470 ~ 5 725	Low	5 500.00	0.21	0.05	0.26	8.00	7.74
	Middle	5 580.00	0.67	0.05	0.72	8.00	7.28
	High	5 700.00	-0.04	0.05	0.01	8.00	7.99
5 725 ~ 5 850	Low	5 745.00	-2.94	0.05	-2.89	27.00	29.89
	Middle	5 785.00	-3.08	0.05	-3.03	27.00	30.03
	High	5 825.00	-3.73	0.05	-3.68	27.00	30.68

Remark.1: See next page for measurement data.

Remark.2: Peak Power Spectral Density = Reading Value + Duty Cycle Factor

10.5.2 Test data for Antenna 1

- . Operating condition : Highest Output Power Transmitting Mode

- . Test Result : Pass

FREQUENCY RANGE (MHz)	CHANNEL	FREQUENCY (MHz)	MEASURED VALUE (dBm)	Duty Factor (dB)	Result value' (dBm)	LIMIT (dBm / MHz)	MARGIN (dB)
5 150 ~ 5 250	Low	5 180.00	-0.22	0.06	-0.17	8.00	8.17
	Middle	5 220.00	-0.02	0.06	0.04	8.00	7.97
	High	5 240.00	0.06	0.06	0.12	8.00	7.89
5 250 ~ 5 350	Low	5 260.00	-0.42	0.06	-0.37	8.00	8.37
	Middle	5 300.00	-0.20	0.06	-0.15	8.00	8.15
	High	5 320.00	0.17	0.06	0.23	8.00	7.78
5 470 ~ 5 725	Low	5 500.00	0.22	0.06	0.28	8.00	7.73
	Middle	5 580.00	0.46	0.06	0.52	8.00	7.49
	High	5 700.00	-0.50	0.06	-0.45	8.00	8.45
5 725 ~ 5 850	Low	5 745.00	-3.01	0.06	-2.96	27.00	29.96
	Middle	5 785.00	-3.91	0.06	-3.86	27.00	30.86
	High	5 825.00	-3.98	0.06	-3.93	27.00	30.93

Remark.1: See next page for measurement data.

Remark.2: Peak Power Spectral Density = Reading Value + Duty Cycle Factor

10.5.3 Test data for Multiple Transmit

- . Operating condition : Highest Output Power Transmitting Mode

- . Test Result : Pass

FREQUENCY RANGE (MHz)	CHANNEL	FREQUENCY (MHz)	ANT 0 TOTAL VALUE (dBm)	ANT 1 TOTAL VALUE (dBm)	ANT0 + ANT1 TOTAL VALUE (dBm)	LIMIT (dBm / MHz)	MARGIN (dB)
5 150 ~ 5 250	Low	5 180.00	0.28	-0.17	3.07	5.00	1.93
	Middle	5 220.00	0.80	0.04	3.44	5.00	1.56
	High	5 240.00	0.92	0.12	3.55	5.00	1.45
5 250 ~ 5 350	Low	5 260.00	0.59	-0.37	3.15	5.00	1.85
	Middle	5 300.00	0.63	-0.15	3.27	5.00	1.73
	High	5 320.00	0.72	0.23	3.49	5.00	1.51
5 470 ~ 5 725	Low	5 500.00	0.26	0.28	3.28	5.00	1.72
	Middle	5 580.00	0.72	0.52	3.63	5.00	1.37
	High	5 700.00	0.01	-0.45	2.80	5.00	2.20
5 725 ~ 5 850	Low	5 745.00	-2.89	-2.96	0.09	24.00	23.91
	Middle	5 785.00	-3.03	-3.86	-0.41	24.00	24.41
	High	5 825.00	-3.68	-3.93	-0.79	24.00	24.79

10.5.4 Test data for Staddle Channel_Antenna 0

- . Operating condition : Highest Output Power Transmitting Mode

- . Test Result : Pass

FREQUENCY RANGE (MHz)	FREQUENCY (MHz)	MEASURED VALUE (dBm)	Duty Factor (dB)	Result Value (dBm)	LIMIT (dBm / MHz)	MARGIN (dB)
5 470 ~ 5 725	5 720.00	-0.96	0.05	-0.91	8.00	8.91
5 725 ~ 5 850	5 720.00	-4.09	0.05	-4.04	27.00	31.04

Remark.1: See next page for measurement data.

Remark.2: Peak Power Spectral Density = Reading Value + Duty Cycle Factor

10.5.5 Test data for Staddle Channel_Antenna 1

- . Operating condition : Highest Output Power Transmitting Mode

- . Test Result : Pass

FREQUENCY RANGE (MHz)	FREQUENCY (MHz)	MEASURED VALUE (dBm)	Duty Factor (dB)	Result Value (dBm)	LIMIT (dBm / MHz)	MARGIN (dB)
5 470 ~ 5 725	5 720.00	-0.90	0.06	-0.84	8.00	8.84
5 725 ~ 5 850	5 720.00	-3.87	0.06	-3.81	27.00	30.81

Remark.1: See next page for measurement data.

Remark.2: Peak Power Spectral Density = Reading Value + Duty Cycle Factor

10.5.6 Test data for Staddle Channel_Multiple Transmit

- . Operating condition : Highest Output Power Transmitting Mode

- . Test Result : Pass

FREQUENCY RANGE (MHz)	CHANNEL	FREQUENCY (MHz)	ANT 0 TOTAL VALUE (dBm)	ANT 1 TOTAL VALUE (dBm)	ANT0 + ANT1 TOTAL VALUE (dBm)	LIMIT (dBm / MHz)	MARGIN (dB)
5 470 ~ 5 725	Middle	5 720.00	-0.91	-0.84	2.14	5.00	2.86
5 725 ~ 5 850	Middle	5 720.00	-4.04	-3.81	-0.91	24.00	24.91

10.6 Test data for 802.11n_HT40 RLAN Mode

10.6.1 Test data for Antenna 0

- Operating condition : Highest Output Power Transmitting Mode
- Test Result : Pass

FREQUENCY RANGE (MHz)	CHANNEL	FREQUENCY (MHz)	MEASURED VALUE (dBm)	Duty Factor (dB)	Result Value (dBm)	LIMIT (dBm / MHz)	MARGIN (dB)
5 150 ~ 5 250	Low	5 190.00	-5.54	0.10	-5.44	8.00	13.44
	High	5 230.00	-4.97	0.10	-4.87	8.00	12.87
5 250 ~ 5 350	Low	5 270.00	-6.23	0.10	-6.13	8.00	14.13
	High	5 310.00	-6.16	0.10	-6.06	8.00	14.06
5 470 ~ 5 725	Low	5 510.00	-4.82	0.10	-4.72	8.00	12.72
	Middle	5 550.00	-4.64	0.10	-4.54	8.00	12.54
	High	5 670.00	-4.98	0.10	-4.88	8.00	12.88
5 725 ~ 5 850	Low	5 755.00	-6.92	0.10	-6.82	27.00	33.82
	High	5 795.00	-7.55	0.10	-7.45	27.00	34.45

Remark.1: See next page for measurement data.

Remark.2: Peak Power Spectral Density = Reading Value + Duty Cycle Factor

10.6.2 Test data for Antenna 1

- . Operating condition : Highest Output Power Transmitting Mode

- . Test Result : Pass

FREQUENCY RANGE (MHz)	CHANNEL	FREQUENCY (MHz)	MEASURED VALUE (dBm)	Duty Factor (dB)	Result VALUE (dBm)	LIMIT (dBm / MHz)	MARGIN (dB)
5 150 ~ 5 250	Low	5 190.00	-6.25	0.12	-6.13	8.00	14.13
	High	5 230.00	-5.95	0.12	-5.83	8.00	13.83
5 250 ~ 5 350	Low	5 270.00	-6.84	0.12	-6.72	8.00	14.72
	High	5 310.00	-6.53	0.12	-6.41	8.00	14.41
5 470 ~ 5 725	Low	5 510.00	-4.80	0.12	-4.68	8.00	12.68
	Middle	5 550.00	-4.65	0.12	-4.53	8.00	12.53
	High	5 670.00	-5.32	0.12	-5.20	8.00	13.20
5 725 ~ 5 850	Low	5 755.00	-7.22	0.12	-7.10	27.00	34.10
	High	5 795.00	-7.83	0.12	-7.71	27.00	34.71

Remark.1: See next page for measurement data.

Remark.2: Peak Power Spectral Density = Reading Value + Duty Cycle Factor

10.6.3 Test data for Multiple Transmit

- . Operating condition : Highest Output Power Transmitting Mode
- . Test Result : Pass

FREQUENCY RANGE (MHz)	CHANNEL	FREQUENCY (MHz)	ANT 0 TOTAL VALUE (dBm)	ANT 1 TOTAL VALUE (dBm)	ANT0 + ANT1 TOTAL VALUE (dBm)	LIMIT (dBm / MHz)	MARGIN (dB)
5 150 ~ 5 250	Low	5 190.00	-5.44	-6.13	-2.76	5.00	7.76
	High	5 230.00	-4.87	-5.83	-2.32	5.00	7.32
5 250 ~ 5 350	Low	5 270.00	-6.13	-6.72	-3.41	5.00	8.41
	High	5 310.00	-6.06	-6.41	-3.22	5.00	8.22
5 470 ~ 5 725	Low	5 510.00	-4.72	-4.68	-1.69	5.00	6.69
	Middle	5 550.00	-4.54	-4.53	-1.53	5.00	6.53
	High	5 670.00	-4.88	-5.20	-2.03	5.00	7.03
5 725 ~ 5 850	Low	5 755.00	-6.82	-7.10	-3.95	24.00	27.95
	High	5 795.00	-7.45	-7.71	-4.57	24.00	28.57

10.6.4 Test data for Staddle Channel_Antenna 0

- . Operating condition : Highest Output Power Transmitting Mode
- . Test Result : Pass

FREQUENCY RANGE (MHz)	FREQUENCY (MHz)	MEASURED VALUE (dBm)	DUTY FACTOR (dB)	Result VALUE (dBm)	LIMIT (dBm / MHz)	MARGIN (dB)
5 470 ~ 5 725	5 710.00	-6.38	0.10	-6.28	8.00	14.28
5 725 ~ 5 850	5 710.00	-9.76	0.10	-9.66	27.00	36.66

Remark.1: See next page for measurement data.

Remark.2: Peak Power Spectral Density = Reading Value + Duty Cycle Factor

10.6.5 Test data for Staddle Channel_Antenna 1

- . Operating condition : Highest Output Power Transmitting Mode
- . Test Result : Pass

FREQUENCY RANGE (MHz)	FREQUENCY (MHz)	MEASURED VALUE (dBm)	DUTY FACTOR (dB)	Result VALUE (dBm)	LIMIT (dBm / MHz)	MARGIN (dB)
5 470 ~ 5 725	5 710.00	-6.25	0.12	-6.13	8.00	14.13
5 725 ~ 5 850	5 710.00	-9.32	0.12	-9.20	27.00	36.20

Remark.1: See next page for measurement data.

Remark.2: Peak Power Spectral Density = Reading Value + Duty Cycle Factor

10.6.6 Test data for Staddle Channel_Multiple Transmit

- . Operating condition : Highest Output Power Transmitting Mode
- . Test Result : Pass

FREQUENCY RANGE (MHz)	CHANNEL	FREQUENCY (MHz)	ANT 0 TOTAL VALUE (dBm)	ANT 1 TOTAL VALUE (dBm)	ANT0 + ANT1 TOTAL VALUE (dBm)	LIMIT (dBm / MHz)	MARGIN (dB)
5 470 ~ 5 725	Middle	5 710.00	-6.28	-6.13	-3.19	5.00	8.19
5 725 ~ 5 850	Middle	5 710.00	-9.66	-9.20	-6.41	24.00	30.41

10.7 Test data for 802.11ac_HT80 RLAN Mode

10.7.1 Test data for Antenna 0

- . Operating condition : Highest Output Power Transmitting Mode
- . Test Result : Pass

FREQUENCY RANGE (MHz)	CHANNEL	FREQUENCY (MHz)	MEASURED VALUE (dBm)	Duty Factor (dB)	Result VALUE (dBm)	LIMIT (dBm / MHz)	MARGIN (dB)
5 150 ~ 5 250	Low	5 210.00	-9.22	0.20	-9.02	8.00	17.02
5 250 ~ 5 350	Low	5 290.00	-11.96	0.20	-11.76	8.00	19.76
5 470 ~ 5 725	Low	5 530.00	-11.84	0.20	-11.64	8.00	19.64
5 725 ~ 5 850	Low	5 775.00	-13.11	0.20	-12.91	27.00	39.91

Remark.1: See next page for measurement data.

Remark.2: Peak Power Spectral Density = Reading Value + Duty Cycle Factor

10.7.2 Test data for Antenna 1

- . Operating condition : Highest Output Power Transmitting Mode
- . Test Result : Pass

FREQUENCY RANGE (MHz)	CHANNEL	FREQUENCY (MHz)	MEASURED VALUE (dBm)	Duty Factor (dB)	Result VALUE (dBm)	LIMIT (dBm / MHz)	MARGIN (dB)
5 150 ~ 5 250	Low	5 210.00	-10.23	0.20	-10.03	8.00	18.03
5 250 ~ 5 350	Low	5 290.00	-12.21	0.20	-12.01	8.00	20.01
5 470 ~ 5 725	Low	5 530.00	-12.09	0.20	-11.89	8.00	19.89
5 725 ~ 5 850	Low	5 775.00	-13.69	0.20	-13.49	27.00	40.49

Remark.1: See next page for measurement data.

Remark.2: Peak Power Spectral Density = Reading Value + Duty Cycle Factor

10.7.3 Test data for Multiple Transmit

- . Operating condition : Highest Output Power Transmitting Mode

- . Test Result : Pass

FREQUENCY RANGE (MHz)	CHANNEL	FREQUENCY (MHz)	ANT 0 TOTAL VALUE (dBm)	ANT 1 TOTAL VALUE (dBm)	ANT0 + ANT1 TOTAL VALUE (dBm)	LIMIT (dBm / MHz)	MARGIN (dB)
5 150 ~ 5 250	Middle	5 210.00	-9.02	-10.03	-6.48	5.00	11.48
5 250 ~ 5 350	Middle	5 290.00	-11.76	-12.01	-8.87	5.00	13.87
5 470 ~ 5 725	Middle	5 530.00	-11.64	-11.89	-8.75	5.00	13.75
5 725 ~ 5 850	Middle	5 775.00	-12.91	-13.49	-10.18	24.00	34.18

10.7.4 Test data for Staddle Channel_Antenna 0

- . Operating condition : Highest Output Power Transmitting Mode

- . Test Result : Pass

FREQUENCY RANGE (MHz)	FREQUEN CY (MHz)	MEASURED VALUE (dBm)	Duty Factor (dB)	Result VALUE (dBm)	LIMIT (dBm / MHz)	MARGIN (dB)
5 470 ~ 5 725	5 690.00	-12.63	0.20	-12.43	8.00	20.43
5 725 ~ 5 850	5 690.00	-16.74	0.20	-16.54	27.00	43.54

Remark.1: See next page for measurement data.

Remark.2: Peak Power Spectral Density = Reading Value + Duty Cycle Factor

10.7.5 Test data for Staddle Channel_Antenna 1

- . Operating condition : Highest Output Power Transmitting Mode

- . Test Result : Pass

FREQUENCY RANGE (MHz)	FREQUEN CY (MHz)	MEASURED VALUE (dBm)	Duty Factor (dB)	Result VALUE (dBm)	LIMIT (dBm / MHz)	MARGIN (dB)
5 470 ~ 5 725	5 690.00	-13.31	0.20	-13.11	8.00	21.11
5 725 ~ 5 850	5 690.00	-16.34	0.20	-16.14	27.00	43.14

Remark.1: See next page for measurement data.

Remark.2: Peak Power Spectral Density = Reading Value + Duty Cycle Factor

10.7.6 Test data for Staddle Channel_Multiple Transmit

- . Operating condition : Highest Output Power Transmitting Mode

- . Test Result : Pass

FREQUENCY RANGE (MHz)	CHANNEL	FREQUENCY (MHz)	ANT 0 TOTAL VALUE (dBm)	ANT 1 TOTAL VALUE (dBm)	ANT0 + ANT1 TOTAL VALUE (dBm)	LIMIT (dBm / MHz)	MARGIN (dB)
5 470 ~ 5 725	Middle	5 690.00	-12.43	-13.11	-9.75	5.00	14.75
5 725 ~ 5 850	Middle	5 690.00	-16.54	-16.14	-13.33	24.00	37.33

11. FREQUENCY STABILITY WITH TEMPERATURE VARIATION


11.1 Operating environment

Temperature : 23 °C

Relative humidity : 45 % R.H.

11.2 Test set-up

Turn EUT off and set chamber temperature to -20 °C and then allow sufficient time (approximately 20 min to 30 min after chamber reach the assigned temperature) for EUT to stabilize. Turn on the EUT and measure the EUT operating frequency and then turn off the EUT after the measurement. The temperature in the chamber was raised 10 °C step from -20 °C to +80 °C. Repeat above method for frequency measurements every 10 °C step and then record all measured frequencies on each temperature step.



11.3 Test Date

December 05, 2021 ~ March 08, 2022

11.4 Test Data for U-NII-1

- Result : Pass

Temperature (°C)	Carrier Freq. (Hz)	Measured Freq. (Hz)	Frequency Error (Hz)
-20	5 180 000 000	5 180 004 075	4 075
-10		5 180 008 867	8 867
0		5 180 006 537	6 537
10		5 180 010 974	10 974
20		5 180 013 886	13 886
30		5 180 016 943	16 943
40		5 180 013 930	13 930
50		5 180 017 081	17 081
-20	5 220 000 000	5 220 003 264	3 264
-10		5 220 005 573	5 573
0		5 220 007 758	7 758
10		5 220 009 672	9 672
20		5 220 012 393	12 393
30		5 220 016 063	16 063
40		5 220 019 236	19 236
50		5 220 022 895	22 895
-20	5 240 000 000	5 240 004 369	4 369
-10		5 240 006 795	6 795
0		5 240 010 129	10 129
10		5 240 012 763	12 763
20		5 240 013 260	13 260
30		5 240 016 991	16 991
40		5 240 020 411	20 411
50		5 240 022 948	22 948

Note : While maintaining a constant temperature inside the environmental chamber, turn the EUT ON and record the operating frequency at startup, and at 2 minutes, 5 minutes, and 10 minutes after the EUT is energized.

Four measurements in total are made.(ANSI C63.10-2020)

11.5 Test Data for U-NII-2A

- . Result : Pass

Temperature (°C)	Carrier Freq. (Hz)	Measured Freq. (Hz)	Frequency Error (Hz)
-20	5 260 000 000	5 260 004 657	4 657
-10		5 260 007 670	7 670
0		5 260 012 764	12 764
10		5 260 016 745	16 745
20		5 260 020 985	20 985
30		5 260 024 451	24 451
40		5 260 019 004	19 004
50		5 260 022 461	22 461
-20	5 300 000 000	5 300 004 006	4 006
-10		5 300 007 820	7 820
0		5 300 008 491	8 491
10		5 300 012 990	12 990
20		5 300 015 459	15 459
30		5 300 020 133	20 133
40		5 300 023 903	23 903
50		5 300 026 665	26 665
-20	5 320 000 000	5 320 003 801	3 801
-10		5 320 009 364	9 364
0		5 320 013 186	13 186
10		5 320 017 117	17 117
20		5 320 020 674	20 674
30		5 320 015 461	15 461
40		5 320 017 185	17 185
50		5 320 020 512	20 512

Note : While maintaining a constant temperature inside the environmental chamber, turn the EUT ON and record the operating frequency at startup, and at 2 minutes, 5 minutes, and 10 minutes after the EUT is energized.

Four measurements in total are made.(ANSI C63.10-2020)

11.6 Test Data for U-NII-2C

- Result : Pass

Temperature (°C)	Carrier Freq. (Hz)	Measured Freq. (Hz)	Frequency Error (Hz)
-20	5 500 000 000	5 500 004 069	4 069
-10		5 500 007 970	7 970
0		5 500 012 716	12 716
10		5 500 016 545	16 545
20		5 500 018 254	18 254
30		5 500 021 500	21 500
40		5 500 024 449	24 449
50		5 500 028 954	28 954
-20	5 660 000 000	5 580 002 885	2 885
-10		5 580 005 384	5 384
0		5 580 010 167	10 167
10		5 580 012 455	12 455
20		5 580 016 276	16 276
30		5 580 019 312	19 312
40		5 580 021 328	21 328
50		5 580 023 226	23 226
-20	5 700 000 000	5 700 003 291	3 291
-10		5 700 005 766	5 766
0		5 700 008 861	8 861
10		5 700 012 879	12 879
20		5 700 017 721	17 721
30		5 700 019 416	19 416
40		5 700 021 473	21 473
50		5 700 024 221	24 221

Note : While maintaining a constant temperature inside the environmental chamber, turn the EUT ON and record the operating frequency at startup, and at 2 minutes, 5 minutes, and 10 minutes after the EUT is energized.

Four measurements in total are made.(ANSI C63.10-2020)

11.7 Test Data for U-NII-3

- Result : Pass

Temperature (°C)	Carrier Freq. (Hz)	Measured Freq. (Hz)	Frequency Error (Hz)
-20	5 745 000 000	5 745 002 238	2 238
-10		5 745 003 538	3 538
0		5 745 007 319	7 319
10		5 745 012 146	12 146
20		5 745 016 935	16 935
30		5 745 021 338	21 338
40		5 745 025 744	25 744
50		5 745 028 820	28 820
-20	5 785 000 000	5 785 003 581	3 581
-10		5 785 008 206	8 206
0		5 785 010 843	10 843
10		5 785 012 762	12 762
20		5 785 013 284	13 284
30		5 785 014 781	14 781
40		5 785 016 194	16 194
50		5 785 019 131	19 131
-20	5 825 000 000	5 825 001 757	1 757
-10		5 825 003 636	3 636
0		5 825 005 059	5 059
10		5 825 007 127	7 127
20		5 825 009 891	9 891
30		5 825 013 868	13 868
40		5 825 018 290	18 290
50		5 825 022 065	22 065

Note : While maintaining a constant temperature inside the environmental chamber, turn the EUT ON and record the operating frequency at startup, and at 2 minutes, 5 minutes, and 10 minutes after the EUT is energized.

Four measurements in total are made.(ANSI C63.10-2020)

12. FREQUENCY STABILITY WITH VOLTAGE VARIATION


12.1 Operating environment

Temperature : 23 °C

Relative humidity : 45 % R.H.

12.2 Test set-up

An external DC power supply was connected to the input of the EUT. The voltage of EUT set to 115.0 % of the nominal value and then was reduced to 85.0 % of nominal voltage. The output frequency was recorded at each step.



12.3 Test Date

December 05, 2021 ~ March 08, 2022

12.4 Test Data for U-NII-1

- Result : Pass

Voltage (VDC)	Carrier Freq. (Hz)	Measured Freq. (Hz)	Frequency Error (Hz)
3.30	5 180 000 000	5 180 013 255	13 255
2.97		5 180 013 149	13 149
3.63		5 180 013 399	13 399
3.30	5 220 000 000	5 220 015 329	15 329
2.97		5 220 015 183	15 183
3.63		5 220 015 462	15 462
3.30	5 240 000 000	5 240 013 330	13 330
2.97		5 240 013 187	13 187
3.63		5 240 013 478	13 478

12.5 Test Data for U-NII-2A

- Result : Pass

Voltage (VDC)	Carrier Freq. (Hz)	Measured Freq. (Hz)	Frequency Error (Hz)
3.30	5 260 000 000	5 260 012 895	12 895
2.97		5 260 012 762	12 762
3.63		5 260 013 016	13 016
3.30	5 300 000 000	5 300 016 125	16 125
2.97		5 300 016 007	16 007
3.63		5 300 016 289	16 289
3.30	5 320 000 000	5 320 013 710	13 710
2.97		5 320 013 597	13 597
3.63		5 320 013 862	13 862

12.6 Test Data for U-NII-2C

- Result : Pass

Voltage (VDC)	Carrier Freq. (Hz)	Measured Freq. (Hz)	Frequency Error (Hz)
3.30	5 500 000 000	5 500 015 984	15 984
2.97		5 500 015 845	15 845
3.63		5 500 016 152	16 152
3.30	5 580 000 000	5 580 011 069	11 069
2.97		5 580 010 945	10 945
3.63		5 580 011 199	11 199
3.30	5 700 000 000	5 700 015 901	15 901
2.97		5 700 015 772	15 772
3.63		5 700 016 093	16 093

12.7 Test Data for U-NII-3

- Result : Pass

Voltage (VDC)	Carrier Freq. (Hz)	Measured Freq. (Hz)	Frequency Error (Hz)
3.30	5 745 000 000	5 745 017 884	17 884
2.97		5 745 017 756	17 756
3.63		5 745 018 024	18 024
3.30	5 785 000 000	5 785 017 606	17 606
2.97		5 785 017 484	17 484
3.63		5 785 017 789	17 789
3.30	5 825 000 000	5 825 016 217	16 217
2.97		5 825 016 077	16 077
3.63		5 825 016 404	16 404

13. RADIATED SPURIOUS EMISSIONS

13.1 Operating environment


Temperature : 23 °C

Relative humidity : 45 % R.H.

13.2 Test set-up for conducted measurement

The radiated emissions measurements were on the 3 m semi anechoic chamber. The EUT and other support equipment were placed on a non-conductive turntable above the ground plane. The interconnecting cables from outside test site were inserted into ferrite clamps at the point where the cables reach the turntable.

The frequency spectrum from 30 MHz to 40 GHz was scanned and maximum emission levels at each frequency recorded. The system was rotated 360°, and the antenna was varied in the height between 1.0 m and 4.0 m in order to determine the maximum emission levels. This procedure was performed for horizontal and vertical polarization of the receiving antenna.



13.3 Test Date

December 05, 2021 ~ March 08, 2022

13.4 Test data for Below 30 MHz

- . Resolution bandwidth : 200 Hz (from 9 kHz to 0.15 MHz), 9 kHz (from 0.15 MHz to 30 MHz)
- . Frequency range : 9 kHz ~ 30 MHz
- . Measurement distance : 3 m
- . Operating mode : Transmitting mode

Frequency (MHz)	Reading (dB μ V)	Ant. Pol. (H/V)	Ant. Height (m)	Angle (°)	Ant. Factor (dB/m)	Cable Loss	Emission Level(dB μ V/m)	Limits (dB μ V/m)	Margin (dB)
Emission from the EUT more than 20 dB below the limit in each frequency range.									

13.5 Test data for 30 MHz ~ 1 000 MHz


13.5.1 Test data for WLAN 5 GHz

Humidity Level : 45 % R.H. Temperature: 23 °C
 Limits apply to : FCC CFR 47, PART 15, SUBPART C, SECTION 15.247
 Result : PASSED

EUT : RF Module

Detector : CISPR Quasi-Peak (6 dB Bandwidth: 120 kHz)

- Antenna 0, Antenna 1 and Multiple transmit tested, but the worst data were recorded.




No.	FREQ [MHz]	READING QP [dBuV]	ANT FACTOR [dB]	LOSS [dB]	GAIN [dB]	RESULT [dBuV/m]	LIMIT [dBuV/m]	MARGIN [dB]	ANTENNA [cm]	TABLE [DEG]
<hr/>										
1	65.890	28.6	12.6	1.5	32.0	10.7	40.0	29.3	100	251
2	486.871	27.4	22.8	3.8	32.3	21.7	46.0	24.3	100	330
3	950.517	26.1	28.0	5.4	31.7	27.8	46.0	18.2	100	359
<hr/>										
----- Vertical -----										
4	119.240	28.9	18.5	2.0	32.1	17.3	43.5	26.2	100	358
5	562.529	35.1	23.8	4.1	32.4	30.6	46.0	15.4	100	358
6	687.655	37.3	25.4	4.6	32.4	34.9	46.0	11.1	100	137

13.5.2 Test data for Intermodulation Mode(WLAN 5 GHz + Bluetooth)Humidity Level : 45 % R.H. Temperature: 23 °CLimits apply to : FCC CFR 47, PART 15, SUBPART C, SECTION 15.247Result : PASSED

EUT : RF Module

Detector : CISPR Quasi-Peak (6 dB Bandwidth: 120 kHz)




No.	FREQ [MHz]	READING QP [dBuV]	ANT FACTOR [dB]	LOSS [dB]	GAIN [dB]	RESULT [dBuV/m]	LIMIT [dBuV/m]	MARGIN [dB]	ANTENNA [cm]	TABLE [DEG]
----- Horizontal -----										
1	62.980	30.4	12.3	1.5	32.0	12.2	40.0	27.8	200	107
2	837.031	30.1	27.2	5.1	32.2	30.2	46.0	15.8	100	58
----- Vertical -----										
3	65.890	31.6	12.6	1.5	32.0	13.7	40.0	26.3	200	0
4	119.240	28.8	18.5	2.0	32.1	17.2	43.5	26.3	100	359
5	562.529	33.9	23.8	4.1	32.4	29.4	46.0	16.6	100	359
6	687.655	37.2	25.4	4.6	32.4	34.8	46.0	11.2	100	179

13.5.3 Test data for Intermodulation Mode(WLAN 5 GHz + Bluetooth LE)Humidity Level : 45 % R.H. Temperature: 23 °CLimits apply to : FCC CFR 47, PART 15, SUBPART C, SECTION 15.247Result : PASSED

EUT : RF Module

Detector : CISPR Quasi-Peak (6 dB Bandwidth: 120 kHz)




No.	FREQ [MHz]	READING QP [dBuV]	ANT FACTOR [dB]	LOSS [dB]	GAIN [dB]	RESULT [dBuV/m]	LIMIT [dBuV/m]	MARGIN [dB]	ANTENNA [cm]	TABLE [DEG]
----- Horizontal -----										
1	65.890	31.2	12.6	1.5	32.0	13.3	40.0	26.7	200	359
2	119.240	28.0	18.5	2.0	32.1	16.4	43.5	27.1	100	105
3	457.771	27.7	22.1	3.7	32.3	21.2	46.0	24.8	200	359
4	857.400	27.2	27.3	5.1	32.1	27.5	46.0	18.5	100	0
----- Vertical -----										
5	562.529	33.3	23.8	4.1	32.4	28.8	46.0	17.2	100	0
6	687.655	36.5	25.4	4.6	32.4	34.1	46.0	11.9	100	0

13.5.4 Test data for Intermodulation Mode(WLAN 5 GHz + WLAN 2.4 GHz)

Humidity Level : 45 % R.H. Temperature: 23 °C
Limits apply to : FCC CFR 47, PART 15, SUBPART C, SECTION 15.247
Result : PASSED

EUT : RF Module
Detector : CISPR Quasi-Peak (6 dB Bandwidth: 120 kHz)



No.	FREQ	READING	ANT	LOSS	GAIN	RESULT	LIMIT	MARGIN	ANTENNA	TABLE
	QP		FACTOR			[dBuV/m]	[dBuV/m]	[dB]	[cm]	[DEG]
<hr/>										
-----	Horizontal	-----								
1	119.240	28.0	18.5	2.0	32.1	16.4	43.5	27.1	200	13
2	250.190	28.8	17.8	2.8	32.2	17.2	46.0	28.8	200	78
3	893.289	27.2	27.5	5.3	32.0	28.0	46.0	18.0	200	194
-----	Vertical	-----								
4	65.890	31.5	12.6	1.5	32.0	13.6	40.0	26.4	200	62
5	562.529	34.0	23.8	4.1	32.4	29.5	46.0	16.5	100	358
6	687.655	37.3	25.4	4.6	32.4	34.9	46.0	11.1	100	189

13.6 Test data for Above 1 GHz

13.6.1 Test data for Frequency UNII I

13.6.1.1 Test data for 802.11a RLAN Mode

- Resolution bandwidth : 1 MHz and Peak Detector for Peak Mode for the emissions fall in restricted band,
1 MHz and RMS Detector for Average Mode for the emissions fall in restricted band
100 kHz for Peak Mode for the emissions outside restricted band
- Video bandwidth : 3 MHz for Peak and Average Mode
- Frequency range : 1 GHz ~ 40 GHz
- Measurement distance : 3 m
- Duty Cycle : > 98 %
- Operating mode : Transmitting mode

Frequency (MHz)	Reading (dB μ V)	Detector Mode	Ant. Pol. (H/V)	Ant. Factor	Cable Loss	Duty Factor(dB)	AMP Factor	Total (dB μ V/m)	Limits (dB μ V/m)	Margin (dB)
-----------------	----------------------	---------------	-----------------	-------------	------------	-----------------	------------	----------------------	-----------------------	-------------

Antenna 0

10 360.00	49.27	Peak	H	39.20	11.31	-	46.00	53.78	68.20	14.42
10 360.00	49.10	Peak	V	39.20	11.31	-	46.00	53.61	68.20	14.59
10 440.00	51.50	Peak	H	39.30	11.35	-	46.00	56.15	68.20	12.05
10 440.00	51.18	Peak	V	39.30	11.35	-	46.00	55.83	68.20	12.37
10 480.00	49.05	Peak	H	39.40	11.36	-	46.00	53.81	68.20	14.39
10 480.00	51.08	Peak	V	39.40	11.36	-	46.00	55.84	68.20	12.36

Antenna 1

10 360.00	50.46	Peak	H	39.20	11.31	-	46.00	54.97	68.20	13.23
10 360.00	49.44	Peak	V	39.20	11.31	-	46.00	53.95	68.20	14.25
10 440.00	50.95	Peak	H	39.30	11.35	-	46.00	55.60	68.20	12.60
10 440.00	49.82	Peak	V	39.30	11.35	-	46.00	54.47	68.20	13.73
10 480.00	50.78	Peak	H	39.40	11.36	-	46.00	55.54	68.20	12.66
10 480.00	49.74	Peak	V	39.40	11.36	-	46.00	54.50	68.20	13.70

Remark - "H": Horizontal, "V": Vertical

Margin (dB) = Limits (dB μ V/m) - Emission Level (dB μ V/m)

13.6.1.2 Test data for 802.11n_HT20 RLAN Mode

13.6.1.2.1 Test data for Multiple Transmit

- Resolution bandwidth : 1 MHz and Peak Detector for Peak Mode for the emissions fall in restricted band,
1 MHz and RMS Detector for Average Mode for the emissions fall in restricted band
100 kHz for Peak Mode for the emissions outside restricted band
- Video bandwidth : 3 MHz for Peak and Average Mode
- Frequency range : 1 GHz ~ 40 GHz
- Measurement distance : 3 m
- Duty Cycle : > 98 %
- Operating mode : Transmitting mode

Frequency (MHz)	Reading (dB μ V)	Detector Mode	Ant. Pol. (H/V)	Ant. Factor	Cable Loss	Duty Factor(dB)	AMP Factor	Total (dB μ V/m)	Limits (dB μ V/m)	Margin (dB)
Multiple Transmit										
10 360.00	49.72	Peak	H	39.20	11.31	-	46.00	54.23	68.20	13.97
10 360.00	50.55	Peak	V	39.20	11.31	-	46.00	55.06	68.20	13.14
10 440.00	50.26	Peak	H	39.30	11.35	-	46.00	54.91	68.20	13.29
10 440.00	49.75	Peak	V	39.30	11.35	-	46.00	54.40	68.20	13.80
10 480.00	49.19	Peak	H	39.40	11.36	-	46.00	53.95	68.20	14.25
10 480.00	49.32	Peak	V	39.40	11.36	-	46.00	54.08	68.20	14.12

Remark - "H": Horizontal, "V": Vertical

Margin (dB) = Limits (dB μ V/m) - Emission Level (dB μ V/m)

13.6.1.3 Test data for 802.11n_HT40 RLAN Mode

13.6.1.3.1 Test data for Multiple Transmit

- Resolution bandwidth : 1 MHz and Peak Detector for Peak Mode for the emissions fall in restricted band,
1 MHz and RMS Detector for Average Mode for the emissions fall in restricted band
100 kHz for Peak Mode for the emissions outside restricted band
- Video bandwidth : 3 MHz for Peak and Average Mode
- Frequency range : 1 GHz ~ 40 GHz
- Measurement distance : 3 m
- Duty Cycle : > 98 %
- Operating mode : Transmitting mode

Frequency (MHz)	Reading (dB μ V)	Detector Mode	Ant. Pol. (H/V)	Ant. Factor	Cable Loss	Duty Factor(dB)	AMP Factor	Total (dB μ V/m)	Limits (dB μ V/m)	Margin (dB)
Multiple Transmit										
10 380.00	49.45	Peak	H	39.20	11.31	-	46.00	53.96	68.20	14.24
10 380.00	49.97	Peak	V	39.20	11.31	-	46.00	54.48	68.20	13.72
10 460.00	49.05	Peak	H	39.30	11.36	-	46.00	53.71	68.20	14.49
10 460.00	48.24	Peak	V	39.30	11.36	-	46.00	52.90	68.20	15.30

Remark - "H": Horizontal, "V": Vertical

Margin (dB) = Limits (dB μ V/m) - Emission Level (dB μ V/m)

13.6.1.4 Test data for 802.11ac_HT80 RLAN Mode

13.6.1.4.1 Test data for Multiple Transmit

- Resolution bandwidth : 1 MHz and Peak Detector for Peak Mode for the emissions fall in restricted band,
1 MHz and RMS Detector for Average Mode for the emissions fall in restricted band
100 kHz for Peak Mode for the emissions outside restricted band
- Video bandwidth : 3 MHz for Peak and Average Mode
- Frequency range : 1 GHz ~ 40 GHz
- Measurement distance : 3 m
- Duty Cycle : > 98 %
- Operating mode : Transmitting mode

Frequency (MHz)	Reading (dB μ V)	Detector Mode	Ant. Pol. (H/V)	Ant. Factor	Cable Loss	Duty Factor(dB)	AMP Factor	Total (dB μ V/m)	Limits (dB μ V/m)	Margin (dB)
Multiple Transmit										
10 420.00	51.20	Peak	H	39.30	11.36	-	46.00	55.86	68.20	12.34
10 420.00	51.10	Peak	V	39.30	11.36	-	46.00	55.76	68.20	12.44

Remark - "H": Horizontal, "V": Vertical

Margin (dB) = Limits (dB μ V/m) - Emission Level (dB μ V/m)

13.6.2 Test data for Frequency UNII 2A

13.6.2.1 Test data for 802.11a RLAN Mode

- Resolution bandwidth : 1 MHz and Peak Detector for Peak Mode for the emissions fall in restricted band,
1 MHz and RMS Detector for Average Mode for the emissions fall in restricted band
100 kHz for Peak Mode for the emissions outside restricted band
- Video bandwidth : 3 MHz for Peak and Average Mode
- Frequency range : 1 GHz ~ 40 GHz
- Measurement distance : 3 m
- Duty Cycle : > 98 %
- Operating mode : Transmitting mode

Frequency (MHz)	Reading (dB μ V)	Detector Mode	Ant. Pol. (H/V)	Ant. Factor	Cable Loss	Duty Factor(dB)	AMP Factor	Total (dB μ V/m)	Limits (dB μ V/m)	Margin (dB)
Antenna 0										
10 520.00	47.25	Peak	H	39.40	11.30	-	46.05	51.90	68.20	16.30
10 520.00	49.29	Peak	V	39.40	11.30	-	46.05	53.94	68.20	14.26
10 600.00	49.00	Peak	H	39.40	11.41	-	46.05	53.76	74.00	20.24
10 600.00	38.76	Average	H	39.40	11.41	0.05	46.05	43.57	54.00	10.44
10 600.00	50.25	Peak	V	39.40	11.41	-	46.05	55.01	74.00	18.99
10 600.00	38.87	Average	V	39.40	11.41	0.05	46.05	43.68	54.00	10.33
10 640.00	48.33	Peak	H	39.40	11.43	-	46.05	53.11	74.00	20.89
10 640.00	39.02	Average	H	39.40	11.43	0.05	46.05	43.85	54.00	10.16
10 640.00	49.68	Peak	V	39.40	11.43	-	46.05	54.51	74.00	19.50
10 640.00	39.63	Average	V	39.40	11.43	0.05	46.05	44.41	54.00	9.59

Frequency (MHz)	Reading (dB μ V)	Detector Mode	Ant. Pol. (H/V)	Ant. Factor	Cable Loss	Duty Factor(dB)	AMP Factor	Total (dB μ V/m)	Limits (dB μ V/m)	Margin (dB)
Antenna 1										
10 520.00	48.22	Peak	H	39.40	11.30	-	46.05	52.87	68.20	15.33
10 520.00	48.41	Peak	V	39.40	11.30	-	46.05	53.06	68.20	15.14
10 600.00	49.04	Peak	H	39.40	11.41	-	46.05	53.80	74.00	20.20
10 600.00	39.00	Average	H	39.40	11.41	0.05	46.05	43.81	54.00	10.20
10 600.00	49.16	Peak	V	39.40	11.41	-	46.05	53.92	74.00	20.08
10 600.00	39.06	Average	V	39.40	11.41	0.05	46.05	43.87	54.00	10.14
10 640.00	47.17	Peak	H	39.40	11.43	-	46.05	51.95	74.00	22.05
10 640.00	38.66	Average	H	39.40	11.43	0.05	46.05	43.49	54.00	10.52
10 640.00	48.10	Peak	V	39.40	11.43	-	46.05	52.93	74.00	21.08
10 640.00	38.79	Average	V	39.40	11.43	0.05	46.05	43.57	54.00	10.43

Remark - "H": Horizontal, "V": Vertical

Margin (dB) = Limits (dB μ V/m) - Emission Level (dB μ V/m)

13.6.2.2 Test data for 802.11n_HT20 RLAN Mode

13.6.2.2.1 Test data for Multiple Transmit

- Resolution bandwidth : 1 MHz and Peak Detector for Peak Mode for the emissions fall in restricted band,
1 MHz and RMS Detector for Average Mode for the emissions fall in restricted band
100 kHz for Peak Mode for the emissions outside restricted band
- Video bandwidth : 3 MHz for Peak and Average Mode
- Frequency range : 1 GHz ~ 40 GHz
- Measurement distance : 3 m
- Duty Cycle : > 98 %
- Operating mode : Transmitting mode

Frequency (MHz)	Reading (dB μ V)	Detector Mode	Ant. Pol. (H/V)	Ant. Factor	Cable Loss	Duty Factor(dB)	AMP Factor	Total (dB μ V/m)	Limits (dB μ V/m)	Margin (dB)
Multiple Transmit										
10 520.00	47.91	Peak	H	39.40	11.30	-	46.05	52.56	68.20	15.64
10 520.00	48.35	Peak	V	39.40	11.30	-	46.05	53.00	68.20	15.20
10 600.00	48.63	Peak	H	39.40	11.41	-	46.05	53.39	74.00	20.61
10 600.00	38.84	Average	H	39.40	11.41	0.06	46.05	43.66	54.00	10.35
10 600.00	49.25	Peak	V	39.40	11.41	-	46.05	54.01	74.00	19.99
10 600.00	38.92	Average	V	39.40	11.41	0.06	46.05	43.74	54.00	10.27
10 640.00	48.75	Peak	H	39.40	11.43	-	46.05	53.53	74.00	20.47
10 640.00	39.31	Average	H	39.40	11.43	0.06	46.05	44.15	54.00	9.85
10 640.00	49.06	Peak	V	39.40	11.43	-	46.05	53.84	74.00	20.16
10 640.00	38.79	Average	V	39.40	11.43	0.06	46.05	43.63	54.00	10.38

Remark - "H": Horizontal, "V": Vertical

Margin (dB) = Limits (dB μ V/m) - Emission Level (dB μ V/m)

13.6.2.3 Test data for 802.11n_HT40 RLAN Mode

13.6.2.3.1 Test data for Multiple Transmit

- Resolution bandwidth : 1 MHz and Peak Detector for Peak Mode for the emissions fall in restricted band,
1 MHz and RMS Detector for Average Mode for the emissions fall in restricted band
100 kHz for Peak Mode for the emissions outside restricted band
- Video bandwidth : 3 MHz for Peak and Average Mode
- Frequency range : 1 GHz ~ 40 GHz
- Measurement distance : 3 m
- Duty Cycle : > 98 %
- Operating mode : Transmitting mode

Frequency (MHz)	Reading (dB μ V)	Detector Mode	Ant. Pol. (H/V)	Ant. Factor	Cable Loss	Duty Factor(dB)	AMP Factor	Total (dB μ V/m)	Limits (dB μ V/m)	Margin (dB)
Multiple Transmit										
10 540.00	47.42	Peak	H	39.40	11.30	-	46.05	52.07	68.20	16.13
10 540.00	48.84	Peak	V	39.40	11.30	-	46.05	53.49	68.20	14.71
10 620.00	47.52	Peak	H	39.40	11.43	-	46.05	52.30	74.00	21.70
10 620.00	39.01	Average	H	39.40	11.43	0.12	46.05	43.91	54.00	10.09
10 620.00	48.25	Peak	V	39.40	11.43	-	46.05	53.03	74.00	20.97
10 620.00	38.96	Average	V	39.40	11.43	0.12	46.05	43.86	54.00	10.14

Remark - "H": Horizontal, "V": Vertical

Margin (dB) = Limits (dB μ V/m) - Emission Level (dB μ V/m)

13.6.2.4 Test data for 802.11ac_HT80 RLAN Mode

13.6.2.4.1 Test data for Multiple Transmit

- Resolution bandwidth : 1 MHz and Peak Detector for Peak Mode for the emissions fall in restricted band,
1 MHz and RMS Detector for Average Mode for the emissions fall in restricted band
100 kHz for Peak Mode for the emissions outside restricted band
- Video bandwidth : 3 MHz for Peak and Average Mode
- Frequency range : 1 GHz ~ 40 GHz
- Measurement distance : 3 m
- Duty Cycle : > 98 %
- Operating mode : Transmitting mode

Frequency (MHz)	Reading (dB μ V)	Detector Mode	Ant. Pol. (H/V)	Ant. Factor	Cable Loss	Duty Factor(dB)	AMP Factor	Total (dB μ V/m)	Limits (dB μ V/m)	Margin (dB)
Multiple Transmit										
10 580.00	48.36	Peak	H	39.40	11.41	-	46.05	53.12	68.20	15.08
10 580.00	48.38	Peak	V	39.40	11.41	-	46.05	53.14	68.20	15.06

Remark - "H": Horizontal, "V": Vertical

Margin (dB) = Limits (dB μ V/m) - Emission Level (dB μ V/m)

13.6.3 Test data for Frequency UNII 2C

13.6.3.1 Test data for 802.11a RLAN Mode

- Resolution bandwidth : 1 MHz and Peak Detector for Peak Mode for the emissions fall in restricted band,
1 MHz and RMS Detector for Average Mode for the emissions fall in restricted band
100 kHz for Peak Mode for the emissions outside restricted band
- Video bandwidth : 3 MHz for Peak and Average Mode
- Frequency range : 1 GHz ~ 40 GHz
- Measurement distance : 3 m
- Duty Cycle : > 98 %
- Operating mode : Transmitting mode

Frequency (MHz)	Reading (dB μ V)	Detector Mode	Ant. Pol. (H/V)	Ant. Factor	Cable Loss	Duty Factor(dB)	AMP Factor	Total (dB μ V/m)	Limits (dB μ V/m)	Margin (dB)
Antenna 0										
11 000.00	49.88	Peak	H	39.00	11.85	-	46.50	54.23	74.00	19.77
11 000.00	41.36	Average	H	39.00	11.85	0.05	46.50	45.76	54.00	8.25
11 000.00	49.57	Peak	V	39.00	11.85	-	46.50	53.92	74.00	20.08
11 000.00	40.90	Average	V	39.00	11.85	0.05	46.50	45.30	54.00	8.71
11 160.00	48.76	Peak	H	39.00	12.36	-	46.50	53.62	74.00	20.38
11 160.00	40.27	Average	H	39.00	12.36	0.05	46.50	45.18	54.00	8.82
11 160.00	48.57	Peak	V	39.00	12.36	-	46.50	53.43	74.00	20.57
11 160.00	40.50	Average	V	39.00	12.36	0.05	46.50	45.41	54.00	8.60
11 400.00	50.70	Peak	H	39.00	13.11	-	46.50	56.31	74.00	17.69
11 400.00	40.71	Average	H	39.00	13.11	0.05	46.50	46.37	54.00	7.63
11 400.00	49.47	Peak	V	39.00	13.11	-	46.50	55.08	74.00	18.92
11 400.00	40.76	Average	V	39.00	13.11	0.05	46.50	46.42	54.00	7.59

Frequency (MHz)	Reading (dB μ V)	Detector Mode	Ant. Pol. (H/V)	Ant. Factor	Cable Loss	Duty Factor(dB)	AMP Factor	Total (dB μ V/m)	Limits (dB μ V/m)	Margin (dB)
Antenna 1										
11 000.00	50.16	Peak	H	39.00	11.85	-	46.50	54.51	74.00	19.49
11 000.00	41.04	Average	H	39.00	11.85	0.05	46.50	45.44	54.00	8.57
11 000.00	50.02	Peak	V	39.00	11.85	-	46.50	54.37	74.00	19.63
11 000.00	41.41	Average	V	39.00	11.85	0.05	46.50	45.81	54.00	8.20
11 160.00	49.30	Peak	H	39.00	12.36	-	46.50	54.16	74.00	19.84
11 160.00	40.40	Average	H	39.00	12.36	0.05	46.50	45.31	54.00	8.69
11 160.00	49.00	Peak	V	39.00	12.36	-	46.50	53.86	74.00	20.14
11 160.00	40.06	Average	V	39.00	12.36	0.05	46.50	44.97	54.00	9.04
11 400.00	49.82	Peak	H	39.00	13.11	-	46.50	55.43	74.00	18.57
11 400.00	40.69	Average	H	39.00	13.11	0.05	46.50	46.35	54.00	7.66
11 400.00	49.77	Peak	V	39.00	13.11	-	46.50	55.38	74.00	18.62
11 400.00	40.64	Average	V	39.00	13.11	0.05	46.50	46.30	54.00	7.71

Remark - "H": Horizontal, "V": Vertical

Margin (dB) = Limits (dB μ V/m) - Emission Level (dB μ V/m)

13.6.3.2 Test data for 802.11n_HT20 RLAN Mode

13.6.3.2.1 Test data for Multiple Transmit

- Resolution bandwidth : 1 MHz and Peak Detector for Peak Mode for the emissions fall in restricted band,
1 MHz and RMS Detector for Average Mode for the emissions fall in restricted band
100 kHz for Peak Mode for the emissions outside restricted band
- Video bandwidth : 3 MHz for Peak and Average Mode
- Frequency range : 1 GHz ~ 40 GHz
- Measurement distance : 3 m
- Duty Cycle : > 98 %
- Operating mode : Transmitting mode

Frequency (MHz)	Reading (dB μ V)	Detector Mode	Ant. Pol. (H/V)	Ant. Factor	Cable Loss	Duty Factor(dB)	AMP Factor	Total (dB μ V/m)	Limits (dB μ V/m)	Margin (dB)
Multiple Transmit										
11 000.00	50.52	Peak	H	39.00	11.85	-	46.50	54.87	74.00	19.13
11 000.00	42.36	Average	H	39.00	11.85	0.06	46.50	46.77	54.00	7.24
11 000.00	49.72	Peak	V	39.00	11.85	-	46.50	54.07	74.00	19.93
11 000.00	41.28	Average	V	39.00	11.85	0.06	46.50	45.69	54.00	8.32
11 160.00	49.41	Peak	H	39.00	12.36	-	46.50	54.27	74.00	19.73
11 160.00	40.73	Average	H	39.00	12.36	0.06	46.50	45.65	54.00	8.36
11 160.00	49.60	Peak	V	39.00	12.36	-	46.50	54.46	74.00	19.54
11 160.00	40.38	Average	V	39.00	12.36	0.06	46.50	45.30	54.00	8.71
11 400.00	50.98	Peak	H	39.00	13.11	-	46.50	56.59	74.00	17.41
11 400.00	41.35	Average	H	39.00	13.11	0.06	46.50	47.02	54.00	6.99
11 400.00	50.87	Peak	V	39.00	13.11	-	46.50	56.48	74.00	17.52
11 400.00	41.43	Average	V	39.00	13.11	0.06	46.50	47.10	54.00	6.90

Remark - "H": Horizontal, "V": Vertical

Margin (dB) = Limits (dB μ V/m) - Emission Level (dB μ V/m)

13.6.3.3 Test data for 802.11n_HT40 RLAN Mode

13.6.3.3.1 Test data for Multiple Transmit

- Resolution bandwidth : 1 MHz and Peak Detector for Peak Mode for the emissions fall in restricted band,
1 MHz and RMS Detector for Average Mode for the emissions fall in restricted band
100 kHz for Peak Mode for the emissions outside restricted band
- Video bandwidth : 3 MHz for Peak and Average Mode
- Frequency range : 1 GHz ~ 40 GHz
- Measurement distance : 3 m
- Duty Cycle : > 98 %
- Operating mode : Transmitting mode

Frequency (MHz)	Reading (dB μ V)	Detector Mode	Ant. Pol. (H/V)	Ant. Factor	Cable Loss	Duty Factor(dB)	AMP Factor	Total (dB μ V/m)	Limits (dB μ V/m)	Margin (dB)
Multiple Transmit										
11 020.00	50.52	Peak	H	39.00	11.85	-	46.50	54.87	74.00	19.13
11 020.00	41.18	Average	H	39.00	11.85	0.12	46.50	45.65	54.00	8.35
11 020.00	49.79	Peak	V	39.00	11.85	-	46.50	54.14	74.00	19.86
11 020.00	41.26	Average	V	39.00	11.85	0.12	46.50	45.73	54.00	8.27
11 100.00	49.70	Peak	H	39.00	12.36	-	46.50	54.56	74.00	19.44
11 100.00	40.50	Average	H	39.00	12.36	0.12	46.50	45.48	54.00	8.52
11 100.00	50.50	Peak	V	39.00	12.36	-	46.50	55.36	74.00	18.64
11 100.00	40.51	Average	V	39.00	12.36	0.12	46.50	45.49	54.00	8.51
11 340.00	48.92	Peak	H	39.00	13.11	-	46.50	54.53	74.00	19.47
11 340.00	39.99	Average	H	39.00	13.11	0.12	46.50	45.72	54.00	8.28
11 340.00	49.37	Peak	V	39.00	13.11	-	46.50	54.98	74.00	19.02
11 340.00	40.34	Average	V	39.00	13.11	0.12	46.50	46.07	54.00	7.93

Remark - "H": Horizontal, "V": Vertical

Margin (dB) = Limits (dB μ V/m) - Emission Level (dB μ V/m)

13.6.3.4 Test data for 802.11ac_VHT80 RLAN Mode

13.6.3.4.1 Test data for Multiple Transmit

- Resolution bandwidth : 1 MHz and Peak Detector for Peak Mode for the emissions fall in restricted band,
1 MHz and RMS Detector for Average Mode for the emissions fall in restricted band
100 kHz for Peak Mode for the emissions outside restricted band
- Video bandwidth : 3 MHz for Peak and Average Mode
- Frequency range : 1 GHz ~ 40 GHz
- Measurement distance : 3 m
- Duty Cycle : > 98 %
- Operating mode : Transmitting mode

Frequency (MHz)	Reading (dB μ V)	Detector Mode	Ant. Pol. (H/V)	Ant. Factor	Cable Loss	Duty Factor(dB)	AMP Factor	Total (dB μ V/m)	Limits (dB μ V/m)	Margin (dB)
Multiple Transmit										
11 060.00	50.00	Peak	H	39.00	11.85	-	46.50	54.35	74.00	19.65
11 060.00	40.84	Average	H	39.00	11.85	0.20	46.50	45.39	54.00	8.61
11 060.00	49.22	Peak	V	39.00	11.85	-	46.50	53.57	74.00	20.43
11 060.00	40.79	Average	V	39.00	11.85	0.20	46.50	45.34	54.00	8.66

Remark - "H": Horizontal, "V": Vertical

Margin (dB) = Limits (dB μ V/m) - Emission Level (dB μ V/m)

13.6.4 Test data for Frequency UNII 3

13.6.4.1 Test data for 802.11a RLAN Mode

- Resolution bandwidth : 1 MHz and Peak Detector for Peak Mode for the emissions fall in restricted band,
1 MHz and RMS Detector for Average Mode for the emissions fall in restricted band
100 kHz for Peak Mode for the emissions outside restricted band
- Video bandwidth : 3 MHz for Peak and Average Mode
- Frequency range : 1 GHz ~ 40 GHz
- Measurement distance : 3 m
- Duty Cycle : > 98 %
- Operating mode : Transmitting mode

Frequency (MHz)	Reading (dB μ V)	Detector Mode	Ant. Pol. (H/V)	Ant. Factor	Cable Loss	Duty Factor(dB)	AMP Factor	Total (dB μ V/m)	Limits (dB μ V/m)	Margin (dB)
Antenna 0										
11 490.00	48.86	Peak	H	39.30	13.11	-	46.35	54.92	74.00	19.08
11 490.00	40.56	Average	H	39.30	13.11	0.05	46.35	46.67	54.00	7.34
11 490.00	49.39	Peak	V	39.30	13.11	-	46.35	55.45	74.00	18.55
11 490.00	40.60	Average	V	39.30	13.11	0.05	46.35	46.71	54.00	7.29
11 570.00	50.84	Peak	H	39.40	13.15	-	46.35	57.04	74.00	16.96
11 570.00	40.48	Average	H	39.40	13.15	0.05	46.35	46.73	54.00	7.28
11 570.00	49.44	Peak	V	39.40	13.15	-	46.35	55.64	74.00	18.36
11 570.00	40.36	Average	V	39.40	13.15	0.05	46.35	46.61	54.00	7.40
11 650.00	49.13	Peak	H	39.70	13.19	-	46.35	55.67	74.00	18.33
11 650.00	39.99	Average	H	39.70	13.19	0.05	46.35	46.58	54.00	7.43
11 650.00	49.81	Peak	V	39.70	13.19	-	46.35	56.35	74.00	17.65
11 650.00	40.33	Average	V	39.70	13.19	0.05	46.35	46.92	54.00	7.09

Frequency (MHz)	Reading (dB μ V)	Detector Mode	Ant. Pol. (H/V)	Ant. Factor	Cable Loss	Duty Factor(dB)	AMP Factor	Total (dB μ V/m)	Limits (dB μ V/m)	Margin (dB)
Antenna 1										
11 490.00	49.13	Peak	H	39.30	13.11	-	46.35	55.19	74.00	18.81
11 490.00	40.47	Average	H	39.30	13.11	0.05	46.35	46.58	54.00	7.43
11 490.00	49.11	Peak	V	39.30	13.11	-	46.35	55.17	74.00	18.83
11 490.00	40.41	Average	V	39.30	13.11	0.05	46.35	46.52	54.00	7.49
11 570.00	49.16	Peak	H	39.40	13.15	-	46.35	55.36	74.00	18.64
11 570.00	40.53	Average	H	39.40	13.15	0.05	46.35	46.78	54.00	7.22
11 570.00	50.23	Peak	V	39.40	13.15	-	46.35	56.43	74.00	17.57
11 570.00	40.69	Average	V	39.40	13.15	0.05	46.35	46.94	54.00	7.06
11 650.00	49.47	Peak	H	39.70	13.19	-	46.35	56.01	74.00	17.99
11 650.00	40.12	Average	H	39.70	13.19	0.05	46.35	46.71	54.00	7.30
11 650.00	49.72	Peak	V	39.70	13.19	-	46.35	56.26	74.00	17.74
11 650.00	40.48	Average	V	39.70	13.19	0.05	46.35	47.07	54.00	6.94

Remark - "H": Horizontal, "V": Vertical

Margin (dB) = Limits (dB μ V/m) - Emission Level (dB μ V/m)

13.6.4.2 Test data for 802.11n_HT20 RLAN Mode

13.6.4.2.1 Test data for Test data for Multiple Transmit

- Resolution bandwidth : 1 MHz and Peak Detector for Peak Mode for the emissions fall in restricted band,
1 MHz and RMS Detector for Average Mode for the emissions fall in restricted band
100 kHz for Peak Mode for the emissions outside restricted band
- Video bandwidth : 3 MHz for Peak and Average Mode
- Frequency range : 1 GHz ~ 40 GHz
- Measurement distance : 3 m
- Duty Cycle : > 98 %
- Operating mode : Transmitting mode

Frequency (MHz)	Reading (dB μ V)	Detector Mode	Ant. Pol. (H/V)	Ant. Factor	Cable Loss	Duty Factor(dB)	AMP Factor	Total (dB μ V/m)	Limits (dB μ V/m)	Margin (dB)
Multiple Transmit										
11 490.00	48.49	Peak	H	39.30	13.11	-	46.35	54.55	74.00	19.45
11 490.00	40.55	Average	H	39.30	13.11	0.06	46.35	46.67	54.00	7.34
11 490.00	49.61	Peak	V	39.30	13.11	-	46.35	55.67	74.00	18.33
11 490.00	40.68	Average	V	39.30	13.11	0.06	46.35	46.80	54.00	7.21
11 570.00	50.63	Peak	H	39.40	13.15	-	46.35	56.83	74.00	17.17
11 570.00	40.90	Average	H	39.40	13.15	0.06	46.35	47.16	54.00	6.85
11 570.00	49.05	Peak	V	39.40	13.15	-	46.35	55.25	74.00	18.75
11 570.00	40.72	Average	V	39.40	13.15	0.06	46.35	46.98	54.00	7.02
11 650.00	49.46	Peak	H	39.70	13.19	-	46.35	56.00	74.00	18.00
11 650.00	40.47	Average	H	39.70	13.19	0.06	46.35	47.07	54.00	6.94
11 650.00	49.20	Peak	V	39.70	13.19	-	46.35	55.74	74.00	18.26
11 650.00	40.43	Average	V	39.70	13.19	0.06	46.35	47.03	54.00	6.98

Remark - "H": Horizontal, "V": Vertical

Margin (dB) = Limits (dB μ V/m) - Emission Level (dB μ V/m)

13.6.4.3 Test data for 802.11n_HT40 RLAN Mode

13.6.4.3.1 Test data for Multiple Transmit

- Resolution bandwidth : 1 MHz and Peak Detector for Peak Mode for the emissions fall in restricted band,
1 MHz and RMS Detector for Average Mode for the emissions fall in restricted band
100 kHz for Peak Mode for the emissions outside restricted band
- Video bandwidth : 3 MHz for Peak and Average Mode
- Frequency range : 1 GHz ~ 40 GHz
- Measurement distance : 3 m
- Duty Cycle : > 98 %
- Operating mode : Transmitting mode

Frequency (MHz)	Reading (dB μ V)	Detector Mode	Ant. Pol. (H/V)	Ant. Factor	Cable Loss	Duty Factor(dB)	AMP Factor	Total (dB μ V/m)	Limits (dB μ V/m)	Margin (dB)
Multiple Transmit										
11 510.00	50.15	Peak	H	39.30	13.11	-	46.35	56.21	74.00	17.79
11 510.00	40.30	Average	H	39.30	13.11	0.12	46.35	46.48	54.00	7.52
11 510.00	49.32	Peak	V	39.30	13.11	-	46.35	55.38	74.00	18.62
11 510.00	40.45	Average	V	39.30	13.11	0.12	46.35	46.63	54.00	7.37
11 590.00	49.26	Peak	H	39.40	13.15	-	46.35	55.46	74.00	18.54
11 590.00	40.22	Average	H	39.40	13.15	0.12	46.35	46.54	54.00	7.46
11 590.00	49.04	Peak	V	39.40	13.15	-	46.35	55.24	74.00	18.76
11 590.00	40.11	Average	V	39.40	13.15	0.12	46.35	46.43	54.00	7.57

Remark - "H": Horizontal, "V": Vertical

Margin (dB) = Limits (dB μ V/m) - Emission Level (dB μ V/m)

13.6.4.4 Test data for 802.11ac_VHT80 RLAN Mode

13.6.4.4.1 Test data for Multiple Transmit

- Resolution bandwidth : 1 MHz and Peak Detector for Peak Mode for the emissions fall in restricted band,
1 MHz and RMS Detector for Average Mode for the emissions fall in restricted band
100 kHz for Peak Mode for the emissions outside restricted band
- Video bandwidth : 3 MHz for Peak and Average Mode
- Frequency range : 1 GHz ~ 40 GHz
- Measurement distance : 3 m
- Duty Cycle : > 98 %
- Operating mode : Transmitting mode

Frequency (MHz)	Reading (dB μ V)	Detector Mode	Ant. Pol. (H/V)	Ant. Factor	Cable Loss	Duty Factor(dB)	AMP Factor	Total (dB μ V/m)	Limits (dB μ V/m)	Margin (dB)
Multiple Transmit										
11550.00	49.01	Peak	H	39.40	13.15	-	46.50	55.06	74.00	18.94
11550.00	39.82	Average	H	39.40	13.15	0.20	46.50	46.07	54.00	7.93
11550.00	49.30	Peak	V	39.40	13.15	-	46.50	55.35	74.00	18.65
11550.00	39.69	Average	V	39.40	13.15	0.20	46.50	45.94	54.00	8.06

Remark - "H": Horizontal, "V": Vertical

Margin (dB) = Limits (dB μ V/m) - Emission Level (dB μ V/m)

14. RADIATED RESTRICTED BAND EDGE MEASUREMENTS

14.1 Operating environment


Temperature : 23 °C

Relative humidity : 45 % R.H.

14.2 Test set-up for conducted measurement

The radiated emissions measurements were performed on the 3 m, open-field test site. The EUT was placed on a non-conductive turntable above the ground plane.

The system was rotated 360°, and the antenna was varied in the height between 1.0 m and 4.0 m in order to determine the maximum emission levels. This procedure was performed for horizontal and vertical polarization of the receiving antenna.



14.3 Test Date

December 05, 2021 ~ March 08, 2022

14.4 Test data for Frequency UNII I

14.4.1 Test data for 802.11a RLAN Mode

- Resolution bandwidth : 1 MHz and Peak Detector for Peak Mode
1 MHz and RMS Detector for Average Mode
- Video bandwidth : 3 MHz for Peak and Average Mode
- Measurement distance : 3 m
- Duty Cycle : > 98 %
- Result : Pass

Frequency (MHz)	Reading (dB μ V)	Detector Mode	Ant. Pol. (H/V)	Ant. Factor	Cable Loss	Duty Factor(dB)	AMP Factor	ATT Factor	Total (dB μ V/m)	Limits (dB μ V/m)	Margin (dB)
Antenna 0											
5 149.770	57.38	Peak	H	34.20	8.21	-	45.03	6.16	60.92	74.00	13.08
5 149.091	44.98	Average	H	34.20	8.21	0.05	45.03	6.16	48.57	54.00	5.43
5 147.732	59.77	Peak	V	34.20	8.21	-	45.03	6.16	63.31	74.00	10.69
5 149.770	45.15	Average	V	34.20	8.21	0.05	45.03	6.16	48.74	54.00	5.27
Antenna 1											
5 139.580	54.30	Peak	H	34.20	8.21	-	45.03	6.16	57.84	74.00	16.16
5 146.374	44.33	Average	H	34.20	8.21	0.05	45.03	6.16	47.92	54.00	6.08
4 979.940	53.75	Peak	V	34.20	8.21	-	45.03	6.16	57.29	74.00	16.71
5 149.770	44.43	Average	V	34.20	8.21	0.05	45.03	6.16	48.02	54.00	5.99

Tabulated test data for Restricted Band

Remark - "H": Horizontal, "V": Vertical

Margin (dB) = Limits (dB μ V/m) - Emission Level (dB μ V/m)

14.4.2 Test data for 802.11n_HT20 RLAN Mode

- Resolution bandwidth : 1 MHz and Peak Detector for Peak Mode
1 MHz and RMS Detector for Average Mode
- Video bandwidth : 3 MHz for Peak and Average Mode
- Measurement distance : 3 m
- Duty Cycle : > 98 %
- Result : Pass

Frequency (MHz)	Reading (dB μ V)	Detector Mode	Ant. Pol. (H/V)	Ant. Factor	Cable Loss	Duty Factor(dB)	AMP Factor	ATT Factor	Total (dB μ V/m)	Limits (dB μ V/m)	Margin (dB)
Multiple Transmit											
5 149.770	62.12	Peak	H	34.20	8.21	-	45.03	6.16	65.66	74.00	8.34
5 120.559	45.89	Average	H	34.20	8.21	0.06	45.03	6.16	49.49	54.00	4.51
5 149.770	62.76	Peak	V	34.20	8.21	-	45.03	6.16	66.30	74.00	7.70
5 146.374	45.56	Average	V	34.20	8.21	0.06	45.03	6.16	49.16	54.00	4.85

Tabulated test data for Restricted Band

Remark - "H": Horizontal, "V": Vertical

Margin (dB) = Limits (dB μ V/m) - Emission Level (dB μ V/m)

14.4.3 Test data for 802.11n_HT40 RLAN Mode

- Resolution bandwidth : 1 MHz and Peak Detector for Peak Mode
1 MHz and RMS Detector for Average Mode
- Video bandwidth : 3 MHz for Peak and Average Mode
- Measurement distance : 3 m
- Duty Cycle : > 98 %
- Result : Pass

Frequency (MHz)	Reading (dB μ V)	Detector Mode	Ant. Pol. (H/V)	Ant. Factor	Cable Loss	Duty Factor(dB)	AMP Factor	ATT Factor	Total (dB μ V/m)	Limits (dB μ V/m)	Margin (dB)
Multiple Transmit											
5 144.336	61.18	Peak	H	34.20	8.21	-	45.03	6.16	64.72	74.00	9.28
5 148.412	48.53	Average	H	34.20	8.21	0.12	45.03	6.16	52.19	54.00	1.81
5 147.732	61.01	Peak	V	34.20	8.21	-	45.03	6.16	64.55	74.00	9.45
5 149.091	48.42	Average	V	34.20	8.21	0.12	45.03	6.16	52.08	54.00	1.92

Tabulated test data for Restricted Band

Remark - "H": Horizontal, "V": Vertical

Margin (dB) = Limits (dB μ V/m) - Emission Level (dB μ V/m)

14.4.4 Test data for 802.11ac_VHT80 RLAN Mode

- Resolution bandwidth : 1 MHz and Peak Detector for Peak Mode
1 MHz and RMS Detector for Average Mode
- Video bandwidth : 3 MHz for Peak and Average Mode
- Measurement distance : 3 m
- Duty Cycle : > 98 %
- Result : Pass

Frequency (MHz)	Reading (dB μ V)	Detector Mode	Ant. Pol. (H/V)	Ant. Factor	Cable Loss	Duty Factor(dB)	AMP Factor	ATT Factor	Total (dB μ V/m)	Limits (dB μ V/m)	Margin (dB)
Multiple Transmit											
5 149.091	58.28	Peak	H	34.20	8.21	-	45.03	6.16	61.82	74.00	12.18
5 148.412	48.76	Average	H	34.20	8.21	0.20	45.03	6.16	52.50	54.00	1.50
5 147.053	60.79	Peak	V	34.20	8.21	-	45.03	6.16	64.33	74.00	9.67
5 148.412	48.86	Average	V	34.20	8.21	0.20	45.03	6.16	52.60	54.00	1.40

Tabulated test data for Restricted Band

Remark - "H": Horizontal, "V": Vertical

Margin (dB) = Limits (dB μ V/m) - Emission Level (dB μ V/m)

14.5 Test data for Frequency UNII 2A

14.5.1 Test data for 802.11a RLAN Mode

- Resolution bandwidth : 1 MHz and Peak Detector for Peak Mode
1 MHz and RMS Detector for Average Mode
- Video bandwidth : 3 MHz for Peak and Average Mode
- Measurement distance : 3 m
- Duty Cycle : > 98 %
- Result : Pass

Frequency (MHz)	Reading (dB μ V)	Detector Mode	Ant. Pol. (H/V)	Ant. Factor	Cable Loss	Duty Factor(dB)	AMP Factor	ATT Factor	Total (dB μ V/m)	Limits (dB μ V/m)	Margin (dB)
Antenna 0											
5 350.839	61.91	Peak	H	34.10	8.58	-	45.21	6.16	65.54	74.00	8.46
5 350.839	45.48	Average	H	34.10	8.58	0.05	45.21	6.16	49.16	54.00	4.85
5 350.140	62.74	Peak	V	34.10	8.58	-	45.21	6.16	66.37	74.00	7.63
5 350.280	45.49	Average	V	34.10	8.58	0.05	45.21	6.16	49.17	54.00	4.83
Antenna 1											
5 350.280	62.80	Peak	H	34.10	8.58	-	45.21	6.16	66.43	74.00	7.57
5 350.559	45.30	Average	H	34.10	8.58	0.05	45.21	6.16	48.98	54.00	5.02
5 350.420	61.55	Peak	V	34.10	8.58	-	45.21	6.16	65.18	74.00	8.82
5 351.538	45.28	Average	V	34.10	8.58	0.05	45.21	6.16	48.96	54.00	5.05

Tabulated test data for Restricted Band

Remark - "H": Horizontal, "V": Vertical

Margin (dB) = Limits (dB μ V/m) - Emission Level (dB μ V/m)

14.5.2 Test data for 802.11n_HT20 RLAN Mode

- Resolution bandwidth : 1 MHz and Peak Detector for Peak Mode
1 MHz and RMS Detector for Average Mode
- Video bandwidth : 3 MHz for Peak and Average Mode
- Measurement distance : 3 m
- Duty Cycle : > 98 %
- Result : Pass

Frequency (MHz)	Reading (dB μ V)	Detector Mode	Ant. Pol. (H/V)	Ant. Factor	Cable Loss	Duty Factor(dB)	AMP Factor	ATT Factor	Total (dB μ V/m)	Limits (dB μ V/m)	Margin (dB)
Multiple Transmit											
5 351.259	63.30	Peak	H	34.10	8.58	-	45.21	6.16	66.93	74.00	7.07
5 350.140	46.04	Average	H	34.10	8.58	0.06	45.21	6.16	49.73	54.00	4.28
5 351.259	63.14	Peak	V	34.10	8.58	-	45.21	6.16	66.77	74.00	7.23
5 350.699	46.35	Average	V	34.10	8.58	0.06	45.21	6.16	50.04	54.00	3.97

Tabulated test data for Restricted Band

Remark - "H": Horizontal, "V": Vertical

Margin (dB) = Limits (dB μ V/m) - Emission Level (dB μ V/m)

14.5.3 Test data for 802.11n_HT40 RLAN Mode

- Resolution bandwidth : 1 MHz and Peak Detector for Peak Mode
1 MHz and RMS Detector for Average Mode
- Video bandwidth : 3 MHz for Peak and Average Mode
- Measurement distance : 3 m
- Duty Cycle : > 98 %
- Result : Pass

Frequency (MHz)	Reading (dB μ V)	Detector Mode	Ant. Pol. (H/V)	Ant. Factor	Cable Loss	Duty Factor(dB)	AMP Factor	ATT Factor	Total (dB μ V/m)	Limits (dB μ V/m)	Margin (dB)
Multiple Transmit											
5 351.958	64.90	Peak	H	34.10	8.58	-	45.21	6.16	68.53	74.00	5.47
5 352.098	48.04	Average	H	34.10	8.58	0.12	45.21	6.16	51.79	54.00	2.21
5 350.420	63.45	Peak	V	34.10	8.58	-	45.21	6.16	67.08	74.00	6.92
5 353.497	47.83	Average	V	34.10	8.58	0.12	45.21	6.16	51.58	54.00	2.42

Tabulated test data for Restricted Band

Remark - "H": Horizontal, "V": Vertical

Margin (dB) = Limits (dB μ V/m) - Emission Level (dB μ V/m)

14.5.4 Test data for 802.11ac_VHT80 RLAN Mode

- Resolution bandwidth : 1 MHz and Peak Detector for Peak Mode
1 MHz and RMS Detector for Average Mode
- Video bandwidth : 3 MHz for Peak and Average Mode
- Measurement distance : 3 m
- Duty Cycle : > 98 %
- Result : Pass

Frequency (MHz)	Reading (dB μ V)	Detector Mode	Ant. Pol. (H/V)	Ant. Factor	Cable Loss	Duty Factor(dB)	AMP Factor	ATT Factor	Total (dB μ V/m)	Limits (dB μ V/m)	Margin (dB)
Multiple Transmit											
5 358.392	58.15	Peak	H	34.10	8.58	-	45.21	6.16	61.78	74.00	12.22
5 353.217	46.95	Average	H	34.10	8.58	0.20	45.21	6.16	50.78	54.00	3.22
5 353.077	57.96	Peak	V	34.10	8.58	-	45.21	6.16	61.59	74.00	12.41
5 352.517	47.12	Average	V	34.10	8.58	0.20	45.21	6.16	50.95	54.00	3.05

Tabulated test data for Restricted Band

Remark - "H": Horizontal, "V": Vertical

Margin (dB) = Limits (dB μ V/m) - Emission Level (dB μ V/m)

14.6 Test data for Frequency UNII 2C

14.6.1 Test data for 802.11a RLAN Mode

- Resolution bandwidth : 1 MHz and Peak Detector for Peak Mode
1 MHz and RMS Detector for Average Mode
- Video bandwidth : 3 MHz for Peak and Average Mode
- Measurement distance : 3 m
- Duty Cycle : > 98 %
- Result : Pass

Frequency (MHz)	Reading (dB μ V)	Detector Mode	Ant. Pol. (H/V)	Ant. Factor	Cable Loss	Duty Factor(dB)	AMP Factor	ATT Factor	Total (dB μ V/m)	Limits (dB μ V/m)	Margin (dB)
Antenna 0											
5 459.016	56.75	Peak	H	34.10	8.58	-	45.21	6.16	60.38	74.00	13.62
5 449.575	44.11	Average	H	34.10	8.58	0.05	45.21	6.16	47.79	54.00	6.21
5 456.169	55.81	Peak	V	34.10	8.58	-	45.21	6.16	59.44	74.00	14.56
5 446.728	44.22	Average	V	34.10	8.58	0.05	45.21	6.16	47.90	54.00	6.11
Antenna 1											
5 460.000	56.17	Peak	H	34.10	8.58	-	45.21	6.16	59.80	74.00	14.20
5 451.973	44.04	Average	H	34.10	8.58	0.05	45.21	6.16	47.72	54.00	6.29
5 451.673	56.31	Peak	V	34.10	8.58	-	45.21	6.16	59.94	74.00	14.06
5 459.765	44.29	Average	V	34.10	8.58	0.05	45.21	6.16	47.97	54.00	6.04

Tabulated test data for Restricted Band

Remark - "H": Horizontal, "V": Vertical

Margin (dB) = Limits (dB μ V/m) - Emission Level (dB μ V/m)

14.6.2 Test data for 802.11n_HT20 RLAN Mode

- Resolution bandwidth : 1 MHz and Peak Detector for Peak Mode
1 MHz and RMS Detector for Average Mode
- Video bandwidth : 3 MHz for Peak and Average Mode
- Measurement distance : 3 m
- Duty Cycle : > 98 %
- Result : Pass

Frequency (MHz)	Reading (dB μ V)	Detector Mode	Ant. Pol. (H/V)	Ant. Factor	Cable Loss	Duty Factor(dB)	AMP Factor	ATT Factor	Total (dB μ V/m)	Limits (dB μ V/m)	Margin (dB)
Multiple Transmit											
5 459.615	58.26	Peak	H	34.10	8.58	-	45.21	6.16	61.89	74.00	12.11
5 459.615	44.54	Average	H	34.10	8.58	0.06	45.21	6.16	48.23	54.00	5.78
5 456.319	57.47	Peak	V	34.10	8.58	-	45.21	6.16	61.10	74.00	12.90
5 460.000	44.21	Average	V	34.10	8.58	0.06	45.21	6.16	47.90	54.00	6.11

Tabulated test data for Restricted Band

Remark - "H": Horizontal, "V": Vertical

Margin (dB) = Limits (dB μ V/m) - Emission Level (dB μ V/m)

14.6.3 Test data for 802.11n_HT40 RLAN Mode

- Resolution bandwidth : 1 MHz and Peak Detector for Peak Mode
1 MHz and RMS Detector for Average Mode
- Video bandwidth : 3 MHz for Peak and Average Mode
- Measurement distance : 3 m
- Duty Cycle : > 98 %
- Result : Pass

Frequency (MHz)	Reading (dB μ V)	Detector Mode	Ant. Pol. (H/V)	Ant. Factor	Cable Loss	Duty Factor(dB)	AMP Factor	ATT Factor	Total (dB μ V/m)	Limits (dB μ V/m)	Margin (dB)
Multiple Transmit											
5 459.915	58.29	Peak	H	34.10	8.58	-	45.21	6.16	61.92	74.00	12.08
5 459.615	45.56	Average	H	34.10	8.58	0.12	45.21	6.16	49.31	54.00	4.69
5 451.523	58.02	Peak	V	34.10	8.58	-	45.21	6.16	61.65	74.00	12.35
5 459.765	45.22	Average	V	34.10	8.58	0.12	45.21	6.16	48.97	54.00	5.03

Tabulated test data for Restricted Band

Remark - "H": Horizontal, "V": Vertical

Margin (dB) = Limits (dB μ V/m) - Emission Level (dB μ V/m)

14.6.4 Test data for 802.11ac_VHT80 RLAN Mode

- Resolution bandwidth : 1 MHz and Peak Detector for Peak Mode
1 MHz and RMS Detector for Average Mode
- Video bandwidth : 3 MHz for Peak and Average Mode
- Measurement distance : 3 m
- Duty Cycle : > 98 %
- Result : Pass

Frequency (MHz)	Reading (dB μ V)	Detector Mode	Ant. Pol. (H/V)	Ant. Factor	Cable Loss	Duty Factor(dB)	AMP Factor	ATT Factor	Total (dB μ V/m)	Limits (dB μ V/m)	Margin (dB)
Multiple Transmit											
5 458.117	59.86	Peak	H	34.10	8.58	-	45.21	6.16	63.49	74.00	10.51
5 457.817	47.07	Average	H	34.10	8.58	0.20	45.21	6.16	50.90	54.00	3.10
5 453.322	58.17	Peak	V	34.10	8.58	-	45.21	6.16	61.80	74.00	12.20
5 458.417	47.01	Average	V	34.10	8.58	0.20	45.21	6.16	50.84	54.00	3.16

Tabulated test data for Restricted Band

Remark - "H": Horizontal, "V": Vertical

Margin (dB) = Limits (dB μ V/m) - Emission Level (dB μ V/m)

14.7 Test data for Frequency U-NII-3

14.7.1 Test data for 802.11a RLAN Mode

- Resolution bandwidth : 1 MHz and Peak Detector for Peak Mode
1 MHz and RMS Detector for Average Mode
- Video bandwidth : 3 MHz for Peak and Average Mode
- Measurement distance : 3 m
- Duty Cycle : > 98 %
- Result : Pass

Frequency (MHz)	Reading (dB μ V)	Detector Mode	Ant. Pol. (H/V)	Ant. Factor	Cable Loss	DUTY Factor	AMP Factor	ATT Factor	Total (dB μ V/m)	Limits (dB μ V/m)	Margin (dB)
Low Channel (Antenna 0)											
5 672.650	52.12	Peak	H	34.10	8.71	-	45.31	6.15	55.77	84.96	29.19
5 718.170	51.49	Peak	H	34.10	8.71	-	45.31	6.15	55.14	110.29	55.15
5 724.830	50.62	Peak	H	34.10	8.71	-	45.31	6.15	54.27	121.81	67.54
5 851.400	52.66	Peak	H	34.40	8.91	-	45.19	6.14	56.92	119.01	62.09
5 871.910	52.69	Peak	H	34.40	8.91	-	45.19	6.14	56.95	106.07	49.12
5 891.910	52.94	Peak	H	34.40	8.91	-	45.19	6.14	57.20	92.69	35.49
5 684.940	52.29	Peak	V	34.10	8.71	-	45.31	6.15	55.94	94.06	38.12
5 711.680	53.03	Peak	V	34.10	8.71	-	45.31	6.15	56.68	108.47	51.79
5 723.780	52.82	Peak	V	34.10	8.71	-	45.31	6.15	56.47	119.42	62.95
5 855.000	51.77	Peak	V	34.40	8.91	-	45.19	6.14	56.03	110.80	54.77
5 867.960	52.70	Peak	V	34.40	8.91	-	45.19	6.14	56.96	107.17	50.21
5 881.770	53.79	Peak	V	34.40	8.91	-	45.19	6.14	58.05	100.19	42.14

Tabulated test data for Restricted Band

Remark - "H": Horizontal, "V": Vertical

Margin (dB) = Limits (dB μ V/m) - Emission Level (dB μ V/m)

Frequency (MHz)	Reading (dB μ V)	Detector Mode	Ant. Pol. (H/V)	Ant. Factor	Cable Loss	DUTY Factor	AMP Factor	ATT Factor	Total (dB μ V/m)	Limits (dB μ V/m)	Margin (dB)
High Channel (Antenna 0)											
5 681.090	52.17	Peak	H	34.10	8.71	-	45.31	6.15	55.82	91.21	35.39
5 714.580	51.26	Peak	H	34.10	8.71	-	45.31	6.15	54.91	109.28	54.37
5 722.840	51.85	Peak	H	34.10	8.71	-	45.31	6.15	55.50	117.28	61.78
5 852.570	53.37	Peak	H	34.40	8.91	-	45.19	6.14	57.63	116.34	58.71
5 870.470	52.28	Peak	H	34.40	8.91	-	45.19	6.14	56.54	106.47	49.93
5 909.840	53.14	Peak	H	34.40	8.91	-	45.19	6.14	57.40	79.42	22.02
5 674.050	51.79	Peak	V	34.10	8.71	-	45.31	6.15	55.44	86.00	30.56
5 718.130	53.10	Peak	V	34.10	8.71	-	45.31	6.15	56.75	110.28	53.53
5 723.790	52.33	Peak	V	34.10	8.71	-	45.31	6.15	55.98	119.44	63.46
5 851.620	53.54	Peak	V	34.40	8.91	-	45.19	6.14	57.80	118.51	60.71
5 860.700	52.91	Peak	V	34.40	8.91	-	45.19	6.14	57.17	109.20	52.03
5 892.410	53.05	Peak	V	34.40	8.91	-	45.19	6.14	57.31	92.32	35.01

Tabulated test data for Restricted Band

Remark - "H": Horizontal, "V": Vertical

Margin (dB) = Limits (dB μ V/m) - Emission Level (dB μ V/m)

Tabulated test data for Restricted Band

Frequency (MHz)	Reading (dB μ V)	Detector Mode	Ant. Pol. (H/V)	Ant. Factor	Cable Loss	DUTY Factor	AMP Factor	ATT Factor	Total (dB μ V/m)	Limits (dB μ V/m)	Margin (dB)
Low Channel (Antenna 1)											
5 657.870	52.19	Peak	H	34.10	8.71	-	45.31	6.15	55.84	74.02	18.18
5 705.280	51.39	Peak	H	34.10	8.71	-	45.31	6.15	55.04	106.68	51.64
5 722.210	52.25	Peak	H	34.10	8.71	-	45.31	6.15	55.90	115.84	59.94
5 850.040	50.96	Peak	H	34.40	8.91	-	45.19	6.14	55.22	122.11	66.89
5 862.320	52.47	Peak	H	34.40	8.91	-	45.19	6.14	56.73	108.75	52.02
5 884.070	52.54	Peak	H	34.40	8.91	-	45.19	6.14	56.80	98.49	41.69
5 672.250	53.32	Peak	V	34.10	8.71	-	45.31	6.15	56.97	84.67	27.70
5 714.680	53.05	Peak	V	34.10	8.71	-	45.31	6.15	56.70	109.31	52.61
5 720.110	52.50	Peak	V	34.10	8.71	-	45.31	6.15	56.15	111.05	54.90
5 850.000	52.96	Peak	V	34.40	8.91	-	45.19	6.14	57.22	122.20	64.98
5 862.840	53.60	Peak	V	34.40	8.91	-	45.19	6.14	57.86	108.60	50.74
5 924.980	53.60	Peak	V	34.40	8.91	-	45.19	6.14	57.86	68.21	10.35

Tabulated test data for Restricted Band

Remark - "H": Horizontal, "V": Vertical

Margin (dB) = Limits (dB μ V/m) - Emission Level (dB μ V/m)

Frequency (MHz)	Reading (dB μ V)	Detector Mode	Ant. Pol. (H/V)	Ant. Factor	Cable Loss	DUTY Factor	AMP Factor	ATT Factor	Total (dB μ V/m)	Limits (dB μ V/m)	Margin (dB)
High Channel (Antenna 1)											
5 673.700	51.72	Peak	H	34.10	8.71	-	45.31	6.15	55.37	85.74	30.37
5 706.860	52.29	Peak	H	34.10	8.71	-	45.31	6.15	55.94	107.12	51.18
5 720.080	51.59	Peak	H	34.10	8.71	-	45.31	6.15	55.24	110.98	55.74
5 851.140	51.51	Peak	H	34.40	8.91	-	45.19	6.14	55.77	119.60	63.83
5 866.720	52.59	Peak	H	34.40	8.91	-	45.19	6.14	56.85	107.52	50.67
5 876.820	53.84	Peak	H	34.40	8.91	-	45.19	6.14	58.10	103.85	45.75
5 697.030	53.03	Peak	V	34.10	8.71	-	45.31	6.15	56.68	103.00	46.32
5 718.830	53.28	Peak	V	34.10	8.71	-	45.31	6.15	56.93	110.47	53.54
5 721.840	52.22	Peak	V	34.10	8.71	-	45.31	6.15	55.87	115.00	59.13
5 853.140	52.69	Peak	V	34.40	8.91	-	45.19	6.14	56.95	115.04	58.09
5 868.980	54.04	Peak	V	34.40	8.91	-	45.19	6.14	58.30	106.89	48.59
5 899.450	53.04	Peak	V	34.40	8.91	-	45.19	6.14	57.30	87.11	29.81

Tabulated test data for Restricted Band

Remark - "H": Horizontal, "V": Vertical

Margin (dB) = Limits (dB μ V/m) - Emission Level (dB μ V/m)

14.7.2 Test data for 802.11n_HT20 RLAN Mode

- Resolution bandwidth : 1 MHz and Peak Detector for Peak Mode
1 MHz and RMS Detector for Average Mode
- Video bandwidth : 3 MHz for Peak and Average Mode
- Measurement distance : 3 m
- Duty Cycle : > 98 %
- Result : Pass

Frequency (MHz)	Reading (dB μ V)	Detector Mode	Ant. Pol. (H/V)	Ant. Factor	Cable Loss	DUTY Factor	AMP Factor	AMP Factor	Total (dB μ V/m)	Limits (dB μ V/m)	Margin (dB)
Low Channel (Multiple Transmit)											
5 678.900	52.27	Peak	H	34.10	8.71	-	45.31	6.15	55.92	89.59	33.67
5 707.720	51.97	Peak	H	34.10	8.71	-	45.31	6.15	55.62	107.36	51.74
5 724.870	54.30	Peak	H	34.10	8.71	-	45.31	6.15	57.95	121.90	63.95
5 851.180	52.38	Peak	H	34.40	8.91	-	45.19	6.14	56.64	119.51	62.87
5 749.990	52.14	Peak	H	34.40	8.91	-	45.19	6.14	56.40	140.20	83.80
5 884.920	54.07	Peak	H	34.40	8.91	-	45.19	6.14	58.33	97.86	39.53
5 665.810	52.26	Peak	V	34.10	8.71	-	45.31	6.15	55.91	79.90	23.99
5 707.040	53.97	Peak	V	34.10	8.71	-	45.31	6.15	57.62	107.17	49.55
5 723.080	52.74	Peak	V	34.10	8.71	-	45.31	6.15	56.39	117.82	61.43
5 851.120	51.85	Peak	V	34.40	8.91	-	45.19	6.14	56.11	119.65	63.54
5 861.920	52.52	Peak	V	34.40	8.91	-	45.19	6.14	56.78	108.86	52.08
5 918.280	53.21	Peak	V	34.40	8.91	-	45.19	6.14	57.47	73.17	15.70

Tabulated test data for Restricted Band

Remark - "H": Horizontal, "V": Vertical

Margin (dB) = Limits (dB μ V/m) - Emission Level (dB μ V/m)

Frequency (MHz)	Reading (dB μ V)	Detector Mode	Ant. Pol. (H/V)	Ant. Factor	Cable Loss	DUTY Factor	AMP Factor	AMP Factor	Total (dB μ V/m)	Limits (dB μ V/m)	Margin (dB)
High Channel (Multiple Transmit)											
5 661.160	52.11	Peak	H	34.10	8.71	-	45.31	6.15	55.76	76.46	20.70
5 718.850	52.08	Peak	H	34.10	8.71	-	45.31	6.15	55.73	110.48	54.75
5 724.160	53.08	Peak	H	34.10	8.71	-	45.31	6.15	56.73	120.28	63.55
5 850.590	53.98	Peak	H	34.40	8.91	-	45.19	6.14	58.24	120.85	62.61
5 872.810	52.93	Peak	H	34.40	8.91	-	45.19	6.14	57.19	105.81	48.62
5 900.650	52.38	Peak	H	34.40	8.91	-	45.19	6.14	56.64	86.22	29.58
5 682.540	53.14	Peak	V	34.10	8.71	-	45.31	6.15	56.79	92.28	35.49
5 706.300	51.99	Peak	V	34.10	8.71	-	45.31	6.15	55.64	106.96	51.32
5 722.210	51.52	Peak	V	34.10	8.71	-	45.31	6.15	55.17	115.84	60.67
5 850.000	54.50	Peak	V	34.40	8.91	-	45.19	6.14	58.76	122.20	63.44
5 866.540	54.20	Peak	V	34.40	8.91	-	45.19	6.14	58.46	107.57	49.11
5 896.150	52.81	Peak	V	34.40	8.91	-	45.19	6.14	57.07	89.55	32.48

Tabulated test data for Restricted Band

Remark - "H": Horizontal, "V": Vertical

Margin (dB) = Limits (dB μ V/m) - Emission Level (dB μ V/m)

14.7.3 Test data for 802.11n_HT40 RLAN Mode

- Resolution bandwidth : 1 MHz and Peak Detector for Peak Mode
1 MHz and RMS Detector for Average Mode
- Video bandwidth : 3 MHz for Peak and Average Mode
- Measurement distance : 3 m
- Duty Cycle : > 98 %
- Result : Pass

Frequency (MHz)	Reading (dB μ V)	Detector Mode	Ant. Pol. (H/V)	Ant. Factor	Cable Loss	DUTY Factor	AMP Factor	AMP Factor	Total (dB μ V/m)	Limits (dB μ V/m)	Margin (dB)
Low Channel (Multiple Transmit)											
5 671.150	52.56	Peak	H	34.10	8.71	-	45.31	6.15	56.21	83.85	27.64
5 717.490	55.99	Peak	H	34.10	8.71	-	45.31	6.15	59.64	110.10	50.46
5 721.930	55.43	Peak	H	34.10	8.71	-	45.31	6.15	59.08	115.20	56.12
5 851.350	52.27	Peak	H	34.40	8.91	-	45.19	6.14	56.53	119.12	62.59
5 870.810	52.30	Peak	H	34.40	8.91	-	45.19	6.14	56.56	106.37	49.81
5 901.850	52.95	Peak	H	34.40	8.91	-	45.19	6.14	57.21	85.33	28.12
5 674.200	52.70	Peak	V	34.10	8.71	-	45.31	6.15	56.35	86.11	29.76
5 719.990	59.40	Peak	V	34.10	8.71	-	45.31	6.15	63.05	110.80	47.75
5 724.090	61.45	Peak	V	34.10	8.71	-	45.31	6.15	65.10	120.13	55.03
5 854.870	52.63	Peak	V	34.40	8.91	-	45.19	6.14	56.89	111.10	54.21
5 870.330	53.48	Peak	V	34.40	8.91	-	45.19	6.14	57.74	106.51	48.77
5 896.150	52.59	Peak	V	34.40	8.91	-	45.19	6.14	56.85	89.55	32.70

Tabulated test data for Restricted Band

Remark - "H": Horizontal, "V": Vertical

Margin (dB) = Limits (dB μ V/m) - Emission Level (dB μ V/m)

Frequency (MHz)	Reading (dB μ V)	Detector Mode	Ant. Pol. (H/V)	Ant. Factor	Cable Loss	DUTY Factor	AMP Factor	AMP Factor	Total (dB μ V/m)	Limits (dB μ V/m)	Margin (dB)
High Channel (Multiple Transmit)											
5 665.460	51.96	Peak	H	34.10	8.71	-	45.31	6.15	55.61	79.64	24.03
5 715.410	51.93	Peak	H	34.10	8.71	-	45.31	6.15	55.58	109.51	53.93
5 723.460	51.48	Peak	H	34.10	8.71	-	45.31	6.15	55.13	118.69	63.56
5 855.000	51.32	Peak	H	34.40	8.91	-	45.19	6.14	55.58	110.80	55.22
5 865.500	52.88	Peak	H	34.40	8.91	-	45.19	6.14	57.14	107.86	50.72
5 888.810	53.39	Peak	H	34.40	8.91	-	45.19	6.14	57.65	94.98	37.33
5 664.010	51.95	Peak	V	34.10	8.71	-	45.31	6.15	55.60	78.57	22.97
5 711.760	51.39	Peak	V	34.10	8.71	-	45.31	6.15	55.04	108.49	53.45
5 721.380	51.11	Peak	V	34.10	8.71	-	45.31	6.15	54.76	113.95	59.19
5 851.300	52.00	Peak	V	34.40	8.91	-	45.19	6.14	56.26	119.24	62.98
5 866.840	52.24	Peak	V	34.40	8.91	-	45.19	6.14	56.50	107.48	50.98
5 902.050	52.05	Peak	V	34.40	8.91	-	45.19	6.14	56.31	85.18	28.87

Tabulated test data for Restricted Band

Remark - "H": Horizontal, "V": Vertical

Margin (dB) = Limits (dB μ V/m) - Emission Level (dB μ V/m)

14.7.4 Test data for 802.11ac_VHT80 RLAN Mode

- Resolution bandwidth : 1 MHz and Peak Detector for Peak Mode
1 MHz and RMS Detector for Average Mode
- Video bandwidth : 3 MHz for Peak and Average Mode
- Measurement distance : 3 m
- Duty Cycle : > 98 %
- Result : Pass

Frequency (MHz)	Reading (dB μ V)	Detector Mode	Ant. Pol. (H/V)	Ant. Factor	Cable Loss	DUTY Factor	AMP Factor	AMP Factor	Total (dB μ V/m)	Limits (dB μ V/m)	Margin (dB)
Low Channel (Multiple Transmit)											
5 695.130	51.24	Peak	H	34.10	8.71	-	45.31	6.15	54.89	101.60	46.71
5 704.910	50.91	Peak	H	34.10	8.71	-	45.31	6.15	54.56	106.57	52.01
5 723.670	50.17	Peak	H	34.10	8.71	-	45.31	6.15	53.82	119.17	65.35
5 854.090	51.54	Peak	H	34.40	8.91	-	45.19	6.14	55.80	112.87	57.07
5 867.440	51.40	Peak	H	34.40	8.91	-	45.19	6.14	55.66	107.32	51.66
5 906.990	53.00	Peak	H	34.40	8.91	-	45.19	6.14	57.26	81.53	24.27
5 686.490	53.20	Peak	V	34.10	8.71	-	45.31	6.15	56.85	95.20	38.35
5 712.320	52.59	Peak	V	34.10	8.71	-	45.31	6.15	56.24	108.65	52.41
5 724.660	52.38	Peak	V	34.10	8.71	-	45.31	6.15	56.03	121.42	65.39
5 852.440	53.18	Peak	V	34.40	8.91	-	45.19	6.14	57.44	116.64	59.20
5 860.140	53.50	Peak	V	34.40	8.91	-	45.19	6.14	57.76	109.36	51.60
5 924.980	51.56	Peak	V	34.40	8.91	-	45.19	6.14	55.82	68.21	12.39


Tabulated test data for Restricted Band

Remark - "H": Horizontal, "V": Vertical

Margin (dB) = Limits (dB μ V/m) - Emission Level (dB μ V/m)

14.7.5 U-NII-3 Emission Limits

14.7.5.1 Emission Mask Plots



Remark.

- Title 47 → Part 15 → Subpart E—UNLICENSED NATIONAL INFORMATION INFRASTRUCTURE DEVICES

§ 15.407 General technical requirements.

(4) For transmitters operating in the 5.725-5.85 GHz band:

(i) All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

15. CONDUCTED EMISSION TEST

15.1 Operating environment

Temperature : 23 °C

Relative humidity : 45 % R.H.

15.2 Test set-up


The EUT was placed on a wooden table, 0.8 m height above the floor. Power was fed to the EUT through a $50 \Omega / 50 \mu\text{H} + 5 \Omega$ Artificial Mains Network (AMN). The ground plane was electrically bonded to the reference ground system and all power lines were filtered from ambient.

15.3 Test Date

December 05, 2021 ~ March 08, 2022

15.4 Test data for WLAN 5 GHz

- Resolution bandwidth : 9 kHz
- Frequency range : 0.15 MHz ~ 30 MHz
- Tested Line : LIVE LINE
- Antenna 0, Antenna 1 and Multiple transmit tested, but the worst data were recorded.




NO	FREQ [MHz]	READING		C.FACTOR [dB]	RESULT		LIMIT		MARGIN		PHASE
		QP [dBuV]	AV [dBuV]		QP [dBuV]	AV [dBuV]	QP [dBuV]	AV [dBuV]	QP [dBuV]	AV [dBuV]	
1	0.17200	38.9	----	10.0	48.9	----	64.9	----	16.0	----	H (QP)
2	0.29200	28.1	----	10.0	38.1	----	60.5	----	22.4	----	H (QP)
3	8.83500	17.9	----	10.2	28.1	----	60.0	----	31.9	----	H (QP)
4	16.19000	21.7	----	10.3	32.0	----	60.0	----	28.0	----	H (QP)
5	20.60000	24.4	----	10.4	34.8	----	60.0	----	25.2	----	H (QP)
6	22.08000	24.0	----	10.4	34.4	----	60.0	----	25.6	----	H (QP)
7	0.17200	----	11.6	10.0	----	21.6	----	54.9	----	33.3	H (CAV)
8	0.29200	----	20.7	10.0	----	30.7	----	50.5	----	19.8	H (CAV)
9	8.83500	----	13.9	10.2	----	24.1	----	50.0	----	25.9	H (CAV)
10	16.19000	----	17.8	10.3	----	28.1	----	50.0	----	21.9	H (CAV)
11	20.60000	----	20.4	10.4	----	30.8	----	50.0	----	19.2	H (CAV)
12	22.08000	----	19.7	10.4	----	30.1	----	50.0	----	19.9	H (CAV)

- Tested Line : NEUTRAL LINE

Remark: Margin (dB) = Limit – Level (Result)


The emission level in above table is included the transducer factor that means insertion loss (LISN), cable loss and attenuator.



NO	FREQ [MHz]	READING		C.FACTOR [dB]	RESULT		LIMIT		MARGIN		PHASE
		QP [dBuV]	AV [dBuV]		QP [dBuV]	AV [dBuV]	QP [dBuV]	AV [dBuV]	QP [dBuV]	AV [dBuV]	
1	0.17400	35.6	----	10.0	45.6	----	64.8	----	19.2	----	N (QP)
2	0.29300	28.6	----	10.0	38.6	----	60.4	----	21.8	----	N (QP)
3	0.96500	19.2	----	10.0	29.2	----	56.0	----	26.8	----	N (QP)
4	16.20000	19.2	----	10.3	29.5	----	60.0	----	30.5	----	N (QP)
5	20.61000	21.2	----	10.4	31.6	----	60.0	----	28.4	----	N (QP)
6	22.09000	21.7	----	10.4	32.1	----	60.0	----	27.9	----	N (QP)
7	0.17400	---	9.3	10.0	---	19.3	---	54.8	----	35.5	N (CAV)
8	0.29300	---	20.8	10.0	---	30.8	---	50.4	----	19.6	N (CAV)
9	0.96500	---	7.7	10.0	---	17.7	---	46.0	----	28.3	N (CAV)
10	16.20000	---	16.0	10.3	---	26.3	---	50.0	----	23.7	N (CAV)
11	20.61000	---	18.8	10.4	---	29.2	---	50.0	----	20.8	N (CAV)
12	22.09000	---	17.4	10.4	---	27.8	---	50.0	----	22.2	N (CAV)

15.6 Test data for Intermodulation Mode(WLAN 5 GHz + Bluetooth)

- Resolution bandwidth : 9 kHz
- Frequency range : 0.15 MHz ~ 30 MHz
- Tested Line : LIVE LINE




NO	FREQ [MHz]	READING		C.FACTOR [dB]	RESULT		LIMIT		MARGIN		PHASE
		QP [dBuV]	AV [dBuV]		QP [dBuV]	AV [dBuV]	QP [dBuV]	AV [dBuV]	QP [dBuV]	AV [dBuV]	
1	0.17000	37.5	----	10.0	47.5	----	65.0	----	17.5	----	H (QP)
2	0.29000	27.5	----	10.0	37.5	----	60.5	----	23.0	----	H (QP)
3	8.88500	18.5	----	10.2	28.7	----	60.0	----	31.3	----	H (QP)
4	16.30000	22.2	----	10.3	32.5	----	60.0	----	27.5	----	H (QP)
5	20.73000	25.1	----	10.4	35.5	----	60.0	----	24.5	----	H (QP)
6	22.21000	22.9	----	10.4	33.3	----	60.0	----	26.7	----	H (QP)
7	0.17000	----	10.2	10.0	----	20.2	----	55.0	----	34.8	H (CAV)
8	0.29000	----	20.9	10.0	----	30.9	----	50.5	----	19.6	H (CAV)
9	8.88500	----	14.3	10.2	----	24.5	----	50.0	----	25.5	H (CAV)
10	16.30000	----	10.4	10.3	----	20.7	----	50.0	----	29.3	H (CAV)
11	20.73000	----	20.3	10.4	----	30.7	----	50.0	----	19.3	H (CAV)
12	22.21000	----	19.6	10.4	----	30.0	----	50.0	----	20.0	H (CAV)

- Tested Line : NEUTRAL LINE

Remark: Margin (dB) = Limit – Level (Result)


The emission level in above table is included the transducer factor that means insertion loss (LISN), cable loss and attenuator.



NO	FREQ [MHz]	READING		C.FACTOR [dB]	RESULT		LIMIT		MARGIN		PHASE
		QP [dBuV]	AV [dBuV]		QP [dBuV]	AV [dBuV]	QP [dBuV]	AV [dBuV]	QP [dBuV]	AV [dBuV]	
1	0.17000	35.3	----	10.0	45.3	----	65.0	----	19.7	----	N (QP)
2	0.29000	27.9	----	10.0	37.9	----	60.5	----	22.6	----	N (QP)
3	8.89000	15.9	----	10.2	26.1	----	60.0	----	33.9	----	N (QP)
4	16.30000	19.6	----	10.3	29.9	----	60.0	----	30.1	----	N (QP)
5	20.74000	21.4	----	10.4	31.8	----	60.0	----	28.2	----	N (QP)
6	22.22000	22.1	----	10.4	32.5	----	60.0	----	27.5	----	N (QP)
7	0.17000	11.5	10.0	----	21.5	----	55.0	----	33.5	N (CAV)	
8	0.29000	19.7	10.0	----	29.7	----	50.5	----	20.8	N (CAV)	
9	8.89000	12.4	10.2	----	22.6	----	50.0	----	27.4	N (CAV)	
10	16.30000	15.2	10.3	----	25.5	----	50.0	----	24.5	N (CAV)	
11	20.74000	17.9	10.4	----	28.3	----	50.0	----	21.7	N (CAV)	
12	22.22000	17.1	10.4	----	27.5	----	50.0	----	22.5	N (CAV)	

15.7 Test data for Intermodulation Mode(WLAN 5 GHz + Bluetooth LE)

- Resolution bandwidth : 9 kHz
- Frequency range : 0.15 MHz ~ 30 MHz
- Tested Line : LIVE LINE




NO	FREQ [MHz]	READING		C. FACTOR [dB]	RESULT		LIMIT		MARGIN		PHASE
		QP [dBuV]	AV [dBuV]		QP [dBuV]	AV [dBuV]	QP [dBuV]	AV [dBuV]	QP [dBuV]	AV [dBuV]	
1	0.17100	36.5	----	10.0	46.5	----	64.9	----	18.4	----	H (QP)
2	0.29000	27.8	----	10.0	37.8	----	60.5	----	22.7	----	H (QP)
3	8.90500	18.2	----	10.2	28.4	----	60.0	----	31.6	----	H (QP)
4	16.32000	22.1	----	10.3	32.4	----	60.0	----	27.6	----	H (QP)
5	20.77000	23.8	----	10.4	34.2	----	60.0	----	25.8	----	H (QP)
6	22.25000	22.4	----	10.4	32.8	----	60.0	----	27.2	----	H (QP)
7	0.17100	12.0	10.0	----	22.0	----	54.9	----	32.9	----	H (CAV)
8	0.29000	20.5	10.0	----	30.5	----	50.5	----	20.0	----	H (CAV)
9	8.90500	14.7	10.2	----	24.9	----	50.0	----	25.1	----	H (CAV)
10	16.32000	18.1	10.3	----	28.4	----	50.0	----	21.6	----	H (CAV)
11	20.77000	22.0	10.4	----	32.4	----	50.0	----	17.6	----	H (CAV)
12	22.25000	18.5	10.4	----	28.9	----	50.0	----	21.1	----	H (CAV)

- Tested Line : NEUTRAL LINE

Remark: Margin (dB) = Limit – Level (Result)


The emission level in above table is included the transducer factor that means insertion loss (LISN), cable loss and attenuator.



NO	FREQ [MHz]	READING		C.FACTOR [dB]	RESULT		LIMIT		MARGIN		PHASE
		QP [dBuV]	AV [dBuV]		QP [dBuV]	AV [dBuV]	QP [dBuV]	AV [dBuV]	QP [dBuV]	AV [dBuV]	
1	0.16400	34.6	----	10.0	44.6	----	65.3	----	20.7	----	N (QP)
2	0.28800	27.3	----	10.0	37.3	----	60.6	----	23.3	----	N (QP)
3	8.90500	16.6	----	10.2	26.8	----	60.0	----	33.2	----	N (QP)
4	16.32000	19.2	----	10.3	29.5	----	60.0	----	30.5	----	N (QP)
5	20.77000	22.2	----	10.4	32.6	----	60.0	----	27.4	----	N (QP)
6	22.26000	21.3	----	10.4	31.7	----	60.0	----	28.3	----	N (QP)
7	0.16400	----	9.2	10.0	----	19.2	----	55.3	----	36.1	N (CAV)
8	0.28800	----	18.9	10.0	----	28.9	----	50.6	----	21.7	N (CAV)
9	8.90500	----	12.7	10.2	----	22.9	----	50.0	----	27.1	N (CAV)
10	16.32000	----	15.0	10.3	----	25.3	----	50.0	----	24.7	N (CAV)
11	20.77000	----	19.0	10.4	----	29.4	----	50.0	----	20.6	N (CAV)
12	22.26000	----	16.0	10.4	----	26.4	----	50.0	----	23.6	N (CAV)

15.5 Test data for Intermodulation Mode(WLAN 5 GHz + WLAN 2.4 GHz)

- Resolution bandwidth : 9 kHz
- Frequency range : 0.15 MHz ~ 30 MHz
- Tested Line : LIVE LINE




NO	FREQ [MHz]	READING		C.FACTOR [dB]	RESULT		LIMIT		MARGIN		PHASE
		QP [dBuV]	AV [dBuV]		QP [dBuV]	AV [dBuV]	QP [dBuV]	AV [dBuV]	QP [dBuV]	AV [dBuV]	
1	0.17000	36.5	----	10.0	46.5	----	65.0	----	18.5	----	H (QP)
2	0.29000	28.3	----	10.0	38.3	----	60.5	----	22.2	----	H (QP)
3	8.91500	17.6	----	10.2	27.8	----	60.0	----	32.2	----	H (QP)
4	14.85000	21.7	----	10.3	32.0	----	60.0	----	28.0	----	H (QP)
5	20.79000	24.8	----	10.4	35.2	----	60.0	----	24.8	----	H (QP)
6	22.27000	22.9	----	10.4	33.3	----	60.0	----	26.7	----	H (QP)
7	0.17000	----	11.3	10.0	----	21.3	----	55.0	----	33.7	H (CAV)
8	0.29000	----	20.6	10.0	----	30.6	----	50.5	----	19.9	H (CAV)
9	8.91500	----	14.2	10.2	----	24.4	----	50.0	----	25.6	H (CAV)
10	14.85000	----	17.2	10.3	----	27.5	----	50.0	----	22.5	H (CAV)
11	20.79000	----	19.7	10.4	----	30.1	----	50.0	----	19.9	H (CAV)
12	22.27000	----	18.5	10.4	----	28.9	----	50.0	----	21.1	H (CAV)

- Tested Line : NEUTRAL LINE

Remark: Margin (dB) = Limit – Level (Result)

The emission level in above table is included the transducer factor that means insertion loss (LISN), cable loss and attenuator.



NO	FREQ [MHz]	READING		C.FACTOR [dB]	RESULT		LIMIT		MARGIN		PHASE
		QP [dBuV]	AV [dBuV]		QP [dBuV]	AV [dBuV]	QP [dBuV]	AV [dBuV]	QP [dBuV]	AV [dBuV]	
1	0.17100	33.8	----	10.0	43.8	----	64.9	----	21.1	----	N (QP)
2	0.28700	26.7	----	10.0	36.7	----	60.6	----	23.9	----	N (QP)
3	8.91000	17.6	----	10.2	27.8	----	60.0	----	32.2	----	N (QP)
4	14.85000	19.6	----	10.3	29.9	----	60.0	----	30.1	----	N (QP)
5	20.79000	22.8	----	10.4	33.2	----	60.0	----	26.8	----	N (QP)
6	22.27000	21.9	----	10.4	32.3	----	60.0	----	27.7	----	N (QP)
7	0.17100	----	10.3	10.0	----	20.3	----	54.9	----	34.6	N (CAV)
8	0.28700	----	18.4	10.0	----	28.4	----	50.6	----	22.2	N (CAV)
9	8.91000	----	12.7	10.2	----	22.9	----	50.0	----	27.1	N (CAV)
10	14.85000	----	14.6	10.3	----	24.9	----	50.0	----	25.1	N (CAV)
11	20.79000	----	17.9	10.4	----	28.3	----	50.0	----	21.7	N (CAV)
12	22.27000	----	17.1	10.4	----	27.5	----	50.0	----	22.5	N (CAV)

16. DYNAMIC FREQUENCY SELECTION (DFS)

16.1 Operating environment


Temperature : 24 °C

Relative humidity : 45 % R.H.

16.2 Test set-ups

The FCC 06-96 and RSS-210 A9.3 describes a conducted test setup. A conducted test setup was used for this testing. Figure 1 shows the typical test setup. Each one channel selected between 5 250 MHz and 5 350 MHz, 5 470 MHz and 5 725 MHz is chosen for the testing.

Figure 1. Setup for Client with injection at the Master



The operational behavior and individual DFS requirements that are associated with these modes are as follows:

<Master Devices>

- The Master Device will use DFS in order to detect Radar Waveforms with received signal strength above the DFS Detection Threshold in the 5 250 – 5 350 MHz and 5 470 – 5 725 MHz bands. DFS is not required in the 5 150 – 5 250 MHz or 5 725 – 5 825 MHz bands.
- Before initiating a network on a Channel, the Master Device will perform a Channel Availability Check for a specified time duration (Channel Availability Check Time) to ensure that there is no radar system operating on the Channel, using DFS described under subsection a) above.
- The Master Device initiates a U-NII network by transmitting control signals that will enable other U-NII devices to Associate with the Master Device.
- During normal operation, the Master Device will monitor the Channel (In-Service Monitoring) to ensure that there is no radar system operating on the Channel, using DFS described under a).
- If the Master Device has detected a Radar Waveform during In-Service Monitoring as described under d), the Operating Channel of the U-NII network is no longer an Available Channel. The Master Device will instruct all associated Client Device(s) to stop transmitting on this Channel within the Channel Move Time. The transmissions during the Channel Move Time will be limited to the Channel Closing Transmission Time.

- f) Once the Master Device has detected a Radar Waveform it will not utilize the Channel for the duration of the Non-Occupancy Period. 3
- g) If the Master Device delegates the In-Service Monitoring to a Client Device, then the combination will be tested to the requirements described under d) through f) above.

<Client Devices>

- a) A Client Device will not transmit before having received appropriate control signals from a Master Device.
- b) A Client Device will stop all its transmissions whenever instructed by a Master Device to which it is associated and will meet the Channel Move Time and Channel Closing Transmission Time requirements. The Client Device will not resume any transmissions until it has again received control signals from a Master Device.
- c) If a Client Device is performing In-Service Monitoring and detects a Radar Waveform above the DFS Detection Threshold, it will inform the Master Device. This is equivalent to the Master Device detecting the Radar Waveform and d) through f) of section 5.1.1 apply.
- d) Irrespective of Client Device or Master Device detection the Channel Move Time and Channel Closing Transmission Time requirements remain the same.
- e) The client test frequency must be monitored to ensure no transmission of any type has occurred for 30 minutes. Note: If the client moves with the master, the device is considered compliant if nothing appears in the client non-occupancy period test. For devices that shut down (rather than moving channels), no beacons should appear.

<Channel Connection Information>

- a) Master Devices : RF-AX88U
- b) Client(=EUT) Devices : ATC6NPL002
- c) Connect to test channel : See next page for measurement data.

Note : TPC is not required since the maximum EIRP is less than 500mW(27dBm).

16.3 DFS Test Signals

Table 5 – Short Pulse Radar Test Waveforms

Radar Type	Pulse Width (μsec)	PRI (μsec)	Number of Pulses	Minimum Percentage of Successful Detection	Minimum Number of Trials
0	1	1428	18	See Note 1	See Note 1
1	1	Test A: 15 unique PRI values randomly selected from the list of 23 PRI values in Table 5a	Roundup $\left(\left(\frac{1}{360} \right) \cdot \left(\frac{19 \cdot 10^6}{\text{PRI}_{\mu\text{sec}}} \right) \right)$	60%	30
		Test B: 15 unique PRI values randomly selected within the range of 518-3066 μsec , with a minimum increment of 1 μsec , excluding PRI values selected in Test A			
2	1-5	150-230	23-29	60%	30
3	6-10	200-500	16-18	60%	30
4	11-20	200-500	12-16	60%	30
Aggregate (Radar Types 1-4)				80%	120

Table 6 – Long Pulse Radar Test Waveform

Radar Type	Pulse Width (μsec)	Chirp Width (MHz)	PRI (μsec)	Number of Pulses per Burst	Number of Bursts	Minimum Percentage of Successful Detection	Minimum Number of Trials
5	50-100	5-20	1000-2000	1-3	8-20	80%	30

16.4 Technical Requirement Specification

Table 1: Applicability of DFS Requirements Prior to Use of a Channel

Requirement	Operational Mode		
	Master	Client (without DFS)	Client (with DFS)
<i>Non-Occupancy Period</i>	Yes	Not required	Yes
<i>DFS Detection Threshold</i>	Yes	Not required	Yes
<i>Channel Availability Check Time</i>	Yes	Not required	Not required
<i>Uniform Spreading</i>	Yes	Not required	Not required
<i>U-NII Detection Bandwidth</i>	Yes	Not required	Yes

Table 2: Applicability of DFS requirements during normal operation

Requirement	Operational Mode		
	Master	Client (without DFS)	Client (with DFS)
<i>DFS Detection Threshold</i>	Yes	Not required	Yes
<i>Channel Closing Transmission Time</i>	Yes	Yes	Yes
<i>Channel Move Time</i>	Yes	Yes	Yes
<i>U-NII Detection Bandwidth</i>	Yes	Not required	Yes

16.5 Test Date

December 05, 2021 ~ March 08, 2022


16.6 Test data

Band	Frequency (MHz)	Channel move time(s)		Channel closing transmission time(ms)	
		Measured	Limit	Measured	Limit
UNII 2A	5 290.00	0.88	10.00	4.8	200 milliseconds + an aggregate of 60 milliseconds over remaining 10 second period.
UNII 2C	5 530.00	0.84		3.6	



Note. Channel closing transmission time: $0.4 \times 12 = 4.8$ ms, $0.4 \times 9 = 3.6$ ms

16.6.1 UNII 2A


16.6.1.1 Plot of Radar waveform type 0



Note: The calibrated conducted DFS detection threshold level is set to **-64.56 dBm** ($-62+1+9 = -52.00$ dBm)


16.6.1.2 No traffic signal(master signal)**16.6.1.3 Client(EUT) Data Traffic Signal**

16.6.1.4 Channel move and Channel Closing transmission time






16.6.2 UNII 3

16.6.2.1 Plot of Radar waveform type 1



Note: The calibrated conducted DFS detection threshold level is set to -64.64 dBm (-62+1+9 = -52.00 dBm)

16.6.2.2 No traffic signal(master signal)**16.6.2.3 Client(EUT) Data Traffic Signal**

16.6.2.4 Channel move and Channel Closing transmission time

17. LIST OF TEST EQUIPMENT

Model Number	Manufacturer	Description	Serial Number	Last Cal.(Interval)
FSV40-N	Rohde & Schwarz	Signal Analyzer	102177	Apr. 16, 2021 (1Y)
ESW 44	Rohde & Schwarz	EMI Test Receiver	101851	Mar. 08, 2022 (1Y)
SSE-43CI-A	Samkun Tech	Humidity Chamber	60712	Jan. 18, 2022 (1Y)
ZUP36-6	NEMIC-LAMBDA	DC Power Supply	YJV-535Z14-0018	Apr. 16, 2021(1Y)
310N	Sonoma Instrument	Pre-Amplifier	392756	Oct. 14, 2021 (1Y)
SCU18	Rohde & Schwarz	Pre-Amplifier	102266	Jul. 14, 2021 (1Y)
PAM-118A	Com-Power	Pre-Amplifier	18040081	Oct. 12, 2021 (1Y)
PAM-840A	Com-Power	Pre-Amplifier	461339	Oct. 18, 2021 (1Y)
F-40-5000-RF	RLC Electronis	High Pass Filter	0425	Feb. 01, 2022(1Y)
HPF 3GHz	Rohde & Schwarz	High Pass Filter	N/A	Jan. 19, 2022(1Y)
DT3000-3t	Innco System	Turn Table	DT3000/093	N/A
MA-4000XPET	Innco System	Antenna Master	MA4000/509	N/A
FMZB 1513	Schwarzbeck	Loop Antenna	1513-235	Mar. 24, 2022 (2Y)
HLP-2008	TDK	Hybrid Antenna	131314	Feb. 25, 2022 (2Y)
AH-118	Com-Power	Horn Antenna	10050061	Oct. 15, 2021 (1Y)
BBHA9170	Schwarzbeck	Horn Antenna	BBHA9170178	Jan. 06, 2022(1Y)
ESCI	Rohde & Schwarz	EMI TEST RECEIVER	101012	Oct. 20, 2021 (1Y)
NSLK8126	Schwarzbeck	AMN	8126-404	Mar. 14, 2022 (1Y)
ESH3-Z2	Rohde & Schwarz	PULSE LIMITER	100655	Mar. 14, 2022 (1Y)
D-05180-2	RLC Electronis Inc.	Combiner	0813	N/A
11636B	Hewlett Packard	Combiner	12268	N/A
SMBV100A	R/S	Signal Generator	260423	Jan 17, 2022 (1Y)
RF-AX88U	ASUS	Dual Band Gigabit Router	NA	N/A

All test equipment used is calibrated on a regular basis.