

ELECTROMAGNETIC EMISSION COMPLIANCE REPORT FOR LOW-POWER, NON-LICENSED TRANSMITTER

Test Report No. : OT-214-RWD-107

Reception No. : 2104001698

Applicant : LG Innotek Co., Ltd.

Address : 26, Hanamsandan 5beon-ro Gwangsan-gu, Gwangju, 506-731, South Korea

Manufacturer : LG Innotek Co., Ltd.

Address : 26, Hanamsandan 5beon-ro Gwangsan-gu, Gwangju, 506-731, South Korea

Type of Equipment : Bluetooth Low Energy Module

FCC ID. : YZP-ETWBCLUL05

Model Name : ETWBCLUL05

Serial number : N/A

Total page of Report : 7 pages (including this page)

Date of Incoming : April 16, 2021

Date of issue : April 29, 2021

SUMMARY

The equipment complies with the regulation; *FCC PART 15 SUBPART C Section 15.247*

This test report only contains the result of a single test of the sample supplied for the examination.


It is not a generally valid assessment of the features of the respective products of the mass-production.



Tested by
Hyung-Kwon, Oh / Manager
ONETECH Corp.



Reviewed by
Tae-Ho, Kim / Senior Manager
ONETECH Corp.



Approved by
Ki-Hong, Nam / General Manager
ONETECH Corp.

CONTENTS**PAGE**

| | |
|--|----------|
| 1. VERIFICATION OF COMPLIANCE | 4 |
| 2. GENERAL INFORMATION | 5 |
| 2.1 PRODUCT DESCRIPTION..... | 5 |
| 2.2 ALTERNATIVE TYPE(S)/MODEL(S); ALSO COVERED BY THIS TEST REPORT..... | 5 |
| 3. EUT MODIFICATIONS..... | 5 |
| 4. MAXIMUM PERMISSIBLE EXPOSURE..... | 6 |
| 4.1 RF EXPOSURE CALCULATION | 6 |
| 4.2 EUT DESCRIPTION..... | 6 |
| 4.3 CALCULATED MPE SAFE DISTANCE..... | 7 |

Revision History

| Rev. No. | Issue Report No. | Issued Date | Revisions | Section Affected |
|----------|------------------|----------------|-----------------|------------------|
| 0 | OT-214-RWD-107 | April 29, 2021 | Initial Release | All |
| | | | | |
| | | | | |

1. VERIFICATION OF COMPLIANCE

Applicant : LG Innotek Co., Ltd.
 Address : 26, Hanamsandan 5beon-ro Gwangsang-gu, Gwangju, 506-731, South Korea
 Contact Person : KIM HYUNG SUK / Engineer
 Telephone No. : +82-10-3999-6575
 FCC ID : YZP-ETWBCLUL05
 Model Name : ETWBCLUL05
 Brand Name : -
 Serial Number : N/A
 Date : April 29, 2021

| | |
|--|--|
| EQUIPMENT CLASS | DTS – DIGITAL TRNSMISSION SYSTEM |
| E.U.T. DESCRIPTION | Modular Transmitter, Bluetooth Low Energy Module |
| THIS REPORT CONCERNS | Original Grant |
| MEASUREMENT PROCEDURES | ANSI C63.10: 2020 |
| TYPE OF EQUIPMENT TESTED | Pre-Production |
| KIND OF EQUIPMENT AUTHORIZATION REQUESTED | Certification |
| EQUIPMENT WILL BE OPERATED UNDER FCC RULES PART(S) | FCC PART 15 SUBPART C Section 15.247 KDB 558074 D01 15.247 Meas Guidance v05r02 |
| Modifications on the Equipment to Achieve Compliance | None |
| Final Test was Conducted On | 3 m, Semi Anechoic Chamber |

-. The above equipment was tested by ONETECH Corp. for compliance with the requirement set forth in the FCC Rules and Regulations. This said equipment in the configuration described in this report, shows the maximum emission levels emanating from equipment are within the compliance requirements.

2. GENERAL INFORMATION

2.1 Product Description

The LG Innotek Co., Ltd., Model ETWBCLUL05 (referred to as the EUT in this report) is a Bluetooth Low Energy Module. The product specification described herein was obtained from product data sheet or user's manual.

| | | |
|---|-----------------------------|----------|
| DEVICE TYPE | Bluetooth Low Energy Module | |
| OPERATING FREQUENCY | 2 402 MHz ~ 2 480 MHz | |
| MODULATION TYPE | GFSK | |
| RF OUTPUT POWER | 1 Mbps | 3.31 dBm |
| | 2 Mbps | 3.32 dBm |
| ANTENNA TYPE | PCB Antenna | |
| ANTENNA GAIN | 0.08 dBi | |
| List of each Osc. or crystal Freq.(Freq. >= 1 MHz) | 32 MHz | |

2.2 Alternative type(s)/model(s); also covered by this test report.

-. None

3. EUT MODIFICATIONS

-. None

4. MAXIMUM PERMISSIBLE EXPOSURE

4.1 RF Exposure Calculation

According to the FCC rule 1.1310 table 1B, the limit for the maximum permissible RF exposure for an uncontrolled environment are $f/1500$ mW/cm² for the frequency range between 300 MHz and 1 500 MHz and 1.0 mW/cm² for the frequency range between 1 500 MHz and 100 000 MHz.

The electric field generated for a 1 mW/cm² exposure is calculated as follows:

$$E = \sqrt{(30 * P * G) / d}, \text{ and } S = E^2 / Z = E^2 / 377, \text{ because } 1 \text{ mW/cm}^2 = 10 \text{ W/m}^2$$

Where

S = Power density in mW/cm², Z = Impedance of free space, 377 Ω

E = Electric field strength in V/m, G = Numeric antenna gain, and d = distance in meter

Combining equations and rearranging the terms to express the distance as a function of the remaining variable

$$d = \sqrt{(30 * P * G) / (377 * 10 S)}$$

Changing to units of mW and cm, using P (mW) = P (W) / 1 000, d (cm) = 0.01 * d (m)

$$d = 0.282 * \sqrt{(P * G) / S}$$

Where

d = distance in cm, P = Power in mW, G = Numeric antenna gain, and S = Power density in mW/cm²

4.2 EUT Description

| | |
|-----------------------------|--|
| Kind of EUT | Bluetooth Low Energy Module |
| Device Category | <input type="checkbox"/> Portable (< 20 cm separation) <input type="checkbox"/> Mobile (> 20 cm separation) <input checked="" type="checkbox"/> Others |
| Exposure Evaluation Applied | <input checked="" type="checkbox"/> MPE <input type="checkbox"/> SAR <input type="checkbox"/> N/A |

4.3 Calculated MPE Safe Distance

According to above equation, the following result was obtained.

| Operating Freq. Band (MHz) | Operating Mode | Target Power W/tolerance (dBm) | Max tune up power | | Antenna Gain | | Safe Distance (cm) | Power Density (mW/cm ²) @ 20 cm Separation | Limit (mW/cm ²) |
|----------------------------|----------------|--------------------------------|-------------------|------|--------------|--------|--------------------|--|-----------------------------|
| | | | (dBm) | (mW) | Log | Linear | | | |
| 2 402 ~ 2 480 | BLE_1 Mbps | 3.0 ± 1.0 | 4.00 | 2.51 | 0.08 | 1.02 | 0.45 | 0.000 5 | 1.00 |
| | BLE_2 Mbps | 3.0 ± 1.0 | 4.00 | 2.51 | | | 0.45 | 0.000 5 | 1.00 |

According to above table, for 2 402 ~ 2 480 MHz Band(BLE_1 Mbps), safe distance,

$$D = 0.282 * \sqrt{(2.51 * 1.02)/1.00} = 0.45 \text{ cm.}$$

For getting power density at 20 cm separation in above table, following formula was used.

$$S = P * G / (4\pi * R^2) = 2.51 * 1.02 / (4 * \pi * 20^2) = 0.000 5$$

Where:

S = Power Density,

P = Power input to the external antenna (Output power from the EUT antenna port (dBm) – cable loss (dB)),

G = Gain of Transmit Antenna (linear gain), R = Distance from Transmitting Antenna