

ELECTROMAGNETIC EMISSION COMPLIANCE REPORT FOR LOW-POWER, NON-LICENSED TRANSMITTER

Test Report No. : OT-20D-RWD-064

Reception No. : 2012005224

Applicant : LG Innotek Co., Ltd.

Address : 26, Hanamsandan 5beon-ro Gwangsan-gu, Gwangju, 506-731, South Korea

Manufacturer : LG Innotek Co., Ltd.

Address : 26, Hanamsandan 5beon-ro Gwangsan-gu, Gwangju, 506-731, South Korea

Type of Equipment : BT(V4.2) + WLAN(802.11a/b/g/n/ac) 2x2 MIMO Module

FCC ID. : YZP-RBHPB216C1

Model Name : RBHP-B216C

Serial number : N/A

Total page of Report : 12 pages (including this page)

Date of Incoming : December 03, 2020

Date of issue : December 17, 2020

SUMMARY

The equipment complies with the regulation; *FCC PART 15 SUBPART C Section 15.247 and FCC PART 15 SUBPART E Section 15.407*

This test report only contains the result of a single test of the sample supplied for the examination.


It is not a generally valid assessment of the features of the respective products of the mass-production.



Tested by
Hyung-Kwon, Oh / Manager
ONETECH Corp.



Reviewed by
Tae-Ho, Kim / Senior Manager
ONETECH Corp.



Approved by
Ki-Hong, Nam / General Manager
ONETECH Corp.

CONTENTS

	PAGE
1. VERIFICATION OF COMPLIANCE	4
2. GENERAL INFORMATION	5
2.1 PRODUCT DESCRIPTION.....	5
2.2 ALTERNATIVE TYPE(S)/MODEL(S); ALSO COVERED BY THIS TEST REPORT.....	8
3. EUT MODIFICATIONS.....	8
4. MAXIMUM PERMISSIBLE EXPOSURE.....	9
4.1 RF EXPOSURE CALCULATION	9
4.2 EUT DESCRIPTION.....	9
4.3 CALCULATED MPE SAFE DISTANCE.....	10
4.3.1 DATA for Antenna 0.....	10
4.3.2 DATA for Antenna 1.....	11
4.3.3 DATA for Intermodulation Transmit.....	12

Revision History

Rev. No.	Issue Report No.	Issued Date	Revisions	Section Affected
0	OT-20D-RWD-064	December 17, 2020	Initial Release	All

1. VERIFICATION OF COMPLIANCE

Applicant : LG Innotek Co., Ltd.
 Address : 26, Hanamsandan 5beon-ro Gwangsan-gu, Gwangju, 506-731, South Korea
 Contact Person : Jeong Inchang / Chief Research Engineer
 Telephone No. : +82-10-2326-9972
 FCC ID : YZP-RBHPB216C1
 Model Name : RBHP-B216C
 Brand Name : LG Innotek Co., Ltd.
 Serial Number : N/A
 Date : December 17, 2020

EQUIPMENT CLASS	DTS – DIGITAL TRNSMISSION SYSTEM Unlicensed National Information infrastructure(UNII)
E.U.T. DESCRIPTION	Modular Transmitter, BT(V4.2) + WLAN(802.11a/b/g/n/ac) 2x2 MIMO Module
THIS REPORT CONCERNS	Original Grant
MEASUREMENT PROCEDURES	ANSI C63.10: 2013
TYPE OF EQUIPMENT TESTED	Pre-Production
KIND OF EQUIPMENT AUTHORIZATION REQUESTED	Certification
EQUIPMENT WILL BE OPERATED UNDER FCC RULES PART(S)	FCC PART 15 SUBPART C Section 15.247 KDB 558074 D01 15.247 Meas Guidance v05r02 FCC PART 15 SUBPART E Section 15.407 789033 D02 General UNII Test Procedures New Rules v02r01
Modifications on the Equipment to Achieve Compliance	None
Final Test was Conducted On	3 m, Semi Anechoic Chamber

-. The above equipment was tested by ONETECH Corp. for compliance with the requirement set forth in the FCC Rules and Regulations. This said equipment in the configuration described in this report, shows the maximum emission levels emanating from equipment are within the compliance requirements.

2. GENERAL INFORMATION

2.1 Product Description

The LG Innotek Co., Ltd., Model RBHP-B216C (referred to as the EUT in this report) is a BT(V4.2) + WLAN(802.11a/b/g/n/ac) 2x2 MIMO Module. The product specification described herein was obtained from product data sheet or user’s manual.

DEVICE TYPE	BT(V4.2) + WLAN(802.11a/b/g/n/ac) 2x2 MIMO Module	
OPERATING FREQUENCY	Bluetooth LE	2 402 MHz ~ 2 480 MHz
	Bluetooth	2 402 MHz ~ 2 480 MHz
	WLAN 2.4 GHz	2 412 MHz ~ 2 462 MHz (802.11b/g/n(HT20))
	5 150 MHz ~ 5 250 MHz Band	5 180 MHz ~ 5 240 MHz (802.11a/n(HT20)/ac(VHT20))
		5 190 MHz ~ 5 230 MHz (802.11n(HT40)/ac(VHT40))
		5 210 MHz (802.11ac(VHT80))
	5 250 MHz ~ 5 350 MHz Band	5 260 MHz ~ 5 320 MHz (802.11a/n(HT20)/ac(VHT20))
		5 270 MHz ~ 5 310 MHz (802.11n(HT40)/ac(VHT40))
		5 290 MHz (802.11ac(VHT80))
	5 470 MHz ~ 5 725 MHz Band	5 500 MHz ~ 5 700 MHz (802.11a/n(HT20)/ac(VHT20))
		5 510 MHz ~ 5 670 MHz (802.11n(HT40)/ac(VHT40))
		5 530 MHz ~ 5 690 MHz (802.11ac(VHT80))
5 725 MHz ~ 5 850 MHz Band	5 745 MHz ~ 5 825 MHz (802.11a/n(HT20)/ac(VHT20))	
	5 755 MHz ~ 5 795 MHz (802.11n(HT40)/ac(VHT40))	
	5 775 MHz (802.11ac(VHT80))	
MODULATION TYPE	Bluetooth LE	GFSK for 1 Mbps
	Bluetooth	GFSK for 1 Mbps, $\pi/4$ -DQPSK for 2 Mbps, 8-DPSK for 3 Mbps
	WLAN 2.4 GHz	802.11b: DSSS Modulation(DBPSK/DQPSK/CCK)
		802.11g/n(HT20): OFDM Modulation(BPSK/QPSK/16QAM/64QAM)
WLAN 5 GHz	802.11a/n(HT20)/n(HT40)/ac(VHT80): OFDM Modulation(BPSK/QPSK/16QAM/64QAM)	

RF OUTPUT POWER	Bluetooth LE	1 Mbps	5.44 dBm	
	Bluetooth	1 Mbps	4.05 dBm	
		2 Mbps	1.45 dBm	
		3 Mbps	2.02 dBm	
	WLAN 2.4 GHz	Wi-Fi 802.11b (16.40 dBm) Wi-Fi 802.11g (15.84 dBm) Wi-Fi 802.11n(HT20) (15.05 dBm)		
	5 150 MHz ~ 5 250 MHz Band	Antenna 0	Wi-Fi 802.11a (13.96 dBm) Wi-Fi 802.11n(HT20) (11.80 dBm) Wi-Fi 802.11n(HT40) (10.14 dBm) Wi-Fi 802.11ac(HT80) (12.61 dBm)	
		Antenna 1	Wi-Fi 802.11a (13.92 dBm) Wi-Fi 802.11n(HT20) (10.62 dBm) Wi-Fi 802.11n(HT40) (10.54 dBm) Wi-Fi 802.11ac(HT80) (12.66 dBm)	
		Multiple Antenna	Wi-Fi 802.11n(HT20) (14.24 dBm) Wi-Fi 802.11n(HT40) (13.29 dBm) Wi-Fi 802.11ac(HT80) (12.96 dBm)	
	5 250 MHz ~ 5 350 MHz Band	Antenna 0	Wi-Fi 802.11a (14.42 dBm) Wi-Fi 802.11n(HT20) (14.61 dBm) Wi-Fi 802.11n(HT40) (14.10 dBm) Wi-Fi 802.11ac(HT80) (12.51 dBm)	
		Antenna 1	Wi-Fi 802.11a (14.41 dBm) Wi-Fi 802.11n(HT20) (14.54 dBm) Wi-Fi 802.11n(HT40) (13.56 dBm) Wi-Fi 802.11ac(HT80) (13.21 dBm)	
		Multiple Antenna	Wi-Fi 802.11n(HT20) (17.59 dBm) Wi-Fi 802.11n(HT40) (16.85 dBm) Wi-Fi 802.11ac(HT80) (15.88 dBm)	

RF OUTPUT POWER	5 470 MHz ~ 5 725 MHz Band	Antenna 0	Wi-Fi 802.11a (14.91 dBm) Wi-Fi 802.11n(HT20) (14.94 dBm) Wi-Fi 802.11n(HT40) (14.81 dBm) Wi-Fi 802.11ac(HT80) (12.99 dBm)
		Antenna 1	Wi-Fi 802.11a (14.62 dBm) Wi-Fi 802.11n(HT20) (14.97 dBm) Wi-Fi 802.11n(HT40) (14.32 dBm) Wi-Fi 802.11ac(HT80) (13.44dBm)
		Multiple Antenna	Wi-Fi 802.11n(HT20) (17.88 dBm) Wi-Fi 802.11n(HT40) (17.58 dBm) Wi-Fi 802.11ac(HT80) (16.23 dBm)
	5 725 MHz ~ 5 850 MHz Band	Antenna 0	Wi-Fi 802.11a (14.58 dBm) Wi-Fi 802.11n(HT20) (14.27 dBm) Wi-Fi 802.11n(HT40) (13.88 dBm) Wi-Fi 802.11ac(HT80) (12.80 dBm)
		Antenna 1	Wi-Fi 802.11a (14.74 dBm) Wi-Fi 802.11n(HT20) (14.84 dBm) Wi-Fi 802.11n(HT40) (14.69 dBm) Wi-Fi 802.11ac(HT80) (13.88 dBm)
		Multiple Antenna	Wi-Fi 802.11n(HT20) (17.57 dBm) Wi-Fi 802.11n(HT40) (17.31 dBm) Wi-Fi 802.11ac(HT80) (16.38 dBm)

ANTENNA TYPE	WLAN 2.4 GHz Band & WLAN 5 GHz Band		PCB Antenna	
	Bluetooth & WLAN 5 GHz Band		PIFA antenna	
ANTENNA GAIN	Bluetooth LE	2.20 dBi		
	Bluetooth	2.20 dBi		
	WLAN 2.4 GHz	4.80 dBi		
	5 150 MHz ~ 5 250 MHz Band	Antenna 0	5.40 dBi	
		Antenna 1	5.70 dBi	
		Multiple Antenna	8.56 dBi	
	5 250 MHz ~ 5 350 MHz Band	Antenna 0	5.60 dBi	
		Antenna 1	4.80 dBi	
		Multiple Antenna	8.23 dBi	
	5 470 MHz ~ 5 725 MHz Band	Antenna 0	5.70 dBi	
		Antenna 1	5.30 dBi	
		Multiple Antenna	8.51 dBi	
	5 725 MHz ~ 5 850 MHz Band	Antenna 0	5.20 dBi	
		Antenna 1	5.40 dBi	
		Multiple Antenna	8.31 dBi	
List of each Osc. or crystal Freq.(Freq. >= 1 MHz)		37.4 MHz		
DFS FUNCTION		Slave without radar detection		

2.2 Alternative type(s)/model(s); also covered by this test report.

-. None

3. EUT MODIFICATIONS

-. None

4. MAXIMUM PERMISSIBLE EXPOSURE

4.1 RF Exposure Calculation

According to the FCC rule 1.1310 table 1B, the limit for the maximum permissible RF exposure for an uncontrolled environment are $f/1500$ mW/cm² for the frequency range between 300 MHz and 1 500 MHz and 1.0 mW/cm² for the frequency range between 1 500 MHz and 100 000 MHz.

The electric field generated for a 1 mW/cm² exposure is calculated as follows:

$$E = \sqrt{(30 * P * G) / d}, \text{ and } S = E^2 / Z = E^2 / 377, \text{ because } 1 \text{ mW/cm}^2 = 10 \text{ W/m}^2$$

Where

S = Power density in mW/cm², Z = Impedance of free space, 377 Ω

E = Electric field strength in V/m, G = Numeric antenna gain, and d = distance in meter

Combining equations and rearranging the terms to express the distance as a function of the remaining variable

$$d = \sqrt{(30 * P * G) / (377 * 10 S)}$$

Changing to units of mW and cm, using P (mW) = P (W) / 1 000, d (cm) = 0.01 * d (m)

$$d = 0.282 * \sqrt{(P * G) / S}$$

Where

d = distance in cm, P = Power in mW, G = Numeric antenna gain, and S = Power density in mW/cm²

4.2 EUT Description

Kind of EUT	BT(V4.2) + WLAN(802.11a/b/g/n/ac) 2x2 MIMO Module
Device Category	<input type="checkbox"/> Portable (< 20 cm separation) <input type="checkbox"/> Mobile (> 20 cm separation) <input checked="" type="checkbox"/> Others
Exposure Evaluation Applied	<input checked="" type="checkbox"/> MPE <input type="checkbox"/> SAR <input type="checkbox"/> N/A

4.3 Calculated MPE Safe Distance

4.3.1 DATA for Antenna 0

According to above equation, the following result was obtained.

Operating Freq. Band (MHz)	Operating Mode	Target Power W/tolerance (dBm)	Max tune up power		Antenna Gain		Safe Distance (cm)	Power Density (mW/cm ²) @ 20 cm Separation	Limit (mW/cm ²)
			(dBm)	(mW)	Log	Linear			
2 402 ~ 2 480	BT_1 Mbps	4.0 ± 1.0	5.0	3.16	2.20	1.66	0.65	0.001 0	1.00
	BT_2 Mbps	1.0 ± 1.0	2.0	1.58			0.46	0.000 5	1.00
	BT_3 Mbps	2.0 ± 1.0	3.0	2.00			0.51	0.000 7	1.00
	BLE_1 Mbps	5.0 ± 1.0	6.0	3.98			0.72	0.001 3	1.00
5 150 ~ 5 250	802.11a	14.0 ± 1.0	15.0	31.62	5.40	3.47	2.95	0.021 8	1.00
	802.11n_HT20	10.8 ± 1.0	11.8	15.14			2.04	0.010 4	1.00
	802.11n_HT40	10.0 ± 1.0	11.0	12.59			1.86	0.008 7	1.00
	802.11ac80	10.0 ± 1.0	11.0	12.59			1.86	0.008 7	1.00
5 250 ~ 5 350	802.11a	14.0 ± 1.0	15.0	31.62	5.60	3.63	3.02	0.022 9	1.00
	802.11n_HT20	14.0 ± 1.0	15.0	31.62			3.02	0.022 9	1.00
	802.11n_HT40	14.0 ± 1.0	15.0	31.62			3.02	0.022 9	1.00
	802.11ac80	12.0 ± 1.0	13.0	19.95			2.40	0.014 4	1.00
5 470 ~ 5 725	802.11a	15.0 ± 1.0	16.0	39.81	5.70	3.72	3.43	0.029 4	1.00
	802.11n_HT20	15.0 ± 1.0	16.0	39.81			3.43	0.029 4	1.00
	802.11n_HT40	14.0 ± 1.0	15.0	31.62			3.06	0.023 4	1.00
	802.11ac80	13.0 ± 1.0	14.0	25.12			2.72	0.018 6	1.00
5 725 ~ 5 850	802.11a	14.0 ± 1.0	15.0	31.62	5.20	3.31	2.89	0.020 8	1.00
	802.11n_HT20	14.0 ± 1.0	15.0	31.62			2.89	0.020 8	1.00
	802.11n_HT40	13.0 ± 1.0	14.0	25.12			2.57	0.016 6	1.00
	802.11ac80	12.0 ± 1.0	13.0	19.95			2.29	0.013 2	1.00

According to above table, for 5 470 ~ 5 725 MHz Band(802.11 a), safe distance,

$$D = 0.282 * \sqrt{(39.81 * 3.72)/1.00} = 3.43 \text{ cm.}$$

For getting power density at 20 cm separation in above table, following formula was used.

$$S = P * G / (4\pi * R^2) = 39.81 * 3.72 / (4 * \pi * 20^2) = 0.029 4$$

Where:

S = Power Density,

P = Power input to the external antenna (Output power from the EUT antenna port (dBm) – cable loss (dB)),

G = Gain of Transmit Antenna (linear gain), R = Distance from Transmitting Antenna

4.3.2 DATA for Antenna 1

According to above equation, the following result was obtained.

Operating Freq. Band (MHz)	Operating Mode	Target Power W/tolerance (dBm)	Max tune up power		Antenna Gain		Safe Distance (cm)	Power Density (mW/cm ²) @ 20 cm Separation	Limit (mW/cm ²)
			(dBm)	(mW)	Log	Linear			
2 400 ~ 2 483.5	802.11b	16.0 ± 1.0	17.0	50.12	4.80	3.02	3.47	0.030 1	1.00
	802.11g	15.0 ± 1.0	16.0	39.81			3.09	0.023 9	1.00
	802.11n_HT20	15.0 ± 1.0	16.0	39.81			3.09	0.023 9	1.00
5 150 ~ 5 250	802.11a	14.0 ± 1.0	15.0	31.62	5.70	3.72	3.06	0.023 4	1.00
	802.11n_HT20	10.0 ± 1.0	11.0	12.59			1.93	0.009 3	1.00
	802.11n_HT40	10.0 ± 1.0	11.0	12.59			1.93	0.009 3	1.00
	802.11ac80	10.0 ± 1.0	11.0	12.59			1.93	0.009 3	1.00
5 250 ~ 5 350	802.11a	14.0 ± 1.0	15.0	31.62	4.80	3.02	2.76	0.019 0	1.00
	802.11n_HT20	14.0 ± 1.0	15.0	31.62			2.76	0.019 0	1.00
	802.11n_HT40	13.0 ± 1.0	14.0	25.12			2.46	0.015 1	1.00
	802.11ac80	13.0 ± 1.0	14.0	25.12			2.46	0.015 1	1.00
5 470 ~ 5 725	802.11a	14.0 ± 1.0	15.0	31.62	5.30	3.39	2.92	0.021 3	1.00
	802.11n_HT20	15.0 ± 1.0	16.0	39.81			3.28	0.026 9	1.00
	802.11n_HT40	14.0 ± 1.0	15.0	31.62			2.92	0.021 3	1.00
	802.11ac80	13.0 ± 1.0	14.0	25.12			2.60	0.016 9	1.00
5 725 ~ 5 850	802.11a	14.0 ± 1.0	15.0	31.62	5.40	3.47	2.95	0.021 8	1.00
	802.11n_HT20	14.0 ± 1.0	15.0	31.62			2.95	0.021 8	1.00
	802.11n_HT40	14.0 ± 1.0	15.0	31.62			2.95	0.021 8	1.00
	802.11ac80	13.0 ± 1.0	14.0	25.12			2.63	0.017 3	1.00

According to above table, for 5 470 ~ 5 725 MHz Band(802.11 n_HT20), safe distance,

$$D = 0.282 * \sqrt{(39.81 * 3.39)/1.00} = 3.28 \text{ cm.}$$

For getting power density at 20 cm separation in above table, following formula was used.

$$S = P * G / (4\pi * R^2) = 39.81 * 3.39 / (4 * \pi * 20^2) = 0.026 9$$

Where:

S = Power Density,

P = Power input to the external antenna (Output power from the EUT antenna port (dBm) – cable loss (dB)),

G = Gain of Transmit Antenna (linear gain), R = Distance from Transmitting Antenna

4.3.3 DATA for Intermodulation Transmit

According to above equation, the following result was obtained.

Operating Freq. Band (MHz)	Operating Mode	Target Power W/tolerance (dBm)	Max tune up power		Power Density (mW/cm ²) @ 20 cm Separation	Sum Power Density (mW/cm ²) @ 20 cm Separation	Limit (mW/cm ²)
			(dBm)	(mW)			
Bluetooth LE + WLAN 2 G	BLE_1 Mbps	5.0 ± 1.0	6.0	3.98	0.001 3	0.031 4	1.00
	802.11b	16.0 ± 1.0	17.0	50.12	0.030 1		
WLAN 2 G + WLAN 5 G (5 470 ~ 5 725)	802.11b	16.0 ± 1.0	17.0	50.12	0.030 1	0.059 5	1.00
	802.11a	15.0 ± 1.0	16.0	39.81	0.029 4		
WLAN 5 G (5 470 ~ 5 725) + WLAN 5 G (5 470 ~ 5 725)	802.11a	15.0 ± 1.0	16.0	39.81	0.029 4	0.056 3	1.00
	802.11n_HT20	15.0 ± 1.0	16.0	39.81	0.026 9		