

RF EXPOSURE EVALUATION REPORT

Product Name: IP Phone
Trade Mark: GRANDSTREAM
Model No.: GRP2614
HVIN: GRP2614V3
Report Number: 2403089982RFC-5
Test Standards: FCC 47 CFR Part 1 Subpart I
 RSS-102 Issue 6
FCC ID: YZZGRP2614V3
IC: 11964A-GRP2614V3
Test Result: PASS
Date of Issue: June 25, 2024

Prepared for:

Grandstream Networks, Inc.
126 Brookline Ave., 3rd Floor Boston, MA 02215, USA

Prepared by:

Shenzhen UnionTrust Quality and Technology Co., Ltd.
Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

TEL: +86-755-2823 0888
FAX: +86-755-2823 0886

Prepared by: David Chen
 David Chen
 Senior Project Engineer

Reviewed by: Henry Lu
 Henry Lu
 Team Leader

Approved by: Robben Chen
 Robben Chen
 Assistant Manager

Date: June 25, 2024

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Version

Version No.	Date	Description
V1.0	June 25, 2024	Original



Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-RSS102-V1.1

CONTENTS

1. GENERAL INFORMATION	4
1.1 CLIENT INFORMATION	4
1.2 EUT INFORMATION	4
1.3 PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD	4
1.4 OTHER INFORMATION	7
1.5 GENERAL DESCRIPTION OF APPLIED STANDARDS	8
1.6 DEVIATION FROM STANDARDS	8
1.7 ABNORMALITIES FROM STANDARD CONDITIONS	8
1.8 OTHER INFORMATION REQUESTED BY THE CUSTOMER	8
2. EQUIPMENT LIST	8
3. MPE EVALUATION	9
3.1 REFERENCE DOCUMENTS FOR EVALUATION	9
3.2 MPE COMPLIANCE REQUIREMENT	9
3.2.1 LIMITS	9
3.2.2 TEST PROCEDURE	10
3.3 MPE CALCULATION METHOD	10
3.4 MPE CALCULATION RESULTS	10
3.4.1 FOR WLAN	10
3.4.2 FOR BT	13
3.4.3 SIMULTANEOUS MULTI-BAND TRANSMISSION MPE ANALYSIS	14
APPENDIX 1 PHOTOS OF TEST SETUP	15
APPENDIX 2 PHOTOS OF EUT CONSTRUCTIONAL DETAILS	15

1. GENERAL INFORMATION

1.1 CLIENT INFORMATION

Applicant:	Grandstream Networks, Inc.
Address of Applicant:	126 Brookline Ave., 3rd Floor Boston, MA 02215, USA
Manufacturer:	Grandstream Networks, Inc.
Address of Manufacturer:	126 Brookline Ave., 3rd Floor Boston, MA 02215, USA

1.2 EUT INFORMATION

Product Name:	IP Phone		
Model No.:	GRP2614		
HVIN:	GRP2614V3		
Trade Mark:	GRANDSTREAM		
DUT Stage:	Identical Prototype		
EUT Supports Function: (Provided by the customer)	2.4 GHz ISM Band:	IEEE 802.11b/g/n/ax	
		Bluetooth V5.0	
	5 GHz U-NII Bands:	5 150 MHz to 5 250 MHz	IEEE 802.11a/n/ac/ax
		5 250 MHz to 5 350 MHz	IEEE 802.11a/n/ac/ax
		5 470 MHz to 5 725 MHz	IEEE 802.11a/n/ac/ax
	5 725 MHz to 5 850 MHz	IEEE 802.11a/n/ac/ax	
Sample Received Date:	March 8, 2024		

Remark: The above EUT's information was provided by customer. Please refer to the specifications or user's manual for more detailed description.

1.3 PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD

For BT_LE	
Frequency Band:	2400 MHz to 2483.5 MHz
Frequency Range:	2402 MHz to 2480 MHz
Bluetooth Version:	Bluetooth LE/2LE/LE Code
Type of Modulation:	GFSK
Number of Channels:	40
Channel Separation:	2 MHz
Antenna Type:	PCB Antenna
Antenna Gain: (Provided by the customer)	3.5 dBi
Maximum Peak Power:	6.65 dBm

For BT_EDR	
Frequency Band:	2400 MHz to 2483.5 MHz
Frequency Range:	2402 MHz to 2480 MHz
Bluetooth Version:	Bluetooth BR + EDR
Modulation Technique:	Frequency Hopping Spread Spectrum(FHSS)
Type of Modulation:	GFSK, $\pi/4$ DQPSK, 8DPSK
Number of Channels:	79
Channel Separation:	1 MHz
Antenna Type:	PCB Antenna

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-RSS102-V1.1

Antenna Gain: (Provided by the customer)	3.5 dBi
Maximum Peak Power:	13.28 dBm

For 2.4 GHz ISM Band of Wi-Fi	
Frequency Band:	2400 MHz to 2483.5 MHz
Frequency Range:	2412 MHz to 2462 MHz
Support Standards:	IEEE 802.11b/g/n-HT20/n-HT40/ax-HE20/ax-HE40
Type of Modulation:	IEEE 802.11b: DSSS(CCK, DQPSK, DBPSK) IEEE 802.11g: OFDM(64-QAM, 16-QAM, QPSK, BPSK) IEEE 802.11n-HT20: OFDM(64-QAM, 16-QAM, QPSK, BPSK) IEEE 802.11n-HT40: OFDM(64-QAM, 16-QAM, QPSK, BPSK) IEEE 802.11ax:OFDM/ OFDMA (1024QAM, 256QAM, 64QAM, 16QAM, QPSK, BPSK)
Data Rate:	IEEE 802.11b: Up to 11 Mbps IEEE 802.11g: Up to 54 Mbps IEEE 802.11n-HT20: Up to MCS7 IEEE 802.11n-HT40: Up to MCS7 IEEE 802.11ax-HE20/ HE40: Up to MCS11
Number of Channels:	IEEE 802.11b: 11 IEEE 802.11g: 11 IEEE 802.11n-HT20/ax-HE20: 11 IEEE 802.11n-HT40/ax-HE40: 9
Channel Separation:	5 MHz
Antenna Type:	PCB Antenna
Antenna Gain: (Provided by the customer)	3.5 dBi
Maximum Peak Power:	IEEE 802.11b: 19.42 dBm IEEE 802.11g: 25.72 dBm IEEE 802.11n-HT20: 25.53 dBm IEEE 802.11n-HT40: 25.18 dBm IEEE 802.11ax-HE20: 26.33 dBm IEEE 802.11ax-HE40: 25.41 dBm
Maximum e.i.r.p	IEEE 802.11b: 22.92 dBm IEEE 802.11g: 29.22 dBm IEEE 802.11n-HT20: 29.03 dBm IEEE 802.11n-HT40: 28.68 dBm IEEE 802.11ax-HE20: 29.83 dBm IEEE 802.11ax-HE40: 28.91 dBm

For 5 GHz U-NII Bands of Wi-Fi	
Frequency Bands:	5150 MHz to 5250 MHz (U-NII-1)
	5250 MHz to 5350 MHz (U-NII-2A)
	5470 MHz to 5725 MHz (U-NII-2C)
	5 725 MHz to 5 850 MHz (U-NII-3)
Frequency Ranges:	5180 MHz to 5240 MHz
	5260 MHz to 5320 MHz
	5500 MHz to 5720 MHz
	5745 MHz to 5825 MHz
Support Standards:	IEEE 802.11a/n/ac/ax
TPC Function:	Not Support
DFS Operational mode:	Slave without radar Interference detection function
Type of Modulation:	IEEE 802.11a: OFDM(64QAM, 16QAM, QPSK, BPSK)

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-RSS102-V1.1

	IEEE 802.11n: OFDM(64QAM, 16QAM, QPSK, BPSK)				
	IEEE 802.11ac: OFDM(256QAM, 64QAM, 16QAM, QPSK, BPSK)				
	IEEE 802.11ax: OFDM/OFDMA (1024QAM, 256QAM, 64QAM, 16QAM, QPSK, BPSK)				
Channel Spacing:	IEEE 802.11a/n-HT20/ac-VHT20/ax-HE20: 20 MHz				
	IEEE 802.11n-HT40/ac-VHT40/ax-HE40: 40 MHz				
Data Rate:	IEEE 802.11a: Up to 54 Mbps				
	IEEE 802.11n-HT20: Up to MCS7				
	IEEE 802.11n-HT40: Up to MCS7				
	IEEE 802.11ac-VHT20: Up to MCS8				
	IEEE 802.11ac-VHT40: Up to MCS9				
	IEEE 802.11ax-HE20/HE40: Up to MCS11				
Number of Channels:	5150 MHz to 5250 MHz: 4 for IEEE 802.11a/n-HT20/ac-VHT20/ax-HE20 2 for IEEE 802.11n-HT40/ac-VHT40/ax-HE40				
	5250 MHz to 5350 MHz: 4 for IEEE 802.11a/n-HT20/ac-VHT20/ax-HE20 2 for IEEE 802.11n-HT40/ac-VHT40/ax-HE40				
	5470 MHz to 5725 MHz: 12 for IEEE 802.11a/n-HT20/ac-VHT20/ax-HE20 6 for IEEE 802.11n-HT40/ac-VHT40/ax-HE40				
	5725 MHz to 5850 MHz: 5 for IEEE 802.11a/n-HT20/ac-VHT20/ax-HE20 2 for IEEE 802.11n-HT40/ac-VHT40/ax-HE40				
Antenna Type:	PCB Antenna				
Antenna Gain: (Provided by the customer)	5150 MHz to 5250 MHz: 4.5 dBi				
	5250 MHz to 5350 MHz: 4.5 dBi				
	5470 MHz to 5725 MHz: 4.5 dBi				
	5725 MHz to 5850 MHz: 4.5 dBi				
Maximum conducted output power (dBm):		U-NII-1	U-NII-2A	U-NII-2C	U-NII-3
	IEEE 802.11a:	18.08	18.05	16.98	16.57
	IEEE 802.11n-HT20:	18.27	18.16	17.11	16.70
	IEEE 802.11n-HT40:	17.94	17.90	17.40	16.67
	IEEE 802.11ac-VHT20	18.36	18.20	17.12	16.70
	IEEE 802.11ac-VHT40	17.87	17.84	17.38	16.63
	IEEE 802.11ax-HE20	18.36	18.25	17.20	16.72
	IEEE 802.11ax-HE40	17.98	17.91	17.45	16.80
Maximum EIRP (dBm):		U-NII-1	U-NII-2A	U-NII-2C	U-NII-3
	IEEE 802.11a:	22.58	22.55	21.48	21.07
	IEEE 802.11n-HT20:	22.77	22.66	21.61	21.20
	IEEE 802.11n-HT40:	22.44	22.40	21.90	21.17
	IEEE 802.11ac-VHT20	22.86	22.70	21.62	21.20
	IEEE 802.11ac-VHT40	22.37	22.34	21.88	21.13
	IEEE 802.11ax-HE20	22.86	22.75	21.70	21.22
	IEEE 802.11ax-HE40	22.48	22.41	21.95	21.30

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-RSS102-V1.1

1.4 OTHER INFORMATION

Test channels for BT_LE				
Type of Modulation	Tx/Rx Frequency	Test RF Channel Lists		
GFSK	2402 MHz to 2480 MHz	Lowest(L)	Middle(M)	Highest(H)
		Channel 0	Channel 19	Channel 39
		2402 MHz	2440 MHz	2480 MHz

Test channels for BT_EDR				
Mode	Tx/Rx Frequency	Test RF Channel Lists		
GFSK (DH1, DH3, DH5)	2402 MHz to 2480 MHz	Lowest(L)	Middle(M)	Highest(H)
		Channel 0	Channel 39	Channel 78
$\pi/4$ DQPSK (DH1, DH3, DH5)	2402 MHz to 2480 MHz	2402 MHz	2441 MHz	2480 MHz
		Channel 0	Channel 39	Channel 78
8DPSK (DH1, DH3, DH5)	2402 MHz to 2480 MHz	2402 MHz	2441 MHz	2480 MHz
		Channel 0	Channel 39	Channel 78

Test channels for 2.4 GHz ISM Band of Wi-Fi				
Mode	Tx/Rx Frequency	Test RF Channel Lists		
IEEE 802.11b	2412 MHz to 2462 MHz	Lowest(L)	Middle(M)	Highest(H)
		Channel 1	Channel 6	Channel 11
IEEE 802.11g	2412 MHz to 2462 MHz	2412 MHz	2437 MHz	2462 MHz
		Channel 1	Channel 6	Channel 11
IEEE 802.11n-HT20 IEEE 802.11ax-HE20	2412 MHz to 2462 MHz	2412 MHz	2437 MHz	2462 MHz
		Channel 1	Channel 6	Channel 11
IEEE 802.11n-HT40 IEEE 802.11ax-HE40	2422 MHz to 2452 MHz	2422 MHz	2437 MHz	2452 MHz
		Channel 3	Channel 7	Channel 9

Test channels for 5 GHz U-NII Bands of Wi-Fi					
Mode	Tx/Rx Frequency	Test RF Channel Lists			
IEEE 802.11a	5150 MHz to 5250 MHz	Lowest(L)	Middle(M)	Highest(H)	Straddle band
		Channel 36	Channel 44	Channel 48	--
IEEE 802.11n-HT20	5250 MHz to 5350 MHz	5180 MHz	5220 MHz	5240 MHz	--
		Channel 52	Channel 60	Channel 64	--
IEEE 802.11ac-VHT20	5470 MHz to 5725 MHz	5260 MHz	5300 MHz	5320 MHz	--
		Channel 100	Channel 116	Channel 140	Channel 144
IEEE 802.11ax-HE20	5725 MHz to 5850 MHz	5500 MHz	5580 MHz	5700 MHz	5720 MHz
		Channel 149	Channel 157	Channel 165	--
IEEE 802.11n-HT40	5150 MHz to 5250 MHz	5745 MHz	5785 MHz	5825 MHz	--
		Channel 38	--	Channel 46	--
IEEE 802.11ac-VHT40	5250 MHz to 5350 MHz	5190 MHz	--	5230 MHz	--
		Channel 54	--	Channel 62	--
IEEE 802.11ax-HE40	5470 MHz to 5725 MHz	5270 MHz	--	5310 MHz	--
		Channel 102	Channel 110	Channel 134	Channel 142

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-RSS102-V1.1

		5510 MHz	5550 MHz	5670 MHz	5710 MHz
	5725 MHz to 5850 MHz	Channel 151	--	Channel 159	--
		5755 MHz	--	5795 MHz	--
		--	5775 MHz	--	--

1.5 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF product, according to the specifications of the manufacturers. It must comply with the requirements of the following standards:

FCC 47 CFR Part 1 Subpart I
RSS-102 Issue 6

All test items have been performed and recorded as per the above standards

1.6 DEVIATION FROM STANDARDS

None.

1.7 ABNORMALITIES FROM STANDARD CONDITIONS

None.

1.8 OTHER INFORMATION REQUESTED BY THE CUSTOMER

None.

2. EQUIPMENT LIST

Please refer to the RF test report.

3. MPE EVALUATION

3.1 REFERENCE DOCUMENTS FOR EVALUATION

No.	Identity	Document Title
1	FCC 47 CFR Part 1 Subpart I	PROCEDURES IMPLEMENTING THE NATIONAL ENVIRONMENTAL POLICY ACT OF 1969
2	RSS-102 Issue 6	Radio Frequency (RF) Exposure Compliance of Radiocommunication Apparatus (All Frequency Bands)
3	KDB 447498 D01 General RF Exposure Guidance v06	RF EXPOSURE PROCEDURES AND EQUIPMENT AUTHORIZATION POLICIES FOR MOBILE AND PORTABLE DEVICES

3.2 MPE COMPLIANCE REQUIREMENT

3.2.1 Limits

3.2.1.1 FCC 47 CFR Part 1 Subpart I

According to §1.1307(b)(1), system operating under the provisions of this section shall be operating in a manner that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure.

Limits for Occupational / Controlled Exposure

Frequency range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f)*	6
30-300	61.4	0.163	1.0	6
300-1500	/	/	F/300	6
1500-100000	/	/	5	6

Limits for General Population / Uncontrolled Exposure

Frequency range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	F/1500	30
1500-100000	/	/	1	30

Note: f = frequency in MHz; * = Plane-wave equivalent power density.

3.2.1.2 RSS-102 Issue 6

According to RSS-102 Issue 6, field reference level (FRL) exposure evaluation is required if the separation distance between the user and/or bystander and the device's radiating element is greater than 20 cm (i.e. mobile devices), except when the device operates as follows:

- below 20 MHz and the source-based, time-averaged maximum EIRP of the device is equal to or less than 1 W (adjusted for tune-up tolerance)
- at or above 20 MHz and below 48 MHz and the source-based, time-averaged maximum EIRP of the device is equal to or less than $4.49/f^{0.5}$ W (adjusted for tune-up tolerance), where f is in MHz
- at or above 48 MHz and below 300 MHz and the source-based, time-averaged maximum EIRP of the device is equal to or less than 0.6 W (adjusted for tune-up tolerance)
- at or above 300 MHz and below 6 GHz and the source-based, time-averaged maximum EIRP of the device is equal to or less than $1.31 \times 10^{-2} f^{0.6834}$ W (adjusted for tune-up tolerance), where f is in MHz
- at or above 6 GHz and the source-based, time-averaged maximum EIRP of the device is equal to or less than 5 W (adjusted for tune-up tolerance)

In these cases, the information contained in the RF exposure technical brief may be limited to information that demonstrates how the EIRP was derived.

3.2.2 Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

3.3 MPE CALCULATION METHOD

FCC 47 CFR Part 1 Subpart I

$$S = PG/4\pi R^2 = EIRP/4\pi R^2$$

S = power density (in appropriate units, e.g., mw/cm²)

P = power input to the antenna (in appropriate units, e.g., mw)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor is normally numeric gain.

R = 20cm, distance to the center of radiation of the antenna (in appropriate units, e.g., cm)

3.4 MPE CALCULATION RESULTS

Note: For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.

3.4.1 For WLAN

For Wi-Fi function, operating at 2412MHz to 2462 MHz for IEEE802.11b/g/n and
operating at 5150 MHz to 5250 MHz for IEEE802.11a/n/ac/ax and
operating at 5250 MHz to 5350 MHz for IEEE802.11a/n/ac/ax and
operating at 5470 MHz to 5725 MHz for IEEE802.11a/n/ac/ax and
operating at 5725 MHz to 5850 MHz for IEEE802.11a/n/ac/ax.

3.4.1.1 Antenna Type:

PCB Antenna

3.4.1.2 Antenna Gain:

2412MHz to 2462 MHz: 3.5 dBi

5150 MHz to 5250 MHz: 4.5 dBi

5250 MHz to 5350 MHz: 4.5 dBi

5470 MHz to 5725 MHz: 4.5 dBi

5725 MHz to 5850 MHz: 4.5 dBi

3.4.1.3 Results for FCC 47 CFR Part 1 Subpart I

Operating Mode	Freq.	Declared maximum conducted output power	Max. positive tolerance according manufacturer	Antenna Gain	Calculated maximum EIRP	Declared maximum EIRP	MPE Limit	MPE Value
	(MHz)	(dBm)	(dBm)	(dBi)	(dBm)	(mW)	(mw/cm ²)	
IEEE 802.11b	2412	19	1	3.5	23.5	223.8721	1	0.0445
	2437	18	1	3.5	22.5	177.8279	1	0.0354
	2462	18	1	3.5	22.5	177.8279	1	0.0354
IEEE 802.11g	2412	25	1	3.5	29.5	891.2509	1	0.1773
	2437	25	1	3.5	29.5	891.2509	1	0.1773
	2462	25	1	3.5	29.5	891.2509	1	0.1773
IEEE 802.11n-HT20 IEEE 802.11ax-HE20	2412	26	1	3.5	30.5	1122.0185	1	0.2232
	2437	26	1	3.5	30.5	1122.0185	1	0.2232
	2462	25	1	3.5	29.5	891.2509	1	0.1773
IEEE 802.11n-HT40 IEEE 802.11ax-HE40	2422	25	1	3.5	29.5	891.2509	1	0.1773
	2437	25	1	3.5	29.5	891.2509	1	0.1773
	2452	25	1	3.5	29.5	891.2509	1	0.1773
IEEE 802.11a	5180	18	1	4.5	23.5	223.8721	1	0.0445
	5220	17	1	4.5	22.5	177.8279	1	0.0354
	5240	17	1	4.5	22.5	177.8279	1	0.0354
	5260	18	1	4.5	23.5	223.8721	1	0.0445
	5300	18	1	4.5	23.5	223.8721	1	0.0445
	5320	17	1	4.5	22.5	177.8279	1	0.0354
	5500	16	1	4.5	21.5	141.2538	1	0.0281
	5580	16	1	4.5	21.5	141.2538	1	0.0281
	5700	16	1	4.5	21.5	141.2538	1	0.0281
	5720	16	1	4.5	21.5	141.2538	1	0.0281
	5745	16	1	4.5	21.5	141.2538	1	0.0281
	5785	16	1	4.5	21.5	141.2538	1	0.0281
	5825	15	1	4.5	20.5	112.2018	1	0.0223
IEEE 802.11n-HT20 802.11ac-VHT20 IEEE 802.11ax-HE20	5180	18	1	4.5	23.5	223.8721	1	0.0445
	5220	17	1	4.5	22.5	177.8279	1	0.0354
	5240	17	1	4.5	22.5	177.8279	1	0.0354
	5260	18	1	4.5	23.5	223.8721	1	0.0445
	5300	18	1	4.5	23.5	223.8721	1	0.0445
	5320	17	1	4.5	22.5	177.8279	1	0.0354
	5500	17	1	4.5	22.5	177.8279	1	0.0354
	5580	16	1	4.5	21.5	141.2538	1	0.0281
	5700	16	1	4.5	21.5	141.2538	1	0.0281
	5720	16	1	4.5	21.5	141.2538	1	0.0281
	5745	16	1	4.5	21.5	141.2538	1	0.0281
	5785	16	1	4.5	21.5	141.2538	1	0.0281
	5825	15	1	4.5	20.5	112.2018	1	0.0223
IEEE 802.11n-HT40 IEEE 802.11ac-VHT40 IEEE 802.11ax-HE40	5190	17	1	4.5	22.5	177.8279	1	0.0354
	5230	17	1	4.5	22.5	177.8279	1	0.0354
	5270	17	1	4.5	22.5	177.8279	1	0.0354
	5310	16	1	4.5	21.5	141.2538	1	0.0281
	5510	16	1	4.5	21.5	141.2538	1	0.0281
	5550	16	1	4.5	21.5	141.2538	1	0.0281
	5670	17	1	4.5	22.5	177.8279	1	0.0354
	5710	16	1	4.5	21.5	141.2538	1	0.0281
	5755	16	1	4.5	21.5	141.2538	1	0.0281
	5795	16	1	4.5	21.5	141.2538	1	0.0281

3.4.1.4 Results for RSS-102 Issue 6

Operating Mode	Freq.	Declared maximum conducted output power	Max. positive tolerance according manufacturer	Antenna Gain	Calculated maximum EIRP	Declared maximum EIRP	Declare Limit			
	(MHz)	(dBm)		(dBi)	(dBm)	(W)	(W)			
SSO	IEEE 802.11b	2412	19	1	3.5	23.5	0.2239	2.6840		
		2437	18	1	3.5	22.5	0.1778	2.7030		
		2462	18	1	3.5	22.5	0.1778	2.7219		
	IEEE 802.11g	2412	25	1	3.5	29.5	0.8913	2.6840		
		2437	25	1	3.5	29.5	0.8913	2.7030		
		2462	25	1	3.5	29.5	0.8913	2.7219		
	IEEE 802.11n-HT20 IEEE 802.11ax-HE20	2412	26	1	3.5	30.5	1.1220	2.6840		
		2437	26	1	3.5	30.5	1.1220	2.7030		
		2462	25	1	3.5	29.5	0.8913	2.7219		
	IEEE 802.11n-HT40 IEEE 802.11ax-HE40	2422	25	1	3.5	29.5	0.8913	2.6916		
		2437	25	1	3.5	29.5	0.8913	2.7030		
		2452	25	1	3.5	29.5	0.8913	2.7144		
SSO	IEEE 802.11a	5180	18	1	4.5	23.5	0.2239	4.5253		
		5220	17	1	4.5	22.5	0.1778	4.5491		
		5240	17	1	4.5	22.5	0.1778	4.5610		
		5260	18	1	4.5	23.5	0.2239	4.5729		
		5300	18	1	4.5	23.5	0.2239	4.5966		
		5320	17	1	4.5	22.5	0.1778	4.6085		
		5500	16	1	4.5	21.5	0.1413	4.7145		
		5580	16	1	4.5	21.5	0.1413	4.7613		
		5700	16	1	4.5	21.5	0.1413	4.8310		
		5720	16	1	4.5	21.5	0.1413	4.8426		
		5745	16	1	4.5	21.5	0.1413	4.8570		
		5785	16	1	4.5	21.5	0.1413	4.8801		
		5825	15	1	4.5	20.5	0.1122	4.9031		
		SSO	IEEE 802.11n-HT20 IEEE 802.11ac-VHT20 IEEE 802.11ax-HE20	5180	18	1	4.5	23.5	0.2239	4.5253
				5220	17	1	4.5	22.5	0.1778	4.5491
5240	17			1	4.5	22.5	0.1778	4.5610		
5260	18			1	4.5	23.5	0.2239	4.5729		
5300	18			1	4.5	23.5	0.2239	4.5966		
5320	17			1	4.5	22.5	0.1778	4.6085		
5500	17			1	4.5	22.5	0.1778	4.7145		
5580	16			1	4.5	21.5	0.1413	4.7613		
5700	16			1	4.5	21.5	0.1413	4.8310		
5720	16			1	4.5	21.5	0.1413	4.8426		
5745	16			1	4.5	21.5	0.1413	4.8570		
5785	16			1	4.5	21.5	0.1413	4.8801		
5825	15	1	4.5	20.5	0.1122	4.9031				
SSO	IEEE 802.11n-HT40 802.11ac-VHT40 IEEE 802.11ax-HE40	5190	17	1	4.5	22.5	0.1778	4.5312		
		5230	17	1	4.5	22.5	0.1778	4.5551		
		5270	17	1	4.5	22.5	0.1778	4.5789		
		5310	16	1	4.5	21.5	0.1413	4.6026		
		5510	16	1	4.5	21.5	0.1413	4.7204		
		5550	16	1	4.5	21.5	0.1413	4.7437		
		5670	17	1	4.5	22.5	0.1778	4.8136		
		5710	16	1	4.5	21.5	0.1413	4.8368		
		5755	16	1	4.5	21.5	0.1413	4.8628		
5795	16	1	4.5	21.5	0.1413	4.8859				

3.4.2 For BT

For BT_LE/2LE/ LE Code function, operating at 2402MHz to 2480 MHz for GFSK and
 For BT_EDR function, operating at 2402MHz to 2480 MHz for GFSK, $\pi/4$ DQPSK, 8DPSK

3.4.2.1 Antenna Type:

PCB Antenna

3.4.2.2 Antenna Gain:

2402MHz to 2480 MHz: 3.5 dBi

3.4.2.3 Results for FCC 47 CFR Part 1 Subpart I

Operating Mode	Freq.	Declared maximum conducted output power	Max. positive tolerance according manufacturer	Antenna Gain	Calculated maximum EIRP	Declared maximum EIRP	MPE Limit	MPE Value
	(MHz)	(dBm)	(dBm)	(dBm)	(dBm)	(mW)	(mW /cm ²)	
LE/2LE/ LE Code	2402-2480	6.65	1	3.5	11.15	13.0317	1	0.0026
EDR	2402-2480	13.28	2.5	3.5	19.28	84.7227	1	0.0169

3.4.2.4 Results for RSS-102 Issue 6

Operating Mode	Freq.	Declared maximum conducted output power	Max. positive tolerance according manufacturer	Antenna Gain	Calculated maximum EIRP	Declared maximum EIRP	Limit
	(MHz)	(dBm)	(dBm)	(dBm)	(dBm)	(W)	(W)
LE/2LE/ LE Code	2402-2480	6.65	1	3.5	11.15	0.0130	2.6764
EDR	2402-2480	13.28	2.5	3.5	19.28	0.0847	2.6764

3.4.3 Simultaneous Multi-band Transmission MPE Analysis

3.4.4.1 List of Mode for Simultaneous Multi-band Transmission

No.	Configurations	Support/Not Support
1	2.4G_WLAN + BT	Support
2	5G_WLAN + BT	Support
3	2.4G_WLAN + 5G_WLAN	Not Support

3.4.4.1 Results for transmit simultaneously

FCC 47 CFR Part 1 Subpart I

No.	Configurations	Maximum MPE Value			Limits
		WLAN (mw/cm ²)	BT (mw/cm ²)	Transmit simultaneously	
1	2.4G_WLAN + BT	0.2232	0.0169	0.2401	1
2	5G_WLAN + BT	0.0445	0.0169	0.0614	1

Note:

According to KDB 447498 D01 General RF Exposure Guidance v06, At the transmit simultaneously calculation method is as follows:

$$\text{Transmit simultaneously MPE} = \Sigma \text{ of MPE ratios}$$

$$\text{MPE ratios} = \text{Field strengths or power density} / \text{MPE limit at the test frequency}$$

RSS-102 Issue 6

No.	Configurations	Declared maximum EIRP		Maximum MPE Value	Limits
		WLAN	BT		
		W	W	Transmit simultaneously	
1	2.4G_WLAN + BT	1.1220	0.0847	0.4496	1
2	5G_WLAN + BT	0.2239	0.0847	0.0811	1

Note:

According to KDB 447498 D01 General RF Exposure Guidance v06, At the transmit simultaneously calculation method is as follows:

$$\text{Transmit simultaneously MPE} = \Sigma \text{ of MPE ratios}$$

$$\text{MPE ratios} = \text{Field strengths or power density} / \text{MPE limit at the test frequency}$$

APPENDIX 1 PHOTOS OF TEST SETUP

N/A

APPENDIX 2 PHOTOS OF EUT CONSTRUCTIONAL DETAILS

Refer to Appendix 2 for EUT external and internal Photos.

*** End of Report ***

The test report is effective only with both signature and specialized stamp. The result(s) shown in this report refer only to the sample(s) tested. Without written approval of UnionTrust, this report can't be reproduced except in full.
