



Certificate #4312.01

RF EXPOSURE EVALUATION REPORT

Product Name: IP Phone
Trade Mark: GRANDSTREAM
Model No.: GRP2634
HVIN: GRP2634V2
Report Number: 24032510282RFC-5
Test Standards: FCC 47 CFR Part 1 Subpart I
 RSS-102 Issue 6
FCC ID: YZZGRP2634V2
IC: 11964A-GRP2634V2
Test Result: PASS
Date of Issue: July 24, 2024

Prepared for:

Grandstream Networks, Inc.
126 Brookline Ave., 3rd Floor Boston, MA 02215, USA

Prepared by:

Shenzhen UnionTrust Quality and Technology Co., Ltd.
Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

TEL: +86-755-2823 0888
FAX: +86-755-2823 0886

Prepared by: David Chen
 David Chen
 Senior Project Engineer

Reviewed by: Henry Lu
 Henry Lu
 Team Leader

Approved by: Robben Chen
 Robben Chen
 Assistant Manager

Date: July 24, 2024

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Version

Version No.	Date	Description
V1.0	July 24, 2024	Original



CONTENTS

1. GENERAL INFORMATION	4
1.1 CLIENT INFORMATION	4
1.2 EUT INFORMATION	4
1.3 PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD	4
1.4 OTHER INFORMATION	7
1.5 GENERAL DESCRIPTION OF APPLIED STANDARDS	8
1.6 DEVIATION FROM STANDARDS	8
1.7 ABNORMALITIES FROM STANDARD CONDITIONS	8
1.8 OTHER INFORMATION REQUESTED BY THE CUSTOMER	8
2. EQUIPMENT LIST	8
3. MPE EVALUATION	9
3.1 REFERENCE DOCUMENTS FOR EVALUATION	9
3.2 MPE COMPLIANCE REQUIREMENT	9
3.2.1 LIMITS	9
3.2.2 TEST PROCEDURE	10
3.3 MPE CALCULATION METHOD	10
3.4 MPE CALCULATION RESULTS	10
3.4.1 FOR WLAN	10
3.4.2 FOR BT	14
3.4.3 SIMULTANEOUS MULTI-BAND TRANSMISSION MPE ANALYSIS	15
APPENDIX 1 PHOTOS OF TEST SETUP	16
APPENDIX 2 PHOTOS OF EUT CONSTRUCTIONAL DETAILS	16

1. GENERAL INFORMATION

1.1 CLIENT INFORMATION

Applicant:	Grandstream Networks, Inc.
Address of Applicant:	126 Brookline Ave., 3rd Floor Boston, MA 02215, USA
Manufacturer:	Grandstream Networks, Inc.
Address of Manufacturer:	126 Brookline Ave., 3rd Floor Boston, MA 02215, USA

1.2 EUT INFORMATION

Product Name:	IP Phone		
Model No.:	GRP2634		
HVIN:	GRP2634V2		
Trade Mark:	GRANDSTREAM		
DUT Stage:	Identical Prototype		
EUT Supports Function: (Provided by the customer)	2.4 GHz ISM Band:	IEEE 802.11b/g/n/ax	
		Bluetooth V5.0	
	5 GHz U-NII Bands:	5 150 MHz to 5 250 MHz	IEEE 802.11a/n/ac/ax
		5 250 MHz to 5 350 MHz	IEEE 802.11a/n/ac/ax
		5 470 MHz to 5 725 MHz	IEEE 802.11a/n/ac/ax
	5 725 MHz to 5 850 MHz	IEEE 802.11a/n/ac/ax	
Sample Received Date:	March 23, 2024		

Remark: The above EUT's information was provided by customer. Please refer to the specifications or user's manual for more detailed description.

1.3 PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD

For BT_LE	
Frequency Band:	2400 MHz to 2483.5 MHz
Frequency Range:	2402 MHz to 2480 MHz
Bluetooth Version:	Bluetooth LE/2LE/LE Code
Type of Modulation:	GFSK
Number of Channels:	40
Channel Separation:	2 MHz
Antenna Type:	Dipole Antenna
Antenna Gain: (Provided by the customer)	3.0 dBi
Maximum Peak Power:	8.33 dBm

For BT_EDR	
Frequency Band:	2400 MHz to 2483.5 MHz
Frequency Range:	2402 MHz to 2480 MHz
Bluetooth Version:	Bluetooth BR + EDR
Modulation Technique:	Frequency Hopping Spread Spectrum(FHSS)
Type of Modulation:	GFSK, $\pi/4$ DQPSK, 8DPSK
Number of Channels:	79
Channel Separation:	1 MHz
Antenna Type:	Dipole Antenna

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-RSS102-V1.1

Antenna Gain: (Provided by the customer)	3.0 dBi
Maximum Peak Power:	10.138 dBm

For 2.4 GHz ISM Band of Wi-Fi	
Frequency Band:	2400 MHz to 2483.5 MHz
Frequency Range:	2412 MHz to 2462 MHz
Support Standards:	IEEE 802.11b/g/n-HT20/n-HT40/ax-HE20/ax-HE40
Type of Modulation:	IEEE 802.11b: DSSS(CCK, DQPSK, DBPSK) IEEE 802.11g: OFDM(64-QAM, 16-QAM, QPSK, BPSK) IEEE 802.11n-HT20: OFDM(64-QAM, 16-QAM, QPSK, BPSK) IEEE 802.11n-HT40: OFDM(64-QAM, 16-QAM, QPSK, BPSK) IEEE 802.11ax:OFDM/ OFDMA (1024QAM, 256QAM, 64QAM, 16QAM, QPSK, BPSK)
Data Rate:	IEEE 802.11b: Up to 11 Mbps IEEE 802.11g: Up to 54 Mbps IEEE 802.11n-HT20: Up to MCS7 IEEE 802.11n-HT40: Up to MCS7 IEEE 802.11ax-HE20/ HE40: Up to MCS11
Number of Channels:	IEEE 802.11b: 11 IEEE 802.11g: 11 IEEE 802.11n-HT20/ax-HE20: 11 IEEE 802.11n-HT40/ax-HE40: 7
Channel Separation:	5 MHz
Antenna Type:	Dipole Antenna
Antenna Gain: (Provided by the customer)	3.0 dBi
Maximum EIRP (dBm):	IEEE 802.11b: 22.59 dBm IEEE 802.11g: 30.22 dBm IEEE 802.11n-HT20: 30.21 dBm IEEE 802.11n-HT40: 30.28 dBm IEEE 802.11ax-HE20: 29.97 dBm IEEE 802.11ax-HE40: 29.48 dBm
Maximum conducted output power:	IEEE 802.11b: 19.59 dBm IEEE 802.11g: 27.22 dBm IEEE 802.11n-HT20: 27.21 dBm IEEE 802.11n-HT40: 27.28 dBm IEEE 802.11ax-HE20: 26.97 dBm IEEE 802.11ax-HE40: 26.48 dBm

For 5 GHz U-NII Bands of Wi-Fi	
Frequency Bands:	5150 MHz to 5250 MHz (U-NII-1)
	5250 MHz to 5350 MHz (U-NII-2A)
	5470 MHz to 5725 MHz (U-NII-2C)
	5 725 MHz to 5 850 MHz (U-NII-3)
Frequency Ranges:	5180 MHz to 5240 MHz
	5260 MHz to 5320 MHz
	5500 MHz to 5720 MHz
	5745 MHz to 5825 MHz
Support Standards:	IEEE 802.11a/n/ac/ax
TPC Function:	Not Support
DFS Operational mode:	Slave without radar Interference detection function
Type of Modulation:	IEEE 802.11a: OFDM(64QAM, 16QAM, QPSK, BPSK)

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-RSS102-V1.1

	IEEE 802.11n: OFDM(64QAM, 16QAM, QPSK, BPSK)				
	IEEE 802.11ac: OFDM(256QAM, 64QAM, 16QAM, QPSK, BPSK)				
	IEEE 802.11ax: OFDM/OFDMA (1024QAM, 256QAM, 64QAM, 16QAM, QPSK, BPSK)				
Channel Spacing:	IEEE 802.11a/n-HT20/ac-VHT20/ax-HE20: 20 MHz				
	IEEE 802.11n-HT40/ac-VHT40/ax-HE40: 40 MHz				
Data Rate:	IEEE 802.11a: Up to 54 Mbps				
	IEEE 802.11n-HT20: Up to MCS7				
	IEEE 802.11n-HT40: Up to MCS7				
	IEEE 802.11ac-VHT20: Up to MCS8				
	IEEE 802.11ac-VHT40: Up to MCS9				
	IEEE 802.11ax-HE20/HE40: Up to MCS11				
Number of Channels:	5150 MHz to 5250 MHz: 4 for IEEE 802.11a/n-HT20/ac-VHT20/ax-HE20 2 for IEEE 802.11n-HT40/ac-VHT40/ax-HE40				
	5250 MHz to 5350 MHz: 4 for IEEE 802.11a/n-HT20/ac-VHT20/ax-HE20 2 for IEEE 802.11n-HT40/ac-VHT40/ax-HE40				
	5470 MHz to 5725 MHz: 12 for IEEE 802.11a/n-HT20/ac-VHT20/ax-HE20 6 for IEEE 802.11n-HT40/ac-VHT40/ax-HE40				
	5725 MHz to 5850 MHz: 5 for IEEE 802.11a/n-HT20/ac-VHT20/ax-HE20 2 for IEEE 802.11n-HT40/ac-VHT40/ax-HE40				
Antenna Type:	Dipole Antenna				
Antenna Gain: (Provided by the customer)	5150 MHz to 5250 MHz: 3.5 dBi				
	5250 MHz to 5350 MHz: 3.5 dBi				
	5470 MHz to 5725 MHz: 3.5 dBi				
	5725 MHz to 5850 MHz: 3.5 dBi				
Maximum conducted output power (dBm):		U-NII-1	U-NII-2A	U-NII-2C	U-NII-3
	IEEE 802.11a:	16.01	16.26	16.41	13.15
	IEEE 802.11n-HT20:	16.08	16.38	16.52	13.22
	IEEE 802.11n-HT40:	18.31	18.30	15.33	13.32
	IEEE 802.11ac-VHT20	16.05	16.37	16.49	13.20
	IEEE 802.11ac-VHT40	17.98	18.18	15.17	13.17
	IEEE 802.11ax-HE20	16.12	16.42	16.52	13.27
	IEEE 802.11ax-HE40	18.22	18.31	15.29	13.39
Maximum EIRP (dBm):		U-NII-1	U-NII-2A	U-NII-2C	U-NII-3
	IEEE 802.11a:	19.51	19.76	19.91	16.65
	IEEE 802.11n-HT20:	19.58	19.88	20.02	16.72
	IEEE 802.11n-HT40:	21.81	21.80	18.83	16.82
	IEEE 802.11ac-VHT20	19.55	19.87	19.99	16.70
	IEEE 802.11ac-VHT40	21.48	21.68	18.67	16.67
	IEEE 802.11ax-HE20	19.62	19.92	20.02	16.77
	IEEE 802.11ax-HE40	21.72	21.81	18.79	16.89

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-RSS102-V1.1

1.4 OTHER INFORMATION

Test channels for BT_LE				
Type of Modulation	Tx/Rx Frequency	Test RF Channel Lists		
GFSK	2402 MHz to 2480 MHz	Lowest(L)	Middle(M)	Highest(H)
		Channel 0	Channel 19	Channel 39
		2402 MHz	2440 MHz	2480 MHz

Test channels for BT_EDR				
Mode	Tx/Rx Frequency	Test RF Channel Lists		
GFSK (DH1, DH3, DH5)	2402 MHz to 2480 MHz	Lowest(L)	Middle(M)	Highest(H)
		Channel 0	Channel 39	Channel 78
$\pi/4$ DQPSK (DH1, DH3, DH5)	2402 MHz to 2480 MHz	2402 MHz	2441 MHz	2480 MHz
		Channel 0	Channel 39	Channel 78
8DPSK (DH1, DH3, DH5)	2402 MHz to 2480 MHz	2402 MHz	2441 MHz	2480 MHz
		Channel 0	Channel 39	Channel 78

Test channels for 2.4 GHz ISM Band of Wi-Fi				
Mode	Tx/Rx Frequency	Test RF Channel Lists		
IEEE 802.11b	2412 MHz to 2462 MHz	Lowest(L)	Middle(M)	Highest(H)
		Channel 1	Channel 6	Channel 11
IEEE 802.11g	2412 MHz to 2462 MHz	2412 MHz	2437 MHz	2462 MHz
		Channel 1	Channel 6	Channel 11
IEEE 802.11n-HT20 IEEE 802.11ax-HE20	2412 MHz to 2462 MHz	2412 MHz	2437 MHz	2462 MHz
		Channel 1	Channel 6	Channel 11
IEEE 802.11n-HT40 IEEE 802.11ax-HE40	2422 MHz to 2452 MHz	2422 MHz	2437 MHz	2452 MHz
		Channel 3	Channel 6	Channel 9

Test channels for 5 GHz U-NII Bands of Wi-Fi					
Mode	Tx/Rx Frequency	Test RF Channel Lists			
IEEE 802.11a	5150 MHz to 5250 MHz	Lowest(L)	Middle(M)	Highest(H)	Straddle band
		Channel 36	Channel 44	Channel 48	--
IEEE 802.11n-HT20	5250 MHz to 5350 MHz	5180 MHz	5220 MHz	5240 MHz	--
		Channel 52	Channel 60	Channel 64	--
IEEE 802.11ac-VHT20	5470 MHz to 5725 MHz	5260 MHz	5300 MHz	5320 MHz	--
		Channel 100	Channel 116	Channel 140	Channel 144
IEEE 802.11ax-HE20	5725 MHz to 5850 MHz	5500 MHz	5580 MHz	5700 MHz	5720 MHz
		Channel 149	Channel 157	Channel 165	--
IEEE 802.11n-HT40	5150 MHz to 5250 MHz	5745 MHz	5785 MHz	5825 MHz	--
		Channel 38	--	Channel 46	--
IEEE 802.11ac-VHT40	5250 MHz to 5350 MHz	5190 MHz	--	5230 MHz	--
		Channel 54	--	Channel 62	--
IEEE 802.11ax-HE40	5470 MHz to 5725 MHz	5270 MHz	--	5310 MHz	--
		Channel 102	Channel 110	Channel 134	Channel 142

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-RSS102-V1.1

		5510 MHz	5550 MHz	5670 MHz	5710 MHz
	5725 MHz to 5850 MHz	Channel 151	--	Channel 159	--
		5755 MHz	--	5795 MHz	--

1.5 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF product, according to the specifications of the manufacturers. It must comply with the requirements of the following standards:

FCC 47 CFR Part 1 Subpart I
RSS-102 Issue 6

All test items have been performed and recorded as per the above standards

1.6 DEVIATION FROM STANDARDS

None.

1.7 ABNORMALITIES FROM STANDARD CONDITIONS

None.

1.8 OTHER INFORMATION REQUESTED BY THE CUSTOMER

None.

2. EQUIPMENT LIST

Please refer to the RF test report.

3. MPE EVALUATION

3.1 REFERENCE DOCUMENTS FOR EVALUATION

No.	Identity	Document Title
1	FCC 47 CFR Part 1 Subpart I	PROCEDURES IMPLEMENTING THE NATIONAL ENVIRONMENTAL POLICY ACT OF 1969
2	RSS-102 Issue 6	Radio Frequency (RF) Exposure Compliance of Radiocommunication Apparatus (All Frequency Bands)
3	KDB 447498 D01 General RF Exposure Guidance v06	RF EXPOSURE PROCEDURES AND EQUIPMENT AUTHORIZATION POLICIES FOR MOBILE AND PORTABLE DEVICES

3.2 MPE COMPLIANCE REQUIREMENT

3.2.1 Limits

3.2.1.1 FCC 47 CFR Part 1 Subpart I

According to §1.1307(b)(1), system operating under the provisions of this section shall be operating in a manner that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure.

Limits for Occupational / Controlled Exposure

Frequency range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f)*	6
30-300	61.4	0.163	1.0	6
300-1500	/	/	F/300	6
1500-100000	/	/	5	6

Limits for General Population / Uncontrolled Exposure

Frequency range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	F/1500	30
1500-100000	/	/	1	30

Note: f = frequency in MHz: * = Plane-wave equivalent power density.

3.2.1.2 RSS-102 Issue 6

According to RSS-102 Issue 6, system operating under the provisions of this section shall be operating in a manner that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure.

According to RSS-102 Issue 6, system operating under the provisions of this section shall be operating in a manner that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure.

RF exposure evaluation is required if the separation distance between the user and/or bystander and the device's radiating element is greater than 20 cm, except when the device operates as follows:

- below 20 MHz⁶ and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 1 W (adjusted for tune-up tolerance);
- at or above 20 MHz and below 48 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than $4.49/f^{0.5}$ W (adjusted for tune-up tolerance), where f is in MHz;
- at or above 48 MHz and below 300 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 0.6 W (adjusted for tune-up tolerance);
- at or above 300 MHz and below 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than $1.31 \times 10^{-2} f^{0.6834}$ W (adjusted for tune-up tolerance), where f is in MHz;
- at or above 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 5 W (adjusted for tune-up tolerance).

In these cases, the information contained in the RF exposure technical brief may be limited to information that demonstrates how the e.i.r.p. was derived.

3.2.2 Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

3.3 MPE CALCULATION METHOD

FCC 47 CFR Part 1 Subpart I

$$S = PG/4\pi R^2 = EIRP/4\pi R^2$$

S = power density (in appropriate units, e.g., mw/cm²)

P = power input to the antenna (in appropriate units, e.g., mw)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor is normally numeric gain.

R = 20cm, distance to the center of radiation of the antenna (in appropriate units, e.g., cm)

3.4 MPE CALCULATION RESULTS

Note: For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.

3.4.1 For WLAN

For Wi-Fi function, operating at 2412MHz to 2462 MHz for IEEE802.11b/g/n/ax and
 operating at 5150 MHz to 5250 MHz for IEEE802.11a/n/ac/ax and
 operating at 5250 MHz to 5350 MHz for IEEE802.11a/n/ac/ax and
 operating at 5470 MHz to 5725 MHz for IEEE802.11a/n/ac/ax and
 operating at 5725 MHz to 5850 MHz for IEEE802.11a/n/ac/ax.

3.4.1.1 Antenna Type:

Dipole Antenna

3.4.1.2 Antenna Gain:

2412MHz to 2462 MHz: 3.0 dBi

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-RSS102-V1.1

5150 MHz to 5250 MHz: 3.5 dBi
 5250 MHz to 5350 MHz: 3.5 dBi
 5470 MHz to 5725 MHz: 3.5 dBi
 5725 MHz to 5850 MHz: 3.5 dBi

3.4.1.3 Results for FCC 47 CFR Part 1 Subpart I

Operating Mode	Freq.	Declared maximum conducted output power	Max. positive tolerance according manufacturer	Antenna Gain	Calculated maximum EIRP	Declared maximum EIRP	MPE Limit	MPE Value
	(MHz)	(dBm)		(dBi)	(dBm)	(mW)	(mw/cm ²)	
IEEE 802.11b	2412	19	1	3.0	23	199.5262	1	0.0397
	2437	19	1	3.0	23	199.5262	1	0.0397
	2462	19	1	3.0	23	199.5262	1	0.0397
IEEE 802.11g	2412	27	1	3.0	31	1258.9254	1	0.2504
	2437	27	1	3.0	31	1258.9254	1	0.2504
	2462	27	1	3.0	31	1258.9254	1	0.2504
IEEE 802.11n-HT20 IEEE 802.11ax-HE20	2412	27	1	3.0	31	1258.9254	1	0.2504
	2437	27	1	3.0	31	1258.9254	1	0.2504
	2462	27	1	3.0	31	1258.9254	1	0.2504
IEEE 802.11n-HT40 IEEE 802.11ax-HE40	2422	27	1	3.0	31	1258.9254	1	0.2504
	2437	27	1	3.0	31	1258.9254	1	0.2504
	2452	27	1	3.0	31	1258.9254	1	0.2504
IEEE 802.11a	5180	16	1	3.5	20.5	112.2018	1	0.0223
	5220	16	1	3.5	20.5	112.2018	1	0.0223
	5240	16	1	3.5	20.5	112.2018	1	0.0223
	5260	16	1	3.5	20.5	112.2018	1	0.0223
	5300	16	1	3.5	20.5	112.2018	1	0.0223
	5320	16	1	3.5	20.5	112.2018	1	0.0223
	5500	16	1	3.5	20.5	112.2018	1	0.0223
	5580	15	1	3.5	19.5	89.1251	1	0.0177
	5700	13	1	3.5	17.5	56.2341	1	0.0112
	5720	13	1	3.5	17.5	56.2341	1	0.0112
	5745	13	1	3.5	17.5	56.2341	1	0.0112
	5785	13	1	3.5	17.5	56.2341	1	0.0112
	5825	13	1	3.5	17.5	56.2341	1	0.0112
IEEE 802.11n-HT20 802.11ac-VHT20 IEEE 802.11ax-HE20	5180	16	1	3.5	20.5	112.2018	1	0.0223
	5220	16	1	3.5	20.5	112.2018	1	0.0223
	5240	16	1	3.5	20.5	112.2018	1	0.0223
	5260	16	1	3.5	20.5	112.2018	1	0.0223
	5300	16	1	3.5	20.5	112.2018	1	0.0223
	5320	16	1	3.5	20.5	112.2018	1	0.0223
	5500	16	1	3.5	20.5	112.2018	1	0.0223
	5580	15	1	3.5	19.5	89.1251	1	0.0177
	5700	13	1	3.5	17.5	56.2341	1	0.0112
	5720	13	1	3.5	17.5	56.2341	1	0.0112
	5745	13	1	3.5	17.5	56.2341	1	0.0112
	5785	13	1	3.5	17.5	56.2341	1	0.0112
	5825	13	1	3.5	17.5	56.2341	1	0.0112

Operating Mode	Freq.	Declared maximum conducted output power	Max. positive tolerance according manufacturer	Antenna Gain	Calculated maximum EIRP	Declared maximum EIRP	MPE Limit	MPE Value
	(MHz)	(dBm)		(dBi)	(dBm)	(mW)	(mw/cm ²)	
IEEE 802.11n-HT40 IEEE 802.11ac-VHT40 IEEE 802.11ax-HE40	5190	18	1	3.5	22.5	177.8279	1	0.0354
	5230	18	1	3.5	22.5	177.8279	1	0.0354
	5270	18	1	3.5	22.5	177.8279	1	0.0354
	5310	18	1	3.5	22.5	177.8279	1	0.0354
	5510	15	1	3.5	19.5	89.1251	1	0.0177
	5550	15	1	3.5	19.5	89.1251	1	0.0177
	5670	15	1	3.5	19.5	89.1251	1	0.0177
	5710	14	1	3.5	18.5	70.7946	1	0.0141
	5755	13	1	3.5	17.5	56.2341	1	0.0112
	5795	13	1	3.5	17.5	56.2341	1	0.0112

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-RSS102-V1.1

3.4.1.4 Results for RSS-102 Issue 6

Operating Mode	Freq.	Declared maximum conducted output power	Max. positive tolerance according manufacturer	Antenna Gain	Calculated maximum EIRP	Declared maximum EIRP	Declare Limit
	(MHz)	(dBm)		(dBi)	(dBm)	(W)	(W)
OSIS IEEE 802.11b IEEE 802.11g IEEE 802.11n-HT20 IEEE 802.11ax-HE20 IEEE 802.11n-HT40 IEEE 802.11ax-HE40	2412	19	1	3.0	23	0.1995	2.6840
	2437	19	1	3.0	23	0.1995	2.7030
	2462	19	1	3.0	23	0.1995	2.7219
	2412	27	1	3.0	31	1.2589	2.6840
	2437	27	1	3.0	31	1.2589	2.7030
	2462	27	1	3.0	31	1.2589	2.7219
	2412	27	1	3.0	31	1.2589	2.6840
	2437	27	1	3.0	31	1.2589	2.7030
	2462	27	1	3.0	31	1.2589	2.7219
	2422	27	1	3.0	31	1.2589	2.6916
	2437	27	1	3.0	31	1.2589	2.7030
	2452	27	1	3.0	31	1.2589	2.7144
OSIS IEEE 802.11a IEEE 802.11n-HT20 IEEE 802.11ac-VHT20 IEEE 802.11ax-HE20 IEEE 802.11n-HT40 802.11ac-VHT40 IEEE 802.11ax-HE40	5180	16	1	3.5	20.5	0.1122	4.5253
	5220	16	1	3.5	20.5	0.1122	4.5491
	5240	16	1	3.5	20.5	0.1122	4.5610
	5260	16	1	3.5	20.5	0.1122	4.5729
	5300	16	1	3.5	20.5	0.1122	4.5966
	5320	16	1	3.5	20.5	0.1122	4.6085
	5500	16	1	3.5	20.5	0.1122	4.7145
	5580	15	1	3.5	19.5	0.0891	4.7613
	5700	13	1	3.5	17.5	0.0562	4.8310
	5720	13	1	3.5	17.5	0.0562	4.8426
	5745	13	1	3.5	17.5	0.0562	4.8570
	5785	13	1	3.5	17.5	0.0562	4.8801
	5825	13	1	3.5	17.5	0.0562	4.9031
	5180	16	1	3.5	20.5	0.1122	4.5253
	5220	16	1	3.5	20.5	0.1122	4.5491
	5240	16	1	3.5	20.5	0.1122	4.5610
	5260	16	1	3.5	20.5	0.1122	4.5729
	5300	16	1	3.5	20.5	0.1122	4.5966
	5320	16	1	3.5	20.5	0.1122	4.6085
	5500	16	1	3.5	20.5	0.1122	4.7145
	5580	15	1	3.5	19.5	0.0891	4.7613
	5700	13	1	3.5	17.5	0.0562	4.8310
	5720	13	1	3.5	17.5	0.0562	4.8426
	5745	13	1	3.5	17.5	0.0562	4.8570
5785	13	1	3.5	17.5	0.0562	4.8801	
5825	13	1	3.5	17.5	0.0562	4.9031	
5190	18	1	3.5	22.5	0.1778	4.5312	
5230	18	1	3.5	22.5	0.1778	4.5551	
5270	18	1	3.5	22.5	0.1778	4.5789	
5310	18	1	3.5	22.5	0.1778	4.6026	
5510	15	1	3.5	19.5	0.0891	4.7204	
5550	15	1	3.5	19.5	0.0891	4.7437	
5670	15	1	3.5	19.5	0.0891	4.8136	
5710	14	1	3.5	18.5	0.0708	4.8368	
5755	13	1	3.5	17.5	0.0562	4.8628	
5795	13	1	3.5	17.5	0.0562	4.8859	

3.4.2 For BT

For BT_LE/2LE/ LE Code function, operating at 2402MHz to 2480 MHz for GFSK and
 For BT_EDR function, operating at 2402MHz to 2480 MHz for GFSK, $\pi/4$ DQPSK, 8DPSK

3.4.2.1 Antenna Type:

Dipole Antenna

3.4.2.2 Antenna Gain:

2402MHz to 2480 MHz: 3.0 dBi

3.4.2.3 Results for FCC 47 CFR Part 1 Subpart I

Operating Mode	Freq.	Declared maximum conducted output power	Max. positive tolerance according manufacturer	Antenna Gain	Calculated maximum EIRP	Declared maximum EIRP	MPE Limit	MPE Value
	(MHz)	(dBm)	(dBm)	(dBi)	(dBm)	(mW)	(mW /cm ²)	
LE/2LE/ LE Code	2402-2480	8	1	3.0	12.0	15.8489	1	0.0032
EDR	2402-2480	9	1.5	3.0	13.5	22.3872	1	0.0045

3.4.2.4 Results for RSS-102 Issue 6

Operating Mode	Freq.	Declared maximum conducted output power	Max. positive tolerance according manufacturer	Antenna Gain	Calculated maximum EIRP	Declared maximum EIRP	Limit
	(MHz)	(dBm)	(dBm)	(dBi)	(dBm)	(W)	(W)
LE/2LE/ LE Code	2402-2480	8	1	3.0	12.0	0.0158	2.6764
EDR	2402-2480	9	1.5	3.0	13.5	0.0224	2.6764

3.4.3 Simultaneous Multi-band Transmission MPE Analysis

3.4.4.1 List of Mode for Simultaneous Multi-band Transmission

No.	Configurations	Support/Not Support
1	2.4G_WLAN + BT	Support
2	5G_WLAN + BT	Support
3	2.4G_WLAN + 5G_WLAN	Not Support

3.4.4.1 Results for transmit simultaneously

FCC 47 CFR Part 1 Subpart I

No.	Configurations	Maximum MPE Value			Limits
		WLAN (mw/cm ²)	BT (mw/cm ²)	Transmit simultaneously	
1	2.4G_WLAN + BT	0.2504	0.0045	0.2549	1
2	5G_WLAN + BT	0.0354	0.0045	0.0399	1

Note:

According to KDB 447498 D01 General RF Exposure Guidance v06, At the transmit simultaneously calculation method is as follows:

$$\text{Transmit simultaneously MPE} = \Sigma \text{ of MPE ratios}$$

$$\text{MPE ratios} = \text{Field strengths or power density} / \text{MPE limit at the test frequency}$$

RSS-102 Issue 6

No.	Configurations	Maximum MPE Value			Limits
		WLAN	BT	Transmit simultaneously	
		W	W		
1	2.4G_WLAN + BT	1.2589	0.0224	0.4774	1
2	5G_WLAN + BT	0.1778	0.0224	0.0476	1

Note:

According to KDB 447498 D01 General RF Exposure Guidance v06, At the transmit simultaneously calculation method is as follows:

$$\text{Transmit simultaneously MPE} = \Sigma \text{ of MPE ratios}$$

$$\text{MPE ratios} = \text{Field strengths or power density} / \text{MPE limit at the test frequency}$$

APPENDIX 1 PHOTOS OF TEST SETUP

N/A

APPENDIX 2 PHOTOS OF EUT CONSTRUCTIONAL DETAILS

Refer to Appendix 2 for EUT external and internal Photos.

*** End of Report ***

The test report is effective only with both signature and specialized stamp. The result(s) shown in this report refer only to the sample(s) tested. Without written approval of UnionTrust, this report can't be reproduced except in full.
