

RF EXPOSURE EVALUATION REPORT

Product Name: HD Intercom & Facility Control Station
Trade Mark: GRANDSTREAM
Model No. / HVIN: GSC3570
Add. Model No. / HVIN: N/A
Report Number: 191008003RFC-3
Test Standards: FCC 47 CFR Part 1 Subpart I
RSS-102 Issue 5
FCC ID: YZZGSC3570
IC: 11964A-GSC3570
Test Result: PASS
Date of Issue: November 5, 2019


Prepared for:

Grandstream Networks, Inc.
126 Brookline Ave., 3rd Floor, Boston, MA 02215, USA

Prepared by:

Shenzhen UnionTrust Quality and Technology Co., Ltd.
16/F, Block A, Building 6, Baoneng Science and Technology Park,
Qingxiang Road No.1, Longhua New District, Shenzhen, China
TEL: +86-755-2823 0888
FAX: +86-755-2823 0886

Prepared by:



Eric Yu
Team Leader

Reviewed by:



Kevin Liang
Assistant Manager

Approved by:


Billy Li

Technical Director

Date:

November 5, 2019

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6, Baoneng Science and Technology Park, Qingxiang Road No.1, Longhua New District, Shenzhen, China

Tel: +86-755-28230888
UTTR-RF-RSS102-V1.0

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

Version

Version No.	Date	Description
V1.0	November 5, 2019	Original



CONTENTS

1. GENERAL INFORMATION	4
1.1 CLIENT INFORMATION	4
1.2 EUT INFORMATION	4
1.3 PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD	4
1.4 OTHER INFORMATION	6
1.5 GENERAL DESCRIPTION OF APPLIED STANDARDS	8
1.6 DEVIATION FROM STANDARDS	8
1.7 ABNORMALITIES FROM STANDARD CONDITIONS	8
1.8 OTHER INFORMATION REQUESTED BY THE CUSTOMER	8
2. EQUIPMENT LIST	8
3. MPE EVALUATION	9
3.1 REFERENCE DOCUMENTS FOR EVALUATION	9
3.2 MPE COMPLIANCE REQUIREMENT	9
3.2.1 LIMITS	9
3.2.2 TEST PROCEDURE	10
3.3 MPE CALCULATION METHOD	10
3.4 MPE CALCULATION RESULTS	10
3.4.1 FOR WLAN	10
3.4.2 SIMULTANEOUS MULTI-BAND TRANSMISSION MPE ANALYSIS	12
APPENDIX 1 PHOTOS OF TEST SETUP	13
APPENDIX 2 PHOTOS OF EUT CONSTRUCTIONAL DETAILS	13

1. GENERAL INFORMATION

1.1 CLIENT INFORMATION

Applicant:	Grandstream Networks, Inc.
Address of Applicant:	126 Brookline Ave., 3rd Floor, Boston, MA 02215, USA
Manufacturer:	Grandstream Networks, Inc.
Address of Manufacturer:	126 Brookline Ave., 3rd Floor, Boston, MA 02215, USA

1.2 EUT INFORMATION

Product Name:	HD Intercom & Facility Control Station		
Model No. / HVIN:	GSC3570		
Add. Model No. / HVIN:	N/A		
Trade Mark:	GRANDSTREAM		
DUT Stage:	Identical Prototype		
EUT Supports Function:	2.4 GHz ISM Band:	IEEE 802.11b/g/n	
	5 GHz U-NII Bands:	5 150 MHz to 5 250 MHz	IEEE 802.11a/n/ac
		5 250 MHz to 5 350 MHz	IEEE 802.11a/n/ac
		5 470 MHz to 5 725 MHz	IEEE 802.11a/n/ac
		5 725 MHz to 5 850 MHz	IEEE 802.11a/n/ac
Software Version:	0.0.0.8		
Hardware Version:	V1.4		

1.3 PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD

For 2.4 GHz ISM Band of Wi-Fi	
Frequency Band:	2400 MHz to 2483.5 MHz
Frequency Range:	2412 MHz to 2462 MHz
Support Standards:	IEEE 802.11b, IEEE 802.11g, IEEE 802.11n-HT20
Type of Modulation:	IEEE 802.11b: DSSS(CCK, DQPSK, DBPSK) IEEE 802.11g: OFDM(64-QAM, 16-QAM, QPSK, BPSK) IEEE 802.11n-HT20: OFDM(64-QAM, 16-QAM, QPSK, BPSK)
Data Rate:	IEEE 802.11b: Up to 11 Mbps IEEE 802.11g: Up to 54 Mbps IEEE 802.11n-HT20: Up to MCS7
Number of Channels:	IEEE 802.11b: 11 IEEE 802.11g: 11 IEEE 802.11n-HT20: 11
Channel Separation:	5 MHz
Antenna Type:	Dipole Antenna
Antenna Gain:	2.5 dBi
Maximum Peak Power:	IEEE 802.11b: 18.09 dBm IEEE 802.11g: 23.62 dBm IEEE 802.11n-HT20: 23.51 dBm

For 5 GHz U-NII Bands of Wi-Fi		
Frequency Bands:	5150 MHz to 5250 MHz (U-NII-1)	
	5250 MHz to 5350 MHz (U-NII-2A)	
	5470 MHz to 5725 MHz (U-NII-2C)	
	5 725 MHz to 5 850 MHz (U-NII-3)	
Frequency Ranges:	5180 MHz to 5240 MHz	
	5260 MHz to 5320 MHz	
	5500 MHz to 5700 MHz	
	5 745 MHz to 5 825 MHz	
Support Standards:	IEEE 802.11a/n/ac	
TPC Function:	Not Support	
DFS Operational mode:	Slave without radar Interference detection function	
Type of Modulation:	IEEE 802.11a: OFDM(64QAM, 16QAM, QPSK, BPSK)	
	IEEE 802.11n: OFDM(64QAM, 16QAM, QPSK, BPSK)	
	IEEE 802.11ac: OFDM(256QAM, 64QAM, 16QAM, QPSK, BPSK)	
Channel Spacing:	IEEE 802.11a/n-HT20/ac-VHT20: 20 MHz	
	IEEE 802.11n-HT40/ac-VHT40: 40 MHz	
	IEEE 802.11ac-VHT80: 80 MHz	
Data Rate:	IEEE 802.11a: Up to 54 Mbps	
	IEEE 802.11n-HT20: Up to MCS7	
	IEEE 802.11n-HT40: Up to MCS7	
	IEEE 802.11ac-VHT20: Up to MCS8	
	IEEE 802.11ac-VHT40: Up to MCS9	
	IEEE 802.11ac-VHT80: Up to MCS9	
Number of Channels:	5150 MHz to 5250 MHz: 4 for IEEE 802.11a/n-HT20/ac-VHT20 2 for IEEE 802.11n-HT40/ac-VHT40 1 for IEEE 802.11acVHT80	
	5250 MHz to 5350 MHz: 4 for IEEE 802.11a/n-HT20/ac-VHT20 2 for IEEE 802.11n-HT40/ac-VHT40 1 for IEEE 802.11acVHT80	
	5470 MHz to 5725 MHz: 11 for IEEE 802.11a/n-HT20/ac-VHT20 5 for IEEE 802.11n-HT40/ac-VHT40 2 for IEEE 802.11ac-VHT80	
	5725 MHz to 5850 MHz: 5 for IEEE 802.11a/n-HT20/ac-VHT20 2 for IEEE 802.11n-HT40/ac-VHT40 1 for IEEE 802.11ac-VHT80	
Antenna Type:	Dipole Antenna	
Antenna Gain:	5150 MHz to 5250 MHz: 3.5 dBi	
	5250 MHz to 5350 MHz: 3.5 dBi	
	5470 MHz to 5725 MHz: 3.5 dBi	
	5725 MHz to 5850 MHz: 3.5 dBi	
Maximum EIRP (dBm):	Chain 0	U-NII-1
	IEEE 802.11a:	20.12
	IEEE 802.11n-HT20:	19.68

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6, Baoneng Science and Technology Park, Qingxiang Road No.1, Longhua New District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-RSS102-V1.0

	IEEE 802.11n-HT40:	19.67			
	IEEE 802.11ac-VHT20:	19.56			
	IEEE 802.11ac-VHT40:	19.64			
	IEEE 802.11ac-VHT80:	19.24			
Maximum conducted output power (dBm):		U-NII-1	U-NII-2A	U-NII-2C	U-NII-3
	IEEE 802.11a:	16.62	16.25	16.19	16.13
	IEEE 802.11n-HT20:	16.18	15.99	15.87	15.79
	IEEE 802.11n-HT40:	16.17	16.02	15.97	15.82
	IEEE 802.11ac-VHT20	16.06	15.92	15.72	15.75
	IEEE 802.11ac-VHT40	16.14	15.95	16.04	16.01
	IEEE 802.11ac-VHT80:	15.74	10.72	11.19	15.38

1.4 OTHER INFORMATION

Test channels for BT_LE				
Type of Modulation	Tx/Rx Frequency	Test RF Channel Lists		
GFSK	2402 MHz to 2480 MHz	Lowest(L)	Middle(M)	Highest(H)
		Channel 0	Channel 19	Channel 39
		2402 MHz	2440 MHz	2480 MHz

Test channels for BT_EDR				
Mode	Tx/Rx Frequency	Test RF Channel Lists		
GFSK (DH1, DH3, DH5)	2402 MHz to 2480 MHz	Lowest(L)	Middle(M)	Highest(H)
		Channel 0	Channel 39	Channel 78
π /4DQPSK (DH1, DH3, DH5)	2402 MHz to 2480 MHz	2402 MHz	2441 MHz	2480 MHz
		Channel 0	Channel 39	Channel 78
8DPSK (DH1, DH3, DH5)	2402 MHz to 2480 MHz	2402 MHz	2441 MHz	2480 MHz
		Channel 0	Channel 39	Channel 78

Test channels for 2.4 GHz ISM Band of Wi-Fi				
Mode	Tx/Rx Frequency	Test RF Channel Lists		
		Lowest(L)	Middle(M)	Highest(H)
IEEE 802.11b	2412 MHz to 2462 MHz	Channel 1	Channel 6	Channel 11
		2412 MHz	2437 MHz	2462 MHz
IEEE 802.11g	2412 MHz to 2462 MHz	Channel 1	Channel 6	Channel 11
		2412 MHz	2437 MHz	2462 MHz
IEEE 802.11n-HT20	2412 MHz to 2462 MHz	Channel 1	Channel 6	Channel 11
		2412 MHz	2437 MHz	2462 MHz

Test channels for 5 GHz U-NII Bands of Wi-Fi				
Mode	Tx/Rx Frequency	Test RF Channel Lists		
		Lowest(L)	Middle(M)	Highest(H)
IEEE 802.11a IEEE 802.11n-HT20 IEEE 802.11ac-VHT20	5150 MHz to 5250 MHz	Channel 36	Channel 44	Channel 48
		5180 MHz	5220 MHz	5240 MHz
	5250 MHz to 5350 MHz	Channel 52	Channel 60	Channel 64
		5260 MHz	5300 MHz	5320 MHz
	5470 MHz to 5725 MHz	Channel 100	Channel 116	Channel 140
		5500 MHz	5580 MHz	5700 MHz
5725 MHz to 5850 MHz	Channel 149	Channel 157	Channel 165	
	5745 MHz	5785 MHz	5825 MHz	
IEEE 802.11n-HT40 IEEE 802.11ac-VHT40	5150 MHz to 5250 MHz	Channel 38	--	Channel 46
		5190 MHz	--	5230 MHz
	5250 MHz to 5350 MHz	Channel 54	--	Channel 62
		5270 MHz	--	5310 MHz
	5470 MHz to 5725 MHz	Channel 102	Channel 110	Channel 134
		5510 MHz	5550 MHz	5670 MHz
5725 MHz to 5850 MHz	Channel 151	--	Channel 159	
	5755 MHz	--	5795 MHz	
IEEE 802.11ac-VHT80	5150 MHz to 5250 MHz	--	Channel 42	--
		--	5210 MHz	--
	5250 MHz to 5350 MHz	--	Channel 58	--
		--	5290 MHz	--
	5470 MHz to 5725 MHz	Channel 106	--	--
		5530 MHz	--	--
5725 MHz to 5850 MHz	--	Channel 155	--	
	--	5775 MHz	--	

1.5 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF product, according to the specifications of the manufacturers. It must comply with the requirements of the following standards:

FCC 47 CFR Part 1 Subpart I
RSS-102 Issue 5

All test items have been performed and recorded as per the above standards

1.6 DEVIATION FROM STANDARDS

None.

1.7 ABNORMALITIES FROM STANDARD CONDITIONS

None.

1.8 OTHER INFORMATION REQUESTED BY THE CUSTOMER

None.

2. EQUIPMENT LIST

Please refer to the RF test report.

3. MPE EVALUATION

3.1 REFERENCE DOCUMENTS FOR EVALUATION

No.	Identity	Document Title
1	FCC 47 CFR Part 1 Subpart I	PROCEDURES IMPLEMENTING THE NATIONAL ENVIRONMENTAL POLICY ACT OF 1969
2	RSS-102 Issue 5	Radio Frequency (RF) Exposure Compliance of Radiocommunication Apparatus (All Frequency Bands)
3	KDB 447498 D01 General RF Exposure Guidance v06	RF EXPOSURE PROCEDURES AND EQUIPMENT AUTHORIZATION POLICIES FOR MOBILE AND PORTABLE DEVICES

3.2 MPE COMPLIANCE REQUIREMENT

3.2.1 Limits

3.2.1.1 FCC 47 CFR Part 1 Subpart I

According to §1.1307(b)(1), system operating under the provisions of this section shall be operating in a manner that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure.

Limits for Occupational / Controlled Exposure

Frequency range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f)*	6
30-300	61.4	0.163	1.0	6
300-1500	/	/	F/300	6
1500-100000	/	/	5	6

Limits for General Population / Uncontrolled Exposure

Frequency range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	F/1500	30
1500-100000	/	/	1	30

Note: f = frequency in MHz: * = Plane-wave equivalent power density.

3.2.1.2 RSS-102 Issue 5

According to RSS-102 Issue 5, system operating under the provisions of this section shall be operating in a manner that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure.

According to RSS-102 Issue 5, system operating under the provisions of this section shall be operating in a manner that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure.

RF exposure evaluation is required if the separation distance between the user and/or bystander and the device's radiating element is greater than 20 cm, except when the device operates as follows:

- below 20 MHz⁶ and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 1 W (adjusted for tune-up tolerance);
- at or above 20 MHz and below 48 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than $4.49/f^{0.5}$ W (adjusted for tune-up tolerance), where f is in MHz;
- at or above 48 MHz and below 300 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 0.6 W (adjusted for tune-up tolerance);
- at or above 300 MHz and below 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than $1.31 \times 10^{-2} f^{0.6834}$ W (adjusted for tune-up tolerance), where f is in MHz;
- at or above 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 5 W (adjusted for tune-up tolerance).

In these cases, the information contained in the RF exposure technical brief may be limited to information that demonstrates how the e.i.r.p. was derived.

3.2.2 Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

3.3 MPE CALCULATION METHOD

FCC 47 CFR Part 1 Subpart I

$$S = PG/4\pi R^2 = EIRP/4\pi R^2$$

S = power density (in appropriate units, e.g., mw/cm²)

P = power input to the antenna (in appropriate units, e.g., mw)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor is normally numeric gain.

R = distance to the center of radiation of the antenna (in appropriate units, e.g., cm)

3.4 MPE CALCULATION RESULTS

Note: For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.

3.4.1 For WLAN

For Wi-Fi function, operating at 2412MHz to 2462 MHz for IEEE802.11b/g/n and
 operating at 5150 MHz to 5250 MHz for IEEE802.11a/n/ac and
 operating at 5250 MHz to 5350 MHz for IEEE802.11a/n/ac and
 operating at 5470 MHz to 5725 MHz for IEEE802.11a/n/ac and
 operating at 5725 MHz to 5850 MHz for IEEE802.11a/n/ac.

3.4.1.1 Antenna Type:

Chain 0: Dipole Antenna

3.4.1.2 Antenna Gain:

Chain 0: 2412MHz to 2462 MHz: 2.5 dBi

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6, Baoneng Science and Technology Park, Qingxiang Road No.1, Longhua New District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-RSS102-V1.0

5150 MHz to 5250 MHz: 3.5 dBi
 5250 MHz to 5350 MHz: 3.5 dBi
 5470 MHz to 5725 MHz: 3.5 dBi
 5725 MHz to 5850 MHz: 3.5 dBi

3.4.1.3 Results for FCC 47 CFR Part 1 Subpart I

Operating Mode	Freq.	Declared maximum conducted average output power	Max. positive tolerance according manufacturer	Antenna Gain	Calculated maximum EIRP	Declared maximum EIRP	MPE Limit	MPE Value
	(MHz)	(dBm)		(dBi)	(dBm)	(mW)	(mW/cm ²)	
IEEE 802.11b	2412-2462	15	2	2.5	19.5	89.1251	1	0.0177
IEEE 802.11g	2412-2462	15	2	2.5	19.5	89.1251	1	0.0177
IEEE 802.11n-HT20	2412-2462	14	2	2.5	18.5	70.7946	1	0.0141
IEEE 802.11a	5180-5240	16	2	3.5	21.5	141.2538	1	0.0281
	5260-5320	16	2	3.5	21.5	141.2538	1	0.0281
	5500-5700	15	2	3.5	20.5	112.2018	1	0.0223
	5745-5825	16	2	3.5	21.5	141.2538	1	0.0281
IEEE 802.11n-HT20/ ac-VHT20	5180-5240	16	2	3.5	21.5	141.2538	1	0.0281
	5260-5320	15	2	3.5	20.5	112.2018	1	0.0223
	5500-5700	14	2	3.5	19.5	89.1251	1	0.0177
	5745-5825	16	2	3.5	21.5	141.2538	1	0.0281
IEEE 802.11n-HT40/ ac-VHT40	5190-5230	15	2	3.5	20.5	112.2018	1	0.0223
	5270-5310	14	2	3.5	19.5	89.1251	1	0.0177
	5510-5670	14	2	3.5	19.5	89.1251	1	0.0177
	5755-5795	16	2	3.5	21.5	141.2538	1	0.0281
IEEE 802.11ac-VHT80	5210	16	2	3.5	21.5	141.2538	1	0.0281
	5290	11	2	3.5	16.5	44.6684	1	0.0089
	5530	12	2	3.5	17.5	56.2341	1	0.0112
	5775	15	2	3.5	20.5	112.2018	1	0.0223

3.4.1.4 Results for RSS-102 Issue 5

Operating Mode	Freq.	Declared maximum conducted average output power	Max. positive Tolerance according manufacturer	Directional Gain	Calculated maximum EIRP	Declared maximum EIRP	Limit
	(MHz)	(dBm)		(dBi)	(dBm)	(W)	(W)
IEEE 802.11b	2412-2462	15	2	2.5	19.5	0.0891	2.6840
IEEE 802.11g	2412-2462	15	2	2.5	19.5	0.0891	2.6840
IEEE 802.11n-HT20	2412-2462	14	2	2.5	18.5	0.0708	2.6840
IEEE 802.11a	5180-5240	16	2	3.5	21.5	0.1413	4.5253
	5260-5320	16	2	3.5	21.5	0.1413	4.5729
	5500-5700	15	2	3.5	20.5	0.1122	4.7145
	5745-5825	16	2	3.5	21.5	0.1413	4.8570
IEEE 802.11n-HT20/ ac-VHT20	5180-5240	16	2	3.5	21.5	0.1413	4.5253
	5260-5320	15	2	3.5	20.5	0.1122	4.5729
	5500-5700	14	2	3.5	19.5	0.0891	4.7145
	5745-5825	16	2	3.5	21.5	0.1413	4.8570
IEEE 802.11n-HT40/ ac-VHT40	5190-5230	15	2	3.5	20.5	0.1122	4.5312
	5270-5310	14	2	3.5	19.5	0.0891	4.5789
	5510-5670	14	2	3.5	19.5	0.0891	4.7204
	5755-5795	16	2	3.5	21.5	0.1413	4.8628
IEEE 802.11ac-VHT80	5210	16	2	3.5	21.5	0.1413	4.5432
	5290	11	2	3.5	16.5	0.0447	4.5907
	5530	12	2	3.5	17.5	0.0562	4.7321
	5775	15	2	3.5	20.5	0.1122	4.8743

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6, Baoneng Science and Technology Park, Qingxiang Road No.1, Longhua New District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-RSS102-V1.0

3.4.2 Simultaneous Multi-band Transmission MPE Analysis

3.4.4.1 List of Mode for Simultaneous Multi-band Transmission

No.	Configurations	Support/Not Support
1	2.4G_WLAN + 5G_WLAN	Not Support

3.4.4.2 Results for transmit simultaneously

Not applicable.



APPENDIX 1 PHOTOS OF TEST SETUP

Not applicable

APPENDIX 2 PHOTOS OF EUT CONSTRUCTIONAL DETAILS

Refer to Appendix 2 for EUT external and internal Photos.

*** End of Report ***

The test report is effective only with both signature and specialized stamp. The result(s) shown in this report refer only to the sample(s) tested. Without written approval of UnionTrust, this report can't be reproduced except in full.
