RF EXPOSURE EVALUATION

MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Applicable Standard

According to subpart 15.247(i)and subpart §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Report No.: 2401Y27848E-RFA

Limits for Maximum Permissible Exposure (MPE) (§1.1310, §2.1091)

(B) Limits for General Population/Uncontrolled Exposure									
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm²)	Averaging Time (minutes)					
0.3-1.34	614	1.63	*(100)	30					
1.34–30	824/f	2.19/f	*(180/f ²)	30					
30–300	27.5	0.073	0.2	30					
300–1500	/	/	f/1500	30					
1500-100,000	/	/	1.0	30					

f = frequency in MHz; * = Plane-wave equivalent power density;

According to §1.1310 and §2.1091 RF exposure is calculated.

Result

Calculation formula:

Prediction of power density at the distance of the applicable MPE limit

 $S = PG/4\pi R^2$ = power density (in appropriate units, e.g. mW/cm²);

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

For simultaneously transmit system, the calculated power density should comply with:

$$\sum_{i} \frac{S_{i}}{S_{Limit,i}} \le 1$$

Calculated Data:

For worst case:

Mode	Frequency (MHz)	Antenna Gain [#]		Max Tune-up Power [#]		Evaluation Distance	Power Density	MPE Limit
		(dBi)	(numeric)	(dBm)	(mW)	(cm)	(mW/cm^2)	(mW/cm^2)
2.4G Wi-Fi	2412-2462	7.64	5.81	29.0	794.33	31	0.3822	1.0
5G Wi-Fi	5150-5250	8.67	7.36	25.0	316.23	31	0.1927	1.0
	5250-5350	8.67	7.36	21.5	141.25	31	0.0861	1.0
	5470-5725	8.67	7.36	21.0	125.89	31	0.0767	1.0
	5725-5850	8.67	7.36	26.5	446.68	31	0.2722	1.0
	5850-5895	8.67	7.36	26.0	398.11	31	0.2426	1.0

Report No.: 2401Y27848E-RFA

Note:

- 1) The tune up conducted power and antenna gain was declared by the applicant.
- 2) The antenna gain should be the directional gain.
- 3) The 2.4G Wi-Fi and 5G Wi-Fi can Simultaneous transmitting.

Simultaneous transmitting consideration (worst case):

The ratio=MPE $_{\rm 2.4G\ Wi\text{-}Fi}/limit+MPE _{\rm 5G\ Wi\text{-}Fi}/limit=0.3822/1.0+0.2722/1.0=0.654<1.0,$ so simultaneous exposure is compliant.

To maintain compliance with the FCC's RF exposure guidelines, place the equipment at least 31cm from nearby persons.

Result: Compliant.