

RF EXPOSURE EVALUATION REPORT

Product Name: Long-Range Enterprise Wi-Fi 6 Access Point
Trade Mark: GRANDSTREAM
Model No.: GWN7660ELR
Report Number: 2311037676RFC-6
Test Standards: FCC 47 CFR Part 1 Subpart I
FCC ID: YZZGWN7660ELR
Test Result: PASS
Date of Issue: February 21, 2024

Prepared for:

Grandstream Networks, Inc.
126 Brookline Ave., 3rd Floor Boston, MA 02215, USA


Prepared by:

Shenzhen UnionTrust Quality and Technology Co., Ltd.
Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

TEL: +86-755-2823 0888
FAX: +86-755-2823 0886

Prepared by: David Chen
David Chen
Senior Project Engineer

Reviewed by: Robben Chen
Robben Chen
Assistant Manager

Approved by: 
Billy Li
Technical Director

Date: February 21, 2024

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-FCCPART1-V1.1

Version

Version No.	Date	Description
V1.0	February 21, 2024	Original

**Shenzhen UnionTrust Quality and Technology Co., Ltd.**

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>UTTR-RF-FCCPART1-V1.1

CONTENTS

1. GENERAL INFORMATION	4
1.1 CLIENT INFORMATION	4
1.2 EUT INFORMATION	4
1.3 PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD	4
1.4 OTHER INFORMATION	6
1.5 GENERAL DESCRIPTION OF APPLIED STANDARDS	7
1.6 DEVIATION FROM STANDARDS	7
1.7 ABNORMALITIES FROM STANDARD CONDITIONS	8
1.8 OTHER INFORMATION REQUESTED BY THE CUSTOMER	8
2. EQUIPMENT LIST	8
3. MPE EVALUATION	9
3.1 REFERENCE DOCUMENTS FOR EVALUATION	9
3.2 MPE COMPLIANCE REQUIREMENT	9
3.2.1 LIMITS	9
3.2.2 TEST PROCEDURE	10
3.3 MPE CALCULATION METHOD	10
3.4 MPE CALCULATION RESULTS	10
3.4.1 FOR WLAN	10
3.4.2 FOR BT	13
3.4.3 SIMULTANEOUS MULTI-BAND TRANSMISSION MPE ANALYSIS	14
APPENDIX 1 PHOTOS OF TEST SETUP	15
APPENDIX 2 PHOTOS OF EUT CONSTRUCTIONAL DETAILS	15

1. GENERAL INFORMATION

1.1 CLIENT INFORMATION

Applicant:	Grandstream Networks, Inc.
Address of Applicant:	126 Brookline Ave., 3rd Floor Boston, MA 02215, USA
Manufacturer:	Grandstream Networks, Inc.
Address of Manufacturer:	126 Brookline Ave., 3rd Floor Boston, MA 02215, USA

1.2 EUT INFORMATION

Product Name:	Long-Range Enterprise Wi-Fi 6 Access Point		
Model No.:	GWN7660ELR		
Trade Mark:	GRANDSTREAM		
DUT Stage:	Identical Prototype		
EUT Supports Function: (Provided by the customer)	2.4 GHz ISM Band:	IEEE 802.11b/g/n/ax	
		Bluetooth 5.1	
	5 GHz U-NII Bands:	5 150 MHz to 5 250 MHz	IEEE 802.11a/n/ac/ax
		5 250 MHz to 5 350 MHz	IEEE 802.11a/n/ac/ax
		5 470 MHz to 5 725 MHz	IEEE 802.11a/n/ac/ax
5 725 MHz to 5 850 MHz		IEEE 802.11a/n/ac/ax	
Sample Received Date:	November 3, 2023		
Remark: The above EUT's information was provided by customer. Please refer to the specifications or user's manual for more detailed description.			

1.3 PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD

For BT_LE	
Frequency Band:	2400 MHz to 2483.5 MHz
Frequency Range:	2402 MHz to 2480 MHz
Bluetooth Version:	Bluetooth LE/2LE/LE Code
Type of Modulation:	GFSK
Number of Channels:	40
Channel Separation:	2 MHz
Antenna Type:	PCB Antenna
Antenna Gain: (Provided by the customer)	4.9 dBi

For BT_EDR	
Frequency Band:	2400 MHz to 2483.5 MHz
Frequency Range:	2402 MHz to 2480 MHz
Bluetooth Version:	Bluetooth BR + EDR
Modulation Technique:	Frequency Hopping Spread Spectrum(FHSS)
Type of Modulation:	GFSK, $\pi/4$ DQPSK, 8DPSK
Number of Channels:	79
Channel Separation:	1 MHz
Antenna Type:	PCB Antenna
Antenna Gain: (Provided by the customer)	4.9 dBi

For 2.4 GHz ISM Band of Wi-Fi	
Frequency Band:	2400 MHz to 2483.5 MHz
Frequency Range:	2412 MHz to 2462 MHz
Support Standards:	IEEE 802.11b/g/n-HT20/n-HT40/ax-HE20/ax-HE40
Type of Modulation:	IEEE 802.11b: DSSS (CCK, DQPSK, DBPSK) IEEE 802.11g/n: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11ax: OFDM/OFDMA(1024QAM, 256QAM, 64QAM, 16QAM, QPSK, BPSK)
Data Rate:	IEEE 802.11b: Up to 11 Mbps IEEE 802.11g: Up to 54 Mbps IEEE 802.11n-HT20/HT40: Up to MCS15 IEEE 802.11ax-HE20/ HE40: Up to MCS11
Number of Channels:	IEEE 802.11b/g/n-HT20/ax-HE20: 11 IEEE 802.11n-HT40/ax-HE40: 7
Channel Separation:	5 MHz
Antenna Type: (Provided by the customer)	Antenna 0 PCB Antenna
	Antenna 1 PCB Antenna
Antenna Gain: (Provided by the customer)	Antenna 0 6.44 dBi
	Antenna 1 6.63 dBi

For 5 GHz U-NII Bands of Wi-Fi	
Frequency Bands:	5150 MHz to 5250 MHz (U-NII-1)
	5250 MHz to 5350 MHz (U-NII-2A)
	5470 MHz to 5725 MHz (U-NII-2C)
	5725 MHz to 5850 MHz (U-NII-3)
Frequency Ranges:	5180 MHz to 5240 MHz
	5260 MHz to 5320 MHz
	5500 MHz to 5700 MHz
	5745 MHz to 5825 MHz
Support Standards:	IEEE 802.11a/n/ac/ax
TPC Function:	Support
DFS Operational mode:	Master
Type of Modulation:	IEEE 802.11a/n: OFDM (64QAM, 16QAM, QPSK, BPSK)
	IEEE 802.11ac: OFDM (256QAM, 64QAM, 16QAM, QPSK, BPSK)
	IEEE 802.11ax: OFDM/OFDMA (1024QAM, 256QAM, 64QAM, 16QAM, QPSK, BPSK)
Channel Spacing:	IEEE 802.11a/n-HT20/ac-VHT20/ax-HE20: 20 MHz
	IEEE 802.11n-HT40/ac-VHT40/ax-HE40: 40 MHz
	IEEE 802.11ac-VHT80/ax-HE80: 80 MHz
	IEEE 802.11ac-VHT160/ax-HE160: 160 MHz
Data Rate:	IEEE 802.11a: Up to 54 Mbps
	IEEE 802.11n: Up to MCS15
	IEEE 802.11ac-VHT20: Up to MCS8
	IEEE 802.11ac-VHT40/VHT80/VHT160: Up to MCS9
Number of Channels:	IEEE 802.11ax-HE20/HE40/HE80/HE160: Up to MCS11
	5150 MHz to 5350 MHz:
	8 for 802.11a/n-HT20/ac-VHT20/ax-HE20
	4 for 802.11n-HT40/ac-VHT40/ax-HE40
	2 for 802.11ac-VHT80/ax-HE80
	1 for 802.11ac-VHT160/ax-HE160

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-FCCPART1-V1.1

	5470 MHz to 5725 MHz: 11 for 802.11a/n-HT20/ac-VHT20/ax-HE20 5 for 802.11n-HT40/ac-VHT40/ax-HE40 2 for 802.11ac-VHT80/ax-HE80 1 for 802.11ac-VHT160/ax-HE160				
	5725 MHz to 5850 MHz: 5 for IEEE 802.11a/n-HT20/ac-VHT20/ax-HE20 2 for IEEE 802.11n-HT40/ac-VHT40/ax-HE40 1 for IEEE 802.11ac-VHT80/ax-HE80				
Antenna Type: (Provided by the customer)	Antenna 0:	PCB Antenna			
	Antenna 1:	PCB Antenna			
Antenna Gain (dBi): (Provided by the customer)	Antenna	U-NII-1	U-NII-2A	U-NII-2C	U-NII-3
	Antenna 0:	7.16	7.16	7.16	7.16
	Antenna 1:	7.14	7.14	7.14	7.14

1.4 OTHER INFORMATION

Test channels for BT_LE				
Type of Modulation	Tx/Rx Frequency	Test RF Channel Lists		
		Lowest(L)	Middle(M)	Highest(H)
GFSK	2402 MHz to 2480 MHz	Channel 0	Channel 19	Channel 39
		2402 MHz	2440 MHz	2480 MHz

Test channels for BT_EDR				
Mode	Tx/Rx Frequency	Test RF Channel Lists		
		Lowest(L)	Middle(M)	Highest(H)
GFSK (DH1, DH3, DH5)	2402 MHz to 2480 MHz	Channel 0	Channel 39	Channel 78
		2402 MHz	2441 MHz	2480 MHz
$\pi/4$ DQPSK (DH1, DH3, DH5)	2402 MHz to 2480 MHz	Channel 0	Channel 39	Channel 78
		2402 MHz	2441 MHz	2480 MHz
8DPSK (DH1, DH3, DH5)	2402 MHz to 2480 MHz	Channel 0	Channel 39	Channel 78
		2402 MHz	2441 MHz	2480 MHz

Test channels for 2.4 GHz ISM Band of Wi-Fi				
Mode	Tx/Rx Frequency	Test RF Channel Lists		
		Lowest(L)	Middle(M)	Highest(H)
IEEE 802.11b	2412 MHz to 2462 MHz	Channel 1	Channel 6	Channel 11
		2412 MHz	2437 MHz	2462 MHz
IEEE 802.11g	2412 MHz to 2462 MHz	Channel 1	Channel 6	Channel 11
		2412 MHz	2437 MHz	2462 MHz
IEEE 802.11n-HT20 IEEE 802.11ax-HE20	2412 MHz to 2462 MHz	Channel 1	Channel 6	Channel 11
		2412 MHz	2437 MHz	2462 MHz
IEEE 802.11n-HT40 IEEE 802.11ax-HE40	2422 MHz to 2452 MHz	Channel 3	Channel 6	Channel 9
		2422 MHz	2437 MHz	2452 MHz

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-FCCPART1-V1.1

Test channels for 5 GHz U-NII Bands of Wi-Fi				
Mode	Tx/Rx Frequency	Test RF Channel Lists		
		Lowest(L)	Middle(M)	Highest(H)
IEEE 802.11a IEEE 802.11n-HT20 IEEE 802.11ac-VHT20 IEEE 802.11ax-HE20	5150 MHz to 5250 MHz	Channel 36	Channel 44	Channel 48
		5180 MHz	5220 MHz	5240 MHz
	5250 MHz to 5350 MHz	Channel 52	Channel 60	Channel 64
		5260 MHz	5300 MHz	5320 MHz
	5470 MHz to 5725 MHz	Channel 100	Channel 116	Channel 140
		5500 MHz	5580 MHz	5700 MHz
	5725 MHz to 5850 MHz	Channel 149	Channel 157	Channel 165
		5745 MHz	5785 MHz	5825 MHz
IEEE 802.11n-HT40 IEEE 802.11ac-VHT40 IEEE 802.11ax-HE40	5150 MHz to 5250 MHz	Channel 38	--	Channel 46
		5190 MHz	--	5230 MHz
	5250 MHz to 5350 MHz	Channel 54	--	Channel 62
		5270 MHz	--	5310 MHz
	5470 MHz to 5725 MHz	Channel 102	Channel 110	Channel 134
		5510 MHz	5550 MHz	5670 MHz
	5725 MHz to 5850 MHz	Channel 151	--	Channel 159
		5755 MHz	--	5795 MHz
IEEE 802.11ac-VHT80 IEEE 802.11ax-HE80	5150 MHz to 5250 MHz	--	Channel 42	--
		--	5210 MHz	--
	5250 MHz to 5350 MHz	--	Channel 58	--
		--	5290 MHz	--
	5470 MHz to 5725 MHz	Channel 106	--	--
		5530 MHz	--	--
5725 MHz to 5850 MHz	--	Channel 155	--	
	--	5775 MHz	--	
IEEE 802.11ac-VHT160 IEEE 802.11ax-HE160	5150 - 5350 MHz	Channel 50		
		5250 MHz		
	5470 - 5725 MHz	Channel 114		
		5570 MHz		
5725 - 5850 MHz				

1.5 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF product, according to the specifications of the manufacturers. It must comply with the requirements of the following standards:

FCC 47 CFR Part 1 Subpart I

All test items have been performed and recorded as per the above standards

1.6 DEVIATION FROM STANDARDS

None.

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-FCCPART1-V1.1

1.7 ABNORMALITIES FROM STANDARD CONDITIONS


None.

1.8 OTHER INFORMATION REQUESTED BY THE CUSTOMER

None.

2. EQUIPMENT LIST

Please refer to the RF test report.



3. MPE EVALUATION

3.1 REFERENCE DOCUMENTS FOR EVALUATION

No.	Identity	Document Title
1	FCC 47 CFR Part 1 Subpart I	PROCEDURES IMPLEMENTING THE NATIONAL ENVIRONMENTAL POLICY ACT OF 1969
2	KDB 447498 D01 General RF Exposure Guidance v06	RF EXPOSURE PROCEDURES AND EQUIPMENT AUTHORIZATION POLICIES FOR MOBILE AND PORTABLE DEVICES
3	KDB 662911 D01 Multiple Transmitter Output v02r01	Emissions Testing of Transmitters with Multiple Outputs in the Same Band

3.2 MPE COMPLIANCE REQUIREMENT

3.2.1 Limits

3.2.1.1 FCC 47 CFR Part 1 Subpart I

According to §1.1307(b)(1), system operating under the provisions of this section shall be operating in a manner that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure.

Limits for Occupational / Controlled Exposure

Frequency range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f)*	6
30-300	61.4	0.163	1.0	6
300-1500	/	/	F/300	6
1500-100000	/	/	5	6

Limits for General Population / Uncontrolled Exposure

Frequency range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	F/1500	30
1500-100000	/	/	1	30

Note: f = frequency in MHz: * = Plane-wave equivalent power density.

3.2.2 Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

3.3 MPE CALCULATION METHOD

FCC 47 CFR Part 1 Subpart I

$$S = PG/4\pi R^2 = EIRP/4\pi R^2$$

S = power density (in appropriate units, e.g., mw/cm²)

P = power input to the antenna (in appropriate units, e.g., mw)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor is normally numeric gain.

R = 20cm distance to the center of radiation of the antenna (in appropriate units, e.g., cm)

3.4 MPE CALCULATION RESULTS

Note: For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.

3.4.1 For WLAN

For Wi-Fi function, operating at 2412MHz to 2462 MHz for IEEE802.11b/g/n/ax and operating at 5150 MHz to 5250 MHz for IEEE802.11a/n/ac/ax and operating at 5250 MHz to 5350 MHz for IEEE802.11a/n/ac/ax and operating at 5470 MHz to 5725 MHz for IEEE802.11a/n/ac/ax and operating at 5725 MHz to 5850 MHz for IEEE802.11a/n/ac/ax.

3.4.1.1 Antenna Type:

PCB Antenna

Antenna Gain:

Chain 0: 2412MHz to 2462 MHz: 6.44dBi

Chain 1: 2412MHz to 2462 MHz: 6.63dBi

Chain 0: 5150 MHz to 5250 MHz: 7.16dBi

5250 MHz to 5350 MHz: 7.16dBi

5470 MHz to 5725 MHz: 7.16dBi

5725 MHz to 5850 MHz: 7.16dBi

Chain 1: 5150 MHz to 5250 MHz: 7.14dBi

5250 MHz to 5350 MHz: 7.14dBi

5470 MHz to 5725 MHz: 7.14dBi

5725 MHz to 5850 MHz: 7.14dBi

3.4.1.2 Results for FCC 47 CFR Part 1 Subpart I

For SISO (1TX/1RX) Mode

Operating Mode	Freq. (MHz)	Ant.	Declared maximum conducted avg output power	Max. positive tolerance according manufacturer	Antenna Gain	Calculated maximum EIRP	Declared maximum EIRP	MPE Limit	MPE Value	
			(dBm)	(dBm)	(dBi)	(dBm)	(mW)	(mW/cm ²)		
SISO	IEEE 802.11b	2412-2462	Ant 0,Ant1	20	2	6.63	28.63	729.4575	1	0.1451
	IEEE 802.11g	2412-2462	Ant 0,Ant1	19	1	6.63	26.63	460.2566	1	0.0916
	IEEE 802.11a	5180-5240	Ant 0,Ant1,	17	2	7.16	26.16	413.0475	1	0.0822
		5260-5320	Ant 0,Ant1,	17	2	7.16	26.16	413.0475	1	0.0822
		5500-5720	Ant 0,Ant1,	16	2	7.16	25.16	328.0953	1	0.0653
		5745-5825	Ant 0,Ant1,	18	2	7.16	27.16	519.9960	1	0.1034

For MIMO (2TX/2RX) Mode

Operating Mode	Freq. (MHz)	Ant.	Declared maximum conducted avg output power	Max. positive Tolerance according manufacturer	Antenna Gain	Calculated maximum EIRP	Declared maximum EIRP	MPE Limit	MPE Value	MIMO	
			(dBm)	(dBm)	(dBi)	(dBm)	(mW)	(mW/cm ²)	Value	Limit	
MIMO (2TX/2RX)	IEEE 802.11n-HT20 802.11ax-HE20	Ant 0	19	1	6.44	26.44	440.5549	1	0.0876	0.1603	1
		Ant 1	18	1	6.63	25.63	365.5948	1	0.0727		
	IEEE 802.11n-HT40 802.11ax-HE40	Ant 0	18	1	6.44	25.44	349.9452	1	0.0696	0.1274	1
		Ant 1	17	1	6.63	24.63	290.4023	1	0.0578		
MIMO (2TX/2RX)	IEEE 802.11n-HT20 802.11ac-VHT20 802.11ax-HE20	Ant 0	13	2	7.16	22.16	164.4372	1	0.0327	0.0653	1
		Ant 1	13	2	7.14	22.14	163.6817	1	0.0326		
		Ant 0	13	2	7.16	22.16	164.4372	1	0.0327	0.0653	1
		Ant 1	13	2	7.14	22.14	163.6817	1	0.0326		
	Ant 0	11	2	7.16	20.16	103.7528	1	0.0206	0.0411	1	
	Ant 1	11	2	7.14	20.14	103.2761	1	0.0205			
	Ant 0	18	2	7.16	27.16	519.9960	1	0.1034	0.2064	1	
	Ant 1	18	2	7.14	27.14	517.6068	1	0.1030			
MIMO (2TX/2RX)	IEEE 802.11n-HT40 802.11ac-VHT40 802.11ax-HE40	Ant 0	9	1	7.16	17.16	51.9996	1	0.0103	0.0206	1
		Ant 1	9	1	7.14	17.14	51.7607	1	0.0103		
		Ant 0	9	1.5	7.16	17.66	58.3445	1	0.0116	0.0232	1
		Ant 1	9	1.5	7.14	17.64	58.0764	1	0.0116		
	Ant 0	10	2.5	7.16	19.66	92.4698	1	0.0184	0.0367	1	
	Ant 1	10	2.5	7.14	19.64	92.0450	1	0.0183			
	Ant 0	19	1	7.16	27.16	519.9960	1	0.1034	0.2064	1	
	Ant 1	19	1	7.14	27.14	517.6068	1	0.1030			

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-FCCPART1-V1.1

Operating Mode	Freq.	Ant.	Declared maximum conduct ed avg output power	Max. positive Toleranc e according manufacturer	Antenna Gain	Calculated maximum EIRP	Declared maximum EIRP	MPE Limit	MPE Value	MIMO		
	(MHz)									(dBm)	(dBi)	(dBm)
IEEE 802.11ac-VHT80 802.11ax-HE80	5210	Ant 0	9	1	7.16	17.16	51.9996	1	0.0103	0.0206	1	
		Ant 1	9	1	7.14	17.14	51.7607	1	0.0103			
	5290	Ant 0	10	2	7.16	19.16	82.4138	1	0.0164	0.0327	1	
		Ant 1	10	2	7.14	19.14	82.0352	1	0.0163			
	5530	Ant 0	9	2	7.16	18.16	65.4636	1	0.0130	0.0260	1	
		Ant 1	9	2	7.14	18.14	65.1628	1	0.0130			
	5690	Ant 0	10	3	7.16	20.16	103.7528	1	0.0206	0.0411	1	
		Ant 1	10	3	7.14	20.14	103.2761	1	0.0205			
	5775	Ant 0	18	1	7.16	26.16	413.0475	1	0.0822	0.1640	1	
		Ant 1	18	1	7.14	26.14	411.1497	1	0.0818			
	IEEE 802.11ac-VHT160 802.11ax-HE160	5250	Ant 0	9	1	7.16	17.16	51.9996	1	0.0103	0.0206	1
			Ant 1	9	1	7.14	17.14	51.7607	1	0.0103		
		5570	Ant 0	9	2	7.16	18.16	65.4636	1	0.0130	0.0260	1
			Ant 1	9	2	7.14	18.14	65.1628	1	0.0130		

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-FCCPART1-V1.1

3.4.2 For BT

For BT_LE function, operating at 2402MHz to 2480 MHz for GFSK and

For BT_EDR function, operating at 2402MHz to 2480 MHz for GFSK, $\pi/4$ DQPSK, 8DPSK

3.4.2.1 Antenna Type:

PCB Antenna

3.4.2.2 Antenna Gain:

2402MHz to 2480 MHz: 4.9 dBi

3.4.2.3 Results for FCC 47 CFR Part 1 Subpart I

Operating Mode	Freq.	Maximum conducted output power	Max. positive tolerance according manufacturer	Max. Antenna Gain	Calculated EIRP	Calculated output power	MPE Limit	MPE Value
	(MHz)	(dBm)	(dBm)	(dBi)	(dBm)	(mW)	(mW /cm2)	
LE/2LE/LE Code	2402-2480	14	1	4.9	19.9	97.7237	1	0.0194
EDR	2402-2480	13	2	4.9	19.9	97.7237	1	0.0194

3.4.3 Simultaneous Multi-band Transmission MPE Analysis

3.4.2.1 List of Mode for Simultaneous Multi-band Transmission

No.	Configurations	Support/Not Support
1	2.4G _WLAN + BT	Support
2	5G_WLAN + BT	Support
3	2.4G _WLAN + 5G_WLAN	Support

3.4.2.2 Results for transmit simultaneously

FCC 47 CFR Part 1 Subpart I

No.	Configurations	Maximum MPE Value				Limits
		2.4G WLAN	5G WLAN	BT	Transmit simultaneously	
1	2.4G _WLAN + BT	0.1603	N/A	0.0194	0.1797	1
2	5G_WLAN + BT	N/A	0.2064	0.0194	0.2258	1
3	2.4G _WLAN + 5G_WLAN	0.1603	0.2064	N/A	0.3667	1

Note:

According to KDB 447498 D01 General RF Exposure Guidance v06, At the transmit simultaneously calculation method is as follows:

$$\text{Transmit simultaneously MPE} = \Sigma \text{ of MPE ratios}$$

$$\text{MPE ratios} = \text{Field strengths or power density} / \text{MPE limit at the test frequency}$$

APPENDIX 1 PHOTOS OF TEST SETUP

N/A

APPENDIX 2 PHOTOS OF EUT CONSTRUCTIONAL DETAILS

Refer to Appendix 2 for EUT external and internal Photos.

*** End of Report ***

The test report is effective only with both signature and specialized stamp. The result(s) shown in this report refer only to the sample(s) tested. Without written approval of UnionTrust, this report can't be reproduced except in full.
