

FCC §15.247 (i) & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Applicable Standard

According to subpart 15.247 (i) and subpart 2.1091 systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

Limits for General Population/Uncontrolled Exposure

Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm²)	Averaging Time (Minutes)
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

f = frequency in MHz

* = Plane-wave equivalent power density

a)

Result

Calculated Formulary:

Predication of MPE limit at a given distance

$$S = \frac{PG}{4\pi R^2}$$

S = power density (in appropriate units, e.g. mW/cm²)

P = power input to the antenna (in appropriate units, e.g., mW).

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain.

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

For simultaneously transmit system, the calculated power density should comply with:

$$\sum_i \frac{S_i}{S_{Limit,i}} \leq 1$$

Frequency (MHz)	Antenna Gain		Tune up conducted power		Evaluation Distance (cm)	Power Density (mW/cm ²)	MPE Limit (mW/cm ²)
	(dBi)	(numeric)	(dBm)	(mW)			
2412-2462 (non-beamforming)	3.5	2.24	27.0	501.19	25	0.143	1
2412-2462 (beamforming)	9.5	8.91	25.0	316.23	25	0.359	1
5180-5240	9.5	8.91	23.0	199.53	25	0.226	1
5260-5320	9.5	8.91	19.0	79.43	25	0.090	1
5500-5720	9.5	8.91	19.0	79.43	25	0.090	1
5745-5825	9.5	8.91	24.0	251.19	25	0.285	1

- Note: 1. The tune up conducted power was declared by the applicant.
 2. The 2.4G Wi-Fi can transmit at the same time with the 5G Wi-Fi.
 3. For the 2.4G Wi-Fi, as it can support the beam-forming function, so the directional antenna gain should add the $10\lg 4$, $3.5\text{dBi}+10\lg 4=9.5\text{dBi}$.
 4. For the 5G Wi-Fi, as it can support the beam-forming function, so the directional antenna gain should add the $10\lg 4$, $3.5\text{dBi}+10\lg 4=9.5\text{dBi}$.

Simultaneous transmitting consideration (worst case):

The ratio= $\text{MPE}_{2.4\text{G Wi-Fi}}/\text{limit}+\text{MPE}_{5\text{G Wi-Fi}}/\text{limit}=0.359+0.285=0.644 < 1.0$, so simultaneous exposure is compliant.

To maintain compliance with the FCC's RF exposure guidelines, place the equipment at least 25cm from nearby persons.

Result: Compliant.