5. RF EXPOSURE EVALUATION

5.1 MAXIMUM PERMISSIBLE EXPOSURE (MPE)

5.1.1 Applicable Standard

According to subpart 1.1307 (b)(1), 2.1091 systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

Limits for General Population/Uncontrolled Exposure									
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (Minutes)					
0.3-1.34	614	1.63	*(100)	30					
1.34-30	824/f	2.19/f	*(180/f ²)	30					
30-300	27.5	0.073	0.2	30					
300-1500	/	/	f/1500	30					
1500-100,000	/	/	1.0	30					

Limits for General Population/Uncontrolled Exposure

f = frequency in MHz

* = Plane-wave equivalent power density

5.1.2 Result

Calculated Formulary:

Predication of MPE limit at a given distance

$$S = \frac{PG}{4\pi R^2}$$

S = power density (in appropriate units, e.g. mW/cm²)

P = power input to the antenna (in appropriate units, e.g., mW).

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain.

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

For simultaneously transmit system, the calculated power density should comply with:

$$\sum_{i} \frac{S_i}{S_{Limit,i}} \leq 1$$

China Certification ICT Co., Ltd (Dongguan)

Report No.:CR230955399-00G

Mode	Frequency (MHz)	Tune Up Conducted Power (dBm)	Antenna Gain (dBi) (Note 2)	Evaluation Distance (cm)	Power Density (mW/cm ²)	MPE Limit (mW/cm ²)
Bluetooth	2402-2480	14.5	4.45	32	0.006	1.0
BLE	2402-2480	14.0	4.45	32	0.005	1.0
2.4G Wi-Fi	2412-2462	25.0	7.15	32	0.128	1.0
5G Wi-Fi	5180-5240	27.6	8.26	32	0.300	1.0
	5260-5320	21.73	8.26	32	0.078	1.0
	5500-5700	21.73	8.26	32	0.078	1.0
	5745-5825	27.2	8.26	32	0.273	1.0
6G Wi-Fi	5955-6145	16.0	7.55	32	0.018	1.0
	6435-6515	16.0	7.55	32	0.018	1.0
	6535-6855	16.0	7.55	32	0.018	1.0
	6875-7115	16.0	7.55	32	0.018	1.0

Note:

1) The tune up conducted power was declared by the applicant.

2) For the Wi-Fi mode, the antenna gain would be the directional gain.

3) The Bluetooth, 2.4G Wi-Fi, 5G Wi-Fi and 6G Wi-Fi can transmit simultaneously.

 $The \ ratio=MPE_{Bluetooth}/limit+MPE_{2.4G Wi-Fi}/limit+MPE_{5G Wi-Fi}/limit+MPE_{6G Wi-Fi}/limit\\=0.006+0.128+0.300+0.018=0.452<1.0, \ simultaneous \ exposure \ is \ not \ required.$

To maintain compliance with the FCC's RF exposure guidelines, place the equipment at least 32cm from nearby persons.

Result: Compliance