



Certificate #4312.01

TEST REPORT

Product Name: 5-port Unmanaged Gigabit PoE+ Switch
Trade Mark: GRANDSTREAM
Model No. / HVIN: GWN7700P
Add. Model No. / HVIN: N/A
Report Number: 2301303834EMC-1
Test Standards: FCC 47 CFR Part 15 Subpart B
 ICES-003 Issue 7
FCC ID: YZZGWN7700P
Test Result: PASS
Date of Issue: March 1, 2023

Prepared for:

Grandstream Networks, Inc.
126 Brookline Ave., 3rd Floor Boston, MA 02215, USA

Prepared by:

Shenzhen UnionTrust Quality and Technology Co., Ltd.
**Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and
 technology park, Longhua district, Shenzhen, China**
TEL: +86-755-2823 0888
FAX: +86-755-2823 0886

Prepared by:

 Dylan Zhang
 Senior Project Engineer

Reviewed by:

 Henry Lu
 Team Leader

Approved by:

 Kevin Liang
 Assistant Manager

Date:

March 1, 2023

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-EMC-ICES003-V1.2

Version

Version No.	Date	Description
V1.0	March 1, 2023	Original

**Shenzhen UnionTrust Quality and Technology Co., Ltd.**

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>UTTR-EMC-ICES003-V1.2

CONTENTS

1. GENERAL INFORMATION.....	4
1.1 CLIENT INFORMATION	4
1.2 EUT INFORMATION.....	4
1.2.1 GENERAL DESCRIPTION OF EUT	4
1.2.2 DESCRIPTION OF ACCESSORIES	4
1.3 DESCRIPTION OF SUPPORT UNITS.....	5
1.4 TEST LOCATION	5
1.5 TEST FACILITY	5
1.6 DEVIATION FROM STANDARDS	6
1.7 ABNORMALITIES FROM STANDARD CONDITIONS	6
1.8 OTHER INFORMATION REQUESTED BY THE CUSTOMER	6
1.9 MEASUREMENT UNCERTAINTY	6
2. TEST SUMMARY	7
3. EQUIPMENT LIST.....	8
4. TEST CONFIGURATION.....	9
4.1 ENVIRONMENTAL CONDITIONS FOR TESTING	9
4.1.1 NORMAL OR EXTREME TEST CONDITIONS	9
4.1.2 RECORD OF NORMAL ENVIRONMENT AND TEST SAMPLE	9
4.2 TEST MODES	9
4.3 TEST SETUP	10
4.3.1 FOR RADIATED EMISSIONS TEST SETUP	10
4.3.2 FOR CONDUCTED EMISSIONS TEST SETUP	11
4.4 SYSTEM TEST CONFIGURATION	11
5. REFERENCE DOCUMENTS FOR TESTING.....	12
6. EMC REQUIREMENTS SPECIFICATION.....	12
6.1 RADIATED EMISSION.....	12
6.2 CONDUCTED EMISSION	20
APPENDIX 1 PHOTOS OF TEST SETUP	27
APPENDIX 2 PHOTOS OF EUT CONSTRUCTIONAL DETAILS.....	27

1. GENERAL INFORMATION

1.1 CLIENT INFORMATION

Applicant:	Grandstream Networks, Inc.
Address of Applicant:	126 Brookline Ave., 3rd Floor Boston, MA 02215, USA
Manufacturer:	Grandstream Networks, Inc.
Address of Manufacturer:	126 Brookline Ave., 3rd Floor Boston, MA 02215, USA

1.2 EUT INFORMATION

1.2.1 General Description of EUT

Product Name:	5-port Unmanaged Gigabit PoE+ Switch
Model No. / HVIN:	GWN7700P
Add. Model No. / HVIN:	N/A
Trade Mark:	GRANDSTREAM
DUT Stage:	Identical Prototype
Rated Voltage:	48-53.5 V \equiv 1.22 A
Classification of digital devices:	Class B
Highest Internal Frequency:	25 MHz
Sample Received Date:	January 30, 2023
Sample Tested Date:	February 7, 2023 to February 14, 2023

Remark: The above EUT's information was provided by customer. Please refer to the specifications or user's manual for more detailed description.

1.2.2 Description of Accessories

Adapter(1)	
Model No.:	GQ80-535122-E4
Input:	100-240 V~50/60 Hz 1.8 A Max
Output:	53.5 V \equiv 1.22 A
DC Cable:	1.5 Meter, Unshielded without ferrite

Adapter(2)	
Model No.:	UES63D1-535122SPA
Input:	100-240 V~50-60 Hz 1.5A Max
Output:	53.5 V \equiv 1.22 A 65.27W
DC Cable:	1.5 Meter, Unshielded without ferrite

Adapter(3)	
Model No.:	ADS-65DIB-48-1 53065E
Input:	100-240 V~50/60 Hz 1.5A Max
Output:	53.0 V \equiv 1.22A 64.66W
DC Cable:	1.2 Meter, Unshielded without ferrite

1.3 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested with associated equipment below.

1) Support Equipment

Description	Manufacturer	Model No.	Serial Number	Supplied by
Notebook Computer	Lenovo	E450	SL10G10780	UnionTrust
Network Analyst	Xtramus	nustreams-600	0JNS600C0013	UnionTrust
USB Mouse	Founder	20-1AN03Y105	MA0KZA39	UnionTrust
AE(POE Load)	N/A	N/A	N/A	Applicant

2) Support Cable

Cable No.	Description	Connector	Length	Supplied by
1	Ethernet Cable*4	RJ45	1.0 Unshielded without ferrite	UnionTrust
2	Ethernet Cable*1	RJ45	2.0 Unshielded without ferrite	UnionTrust
3	Ethernet Cable*4	RJ45	0.2 Unshielded without ferrite	UnionTrust

1.4 TEST LOCATION

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China 518109.

Telephone: +86 (0) 755 2823 0888

Fax: +86 (0) 755 2823 0886

1.5 TEST FACILITY

The test facility is recognized, certified, or accredited by the following organizations:

CNAS-Lab Code: L9069

The measuring equipment utilized to perform the tests documented in this report has been calibrated once a year or in accordance with the manufacturer's recommendations, and is traceable under the ISO/IEC 17025 to international or national standards. Equipment has been calibrated by accredited calibration laboratories.

A2LA-Lab Certificate No.: 4312.01

Shenzhen UnionTrust Quality and Technology Co., Ltd. has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

ISED Wireless Device Testing Laboratories

CAB identifier: CN0032

FCC Accredited Lab.

Designation Number: CN1194

Test Firm Registration Number: 259480

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-EMC-ICES003-V1.2

1.6 DEVIATION FROM STANDARDS

None.

1.7 ABNORMALITIES FROM STANDARD CONDITIONS

None.

1.8 OTHER INFORMATION REQUESTED BY THE CUSTOMER

None.

1.9 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the Product as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

No.	Item	Measurement Uncertainty
1	Conducted emission 9kHz-150kHz	±3.2 dB
2	Conducted emission 150kHz-30MHz	±2.7 dB
3	Radiated emission 9kHz-30MHz	± 4.7 dB
4	Radiated emission 30MHz-1GHz	± 4.6 dB
5	Radiated emission 1GHz-18GHz	± 4.4 dB
6	Radiated emission 18GHz-26GHz	± 4.6 dB
7	Radiated emission 26GHz-40GHz	± 4.6 dB

2. TEST SUMMARY

FCC 47 CFR Part 15 Subpart B Test Cases			
Test Item	Test Requirement	Test Method	Result
Conducted Emission	FCC 47 CFR Part 15.107 ICES-003 Issue 7 Section 3.2.1	ANSI C63.4-2014	PASS
Radiated Emission	FCC 47 CFR Part 15.109 ICES-003 Issue 7 Section 3.2.2	ANSI C63.4-2014	PASS



3. EQUIPMENT LIST

Radiated Emission Test Equipment List						
Used	Equipment	Manufacturer	Model No.	Serial Number	Cal. date (mm dd, yyyy)	Cal. Due date (mm dd, yyyy)
<input checked="" type="checkbox"/>	3m SAC	ETS-LINDGREN	3m	Euroshiedpn-CT001270-1317	Jan. 22, 2021	Jan. 21, 2024
<input checked="" type="checkbox"/>	Receiver	R&S	ESIB26	100114	Nov. 3, 2022	Nov. 2, 2023
<input checked="" type="checkbox"/>	Broadband Antenna	ETS-LINDGREN	3142E	00201566	Nov.11, 2021	Nov.10, 2023
<input checked="" type="checkbox"/>	6dB Attenuator	Talent	RA6A5-N-18	18103001	Nov. 3, 2022	Nov. 2, 2023
<input checked="" type="checkbox"/>	Preamplifier	HP	8447F	2805A02960	Nov. 1, 2022	Oct. 31, 2023
<input checked="" type="checkbox"/>	Multi device Controller	ETS-LINDGREN	7006-001	00160105	N/A	N/A
<input checked="" type="checkbox"/>	Test Software	Audix	e3	Software Version: 9.160323		

Conducted Emission Test Equipment List						
Used	Equipment	Manufacturer	Model No.	Serial Number	Cal. date (mm dd, yyyy)	Cal. Due date (mm dd, yyyy)
<input checked="" type="checkbox"/>	Receiver	R&S	ESR7	1316.3003K07-101181-K3	Nov. 1, 2022	Oct. 31, 2023
<input checked="" type="checkbox"/>	Pulse Limiter	R&S	ESH3-Z2	0357.8810.54	Nov. 1, 2022	Oct. 31, 2023
<input checked="" type="checkbox"/>	LISN	R&S	ESH2-Z5	860014/024	Nov. 1, 2022	Oct. 31, 2023
<input checked="" type="checkbox"/>	LISN	ETS-Lindgren	3816/2SH	00201088	Nov. 1, 2022	Oct. 31, 2023
<input checked="" type="checkbox"/>	Test Software	Audix	e3	Software Version: 9.20151119i		

4. TEST CONFIGURATION

4.1 ENVIRONMENTAL CONDITIONS FOR TESTING

4.1.1 Normal or Extreme Test Conditions

Environment Parameter	Selected Values During Tests		
Test Condition	Ambient		
	Temperature (°C)	Voltage (V)	Relative Humidity (%)
NV/NT	+15 to +35	1: AC 120V/60Hz 2: AC 240V/50Hz	20 to 75
Remark: 1) NV: Normal Voltage; NT: Normal Temperature			

4.1.2 Record of Normal Environment and Test sample



Test Item	Temperature (°C)	Relative Humidity (%)	Pressure (kPa)	Sample No.	Tested by
Conducted Emission	22.6	67.8	100.0	S202301301038-ZJA02/2	Andy Lin
Radiated Emission	23.5	45.6	100.4		Lucas Ouyang

4.2 TEST MODES


Test Item	EMI Test Modes
Radiated Emission	Test Mode 1: AC240V/50Hz (Adaptor1) + LAN Port Loop transmission+POE out Test Mode 2: AC120V/60Hz (Adaptor1) + LAN Port Loop transmission+POE out Test Mode 3: Worse from mode 1~2(Adaptor2) Test Mode 4: Worse from mode 1~2(Adaptor3)
Conducted Emission	Test Mode 1: AC240V/50Hz (Adaptor1) + LAN Port Loop transmission+POE out Test Mode 2: AC120V/60Hz (Adaptor1) + LAN Port Loop transmission+POE out Test Mode 3: Worse from mode 1~2(Adaptor2) Test Mode 4: Worse from mode 1~2(Adaptor3)
Remark: The above test modes in boldface were the worst cases.	

4.3 TEST SETUP

4.3.1 For Radiated Emissions test setup



4.3.2 For Conducted Emissions test setup



4.4 SYSTEM TEST CONFIGURATION

All readings are extrapolated back to the equivalent three meter reading using inverse scaling with distance. Analyzer resolution is 100 kHz or greater for frequencies below 1000MHz. The resolution is 1 MHz or greater for frequencies above 1000MHz. The spurious emissions more than 20 dB below the permissible value are not reported.

Radiated emission measurement were performed from the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic (according to KDB 896810 D02 SDoC FAQ v01r01) of the highest fundamental frequency or to 40 GHz, whichever is lower.

5. REFERENCE DOCUMENTS FOR TESTING

No.	Identity	Document Title
1	FCC 47 CFR Part15 Subpart B	Unintentional Radiators
2	ICES-003 Issue 7	Information Technology Equipment (Including Digital Apparatus)
3	ANSI C63.4-2014	American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz
4	KDB 174176 D01 Line Conducted FAQ v01r01	AC power-line conducted emission frequency asked questions
5	KDB 896810 D02 SDoC FAQ v01r02	Supplier's Declaration of Conformity frequency asked questions

6. EMC REQUIREMENTS SPECIFICATION

6.1 RADIATED EMISSION

Test Requirement: FCC 47 CFR Part 15.109
ICES-003 Issue 7 Clause 3.2.2

Test Method: ANSI C63.4-2014

Receiver Setup:

Frequency: (f) (MHz)	Detector type	Measurement receiver bandwidth	
		RBW	VBW
$30 \leq f \leq 1\,000$	Quasi Peak	120 kHz	300 kHz
$f \geq 1000$	Peak	1 MHz	3 MHz
	Average	1 MHz	3 MHz

Measured frequency range

Highest frequency generated or used in the device or on which the device operates or tunes (MHz)	Upper frequency of measurement range (MHz)
Below 1.705	30.
1.705-108	1000.
108-500	2000.
500-1000	5000.
Above 1000	5th harmonic of the highest frequency or 40 GHz, whichever is lower.

Limits:

Limits for Class B devices

FCC 47 CFR Part 15 Subpart B

Frequency (MHz)	limits at 3m (dBµV/m)		
	QP Detector	PK Detector	AV Detector
30 – 88	40.0	--	--
88 – 216	43.5	--	--
216 – 960	46.0	--	--
960 – 1000	54.0	--	--
Above 1000	--	74.0	54.0

ICES-003 Issue 7

Frequency (MHz)	limits at 3m (dBµV/m)		
	QP Detector	PK Detector	AV Detector
30 – 88	40.0	--	--
88 – 216	43.5	--	--
216 – 230	46.0	--	--

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-EMC-ICES003-V1.2

230 – 960	47.0	--	--
960 – 1000	54.0	--	--
Above 1000	--	74.0	54.0

Remark:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBµV/m) = 20 log Emission level (µV/m).
3. For frequencies above 1000 MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20 dB under any condition of modulation.

Test Setup: Refer to section 4.3.1 for details.

Test Procedures:

1. From 30 MHz to 1GHz test procedure as below:
 - 1) The Product was placed on the non-conductive turntable 0.8 m above the ground at a chamber.
 - 2) Set the spectrum analyzer/receiver in Peak detector, Max Hold mode, and 120 kHz RBW. Record the maximum field strength of all the pre-scan process in the full band when the antenna is varied between 1~4 m in both horizontal and vertical, and the turntable is rotated from 0 to 360 degrees.
 - 3) For each frequency whose maximum record was higher or close to limit, measure its QP value: vary the antenna's height and rotate the turntable from 0 to 360 degrees to find the height and degree where Product radiated the maximum emission, then set the test frequency analyzer/receiver to QP Detector and specified bandwidth with Maximum Hold Mode, and record the maximum value.
2. Above 1GHz test procedure as below:
 - 1) The Product was placed on the non-conductive turntable 0.8 m above the ground at a chamber.
 - 2) Set the spectrum analyzer/receiver in Peak detector, Max Hold mode, and 1MHz RBW. Record the maximum field strength of all the pre-scan process in the full band when the antenna is varied in both horizontal and vertical, and the turntable is rotated from 0 to 360 degrees.
 - 3) For each frequency whose maximum record was higher or close to limit, measure its AV value: rotate the turntable from 0 to 360 degrees to find the degree where Product radiated the maximum emission, then set the test frequency analyzer/receiver to AV value and specified bandwidth with Maximum Hold Mode, and record the maximum value.


Equipment Used: Refer to section 3 for details.

Test Result: Pass

The measurement data as follows:

The measurement data for FCC 47 CFR Part 15 Subpart B as follows:

Below 1GHz(Quasi Peak):
 Test Mode 2
 Adapter 1
 Horizontal



No.	Frequency (MHz)	Reading (dB μ V)	Correction factor (dB/m)	Result (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Detector
1	36.524	36.41	-5.97	30.44	40.00	-9.56	QP
2	85.477	51.27	-16.48	34.79	40.00	-5.21	QP
3	173.815	48.23	-11.31	36.92	43.50	-6.58	QP
4	200.043	44.73	-10.39	34.34	43.50	-9.16	QP
5	250.486	41.86	-8.82	33.04	46.00	-12.96	QP
6	376.523	35.45	-5.16	30.29	46.00	-15.71	QP

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China


Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-EMC-ICES003-V1.2



Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888


Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-EMC-ICES003-V1.2

Below 1GHz(Quasi Peak):
 Test Mode 3
 Adapter 2
 Horizontal



No.	Frequency (MHz)	Reading (dB μ V)	Correction factor (dB/m)	Result (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Detector
1	86.687	51.01	-16.52	34.49	40.00	-5.51	QP
2	144.790	49.31	-15.26	34.05	43.50	-9.45	QP
3	177.518	46.30	-10.13	36.17	43.50	-7.33	QP
4	201.454	46.18	-10.45	35.73	43.50	-7.77	QP
5	217.644	43.95	-10.82	33.13	46.00	-12.87	QP
6	754.963	31.09	2.01	33.10	46.00	-12.90	QP

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China


Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-EMC-ICES003-V1.2



Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888


Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-EMC-ICES003-V1.2

Below 1GHz(Quasi Peak):
 Test Mode 4
 Adapter 3
 Horizontal



No.	Frequency (MHz)	Reading (dB μ V)	Correction factor (dB/m)	Result (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Detector
1	86.080	51.39	-16.33	35.06	40.00	-4.94	QP
2	143.776	49.38	-15.35	34.03	43.50	-9.47	QP
3	176.275	47.21	-10.40	36.81	43.50	-6.69	QP
4	216.120	44.55	-10.75	33.80	46.00	-12.20	QP
5	250.486	40.70	-8.82	31.88	46.00	-14.12	QP
6	754.963	29.22	2.01	31.23	46.00	-14.77	QP

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China


Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-EMC-ICES003-V1.2



Remark:

1. Correct Factor = Antenna Factor + Cable Loss - Amplifier Gain, the value was added to Original Receiver Reading by the software automatically.
2. Result = Reading + Correct Factor.
3. Margin = Result – Limit
4. All possible modes of operation were investigated, and testing at two nominal voltages of 240V/50Hz and 120V/60Hz, only the worst case emissions reported.
5. The limit of ICES-003 in the 230MHz to 960MHz band is higher than that of FCC Part 15B, so the radiation emission test data conform to the limit of ICES-003.

6.2 CONDUCTED EMISSION

Test Requirement: FCC 47 CFR Part 15.107
ICES-003 Issue 7 Section 3.2.1

Test Method: ANSI C63.4-2014

Limits:

Limits for Class B devices

Frequency range (MHz)	Limits (dB(μV))	
	Quasi-peak	Average
0,15 to 0,50	66 to 56	56 to 46
0,50 to 5	56	46
5 to 30	60	50

Remark:

1. The lower limit shall apply at the transition frequencies.
2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 to 0.50 MHz.

Test Setup: Refer to section 4.3.2 for details.

Test Procedures:


- 1) The Product was placed on a nonconductive table 0.8 m above the horizontal ground reference plane, and 0.4 m from the vertical ground reference plane, and connected to the main through Line Impedance Stability Network (L.I.S.N).
- 2) The RBW of the receiver was set at 9 kHz in 150 kHz ~ 30MHz with Peak and AVG detector in Max Hold mode. Run the receiver's pre-scan to record the maximum disturbance generated from Product in all power lines in the full band.
- 3) For each frequency whose maximum record was higher or close to limit, measure its QP and AVG values and record.

Equipment Used: Refer to section 3 for details.


Test Result: Pass

The measurement data as follows:
 Quasi Peak and Average:
 Adapter 1
 Test Mode 2

Live Line



No.	Frequency (MHz)	Reading (dBμV)	Correction factor (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)	Detector
1	0.150	29.96	10.03	39.99	56.00	-16.01	Average
2	0.150	41.96	10.03	51.99	66.00	-14.01	QP
3	0.318	30.73	10.03	40.76	49.76	-9.00	Average
4	0.318	41.73	10.03	51.76	59.76	-8.00	QP
5	0.510	13.50	10.04	23.54	46.00	-22.46	Average
6	0.510	24.50	10.04	34.54	56.00	-21.46	QP
7	3.381	16.22	10.23	26.45	46.00	-19.55	Average
8	3.381	33.22	10.23	43.45	56.00	-12.55	QP
9	3.645	14.48	10.25	24.73	46.00	-21.27	Average
10	3.645	33.48	10.25	43.73	56.00	-12.27	QP
11	4.141	13.04	10.28	23.32	46.00	-22.68	Average
12	4.141	32.04	10.28	42.32	56.00	-13.68	QP



Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886


E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-EMC-ICES003-V1.2

Quasi Peak and Average:
 Adapter 2
 Test Mode 3

Live Line



No.	Frequency (MHz)	Reading (dBμV)	Correction factor (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)	Detector
1	0.158	12.55	10.03	22.58	55.57	-32.99	Average
2	0.158	12.55	10.03	22.58	65.57	-42.99	QP
3	0.398	17.67	10.04	27.71	47.90	-20.19	Average
4	0.398	29.67	10.04	39.71	57.90	-18.19	QP
5	0.598	10.81	10.05	20.86	46.00	-25.14	Average
6	0.598	22.81	10.05	32.86	56.00	-23.14	QP
7	1.414	10.68	10.09	20.77	46.00	-25.23	Average
8	1.414	23.68	10.09	33.77	56.00	-22.23	QP
9	3.381	14.67	10.23	24.90	46.00	-21.10	Average
10	3.381	33.67	10.23	43.90	56.00	-12.10	QP
11	3.653	17.24	10.25	27.49	46.00	-18.51	Average
12	3.653	34.24	10.25	44.49	56.00	-11.51	QP

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China


Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-EMC-ICES003-V1.2



No.	Frequency (MHz)	Reading (dBμV)	Correction factor (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)	Detector
1	0.158	11.79	10.02	21.81	55.57	-33.76	Average
2	0.158	31.79	10.02	41.81	65.57	-23.76	QP
3	0.182	11.35	10.00	21.35	54.39	-33.04	Average
4	0.182	30.35	10.00	40.35	64.39	-24.04	QP
5	0.398	19.23	10.02	29.25	47.90	-18.65	Average
6	0.398	31.23	10.02	41.25	57.90	-16.65	QP
7	2.717	12.64	10.16	22.80	46.00	-23.20	Average
8	2.717	30.64	10.16	40.80	56.00	-15.20	QP
9	3.133	14.49	10.19	24.68	46.00	-21.32	Average
10	3.133	33.49	10.19	43.68	56.00	-12.32	QP
11	3.589	16.58	10.23	26.81	46.00	-19.19	Average
12	3.589	34.58	10.23	44.81	56.00	-11.19	QP

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888


Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-EMC-ICES003-V1.2

Quasi Peak and Average:
 Adapter 3
 Test Mode 4



No.	Frequency (MHz)	Reading (dB μ V)	Correction factor (dB)	Result (dB μ V)	Limit (dB μ V)	Margin (dB)	Detector
1	0.158	17.52	10.03	27.55	55.57	-28.02	Average
2	0.158	36.52	10.03	46.55	65.57	-19.02	QP
3	0.382	24.42	10.04	34.46	48.24	-13.78	Average
4	0.382	34.42	10.04	44.46	58.24	-13.78	QP
5	3.221	11.41	10.21	21.62	46.00	-24.38	Average
6	3.221	29.41	10.21	39.62	56.00	-16.38	QP
7	3.965	10.45	10.26	20.71	46.00	-25.29	Average
8	3.965	27.45	10.26	37.71	56.00	-18.29	QP
9	14.091	14.80	10.76	25.56	50.00	-24.44	Average
10	14.091	22.80	10.76	33.56	60.00	-26.44	QP
11	17.690	14.57	11.09	25.66	50.00	-24.34	Average
12	17.690	22.57	11.09	33.66	60.00	-26.34	QP

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China


Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-EMC-ICES003-V1.2



No.	Frequency (MHz)	Reading (dBμV)	Correction factor (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)	Detector
1	0.158	15.45	10.02	25.47	55.57	-30.10	Average
2	0.158	34.45	10.02	44.47	65.57	-21.10	QP
3	0.382	23.69	10.02	33.71	48.24	-14.53	Average
4	0.382	34.69	10.02	44.71	58.24	-13.53	QP
5	2.366	10.31	10.13	20.44	46.00	-25.56	Average
6	2.366	23.31	10.13	33.44	56.00	-22.56	QP
7	3.141	11.77	10.19	21.96	46.00	-24.04	Average
8	3.141	28.77	10.19	38.96	56.00	-17.04	QP
9	5.101	10.39	10.32	20.71	50.00	-29.29	Average
10	5.101	26.39	10.32	36.71	60.00	-23.29	QP
11	13.723	14.25	10.76	25.01	50.00	-24.99	Average
12	13.723	23.25	10.76	34.01	60.00	-25.99	QP

Remark:

1. Correct Factor = LISN Factor + Cable Loss + Pulse Limiter Factor, the value was added to Original Receiver Reading by the software automatically.
2. Result = Reading + Correct Factor.
3. Margin = Result - Limit
4. An initial pre-scan was performed on the Phase and neutral lines with peak detector. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission were detected.
5. All possible modes of operation were investigated, and testing at two nominal voltages of 240V/50Hz and 120V/60Hz, only the worst case emissions reported.

APPENDIX 1 PHOTOS OF TEST SETUP

See test photos attached in Appendix 1 for the actual connections between Product and support equipment.

APPENDIX 2 PHOTOS OF EUT CONSTRUCTIONAL DETAILS

Refer to Appendix 2 for EUT external and internal photos.

***** End of Report *****

The test report is effective only with both signature and specialized stamp. The result(s) shown in this report refer only to the sample(s) tested. Without written approval of UnionTrust, this report can't be reproduced except in full.
