



www.ecmg-global.net

# FCC MPE REPORT

On Model Name: IP Multimedia Phone

Model Numbers: GXV3175

Brand Name: Grandstream

FCC ID Number: YZZGXV3175-T

Prepared for Grandstream Networks,INC

Test Report #: SHE-1208-10861-FCC MPE

Tested by: Daomen Galanz  
Engineer Company Name

Reviewed by: Jamerym ECMG  
Senior Engineer Company Name

QC Manager: Swall Zhang ECMG  
QC Manager Company Name

Test Report Released by: Swall Zhang  
Swall Zhang

September 25<sup>th</sup>, 2012  
Date

### **Test Location**

*Tests performed in a Certified ANSI Semi-Anechoic Chamber and Shielded Room.*

*Test Site Location : Galanz*

*25 South Ronggui Rd., Shunde, Foshan,  
Guangdong, China*

*Tel : (86)-757-23612785*

*Fax : (86)-757-23612537*

### **Test Facility**

*The test facility was recognized, certified, or accredited by the following organizations:*

- *CNAL - LAB Code: L2244*

*Galanz EMC Laboratory has been assessed and in compliance with CNAL/AC01:2002 accreditation criteria for testing laboratories (identical to ISO/IEC 17025:2005 General Requirements) for the Competence of Testing Laboratories.*

- *FCC - Registration No.: 580210*

*Galanz EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC was maintained in our files.*

### **List of Test and Measurement Instruments**

<b>Equipment</b>	<b>Manufacturer</b>	<b>Model No.</b>	<b>Serial No.</b>	<b>Calibrated Untill</b>
<i>Spectrum Analyzer</i>	<i>R&amp;S</i>	<i>FSP30</i>	<i>100755</i>	<i>2012-11-30</i>
<i>EMI Receiver</i>	<i>SCHAFFNER</i>	<i>SMR4503</i>	<i>11725</i>	<i>2012-11-30</i>
<i>LISN</i>	<i>ETS</i>	<i>4825/2</i>	<i>1161</i>	<i>2012-11-30</i>
<i>Coaxial Cable</i>	<i>ATC</i>	<i>---</i>	<i>---</i>	<i>2012-11-30</i>
<i>Double-ridged Wave guide horn</i>	<i>ETS</i>	<i>3115</i>	<i>6587</i>	<i>2012-11-30</i>
<i>Amplifier</i>	<i>Agilent</i>	<i>83017A</i>	<i>MY39500438</i>	<i>2012-11-30</i>
<i>Band filter</i>	<i>ASI</i>	<i>82346</i>	<i>S06389</i>	<i>2012-11-30</i>
<i>Biconilog Antenna</i>	<i>ETS</i>	<i>3142C</i>	<i>00042672</i>	<i>2012-11-30</i>
<i>Semi-anechoic Chamber</i>	<i>ETS</i>	<i>---</i>	<i>---</i>	<i>2012-11-30</i>

*Note: All testing were performed using internationally recognized standards.All test instruments were calibrated.*

# *Table of Contents*

---

<i>DISCLAIMER NOTICE</i> .....	<i>1</i>
<i>REPRODUCTION CLAUSE</i> .....	<i>1</i>
<i>OPINIONS AND INTERPRETATIONS</i> .....	<i>1</i>
<i>STATEMENT OF MEASUREMENT UNCERTAINTY</i> .....	<i>1</i>
<i>ADMINISTRATIVE DATA</i> .....	<i>2</i>
<i>EUT DESCRIPTION</i> .....	<i>3</i>
<i>ATTACHMENT 1 - RF EXPOSURE COMPLIANCE REQUIREMENT</i> .....	<i>5</i>

### **Disclaimer Notice**

*When government drawing, specification, or other data are used for any purpose other than in connection with a definitely related government procurement operation, the United States Government thereby incurs no responsibility nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawing, specifications, or other data, is not to be regarded by implication or otherwise in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell patented invention that may in any way be related thereto. This report must not be used to claim product endorsement by NVLAP or any agency of the U.S. Government.*

### **Reproduction Clause**

*Any reproduction of this document must be done in full. No single part of this document may be reproduced without permission from ECMG Electronic Technical Testing Corp (Shenzhen).*

### **Opinions and Interpretations**

*This test report relates to the abovementioned equipment under test (EUT). Without the permission of ECMG Electronic Technical Testing Corp (Shenzhen). Test Lab this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark on this or similar products. The manufacturer has sole responsibility of continued compliance of the device.*

### **Statement of Measurement Uncertainty**

*The data and results referenced in the document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities that can account for a nominal measurement error. Furthermore, component and process variability of devices similar to that tested may result in additional deviation.*

## **Administrative Data**

*Test Sample* : *IP Multimedia Phone*

*Model Name* : *GXV3175*

*Model Tested* : *GXV3175*

*Receipt Date* : *August 16<sup>th</sup>, 2012*

*Date Tested* : *August 17<sup>th</sup>, 2012 to September 6<sup>th</sup>, 2012*

*Applicant* : *Grandstream Networks, INC*

*Address* : *5F, Bldg #1, No.2 Kefa Rd., Science & Technology Park, Shenzhen, China*

*Telephone* : *(86)-755-26014600*

*Fax* : *(86)-755-26014601*

*Manufacturer* : *Grandstream Networks, INC*

*Address* : *5F, Bldg #1, No.2 Kefa Rd., Science & Technology Park, Shenzhen, China*

*Telephone* : *(86)-755-26014600*

*Fax* : *(86)-755-26014601*

*Factory* : *Grandstream Networks, INC*

*Address* : *5F, Bldg #1, No.2 Kefa Rd., Science & Technology Park, Shenzhen, China*

*Telephone* : *(86)-755-26014600*

*Fax* : *(86)-755-26014601*

## EUT Description

Grandstream Networks, Inc., model tested GXV3175 (referred to as the EUT in this report) is an IP Multimedia Phone.

The EUT is an IP multimedia phone which integrates an IEEE 802.11 b/g/n wireless module. Main technical specifications of the EUT as follows:

Parameter		Range																															
Basic parameters	Rated voltage	DC12V																															
	Rated Current	1.5A																															
802.11b/g/n Module Parameters	Operating band	2400-2483.5MHz																															
	Wi-Fi Module Voltage	5.0VDC $\pm$ 5% (or 3.3VDC $\pm$ 5% upon special requirement)																															
	Working Frequency of Each Channel	<table border="1"> <thead> <tr> <th>Channel No.</th> <th>Frequency (MHz)</th> <th>Channel No.</th> <th>Frequency (MHz)</th> </tr> </thead> <tbody> <tr> <td>001</td> <td>2412</td> <td>007</td> <td>2442</td> </tr> <tr> <td>002</td> <td>2417</td> <td>008</td> <td>2447</td> </tr> <tr> <td>003</td> <td>2422</td> <td>009</td> <td>2452</td> </tr> <tr> <td>004</td> <td>2427</td> <td>010</td> <td>2457</td> </tr> <tr> <td>005</td> <td>2432</td> <td>011</td> <td>2462</td> </tr> <tr> <td>006</td> <td>2437</td> <td>--</td> <td>--</td> </tr> </tbody> </table>				Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)	001	2412	007	2442	002	2417	008	2447	003	2422	009	2452	004	2427	010	2457	005	2432	011	2462	006	2437	--	--
		Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)																												
		001	2412	007	2442																												
		002	2417	008	2447																												
		003	2422	009	2452																												
		004	2427	010	2457																												
005		2432	011	2462																													
006	2437	--	--																														
Frequency of Number	IEEE 802.11b/g: 11 channels; Draft 802.11n standard 20MHz: 11 channels; Draft 802.11n standard 40MHz: 7 channels.																																
Modulation Type	802.11b: DBPSK, DQPSK, CCK (DSSS); 802.11g/n: BPSK, QPSK, 16-QAM, 64-QAM (OFDM)																																
RF Power	802.11b/g: max 17dBm $\pm$ 2%; 802.11n: max 15dBm $\pm$ 2%																																
Data Transfer Rate	11n: up to 150Mbps 11g: 54/48/36/24/18/12/9/6Mbps (Dynamic) 11b: 11/5.5/2/1Mbps (Dynamic)																																
Antenna Spec.	1. Gain: 2dBi 2. Impedance: 50ohm 3. One U.FL-R-SMT antenna connector(1T1R)																																

Continue on the next page...

<i>I/O Ports</i>	<i>PC Ethernet Port</i>	<i>10/100Mbps RJ-45 port connecting to PC</i>
	<i>Network Ethernet Port</i>	<i>10/100Mbps RJ-45 port connecting to Ethernet</i>
	<i>Power Jack</i>	<i>12V DC Power connector port 12V DC Power connector port</i>
	<i>RJ11 Jack</i>	<i>Phone handset connector port</i>
	<i>USB Port</i>	<i>USB devices may be connected via the USB port</i>
	<i>SD Card Slot</i>	<i>SD card could be inserted in for picture/music/video files storage</i>
	<i>HDMI</i>	<i>High-Definition Multimedia Interface</i>
	<i>Headset Jack</i>	<i>3.5mm stereo headset connector port</i>
<i>Power Module</i>	<i>Input</i>	<i>100-240VAC 50/60Hz 0.4A</i>
	<i>Output</i>	<i>12VDC, 1.5A,</i>
	<i>Model</i>	<i>SFF1200150A1BB</i>
	<i>Brand name</i>	<i>Mass</i>

*NOTE: For more detailed informations or features please refer to user's manual of EUT.*



## ATTACHMENT 1 - RF EXPOSURE COMPLIANCE REQUIREMENT

### Applicable Standard:

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2m normally can be maintained between the user and the device.

### Limits for General Population/Uncontrolled Exposure

#### a) Limits for Occupational/Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm <sup>2</sup> )	Averaging Times / E / 2 , / H / 2 or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-100000			5	6

#### (b) Limits for General Population/Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm <sup>2</sup> )	Averaging Times / E / 2 , / H / 2 or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100000			1.0	30

Note: f=frequency in MHz; \*Plane-wave equivalent power density

### **MPE Calculation Method**

$$E \text{ (V/m)} = (30 * P * G)^{0.5} / d \quad \text{Power Density: } S \text{ (mW/m}^2\text{)} = E^2 / 377$$

*E = Electric Field (V/m)*

*P = Peak RF output Power (W)*

*G = EUT Antenna numeric gain (numeric)*

*d = Separation distance between radiator and human body (m)*

*The formula can be changed to*

$$S = (30 * P * G) / (377 * d^2)$$

*From the peak EUT RF output power, the minimum mobile separation distance  $d=0.2\text{m}$ , as well as the gain of the used antenna, the RF power density can be obtained.*

*Note :*

*The maximal conducted peak output power is **19.47dBm(0.0885W)** in the high channel(2.462GHz).*

*The best case gain of the antenna is **2.0dBi**.*

*2.0dB logarithmic terms convert to numeric result is nearly **1.58**.*

### **Test Result:**

<b>Channel (MHz)</b>	<b>Antenna Gain (Numeric)</b>	<b>Peak Output Power (dBm)</b>	<b>Peak Output Power (W)</b>	<b>Power Density (S) (mW/cm<sup>2</sup>)</b>	<b>Limit of Power Density (S) (mW/cm<sup>2</sup>)</b>	<b>Test Result</b>
2412	1.58	19.47	0.0885	0.2782	1.0	Compliant

*The unit does meet the requirement.*