

承認書

SPECIFICATION FOR APPROVAL

樣品承認 新品承認 規格/材質變更承認

客戶名稱(Customer):	東荃科技股份有限公司		
客戶料號(Customer P/N):	5060-A107EF+430		
產品料號(Product No.):	A8-A006-00541		
產品品名(Product Name) :	PCB 11a/b/g/n 1dBi/4dBi 30mmx8mm T0.8 gray OD1.13 low loss 55mm I-PEX plug		
文件編號(Approved No) :			
日期(Issued Date) :	2019 年 7 月 30 日		
客戶承認簽章 Customer Approval Signature	In Charge	Checked	Approval

TSKY™ 天凱科技股份有限公司 TSKY CO., LTD.

新竹縣竹北市自強南路8號21F-2 Tel:03-5502626 Fax:03-5503131

21F-2, No.8, Ziqiang S. Rd., Jhubei City, Hsinchu County 30264, Taiwan (R.O.C.)



業務	核准	審核	主辦員

Contents

Item	Description	Page
1.	Cover	1
2.	Contents	2
3.	Specification	3
4.	Drawing	4
5.	Test Report	5~15
6.	SGS	16~153

Specification

- **Electrical Properties :**

1. Frequency : 2400MHz-2500MHz / 5150MHz-5850MHz
2. Impedance : 50Ω
3. Return Loss : $\leq -10\text{dB}$
4. Peak Gain : 1dBi / 4dBi

- **Physical Properties :**



1. Material : FR-4 T=0.8mm
2. Cable : OD1.13 Low Loss
3. Connector : I-PEX

REV	ECN NO.	DRAWING	DESCRIPTION	APPROVED	DATE
X1		Jane	初次發行	Gary	2019/07/30

(Top VIEW)

(SIDE VIEW)

(BOTTOM VIEW)



ELECTRICAL:

Frequency: 2400MHz~2500MHz/5150MHz~5850MHz


Impedance: 50Ω

Peak Gain: 1dBi/4dBi

Return Loss: ≤ -10dB

MECHANICAL:

Cable: D1.13 Low Loss GRAY L=55mm



NOTE:

1. 文字顏色為白色

2. *為重點量測尺寸

3. I-PEX 方向請按照圖面所示

NO.	PART NO.	DESCRIPTION	REV.	Q'TY
4	A2-A008-000**	銅箔29.4x18mm背膠(導電膠)	X1	1
3	A2-A001-00023	29x7mm G9000 雙面背膠	A	1
2	A0-A003-000**	RF CABLE OD1.13 Low Loss 55mm GRAY IPEX PLUG+3(編)-2(絕)-1.5(芯)	X1	1
1	A1-A003-00056	PCB ANT FR-4 L30 W8 T0.8mm 單面化鍍雙面黑漆 FOR A8-A006-00509	A	1


TOLERANCE UNLESS OTHERWISE SPECIFIED				TSKY CO., LTD.				INITIAL MODEL:			
DIMENSION		ANGLES		CONFIDENTIAL	FINISH:	SIZE:	UNIT:	SCALE:	PART NAME		
.X±	0.2	X.°±	0.5	⊕		A4	mm	1:1	PCB 11a/b/g/n 1dBi/4dBi 30mmx8mm T0.8 gray OD1.13 low loss 55mm I-PEX plug		
.XX±	0.1			DRAWING	DESIGNED	CONCURRED	APPROVED		PART NO.		
.XXX±	0.05			Jane			Gary		A8-A006-00541	REV. X1	SHT. 1/1

Zunidata

Wi-Fi Antenna Test Report

Created : 2019-07-29

Antenna Coordinate System Definition




Antenna Coordinate System Definition






Antenna




Return Loss and VSWR






3D Radiation Pattern @ 2400MHz






3D Radiation Pattern @ 2450MHz






3D Radiation Pattern @ 2500MHz






3D Radiation Pattern @ 5150MHz



3D Radiation Pattern @ 5550MHz



3D Radiation Pattern @ 5850MHz



Antenna Gain and Efficiency

ANT1

Frequency(MHz)	2400	2410	2420	2430	2440	2450	2460	2470	2480	2490	2500
Directivity (dBi)	6.12	5.89	5.64	5.42	5.05	4.76	4.58	4.57	4.56	4.51	4.44
Efficiency (dB)	-4.87	-4.65	-4.17	-4.12	-3.73	-3.93	-3.87	-3.6	-3.92	-3.95	-4.24
Efficiency (%)	32.58	34.28	38.28	38.73	42.36	40.46	41.02	43.65	40.55	40.27	37.67
Gain (dBi)	1.25	1.24	1.47	1.3	1.32	0.83	0.71	0.97	0.64	0.56	0.2

Frequency(MHz)	5150	5250	5350	5450	5550	5650	5750	5850
Directivity (dBi)	7.05	6.66	6.43	6.34	6.7	6.67	6.04	6.88
Efficiency (dB)	-2.22	-2.46	-2.2	-2.12	-2.25	-2.31	-2.44	-2.38
Efficiency (%)	59.98	56.75	60.26	61.38	59.57	58.75	57.02	57.81
Gain (dBi)	4.83	4.2	4.23	4.22	4.45	4.36	3.6	4.5