




FCC Part 15C Measurement and Test Report

For

Perixx Computer GmbH

Heerdter Landstrasse 189e, 40549 Düsseldorf, Germany

FCC ID: Z2G-PERIDUO-605

FCC Rule(s):	<u>FCC Part 15.249</u>
Product Description:	<u>Full Size Wireless Ergonomic Keyboard with Vertical Mouse</u>
Tested Model:	<u>PERIDUO-605</u>
Report No.:	<u>WTX19X08055016W-1</u>
Sample Receipt Date:	<u>2019-08-08</u>
Tested Date:	<u>2019-08-08 to 2019-08-16</u>
Issued Date:	<u>2019-08-19</u>
Tested By:	<u>Mike Shi / Engineer</u> 
Reviewed By:	<u>Silin Chen / EMC Manager</u> 
Approved & Authorized By:	<u>Jandy So / PSQ Manager</u> 
Prepared By:	

Shenzhen SEM Test Technology Co., Ltd.

1/F, Building A, Hongwei Industrial Park, Liuxian 2nd Road,
Bao'an District, Shenzhen, P.R.C. (518101)

Tel.: +86-755-33663308 Fax.: +86-755-33663309 Website: www.semtest.com.cn

Note: This test report is limited to the above client company and the product model only. It may not be duplicated without prior permitted by Shenzhen SEM Test Technology Co., Ltd.

TABLE OF CONTENTS

1. GENERAL INFORMATION	4
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
1.2 TEST STANDARDS	5
1.3 TEST METHODOLOGY	5
1.4 TEST FACILITY	5
1.5 EUT SETUP AND TEST MODE	6
1.6 MEASUREMENT UNCERTAINTY	6
1.7 TEST EQUIPMENT LIST AND DETAILS	7
2. SUMMARY OF TEST RESULTS	9
3. ANTENNA REQUIREMENTS	10
3.1 STANDARD APPLICABLE	10
3.2 TEST RESULT	10
4. RADIATED EMISSIONS	11
4.1 STANDARD APPLICABLE	11
4.2 TEST PROCEDURE	11
4.3 CORRECTED AMPLITUDE & MARGIN CALCULATION	13
4.4 SUMMARY OF TEST RESULTS/PLOTS	13
5. OUT OF BAND EMISSIONS	22
5.1 STANDARD APPLICABLE	22
5.2 TEST PROCEDURE	22
5.3 SUMMARY OF TEST RESULTS/PLOTS	22
6. EMISSION BANDWIDTH	25
6.1 STANDARD APPLICABLE	25
6.2 TEST PROCEDURE	25
6.3 SUMMARY OF TEST RESULTS/PLOTS	25

Report version

Version No.	Date of issue	Description
Rev.00	2019-08-19	Original
/	/	/

1. GENERAL INFORMATION

1.1 Product Description for Equipment Under Test (EUT)

Client Information

Applicant: Perixx Computer GmbH
Address of applicant: Heerdter Landstrasse 189e, 40549 Düsseldorf, Germany

Manufacturer: Perixx Computer GmbH
Address of manufacturer: Heerdter Landstrasse 189e, 40549 Düsseldorf, Germany

General Description of EUT	
Product Name:	Full Size Wireless Ergonomic Keyboard with Vertical Mouse
Trade Name:	PERIXX
Model No.:	PERIDUO-605
Adding Model(s):	/
Rated Voltage:	DC1.5V*2
Power Adapter Model:	/
<i>Note: The test data is gathered from a production sample, provided by the manufacturer.</i>	

Technical Characteristics of EUT	
Frequency Range:	2408-2474 MHz
Max. Field Strength:	95.57dBuV/m
Modulation:	FSK
Quantity of Channels:	34
Channel Separation:	2MHz
Antenna Type:	PCB Antenna
Antenna Gain:	-5.35dBi

1.2 Test Standards

The tests were performed according to following standards:

FCC Rules Part 15.249: Operation within the bands 902-928 MHz, 2400-2483.5 MHz, 5725-5875 MHz, and 24.0-24.25 GHz.

ANSI C63.10-2013: American National Standard for Testing Unlicensed Wireless Devices.

Maintenance of compliance is the responsibility of the manufacturer. Any modification of the product, which results in lowering the emission, should be checked to ensure compliance has been maintained.

1.3 Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, The equipment under test (EUT) was configured to measure its highest possible emission level. The test modes were adapted accordingly in reference to the Operating Instructions.

1.4 Test Facility

FCC – Registration No.: 125990

Shenzhen SEM Test Technology Co., Ltd. Laboratory has been recognized to perform compliance testing on equipment subject to the Commissions Declaration Of Conformity (DOC). The Designation Number is CN5010, and Test Firm Registration Number is 125990.

Industry Canada (IC) Registration No.: 11464A

The 3m Semi-anechoic chamber of Shenzhen SEM Test Technology Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 11464A.

1.5 EUT Setup and Test Mode

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. All testing shall be performed under maximum output power condition, and to measure its highest possible emissions level, more detailed description as follows:

Test Mode List		
Test Mode	Description	Remark
TM1	Low Channel	2408MHz
TM2	Middle Channel	2440MHz
TM3	High Channel	2474MHz

Test Conditions	
Temperature:	22~25 °C
Relative Humidity:	50~55 %.
ATM Pressure:	1019 mbar

EUT Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
/	/	/	/

Special Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
/	/	/	/

Auxiliary Equipment List and Details			
Description	Manufacturer	Model	Serial Number
/	/	/	/

1.6 Measurement Uncertainty

Measurement uncertainty		
Parameter	Conditions	Uncertainty
RF Output Power	Conducted	±0.42dB
Occupied Bandwidth	Conducted	± 1.5%
Conducted Spurious Emission	Conducted	±2.17dB
Conducted Emissions	Conducted	9-150kHz ±3.74dB
		0.15-30MHz ±3.34dB
Transmitter Spurious Emissions	Radiated	30-200MHz ±4.52dB
		0.2-1GHz ±5.56dB
		1-6GHz ±3.84dB
		6-18GHz ±3.92dB

1.7 Test Equipment List and Details

No.	Description	Manufacturer	Model	Serial No.	Cal Date	Due Date
SEMT-1072	Spectrum Analyzer	Agilent	E4407B	MY41440400	2019-04-30	2020-04-29
SEMT-1031	Spectrum Analyzer	Rohde & Schwarz	FSP30	836079/035	2019-04-30	2020-04-29
SEMT-1007	EMI Test Receiver	Rohde & Schwarz	ESVB	825471/005	2019-04-30	2020-04-29
SEMT-1008	Amplifier	Agilent	8447F	3113A06717	2019-04-30	2020-04-29
SEMT-1043	Amplifier	C&D	PAP-1G18	2002	2019-04-30	2020-04-29
SEMT-1011	Broadband Antenna	Schwarz beck	VULB9163	9163-333	2019-05-05	2021-05-04
SEMT-1042	Horn Antenna	ETS	3117	00086197	2019-05-05	2021-05-04
SEMT-1121	Horn Antenna	Schwarzbeck	BBHA 9170	BBHA9170582	2019-05-05	2021-05-04
SEMT-1069	Loop Antenna	Schwarz beck	FMZB 1516	9773	2019-05-05	2021-05-04
SEMT-1001	EMI Test Receiver	Rohde & Schwarz	ESPI	101611	2019-04-30	2020-04-29
SEMT-1003	L.I.S.N	Schwarz beck	NSLK8126	8126-224	2019-04-30	2020-04-29
SEMT-1002	Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100911	2019-04-30	2020-04-29
SEMT-1168	Pre-amplifier	Direction Systems Inc.	PAP-0126	14141-12838	2019-04-30	2020-04-29
SEMT-1169	Pre-amplifier	Direction Systems Inc.	PAP-2640	14145-14153	2019-04-30	2020-04-29
SEMT-1163	Spectrum Analyzer	Rohde & Schwarz	FSP40	100612	2019-04-30	2020-04-29
SEMT-1170	DRG Horn Antenna	A.H. SYSTEMS	SAS-574	571	2019-05-05	2021-05-04
SEMT-1166	Power Limiter	Agilent	N9356B	MY45450376	2019-04-30	2020-04-29
SEMT-1048	RF Limiter	ATTEN	AT-BSF-2400~2500	/	2019-04-30	2020-04-29
SEMT-1076	RF Switcher	Top Precision	RCS03-A2	/	2019-04-30	2020-04-29
SEMT-C001	Cable	Zheng DI	LL142-07-07-10M(A)	/	2019-03-18	2020-03-17
SEMT-C002	Cable	Zheng DI	ZT40-2.92J-2.92J-6M	/	2019-03-18	2020-03-17
SEMT-C003	Cable	Zheng DI	ZT40-2.92J-2.92J-2.5M	/	2019-03-18	2020-03-17
SEMT-C004	Cable	Zheng DI	2M0RFC	/	2019-03-18	2020-03-17
SEMT-C005	Cable	Zheng DI	1M0RFC	/	2019-03-18	2020-03-17
SEMT-C006	Cable	Zheng DI	1M0RFC	/	2019-03-18	2020-03-17

Software List			
Description	Manufacturer	Model	Version
EMI Test Software (Radiated Emission)*	Farad	EZ-EMC	RA-03A1
EMI Test Software (Conducted Emission)*	Farad	EZ-EMC	RA-03A1

*Remark: indicates software version used in the compliance certification testing

2. SUMMARY OF TEST RESULTS

FCC Rules	Description of Test Item	Result
§15.203	Antenna Requirement	Compliant
§15.205	Restricted Band of Operation	Compliant
§15.207(a)	Conducted Emission	N/A
§15.209(a)(f)	Radiated Spurious Emissions	Compliant
§15.249(a)	Field Strength of Emissions	Compliant
§15.249(d)	Out of Band Emission	Compliant
§15.215(c)	Emission Bandwidth	Compliant

N/A: Not Applicable

3. Antenna Requirements

3.1 Standard Applicable

According to FCC Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

3.2 Test Result

This product has a PCB antenna, fulfill the requirement of this section.

4. Radiated Emissions

4.1 Standard Applicable

According to §15.249(a), the field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:

Fundamental Frequency	Field strength of fundamental (milli-volts/meter)	Field strength of Harmonics (micro-volts/meter)
902-928 MHz	50	500
2400-2483.5 MHz	50	500
5725-5875 MHz	50	500
24.0-24.25 GHz	250	2500

(d) Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in §15.209, whichever is the lesser attenuation.



The emission limit in this paragraph is based on measurement instrumentation employing an average detector. The provisions in §15.35 for limiting peak emissions apply. Spurious Radiated Emissions measurements starting below or at the lowest crystal frequency.

4.2 Test Procedure

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.205 15.249(a) and FCC Part 15.209 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.



Frequency :9kHz-30MHz
 RBW=10KHz,
 VBW =30KHz
 Sweep time= Auto
 Trace = max hold
 Detector function = peak

Frequency :30MHz-1GHz
 RBW=120KHz,
 VBW=300KHz
 Sweep time= Auto
 Trace = max hold
 Detector function = peak, QP

Frequency :Above 1GHz
 RBW=1MHz,
 VBW=3MHz(Peak), 10Hz(AV)
 Sweep time= Auto
 Trace = max hold
 Detector function = peak, AV

4.3 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and the Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} + \text{Ant. Factor} + \text{Cable Loss} - \text{Ampl. Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of $-6\text{dB}\mu\text{V}$ means the emission is $6\text{dB}\mu\text{V}$ below the maximum limit. The equation for margin calculation is as follows:


$$\text{Margin} = \text{Corr. Ampl.} - \text{FCC Part 15C Limit}$$

4.4 Summary of Test Results/Plots

Note: this EUT was tested in 3 orthogonal positions and the worst case position data was reported.


➤ Spurious Emissions Below 1GHz

Test Channel	Low	Polarity:	Horizontal
--------------	-----	-----------	------------




No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	53.8818	27.21	-11.89	15.32	40.00	-24.68	66	100	peak
2	96.0986	28.35	-14.07	14.28	43.50	-29.22	91	100	peak
3	216.0240	36.23	-12.45	23.78	46.00	-22.22	91	100	peak
4	300.3673	41.82	-9.23	32.59	46.00	-13.41	105	100	peak
5	360.4477	36.59	-7.86	28.73	46.00	-17.27	242	100	peak
6	601.4265	29.57	-4.02	25.55	46.00	-20.45	209	100	peak

Test Channel	Low	Polarity:	Vertical
--------------	-----	-----------	----------




No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	45.2166	26.67	-11.33	15.34	40.00	-24.66	323	100	peak
2	100.9340	25.91	-13.17	12.74	43.50	-30.76	348	100	peak
3	225.3080	25.44	-12.29	13.15	46.00	-32.85	82	100	peak
4	383.9318	27.21	-7.59	19.62	46.00	-26.38	113	100	peak
5	605.6592	26.85	-4.05	22.80	46.00	-23.20	128	100	peak
6	900.1474	33.29	-0.57	32.72	46.00	-13.28	102	100	peak

Test Channel	Middle	Polarity:	Horizontal
--------------	--------	-----------	------------




No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	48.6719	26.98	-11.08	15.90	40.00	-24.10	261	100	peak
2	119.8556	28.53	-14.13	14.40	43.50	-29.10	94	100	peak
3	216.0240	36.83	-12.45	24.38	46.00	-21.62	157	100	peak
4	300.3673	41.84	-9.23	32.61	46.00	-13.39	96	100	peak
5	336.0352	38.62	-8.82	29.80	46.00	-16.20	244	100	peak
6	372.0045	35.53	-7.64	27.89	46.00	-18.11	126	100	peak

Test Channel	Middle	Polarity:	Vertical
--------------	--------	-----------	----------




No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	38.3462	27.97	-12.78	15.19	40.00	-24.81	261	100	peak
2	105.6415	26.96	-13.08	13.88	43.50	-29.62	157	100	peak
3	193.7728	25.45	-13.13	12.32	43.50	-31.18	136	100	peak
4	383.9318	26.40	-7.59	18.81	46.00	-27.19	105	100	peak
5	651.9417	27.41	-4.24	23.17	46.00	-22.83	199	100	peak
6	958.7943	26.79	0.17	26.96	46.00	-19.04	181	100	peak

Test Channel	High	Polarity:	Horizontal
--------------	------	-----------	------------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	44.9006	27.19	-11.36	15.83	40.00	-24.17	67	100	peak
2	96.0986	28.55	-14.07	14.48	43.50	-29.02	98	100	peak
3	237.4760	35.31	-11.66	23.65	46.00	-22.35	97	100	peak
4	300.3673	41.41	-9.23	32.18	46.00	-13.82	143	100	peak
5	336.0352	37.99	-8.82	29.17	46.00	-16.83	231	100	peak
6	383.9318	33.84	-7.59	26.25	46.00	-19.75	221	100	peak

Test Channel	High	Polarity:	Vertical
--------------	------	-----------	----------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	46.6664	26.57	-11.22	15.35	40.00	-24.65	319	100	peak
2	69.8450	27.28	-15.16	12.12	40.00	-27.88	93	100	peak
3	110.5687	25.82	-13.08	12.74	43.50	-30.76	334	100	peak
4	300.3673	25.94	-9.23	16.71	46.00	-29.29	112	100	peak
5	564.6389	26.06	-4.78	21.28	46.00	-24.72	277	100	peak
6	890.7278	26.13	-0.72	25.41	46.00	-20.59	247	100	peak

➤ Spurious Emissions Above 1GHz

Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	H/V	
Low Channel-2408MHz							
2408	104.89	-9.47	95.42	114	-18.58	H	PK
2408	101.39	-9.47	91.92	94	-2.08	H	AV
4816	64.81	-4.42	60.39	74	-13.61	H	PK
4816	46.82	-4.42	42.40	54	-11.60	H	AV
7224	51.11	-2.13	48.98	74	-25.02	H	PK
7224	42.69	-2.13	40.56	54	-13.44	H	AV
2408	97.03	-9.34	87.69	114	-26.31	V	PK
2408	94.39	-9.34	85.05	94	-8.95	V	AV
4816	62.75	-4.42	58.33	74	-15.67	V	PK
4816	46.06	-4.42	41.64	54	-12.36	V	AV
7224	49.82	-2.13	47.69	74	-26.31	V	PK
7224	42.59	-2.13	40.46	54	-13.54	V	AV
Middle Channel-2440MHz							
2440	104.68	-9.41	95.27	114	-18.73	H	PK
2440	100.94	-9.41	91.53	94	-2.47	H	AV
4880	61.37	-4.47	56.90	74	-17.10	H	PK
4880	45.51	-4.47	41.04	54	-12.96	H	AV
7320	48.68	-2.17	46.51	74	-27.49	H	PK
7320	39.59	-2.17	37.42	54	-16.58	H	AV
2440	98.04	-9.41	88.63	114	-25.37	V	PK
2440	95.62	-9.41	86.21	94	-7.79	V	AV
4880	63.47	-4.47	59.00	74	-15.00	V	PK
4880	43.26	-4.47	38.79	54	-15.21	V	AV
7320	51.39	-2.17	49.22	74	-24.78	V	PK
7320	41.33	-2.17	39.16	54	-14.84	V	AV

Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	H/V	
High Channel-2474MHz							
2474	104.91	-9.34	95.57	114	-18.43	H	PK
2474	101.1	-9.34	91.76	94	-2.24	H	AV
4948	65.44	-4.42	61.02	74	-12.98	H	PK
4948	44.34	-4.42	39.92	54	-14.08	H	AV
7422	50.06	-2.13	47.93	74	-26.07	H	PK
7422	41.84	-2.13	39.71	54	-14.29	H	AV
2474	95.71	-9.34	86.37	114	-27.63	V	PK
2474	93.99	-9.34	84.65	94	-9.35	V	AV
4948	63.35	-4.42	58.93	74	-15.07	V	PK
4948	45.14	-4.42	40.72	54	-13.28	V	AV
7422	50.76	-2.13	48.63	74	-25.37	V	PK
7422	41.59	-2.13	39.46	54	-14.54	V	AV

Note: Testing is carried out with frequency rang 9kHz to the tenth harmonics, which above 5th Harmonics are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

The measurements greater than 20dB below the limit from 9kHz to 30MHz..

5. Out of Band Emissions

5.1 Standard Applicable

Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in §15.209, whichever is the lesser attenuation.

5.2 Test Procedure

As the radiation test, set the Lowest and Highest Transmitting Channel, observed the outside band of 2400MHz to 2483.5MHz, than mark the higher-level emission for comparing with the FCC rules.


5.3 Summary of Test Results/Plots

Test mode	Frequency	Limit	Result
	MHz	dBuV / dBc	
Lowest	2310.00	<54 dBuV	Pass
	2390.00	<54 dBuV	Pass
	2400.00	<54 dBuV	Pass
Highest	2483.50	<54 dBuV	Pass
	2500.00	<54 dBuV	Pass

The edge emissions are below the FCC 15.209 Limits or complies with the 15.249 requirements.


Please refer to the test plots as below.

Test Channel	Low	Polarity:	Horizontal (worst case)
--------------	-----	-----------	-------------------------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2310.000	39.84	-9.66	30.18	54.00	-23.82	Ave Detector
	2310.000	52.27	-9.66	42.61	74.00	-31.39	Peak Detector
2	2390.000	42.53	-9.50	33.03	54.00	-20.97	Ave Detector
	2380.000	54.95	-9.52	45.43	74.00	-28.57	Peak Detector
3	2400.000	57.58	-9.48	48.10	54.00	-5.90	Ave Detector
	2400.000	66.60	-9.48	57.12	74.00	-16.88	Peak Detector
4	2408.070	102.30	-9.47	92.83	/	/	Ave Detector
	2407.545	104.89	-9.47	95.42	/	/	Peak Detector

Test Channel	High	Polarity:	Horizontal (worst case)
--------------	------	-----------	-------------------------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2473.990	101.10	-9.34	91.76			Ave Detector
	2473.450	104.91	-9.34	95.57			Peak Detector
2	2483.500	54.31	-9.31	45.00	54.00	-9.00	Ave Detector
	2483.560	65.93	-9.31	56.62	74.00	-17.38	Peak Detector
3	2500.000	41.69	-9.28	32.41	54.00	-21.59	Ave Detector
	2500.000	53.80	-9.28	44.52	74.00	-29.48	Peak Detector

6. Emission Bandwidth

6.1 Standard Applicable

According to 15.215(c), intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated. The requirement to contain the designated bandwidth of the emission within the specified frequency band includes the effects from frequency sweeping, frequency hopping and other modulation techniques that may be employed as well as the frequency stability of the transmitter over expected variations in temperature and supply voltage. If a frequency stability is not specified in the regulations, it is recommended that the fundamental emission be kept within at least the central 80% of the permitted band in order to minimize the possibility of out-of-band operation.

6.2 Test Procedure

According to the ANSI 63.10-2013, the emission bandwidth test method as follows.

Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.

Set span = 1MHz, centered on a transmitting channel

RBW \geq 1% 20dB Bandwidth, VBW \geq RBW

Sweep = auto

Detector function = peak




Trace = max hold

All the trace to stabilize, use the marker-to-peak function to set the marker to the peak of the emission, use the marker-delta function to measure and record the 20dB down and 99% bandwidth of the emission.

6.3 Summary of Test Results/Plots

Test Channel	20dB Bandwidth(MHz)
Low Channel	2.068
Middle Channel	2.066
High Channel	2.069

Please refer to the following test plots

<p>Low Channel</p>	
<p>Middle Channel</p>	
<p>High Channel</p>	

***** END OF REPORT *****