



Report No. : HCT1405187FCC File reference No: 2014-06-03

Applicant:	AddOn Technology Co., Ltd.				
Product:	Mushroom Jumbo				
Brand Name:	Mushroom, Mushroom Wireless, ELESONIC, Add On, TELEFUNKEN, Freecom, DIGIX, U-MOVE, GECHO Speaker, Jumbo				
Model No:	Mushroom, Mushroom BT SP1, Mushroom BT SP2, Mushroom BT SP-3, EFT-BTS1, EFT-BTS2, EFT-BTS3, BT-100, BT-200, BT-300, BT-350, BT-400, TOUGH SPEAKER, ABuzz 1, ABuzz 2, ABuzz 3, Mushroom Jumbo, Mushroom Jumbo 1, Mushroom Jumbo2, Mushroom Jumbo 3, Boom 1, Boom 2, Boom 3				
Test Standards:	FCC Part 15 Subpart C, Paragraph 15.247				
Test result:	It is herewith confirmed and found to comply with the requirements set up by ANSI C63.4&FCC Part 15 Subpart C, Paragraph 15.247 regulations for the evaluation of electromagnetic compatibility				

Approved By

Ericim

Eric Lin Manager

Dated:

June 03, 2014

Results appearing herein relate only to the sample tested The technical reports is issued errors and omissions exempt and is subject to withdrawal at

Shenzhen HCT Technology Co.,Ltd.

Room104, Number3, Lane14, Shangshatangyan Village, Futian District, Shenzhen



Test Report Conclusion	
Content	

1.0	General Details	3
1.1	Applicant Details	3
1.2	Description of EUT	3
1.3	Submitted Sample	3
1.4	Test Duration	3
1.5	Test Uncertainty	3
1.6	Test By	3
2.0	List of Measurement Equipment	4
3.0	Technical Details	5
3.1	Summary of Test Results	5
3.2	Test Standards	5
4.0	Test Lab Details	5
5.0	Power Line Conducted Emission Test	6
5.1	Schematics of the Test	6
5.2	Test Method and Test Procedure	6
5.3	Configuration of the EUT	6
5.4	EUT Operating Condition	7
5.5	Conducted Emission Limit	7
5.6	Test Result	7
6.0	Radiated Emission test	10
6.1	Test Method and Test Procedure	10
6.2	Configuration of the EUT	10
6.3	EUT Operation Condition	10
6.4	Radiated Emission Limit	11
7.0	20dB Bandwidth Measurement	19
8.0	Maximum Peak Output Power	32
9.0	Carrier Frequency Separation	34
10.0	Number of Hopping Channel	38
11.0	Time of Occupancy (Dwell Time)	42
12.0	Out of Band Measurement	55
13.0	Antenna Requirement	68
14.0	FCC Label	69
15.0	Photo of Test Setup and EUT View	70

This report is issued in confidence to the client and it will be strictly treated as such by the. Shenzhen HCT Technology Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen HCT Technology Co.,Ltd . to his customer. Supplier or others persons directly concerned. Shenzhen HCT Technology Co.,Ltd . will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen HCT Technology Co.,Ltd . reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.



1.0 General Details

1.1 Applicant Details

Applicant:	AddOn Technology Co., Ltd.
Address:	1F, No.11, Lane 206, Da An Road, Sec.1, Taipei, Taiwan
Telephone:	886-2-2917-5726
Fax:	886-2-2917-5921

1.2 Description of EUT

1	
Product:	Mushroom Jumbo
Manufacturer:	AddOn Technology Co., Ltd.
Address:	1F, No.11, Lane 206, Da An Road, Sec.1, Taipei, Taiwan
Brand Name:	Mushroom
Model Number:	Mushroom
Additional Model Name	Mushroom BT SP1, Mushroom BT SP2, Mushroom BT SP-3, EFT-BTS1, EFT-BTS2, EFT-BTS3, BT-100, BT-200, BT-300, BT-350, BT-400, TOUGH SPEAKER, ABuzz 1, ABuzz 2, ABuzz 3, Mushroom Jumbo,
	Mushroom Jumbo 1, Mushroom Jumbo 2, Mushroom Jumbo 3, Boom 1,
	Boom 2, Boom 3
Additional Trade Name	Mushroom Wireless, ELESONIC, Add On, TELEFUNKEN, Freecom, DIGIX,
	U-MOVE, GECHO Speaker, Jumbo
Rating:	3.7V with 1050 mAh powered by Li-ion Battery
Power Supply	N/A
Type of Modulation	GFSK, II/4DQPSK, 8DPSK
Frequency range	2402-2480MHz
Number of Channel	79
Frequency Selection	By software
Antenna type	PCB Printed antenna, and the maximum Gain of this antenna is 1.13dBi

1.3 Submitted Sample: 2 Samples

1.4 Test Duration: 2014-05-23 to 2014-05-30

1.5 Test Uncertainty

Conducted Emissions Uncertainty =3.6dB Radiated Emissions Uncertainty =4.7dB

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the. Shenzhen HCT Technology Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen HCT Technology Co.,Ltd . to his customer. Supplier or others persons directly concerned. Shenzhen HCT Technology Co.,Ltd . will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.



Page 4 of 79

1.6

Test Engineer

The sample tested by

Print Name: Willis Gui

2.0	Test Equipments				
Instrument Type	Manufacturer	Model	Serial No.	Date of Cal.	Due Date
ESPI Test Receiver	ROHDE&SCHWA RZ	ESPI 3	100379	2013-08-26	2014-08-25
EMI Test Receiver	Rohde & Schwarz	ESU	1302.6005.26	2013-08-26	2014-08-25
Impuls-Begrenzer	ROHDE&SCHWA RZ	ESH3-Z2	100281	2013-08-26	2014-08-25
Loop Antenna	EMCO	6502	00042960	2013-08-26	2014-08-25
ESPI Test Receiver	ROHDE&SCHWA RZ	ESI26	838786/013	2013-08-26	2014-08-25
3m OATS			N/A	2013-08-26	2014-08-25
Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170399	2013-08-26	2014-08-25
Horn Antenna	SCHWARZBECK	BBHA 9120	D143	2013-08-26	2014-08-25
Power meter	Anritsu	ML2487A	6K00003613	2013-08-26	2014-08-25
Power sensor	Anritsu	MA2491A	32263	2013-08-26	2014-08-25
Bilog Antenna	Schwarebeck	VULB916 3	9163/142	2013-08-26	2014-08-25
LISN (Three Phase)	Schwarebeck	NSLK 8126	8126453	2013-08-26	2014-08-25
9*6*6 Anechoic			N/A	2013-08-26	2014-08-25
EMI Test Receive	r RS	ESCS30	100139	2013-08-26	2014-08-25
LISN	RS	ESH2-Z5	100225	2013-08-26	2014-08-25
LISN (Three Phase)	Schwarebeck	NSLK 8126	8126453	2013-08-26	2014-08-25
Pre-Amplifier	A.H.	PAM-0126	1415261	2013-08-26	2014-08-25

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the. Shenzhen HCT Technology Co., Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen HCT Technology Co., Ltd . to his customer. Supplier or others persons directly concerned. Shenzhen HCT Technology Co., Ltd . will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.



3.0 Technical Details

3.1 Summary of test results

The EUT has been tested according to the following specifications:					
Requirement	CFR 47 Section	Result	Notes		
Antenna Requirement	15.203, 15.247(b)(4)	PASS	Complies		
Maximum Peak Out Power	15.247 (b)(1), (4)	PASS	Complies		
Carrier Frequency Separation	15.247(a)(1)	PASS	Complies		
20dB Channel Bandwidth	15.247 (a)(1)	PASS	Complies		
Number of Hopping Channels	15.247(a)(iii), 15.247(b)(1)	PASS	Complies		
Time of Occupancy (Dwell Time)	15.247(a)(iii)	PASS	Complies		
Spurious Emission, Band Edge, and	15.247(d),15.205(a),	PASS	Complies		
Restricted bands	15.209 (a),15.109				
Conducted Emissions	15.207(a), 15.107	PASS	Complies		
RF Exposure	15.247(i), 1.1307(b)(1)	PASS	Complies		

3.2 Test Standards

FCC Part 15 Subpart & Subpart C, Paragraph 15.247

4.0 Test Lab Details

Name: Shenzhen Emtek Co., Ltd.


Address: Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052China FCC Registration Number: 406365


The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the. Shenzhen HCT Technology Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen HCT Technology Co.,Ltd . to his customer. Supplier or others persons directly concerned. Shenzhen HCT Technology Co.,Ltd . will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.



5. Power Line Conducted Emission Test






EUT: Equipment Under Test

5.2 Test Method and test Procedure

The EUT was tested according to ANSI C63.4-2003. The Frequency spectrum From 0.15MHz to 30MHz was investigated. The LISN used was 50ohm/50uH as specified by section 5.1 of ANSI C63.4 –2003. Test Voltage: 120V~, 60Hz

Block diagram of Test setup



5.3 Configuration of The EUT

The EUT was configured according to ANSI C63.4-2003. All interface ports were connected to the appropriate peripherals. All peripherals and cables are listed below. 79 channels are provided to the EUT

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the. Shenzhen HCT Technology Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen HCT Technology Co.,Ltd . to his customer. Supplier or others persons directly concerned. Shenzhen HCT Technology Co.,Ltd . will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.



A. EUI

Device	Manufacturer	Model	FCC ID
Mushroom	AddOn Technology	Mushroom, Mushroom BT SP1, Mushroom BT	Z2HMS5312
Jumbo	Co., Ltd.	SP2, Mushroom BT SP-3, EFT-BTS1,	
		EFT-BTS2, EFT-BTS3, BT-100, BT-200,	
		BT-300, BT-350, BT-400, TOUGH SPEAKER,	
		ABuzz 1, ABuzz 2, ABuzz 3, Mushroom Jumbo,	
		Mushroom Jumbo 1, Mushroom Jumbo2,	
		Mushroom Jumbo 3, Boom 1, Boom 2, Boom 3	

B. Internal Device

Device	Manufacturer	Model	FCC ID/DOC
N/A			

C. Peripherals

Device Manufacturer		Model	FCC ID/DOC	Cable
Note Book	IBM	R4	FCC DOC	
Power	Great Wall	GA90SC1-194730	FCC DOC	
Supply				

5.4 EUT Operating Condition

Operating condition is according to ANSI C63.4 -2003.

- A Setup the EUT and simulators as shown on follow
- B Enable AF signal and confirm EUT active to normal condition

5.5 Power line conducted Emission Limit according to Paragraph 15.107, 15.207 and RSS-210

Frequency	Class A Limits (dB µ V)		Class B Limits (dB µ V)		
(MHz)	Quasi-peak Level	Average Level	Quasi-peak Level	Average Level	
$0.15~\sim~0.50$	79.0	66.0	66.0~56.0*	56.0~46.0*	
$0.50~\sim~5.00$	73.0	60.0	56.0	46.0	
$5.00~\sim~30.00$	73.0	60.0	60.0	50.0	

Notes: 1. *Decreasing linearly with logarithm of frequency.

2. The tighter limit shall apply at the transition frequencies

5.6 Test Results

The frequency spectrum from 0.15MHz to 30MHz was investigated. All reading are

quasi-peak values with a resolution bandwidth of 9kHz.

Note: the worse cases was selected to conducted the test

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the. Shenzhen HCT Technology Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen HCT Technology Co.,Ltd . to his customer. Supplier or others persons directly concerned. Shenzhen HCT Technology Co.,Ltd . will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen HCT Technology Co.,Ltd . reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.



Conducted Emission on Line Terminal of the power line (150kHz to 30MHz) A


Pass

EUT set Condition:

Results:

Charging and Bluetooth keep transmitting

Please refer to following diagram for individual



Erecuency		Reading	Limit			
Frequency (MHz)	Neutral		Line		(dB µ V)	
	Quasi-peak	Average	Quasi-peak	Average	Quasi-peak	Average
0.414			43.28	21.28	57.56	47.56
0.178			40.73	16.63	64.57	54.57
0.150			56.69	15.49	66.00	56.00
2.356			34.01	15.01	56.00	46.00
10.687			34.54	12.54	60.00	50.00


The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the. Shenzhen HCT Technology Co., Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen HCT Technology Co., Ltd . to his customer. Supplier or others persons directly concerned. Shenzhen HCT Technology Co., Ltd . will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.



B Conducted Emission on Neutral Terminal of the power line (150kHz to 30MHz)


Pass



Charging and Bluetooth keep transmitting

Results:

Please refer to following diagram for individual



Fraguanay		Reading(dB µ V)				Limit	
Frequency (MHz)	Neutral		Line		(dB µ V)		
(IVITIZ)	Quasi-peak	Average	Quasi-peak	Average	Quasi-peak	Average	
0.150	54.83	30.53			65.96	55.96	
0.182	52.30	31.40			64.38	54.38	
0.426	41.91	22.61			57.32	47.32	
2.311	39.42	21.42			56.00	46.00	
1.220	39.77	19.77			56.00	46.00	


This report is issued in confidence to the client and it will be strictly treated as such by the. Shenzhen HCT Technology Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen HCT Technology Co.,Ltd . to his customer. Supplier or others persons directly concerned. Shenzhen HCT Technology Co.,Ltd . will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen HCT Technology Co.,Ltd . reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.



6 Radiated Emission Test

- 6.1 Test Method and test Procedure:
- (1) The EUT was tested according to ANSI C63.4 –2003. The radiated test was performed at EMTEK Laboratory. This site is on file with the FCC laboratory division, Registration No. 406365
- (2) The EUT, peripherals were put on the turntable which table size is 1m x 1.5 m, table high 0.8 m. All set up is according to ANSI C63.4-2003.
- (3) The frequency spectrum from 30 MHz to 1 GHz was investigated. All readings from 30 MHz to 1 GHz are quasi-peak values with a resolution bandwidth of 120 kHz. For measurement above 1GHz, peak values with RBW=VBW=1MHz and PK detector. AV value with RBW=1MHz, VBW=10Hz and PK detector. Measurements were made at 3 meters.
- (4) The antenna high is varied from 1 m to 4 m high to find the maximum emission for each frequency.
- (5) Maximizing procedure was performed on the six (6) highest emissions to ensure EUT compliance is with all installation combinations. All data was recorded in the peak detection mode. Quasi-peak readings was performed only when an emission was found to be marginal (within -4 dB of specification limit), and are distinguished with a "**QP**" in the data table.
- (6) The antenna polarization: Vertical polarization and Horizontal polarization.



- 6.2 Configuration of The EUT Same as section 5.3 of this report
- 6.3 EUT Operating Condition
 - Same as section 5.4 of this report.

This report is issued in confidence to the client and it will be strictly treated as such by the. Shenzhen HCT Technology Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen HCT Technology Co.,Ltd . to his customer. Supplier or others persons directly concerned. Shenzhen HCT Technology Co.,Ltd . will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen HCT Technology Co.,Ltd . reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.



6.4 Radiated Emission Limit

All emission from a digital device, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strength specified below:

Frequency Range (MHz)	Distance (m)	Field strength (dB μ V/m)
30-88	3	40.0
88-216	3	43.5
216-960	3	46.0
Above 960	3	54.0

Frequencies in restricted band are complied to limit on Paragraph 15.109. 15.209

Note: 1. RF Voltage $(dBuV) = 20 \log RF$ Voltage (uV)

2. In the Above Table, the higher limit applies at the band edges.

3. Distance refers to the distance in meters between the measuring instrument antenna and the EUT

4. This is a handhold device. The radiated emissions should be tested under 3-axes position (Lying, Side, and Stand), After pre-test. It was found that the worse radiated emission was get at the lying position.

5. Battery was fully charged during the radiated test.

6. After pre-scan, GFSK modulation mode was the worse case and it was selected to conduct the radiated emission tests.


This report is issued in confidence to the client and it will be strictly treated as such by the. Shenzhen HCT Technology Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen HCT Technology Co.,Ltd . to his customer. Supplier or others persons directly concerned. Shenzhen HCT Technology Co.,Ltd . will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen HCT Technology Co.,Ltd . reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

/m



Test result General Radiated Emission Data and Harmonics Radiated Emission Data Radiated Emission In Horizontal (30MHz----1000MHz) EUT set Condition: Transmitting Mode (GFSK) **Results:** Pass Test Figure: Transmitting mode Η RBW 120 kHz MТ 50 µs Att 10 dB PREAMP ON dBµV 100 MHz 1 GHz 80 70 -60



Date: 23.MAY.2014 16:39:04


Frequency (MHz)	Level@3m (dBµV/m)	Antenna Polarity	Limit@3m (dBµV/m)
		Н	

-The test data shows much less than the limit, no necessary to take down the records.

This report is issued in confidence to the client and it will be strictly treated as such by the. Shenzhen HCT Technology Co., Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen HCT Technology Co., Ltd . to his customer. Supplier or others persons directly concerned. Shenzhen HCT Technology Co., Ltd . will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen HCT Technology Co., Ltd. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.





Date: 23.MAY.2014 16:42:05

Frequency (MHz)	Level@3m (dBµV/m)	Antenna Polarity	Limit@3m (dBµV/m)
		V	

-The test data shows much less than the limit, no necessary to take down the records.

This report is issued in confidence to the client and it will be strictly treated as such by the. Shenzhen HCT Technology Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen HCT Technology Co.,Ltd . to his customer. Supplier or others persons directly concerned. Shenzhen HCT Technology Co.,Ltd . will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen HCT Technology Co.,Ltd . reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.



Operation Mode: Transmitting under Low Channel (2402MHZ)							
Frequency (MHz)	Level@3m (dB μ V/m)	Antenna Polarity	Limit@3m (dB µ V/m)				
2402	84.92(PK)	V	Evendomental Encourance				
2402	85.87(PK)	Н	Fundamental Frequency				
4804		Н	74(Peak)/ 54(AV)				
4804		V	74(Peak)/ 54(AV)				
7206		H/V	74(Peak)/ 54(AV)				
9608		H/V	74(Peak)/ 54(AV)				
12010		H/V	74(Peak)/ 54(AV)				
14412		H/V	74(Peak)/ 54(AV)				
16814		H/V	74(Peak)/ 54(AV)				
19216		H/V	74(Peak)/ 54(AV)				
21618		H/V	74(Peak)/ 54(AV)				
24020		H/V	74(Peak)/ 54(AV)				

Operation Mode: Transmitting under Low Channel (2402MHz)

Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

2. Remark "---" means that the emissions level is too low to be measured

Operation w	Operation Mode. Transmitting _ under Midule Channel (2441Millz)						
Frequency (MHz)	Level@3m (dB μ V/m)	Antenna Polarity	Limit@3m (dB µ V/m)				
2441	84.86(PK)	Н	Fundamental Frequency				
2441	85.36(PK)	V	Fundamental Frequency				
4882		Н	74(Peak)/ 54(AV)				
4882		V	74(Peak)/ 54(AV)				
7323		H/V	74(Peak)/ 54(AV)				
9764		H/V	74(Peak)/ 54(AV)				
12205		H/V	74(Peak)/ 54(AV)				
14646		H/V	74(Peak)/ 54(AV)				
17087		H/V	74(Peak)/ 54(AV)				
19528		H/V	74(Peak)/ 54(AV)				
21969		H/V	74(Peak)/ 54(AV)				
24410		H/V	74(Peak)/ 54(AV)				

Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

2. Remark "---" means that the emissions level is too low to be measured

This report is issued in confidence to the client and it will be strictly treated as such by the. Shenzhen HCT Technology Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen HCT Technology Co.,Ltd . to his customer. Supplier or others persons directly concerned. Shenzhen HCT Technology Co.,Ltd . will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen HCT Technology Co.,Ltd . reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.



operation	Operation Mode. Transmitting under Trign Channel						
Frequency (MHz)	Level@3m (dB μ V/m)	Antenna Polarity	Limit@3m (dB µ V/m)				
2480	86.82(PK)	Н	Eurodomontol Enoquenery				
2480	86.48(PK)	V	Fundamental Frequency				
4960		Н	74(Peak)/ 54(AV)				
4960		V	74(Peak)/ 54(AV)				
7440		H/V	74(Peak)/ 54(AV)				
9920		H/V	74(Peak)/ 54(AV)				
12400		H/V	74(Peak)/ 54(AV)				
14880		H/V	74(Peak)/ 54(AV)				
17360		H/V	74(Peak)/ 54(AV)				
19840		H/V	74(Peak)/ 54(AV)				
22320		H/V	74(Peak)/ 54(AV)				
24800		H/V	74(Peak)/ 54(AV)				

Operation Mode: Transmitting under High Channel

Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit


2. Remark "---" means that the emissions level is too low to be measured

This report is issued in confidence to the client and it will be strictly treated as such by the. Shenzhen HCT Technology Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen HCT Technology Co.,Ltd . to his customer. Supplier or others persons directly concerned. Shenzhen HCT Technology Co.,Ltd . will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen HCT Technology Co.,Ltd . reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.



Please refer to the following test plots for details: Low Channel: Vertical




The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the. Shenzhen HCT Technology Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen HCT Technology Co.,Ltd . to his customer. Supplier or others persons directly concerned. Shenzhen HCT Technology Co.,Ltd . will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.



Middle Channel : Horizontal




The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the. Shenzhen HCT Technology Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen HCT Technology Co.,Ltd . to his customer. Supplier or others persons directly concerned. Shenzhen HCT Technology Co.,Ltd . will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.



High Channel : Horizontal



FCC rule.

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the. Shenzhen HCT Technology Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen HCT Technology Co.,Ltd . to his customer. Supplier or others persons directly concerned. Shenzhen HCT Technology Co.,Ltd . will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen HCT Technology Co.,Ltd . reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.



7.0 20dB Bandwidth Measurement 7.1 Regulation

According to \$15.247(b)(1), for frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts. According to \$15.247(b)(4), the conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

7.2 Limits of 20dB Bandwidth Measurement

N/A

7.3 Test Procedure.

1. Check the calibration of the measuring instrument (spectrum analyzer) using either an internal calibrator or a known signal from an external generator.

2. Set the spectrum analyzer as follows: Span = 3MHz, RBW=30 kHz, VBW=100 kHz,

Sweep = auto Detector function = peak Trace = max hold

3. Measure the highest amplitude appearing on spectral display and record the level to calculate results. Repeat above procedures until all frequencies measured were complete.

7.4 Test Result:

This report is issued in confidence to the client and it will be strictly treated as such by the. Shenzhen HCT Technology Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen HCT Technology Co.,Ltd . to his customer. Supplier or others persons directly concerned. Shenzhen HCT Technology Co.,Ltd . will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen HCT Technology Co.,Ltd . reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.



GFSK Modulation

EU	Г	Mushroom Jumbo		Mod	Model		oom		
Mod	le	Keep	Transmitting Input Voltage		Transmitting Input Voltage DC3		DC3.	7V	
Temper	ature	24	24 deg. C, Humidity 56%		24 deg. C, Humidity 560		Humidity 56%		RH
Channel		el Frequency (MHz)	20 dB Channel (kHz)	Bandwidth	andwidth Maximum I (kHz)		Pass/ Fail		
Low		2402	966				Pass		
Middle		2441 966					Pass		
High		2480	948				Pass		


This report is issued in confidence to the client and it will be strictly treated as such by the. Shenzhen HCT Technology Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen HCT Technology Co.,Ltd . to his customer. Supplier or others persons directly concerned. Shenzhen HCT Technology Co.,Ltd . will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen HCT Technology Co.,Ltd . reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.



Test Figure:

1. Condition: Low Channel




Date: 27.MAY.2014 19:56:17

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the. Shenzhen HCT Technology Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen HCT Technology Co.,Ltd . to his customer. Supplier or others persons directly concerned. Shenzhen HCT Technology Co.,Ltd . will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.






2. Condition: Middle Channel


Date: 27.MAY.2014 19:57:23

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the. Shenzhen HCT Technology Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen HCT Technology Co.,Ltd . to his customer. Supplier or others persons directly concerned. Shenzhen HCT Technology Co.,Ltd . will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.







Date: 27.MAY.2014 19:58:18

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the. Shenzhen HCT Technology Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen HCT Technology Co.,Ltd . to his customer. Supplier or others persons directly concerned. Shenzhen HCT Technology Co.,Ltd . will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.



Л/4DQPSK Modulation

EU	Г	Mushroom Jumbo N		Model		Mushroom			
Mod	le	Keep '	o Transmitting Input Voltag		Transmitting Input Voltage DC		DTransmitting Input Voltage DC3.7		7V
Temper	ature	24	24 deg. C, Humidity 56% R		24 deg. C, Humidity 56%		Humidity 56		RH
Channel		el Frequency (MHz)	20 dB Channel B (kHz)	andwidth Maximum Lin (kHz)			Pass/ Fail		
Low		2402	1308				Pass		
Middle		2441	1314				Pass		
High		2480	1314				Pass		


This report is issued in confidence to the client and it will be strictly treated as such by the. Shenzhen HCT Technology Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen HCT Technology Co.,Ltd . to his customer. Supplier or others persons directly concerned. Shenzhen HCT Technology Co.,Ltd . will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen HCT Technology Co.,Ltd . reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.



Test Figure:

Low Channel




Date: 27.MAY.2014 20:00:55

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the. Shenzhen HCT Technology Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen HCT Technology Co.,Ltd . to his customer. Supplier or others persons directly concerned. Shenzhen HCT Technology Co.,Ltd . will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.



Middle Channel




Date: 27.MAY.2014 19:59:58

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the. Shenzhen HCT Technology Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen HCT Technology Co.,Ltd . to his customer. Supplier or others persons directly concerned. Shenzhen HCT Technology Co.,Ltd . will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.



High Channel



Date: 27.MAY.2014 19:59:06

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the. Shenzhen HCT Technology Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen HCT Technology Co.,Ltd . to his customer. Supplier or others persons directly concerned. Shenzhen HCT Technology Co.,Ltd . will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.



8DPSK Modulation

EU	Г	Mush	Mushroom Jumbo N		Model		oom			
Mod	le	Keep	Transmitting Input Volta		Transmitting Input Voltage		Transmitting Input Voltage DC3		DC3.	7V
Temper	ature	24	l deg. C,	Humidity 5		Humidity 56% RH		RH		
Channel		el Frequency (MHz)	20 dB Channel B (kHz)			num Limit (kHz)	Pass/ Fail			
Low		2402	02 1296				Pass			
Middle		2441	1290				Pass			
High		2480	1302				Pass			


This report is issued in confidence to the client and it will be strictly treated as such by the. Shenzhen HCT Technology Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen HCT Technology Co.,Ltd . to his customer. Supplier or others persons directly concerned. Shenzhen HCT Technology Co.,Ltd . will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen HCT Technology Co.,Ltd . reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.



Test Figure:

Low Channel




Date: 27.MAY.2014 20:01:44

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the. Shenzhen HCT Technology Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen HCT Technology Co.,Ltd . to his customer. Supplier or others persons directly concerned. Shenzhen HCT Technology Co.,Ltd . will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.



Middle Channel




Date: 27.MAY.2014 20:02:33

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the. Shenzhen HCT Technology Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen HCT Technology Co.,Ltd . to his customer. Supplier or others persons directly concerned. Shenzhen HCT Technology Co.,Ltd . will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.



High Channel



Date: 27.MAY.2014 20:03:32

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the. Shenzhen HCT Technology Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen HCT Technology Co.,Ltd . to his customer. Supplier or others persons directly concerned. Shenzhen HCT Technology Co.,Ltd . will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.



8. Maximum Peak Output Power

8.1 Regulation

According to §15.247(b)(1), for frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5MHz band:0.125 watts. According to §15.247(b)(4), the conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

8.2 Limits of Maximum Peak Output Power

The Maximum Peak Output Power Measurement is 30dBm.

8.3 Test Procedure

1. Check the calibration of the measuring instrument (spectrum analyzer) using either an internal calibrator or a known signal from an external generator.

2. Set the spectrum analyzer as follows: Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel; RBW > the 20 dB bandwidth of the emission being measured; VBW \ge RBW; Sweep = auto; Detector function = peak; Trace = max hold

3. Measure the highest amplitude appearing on spectral display and record the level to calculate results.

4. Repeat above procedures until all frequencies measured were complete.

EUT		Mushroom Jumbo		Model		Mushroom	
Mode		Keep Transmitting		Input Voltage		DC3.7V	
Temperature		24 deg. C,		Humidity		56% RH	
Channel	Cha	annel Frequency (MHz)	Peak Power Output (dBm)		Peak Power Limit (dBm)		Pass/ Fail
Low		2402	-2.33		30		Pass
Middle		2441	-2.39		30		Pass
High		2480	-2.91		30)	Pass

8.4Test Results (GFSK MODE)

This report is issued in confidence to the client and it will be strictly treated as such by the. Shenzhen HCT Technology Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen HCT Technology Co.,Ltd . to his customer. Supplier or others persons directly concerned. Shenzhen HCT Technology Co.,Ltd . will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen HCT Technology Co.,Ltd . reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.



8.5Test Results (II/4DQPSK MODE)

EUT		Mushroom Jumbo		Model		Mushroom	
Mode		Keep Transmitting		Input Voltage		DC3.7V	
Temperature		24 deg. C,		Humidity		56% RH	
Channel	Cha	hannel Frequency Peak Power Output (MHz) (dBm)		Peak P Lin (dB	nit	Pass/ Fail	
Low		2402	-4.10		30		Pass
Middle		2441 -4.19			30		Pass
High		2480 -4.80			30		Pass

8.6Test Results (8DPSK MODE)

EUT		Mushroom Jumbo		Model		Mushroom	
Mode		Keep Transmitting		Input Voltage		DC3.7V	
Temperature		24 deg. C,		Humidity		56% RH	
Channel	Cha	annel Frequency (MHz)	Peak Power ((dBm)	Output	Peak Power Limit (dBm)		Pass/ Fail
Low		2402	-3.95		30		Pass
Middle		2441	2441 -3.98		30		Pass
High		2480	80 -4.65		30		Pass

Note: the result basic equation calculation as follow:

Peak Power Output = Peak Power Reading + Cable loss + Attenuator

This report is issued in confidence to the client and it will be strictly treated as such by the. Shenzhen HCT Technology Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen HCT Technology Co.,Ltd . to his customer. Supplier or others persons directly concerned. Shenzhen HCT Technology Co.,Ltd . will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen HCT Technology Co.,Ltd . reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.



9. Carrier Frequency Separation

9.1 Regulation

According to §15.247(a)(1), frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

9.2 Limits of Carrier Frequency Separation

The Maximum Power Spectral Density Measurement is 25kHz or two-thirds of the 20dB bandwidth of the hopping Channel which is great.

9.3 Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.

2. Set the spectrum analyzer as follows: Span = wide enough to capture the peaks of two adjacent channels: Resolution (or IF) Bandwidth (RBW) $\geq 1\%$ of the span; Video (or Average) Bandwidth (VBW) $\geq RBW$; Sweep = auto; Detector function = peak; Trace = max hold

3. Measure the separation between the peaks of the adjacent channels using the marker-delta function.

4. Repeat above procedures until all frequencies measured were complete.

9.4Test Result

This report is issued in confidence to the client and it will be strictly treated as such by the. Shenzhen HCT Technology Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen HCT Technology Co.,Ltd . to his customer. Supplier or others persons directly concerned. Shenzhen HCT Technology Co.,Ltd . will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen HCT Technology Co.,Ltd . reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.




GFSK Modulation

EUT		Mushroom Jumbo		Model		Mushroom	
Mode		Hopping On		Input Voltage		DC3.7V	
Temperature		24 deg. C,		Humidity		56% RH	
Channel	Ch	annel Frequency (MHz)	Carrier Frequency Separation		Limit		Pass/ Fail
Middle		2441	1.010MHz		 ≥ 25 kHz or two-thirds of 20 dB bandwidth 		Pass

Test Plots

Middle Channel



Date: 27.MAY.2014 20:39:13

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the. Shenzhen HCT Technology Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen HCT Technology Co.,Ltd . to his customer. Supplier or others persons directly concerned. Shenzhen HCT Technology Co.,Ltd . will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.




Л/4DQPSK Modulation

EUT		Mushroom Jumbo		Model		Mushroom	
Mode		Hopping On		Input Voltage		DC3.7V	
Temperature		24 deg. C,		Humidity		56% RH	
Channel	Ch	annel Frequency (MHz)	Carrier Frequency Separation		Limit		Pass/ Fail
Middle		2441	1.000MHz		≥ 25 kHz ortwo-thirds of 20dB bandwidth		Pass

Test Plots

Middle Channel



Date: 27.MAY.2014 20:32:32

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the. Shenzhen HCT Technology Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen HCT Technology Co.,Ltd . to his customer. Supplier or others persons directly concerned. Shenzhen HCT Technology Co.,Ltd . will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.




8DPSK Modulation

EUT		Mushroon	Jumbo Mo		odel	Mushroom		
Mode		Hoppin	ng On Input V		Input Voltage		C3.7V	
Temperat	ure	24 deg	g. C,	Hur	nidity 56		56% RH	
Channel	Ch	annel Frequency (MHz)	Carrier Frequency Separation		Lin	nit	Pass/ Fail	
Middle		2441	1.000MH	[z	≥ 25 k two-third dB band	ls of 20	Pass	

Test Plots

Middle Channel



Date: 27.MAY.2014 20:28:28

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the. Shenzhen HCT Technology Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen HCT Technology Co.,Ltd . to his customer. Supplier or others persons directly concerned. Shenzhen HCT Technology Co.,Ltd . will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.



10. Number of Hopping Channels 10.1 Regulation

According to §15.247(a)(1)(iii), frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used. According to §15.247(b)(1), for frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.

10.2 Limits of Number of Hopping Channels

The frequency hopping systems in the 2400-2483.5MHz band shall use at least 15 channels.

10.3 Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.

2. Set the spectrum analyzer as follows: Span = the frequency band of operation; RBW $\geq 1\%$ of the span; VBW \geq RBW; Sweep = auto; Detector function = peak; Trace = max hold

3. Record the number of hopping channels.

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the. Shenzhen HCT Technology Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen HCT Technology Co.,Ltd . to his customer. Supplier or others persons directly concerned. Shenzhen HCT Technology Co.,Ltd . will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.


In the event of the improper use of the report. The Shenzhen HCT Technology Co.,Ltd . reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.



10.4Test Result (GFSK MODE)

EUT	Mushroom Jumbo		Model		Mı	ıshroom
Mode	Hopping On		Input Voltage D		C3.7V	
Temperature	24 deg. C,		Humidity		50	5% RH
Operating Frequency		ncy Number of hopping char		Lin	nit	Pass/ Fail
2402-2480MHz		79		≥ 1	5	Pass

Test Plot (GFSK MODE)



Date: 27.MAY.2014 20:11:53

The report refers only to the sample tested and does not apply to the bulk.


This report is issued in confidence to the client and it will be strictly treated as such by the. Shenzhen HCT Technology Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen HCT Technology Co.,Ltd . to his customer. Supplier or others persons directly concerned. Shenzhen HCT Technology Co.,Ltd . will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.



10.5 Test Result (Π/4DQPSK MODE)

EUT	Mushroom Jumbo		Model		Mushroom	
Mode	Hopping On		Input Voltage D		C3.7V	
Temperature	24 deg. C,		Humidity		50	5% RH
Operating Frequency		Number of hopping char		Lin	nit	Pass/ Fail
2402-2480MHz		79		≥ 1	5	Pass

Test Plot (Π/4DQPSK MODE)



Date: 27.MAY.2014 20:14:30

The report refers only to the sample tested and does not apply to the bulk.


This report is issued in confidence to the client and it will be strictly treated as such by the. Shenzhen HCT Technology Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen HCT Technology Co.,Ltd . to his customer. Supplier or others persons directly concerned. Shenzhen HCT Technology Co.,Ltd . will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.



10.5 Test Result (8DSK MODE)

EUT	Mushroom Jumbo		Model		Mı	ıshroom
Mode		Hopping On		Input Voltage I		C3.7V
Temperature	24 deg. C,		Humidity		50	5% RH
Operating Frequ	iency	ncy Number of hopping char		Lin	nit	Pass/ Fail
2402-2480MHz		79		≥ 1	5	Pass

Test Plot (8DPSK MODE)



Date: 27.MAY.2014 20:21:19

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the. Shenzhen HCT Technology Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen HCT Technology Co.,Ltd . to his customer. Supplier or others persons directly concerned. Shenzhen HCT Technology Co.,Ltd . will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.



11. Time of Occupancy (Dewell Time)

11.1 Regulation

According to §15.247(a)(1)(iii), frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

11.2 Limits of Carrier Frequency Separation

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed

11.3 Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.

2. Set the spectrum analyzer as follows: Span = zero span, centered on a hopping channel; RBW = 1 MHz; VBW

 \geq RBW; Sweep = as necessary to capture the entire dwell time per hopping channel; Detector function = peak; Trace = max hold

3. Measure the dwell time using the marker-delta function.

4. Repeat above procedures until all frequencies measured were complete.

5. Repeat this test for different modes of operation (e.g., data rate, modulation format, etc.), if applicable.

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the. Shenzhen HCT Technology Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen HCT Technology Co.,Ltd . to his customer. Supplier or others persons directly concerned. Shenzhen HCT Technology Co.,Ltd . will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen HCT Technology Co.,Ltd . reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.



11.4 Test Result

GFSK Modulation

EUT		Mushroom Jumbo			Mode	1	Mushroom
Mode		K	Keep Transmitting			tage	DC3.7
Temperatur	re		24 deg. C,			ty	56% RH
Channel		Reading	Hoping Rate	P	Actual		Limit
Low		2.96	266.667 hop/s	0.316			0.4s
Middle		2.96	266.667 hop/s	(0.316		0.4s
High		2.96	266.667 hop/s		0.316		0.4s

Actual = Reading \times (Hopping rate / Number of channels) \times Test period, Test period = 0.4 [seconds / channel] \times 79 [channel] = 31.6 [seconds] NOTE: The EUT makes worst case 1600 hops per second or 1 time slot has a length of 625µs with 79 channels. A DH1 Packet needs 5 time slot for transmitting and 1 time slot for receiving. Then the EUT makes worst case 266.667 hops per second with 79 channels.

Note: DH5 is the worse case

The report refers only to the sample tested and does not apply to the bulk.


This report is issued in confidence to the client and it will be strictly treated as such by the. Shenzhen HCT Technology Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen HCT Technology Co.,Ltd . to his customer. Supplier or others persons directly concerned. Shenzhen HCT Technology Co.,Ltd . will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen HCT Technology Co.,Ltd . reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.



Test Plots:

Low Channel:




Date: 27.MAY.2014 20:56:43

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the. Shenzhen HCT Technology Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen HCT Technology Co.,Ltd . to his customer. Supplier or others persons directly concerned. Shenzhen HCT Technology Co.,Ltd . will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.



Middle Channel:



Date: 27.MAY.2014 20:57:10

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the. Shenzhen HCT Technology Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen HCT Technology Co.,Ltd . to his customer. Supplier or others persons directly concerned. Shenzhen HCT Technology Co.,Ltd . will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.



High Channel DELTA MARKER 2 RBW 1 MHz Delta 2 [T1] 2.96 ms *VBW 3 MHz 1.04 dB Ref 10 dBm * Att 20 dB SWT 10 ms 2.960000 ms 10 Marker 1 [T1 -67 77 dBm Α 620 00 -0 SGL 1 РК МАХН -10 -20 -30 -40 3DB -50 60 Mulu 1 mil -70 -80 -90 Center 2.48 GHz 1 ms/

Date:

27.MAY.2014 20:57:38

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the. Shenzhen HCT Technology Co., Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen HCT Technology Co., Ltd . to his customer. Supplier or others persons directly concerned. Shenzhen HCT Technology Co., Ltd . will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.



Л/4DQPSK Modulation

EUT		Mushroom Jumbo			Model		Mushroom
Mode		Ke	Keep Transmitting			tage	DC3.7
Temperatur	re		24 deg. C,			ty	56% RH
Channel		Reading	Hoping Rate	A	Actual		Limit
Low		2.96	266.667 hop/s	(0.316		0.4s
Middle		2.96	266.667 hop/s	(0.316		0.4s
High		2.98	266.667 hop/s	(0.318		0.4s

Actual = Reading × (Hopping rate / Number of channels) × Test period, Test period = 0.4 [seconds / channel] × 79 [channel] = 31.6 [seconds] NOTE: The EUT makes worst case 1600 hops per second or 1 time slot has a length of 625µs with 79 channels. A DH1 Packet needs 5 time slot for transmitting and 1 time slot for receiving. Then the EUT makes worst case 266.667 hops per second with 79 channels.


Note: DH5 is the worse case

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the. Shenzhen HCT Technology Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen HCT Technology Co.,Ltd . to his customer. Supplier or others persons directly concerned. Shenzhen HCT Technology Co.,Ltd . will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen HCT Technology Co.,Ltd . reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.






Date: 27.MAY.2014 20:59:21

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the. Shenzhen HCT Technology Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen HCT Technology Co.,Ltd . to his customer. Supplier or others persons directly concerned. Shenzhen HCT Technology Co.,Ltd . will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.



Middle Channel




Date: 27.MAY.2014 20:58:44

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the. Shenzhen HCT Technology Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen HCT Technology Co.,Ltd . to his customer. Supplier or others persons directly concerned. Shenzhen HCT Technology Co.,Ltd . will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.



High Channel



Date: 27.MAY.2014 20:58:15

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the. Shenzhen HCT Technology Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen HCT Technology Co.,Ltd . to his customer. Supplier or others persons directly concerned. Shenzhen HCT Technology Co.,Ltd . will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.



8DPSK Modulation

EUT		Mushroom Jumbo			Mode	1	Mushroom
Mode		K	Keep Transmitting			tage	DC3.7
Temperatur	re		24 deg. C,			ty	56% RH
Channel		Reading	Hoping Rate	A	Actual		Limit
Low		2.98	266.667 hop/s	(0.318		0.4s
Middle		2.98 266.667 hop/s		0.318		0.4s	
High		2.96	266.667 hop/s	(0.316		0.4s

Actual = Reading × (Hopping rate / Number of channels) × Test period, Test period = 0.4 [seconds / channel] × 79 [channel] = 31.6 [seconds] NOTE: The EUT makes worst case 1600 hops per second or 1 time slot has a length of 625µs with 79 channels. A DH1 Packet needs 5 time slot for transmitting and 1 time slot for receiving. Then the EUT makes worst case 266.667 hops per second with 79 channels.

Note: DH5 is the worse case


The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the. Shenzhen HCT Technology Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen HCT Technology Co.,Ltd . to his customer. Supplier or others persons directly concerned. Shenzhen HCT Technology Co.,Ltd . will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen HCT Technology Co.,Ltd . reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.



Low Channel




Date: 27.MAY.2014 20:59:44

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the. Shenzhen HCT Technology Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen HCT Technology Co.,Ltd . to his customer. Supplier or others persons directly concerned. Shenzhen HCT Technology Co.,Ltd . will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.



Middle Channel




Date: 27.MAY.2014 21:00:32

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the. Shenzhen HCT Technology Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen HCT Technology Co.,Ltd . to his customer. Supplier or others persons directly concerned. Shenzhen HCT Technology Co.,Ltd . will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.



High Channel



Date: 27.MAY.2014 21:00:58


The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the. Shenzhen HCT Technology Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen HCT Technology Co.,Ltd . to his customer. Supplier or others persons directly concerned. Shenzhen HCT Technology Co.,Ltd . will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.



12 Out of Band Measurement

12.1 Test Setup



The restricted band requirement based on radiated emission test; please see the clause 6 for the test setup

12.2 Limits of Out of Band Emissions Measurement

- 1. Below –20dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).
- 2. Fall in the restricted bands listed in section 15.205. The maximum permitted average field strength is listed in section 15.209.

12.3 Test Procedure

For signals in the restricted bands above and below the 2.4-2.483GHz allocated band a measurement was made of radiated emission test. (Peak values with RBW=VBW=1MHz and PK detector. AV value with RBW=1MHz, VBW=10Hz and PK detector)

For bandage test, the spectrum set as follows: RBW=VBW=100 kHz. A conducted measurement used

Note: 1. For band-edge measurement, the frequency from 30MHz-25GHz was tested. And It met the FCC rule.2. This is a handhold device. The radiated emissions should be tested under 3-axes position (Lying, Side, and Stand), After pre-test. It was found that the worse radiated emission was get at the lying position.

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the. Shenzhen HCT Technology Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen HCT Technology Co.,Ltd . to his customer. Supplier or others persons directly concerned. Shenzhen HCT Technology Co.,Ltd . will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen HCT Technology Co.,Ltd . reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.




Type of Modulation: GFSK

12.4 Out of Band Test Result

Product:	Mushroom Jumbo		Test Mode:	Low Channel
Mode	Keeping Transmitting I		Input Voltage	DC3.7V
Temperature		24 deg. C		56% RH
Test Result:		Pass	Detector	РК
The Max. FS in	PK (dBµV/m)	36.9		74(dBµV/m)
Restrict Band	AV(dBµV/m)		Limit	54(dBµV/m)
2390MHz				

Test Figure:



Date: 27.MAY.2014 20:42:42

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the. Shenzhen HCT Technology Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen HCT Technology Co.,Ltd . to his customer. Supplier or others persons directly concerned. Shenzhen HCT Technology Co.,Ltd . will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.




Type of Modulation: GFSK

12.4 Out of Band Test Result

Product:	Mushroom Jumbo		Test Mode:	High Channel
Mode	Keeping Transmitting		Input Voltage	DC3.7V
Temperature	24 deg. C,		Humidity	56% RH
Test Result:		Pass	Detector	РК
The Max. FS in	PK (dBµV/m)	39.6		74(dBµV/m)
Restrict Band	$AV(dB\mu V/m)$		Limit	54(dBµV/m)
2483.5MHz				

Test Figure:



Date: 27.MAY.2014 20:53:36

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the. Shenzhen HCT Technology Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen HCT Technology Co.,Ltd . to his customer. Supplier or others persons directly concerned. Shenzhen HCT Technology Co.,Ltd . will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.




Type of Modulation: GFSK

12.4 Out of Band Test Result

Product:	M	ushroom Jumbo	Test Mode:	Hopping mode
Mode		Hopping On	Input Voltage	DC3.7V
Temperature		24 deg. C,	Humidity	56% RH
Test Result:		Pass	Detector	РК
The Max. FS in	PK (dBµV/m)	37.2		74(dBµV/m)
Restrict Band	$AV(dB\mu V/m)$		Limit	54(dBµV/m)
2390MHz				

Test Figure:



Date: 27.MAY.2014 20:41:27

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the. Shenzhen HCT Technology Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen HCT Technology Co.,Ltd . to his customer. Supplier or others persons directly concerned. Shenzhen HCT Technology Co.,Ltd . will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.




Type of Modulation: GFSK

12.4 Out of Band Test Result

Product:	M	ushroom Jumbo	Test Mode:	Hopping mode
Mode	Hopping On I		Input Voltage	DC3.7V
Temperature		24 deg. C, H		56% RH
Test Result:		Pass	Detector	РК
The Max. FS in	PK (dBµV/m)	39.2		74(dBµV/m)
Restrict Band	$AV(dB\mu V/m)$		Limit	54(dBµV/m)
2483.5MHz				

Test Figure:



Date: 27.MAY.2014 20:55:22

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the. Shenzhen HCT Technology Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen HCT Technology Co.,Ltd . to his customer. Supplier or others persons directly concerned. Shenzhen HCT Technology Co.,Ltd . will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.




Type of Modulation: Л/4DQPSK

12.4 Out of Band Test Result

Product:	Mushroom Jumbo		Test Mode:	Low Channel
Mode	Kee	Keeping Transmitting I		DC3.7V
Temperature		24 deg. C H		56% RH
Test Result:		Pass	Detector	РК
The Max. FS in	PK (dBµV/m)	37.5		74(dBµV/m)
Restrict Band	AV(dBµV/m)		Limit	54(dBµV/m)
2390MHz				

Test Figure:



Date: 27.MAY.2014 20:43:20

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the. Shenzhen HCT Technology Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen HCT Technology Co.,Ltd . to his customer. Supplier or others persons directly concerned. Shenzhen HCT Technology Co.,Ltd . will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.




Type of Modulation: Л/4DQPSK

12.4 Out of Band Test Result

Product:	Mushroom Jumbo		Test Mode:	High Channel
Mode	Keeping Transmitting		Input Voltage	DC3.7V
Temperature	24 deg. C,		Humidity	56% RH
Test Result:	Pass		Detector	РК
The Max. FS in	PK (dBμV/m) 38.7			74(dBµV/m)
Restrict Band	AV(dBµV/m)		Limit	54(dBµV/m)
2483.5MHz				

Test Figure:



Date: 27.MAY.2014 20:52:27

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the. Shenzhen HCT Technology Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen HCT Technology Co.,Ltd . to his customer. Supplier or others persons directly concerned. Shenzhen HCT Technology Co.,Ltd . will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.




Type of Modulation: Л/4DQPSK

12.4 Out of Band Test Result

Product:	Mushroom Jumbo		Test Mode:	Hopping mode
Mode	Hopping On		Input Voltage	DC3.7V
Temperature	24 deg. C,		Humidity	56% RH
Test Result:	Pass		Detector	РК
The Max. FS in	PK (dBµV/m) 36.6			74(dBµV/m)
Restrict Band	AV(dBμV/m)		Limit	54(dBµV/m)
2390MHz				

Test Figure:



Date: 27.MAY.2014 20:45:04

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the. Shenzhen HCT Technology Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen HCT Technology Co.,Ltd . to his customer. Supplier or others persons directly concerned. Shenzhen HCT Technology Co.,Ltd . will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.




Type of Modulation: Л/4DQPSK

12.4 Out of Band Test Result

Product:	Mushroom Jumbo		Test Mode:	Hopping mode
Mode	Hopping On		Input Voltage	DC3.7V
Temperature	24 deg. C,		Humidity	56% RH
Test Result:	Pass		Detector	РК
The Max. FS in	PK (dBµV/m)	38.4		74(dBµV/m)
Restrict Band	AV(dBµV/m)		Limit	54(dBµV/m)
2483.5MHz				

Test Figure:



Date: 27.MAY.2014 20:51:43

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the. Shenzhen HCT Technology Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen HCT Technology Co.,Ltd . to his customer. Supplier or others persons directly concerned. Shenzhen HCT Technology Co.,Ltd . will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.




Type of Modulation: 8DPSK

12.4 Out of Band Test Result

Product:	Mushroom Jumbo		Test Mode:	Low Channel
Mode	Keeping Transmitting		Input Voltage	DC3.7V
Temperature	24 deg. C		Humidity	56% RH
Test Result:	Pass		Detector	РК
The Max. FS in	PK (dBµV/m) 37.5			74(dBµV/m)
Restrict Band	AV(dBµV/m)		Limit	54(dBµV/m)
2390MHz				

Test Figure:



Date: 27.MAY.2014 20:47:24

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the. Shenzhen HCT Technology Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen HCT Technology Co.,Ltd . to his customer. Supplier or others persons directly concerned. Shenzhen HCT Technology Co.,Ltd . will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.




Type of Modulation: 8DPSK

12.4 Out of Band Test Result

Product:	Mushroom Jumbo		Test Mode:	High Channel
Mode	Keeping Transmitting		Input Voltage	DC3.7V
Temperature	24 deg. C,		Humidity	56% RH
Test Result:	Pass		Detector	РК
The Max. FS in	PK (dBμV/m) 38.9			74(dBµV/m)
Restrict Band	AV(dBµV/m)		Limit	54(dBµV/m)
2483.5MHz				

Test Figure:



Date: 27.MAY.2014 20:48:33

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the. Shenzhen HCT Technology Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen HCT Technology Co.,Ltd . to his customer. Supplier or others persons directly concerned. Shenzhen HCT Technology Co.,Ltd . will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.




Type of Modulation: 8DPSK

12.4 Out of Band Test Result

Product:	Mushroom Jumbo		Test Mode:	Hopping mode
Mode	Hopping On		Input Voltage	DC3.7V
Temperature	24 deg. C,		Humidity	56% RH
Test Result:	Pass		Detector	РК
The Max. FS in	PK (dBμV/m) 37.0			74(dBµV/m)
Restrict Band	AV(dBμV/m)		Limit	54(dBµV/m)
2390MHz				

Test Figure:



Date: 27.MAY.2014 20:46:28

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the. Shenzhen HCT Technology Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen HCT Technology Co.,Ltd . to his customer. Supplier or others persons directly concerned. Shenzhen HCT Technology Co.,Ltd . will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.




Type of Modulation: 8DPSK

12.4 Out of Band Test Result

Product:	Mushroom Jumbo		Test Mode:	Hopping mode
Mode	Hopping On		Input Voltage	DC3.7V
Temperature	24 deg. C,		Humidity	56% RH
Test Result:	Pass		Detector	РК
The Max. FS in	PK (dBµV/m)	38.3		74(dBµV/m)
Restrict Band	AV(dBµV/m)		Limit	54(dBµV/m)
2483.5MHz				

Test Figure:



Date: 27.MAY.2014 20:50:14

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the. Shenzhen HCT Technology Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen HCT Technology Co.,Ltd . to his customer. Supplier or others persons directly concerned. Shenzhen HCT Technology Co.,Ltd . will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.



13.0 Antenna Requirement

13.1 Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitter antennas of directional gain greater than 6 dBi are used, the power shall be reduced by the mount in dB that the directional gain of the antenna exceeds 6 dBi.

13.2 Antenna Connected construction

There is a PCB printed antenna, and the maximum Gain of this antenna is 1.13dBi.

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the. Shenzhen HCT Technology Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen HCT Technology Co.,Ltd . to his customer. Supplier or others persons directly concerned. Shenzhen HCT Technology Co.,Ltd . will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen HCT Technology Co.,Ltd . reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.




14.0 FCC ID Label

FCC ID: Z2HMS5312

The label on these products must be permanently affixed to the product and readily visible at the time of purchase and must last the expected lifetime of the equipment not be readily detachable.

Mark Location:




The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the. Shenzhen HCT Technology Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen HCT Technology Co.,Ltd . to his customer. Supplier or others persons directly concerned. Shenzhen HCT Technology Co.,Ltd . will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.



15.0 Photo of testing

15.1 Conducted test View




The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the. Shenzhen HCT Technology Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen HCT Technology Co.,Ltd . to his customer. Supplier or others persons directly concerned. Shenzhen HCT Technology Co.,Ltd . will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.



15.2 Emission Radiated test View



The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the. Shenzhen HCT Technology Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen HCT Technology Co.,Ltd . to his customer. Supplier or others persons directly concerned. Shenzhen HCT Technology Co.,Ltd . will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.



Photos of the Product



The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the. Shenzhen HCT Technology Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen HCT Technology Co.,Ltd . to his customer. Supplier or others persons directly concerned. Shenzhen HCT Technology Co.,Ltd . will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.



Photos of the Product





The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the. Shenzhen HCT Technology Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen HCT Technology Co.,Ltd . to his customer. Supplier or others persons directly concerned. Shenzhen HCT Technology Co.,Ltd . will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.



Photos of the Product






The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the. Shenzhen HCT Technology Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen HCT Technology Co.,Ltd . to his customer. Supplier or others persons directly concerned. Shenzhen HCT Technology Co.,Ltd . will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.



Photos of the Product




The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the. Shenzhen HCT Technology Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen HCT Technology Co.,Ltd . to his customer. Supplier or others persons directly concerned. Shenzhen HCT Technology Co.,Ltd . will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.



Photos of the Product




The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the. Shenzhen HCT Technology Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen HCT Technology Co.,Ltd . to his customer. Supplier or others persons directly concerned. Shenzhen HCT Technology Co.,Ltd . will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.



Photos of the Product




The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the. Shenzhen HCT Technology Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen HCT Technology Co.,Ltd . to his customer. Supplier or others persons directly concerned. Shenzhen HCT Technology Co.,Ltd . will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.



Photos of the Product




The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the. Shenzhen HCT Technology Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen HCT Technology Co.,Ltd . to his customer. Supplier or others persons directly concerned. Shenzhen HCT Technology Co.,Ltd . will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.



Additional Li-ion Battery



End of the report

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the. Shenzhen HCT Technology Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen HCT Technology Co.,Ltd . to his customer. Supplier or others persons directly concerned. Shenzhen HCT Technology Co.,Ltd . will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.