



FCC PART 15.247

TEST REPORT

For

Weccan Industrial Limited

Room209, 2/F, Building W1-A, No.34 Gaoxin South 4th St Hi-tech Industrial Park, Nanshan District, Shenzhen, China

FCC ID: Z3CDRW358F60

| | |
|--|--|
| Report Type: Original Report | Product Type: 2.4 G RC Drone With WIFI Camera(camera unit) |
| Report Number: | <u>RSZ170623802-00B</u> |
| Report Date: | <u>2017-08-04</u> |
| Reviewed By: | <u>Engineer</u>  |
| Prepared By: | Bay Area Compliance Laboratories Corp. (Kunshan) No.248 Chenghu Road, Kunshan, Jiangsu province, China Tel: +86-0512-86175000 Fax: +86-0512-88934268 www.baclcorp.com.cn |

Note: This test report is prepared for the customer shown above and for the equipment described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp.

TABLE OF CONTENTS

| | |
|---|-----------|
| GENERAL INFORMATION..... | 3 |
| PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)..... | 3 |
| OBJECTIVE | 3 |
| RELATED SUBMITTAL(S)/GRANT(S)..... | 3 |
| TEST METHODOLOGY | 3 |
| MEASUREMENT UNCERTAINTY..... | 4 |
| TEST FACILITY..... | 4 |
| SYSTEM TEST CONFIGURATION..... | 5 |
| DESCRIPTION OF TEST CONFIGURATION | 5 |
| EQUIPMENT MODIFICATIONS | 5 |
| EUT EXERCISE SOFTWARE | 5 |
| DUTY CYCLE | 6 |
| EXTERNAL I/O CABLE..... | 7 |
| BLOCK DIAGRAM OF TEST SETUP | 8 |
| SUMMARY OF TEST RESULTS | 9 |
| TEST EQUIPMENT LIST | 10 |
| FCC §15.247 (i) & §1.1307 (b) (1) & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)..... | 11 |
| APPLICABLE STANDARD | 11 |
| RESULT | 11 |
| FCC §15.203 – ANTENNA REQUIREMENT..... | 12 |
| APPLICABLE STANDARD | 12 |
| ANTENNA CONNECTOR CONSTRUCTION | 12 |
| FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS..... | 13 |
| APPLICABLE STANDARD | 13 |
| EUT SETUP | 13 |
| EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP | 14 |
| TEST PROCEDURE | 14 |
| CORRECTED AMPLITUDE & MARGIN CALCULATION | 14 |
| TEST RESULTS SUMMARY | 14 |
| TEST DATA | 15 |
| FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH..... | 21 |
| APPLICABLE STANDARD | 21 |
| TEST PROCEDURE | 21 |
| TEST DATA | 21 |
| FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER..... | 28 |
| APPLICABLE STANDARD | 28 |
| TEST PROCEDURE | 28 |
| TEST DATA | 28 |
| FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE..... | 30 |
| APPLICABLE STANDARD | 30 |
| TEST PROCEDURE | 30 |
| TEST DATA | 30 |
| FCC §15.247(e) - POWER SPECTRAL DENSITY | 34 |
| APPLICABLE STANDARD | 34 |
| TEST PROCEDURE | 34 |
| TEST DATA | 34 |

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The *Weccan Industrial Limited's* product, model number: *DRW358S (FCC ID: Z3CDRW358F60)* or the "EUT" in this report was a *2.4 G RC Drone With WIFI Camera*(camera unit), which was measured approximately: 380 mm (L) x 380 mm (W) x 80 mm (H), rated with input voltage: 3.7V from battery.

Notes: This series products model: SG-F50, SG-F51, SG-F52, SG-F53, SG-F54, SG-F55, SG-F56, SG-F57, SG-F58, SG-F59, SG-F60, SG-F61, SG-F62, SG-F63, SG-F64, SG-F65, SG-F66, SG-F67, SG-68, SG-F69, SG-F70, SG-F71, SG-F72, SG-F73, SG-F74, SG-F75, SG-F76, SG-F77, SG-F78, SG-F79, SG-F80, SG-F81, SG-F82, SG-F83, SG-F84, SG-F85, SG-F86, SG-F87, SG-F88, SG-F89, SG-F90, SG-F91, SG-F92, SG-F93, SG-F94, SG-F95, SG-F96, SG-F97, SG-F98, SG-F99 and DRW358S are identical; they have the identical schematics, they have different model number and color. Model DRW358S was selected for fully testing, the detailed information can be referred to the declaration which was stated and guaranteed by the applicant.

* All measurement and test data in this report was gathered from production sample serial number: 170623802 (Assigned by BACL, Kunshan). The EUT supplied by the applicant was received on 2017-06-23.

Objective

This report is prepared on behalf of *Weccan Industrial Limited* in accordance with Part 2-Subpart J, Part 15-Subparts A and C of the Federal Communication Commissions rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Related Submittal(s)/Grant(s)

The remote control Unit of a system submission with FCC ID: Z3CDRW358F60W.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

All emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Kunshan). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement Uncertainty

| Item | Uncertainty | |
|----------------------------------|-------------|---------|
| RF conducted test with spectrum | ±0.9dB | |
| RF Output Power with Power meter | ±0.5dB | |
| Radiated emission | 30MHz~1GHz | ±5.91dB |
| | Above 1G | ±4.92dB |
| Occupied Bandwidth | ±0.5kHz | |
| Temperature | ±1.0°C | |
| Humidity | ±6% | |

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Kunshan) to collect test data is located on the No.248 Chenghu Road, Kunshan, Jiangsu province, China

Bay Area Compliance Laboratories Corp. (Kunshan) has been accredited to ISO/IEC 17025 by CNAS(Lab code: L9963). And accredited to ISO/IEC 17025 by A2LA(Lab code: 4323.01), the FCC Designation No. CN1185 under the KDB 974614 D01.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 815570. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

Bay Area Compliance Laboratories Corp. (Kunshan) was registered with ISED Canada under ISED Canada Registration Number 3062E.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

For 802.11b, 802.11g and 802.11n-HT20 mode, 11 channels are provided to testing:

| Channel | Frequency (MHz) | Channel | Frequency (MHz) |
|---------|-----------------|---------|-----------------|
| 1 | 2412 | 8 | 2447 |
| 2 | 2417 | 9 | 2452 |
| 3 | 2422 | 10 | 2457 |
| 4 | 2427 | 11 | 2462 |
| 5 | 2432 | / | / |
| 6 | 2437 | / | / |
| 7 | 2442 | / | / |

For 802.11b, 802.11g, 802.11n-HT20 mode, EUT was tested with Channel 1, 6 and 11

Equipment Modifications

No modification was made to the EUT tested.

EUT Exercise Software



BLE & Wi-Fi test in the engineer mode.


802.11b: Data rate: 11 Mbps, Power level: 15

802.11g: Data rate: 54 Mbps, Power level: 10

802.11n-HT20: Data rate: MCS7, Power level: 10

Pre-scan with all the date rates, the above date rate is the worst case for Wi-Fi test.

Duty cycle**802.11b mode****802.11g mode**

802.11n-HT20 Mode


| Band | Duty Cycle(%) | T(us) | 1/T(kHz) | VBW Setting | 10log(1/x) |
|---------------------|---------------|-------|----------|-------------|------------|
| 802.11b | 47 | 982.0 | 1.02 | 3kHz | 3.28 |
| 802.11g | 16 | 300.6 | 3.32 | 10kHz | 7.96 |
| 802.11n-HT20 | 5 | 280.6 | 3.56 | 10kHz | 13.01 |

External I/O Cable

| Cable Description | Length (m) | From Port | To |
|-------------------|------------|-----------|----|
| / | / | / | / |

Block Diagram of Test Setup

For radiated emission



SUMMARY OF TEST RESULTS

| FCC Rules | Description of Test | Result |
|---|--|----------------|
| FCC §15.247 (i) & §1.1307 (b) (1) & §2.1091 | MaximuM Permissible exposure (MPE) | Compliance |
| §15.203 | Antenna Requirement | Compliance |
| §15.207 (a) | AC Line Conducted Emissions | Not Applicable |
| §15.205, §15.209, §15.247(d) | Spurious Emissions | Compliance |
| §15.247 (a)(2) | 6 dB Emission Bandwidth | Compliance |
| §15.247(b)(3) | Maximum Conducted Output Power | Compliance |
| §15.247(d) | 100 kHz Bandwidth of Frequency Band Edge | Compliance |
| §15.247(e) | Power Spectral Density | Compliance |

Note: EUT power by battery. The battery need to pull out while it in charging.

TEST EQUIPMENT LIST

| Manufacturer | Description | Model | Serial Number | Calibration Date | Calibration Due Date |
|--------------------------|--------------------|----------------|---------------|------------------|----------------------|
| Radiation test | | | | | |
| Sonoma Instrumen | Amplifier | 330 | 171377 | 2016-12-12 | 2017-12-12 |
| Rohde & Schwarz | EMI Test Receiver | ESCI | 100195 | 2016-11-25 | 2017-11-25 |
| Sunol Sciences | Broadband Antenna | JB3 | A090314-2 | 2016-01-09 | 2019-01-08 |
| Narda | Pre-amplifier | AFS42-00101800 | 2001270 | 2016-09-08 | 2017-09-08 |
| EMCO | Horn Antenna | 3116 | 00084159 | 2016-10-18 | 2019-10-17 |
| Rohde & Schwarz | Signal Analyzer | FSIQ26 | 100048 | 2016-11-25 | 2017-11-25 |
| ETS | Horn Antenna | 3115 | 9311-4159 | 2016-12-12 | 2019-12-12 |
| R&S | Auto test Software | EMC32 | V 09.10.0 | NCR | NCR |
| BACL | RF cable | KS-LAB-012 | KS-LAB-012 | 2016-12-15 | 2017-12-15 |
| Ducommun technologies | RF Cable | 104PEA | 218124002 | 2017-04-22 | 2018-04-22 |
| RF Conducted test | | | | | |
| BACL | TS 8997 Cable-01 | T-KS-EMC086 | T-KS-EMC086 | 2016-12-09 | 2017-12-08 |
| BACL | RF cable | KS-LAB-012 | KS-LAB-012 | 2016-12-15 | 2017-12-15 |
| WEINSCHEL | 3dB Attenuator | 5326 | N/A | 2017-06-18 | 2018-06-18 |
| Agilent | Power Meter | N1912A | MY5000492 | 2016-11-17 | 2017-11-16 |
| Agilent | Power Sensor | N1921A | MY54210024 | 2016-11-17 | 2017-11-16 |
| Rohde & Schwarz | Signal Analyzer | FSIQ26 | 836131 | 2016-09-21 | 2017-09-21 |

*** Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Kunshan) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC §15.247 (i) & §1.1307 (b) (1) & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Applicable Standard

According to subpart 15.247 (i) and subpart 1.1307 (b)(1), 2.1091 systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

Limits for General Population/Uncontrolled Exposure

| Limits for General Population/Uncontrolled Exposure | | | | |
|---|-------------------------------|-------------------------------|-------------------------------------|--------------------------|
| Frequency Range (MHz) | Electric Field Strength (V/m) | Magnetic Field Strength (A/m) | Power Density (mW/cm ²) | Averaging Time (Minutes) |
| 0.3-1.34 | 614 | 1.63 | *(100) | 30 |
| 1.34-30 | 824/f | 2.19/f | *(180/f ²) | 30 |
| 30-300 | 27.5 | 0.073 | 0.2 | 30 |
| 300-1500 | / | / | f/1500 | 30 |
| 1500-100,000 | / | / | 1.0 | 30 |

f = frequency in MHz

* = Plane-wave equivalent power density

Result

Calculated Formulary:

Predication of MPE limit at a given distance

$$S = \frac{PG}{4\pi R^2}$$

S = power density (in appropriate units, e.g. mW/cm²)

P = power input to the antenna (in appropriate units, e.g., mW).

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain.

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

| Frequency (MHz) | Antenna Gain | | Conducted Power | | Evaluation Distance (cm) | Power Density (mW/cm ²) | MPE Limit (mW/cm ²) |
|-----------------|--------------|-----------|-----------------|--------|--------------------------|-------------------------------------|---------------------------------|
| | (dBi) | (numeric) | (dBm) | (mW) | | | |
| 2412-2462 | 1.5 | 1.41 | 24 | 251.19 | 20 | 0.07 | 1 |

Note: To maintain compliance with the FCC's RF exposure guidelines, place the equipment at least 20cm from nearby persons.

Result: Compliance

FCC §15.203 – ANTENNA REQUIREMENT

Applicable Standard

According to FCC § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Antenna Connector Construction

The EUT has one internal antenna arrangement which was permanently attached and the antenna gain is 1.5 dBi, fulfill the requirement of this section. Please refer to the EUT photos.

Result: Compliance.


FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS

Applicable Standard


FCC §15.247 (d); §15.209; §15.205;

EUT Setup

Below 1 GHz:



Above 1GHz:



The radiated emission tests were performed in the 3 meters test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209 and FCC 15.247 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

| Frequency Range | RBW | Video B/W | IF B/W | Detector |
|-------------------|---------|-------------------------|---------|----------|
| 30 MHz – 1000 MHz | 100 kHz | 300 kHz | 120 kHz | QP |
| Above 1 GHz | 1MHz | 3 MHz | / | PK |
| | 1MHz | 10 Hz ^{Note 1} | / | Ave. |
| | 1MHz | >1/T ^{Note 2} | / | Ave. |

Note 1: when duty cycle is no less than 98%

Note 2: when duty cycle is less than 98%

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

All final data was recorded in Quasi-peak detection mode for frequency range of 30 MHz to 1GHz and peak and Average detection modes for frequencies above 1GHz.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “Margin” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Title 47, Part 15, Subpart C, section 15.205, 15.209 and 15.247.

Refer to CISPR16-4-2:2011 and CISPR 16-4-1:2009, the measured level compliance with the limit if

$$L_m + U_{(Lm)} \leq L_{lim} + U_{cispr}$$

In BACL, $U_{(Lm)}$ is less than U_{cispr} , if L_m is less than L_{lim} , it implies that the EUT complies with the limit.

Test Data

Environmental Conditions

| | |
|---------------------------|---------|
| Temperature: | 21 °C |
| Relative Humidity: | 50 % |
| ATM Pressure: | 101 kPa |

The testing was performed by Layne Li on 2017-07-01.

Test Mode: Transmitting

30 MHz -25 GHz:

802.11b Mode:

| Frequency (MHz) | Receiver | | Turn table Degree | Rx Antenna | | Corrected Factor (dB) | Corrected Amplitude (dB μ V/m) | FCC Part 15.247/205/209 | |
|-----------------------------|-------------------------|--------------------------|-------------------------|---------------|----------------|-----------------------------|--|----------------------------|----------------|
| | Reading (dB μ V) | Detector (PK/QP/Ave.) | | Height (m) | Polar (H/V) | | | Limit (dB μ V/m) | Margin (dB) |
| Low Channel(2412MHz) | | | | | | | | | |
| 748.72 | 29.17 | QP | 150 | 2.0 | H | 8.58 | 37.75 | 46 | 8.25 |
| 2412.00 | 115.75 | PK | 295 | 1.5 | H | -6.19 | 109.56 | / | / |
| 2412.00 | 107.43 | Ave. | 295 | 1.5 | H | -6.19 | 101.24 | / | / |
| 2412.00 | 111.58 | PK | 258 | 1.7 | V | -6.19 | 105.39 | / | / |
| 2412.00 | 103.08 | Ave. | 258 | 1.7 | V | -6.19 | 96.89 | / | / |
| 2386.95 | 69.29 | PK | 81 | 1.7 | H | -6.19 | 63.10 | 74 | 10.90 |
| 2386.95 | 54.03 | Ave. | 81 | 1.7 | H | -6.19 | 47.84 | 54 | 6.16 |
| 2389.51 | 68.53 | PK | 60 | 1.9 | H | -6.19 | 62.34 | 74 | 11.66 |
| 2389.51 | 53.99 | Ave. | 60 | 1.9 | H | -6.19 | 47.80 | 54 | 6.20 |
| 2496.56 | 66.85 | PK | 123 | 1.7 | H | -5.97 | 60.88 | 74 | 13.12 |
| 2496.56 | 53.39 | Ave. | 123 | 1.7 | H | -5.97 | 47.42 | 54 | 6.58 |
| 4824.00 | 49.9 | PK | 42 | 1.9 | H | 1.6 | 51.50 | 74 | 22.50 |
| 4824.00 | 35.18 | Ave. | 42 | 1.9 | H | 1.6 | 36.78 | 54 | 17.22 |

| Frequency (MHz) | Receiver | | Turn table Degree | Rx Antenna | | Corrected Factor (dB) | Corrected Amplitude (dB μ V/m) | FCC Part 15.247/205/209 | |
|--------------------------------|-------------------------|--------------------------|-------------------------|---------------|----------------|-----------------------------|--|----------------------------|----------------|
| | Reading (dB μ V) | Detector (PK/QP/Ave.) | | Height (m) | Polar (H/V) | | | Limit (dB μ V/m) | Margin (dB) |
| Middle Channel(2437MHz) | | | | | | | | | |
| 748.72 | 28.47 | QP | 112 | 1.9 | H | 8.58 | 37.05 | 46 | 8.95 |
| 2437.00 | 116.35 | PK | 42 | 2.4 | H | -6.19 | 110.16 | / | / |
| 2437.00 | 109.15 | Ave. | 42 | 2.4 | H | -6.19 | 102.96 | / | / |
| 2437.00 | 110.49 | PK | 342 | 1.3 | V | -6.19 | 104.30 | / | / |
| 2437.00 | 102.62 | Ave. | 342 | 1.3 | V | -6.19 | 96.43 | / | / |
| 2345.11 | 68.32 | PK | 284 | 1.4 | H | -6.42 | 61.90 | 74 | 12.10 |
| 2345.11 | 54.16 | Ave. | 284 | 1.4 | H | -6.42 | 47.74 | 54 | 6.26 |
| 2337.41 | 67.65 | PK | 355 | 1.0 | H | -6.42 | 61.23 | 74 | 12.77 |
| 2337.41 | 54.25 | Ave. | 355 | 1.0 | H | -6.42 | 47.83 | 54 | 6.17 |
| 2496.36 | 67.06 | PK | 14 | 2.0 | H | -5.97 | 61.09 | 74 | 12.91 |
| 2496.36 | 53.5 | Ave. | 14 | 2.0 | H | -5.97 | 47.53 | 54 | 6.47 |
| 4874.00 | 49.04 | PK | 273 | 1.8 | H | 1.83 | 50.87 | 74 | 23.13 |
| 4874.00 | 34.5 | Ave. | 273 | 1.8 | H | 1.83 | 36.33 | 54 | 17.67 |
| High Channel(2462 MHz) | | | | | | | | | |
| 748.72 | 30.59 | QP | 158 | 1.8 | H | 8.58 | 39.17 | 46 | 6.83 |
| 2462.00 | 116.21 | PK | 147 | 1.5 | H | -5.97 | 110.24 | / | / |
| 2462.00 | 108.69 | Ave. | 147 | 1.5 | H | -5.97 | 102.72 | / | / |
| 2462.00 | 111.87 | PK | 312 | 2.5 | V | -5.97 | 105.90 | / | / |
| 2462.00 | 103.24 | Ave. | 312 | 2.5 | V | -5.97 | 97.27 | / | / |
| 2366.91 | 67.71 | PK | 149 | 1.2 | H | -6.19 | 61.52 | 74 | 12.48 |
| 2366.91 | 54.05 | Ave. | 149 | 1.2 | H | -6.19 | 47.86 | 54 | 6.14 |
| 2493.48 | 67.58 | PK | 301 | 2.5 | H | -5.97 | 61.61 | 74 | 12.39 |
| 2493.48 | 53.43 | Ave. | 301 | 2.5 | H | -5.97 | 47.46 | 54 | 6.54 |
| 2499.47 | 66.86 | PK | 47 | 2.2 | H | -5.97 | 60.89 | 74 | 13.11 |
| 2499.47 | 53.7 | Ave. | 47 | 2.2 | H | -5.97 | 47.73 | 54 | 6.27 |
| 4924.00 | 48.78 | PK | 40 | 1.0 | H | 1.83 | 50.61 | 74 | 23.39 |
| 4924.00 | 34.45 | Ave. | 40 | 1.0 | H | 1.83 | 36.28 | 54 | 17.72 |

802.11g Mode:

| Frequency (MHz) | Receiver | | Turntable Degree | Rx Antenna | | Corrected Factor (dB) | Corrected Amplitude (dB μ V/m) | FCC Part 15.247/205/209 | |
|---------------------------------|-------------------------|--------------------------|---------------------|---------------|----------------|-----------------------------|--|----------------------------|----------------|
| | Reading (dB μ V) | Detector (PK/QP/Ave.) | | Height (m) | Polar (H/V) | | | Limit (dB μ V/m) | Margin (dB) |
| Low Channel (2412 MHz) | | | | | | | | | |
| 748.72 | 28.86 | QP | 124 | 1.9 | H | 8.58 | 37.44 | 46 | 8.56 |
| 2412.00 | 112.56 | PK | 336 | 2.2 | H | -6.19 | 106.37 | / | / |
| 2412.00 | 101.36 | Ave. | 336 | 2.2 | H | -6.19 | 95.17 | / | / |
| 2412.00 | 109.98 | PK | 202 | 1.9 | V | -6.19 | 103.79 | / | / |
| 2412.00 | 98.74 | Ave. | 202 | 1.9 | V | -6.19 | 92.55 | / | / |
| 2389.03 | 73 | PK | 102 | 1.6 | H | -6.19 | 66.81 | 74 | 7.19 |
| 2389.03 | 54.34 | Ave. | 102 | 1.6 | H | -6.19 | 48.15 | 54 | 5.85 |
| 2384.19 | 71.56 | PK | 216 | 1.5 | H | -6.19 | 65.37 | 74 | 8.63 |
| 2384.19 | 54.23 | Ave. | 216 | 1.5 | H | -6.19 | 48.04 | 54 | 5.96 |
| 2489.87 | 68.07 | PK | 156 | 1.3 | H | -5.97 | 62.10 | 74 | 11.90 |
| 2489.87 | 53.42 | Ave. | 156 | 1.3 | H | -5.97 | 47.45 | 54 | 6.55 |
| 4824.00 | 49.36 | PK | 45 | 1.1 | H | 1.6 | 50.96 | 74 | 23.04 |
| 4824.00 | 33.71 | Ave. | 45 | 1.1 | H | 1.6 | 35.31 | 54 | 18.69 |
| Middle Channel (2437MHz) | | | | | | | | | |
| 748.72 | 27.8 | QP | 184 | 1.5 | H | 8.58 | 36.38 | 46 | 9.62 |
| 2437.00 | 112.26 | PK | 204 | 1.4 | H | -6.19 | 106.07 | / | / |
| 2437.00 | 101.30 | Ave. | 204 | 1.4 | H | -6.19 | 95.11 | / | / |
| 2437.00 | 109.25 | PK | 221 | 1.0 | V | -6.19 | 103.06 | / | / |
| 2437.00 | 98.87 | Ave. | 221 | 1.0 | V | -6.19 | 92.68 | / | / |
| 2387.15 | 69.25 | PK | 324 | 1.8 | H | -6.19 | 63.06 | 74 | 10.94 |
| 2387.15 | 54.08 | Ave. | 324 | 1.8 | H | -6.19 | 47.89 | 54 | 6.11 |
| 2389.10 | 68.67 | PK | 323 | 1.8 | H | -6.19 | 62.48 | 74 | 11.52 |
| 2389.10 | 54.07 | Ave. | 323 | 1.8 | H | -6.19 | 47.88 | 54 | 6.12 |
| 2490.57 | 67.21 | PK | 24 | 1.4 | H | -5.97 | 61.24 | 74 | 12.76 |
| 2490.57 | 53.41 | Ave. | 24 | 1.4 | H | -5.97 | 47.44 | 54 | 6.56 |
| 4874.00 | 49.05 | PK | 148 | 1.9 | H | 1.83 | 50.88 | 74 | 23.12 |
| 4874.00 | 34.21 | Ave. | 148 | 1.9 | H | 1.83 | 36.04 | 54 | 17.96 |

| Frequency (MHz) | Receiver | | Turntable Degree | Rx Antenna | | Corrected Factor (dB) | Corrected Amplitude (dB μ V/m) | FCC Part 15.247/205/209 | |
|--------------------------------|-------------------------|--------------------------|---------------------|---------------|----------------|-----------------------------|--|----------------------------|----------------|
| | Reading (dB μ V) | Detector (PK/QP/Ave.) | | Height (m) | Polar (H/V) | | | Limit (dB μ V/m) | Margin (dB) |
| High Channel (2462 MHz) | | | | | | | | | |
| 748.72 | 28.26 | QP | 224 | 1.5 | H | 8.58 | 36.84 | 46 | 9.16 |
| 2462.00 | 112.6 | PK | 315 | 1.7 | H | -5.97 | 106.63 | / | / |
| 2462.00 | 101.28 | Ave. | 315 | 1.7 | H | -5.97 | 95.31 | / | / |
| 2462.00 | 110.89 | PK | 227 | 1.5 | V | -5.97 | 104.92 | / | / |
| 2462.00 | 99.18 | Ave. | 227 | 1.5 | V | -5.97 | 93.21 | / | / |
| 2389.03 | 73 | PK | 271 | 1.3 | H | -6.19 | 66.81 | 74 | 7.19 |
| 2389.03 | 54.34 | Ave. | 271 | 1.3 | H | -6.19 | 48.15 | 54 | 5.85 |
| 2483.50 | 71.25 | PK | 311 | 2.4 | H | -5.97 | 65.28 | 74 | 8.72 |
| 2483.50 | 53.64 | Ave. | 311 | 2.4 | H | -5.97 | 47.67 | 54 | 6.33 |
| 2483.56 | 68.07 | PK | 222 | 1.5 | H | -5.97 | 62.10 | 74 | 11.90 |
| 2483.56 | 53.66 | Ave. | 222 | 1.5 | H | -5.97 | 47.69 | 54 | 6.31 |
| 4924.00 | 48.23 | PK | 275 | 1.7 | H | 1.83 | 50.06 | 74 | 23.94 |
| 4924.00 | 34.17 | Ave. | 275 | 1.7 | H | 1.83 | 36.00 | 54 | 18.00 |

802.11n-HT20 Mode:

| Frequency (MHz) | Receiver | | Turntable Degree | Rx Antenna | | Corrected Factor (dB) | Corrected Amplitude (dB μ V/m) | FCC Part 15.247/205/209 | |
|---------------------------------|-------------------------|--------------------------|---------------------|---------------|----------------|-----------------------------|--|----------------------------|----------------|
| | Reading (dB μ V) | Detector (PK/QP/Ave.) | | Height (m) | Polar (H/V) | | | Limit (dB μ V/m) | Margin (dB) |
| Low Channel (2412 MHz) | | | | | | | | | |
| 748.72 | 29.87 | QP | 167 | 1.8 | H | 8.58 | 38.45 | 46 | 7.55 |
| 2412.00 | 110.81 | PK | 124 | 1.7 | H | -6.19 | 104.62 | / | / |
| 2412.00 | 99 | Ave. | 124 | 1.7 | H | -6.19 | 92.81 | / | / |
| 2412.00 | 106.4 | PK | 86 | 1.1 | V | -6.19 | 100.21 | / | / |
| 2412.00 | 93.56 | Ave. | 86 | 1.1 | V | -6.19 | 87.37 | / | / |
| 2389.51 | 68.13 | PK | 325 | 1.9 | H | -6.19 | 61.94 | 74 | 12.06 |
| 2389.51 | 54.05 | Ave. | 325 | 1.9 | H | -6.19 | 47.86 | 54 | 6.14 |
| 2495.53 | 66.85 | PK | 290 | 2.4 | H | -5.97 | 60.88 | 74 | 13.12 |
| 2495.53 | 53.39 | Ave. | 290 | 2.4 | H | -5.97 | 47.42 | 54 | 6.58 |
| 2497.86 | 66.95 | PK | 318 | 1.3 | H | -5.97 | 60.98 | 74 | 13.02 |
| 2497.86 | 53.4 | Ave. | 318 | 1.3 | H | -5.97 | 47.43 | 54 | 6.57 |
| 4824.00 | 47.53 | PK | 36 | 2.0 | H | 1.6 | 49.13 | 74 | 24.87 |
| 4824.00 | 33.34 | Ave. | 36 | 2.0 | H | 1.6 | 34.94 | 54 | 19.06 |
| Middle Channel (2437MHz) | | | | | | | | | |
| 748.72 | 28.44 | QP | 117 | 1.2 | H | 8.58 | 37.02 | 46 | 8.98 |
| 2437.00 | 110.56 | PK | 138 | 1.9 | H | -6.19 | 104.37 | / | / |
| 2437.00 | 97.98 | Ave. | 138 | 1.9 | H | -6.19 | 91.79 | / | / |
| 2437.00 | 106.58 | PK | 288 | 1.4 | V | -6.19 | 100.39 | / | / |
| 2437.00 | 94.07 | Ave. | 288 | 1.4 | V | -6.19 | 87.88 | / | / |
| 2333.72 | 68.16 | PK | 108 | 1.1 | H | -6.42 | 61.74 | 74 | 12.26 |
| 2333.72 | 54.22 | Ave. | 108 | 1.1 | H | -6.42 | 47.80 | 54 | 6.20 |
| 2383.58 | 67.87 | PK | 45 | 1.8 | H | -6.19 | 61.68 | 74 | 12.32 |
| 2383.58 | 54.05 | Ave. | 45 | 1.8 | H | -6.19 | 47.86 | 54 | 6.14 |
| 2490.57 | 67.17 | PK | 40 | 2.1 | H | -5.97 | 61.20 | 74 | 12.80 |
| 2490.57 | 53.39 | Ave. | 40 | 2.1 | H | -5.97 | 47.42 | 54 | 6.58 |
| 4874.00 | 48.21 | PK | 235 | 1.5 | H | 1.83 | 50.04 | 74 | 23.96 |
| 4874.00 | 33.83 | Ave. | 235 | 1.5 | H | 1.83 | 35.66 | 54 | 18.34 |

| Frequency (MHz) | Receiver | | Turntable Degree | Rx Antenna | | Corrected Factor (dB) | Corrected Amplitude (dB μ V/m) | FCC Part 15.247/205/209 | |
|--------------------------------|-------------------------|--------------------------|---------------------|---------------|----------------|-----------------------------|--|----------------------------|----------------|
| | Reading (dB μ V) | Detector (PK/QP/Ave.) | | Height (m) | Polar (H/V) | | | Limit (dB μ V/m) | Margin (dB) |
| High Channel (2462 MHz) | | | | | | | | | |
| 748.72 | 26.9 | QP | 285 | 1.6 | H | 8.58 | 35.48 | 46 | 10.52 |
| 2462.00 | 109.13 | PK | 42 | 2.2 | H | -5.97 | 103.16 | / | / |
| 2462.00 | 96.72 | Ave. | 42 | 2.2 | H | -5.97 | 90.75 | / | / |
| 2462.00 | 105.44 | PK | 29 | 1.8 | V | -5.97 | 99.47 | / | / |
| 2462.00 | 92.53 | Ave. | 29 | 1.8 | V | -5.97 | 86.56 | / | / |
| 2387.56 | 68.05 | PK | 212 | 1.5 | H | -6.19 | 61.86 | 74 | 12.14 |
| 2387.56 | 54.03 | Ave. | 212 | 1.5 | H | -6.19 | 47.84 | 54 | 6.16 |
| 2484.19 | 72.92 | PK | 249 | 2.0 | H | -5.97 | 66.95 | 74 | 7.05 |
| 2484.19 | 53.46 | Ave. | 249 | 2.0 | H | -5.97 | 47.49 | 54 | 6.51 |
| 2485.05 | 70.5 | PK | 220 | 1.1 | H | -5.97 | 64.53 | 74 | 9.47 |
| 2485.05 | 53.39 | Ave. | 220 | 1.1 | H | -5.97 | 47.42 | 54 | 6.58 |
| 4924.00 | 48.43 | PK | 2 | 2.4 | H | 1.83 | 50.26 | 74 | 23.74 |
| 4924.00 | 34.02 | Ave. | 2 | 2.4 | H | 1.83 | 35.85 | 54 | 18.15 |

Note:

1. Corrected Factor=Antenna factor (RX) +cable loss – amplifier factor

2. Corrected Amplitude = Corrected Factor + Receiver Reading

3. Margin = Limit- Corrected Amplitude

The other spurious emission which is 20dB to the limit was not recorded.


FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH

Applicable Standard

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 6 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.



Test Data

Environmental Conditions

| | |
|--------------------|-----------|
| Temperature: | 24 °C |
| Relative Humidity: | 55 % |
| ATM Pressure: | 101.0 kPa |



The testing was performed by Ada Yu on 2017-07-08.



Test Result: Compliance.



EUT operation mode: Transmitting



Please refer to following table and plots.


| Channel | Frequency (MHz) | 6 dB Emission Bandwidth (MHz) | Limit (kHz) |
|-------------------|--------------------|-------------------------------------|----------------|
| 802.11b mode | | | |
| Low | 2412 | 9.7 | ≥500 |
| Middle | 2437 | 9.54 | ≥500 |
| High | 2462 | 9.78 | ≥500 |
| 802.11g | | | |
| Low | 2412 | 16.51 | ≥500 |
| Middle | 2437 | 16.59 | ≥500 |
| High | 2462 | 16.59 | ≥500 |
| 802.11n-HT20 mode | | | |
| Low | 2412 | 17.72 | ≥500 |
| Middle | 2437 | 17.72 | ≥500 |
| High | 2462 | 17.72 | ≥500 |

802.11b Low Channel**802.11b Middle Channel**

802.11b High Channel**802.11g Low Channel**

802.11g Middle Channel**802.11g High Channel**

802.11n-HT20 Low Channel**802.11n-HT20 Middle Channel**

802.11n-HT20 High Channel


FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER

Applicable Standard

According to FCC §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

Test Procedure

1. Place the EUT on a bench and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.
3. Add a correction factor to the display.



Test Data

Environmental Conditions

| | |
|--------------------|-----------|
| Temperature: | 24 °C |
| Relative Humidity: | 55 % |
| ATM Pressure: | 101.0 kPa |

The testing was performed by Ada Yu on 2017-07-08.

Test Result: Compliance.

EUT operation mode: Transmitting

Please refer to following table and plots.

Wi-Fi mode

| Channel | Frequency (MHz) | Max Conducted Peak Output Power (dBm) | Limit (dBm) |
|--------------|-----------------|---------------------------------------|-------------|
| 802.11b | | | |
| Low | 2412 | 23.49 | 30 |
| Middle | 2437 | 22.81 | 30 |
| High | 2462 | 22.91 | 30 |
| 802.11g | | | |
| Low | 2412 | 18.53 | 30 |
| Middle | 2437 | 18.32 | 30 |
| High | 2462 | 18.13 | 30 |
| 802.11n HT20 | | | |
| Low | 2412 | 17.01 | 30 |
| Middle | 2437 | 17.62 | 30 |
| High | 2462 | 17.27 | 30 |


FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE

Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.



Test Data

Environmental Conditions

| | |
|---------------------------|-----------|
| Temperature: | 24 °C |
| Relative Humidity: | 55 % |
| ATM Pressure: | 101.0 kPa |


The testing was performed by Ada Yu on 2017-07-08.

Test Result: Compliance.


EUT operation mode: Transmitting

Please refer to the following plots


802.11b: Band Edge, Left Side




802.11b: Band Edge, Right Side





802.11g: Band Edge, Left Side



802.11g: Band Edge, Right Side



802.11n-HT20: Band Edge, Left Side**802.11n-HT20: Band Edge, Right Side**


FCC §15.247(e) - POWER SPECTRAL DENSITY

Applicable Standard

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

Test Procedure

1. Use this procedure when the maximum peak conducted output power in the fundamental emission is used to demonstrate compliance.
2. Set the RBW to: $3\text{kHz} \leq \text{RBW} \leq 100\text{ kHz}$.
3. Set the VBW $\geq 3 \times \text{RBW}$.
4. Set the span to 1.5 times the DTS bandwidth.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level within the RBW.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.



Test Data

Environmental Conditions

| | |
|--------------------|-----------|
| Temperature: | 24 °C |
| Relative Humidity: | 55 % |
| ATM Pressure: | 101.0 kPa |



The testing was performed by Ada Yu on 2017-07-08.



Test Result: Compliance.



EUT operation mode: Transmitting



Please refer to following table and plots.


| Channel | Frequency (MHz) | PSD (dBm/3kHz) | Limit (dBm/3kHz) |
|-------------------|-----------------|----------------|------------------|
| 802.11b mode | | | |
| Low | 2412 | -9.32 | ≤8 |
| Middle | 2437 | -9.13 | ≤8 |
| High | 2462 | -8.64 | ≤8 |
| 802.11g mode | | | |
| Low | 2412 | -10.24 | ≤8 |
| Middle | 2437 | -9.91 | ≤8 |
| High | 2462 | -10.83 | ≤8 |
| 802.11n-HT20 mode | | | |
| Low | 2412 | -10.32 | ≤8 |
| Middle | 2437 | -10.94 | ≤8 |
| High | 2462 | -11.28 | ≤8 |

Power Spectral Density, 802.11b Low Channel**Power Spectral Density, 802.11b Middle Channel**

Power Spectral Density, 802.11b High Channel**Power Spectral Density, 802.11g Low Channel**

Power Spectral Density, 802.11g Middle Channel**Power Spectral Density, 802.11g High Channel**

Power Spectral Density, 802.11n-HT20 Low Channel**Power Spectral Density, 802.11n-HT20 Middle Channel**

Power Spectral Density, 802.11n-HT20 High Channel******* END OF REPORT *******